

SELF-SUPERVISED STATE-CONTROL THROUGH INTRINSIC MUTUAL INFORMATION REWARDS

Anonymous authors

Paper under double-blind review

ABSTRACT

Learning to discover useful skills without a manually-designed reward function would have many applications, yet is still a challenge for reinforcement learning. In this paper, we propose Mutual Information-based State-Control (MISC), a new self-supervised Reinforcement Learning approach for learning to control states of interest without any external reward function. We formulate the intrinsic objective as rewarding the skills that maximize the mutual information between the context states and the states of interest. For example, in robotic manipulation tasks, the context states are the robot states and the states of interest are the states of an object. We evaluate our approach for different simulated robotic manipulation tasks from OpenAI Gym. We show that our method is able to learn to manipulate the object, such as pushing and picking up, purely based on the intrinsic mutual information rewards. Furthermore, the pre-trained policy and mutual information discriminator can be used to accelerate learning to achieve high task rewards. Our results show that the mutual information between the context states and the states of interest can be an effective ingredient for overcoming challenges in robotic manipulation tasks with sparse rewards. A video showing experimental results is available at <https://youtu.be/cLRrkd3Y7vU>.

1 INTRODUCTION

Reinforcement Learning (RL) (Sutton & Barto, 1998) combined with Deep Learning (DL) (Goodfellow et al., 2016) has led to great successes in various reward-driven tasks, such as playing video games (Mnih et al., 2015), learning continuous control (Ng et al., 2006; Peters & Schaal, 2008; Levine et al., 2016; Chebotar et al., 2017), navigating in complex environments (Mirowski et al., 2017; Zhu et al., 2017), and manipulating objects (Andrychowicz et al., 2017; 2018).

Despite these successes, RL agents that learn only from reward signals differ in the manner that humans learn. In the case of learning to manipulate objects, a human agent not only attempts to accomplish the task but also learns to master the controllable aspects of the environment (Lake et al., 2017). Notably, a human agent can quickly discover the correlation between its own action and the state change of an object, even without supervision, to later use the acquired skill to manipulate the object into the desired state.

The ability to fully autonomously learn to control the states of interest has many benefits. First, it would make learning possible in the absence of hand-engineered reward functions or manually-specified agent goals. It is known that designing a reward function that ensures the agent to learn the desired behaviors is challenging (Hadfield-Menell et al., 2017). Secondly, to learn to “master” the environment potentially helps the agent to learn to achieve goals in sparse reward settings. Thirdly, the policy of controlling states of interest can be quickly adapted to unknown tasks. It is currently an open challenge to design RL agents that discover useful skills to control the states of the environment, without rewards (Warde-Farley et al., 2019).

A *skill* is a latent-conditioned policy that changes the state of the environment in a consistent way (Eysenbach et al., 2019). One way to discover skills is to simultaneously train a discriminator to discern the skill-options of the agent (Szepesvari et al., 2014) based on the states of the trajectory (Eysenbach et al., 2019). In this way, the agent should be able to learn a diverse set of skills. Another way is to learn an environment model to encourage the agent to explore the states, which are relatively unpredictable (Houthoofd et al., 2016; Pathak et al., 2017; Ha & Schmidhuber,




Figure 1: Fetch robot arm environments: FetchPush, FetchPickAndPlace, FetchSlide.

2018). These methods are more focused on efficiently exploring novel states instead of controlling states of interest.

We propose a new self-supervised reinforcement learning method, Mutual Information-based State-Control (MISC), which is an approach that learns skills to control states of interest without any reward signal. *States of interest* are the states of the environment that we are interested in. *Context states* are the states of the environment excluding the states of interest. The idea of our method is to encourage the agent to find skills that maximize the mutual information between the context states and the states of interest. We first divide the observation states into two sets, the context states and the states of interest. In the case of robotic manipulation tasks, see Figure 1, the context states are the robot states; the states of interest are the states of an object. During the learning process of the agent, a discriminator learns to evaluate the mutual information between the context states and the states of interest. The agent receives high intrinsic rewards from the discriminator when there is high mutual information. Our hypothesis is that if the agent learns to control the object, then the mutual information of the agent states and the object states should be relatively high. Interestingly, this automated RL scheme bears similarities to the self-supervised learning of feature representations in computer vision tasks, where a neural network is trained to predict a part of the image given another part of the same image (Doersch et al., 2015). During the process, the neural network captures the mutual information among different parts of the image. Similarly, in our work, we want to capture the mutual information among different sets of states.

This paper contains the following five contributions. First, we introduce a new self-supervised RL method, Mutual Information-based State-Control, for learning to control states of interest. Secondly, we evaluate the developed framework in the robotic simulations of OpenAI Gym and demonstrate that MISC enables the agent to discover manipulation skills, such as reaching, pushing, picking up, and sliding the object without rewards. Thirdly, we show that the pre-trained policy can be quickly adapted to the specific tasks with external sparse reward signal. Fourthly, the pre-trained mutual information discriminator also improves the learning process of the agent, either as intrinsic rewards or as priorities for experience replay, in addition to the sparse rewards. Finally, we show that the learned mutual information discriminator can be transferred among different tasks and still improves the performance.

2 PROBLEM FORMULATION

In the RL setup, an agent interacts with an environment. The environment is fully observable and includes a set of states \mathcal{S} , a set of actions \mathcal{A} , a distribution of initial states $p(s_0)$, transition probabilities $p(s_{t+1} | s_t, a_t)$, a reward function $r: \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, and a discount factor $\gamma \in [0, 1]$. These components formulate a Markov decision process represented as a tuple, $(\mathcal{S}, \mathcal{A}, p, r, \gamma)$. A policy π maps a state to an action, $\pi: \mathcal{S} \rightarrow \mathcal{A}$. The goal of the agent is to maximize the accumulated reward, i.e., the return, $R_t = \sum_{i=t}^{\infty} \gamma^{i-t} r_i$, over all episodes, which is equivalent to maximizing the expected return, $\mathbb{E}_{s_0} [R_0 | s_0]$.

We consider robotic manipulation tasks, like the robotic simulations provided by OpenAI Gym (Todorov et al., 2012; Plappert et al., 2018), where a robot arm attempts to manipulate an object to a goal position via pushing, picking & placing, or sliding, as shown in Figure 1. The states of the environment s consist of positions, orientations, linear and angular velocities of all robot joints and of an object. We divide the states s into two sets, the robot states s^r and the object states s^o . For manipulation tasks, we are interested in the states of the object. Therefore, we define the states of interest s^i as the object states, $s^i = s^o$; the context states s^c as the robot states, $s^c = s^r$. For




Figure 2: **MISC Algorithm:** We update the discriminator to better estimate the mutual information (MI), and update the agent to control states of interest to have higher MI with the context states.

simplicity, we represent the states of interest using only the object positions, $s^i = (x^o, y^o, z^o)$, and the context states using only the gripper positions, $s^c = (x^g, y^g, z^g)$.

In this paper, we focus on learning to control states of interest purely using the agent’s observations and actions, without any reward function. Motivated by the idea that an agent capable of controlling states of interest s^i to have high mutual information with its context state s^c has “mastered” the environment, we formulate the problem of learning without external supervision as one of learning a policy $\pi_\theta(a_t | s_t)$ with parameters θ to maximize intrinsic mutual information rewards, $r = I(S^i; S^c)$. Here, we use upper letters, such as S^i , to denote random variables and the corresponding lower case letter, such as s^i , to represent the values of random variables.

3 METHOD

In this section, we formally describe our method, including the mutual information reward function and the self-supervised RL framework.

3.1 LEARNING A MUTUAL INFORMATION REWARD FUNCTION OF STATES

Our method simultaneously learns a policy and an intrinsic reward function by maximizing the mutual information between the states of interest and the context states. Mathematically, the mutual information between the state of interest random variable S^i and the context state random variable S^c is represented as:

$$\begin{aligned} I(S^i; S^c) &= H(S^i) - H(S^i | S^c) \\ &= D_{KL}(\mathbb{P}_{S^i S^c} \parallel \mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}) \end{aligned} \quad (1)$$

where $\mathbb{P}_{S^i S^c}$ is the joint probability distribution; $\mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}$ is the product of the marginal distributions \mathbb{P}_{S^i} and \mathbb{P}_{S^c} ; D_{KL} denotes the Kullback-Leibler (KL) divergence. The first line in Equation (1) tells us that the agent should maximize the entropy of states of interest, $H(S^i)$, and concurrently, minimize the conditional entropy of states of interest given the context states, $H(S^i | S^c)$. When the conditional entropy, $H(S^i | S^c)$, is small, it becomes easy to predict the states of interest based on the context states. In this case, for example in robotic manipulation tasks, we can say that the robot can control the object because it is easy to predict the location of the object S^i , given the robot states S^c . The second line in Equation (1) gives us the mutual information in the KL divergence form.

Mutual information is notoriously difficult to compute in real-world settings (Hjelm et al., 2019). Motivated by Belghazi et al. (2018), we use a lower bound to approximate the mutual information quantity, $I(S^i; S^c)$. First, we rewrite the KL formulation of mutual information objective, Equation (1), using the Donsker-Varadhan representation (Donsker & Varadhan, 1975):

$$\begin{aligned} I(S^i; S^c) &= D_{KL}(\mathbb{P}_{S^i S^c} \parallel \mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}) \\ &= \sup_{\mathcal{T}: \Omega \rightarrow \mathbb{R}} \mathbb{E}_{\mathbb{P}_{S^i S^c}}[\mathcal{T}] - \log(\mathbb{E}_{\mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}}[e^{\mathcal{T}}]) \end{aligned} \quad (2)$$

where the input space Ω is a compact domain of \mathbb{R}^d , i.e., $\Omega \subset \mathbb{R}^d$; the supremum is taken over all functions \mathcal{T} such that the two expectations are finite. Secondly, we lower bound the mutual information in Donsker-Varadhan representation with the compression lemma in the PAC-Bayes literature (Banerjee, 2006), mathematically,

$$\begin{aligned} I(S^i; S^c) &= \sup_{\mathcal{T}: \Omega \rightarrow \mathbb{R}} \mathbb{E}_{\mathbb{P}_{S^i S^c}}[\mathcal{T}] - \log(\mathbb{E}_{\mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}}[e^{\mathcal{T}}]) \\ &\geq \sup_{\phi \in \Phi} \mathbb{E}_{\mathbb{P}_{S^i S^c}}[\mathcal{T}_\phi] - \log(\mathbb{E}_{\mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}}[e^{\mathcal{T}_\phi}]) \\ &= I_\Phi(S^i, S^c). \end{aligned} \quad (3)$$

The expectations in Equation (3) are estimated using empirical samples from $\mathbb{P}_{S^i S^c}$ and $\mathbb{P}_{S^i} \otimes \mathbb{P}_{S^c}$ or by shuffling the samples from the joint distribution along the batch axis (Belghazi et al., 2018). The mutual information reward function, $r = I_\Phi(S^i, S^c)$, can be trained by gradient ascent. The statistics model \mathcal{T}_ϕ is parameterized by a deep neural network with parameters $\phi \in \Phi$, which aims to estimate the mutual information with arbitrary accuracy.

3.2 MUTUAL INFORMATION-BASED STATE-CONTROL

We want to train an agent to “master” the states of interest in a self-supervised reinforcement learning fashion. The agent aims to maximize the mutual information between the states of interest and the context states. At the beginning of each episode, the agent takes actions a_t following a partially random policy, such as ϵ -greedy, to explore the environment and collects trajectories into a buffer for later replay. The trajectory contains a series of states, $\{s_1, s_2, \dots, s_T\}$, where T is the time horizon of the trajectory. Each state s_t consists of the states of interest s_t^i and the context states s_t^c , where in robot manipulation tasks, we use the object position as s_t^i , and the gripper position as s_t^c .

For training the mutual information discriminator network, we first randomly sample trajectories of states $s_{1:T} = \{s_1, s_2, \dots, s_T\}$ from the replay buffer. Here, we use $s_{t:t'}$ to indicate a subsequence of a trajectory, for instance, $s_{1:t}$ refers to $\{s_1, s_2, \dots, s_t\}$. Then, we evaluate the mutual information lower bound, $I_\phi(s_{1:T}^i, s_{1:T}^c)$, mathematically,

$$I_\phi(s_{1:T}^i, s_{1:T}^c) = \frac{1}{T} \sum_{t=1}^T \mathcal{T}_\phi(s_t^i, s_t^c) - \log \left(\frac{1}{T} \sum_{t=1}^T e^{\mathcal{T}_\phi(s_t^i, \bar{s}_t^c)} \right), \quad (4)$$

where the states \bar{s}_t^c are sampled by shuffling the states s_t^c along the temporal axis t within each trajectory. After evaluating the lower bound, $I_\phi(s_{1:T}^i, s_{1:T}^c)$, we use back-propagation to optimize the parameter (ϕ) to maximize the mutual information lower bound. Here, we calculate the mutual information using the samples from the same trajectory. If the context states or the states of interest do not change within the trajectory, then the mutual information of these states is zero. Therefore, if the agent does not alter the object states during the episode, then the mutual information between the agent states and the object states remains zero.

We define the transition mutual information reward as the mutual information estimation of a trajectory fraction, $s_{t:t+1}$, mathematically,

$$r_t = I_\phi(s_{t:t+1}^i, s_{t:t+1}^c) = \text{clip} \left(\frac{1}{2} \sum_{t=t}^{t+1} \mathcal{T}_\phi(s_t^i, s_t^c) - \log \left(\frac{1}{2} \sum_{t=t}^{t+1} e^{\mathcal{T}_\phi(s_t^i, \bar{s}_t^c)} \right), 0, I_{tran}^{max} \right), \quad (5)$$

where I_{tran}^{max} is the predefined maximal transition mutual information value. The clip function limits the transition mutual information value in an interval of $[0, I_{tran}^{max}]$. The lower threshold 0 forces the mutual information estimation to be non-negative. In practice, to mitigate the influence of some particular large transition mutual information, we find it useful to clip the intrinsic reward with the threshold value I_{tran}^{max} . This clipping trick makes the training stable. The threshold value can be considered as a hyper-parameter.

We implement MISC with both deep deterministic policy gradient (DDPG) (Lillicrap et al., 2016) and soft actor-critic (SAC) (Haarnoja et al., 2018) to learn a policy $\pi_\theta(a | s)$ that aims to control the states of interest. In comparison to DDPG and SAC, the DDPG method improves the policy in a more “greedy” fashion, while the SAC approach is more conservative, in the sense that SAC incorporates an entropy regularizer $\mathcal{H}(a | s)$ that maximizing the policy’s entropy over actions.




Figure 3: **Manipulation skills:** Without any reward, MISC discovers skills for reaching, pushing, sliding, and picking up an object. The video of the learned skills is shown at <https://youtu.be/cLRrkd3Y7vU>. It is time-consuming to manually design reward functions that enforce these behaviors.

We found empirically that DDPG works better when the agent starts learning quickly, while SAC explores the environment more thoroughly in general.

Overall, the agent is rewarded for controlling states of interest to have higher mutual information with its context states, which is considered to gain a degree of mastery of the environment. We summarize the complete training algorithm in Algorithm 1 and in Figure 2.

4 EXPERIMENTS

To evaluate MISC, we use the robotic manipulation environments provided by OpenAI Gym, see Figure 1 (Brockman et al., 2016; Plappert et al., 2018). First, we analyze the skills learned purely with the intrinsic reward. We show that the agent is able to learn skills, such as reaching, pushing, picking up, and sliding an object, see Figure 3. We also compare our method with “Diversity is All You Need” (DIAYN) method (Eysenbach et al., 2019). Secondly, we show that the pre-trained models, including the policy and the MI discriminator, can be used for improving performance in conjunction with the rewards. There are several ways to improve performance, such as via policy initialization, with the MI intrinsic rewards, and using the MI value for prioritized experience replay. Interestingly, we also show that the pre-trained MI discriminator can be transferred among different tasks and still improves performance. We compare our method with other methods, including DDPG (Lillicrap et al., 2016), SAC (Haarnoja et al., 2018), DIAYN (Eysenbach et al., 2019), PER (Schaul et al., 2016), and VIME (Houthoofd et al., 2016). Thirdly, we show some insights about how MISC rewards are distributed across a trajectory. Our code is available at <https://github.com/misc-project/misc>.

4.1 ANALYSIS OF LEARNED SKILLS

Question 1. *What skill does MISC learn?*

We tested MISC in multiple robotic manipulation tasks, including push, pick & place, and slide, see Figure 1. In the push and slide tasks, the gripper is fixed to be closed. In the pick & place task, the agent has the control of the gripper to be open or closed. Unlike in push and pick &




Figure 4: **Mean success rate with standard deviation:** The percentage values after colon (:) represent the best mean success rate during training. The shaded area describes the standard deviation.

place environments, the surface of the table in the slide task has very low friction so that the object can slide on these surface. In all the environments, the object is randomly placed on the table at the beginning of each episode. During training, the agent only receives the intrinsic MISC reward, see Section 3.2. In all three environments, the behavior of reaching objects emerges from the self-supervised training, for example, as shown in Figure 3 (1st row). Furthermore, in the push and pick & place environments, the agent learns to push the object around on the table, see Figure 3 (2nd row). In the slide environment, the agent learns to slide the object into different directions, see Figure 3 (3rd row). Perhaps surprisingly, in the pick & place environment, the agent learns to pick up the object from the table without any reward, which means taking full control of the object states, see Figure 3 (4th row).

We implemented the MISC with both DDPG and SAC and ran the experiments with 5 different random seeds. To compare DDPG+MISC and SAC+MISC, we ran 20 trials using the learned policy in the pick & place environment with each seed. We observed that, in all 5 random seed settings, SAC+MISC learns the picking-up skill, while DDPG+MISC learns to pick up an object in only 1 out of 5 random seed settings. Mostly, the agent learns to push, flip, or grip the object. These observations show that the entropy bonus, $\mathcal{H}(A | S)$, of SAC can incorporate with MISC and helps the agent to better explore the skill space.

Question 2. *How does MISC compare to DIAYN (Eysenbach et al., 2019)?*

The most related prior work on unsupervised skill discovery, DIAYN, introduces an information-theoretic objective $\mathcal{F}_{\text{DIAYN}}$, which learns diverse discriminable skills indexed by the latent variable Z , mathematically,

$$\begin{aligned}
 \mathcal{F}_{\text{DIAYN}} &= I(S; Z) + \mathcal{H}(A | S) - I(A; Z | S) \\
 &= I(S; Z) + \mathcal{H}(A | S, Z) \\
 &\geq \mathbb{E}_{z \sim p(z), s \sim \pi(z)} [\log q_{\phi}(z | s) - \log p(z)] + \mathcal{H}(A | S, Z).
 \end{aligned}
 \tag{6}$$

The first term, $I(S; Z)$, in the objective, $\mathcal{F}_{\text{DIAYN}}$, is implemented via a skill discriminator, which is proven to be a variational lower bound of the original objective (Barber & Agakov, 2003; Eysenbach et al., 2019). The skill discriminator assigns high rewards to the agent, if it can predict the skill-options, Z , given the states, S . The second term, $\mathcal{H}(A | S, Z)$, is implemented through SAC (Haarnoja et al., 2018) conditioned on skill-options (Szepesvari et al., 2014). In the DIAYN paper, the authors mainly evaluated the algorithm on navigation and locomotion environments (Todorov et al., 2012; Brockman et al., 2016). We can adapt DIAYN to manipulation tasks by replacing the full states, S , with states of interest, S^i , i.e., the object states, as $I(S^i; Z)$. In comparison, our

method MISC proposes to maximize the mutual information between the context states and the states of interest, i.e., $I(S^c; S^i)$, so that the agent learns to control the states of interest in a self-supervised fashion. These two methods can be combined as follows:

$$\mathcal{F}_{\text{MISC+DIAYN}} = I(S^c; S^i) + I(S^i; Z) + \mathcal{H}(A | S, Z). \quad (7)$$

We compare MISC, DIAYN and MISC+DIAYN in the pick & place environment. For implementing MISC+DIAYN, we first pre-train the agent with only MISC, and then fine-tune the policy with DIAYN. After pre-training, MISC learns manipulation behaviors such as, reaching, pushing, sliding, and picking up, as shown in Figure 3. Compared to MISC, DIAYN rarely learns to pick up the object. We found that DIAYN does not fully control the object. The DIAYN-trained agent mostly pushes or flicks the object with the gripper. However, the combined model, MISC+DIAYN, learns to pick up the object and moves it to different locations, which depends on the conditioned skill-option. These observations are shown in the video at <https://youtu.be/cLRrkd3Y7vU?t=47>. MISC helps the agent to learn the DIAYN objective. The agent first learns to control the object with MISC, and then discovers diverse manipulation skills with DIAYN.

4.2 ACCELERATING LEARNING WITH MISC

Question 3. *How can we use the learned skills or the trained MI discriminator to accelerate learning new tasks?*

We investigate three ways of using the pre-trained policy and the MI discriminator to accelerate learning in addition to the task reward.

The first method is using the MISC pre-trained policy as parameter initialization and fine-tune the agent with rewards. We denote this variant as “MISC-f”, where “-f” stands for fine-tuning. The second variant is to use the MI intrinsic reward to help the agent explore high mutual information states. We name this method as “MISC-r”, where “-r” stands for rewarding. The third approach is to use the mutual information quantity from MISC to prioritize trajectories for replay. We name this method as “MISC-p”, where “-p” stands for prioritization.

We combined these three variants with DDPG and SAC and tested them in the robotic simulations provided in OpenAI Gym. The environments, including push, pick & place, and slide, have a set of predefined goals, which are represented as the red dots, as shown in Figure 1. The task for the RL agent is to manipulate the object to the goal positions. We ran all the methods in each environment with 5 different random seeds and report the mean success rate and the standard deviation, as shown in Figure 4. The percentage values alongside the plots are the best mean success rates during training. Each experiment is carried out with 16 CPU-cores.

From Figure 4, we can see that all these three methods, including MISC-f, MISC-p, and MISC-r, accelerate learning in the presence of task rewards. Among these variants, the MISC-r has the best overall improvements. In the push and pick & place tasks, MISC enables the agent to learn in a short period of training time, as shown in Figure 4. In the slide tasks, MISC-r also improves the performances by a decent margin.

We also compare our methods with more advanced RL methods. To be more specific, we compare MISC-f against parameter initialization using DIAYN (Eysenbach et al., 2019); MISC-p against Prioritized Experience Replay (PER), which uses TD-errors for prioritization (Schaul et al., 2016); MISC-r versus Variational Information Maximizing Exploration (VIME) (Houthoofd et al., 2016). The experimental results are shown in Figure 5. From Figure 5 (1st row), we can see that MISC-f enables the agent to learn, while DIAYN does not. The reason is that DIAYN is more focused on learning a diverse set of skills instead of learning to control the states. In the manipulation tasks, controlling states is more important, therefore MISC outperforms DIAYN. In the 2nd row of Figure 5, MISC-r performs better than VIME. This result indicates that the mutual information between states is a crucial quantity for accelerating learning. The mutual information intrinsic rewards boost performance significantly compared to VIME. This observation is consistent with the experimental results of MISC-p and PER, as shown in Figure 5 (3rd row), where the mutual information-based prioritization framework performs better than the TD-error based approach, PER. On all tasks, MISC enables the agent to learn the benchmark task more quickly.




Figure 5: **Performance comparison:** We compare the MISC variants, including MISC-f, MISC-r, and MISC-p, with DIAYN, VIME, and PER, respectively.

4.3 TRANSFER LEARNING WITH MISC

Question 4. *Can the learned MI discriminator be transferred to different tasks?*

It would be beneficial if the pre-trained MI discriminator can be transferred to new tasks and still improves the performance (Pan et al., 2010; Bengio, 2012). To verify this idea, we directly applied the pre-trained MI discriminator from the pick & place environment to the push and slide environments, respectively. We denote this transferred method as “MISC-t”, where “-t” stands for transfer. The MISC reward function trained in its corresponding environments is denoted as “MISC-r”. We compare the performance of DDPG baseline, MISC-r, and MISC-t. The results are shown in Figure 6. Perhaps surprisingly, the transferred MISC still improves the performance significantly. Furthermore, as expected, MISC-r performs better than MISC-t in both tasks. We can see that the MI discriminator can be trained in a task-agnostic fashion and later utilized in unseen tasks.




Figure 6: **Transferred MISC**

4.4 INSIGHTS

Question 5. *How does MISC distribute rewards across a trajectory?*

To understand why MISC works and how MISC distributes rewards, we visualize the learned MISC rewards, defined in Section 3.2, in Figure 7 and in a video at <https://youtu.be/cLRrkd3Y7vU?t=92>. From Figure 7, we can observe that the mutual information reward peaks between the fourth and fifth frame, where the robot quickly picks up the object from the table.

Around the peak reward value, the middle range reward values are corresponding to the relatively slow movement of the object and the gripper, see the third, ninth, and tenth frame. When there is no contact between the gripper and the object, see the first two frames in Figure 7, or the gripper holds the object still, see the sixth to eighth frames, the intrinsic reward remains nearly zero. From this example, we see that MISC distributes positive intrinsic rewards, when the object states, s^i , has correlated changes with the robot state, s^c .




Figure 7: MISC rewards over a trajectory

5 RELATED WORK

Unsupervised skill discovery is a challenging topic in RL. Variational Intrinsic Control (VIC) (Gregor et al., 2016) proposes an information-theoretic objective (Barber & Agakov, 2003) to jointly maximize the entropy of a set of options while keeping the options distinguishable based on the final states of the trajectory. Recently, Eysenbach et al. (2019) introduce DIAYN, which maximizes the mutual information between a fixed number of skill-options and the entire states of the trajectory. Eysenbach et al. (2019) show that DIAYN can scale to more complex tasks compared to VIC and provides a handful of low-level primitive skills as the basis for hierarchical reinforcement learning.

Another trunk of work on skill discovery is based on goal-conditioned policies. Warde-Farley et al. (2019) propose, DISCERN, a method to learn a mutual information objective between the states and goals, which enables the agent to learn to achieve goals in environments with continuous high-dimensional observation spaces. Based on DISCERN, Pong et al. (2019) introduce Skew-fit, which adapts a maximum entropy strategy to sample goals from the replay buffer (Zhao & Tresp, 2019; Zhao et al., 2019) in order to make the agent learn more efficiently in the absence of rewards. More recently, Hartikainen et al. (2019) propose to automatically learn dynamical distances: a measure of the expected number of time steps to reach a given goal state, which can be used as rewards for learning to achieve new goals.

Similar to the skill discovery methods, intrinsic rewards are also often used to help the agent learn more efficiently to solve tasks. For example, Jung et al. (2011) and Mohamed & Rezende (2015) use empowerment, which is the mutual information between states and actions, for intrinsically motivated agents. VIME (Houthoofd et al., 2016) and ICM (Pathak et al., 2017) use curiosity as intrinsic rewards to encourage the agents to explore the environment more thoroughly.

Based on a similar motivation as previous works, we introduce MISC, a method that uses the mutual information between the states of interest and the context states (Doersch et al., 2015) as an intrinsic reward function. MISC enables the agent to discover manipulation skills without supervision. Our method is complementary to the previous skill discovery works, such as DIAYN, and can be combined with them. The idea of MISC is to encourage the agent to learn to control states of interest, as one step forward towards mastery of the environment. Inspired by previous works (Schaul et al., 2016; Houthoofd et al., 2016; Zhao & Tresp, 2018; Eysenbach et al., 2019), we additionally demonstrate three variants, including MISC-based fine-tuning, rewarding, and prioritizing mechanisms, to accelerate learning in the case when the task rewards are available.

6 CONCLUSION

This paper introduces Mutual Information-based State-Control (MISC), a self-supervised reinforcement learning framework for attaining robotic manipulation skills. MISC utilizes a mutual information-based theoretic objective to encourage the agent to control states of interest without any reward function. In robotic manipulation tasks, MISC enables the agent to self-learn manipulation behaviors, like reaching, pushing, picking up, and sliding an object. Additionally, the unsupervised pre-trained policy and the mutual information discriminator accelerate learning in the presence of task rewards. We evaluate three MISC-based variants in different tasks and demonstrate a substantial improvement in learning efficiency compared to state-of-the-art methods.

REFERENCES

- Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, pp. 5048–5058, 2017.
- Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Jozefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, et al. Learning dexterous in-hand manipulation. *arXiv preprint arXiv:1808.00177*, 2018.
- Arindam Banerjee. On bayesian bounds. In *Proceedings of the 23rd international conference on Machine learning*, pp. 81–88. ACM, 2006.
- David Barber and Felix V Agakov. The im algorithm: a variational approach to information maximization. In *Advances in neural information processing systems*, pp. None, 2003.
- Mohamed Ishmael Belghazi, Aristide Baratin, Sai Rajeswar, Sherjil Ozair, Yoshua Bengio, Aaron Courville, and R Devon Hjelm. Mine: mutual information neural estimation. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 531–540. PMLR, 2018.
- Yoshua Bengio. Deep learning of representations for unsupervised and transfer learning. In *Proceedings of ICML workshop on unsupervised and transfer learning*, pp. 17–36, 2012.
- Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.
- Yevgen Chebotar, Mrinal Kalakrishnan, Ali Yahya, Adrian Li, Stefan Schaal, and Sergey Levine. Path integral guided policy search. In *Robotics and Automation (ICRA), 2017 IEEE International Conference on*, pp. 3381–3388. IEEE, 2017.
- Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1422–1430, 2015.
- Monroe D Donsker and SR Srinivasa Varadhan. Asymptotic evaluation of certain markov process expectations for large time, i. *Communications on Pure and Applied Mathematics*, 28(1):1–47, 1975.
- Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2019. URL <https://openreview.net/forum?id=SJx63jRqFm>.
- Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT press Cambridge, 2016.
- Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.
- David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.
- Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1861–1870. PMLR, 2018.
- Dylan Hadfield-Menell, Smitha Milli, Pieter Abbeel, Stuart J Russell, and Anca Dragan. Inverse reward design. In *Advances in neural information processing systems*, pp. 6765–6774, 2017.
- Kristian Hartikainen, Xinyang Geng, Tuomas Haarnoja, and Sergey Levine. Dynamical distance learning for unsupervised and semi-supervised skill discovery. *arXiv preprint arXiv:1907.08225*, 2019.
- R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *International Conference on Learning Representations*, 2019. URL <https://openreview.net/forum?id=Bk1r3j0cKX>.

- Rein Houthoofd, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Vime: Variational information maximizing exploration. In *Advances in Neural Information Processing Systems*, pp. 1109–1117, 2016.
- Tobias Jung, Daniel Polani, and Peter Stone. Empowerment for continuous agent–environment systems. *Adaptive Behavior*, 19(1):16–39, 2011.
- Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behavioral and brain sciences*, 40, 2017.
- Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.
- Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.
- Piotr Mirowski, Razvan Pascanu, Fabio Viola, Hubert Soyer, Andrew J Ballard, Andrea Banino, Misha Denil, Ross Goroshin, Laurent Sifre, Koray Kavukcuoglu, et al. Learning to navigate in complex environments. In *International Conference on Learning Representations*, 2017.
- Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Belle-mare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.
- Shakir Mohamed and Danilo Jimenez Rezende. Variational information maximisation for intrinsically motivated reinforcement learning. In *Advances in neural information processing systems*, pp. 2125–2133, 2015.
- Andrew Y Ng, Adam Coates, Mark Diel, Varun Ganapathi, Jamie Schulte, Ben Tse, Eric Berger, and Eric Liang. Autonomous inverted helicopter flight via reinforcement learning. In *Experimental Robotics IX*, pp. 363–372. Springer, 2006.
- Sinno Jialin Pan, Qiang Yang, et al. A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, 22(10):1345–1359, 2010.
- Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning (ICML)*, volume 2017, 2017.
- Jan Peters and Stefan Schaal. Reinforcement learning of motor skills with policy gradients. *Neural networks*, 21(4):682–697, 2008.
- Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*, 2018.
- Vitchyr H Pong, Murtaza Dalal, Steven Lin, Ashvin Nair, Shikhar Bahl, and Sergey Levine. Skew-fit: State-covering self-supervised reinforcement learning. *arXiv preprint arXiv:1903.03698*, 2019.
- Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *International Conference on Learning Representations*, 2016.
- Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*, volume 1. MIT press Cambridge, 1998.
- Csaba Szepesvari, Richard S Sutton, Joseph Modayil, Shalabh Bhatnagar, et al. Universal option models. In *Advances in Neural Information Processing Systems*, pp. 990–998, 2014.
- Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *Intelligent Robots and Systems (IROS), 2012 IEEE/RSJ International Conference on*, pp. 5026–5033. IEEE, 2012.

- David Warde-Farley, Tom Van de Wiele, Tejas Kulkarni, Catalin Ionescu, Steven Hansen, and Volodymyr Mnih. Unsupervised control through non-parametric discriminative rewards. In *International Conference on Learning Representations*, 2019. URL <https://openreview.net/forum?id=r1eVMnA9K7>.
- Rui Zhao and Volker Tresp. Energy-based hindsight experience prioritization. In *Proceedings of the 2nd Conference on Robot Learning*, pp. 113–122, 2018.
- Rui Zhao and Volker Tresp. Curiosity-driven experience prioritization via density estimation. *arXiv preprint arXiv:1902.08039*, 2019.
- Rui Zhao, Xudong Sun, and Volker Tresp. Maximum entropy-regularized multi-goal reinforcement learning. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 7553–7562. PMLR, 2019.
- Yuke Zhu, Roozbeh Mottaghi, Eric Kolve, Joseph J Lim, Abhinav Gupta, Li Fei-Fei, and Ali Farhadi. Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *2017 IEEE international conference on robotics and automation (ICRA)*, pp. 3357–3364. IEEE, 2017.