

REINFORCEMENT LEARNING WITH STRUCTURED HIERARCHICAL GRAMMAR REPRESENTATIONS OF ACTIONS

Anonymous authors

Paper under double-blind review

ABSTRACT

From a young age humans learn to use grammatical principles to hierarchically combine words into sentences. Action grammars is the parallel idea; that there is an underlying set of rules (a “grammar”) that govern how we hierarchically combine actions to form new, more complex actions. We introduce the Action Grammar Reinforcement Learning (AG-RL) framework which leverages the concept of action grammars to consistently improve the sample efficiency of Reinforcement Learning agents. AG-RL works by using a grammar inference algorithm to infer the “action grammar” of an agent midway through training, leading to a higher-level action representation. The agent’s action space is then augmented with macro-actions identified by the grammar. We apply this framework to Double Deep Q-Learning (AG-DDQN) and a discrete action version of Soft Actor-Critic (AG-SAC) and find that it improves performance in 8 out of 8 tested Atari games (median +31%, max +668%) and 19 out of 20 tested Atari games (median +96%, maximum +3,756%) respectively without substantive hyperparameter tuning. We also show that AG-SAC beats the model-free state-of-the-art for sample efficiency in 17 out of the 20 tested Atari games (median +62%, maximum +13,140%), again without substantive hyperparameter tuning.

1 INTRODUCTION

Reinforcement Learning (RL) has famously made great progress in recent years, successfully being applied to settings such as board games Silver et al. (2017), video games Mnih et al. (2015) and robot tasks OpenAI et al. (2018). However, widespread adoption of RL in real-world domains has remained slow primarily because of its poor sample efficiency which Wu et al. (2017) see as a “dominant concern in RL”.

Hierarchical Reinforcement Learning (HRL) attempts to improve the sample efficiency of RL agents by forcing their policies to be hierarchical rather than single level. Identifying the right hierarchical policy structure is however “not a trivial task” (Osa et al., 2019) and so far progress in HRL has been slow and incomplete - Vezhnevets et al. (2016) argued that: “no truly scalable and successful [hierarchical] architectures exist” and even today’s state-of-the-art RL agents are rarely hierarchical.

Humans, however, heavily rely on hierarchical grammatical principles to combine words into larger structures like phrases or sentences (Ding et al., 2012). For example, to construct a valid sentence we generally combine a noun phrase with a verb phrase (Yule, 2015). Action grammars are the parallel idea that there is an underlying set of rules for how we hierarchically combine actions over time to produce new actions. There is growing biological evidence for this link between language and action as explained in Pastra & Aloimonos (2012). Given this, we explore the idea that we can use techniques from computational linguistics to infer a grammar of action in a similar way to how we can infer a grammar of language. Furthermore, hierarchical approaches to RL can lead to higher interpretability for a human observer: higher-level representations of an agent’s behaviour, can be better understood by humans, as opposed to when only low-level actions are visible (Beyret et al., 2019). We argue that basing the abstractions of an agent’s actions, and the definitions of hierarchies, on the concept of action grammars, can further increase interpretability, as per the above described biological link, making it more familiar for interacting humans.

Action Grammar Reinforcement Learning (AG-RL) is a framework for incorporating the concept of action grammars into RL agents. It works by pausing training after a fixed number of steps and using the observed actions of the agent to infer an action grammar, obtaining a higher-level action representation for the agent’s behaviour so far. Effectively, we compose primitive actions (i.e. words) into temporal abstractions (i.e. sentences). The extracted action grammar then gets appended to the agent’s action set in the form of macro-actions. The agent continues playing in the environment but with a new action set that now includes macro-actions. We show that AG-RL is able to consistently and significantly improve sample efficiency across a wide range of Atari settings.

2 RELATED WORK

We are not aware of other attempts to incorporate the concept of action grammars into RL but others have created agents that use macro-actions. We review two of the most notable and relevant below before commenting on the link with symbolic and connectionist RL research.

Vezhnevets et al. (2016) define a macro-action as a sequence of actions where the action sequence (or distribution over them) is decided at the time the macro-action is initiated. They provide the Strategic Attentive Writer (STRAW) algorithm which is a hierarchical RL agent that uses macro actions. STRAW is a deep recurrent neural network with two modules. The first module takes in an observation of the environment and produces an “action-plan” $A \in R^{|A| \times T}$ where A is the discrete action set and T is a pre-defined number of timesteps greater than one. Each column in the action-plan gives the probability of the agent choosing each action at that timestep. As $T > 1$, creating an action-plan involves making decisions that span multiple timesteps. The second module produces a commitment-plan $c \in R^{1 \times T}$ which is used to determine the probabilities of terminating the macro-action and re-calculating the action-plan at a particular timestep. Here, instead of allowing the agent to choose amongst all possible macro-actions, AG-RL only allows the agent to pick macro-actions identified by the grammar algorithm.

Sharma et al. (2017) provide another interesting agent that uses macro-actions called Fine Grained Action Repetition (FiGAR). FiGAR agents maintain two policies: one policy which chooses a primitive action (i.e. an action that only lasts for one timestep) as normal and another policy that chooses how many times the chosen primitive action will be repeated. AG-RL differs to FiGAR by allowing the agent to pick macro-actions that are not necessarily the repetition of single primitive actions and instead could be complicated combinations of primitive actions.

Unlike recent advances in unifying symbolic and connectionist methods, we do not aim to discover relationships between objects (Garnelo et al., 2016; Garnelo & Shanahan, 2019; Zambaldi et al., 2018). Instead our proposed AG-RL framework achieves interpretability by extracting hierarchical subroutines associated with sub-goal achievements.

3 METHODOLOGY

Action Grammar Reinforcement Learning works by having the agent repeatedly iterate through two steps (as laid out in Figure 1):

- (A) **Gather Experience:** the base off-policy RL agent interacts with the environment and stores its experiences
- (B) **Identify Action Grammar:** the experiences are used to identify the agent’s action grammar which is then appended to the agent’s action set in the form of macro-actions

During the first **Gather Experience** step of the game the base RL agent plays normally in the environment for some set number of episodes. The only difference is that during this time we occasionally run an episode of the game with all random exploration turned off and store these experiences separately. We do this because we will later use these experiences to identify the action grammar and so we do not want them to be influenced by noise. See left part of Figure 1.

After some set number of episodes we pause the agent’s interaction with the environment and enter the first **Identify Action Grammar** stage, see middle part of Figure 1. This firstly involves collecting the actions used in the best performing of the no-exploration episodes mentioned above. We




Figure 1: The high-level steps involved in the AG-RL algorithm. In the first Gather Experience step the base agent interacts as normal with the environment for N_1 episodes. Then we feed the experiences of the agent to a grammar calculator which outputs macro-actions that get appended to the action set. The agent starts interacting with the environment again with this updated action set. This process repeats as many times as required, as set through hyperparameters.

then feed these actions into a grammar calculator which identifies the action grammar. A simple choice for the grammar calculator is Sequitur (Nevill-Manning & Witten, 1997). Sequitur receives a sequence of actions as input and then iteratively creates new symbols to replace any repeating sub-sequences of actions. These newly created symbols then represent the macro-actions of the action grammar. To minimise the influence of noise on grammar generation, however, we need to regularise the process. A naive regulariser is k -Sequitur (Stout et al., 2018) which is a version of Sequitur that only creates a new symbol if a sub-sequence repeats at least k times (instead of at least two times), where higher k corresponds to stronger regularisation. Here we use a more principled approach and regularise on the basis of an information theoretic criterion: we generate a new symbol if doing so reduces the total amount of information needed to encode the sequence.

After we have identified the action grammar we enter our second **Gather Experience** step. This firstly involves appending the macro-actions in the action grammar to the agent’s action set. To do this without destroying what our q-network and/or policy has already learned we use transfer learning. For every new macro-action we add a new node to the final layer of the network, leaving all other nodes and weights unchanged. We also initialise the weights of each new node to the weights of their first primitive action (as it is this action that is most likely to have a similar action value to the macro-action). e.g. if the primitive actions are $\{a, b\}$ and we are adding macro-action abb then we initialise the weights of the new macro-action to those of a .

Then our agent begins interacting with the environment as normal but with an action set that now includes macro-actions and four additional changes:

i) In order to maximise information efficiency, when storing experiences from this stage onwards we use a new technique we call Hindsight Action Replay (HAR). It is related to Hindsight Experience Replay which creates new experiences by reimagining the goals the agent was trying to achieve. Instead of reimagining the goals, HAR creates new experiences by reimagining the *actions*. In particular it reimagines them in two ways:

1. If we play a macro-action then we also store the experiences as if we had played the sequence of primitive actions individually
2. If we play a sequence of primitive actions that matches an existing macro-action then we also store the experiences as if we had played the macro-action

See Appendix A for an example of how HAR is able to more than double the number of collected experiences in some cases.

ii) To make sure that the longer macro-actions receive enough attention while learning, we sample experiences from an action balanced replay buffer. This acts as a normal replay buffer except it returns samples of experiences containing equal amounts of each action.

iii) To reduce the variance involved in using long macro-actions we develop a new technique called Abandon Ship. During every timestep of conducting a macro-action we calculate how much worse it is for the agent to continue executing its macro-action compared to abandoning the macro-action and picking the highest value primitive action instead. Formally we calculate this value as $d = 1 - \frac{\exp(q_m)}{\exp(q_{highest})}$ where q_m is the action value of the primitive action we are conducting as part of the macro-action and $q_{highest}$ is the action value of the primitive action with the highest action value. We also store the moving average, $m(d)$, and moving standard deviation, $std(d)$, of d . Then each timestep we compare d to threshold $t = m(d) + std(d)z$ where z is the abandon ship hyperparameter that determines how often we will abandon macro-actions. If $d > t$ then we abandon our macro-action and return control back to the policy, otherwise we continue executing the macro-action.

iv) When our agent is picking random exploration moves we bias its choices towards macro-actions. For example, when a DQN agent picks a random move (which it does epsilon proportion of the time) we set the probability that it will pick a macro-action, rather than a primitive action, to the higher probability given by the hyperparameter ‘‘Macro Action Exploration Bonus’’. In these cases, we do not use Abandon Ship and instead let the macro-actions fully roll out.

The second Gather Experience step then continues until it is time to do another Identify Action Grammar step or until the agent has been trained for long enough and the game ends. Algorithm 1 provides the full AG-RL algorithm.

Algorithm 1 AG-RL

```

1: Initialise environment env, base RL algorithm R, replay buffer D and action set A
2: for each iteration do
3:    $F \leftarrow \text{GATHER\_EXPERIENCE}(A)$ 
4:    $A \leftarrow \text{IDENTIFY\_ACTION\_GRAMMAR}(F)$ 
5:
6: procedure GATHER_EXPERIENCE(A)
7:   transfer_learning(A) ▷ If action set changed do transfer learning
8:    $F \leftarrow \emptyset$  ▷ Initialise F to store no-exploration episode experiences
9:   for each episode do
10:    if no exploration time then turn off exploration ▷ Periodically turn off exploration
11:     $E \leftarrow \emptyset$  ▷ Initialise E to store an episode’s experiences
12:    while not done do
13:       $ma_t = \text{R.pick\_action}(s_t)$  ▷ Pick next primitive action / macro-action
14:      for  $a_t$  in  $ma_t$  do ▷ Iterate through each primitive action in the macro-action
15:        if abandon_ship( $s_t, a_t$ ) then break ▷ Abandon macro-action if required
16:         $s_{t+1}, r_{t+1}, d_{t+1} = \text{env.step}(a_t)$  ▷ Play action in environment
17:         $E \leftarrow E \cup \{(s_t, a_t, r_{t+1}, s_{t+1}, d_{t+1})\}$  ▷ Store the episode’s experiences
18:        R.learn(D) ▷ Learning iteration for base RL algorithm
19:         $D \leftarrow D \cup \text{HAR}(E)$  ▷ Use HAR when updating replay buffer
20:        if no exploration time then  $F \leftarrow F \cup E$  ▷ Store no-exploration experiences
21:    return F
22:
23: procedure IDENTIFY_ACTION_GRAMMAR(F)
24:    $F \leftarrow \text{extract\_best\_episodes}(F)$  ▷ Keep only the best performing no-exploration episodes
25:   action_grammar  $\leftarrow \text{grammar\_algorithm}(F)$  ▷ Infer action grammar using experiences
26:    $A \leftarrow A \cup \text{action\_grammar}$  ▷ Update the action set with identified macro-actions
27:   return A

```

4 SIMPLE EXAMPLE

We now highlight the core aspects of how AG-RL works using a simple example of the game Towers of Hanoi. The game starts with a set of disks placed on a rod in decreasing size order. The objective of the game is to move the entire stack to another rod while obeying the following rules: i) Only one disk can be moved at a time; ii) Each move consists of taking the upper disk from one of the stacks and placing it on top of another stack or on an empty rod; and iii) No larger disk may be




Figure 2: Example of a solution to the Towers of Hanoi game. Letters *a* to *f* represent the 6 different possible moves. After 7 moves the agent has solved the game and receives +100 reward.

placed on top of a smaller disk. The agent only receives a reward when the game is solved, meaning rewards are sparse and that it is difficult for an RL agent to learn the solution. Figure 2 runs through an example of how the game can be solved with the letters ‘*a*’ to ‘*f*’ being used to represent the 6 possible moves in the game.

In this game, AG-RL proceeds by having the base agent (which can be any off-policy RL agent) play the game as normal. After some period of time we pause the agent and collect some of the actions taken by the agent, e.g. say the agent played the sequence of actions: “*bafbcdbafecfbaf-bcdbcfecdbafbcdb*”. Then we use a grammar induction algorithm such as Sequitur to create new symbols to represent repeating sub-sequences. In this example, Sequitur would create the 4 new symbols: $\{G : bc, H : ec, I : baf, J : bafbcd\}$. We then append these symbols to the agent’s action set as macro-actions, so that the action set goes from $A = \{a, b, c, d, e, f\}$ to:

$$A = \{a, b, c, d, e, f\} \cup \{bc, ec, baf, bafbcd\}$$

The agent then continues playing in the environment with this new action set which includes macro-actions. Because the macro-actions are of length greater than one it means that their usage effectively reduces the time dimensionality of the problem, making it an easier problem to solve in some cases.

We now demonstrate the ability of AG-RL to consistently improve sample efficiency on the much more complicated Atari suite setting.

5 RESULTS

We first evaluate the AG-RL framework using DDQN as the base RL algorithm. We refer to this as AG-DDQN. We compare the performance of AG-DDQN and DDQN after training for 350,000 steps on 8 Atari games chosen a priori to represent a broad range. To accelerate training times for both we set their convolutional layer weights as equal to those of some pre-trained agents¹ and then only train the fully connected layers.

For the DDQN-specific hyperparameters of both networks we do no hyperparameter tuning and instead use the hyperparameters from van Hasselt et al. (2015) or set them manually. For the AG-specific hyperparameters we tried four options for the abandon ship hyperparameter (No Abandon Ship, 1, 2, 3) for the game Qbert and chose the option with the highest score. No other hyperparameters were tuned and all games then used the same hyperparameters which can all be found in Appendix B along with a more detailed description of the experimental setup.

We find that *AG-DDQN outperforms DDQN in all 8 games with a median final improvement of 31% and a maximum final improvement of 668%* - Figure 3 summarises the results.

Next we further evaluate AG-RL by using SAC as the base RL algorithm, leading to AG-SAC. We compare the performance of AG-SAC to SAC. We train both algorithms for 100,000 steps on 20 Atari games chosen a priori to represent a broad range games. As SAC is a much more efficient algorithm than DDQN this time we train both agents from scratch and do not use pre-trained convolutional layers.

For the SAC-specific hyperparameters of both networks we did no hyperparameter tuning and instead used a mixture of the hyperparameters found in Haarnoja et al. (2018) and Kaiser et al. (2019).

¹We used the pre-trained agents in the GitHub repository rl-baselines-zoo https://github.com/araffin/rl-baselines-zoo/tree/master/trained_agents/dqn




Figure 3: Comparing AG-DDQN to DDQN for 8 Atari games. Graphs show the average evaluation score over 5 random seeds where an evaluation score is calculated every 25,000 steps and averaged over the previous 3 scores. For the evaluation methodology we used the same no-ops condition as in van Hasselt et al. (2015). The shaded area shows ± 1 standard deviation.




Figure 4: Comparing AG-SAC to SAC for 20 Atari games. Graphs show the average evaluation score over 5 random seeds where an evaluation score is calculated at the end of 100,000 steps of training. For the evaluation methodology we used the same no-ops condition as in van Hasselt et al. (2015).

For the AG-specific hyperparameters again the only tuning we did was amongst 4 options for the abandon ship hyperparameter (No Abandon Ship, 1, 2, 3) on the game Qbert. No other hyperparameters were tuned and all games then used the same hyperparameters, details of which can be found in Appendix C.

Our results show *AG-SAC outperforms SAC in 19 out of 20 games with a median improvement of 96% and a maximum improvement of 3,756%* - Figure 4 summarises the results and Appendix D provides them in more detail.

We also find that *AG-SAC outperforms Rainbow, which is the model-free state-of-the-art for Atari sample efficiency, in 17 out of 20 games with a median improvement of 62% and maximum improvement of 13,140%* - see Appendix D for more details. Also note that the Rainbow scores used were taken from Kaiser et al. (2019) who explain they were the result of extensive hyperparameter tuning compared to our AG-SAC scores which benefited from very little hyperparameter tuning.

6 DISCUSSION

To better understand the results, we first explore what types of macro-actions get identified during the Identify Action Grammar stage, whether the agents use them extensively or not, and to what extent the Abandon Ship technique plays a role. We find that the length of macro-actions can vary greatly from length 2 to over 100. An example of an inferred macro-action was `8888111188881111` from the game Beam Rider where 1 represents Shoot and 8 represents move Down-Right. This macro-action seems particularly useful in this game as the game is about shooting enemies whilst avoiding being hit by them.




Figure 5: Ablation study comparing DDQN to different versions of AG-DDQN for the game Qbert. The dark line is the average of 5 random seeds, the shaded area shows ± 1 standard deviation across the seeds.

We also found that the agents made extensive use of the macro-actions. Taking each game’s best performing AG-SAC agent, the average *attempted* move length during evaluation was 20.0. Because of Abandon Ship the average *executed* move length was significantly lower at 6.9 but still far above the average of 1.0 we would get if the agents were not using their macro-actions. Appendix E gives more details on the differences in move lengths between games.

We now conduct an ablation study to investigate the main drivers of AG-DDQN’s performance in the game Qbert, with results in Figure 5 . Firstly we find that HAR was crucial for the improved performance and without it AG-DDQN performed no better than DDQN. We suspect that this is because without HAR there are much fewer experiences to learn from and so our action value estimates have very high variance.

Next we find that using an action balanced replay buffer improved performance somewhat but by a much smaller and potentially insignificant amount. This potentially implies that it may not be necessary to use an action balanced replay and that the technique may work with an ordinary replay buffer. We also see that with our chosen abandon ship hyperparameter of 1.0, performance was higher than when abandon ship was not used. Performance was also similar for the choice of 2.0 which suggests performance was not too sensitive to this choice of hyperparameter. Finally we see improved performance from using transfer learning when appending macro-actions to the agent’s action set rather than creating a new network.

Lastly, we note that the game in which AG-DDQN and AG-SAC both do relatively best in is Enduro. Enduro is a game with sparse rewards and therefore one where exploration is very important. We therefore speculate that AG-RL does best on this game because using long macro-actions increases the variance of where an agent can end up and therefore helps exploration.

7 CONCLUSION

Motivated by the parallels between the hierarchical composition of language and that of actions, we combine techniques from computational linguistics and RL to help develop the Action Grammars Reinforcement Learning framework.

The framework expands on two key areas of RL research: Symbolic RL and Hierarchical RL. We extend the ideas of symbolic manipulation in RL (Garnelo et al., 2016; Garnelo & Shanahan, 2019) to the dynamics of sequential action execution. Moreover, while Relational RL approaches (Zambaldi et al., 2018) draw on the complex logic-based framework of inductive programming, we merely observe successful behavioral sequences to induce higher order structures.

We provided two implementations of the framework: AG-DDQN and AG-SAC. We showed that AG-DDQN improves on DDQN in 8 out of 8 tested Atari games (median +31%, max +668%) and AG-SAC improves on SAC in 19 out of 20 tested Atari games (median +96%, max +3,756%) all without substantive hyperparameter tuning. We also show that AG-SAC beats the model-free state-of-the-art for 17 out of 20 Atari games (median +62%, max +13,140%) in terms of sample efficiency, again even without substantive hyperparameter tuning.

As part of AG-RL we also provided two new and generally applicable techniques: Hindsight Action Replay and Abandon Ship. Hindsight Action Replay can be used to drastically improve information efficiency in any off-policy setting involving macro-actions. Abandon Ship reduces the variance involved when training macro-actions, making it feasible to train algorithms with very long macro-actions (over 100 steps in some cases).

Overall, we have demonstrated the power of action grammars to consistently improve the performance of RL agents. We believe our work is just one of many possible ways of incorporating the concept of action grammars into RL and we look forward to exploring other methods. By improving sample efficiency we hope that action grammars can eventually help make RL a universally practical and useful tool in modern society.

REFERENCES

- Benjamin Beyret, Ali Shafti, and A Aldo Faisal. Dot-to-dot: Explainable hierarchical reinforcement learning for robotic manipulation. 2019.
- N. Ding, L. Melloni, X. Tian, and D. Poeppel. Rule-based and word-level statistics-based processing of language: Insights from neuroscience. *Philosophical Transactions of the Royal Society of London B: Biological Sciences*, 2012.
- Marta Garnelo and Murray Shanahan. Reconciling deep learning with symbolic artificial intelligence: representing objects and relations. *Current Opinion in Behavioral Sciences*, 29:17–23, 2019.
- Marta Garnelo, Kai Arulkumaran, and Murray Shanahan. Towards deep symbolic reinforcement learning. *arXiv preprint arXiv:1609.05518*, 2016.
- Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and Sergey Levine. Soft actor-critic algorithms and applications. *ArXiv*, abs/1812.05905, 2018.
- Lukasz Kaiser, Mohammad Babaeizadeh, Piotr Milos, Blazej Osinski, Roy H. Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, Ryan Sepassi, George Tucker, and Henryk Michalewski. Model-based reinforcement learning for atari. *ArXiv*, abs/1903.00374, 2019.

- Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dhharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.
- C. Nevill-Manning and I. Witten. Identifying hierarchical structure in sequences: A linear-time algorithm. *CoRR*, 1997.
- OpenAI, Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Józefowicz, Bob McGrew, Jakub W. Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, Jonas Schneider, Szymon Sidor, Josh Tobin, Peter Welinder, Lilian Weng, and Wojciech Zaremba. Learning dexterous in-hand manipulation. *ArXiv*, abs/1808.00177, 2018.
- T. Osa, V. Tangkaratt, and M. Sugiyama. Hierarchical reinforcement learning via advantage-weighted information maximization. *International Conference on Learning Representations*, 2019.
- K. Pastra and Y. Aloimonos. The minimalist grammar of action. *Philosophical Transactions of the Royal Society of London B: Biological Sciences*, 2012.
- Sahil Sharma, Aravind S. Lakshminarayanan, and Balaraman Ravindran. Learning to repeat: Fine grained action repetition for deep reinforcement learning. *ArXiv*, abs/1702.06054, 2017.
- David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lynette R. Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy P. Lillicrap, Hui zhen Fan, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of go without human knowledge. *Nature*, 550:354–359, 2017.
- Dietrich Stout, Thierry Chaminade, Andreas A. C. Thomik, Jan Apel, and Aldo A. Faisal. Grammars of action in human behavior and evolution. 2018.
- Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *AAAI*, 2015.
- Alexander Vezhnevets, Volodymyr Mnih, John Agapiou, Simon Osindero, Alex Graves, Oriol Vinyals, and Koray Kavukcuoglu. Strategic attentive writer for learning macro-actions. In *NIPS*, 2016.
- Yuhuai Wu, Elman Mansimov, Shun Liao, Roger B. Grosse, and Jimmy Ba. Scalable trust-region method for deep reinforcement learning using kronecker-factored approximation. In *NIPS*, 2017.
- G. Yule. *The Study of Language*. Cambridge University Press, 2015.
- Vinicius Zambaldi, David Raposo, Adam Santoro, Victor Bapst, Yujia Li, Igor Babuschkin, Karl Tuyls, David Reichert, Timothy Lillicrap, Edward Lockhart, et al. Relational deep reinforcement learning. *arXiv preprint arXiv:1806.01830*, 2018.

APPENDIX

A HINDSIGHT ACTION REPLAY

Below we provide an example of how HAR stores the experiences of an agent after they played the moves *acab* where *a* and *b* are primitive actions and *c* represents the macro-action *ababa*.




Figure 6: The Hindsight Action Replay (HAR) process with Action Set: $\{a, b, c:\{abab\}\}$ meaning that there are 2 primitive actions *a* and *b*, and one macro-action *c* which represents the sequence of primitive actions *abab*. The example shows how using HAR leads to the original sequence of 4 actions *acab* producing 9 experiences for the replay buffer instead of only 4.

B AG-DDQN EXPERIMENT AND HYPERPARAMETERS

The hyperparameters used for the DDQN results are given by Table 1. The network architecture was the same as in the original Deepmind Atari paper (Mnih et al., 2015).

Table 1: Hyperparameters used for DDQN and AG-DDQN results

Hyperparameter	Value
Batch size	32
Replay buffer size	1,000,000
Discount rate	0.99
Steps per learning update	4
Learning iterations per round	1
Learning rate	0.0005
Optimizer	Adam
Weight Initialiser	He
Min Epsilon	0.1
Epsilon decay steps	1,000,000
Fixed network update frequency	10000
Loss	Huber
Clip rewards	Clip to [-1, +1]
Initial random steps	25,000

The architecture and hyperparameters used for the AG-DDQN results that are relevant to DDQN are the same as for DDQN and then the rest of the hyperparameters are given by Table 2.

Table 2: Hyperparameters used for AG-DDQN results

Hyperparameter	Value	Description
Evaluation episodes	5	The number of no exploration episodes we use to infer the action grammar
Replay buffer type	Action balanced	The type of replay buffer we use
Steps before inferring grammar	75,001	The number of steps we run before inferring the action grammar
Abandon ship	1.0	The threshold for the abandon ship algorithm
Macro-action exploration bonus	4.0	How much more likely we are to pick a macro-action than a primitive action when acting randomly

C AG-SAC HYPERPARAMETERS

The hyperparameters used for the discrete SAC results are given by Table 3. The network architecture for both the actor and the critic was the same as in the original Deepmind Atari paper (Mnih et al., 2015).

Table 3: Hyperparameters used for SAC and AG-SAC results

Hyperparameter	Value
Batch size	64
Replay buffer size	1,000,000
Discount rate	0.99
Steps per learning update	4
Learning iterations per round	1
Learning rate	0.0003
Optimizer	Adam
Weight Initialiser	He
Fixed network update frequency	8000
Loss	Mean squared error
Clip rewards	Clip to [-1, +1]
Initial random steps	20,000

The architecture and hyperparameters used for the AG-SAC results that are relevant to SAC are the same as for SAC and then the rest of the hyperparameters are given by Table 4.

Table 4: Hyperparameters used for AG-SAC results

Hyperparameter	Value	Description
Evaluation episodes	5	The number of no exploration episodes we use to infer the action grammar
Replay buffer type	Action balanced	The type of replay buffer we use
Steps before inferring grammar	30,001	The number of steps we run before inferring the action grammar
Abandon ship	2.0	The threshold for the abandon ship algorithm
Macro-action exploration bonus	4.0	How much more likely we are to pick a macro-action than a primitive action when acting randomly
Post inference random steps	5,000	The number of random steps we run immediately after updating the action set with new macro-actions

D SAC, AG-SAC AND RAINBOW ATARI RESULTS

Below we provide all SAC, AG-SAC and Rainbow results after running 100,000 iterations for 5 random seeds. We see that AG-SAC improves over SAC in 19 out of 20 games (median improvement of 96%, maximum improvement of 3756%) and that AG-SAC improves over Rainbow in 17 out of 20 games (median improvement 62%, maximum improvement 13140%).

Table 5: SAC, AG-SAC and Rainbow results on 20 Atari games. The mean result of 5 random seeds is shown with the standard deviation in brackets. As a benchmark we also provide a column indicating the score an agent would get if it acted purely randomly.

Game	Random	Rainbow	SAC	AG-SAC
Enduro	0.0	0.53	0.8 (0.8)	30.1 (10.1)
Amidar	11.8	20.8	7.9 (5.1)	56.7 (15.4)
UpNDown	488.4	1346.3	250.7 (176.5)	1739.1 (835.8)
Road Runner	0.0	524.1	305.3 (557.4)	1868.7 (1658.3)
Frostbite	74.0	140.1	59.4 (16.3)	252.3 (79.8)
Freeway	0.0	0.1	4.4 (9.9)	13.2 (12.1)
Kangaroo	42.0	38.7	29.3 (55.1)	69.3 (80.4)
Pong	-20.4	-19.5	-20.98 (0.0)	-20.95 (0.1)
Breakout	0.9	3.3	0.7 (0.5)	1.5 (1.4)
Crazy Climber	7339.5	12558.3	3668.7 (600.8)	7510.0 (3898.7)
Space Invaders	148.0	135.1	160.8 (17.3)	301.0 (75.1)
Asterix	248.8	285.7	272.0 (33.3)	459.0 (104.2)
Alien	184.8	290.6	216.9 (43.0)	349.7 (33.4)
Assault	233.7	300.3	350.0 (40.0)	490.6 (119.0)
Qbert	166.1	235.6	280.5 (124.9)	359.7 (172.8)
BattleZone	2895.0	3363.5	4386.7 (1163.0)	5486.7 (1461.7)
Seaquest	61.1	206.3	211.6 (59.1)	261.9 (56.3)
Beam Rider	372.1	365.6	432.1 (44.0)	463.0 (219.1)
MsPacman	235.2	364.3	690.9 (141.8)	712.9 (194.5)
JamesBond	29.2	61.7	68.3 (26.2)	66.3 (19.4)

Note that the scores for Pong are negative and so to calculate the proportional improvement for this game we first convert the scores to their increment over the minimum possible score. In Pong the minimum score is -21.0 and so we first add 21 to all scores before calculating relative performance.

Also note that for Pong both AG-SAC and SAC perform worse than random. The improvement of AG-SAC over SAC for Pong therefore could be considered a somewhat spurious result and potentially should be ignored. Note that there are no other games where AG-SAC performs worse than random though and so this issue is contained to the game Pong.

E MACRO-ACTIONS AND ABANDON SHIP

Table 6: The lengths of moves attempted and executed in the best performing AG-SAC seed for each game. Executed move lengths being shorter than attempted move lengths indicates that the Abandon Ship technique was used. The games are ordered in terms of the percentage improvement AG-SAC saw over SAC with the first game being the game that saw the most improvement.

Game	Attempted Move Lengths	Executed Move Lengths	Executed / Attempted
Enduro	14.8	12.0	81.1%
Amidar	3.4	2.8	82.4%
UpNDown	16.4	11.6	71.0%
Road Runner	8.2	6.8	82.9%
Frostbite	2.0	2.0	100.0%
Freeway	15.8	15.2	96.2%
Kangaroo	2.1	1.5	73.8%
Breakout	7.9	2.2	27.8%
Crazy Climber	7.1	4.4	62.0%
Space Invaders	8.7	6.3	72.4%
Asterix	58.3	9.8	16.8%
Alien	13.1	11.6	88.5%
Assault	126.9	8.1	6.4%
Qbert	8.2	8.0	97.6%
Battle Zone	63.4	6.0	9.5%
Seaquest	14.0	8.6	61.4%
Beam Rider	12.2	5.8	47.5%
MsPacman	8.2	7.5	91.5%
Pong	8.4	6.5	77.4%
James Bond	1.3	1.2	97.8%