# On the Interplay Between Labeling and Evaluating Regions

## Abstract

Consider a setting where we wish to automate an expensive task with a machine learning algorithm using a limited labeling resource. In such settings, examples routed for labeling are often out of scope for the machine learning algorithm. For example, in a spam detection setting, human reviewers not only provide labeled data but are such high-quality detectors of spam that examples routed to them no longer require machine evaluation. As a consequence, the distribution of examples routed to the machine is intimately tied to the process generating labels. We introduce a formalization of this setting, and give an algorithm that simultaneously learns a model and decides when to request a label by leveraging ideas from both the abstention and active learning literatures. We prove an upper bound on the algorithm's label complexity and a matching lower bound for any algorithm in this setting. We conduct a thorough set of experiments including an ablation study to test different components of our algorithm. We demonstrate the effectiveness of an efficient version of our algorithm over margin sampling on a variety of datasets.

## 1 Introduction

In this paper, we consider a system that relies on automated predictions made by a machine learning model. We assume this system has a limited budget for requesting ground-truth labels (e.g. from a domain expert). In practice, such request can be used, among other purposes, to gather additional training data for the machine learning model. If the system asks for a label for an example, then it no longer needs the model's prediction for that particular example. Thus, the pattern of label queries effectively defines the distribution that the model will learn with and predict on.

Take for example a large-scale video-hosting website. The website wants to automatically detect videos that violate its community guidelines. In order to acquire labels for this task, some of these videos are evaluated by a finite pool of human reviewers. There are two consequences of this evaluation. Firstly, the reviewer provides a training label for the model. Secondly, the human intervention makes it so that the machine learning algorithm is no longer tasked with making predictions on these examples.

We take the perspective of a system designer who wants to understand (and optimize for) the performance of the automated system on the examples that it will be asked to evaluate. Let $r : \mathcal{X} \to \{0, 1\}$ be a rule governing whether the system requests a label for $x \in \mathcal{X}$. Let $h : \mathcal{X} \to \mathbb{R}$ be a hypothesis describing the automated system. We seek to minimize $\mathbb{E}[L(h(x), y) \mid r(x) = 0]$, where $L$ is a loss function. We can think of this setting as combining the objective studied in *abstention learning* (minimizing $E[L(h(x), y) \mid r(x) = 0]$) with the feedback model studied in *active learning* (labels are only available when $r(x) = 1$). We introduce a new framework, which we call *dual purpose learning* framework, that combines these elements.

We first analyze the *proper* dual purpose labeling framework in an online setting, which proceeds as follows. At the start of each round $t$, the learner selects both a requester function $r_t$ from some class $\mathcal{R}_\rho$, where $\rho$ is an upper bound on the request-rate of functions in this class, and a hypothesis $h_t$ from some class $\mathcal{H}$ using all the feedback available from the past. The learner's expected loss on this round is given by $E[L(h_t(x), y) \mid r_t(x) = 0]$. The function $r_t$ also determines the feedback available to the algorithm. If $r_t(x) = 1$, the learner observes $(x, y)$, which was drawn i.i.d. from an unknown distribution, and otherwise, only $x$ is revealed and $y$ is censored. The goal of the learner is to compete with the optimal choice of hypothesis and requester by minimizing the excess loss
$$\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}(h_t, r_t) = E[L(h_t(x), y) \mid r_t(x) = 0] - \inf_{(h^*, r^*) \in \mathcal{H} \times \mathcal{R}_\rho} \mathbb{E}[L(h^*(x), y) \mid r^*(x) = 0].$$

Our first main result is the surprising fact that, under mild assumptions, bounds on the excess loss that match the $O(1/\sqrt{t})$ generalization rates of full-feedback passive learning are not possible in the proper dual purpose labeling framework. This lower bound also suggests a relaxation of the proper dual purpose labeling framework, which we call *improper dual purpose labeling*. In the improper setting, the learner is still interested in learning $h_t, r_t$ that minimize $\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}$. However, the learner is allowed to request labels using a more powerful requester class than $\mathcal{R}_\rho$ during training. As in classical PAC-learning results, improper learning allows circumvention of the impossibility result.

As a practical matter, the improper setting is useful when the system designer is willing to spend more resources during training. In our motivating example, the designer of the abuse-detection system might be willing to implement a more complicated system during training, which might include a larger budget (in dollars or man-power) for human intervention. However, after a time horizon $T$, training stops, and the designer commits to some $h_T, r_T$ for $r_T \in \mathcal{R}_\rho$. From then on, examples satisfyng $r_T(x) = 0$ are routed to $h_T$, and thus, we wish to characterize $\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}(h_T, r_T)$.

In the improper setting, we demonstrate that IWAL, an algorithm from the active learning literature [7], can be adapted to our setting into an algorithm which we call DPL-IWAL. Since our objective is no longer an expectation of some loss function, but rather, the conditional expectation evaluated on the event that $r(x) = 0$, IWAL's standard analysis does not apply. A key technical hurdle is proving that estimates of this conditional loss concentrate at the right rate in order to attain generalization guarantees for the pair $(h, r)$ returned by DPL-IWAL. We show that over a time horizon $T$, DPL-IWAL algorithm requests $O((\rho + \eta)T)$ examples where $\eta = \min_{(h,r) \in \mathcal{H} \times \mathcal{R}_\rho} \mathbb{E}[L(h(x), y) \mid r(x) = 0]$ is the optimum value of our objective. At the same time our main lower bound demonstrates that $\Omega((\rho + \eta)T)$ requests are in fact necessary to compete with the best policy in $\mathcal{H} \times \mathcal{R}_\rho$.

Finally, we conduct a thorough exploration of these techniques on a number of datasets. We first undertake an ablation study, using a finite hypothesis class, showing that DPL-IWAL outperforms baselines that either ignore the active learning or abstention learning aspects of the problem. DPL-IWAL is not computationally efficient to implement since just like IWAL, it maintains a version space, that is a set of candidate hypotheses, which is non-trivial to optimize over in general. We therefore also conduct a number of experiments with an efficient heuristic inspired by our results using continuous hypothesis classes, outperforming natural baselines including margin sampling [26, 4], which admits state-of-the-art performance for active learning problems in practice [29, 27, 11].

**Related Work:** Our setting encompasses an objective considered in abstention learning (sometimes called selective classification), where the learner controls its evaluation region, that is the region of the domain where the learner is evaluated, by abstaining on the complement. In our setting, the evaluation region is where the learner does not request a label and the complementing abstention region is where the learner makes a request. At the same time, our setting considers the feedback mechanism from active learning. These are tied in a specific way in our framework: feedback is only available on the abstention (i.e. requesting) region and no information is revealed about the evaluation region. Neither an abstention algorithm nor a standard active learning algorithm would work in our setting and the algorithms in these settings can lead to incorrect solutions (see Appendix C). Nevertheless, we survey some of the relevant literature.

Learning with abstention was first studied by [9, 10] for specific practical applications. Subsequently, several authors analyzed algorithms [6, 23, 30, 31] for this setting with an emphasis on developing margin-based rules for abstention. Along a different line of work, [20, 21] analyze the theoretical trade-off between the coverage of an abstention function and a classifier's performance when not abstaining. All these works share in common the assumption that the learner has offline access to fully labeled samples, unlike the setting considered in this work.

A more recent line of work [15, 14, 16] considers a setting where the algorithms learn over two classes of functions, a hypothesis class and an abstention class. These work either assume full feedback is always available (e.g. [15, 14]), or like in [16], the feedback is only available in the evaluation region, which is the exact opposite feedback mechanism than that of our setting since we receive feedback in the abstention region. Similarly, [28] consider a setting where feedback is always available.

In the active learning literature, several authors focus on analyzing margin-based active learning which requests the labels for points close to a learned model classification surface [19, 4, 5, 3, 2, 32, 25, 34]. Other algorithms admit generalization guarantees on the same order as passive learning while proving that their algorithm's label complexity, i.e. the number of points requested during learning, is bounded by a favorable rate. [7] derived an algorithm, called IWAL, for general loss functions with strong theoretical guarantees. We wish to use this algorithm for our setting with the abstention learning objective. However, the loss function we consider is in fact a conditional expectation evaluated on an event, which is not amenable to standard IWAL. Our analysis and corresponding algorithm, DPL-IWAL, describes how to apply IWAL to such a setting.

Finally, ideas from the abstention framework have been applied to the active learning previously. [33] used confidence-based predictors as a subroutine of an active learning algorithm. [22] applied an abstention strategy from [20] to the CAL algorithm of [12] proving theoretical guarantees, but only under specific model and distributional assumptions, which we do not make in our setting.

# 2    Setting and Preliminaries

In the dual purpose labeling framework, a learner is given a hypothesis class $\mathcal{H}$ with finite VC-dimension $d$, and a class of deterministic requester functions $\mathcal{R} \subset \{X \to \{0, 1\}\}$. Nature fixes a distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$, unknown to the learner. Given the marginal over $\mathcal{X}$, and $\rho > 0$, we denote $\mathcal{R}_\rho \subset \mathcal{R}$ as the subset of $\mathcal{R}$ with bounded request-rate $\mathbb{E}_x[r(x) = 1] \leq \rho$ for all $r \in \mathcal{R}_\rho$. $\mathbb{E}_x[r(x) = 1]$ can be well estimated using unlabeled data, which is generally readily available, allowing a bound on request-rate to be enforced in practice.

The interaction between the learner and nature proceeds through a sequence of rounds $t$. The learner first selects $(h_t, r_t) \in \mathcal{H} \times \mathcal{R}_\rho$ as a function of the past. Nature then draws an independent sample $(x_t, y_t)$ from $\mathcal{D}$, where $x_t$ is revealed to the learner. If $r_t(x_t) = 1$, the learner additionally observes $y_t$, but the performance of $h_t$ is not evaluated. If $r_t(x_t) = 0$, the learner does not observe $y_t$, but the performance of $h_t$ is evaluated. Thus, the choice of $r_t$ serves dual purposes: it determines whether the algorithm receives feedback, and whether its performance will be evaluated.

Formalizing this further, we suppose that the learner is given a loss function $L : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}$. The learner seeks to output $h_t$ that generalizes well on the region where $r_t$ dictates that $h_t$ should be evaluated. We therefore seek to bound the (conditional) excess loss $\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}(h_t, r_t) = E[L(h_t(x), y) \mid r(x) = 0] - \inf_{(h^*, r^*) \in \mathcal{H} \times \mathcal{R}_\rho} \mathbb{E}[L(h^*(x), y) \mid r^*(x) = 0]$. In particular we seek $O(1/\sqrt{t})$ bounds on $\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}(h_t, r_t)$, matching the generalization rate of full-feedback passive learning.

The conditional loss of the best pair in $\mathcal{H} \times \mathcal{R}_\rho$ plays an important role in our lower bounds, and so it is useful to define $\eta = \inf_{(h^*, r^*) \in \mathcal{H} \times \mathcal{R}_\rho} E_{x,y}[L(h^*(x), y) \mid r^*(x) = 0]$.

Finally, we call this the *proper dual purpose framework* since the algorithm is attempting to generalize well with respect to the class $\mathcal{H} \times \mathcal{R}_\rho$ and labels are generated according to functions in $\mathcal{R}_\rho$. In the subsequent section, we will see that $O(1/\sqrt{t})$ bounds on $\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}(h_t, r_t)$ are impossible in general. This motivates the *improper dual purpose framework* as introduced in the following section.

# 3    Lower Bound

In this section, we present a lower bound stating that it is impossible for any algorithm to achieve an $O(1/\sqrt{t})$ generalization rate in the proper dual purpose setting. Thus, we here introduce the notion of *improper algorithms*. On each round $t$, an improper algorithm selects $h_t \in \mathcal{H}$ and an $R_t : X \to \{0, 1\}$ that is unconstrained for the purposes of showing a lower bound (e.g. $R_t$ is not necessarily in the set $\mathcal{R}_\rho$). As in the proper setting, label requests are tied to the evaluation region. That is, the algorithm sees $y_t$ i.f.f. $R_t(x_t) = 1$, and wishes to minimize $\mathcal{L}_{\mathcal{H}, \mathcal{R}_\rho}(h_t, R_t)$. Notice that $\mathcal{L}$ is still defined with respect to the reference class $\mathcal{R}_\rho$, and that the proper setting is a special case of the improper setting where $R_t$ is equal to an $r_t \in \mathcal{R}_\rho$. The lower bound below shows that any

143  algorithm with the desired generalization rate must satisfy $\frac{1}{T}\sum_{t=1}^{T} E[R_t(x_t)] > \rho$. Thus, since
144  $E[r(x)] \leq \rho$ for every $r \in \mathcal{R}_\rho$, no proper algorithm can attain the desired rate.

145  We prove a bound that holds for almost any possible classes of functions $\mathcal{H}, \mathcal{R}$, with some restrictions
146  on $\mathcal{R}$. We say that $\mathcal{R}$ separates $\mathcal{X}$ if given any finite set of examples in $x_0, \ldots, x_n \in \mathcal{X}$, there exists
147  a point $\hat{x}$ outside this finite set of points and a requester in $\mathcal{R}$ such $r(\hat{x}) = 1$ while $r(x_0) = \cdots =$
148  $r(x_n) = 0$. This condition is much stronger than is necessary for the lower bound, but is already
149  satisfied by simple classes such as when $\mathcal{R}$ contains linear separators and $\mathcal{X}$ is a ball in any dimension
150  $\geq 2$, and becomes easier to satisfy as $\mathcal{R}$ becomes more complex. We need a weaker condition that
151  requires only the separation property hold for *some* set shattered by $\mathcal{H}$.

152  **Definition 1.** $\mathcal{R}$ separates $\mathcal{X}$ with respect to $\mathcal{H}$ if $d = \text{VCD}(\mathcal{H})$, and there exists *a set of $d$ examples*
153  $x_0, \ldots, x_{d-1}$ shattered by $\mathcal{H}$, $\hat{x} \in \mathcal{X}$, and $r \in \mathcal{R}$ such that $r(\hat{x}) = 1$ and $r(x_0) = \ldots r(x_{d-1}) = 0$.

154  We first describe a distribution that follows the basic construction used to demonstrate lower bounds
155  for pure active learning [7]. We then augment this distribution to include a region of mass $\rho$ that
156  contains random noise. Intuitively, one can think of an algorithm as requesting a label either to solve
157  the active learning problem or to avoid loss on examples that it is uncertain on in the region of mass
158  $\rho$. We argue that the optimal algorithm, when not solving the active learning problem, spends $\rho T$
159  labels requesting on the random noise.

160  While this is the basic idea, the proof needs to preclude the possibility that an algorithm with a
161  suboptimal prediction $h$ benefits from requesting labels outside the region of mass $\rho$ purely for the
162  purpose of avoiding loss (and not to solve the active learning problem). An algorithm can also
163  request labels at a rate greater than $\rho$ on any given round with the hope of decreasing its overall label
164  complexity over $T$ rounds. The proof shows that neither of these strategies benefits an algorithm
165  enough to deviate from the optimal strategy outlined in the previous paragraph.

166  **Definition 2.** *Fix any $\rho \geq 0$. We say that a round $t$ is a* failed round *if the algorithm selects a*
167  *requesting strategy $R_t : \mathcal{X} \to \{0,1\}$, and hypothesis $h_t \in \mathcal{H}$ satisfying $\mathbb{E}[L(h_t(x), y) \mid R_t(x) =$*
168  $0] \geq \min_{(h,r) \in \mathcal{H} \times \mathcal{R}_\rho} \mathbb{E}[L(h(x), y) \mid r(x) = 0] + \sqrt{\frac{d\eta}{t}}$.

169  As a practical matter, we will also require that an improper algorithm outputs a model $(h_T, r_T) \in$
170  $\mathcal{H} \times \mathcal{R}_\rho$ at the end of its time horizon, where $r_T$ comes from the reference class. This paves the way
171  for algorithms discussed in the subsequent sections which are applicable in systems that are able to
172  tolerate a higher labeling overhead during a finite training horizon, but eventually need to converge on
173  a model with request rate $\rho$. Crucially, the lower bound establishes the minimum additional overhead
174  during training as $\eta$ (defined in Section 2), which is matched by our upper bounds.

175  **Theorem 1.** *Let $L(h(x), y) = 1[yh(x) \leq 0]$ be the misclassification loss. Given $\mathcal{R}$ that separates*
176  *$\mathcal{X}$ with respect to $\mathcal{H}$ with $d = \text{VCD}(\mathcal{H})$, let $\mathcal{R}_\rho \subset \mathcal{R}$ consist of requesters with bounded request-*
177  *rate $\rho$. For any $\eta \leq 1/4$, $\rho \leq 1/2$, there exists a distribution on $\mathcal{X} \times \{-1, 1\}$ such that $\eta =$*
178  *$\min_{(h,r) \in \mathcal{H} \times \mathcal{R}_\rho} \mathbb{E}[L(h(x), y) \mid r(x) = 0]$.*

179  *Furthermore, there exists a sufficiently large $T \geq 0$ such that with probability at least $1/2$ any*
180  *algorithm that, (A) outputs $(h_T, r_T) \in \mathcal{H} \times \mathcal{R}_\rho$, such that $\mathbb{E}[L(h_T(x), y) \mid r_T(x) = 0] \leq \eta + \sqrt{d\eta/T}$,*
181  *and (B) suffers no more than $T/2$ failed rounds, requires that: $\mathbb{E}[\sum_t R_t] \geq \Omega((\eta + \rho)T)$.*

182  The above theorem states that an algorithm must request the labels of at least $\Omega((\eta + \rho)T)$ examples
183  (in expectation) if we require that the pair returned by the algorithm generalizes at a rate approximating
184  that of standard supervised learning. This then directly implies that $R_t$ must be selected outside of
185  the class $\mathcal{R}_\rho$ since this class only contains functions with a requesting rate of at most $\rho$, resulting in
186  label complexity at most $O(\rho T)$ in expectation. All proofs can be found in Appendix A.

187  Although we state the lower bound for classification loss, it can be extended to any loss function
188  where mispredicting the sign of an example, $yh(x) \leq 0$, implies $L(h(x), y) \geq C$ for some constant
189  $C$. This is true for the logistic, hinge, squared, and absolute losses.

## 4  Dual Purpose Labeling Algorithm

191  In this section, we present our algorithm, DPL-IWAL (see Algorithm 1 for the pseudo-code), in the
192  improper dual purpose framework. At a high level, DPL-IWAL finds the pair $(h, r) \in \mathcal{H} \times \mathcal{R}_\rho$ that

---

**Algorithm 1** DPL-IWAL Algorithm

---

**Require:** Max iteration $T > 0$, $V_1 = \mathcal{H} \times \mathcal{R}_\rho$, $t_0$ be the first time $t$ such that $t \geq 16 \log(t/\delta)$
    **for** $t \in [1, t_0]$ **do**
        Observe $x_t$ in order to construct estimates $\frac{1}{t-1} \sum_{s=1}^{t-1} \mathbf{1}[r(x_s) = 0]$
    **for** $t \in [t_0 + 1, T]$ **do**
        $(h_t, r_t) \leftarrow \operatorname{argmin}_{(h,r) \in V_t} \widehat{L}_{t-1}(h, r)$
        Receive $x_t$
        **if** $r_t(x_t) = 1$ **then** Request label $y_t$
        $p_t(x_t) \leftarrow \min\left(1, \max\limits_{(h,r),(h',r') \in V_t} \max\limits_{y \in Y} \left| \frac{L(h(x_t),y)\mathbf{1}[r(x_t)=0]}{\frac{1}{t-1}\sum_{s=1}^{t-1}\mathbf{1}[r(x_s)=0]} - \frac{L(h'(x_t),y)\mathbf{1}[r'(x_t)=0]}{\frac{1}{t-1}\sum_{s=1}^{t-1}\mathbf{1}[r'(x_s)=0]} \right| \right)$
        $q_t \sim \text{Bernoulli}(p_t)$
        **if** $q_t = 1$ **then** Request or re-use label $y_t$
        $V_{t+1} \leftarrow \{(h,r) \in V_t : \widehat{L}_t(h,r) \leq \min_{(h,r) \in V_t} \widehat{L}_t(h,r) + \tilde{\Delta}_t\}$
        **if** $r_t(x_t) = 0 \wedge q_t = 0$ **then** Predict label using $\operatorname{sgn}(h_t(x_t))$
    **Return:** $(h_T, r_T)$

---

minimizes the conditional loss, $\mathbb{E}[L(h(x), y)|r(x) = 0]$, i.e. the expected loss of $h$ conditioned on the event that the label is not requested by $r$. Intuitively, the best pair $(h, r)$ requests the label of the point whenever the prediction of $\operatorname{sgn}(h(x))$ is likely to be incorrect.

To find such a pair, at each round $t$, the algorithm first constructs an importance weighted estimate, $\widehat{L}_t(h, r)$, of $\mathbb{E}[L(h(x), y)|r(x) = 0]$ by using the fewest number of labeled points as possible and then chooses the pair $(h_t, r_t)$ that minimizes $\widehat{L}_t(h, r)$. Ideally, the importance weighted estimates $\widehat{L}_t(h, r)$ could be constructed from the set of points whose labels have been requested by $r_1, \ldots, r_t$, but these sets of points are a non-trivially biased sample of the underlying distribution. Moreover, these points could reside in regions of the space that are not useful for calculating $\mathbb{E}[L(h(x), y)|r(x) = 0]$. To see this more clearly, consider a simple case when $\mathcal{R}_\rho$ is contains just one function and the algorithm is then simply finding the $\operatorname{argmin}_{h \in \mathcal{H}} \mathbb{E}[L(h(x), y)|r(x) = 0]$. The points the $r$ functions request the label for, meaning points where $r(x) = 1$, do not reveal any information necessary to estimate $\mathbb{E}[L(h(x), y)|r(x) = 0]$ for $h \in \mathcal{H}$. Thus, the algorithm must label other regions in the space. Below, we describe how the algorithm uses a subset of the points requested by the $r_t \in \mathcal{R}_\rho$ in conjunction with some additional carefully chosen points, via a function $q_t$ outside $\mathcal{R}_\rho$, to construct unbiased estimators, $\widehat{L}_t(h, r)$. This fact thus makes DPL-IWAL an improper dual purpose algorithm.

Similarly to IWAL [7], the DPL-IWAL algorithm constructs an importance weighted estimate, but instead of estimating the expected loss as is done in IWAL, we craft an estimate of the conditional losses for $t > t_0$,

$$\widehat{L}_t(h, r) = \frac{1}{t - t_0 - 1} \sum_{s=t_0+1}^{t} \frac{q_s}{p_s(x_s)} \frac{L(h(x_s), y_s)\mathbf{1}[r(x_s) = 0]}{\frac{1}{s-1}\sum_{s'=1}^{s-1}\mathbf{1}[r(x_{s'}) = 0]},$$

where a coin $q_s \in \{0, 1\}$ is flipped with a bias probability $p_s(x_s)$ and where $t_0$ is the first time $t$ such that $t \geq 16 \log(t/\delta)$. Note that for the first $s \in [1, t_0]$, we simply observe the features $x_s$ in order to construct $\frac{1}{s-1} \sum_{s'=1}^{s-1} \mathbf{1}[r(x_{s'}) = 0]$ that are non-zero with high probability since these are needed in definition of the denominator of $\widehat{L}_t(h, r)$. Ignoring the $q_s$ and $p_s(x_s)$ for now, the numerator $\frac{1}{t-t_0-1} \sum_{s=t_0+1}^{t} L(h(x_s), y_s)\mathbf{1}[r(x_s) = 0]$ is a measure of the joint expectation $\mathbb{E}[L(h(x), y)\mathbf{1}[r(x) = 0]]$ while the denominator contains running averages of the $\mathbb{E}[r(x) = 0]$. Roughly speaking, by considering the ratio of these two terms, we estimate the conditional expected loss, $\mathbb{E}[L(h(x), y)|r(x) = 0] = \frac{\mathbb{E}[L(h(x),y)\mathbf{1}[r(x)=0]]}{\mathbb{E}[r(x)=0]}$.

The algorithm maintains a version space, $V_t$, as defined in Algorithm 1, which it reduces at each round. We prove that it suffices to use a slack term $\tilde{\Delta}_t = \tilde{O}\big(\sqrt{(1/t)\log(1/\delta)}\big)$, in order to ensure with high probability that $(h^*, r^*)$ remain within the version space as it shrinks. The $\tilde{O}(\cdot)$ hides constants and $\log(t|\mathcal{H} \times \mathcal{R}_\rho|)$ factors; see the appendix for exact constants. In order to reduce the number of labeled points used to construct the importance-weighted estimates, the probability of requesting a point $p_t$ is defined by the (estimated) conditional loss difference between pairs of functions in this

226 shrinking set $V_t$. Given the above, the algorithm's overall requesting rule, $R_t$, is thus defined by the
227 following condition: $R_t(x_t) = 1$ if and only if $r_t(x_t) = 1 \lor q_t = 1$ where $r_t \in \mathcal{R}_\rho$ and $q_t \notin \mathcal{R}_\rho$.

## 5  Generalization and Label Complexity Guarantees

229 In this section, we present a series of theoretical guarantees that analyze the performance of our
230 approach as compared to different baselines as well as prove an upper bound on the expected number
231 of label requests by the DPL-IWAL algorithm.

232 In our framework, we seek to select a hypothesis $h_t$ which incurs minimal loss whenever a label
233 request is not made. Below, we prove an upper bound on this type of loss that is in terms of the best
234 pair of functions, $(h^*, r^*) = \text{argmin}_{(h,r) \in \mathcal{H} \times \mathcal{R}_\rho} \mathbb{E}[L(h(x), y)|r(x) = 0]$.

235 **Theorem 2.** *Given any $\rho < \frac{1}{2}$, for any $\delta > 0$, with probability at least $1 - \delta$, for all $t \geq 16 \log(3t/\delta)$,*
236 $\mathbb{E}[L(h_t(x), y)|r_t(x) = 0] \leq \mathbb{E}[L(h^*(x), y)|r^*(x) = 0] + \tilde{O}\big(\sqrt{(1/t) \log(1/\delta)}\big).$

237 This guarantee states that the pair $(h_t, r_t)$ chosen by the algorithm is converging to the best pair
238 $(h^*, r^*)$ as a function of the time $t$ with respect to the conditional loss. The assumption $t \geq$
239 $16 \log(3t/\delta)$ is mild condition, for example, if $\delta = 0.0001$ we then require $t > 104$. Also, in most
240 standard applications, only a small fraction of examples can be labeled and it is natural to assume that
241 $\rho < \frac{1}{2}$. Nevertheless, this assumption can be reduced by increasing the constraint on $t$ in the bound.

242 Overall, the theoretical analysis, which is given in Appendix B, departs from standard derivations
243 since we need to carefully deal with conditional losses and the constructed estimates, $\widehat{L}_t(h, r)$.
244 More concretely, we first must ensure that the denominator of the estimate $\widehat{L}_t(h, r)$ is non-zero
245 with high probability as otherwise the estimate would not be well defined. To do so, we start the
246 labeling process of our algorithm only after $t_0$ examples have been observed. After $t_0$ examples have
247 been observed and using the fact that $\mathbb{E}[r(x) = 0] > 1 - \rho$, we can then prove that the condition
248 $\frac{1}{s-1} \sum_{s'=1}^{s-1} \mathbf{1}[r(x_{s'}) = 0] > 0$ holds with high probability (Lemma 1). Then, in order to apply
249 Azuma's inequality on conditional losses, we need to prove that $\frac{L(h(x_s), y_s)\mathbf{1}[r(x_s)=0]}{\frac{1}{s-1} \sum_{s'=1}^{s-1} \mathbf{1}[r(x_{s'})=0]}$ is bounded
250 by a favorable constant despite the variable denominator term (Lemma 2). Azuma's inequality
251 implies that the estimates are converging to $\mathbb{E}[\widehat{L}_t(h, r)]$, but this is not enough since we want to prove
252 guarantees in terms of $\mathbb{E}[L(h(x), y)|r(x) = 0]$. Thus, using a series of concentration inequalities, we
253 prove that expected value of the estimate, $\mathbb{E}[\widehat{L}_t(h, r)]$, converges to the expected conditional loss,
254 $\mathbb{E}[L(h(x), y)|r(x) = 0]$ at the desired rate (see proof of Theorem 2).

255 Next, we compare the quality of the predictions of our approach to that of simply predicting according
256 to the best-in-class as measured by the non-conditional loss, $h_b = \text{argmin}_{h \in \mathcal{H}} \mathbb{E}[L(h(x), y)]$. This
257 comparison quantifies the potential benefits of our framework as compared to that of supervised
258 learning since $h_b$ is the hypothesis that an algorithm in the supervised setting is attempting to learn.

259 In the next corollary, we consider the never-requester function, $r_\diamond$, that is $\mathbf{1}[r_\diamond(x) = 0] = 1$ for all
260 $x \in \mathcal{X}$. The never-requester is in $\mathcal{R}_\rho$ for any value of $\rho > 0$. The never-requester trivially does not
261 increase the label complexity and since it's a single function, it also does not discernibly augment the
262 complexity of class, $\mathcal{R}_\rho$, and so it can be included in $\mathcal{R}_\rho$ at effectively no cost.

263 **Corollary 1.** *Given any $\rho < \frac{1}{2}$, for any $\delta > 0$, with probability at least $1 - \delta$, for all $t \geq$*
264 $16 \log(3t/\delta)$, $\mathbb{E}[L(h_t(x), y)|r_t(x) = 0] \leq \mathbb{E}[L(h_b(x), y)] + \gamma + \tilde{O}\big(\sqrt{(1/t) \log(1/\delta)}\big)$, where $\gamma =$
265 $\mathbb{E}[L(h^*(x), y)|r^*(x) = 0] - \mathbb{E}[L(h_b(x), y)]$. *Furthermore, if $r_\diamond \in \mathcal{R}_\rho$, then $\gamma \leq 0$.*

266 The above corollary states the predictions of the chosen function $h_t$ when not requesting admit
267 strictly fewer mistakes as compared to the predictions of $h_b$, the best-in-class in $\mathcal{H}$, whenever
268 $\gamma < -\tilde{O}\big(\sqrt{(1/t) \log(1/\delta)}\big)$. The value $\gamma$ characterizes the difference between the best-in-class in
269 our setting versus the best-in-class in the supervised learning. The more negative this term is, the
270 fewer number of mistakes are made. In an empirical study in Appendix D, we show that typically $\gamma$
271 is significantly smaller than 0.

272 To derive label complexity guarantees, we define a disagreement coefficient for conditional
273 losses, directly derived from the coefficient definitions in [24, 7]. Let $\rho((h, r), (h', r')) =$
274 $\mathbb{E}\big[\big|\frac{L(h(x), y)\mathbf{1}[r(x)=0]}{\mathbb{E}[r(x)=0]} - \frac{L(h'(x), y)\mathbf{1}[r'(x)=0]}{\mathbb{E}[r'(x)=0]}\big|\big]$ be a measure of the distance between two pairs $(h, r)$

and $(h', r')$. Based on this metric, we define the ball around the best pair $(h^*, r^*)$ as follows: $B(h^*, r^*, \Lambda) = \{(h, r) \in \mathcal{H} \times \mathcal{R}_\rho : \rho((h, r), (h^*, r^*)) \leq \Lambda\}$. The disagreement coefficient is the infimum value of $\theta > 0$ such that for all $\Lambda \geq 0$: $\mathbb{E}\left[\max_{(h,r) \in B(h^*, r^*, \Lambda)} \max_y \left| \frac{L(h(x), y)\mathbf{1}[r(x) = 0]}{\mathbb{E}[r(x) = 0]} - \frac{L(h^*(x), y)\mathbf{1}[r^*(x) = 0]}{\mathbb{E}[r^*(x) = 0]} \right| \right] \leq \theta\Lambda$. The next theorem bounds the expected number of points requested needed to construct the estimates, $\hat{L}_t(h, r)$ in terms of the coefficient $\theta$.

**Theorem 3.** *Given any $\rho < \frac{1}{2}$, for all $\delta > 0$, with probability at least $1 - \delta$, $\sum_{s=1}^T \mathbb{E}[p_s(x_s)] = \tilde{O}(\theta\eta T + \theta\sqrt{T})$, where $\theta$ is the disagreement coefficient.*

Since the labeling rate of $r_t$ is at most $\rho$, the label complexity of the DPL-IWAL algorithm is then given by $\sum_{s=1}^T \mathbb{E}[r_s(x_s) = 1] + \mathbb{E}[p_s(x_s)] = \tilde{O}((\theta\eta + \rho)T + \theta\sqrt{T})$. Assume that $\mathbb{E}[L(h_t(x), y) \mid R_t(x) = 0] \leq \mathbb{E}[L(h_t(x), y) | r_t(x) = 0]$; intuitively, this implies using $q_t$ in addition to $r_t$ to make requests helps reduce our conditional loss and it holds in practice as shown by our experiments in Appendix D. Then it follows, by Theorem 2, that $\mathbb{E}[L(h_t(x), y) \mid R_t(x) = 0] \leq \eta + \tilde{O}(\sqrt{(1/t)\log(1/\delta)})$, i.e. with high probability failed rounds do not occur. Thus, in this case, DPL-IWAL exhibits an upper bound on the label complexity that matches the lower bound stated in the previous section, apart for $o(T)$ terms, namely $\sqrt{T}$. An even sharper bound for the $o(T)$ term is possible, using analysis similar to that of the EIWAL algorithm in [13], resulting in rate of $\sqrt{\eta T}$.

The analysis that proves the label complexity bound carefully deals with the denominator term of the estimates of the conditional loss as well as the fact that we are working with two function classes. Similarly to the generalization bound analysis, we first prove that the denominator term is well behaved and is not too far form its mean. Then, we leverage the disagreement coefficient $\theta$ and shrinking version space over the two classes.

In this paper, we analyzed the scenario where the requesting functions $r_t \in \mathcal{R}_\rho$ are constrained to request at most $\rho$ times and minimize the conditional loss over this set of requesters. One could instead consider a Lagrangian relaxation of this constraint and pay a fixed cost $c$ for each request. That is, consider the cost-based loss defined by $1_{r(x)=0}L(h(x), y) + c1_{r(x)=1}$. Both of these loss views are important and in fact have been analyzed in the abstention setting (e.g., see [20] for conditional loss and see [15] for cost-based loss). Despite focusing on conditional loss over constrained requester functions, the theory and algorithms in this paper can be extended to the cost-based loss. In particular, for the algorithm not to incur too many mistakes during training and to return a pair of function that generalized well, the algorithm must select $R_t$ outside of the class of requesters. The version of DPL-IWAL for cost-based loss will thus require requesting according to both $q_t$ and $r_t$.

# 6 Empirical Investigation

We start our empirical investigation by corroborating the theoretical insights made in the previous sections with an ablation study of DPL-IWAL. Since IWAL needs to solve a computationally intractable constrained optimization problem over its version space, which is only made more challenging in our setting by the joint optimization over $\mathcal{H} \times \mathcal{R}_\rho$, we use finite classes for these initial experiments. Then, we turn to a more practical algorithm inspired by the DPL-IWAL algorithm, but that leverages readily available optimization routines and empirically effective heuristics.

**Ablation Study:** We compare the performance of DPL-IWAL against baselines which ignore either the active learning and/or the abstention aspects of the dual purpose labeling, in order to demonstrate that indeed both aspects are necessary. To do so, we compare our algorithm to several variants, defined as follows. The *fully uniform* baseline simply decides to request a label using a random biased coin-flip independent of the example, thereby mimicking standard passive supervised learning. The *uniform $r_t$* baseline uses the DPL-IWAL algorithm in conjunction with trivial requester class that fixes its output uniformly at random, independent of the input $x_t$. The *uniform $q_t$* baseline is similar to DPL-IWAL, with outcomes $q_t$ determined by coin-flips with a fixed bias, independent of $x_t$.

For this experiment, we define a set of requester regions near the margin of the classification surface, each covering a mass $\rho$ of the overall distribution. Specifically, for any set of real-valued hypotheses set $\mathcal{H}$, where the classification of point $x$ made by $h \in \mathcal{H}$ is defined as $\text{sgn}(h(x))$, we define a margin-based requester function class as: $\mathcal{R}_{\rho, \mathcal{H}} = \{r_h(x) \mapsto \mathbf{1}[|h(x)| \leq \tau_{h,\rho}(\mathcal{D}_\mathcal{X})] : h \in \mathcal{H}\}$,

**DPL-Simplified Algorithm**

---

**Require:** Max iteration $T > 0$, classes $\mathcal{H} \times \mathcal{R}_\rho$
  **for** $t \in [1, T]$ **do**
    $h_t \leftarrow \operatorname{argmin}_{h \in \mathcal{H}} \sum_{s=1}^{t-1} q_s L(h(x_s), y_s)$
    $r_t \leftarrow \operatorname{argmin}_{r \in \mathcal{R}_\rho} \sum_{s=1}^{t-1} q_s \frac{L(h_t(x_s), y_s)\mathbf{1}[r(x_s)=0]}{\frac{1}{s-1}\sum_{s'=1}^{s-1}\mathbf{1}[r(x_{s'})=0]}$
    Receive $x_t$
    **if** $r_t(x_t) = 1$ **then** $q_t \leftarrow 1$, request label $y_t$
    **else** $q_t \leftarrow 0$, predict label using $\operatorname{sgn}(h_t(x_t))$
  **Return:** $(h_T, r_T)$

$\vdash$ DPL    $\vdash$ uniform $r_t$    $\vdash$ uniform $q_t$    $\vdash$ fully uniform

Figure 1: On the left, the number of online mistakes made while processing a stream of data and the held-out conditional loss on non-requested points made by DPL-IWAL and baselines comparators. The plots show the mean and standard deviation over 10 trials. On the right, the pseudo-code of DPL-Simplified Algorithm.

325   where $\mathcal{D}_{\mathcal{X}}$ is marginal distribution on $\mathcal{X}$ and $\tau_{h,\rho}(\mathcal{D}_{\mathcal{X}})$ is the largest threshold value that satisfies
326   $\mathbb{E}_{\mathcal{D}_{\mathcal{X}}}[r_h(x) = 1] \le \rho$. Note, the $\tau_{h,\rho}$ threshold can be estimated using unlabeled data.

327   We test six publicly available datasets [8] and for each, we use linear logistic regression models
328   trained using the Python `scikit-learn` library. For all datasets, we construct a finite hypothesis
329   class $\mathcal{H}$ and a matching finite margin-based requester set $\mathcal{R}_{\rho,\mathcal{H}}$. We then stream unlabeled examples
330   to each algorithm by sampling without replacement from a training split. The process is repeated 10
331   times, using a different random train/test split for each trial. For details, see Appendix D.

332   In Figure 1 (left), we compare each method using two metrics. First, we consider the number of
333   incorrect predictions (i.e. "online mistakes") that the model makes while processing the stream
334   of unlabeled training data, where label-requests are spared mistakes. Second, we consider the
335   conditional loss of the currently selected pair $(h_t, r_t)$ by measuring the average misclassification loss
336   on non-requested points using a held-out test split. See Appendix D for our results on all datasets,
337   which all show a similar pattern.

338   Overall these results show that our DPL-IWAL algorithm, with both a non-trivial sampling function
339   $q_t$ and requesting function $r_t$, outperforms all baseline methods. This indicates that both active
340   learning and abstention aspects of DPL-IWAL are necessary since naively applying an active learning
341   algorithm without abstention (e.g. uniform $r_t$) or naively applying an abstention algorithm without
342   active learning (e.g. uniform $q_t$) admit suboptimal results.

343   **DPL-Simplified Algorithm:** Here, we consider the DPL-Simplified Algorithm (Figure 1 right)
344   where, the joint optimization problem over $\mathcal{H} \times R_\rho$ is split into two separate optimizations. This
345   piece-wise optimization may not arrive at the same solution as the joint optimization, but we find it
346   to be an empirically effective proxy. The first optimization over $\mathcal{H}$ is a standard learning problem
347   over the currently labeled examples and any off-the-shelf hypothesis class and training algorithm
348   can be used. The second optimization over $\mathcal{R}_\rho$ is still non-trivial to solve. However, the objective
349   does provide the intuition that an optimal requester seeks to cover all of classifier $h_t$'s mistakes. This
350   suggests an approximate solution, where we train a requester $r$ that seeks to classify the incorrect
351   predictions of a fixed hypothesis $h_t$ over the set of labeled examples thus far. At the same time, notice
352   that the simplified algorithm fixes $q_t = r_t(x_t)$ (and no longer needs to solve IWAL's constrained
353   optimization problem). This makes the requester function responsible for not just sampling regions of
354   the space that $\mathcal{H}$ cannot correctly capture, but also sampling examples that are effective for training.

355   To cover the regions where the classifier is incorrect, we leverage what we call a **KNN-Requester**
356   function. In particular, we use scikit-learn's `KNeighborsClassifier` to train a non-parametric
357   model to predict hypothesis $h_t$'s training mistakes. The resulting requester is $r_{\text{KNN},h,\rho}(x) =$
358   $\mathbf{1}[|1 - \Pr_\theta(h(x) \ne y|x)| < \tau_\theta]$, where $\Pr_\theta(h(x) \ne y|x)$ denotes the probability that $h$ makes a
359   mistake according to the KNN model and $\rho$ indicates the classifier's threshold $\tau_\theta$ has been tuned
360   so that the requester labels approximately a $\rho$ fraction examples. To select points that are effective
361   for training the classifier, we borrow intuition from the simple yet empirically very effective *margin*
362   (or *uncertainty*) active learning algorithm, which samples examples that the current model is least
363   confident on (i.e., example closest to the decision surface).

364   This leads us to the **Mixture-Requester** (**MIX**) function which merges the margin and KNN
365   strategies. Specifically, we uniformly combine the probability score produced by the KNN model

| dataset | # Online Mistakes | | | Conditional Test Error (%) | | |
|---|---|---|---|---|---|---|
| | KNN | MAR | MIX | KNN | MAR | MIX |
| a9a | $2017 \pm 35$ | $\mathbf{1531 \pm 44}$ | $1713 \pm 51$ | $12.1 \pm 0.39$ | $\mathbf{8.9 \pm 0.44}$ | $10.3 \pm 0.30$ |
| acoustic | $1654 \pm 58$ | $\mathbf{1458 \pm 52}$ | $1418 \pm 51$ | $9.4 \pm 0.35$ | $8.1 \pm 0.13$ | $\mathbf{7.8 \pm 0.28}$ |
| cifar | $904 \pm 30$ | $849 \pm 38$ | $\mathbf{701 \pm 26}$ | $5.0 \pm 0.23$ | $5.1 \pm 0.14$ | $\mathbf{3.8 \pm 0.09}$ |
| cod-rna | $644 \pm 27$ | $360 \pm 13$ | $\mathbf{329 \pm 12}$ | $3.1 \pm 0.11$ | $2.2 \pm 0.06$ | $\mathbf{1.5 \pm 0.07}$ |
| covtype | $3471 \pm 89$ | $3365 \pm 89$ | $3318 \pm 78$ | $18.6 \pm 0.30$ | $19.3 \pm 0.18$ | $\mathbf{17.9 \pm 0.28}$ |
| HIGGS | $5862 \pm 79$ | $\mathbf{5500 \pm 90}$ | $5689 \pm 69$ | $35.2 \pm 0.31$ | $\mathbf{32.7 \pm 0.25}$ | $34.0 \pm 0.27$ |
| ijcnn | $654 \pm 52$ | $420 \pm 20$ | $\mathbf{310 \pm 30}$ | $2.2 \pm 0.28$ | $2.4 \pm 0.16$ | $\mathbf{0.7 \pm 0.14}$ |
| mnist | $1489 \pm 69$ | $1032 \pm 26$ | $\mathbf{958 \pm 50}$ | $6.7 \pm 0.31$ | $5.1 \pm 0.09$ | $\mathbf{4.1 \pm 0.12}$ |
| shuttle | $\mathbf{29 \pm 16}$ | $122 \pm 27$ | $\mathbf{21 \pm 8}$ | $\mathbf{0.1 \pm 0.05}$ | $0.8 \pm 0.09$ | $\mathbf{0.1 \pm 0.05}$ |
| skin | $\mathbf{61 \pm 64}$ | $662 \pm 110$ | $\mathbf{36 \pm 31}$ | $0.1 \pm 0.02$ | $4.0 \pm 0.89$ | $\mathbf{0.02 \pm 0.01}$ |

Figure 2: The left side of the table displays the mean and standard deviation over 10 trials of the number of total online mistakes after processing 20,000 examples for each of the requestor strategies (all limited to requesting labels for 20% of examples). The right side of the table shows the mean and standard deviation of the conditional misclassification loss $\Pr(h(x) \neq y | r(x) = 0)$, measured on the test set, for $(h_T, r_T)$. On the right, histograms show the number of errors made by a partially-trained linear hypothesis $h$ as a function of the model confidence for two datasets.

underlying $r_{\text{KNN},h,\rho}$ and the margin score derived from $h_t(x)$ as follows: $r_{\text{MIX},h,\rho}(x) = \mathbf{1}[|1 - \Pr_\theta(h(x) \neq y|x)| + |\sigma(h(x)) - 0.5| < \tau_{h,\theta}]$, where $\sigma$ is a normalizing function that maps the input into $[0, 1]$, which in our case is the output of scikit-learn's `predict_proba` method. Thus, this requester seeks to sample points that are both covering mistakes of the classifier as well as sampling points that are effective for training.

In addition to the above, we evaluate the simpler **Margin-Requester** to serve as a natural, yet effective baseline: $r_{\text{MAR},h,\rho}(x) = \mathbf{1}[|\sigma(h(x)) - 0.5| < \tau_{h,\theta}]$. This requester is essentially mimicking the behavior of using uncertainty-based active learning without any regard to the DPL setting.

In the following experiments, the hypothesis class $\mathcal{H}$ is the set of linear models with bounded $L_2$-norm, trained using scikit-learn's `LogisticRegression` implementation, and we use 10 publicly available datasets, all which we cast as binary classification problems (see Appendix D for details). We execute a batch variant of DPL-Simplified, where at each iteration we process a batch of 5,000 examples, querying 20% of the examples for their labels and making prediction for the rest. Upon the completion of the iteration, we receive the requested labels and update the choice of $(h, r)$. This larger batch size, more closely reflects practical learning settings, where it is impractical to re-train the model after every single label query [1]. All methods are seeded with 500 randomly sampled initial examples and each experiment is run for 10 trials.

In Figure 2, we show both the number of online errors incurred during the iterative labeling/training procedure as well as the average conditional misclassification loss of the final $(h, r)$ pair on a test set. In Appendix D, we plot the full learning curves in Figure 8 associated with Figure 2. Overall, MIX is very effective, outperforming the baseline methods in 8 out of 10 datasets. To better understand when MIX outperforms the margin-requester, we present a histogram of errors as a function the confidence of a model trained with a set of 3,500 examples sampled uniformly at random (Figure 2 right). The histogram for the HIGGS dataset, where the margin baseline performs well, shows that most of the errors are highly concentrated around the minimum model certainty region, i.e. where the model prediction score is close to $0.5$. In contrast, the histogram for cod-rna, where the DPL-inspired mixture-requester excels, shows that while there are some errors concentrated around the 0.5 threshold, there are also a number of errors far away from the model decision boundary.

# 7 Conclusion

We introduced a new setting which models the relationship between labeling and learning in real systems. We derived a lower bound in terms of the abstention-rate of a reference class and the optimum value of our objective. We presented an algorithm DPL-IWAL that admits strong generalization and label complexity guarantees and a more efficient variant, DPL-Simplified. Finally, we reported experiments which corroborate our theoretical findings and demonstrate that our algorithm outperforms natural baselines, including the ubiquitous margin sampling algorithm.

# References

[1] Kareem Amin, Corinna Cortes, Giulia DeSalvo, and Afshin Rostamizadeh. Understanding the effects of batching in online active learning. In *The 23nd International Conference on Artificial Intelligence and Statistics*, 2020.

[2] Pranjal Awasthi, Maria-Florina Balcan, Nika Haghtalab, and Ruth Urner. Efficient learning of linear separators under bounded noise. In *Conference on Learning Theory*, pages 167–190, 2015.

[3] Pranjal Awasthi, Maria-Florina Balcan, and Philip M. Long. The power of localization for efficiently learning linear separators with noise. In *Proceedings of the forty-sixth annual ACM symposium on theory of computing*, pages 449–458. ACM, 2014.

[4] Maria-Florina Balcan, Andrei Broder, and Tong Zhang. Margin based active learning. In *Proceeedings of COLT*, pages 35–50. Springer, 2007.

[5] Maria-Florina Balcan and Phil M. Long. Active and passive learning of linear separators under log-concave distributions. In *Conference on Learning Theory*, pages 288–316, 2013.

[6] Peter Bartlett and Marten Wegkamp. Classification with a reject option using a hinge loss. *JMLR*, pages 291–307, 2008.

[7] Alina Beygelzimer, Sanjoy Dasgupta, and John Langford. Importance weighted active learning. In *Proceedings of the 26th International Conference on Machine Learning*, pages 49–56. ACM, 2009.

[8] Chih-Chung Chang and Chih-Jen Lin. Libsvm. https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/. Accessed: 2021-05-28.

[9] C.K. Chow. An optimum character recognition system using decision function. *IEEE T. C.*, 1957.

[10] C.K. Chow. On optimum recognition error and reject trade-off. *IEEE T. C.*, 1970.

[11] Galen Chuang, Giulia DeSalvo, Lazarus Karydas, Jean-francois Kagy, Afshin Rostamizadeh, and A Theeraphol. Active learning empirical study. In *NeurIPS2019 LIRE Workshop*, 2019.

[12] David Cohn, Les Atlas, and Richard Ladner. Improving generalization with active learning. *Machine Learning*, 15(2):201–221, 1994.

[13] Corinna Cortes, Giulia DeSalvo, Claudio Gentile, Mehryar Mohri, and Ningshan Zhang. Region-based active learning. In *International Conference on Artificial Intelligence and Statistics*, 2019.

[14] Corinna Cortes, Giulia DeSalvo, and Mehryar Mohri. Boosting with abstention. In *NIPS*. MIT Press, 2016.

[15] Corinna Cortes, Giulia DeSalvo, and Mehryar Mohri. Learning with rejection. In *ALT*, pages 67–82. Springer, Heidelberg, Germany, 2016.

[16] Corinna Cortes, Giulia DeSalvo, and Mehryar Mohri. Online learning with abstention. In *ICML*, 2018.

[17] Ido Dagan and Sean P Engelson. Committee-based sampling for training probabilistic classifiers. In *Machine Learning Proceedings 1995*, pages 150–157. Elsevier, 1995.

[18] Sanjoy Dasgupta, Daniel J. Hsu, and Claire Monteleoni. A general agnostic active learning algorithm. In *Advances in Neural Information Processing Systems*, pages 353–360, 2008.

[19] Sanjoy Dasgupta, Adam Tauman Kalai, and Claire Monteleoni. Analysis of perceptron-based active learning. In *Conference on Learning Theory*, pages 249–263. Springer Berlin Heidelberg, 2005.

[20] Ran El-Yaniv and Yair Wiener. On the foundations of noise-free selective classification. *JMLR*, 2010.

[21] Ran El-Yaniv and Yair Wiener. Agnostic selective classification. In *NIPS*, 2011.

[22] Ran El-Yaniv and Yair Wiener. Active learning via perfect selective classification. In *JMLR*, 2012.

[23] Yves Grandvalet, Joseph Keshet, Alain Rakotomamonjy, and Stephane Canu. Suppport vector machines with a reject option. In *NIPS*, 2008.

[24] Stephen Henneke. A bound on the label complexity of agnostic active learning. In *ICML*, 2007.

[25] Boshuang Huang, Sudeep Salgia, and Qing Zhao. Disagreement-based active learning in online settings. *arXiv preprint arXiv:1904.09056*, 2019.

[26] David Lewis and William Gale. A sequential algorithm for training text classifiers. In *Proceedings of SIGIR*, 1994.

[27] Stephen Mussmann and Percy Liang. Uncertainty sampling is preconditioned stochastic gradient descent on zero-one loss. In *Proceedings of NeurIPS*, 2018.

[28] Shubhanshu Shekhar, Mohammad Ghavamzadeh, and Tara Javidi. Active learning for classification with abstention. *IEEE Journal on Selected Areas in Information Theory*, 2021.

[29] Yazhou Yang and Marco Loog. A benchmark and comparison of active learning for logistic regression. In *arXivpreprint arXiv:1611.08618*, 2016.

[30] Ming Yuan and Marten Wegkamp. Classification methods with reject option based on convex risk minimizations. In *Journal of Machine Learning Research*, 2010.

[31] Ming Yuang and Marten Wegkamp. Support vector machines with a reject option. In *Bernoulli*, 2011.

[32] Chicheng Zhang. Efficient active learning of sparse halfspaces. In *Conference on Learning Theory*, 2018.

[33] Chicheng Zhang and Kamalika Chaudhuri. Beyond disagreement-based agnostic active learning. In *Advances in Neural Information Processing Systems*, pages 442–450, 2014.

[34] Chicheng Zhang, Jie Shen, and Pranjal Awasthi. Efficient active learning of sparse halfspaces with arbitrary bounded noise. *Advances in Neural Information Processing Systems*, 33, 2020.