NETWORK INSENSITIVITY TO PARAMETER NOISE VIA PARAMETER ATTACK DURING TRAINING

ABSTRACT

Neuromorphic neural network processors, in the form of compute-in-memory cross-bar arrays of memristors, or in the form of subthreshold analog and mixed-signal ASICs, promise enormous advantages in compute density and energy efficiency for NN-based ML tasks. However, these technologies are prone to computational non-idealities, due to process variation and intrinsic device physics. This degrades the task performance of networks deployed to the processor, by introducing parameter noise into the deployed model. While it is possible to calibrate each device, or train networks individually for each processor, these approaches are expensive and impractical for commercial deployment. Alternative methods are therefore needed to train networks that are inherently robust against parameter variation, as a consequence of network architecture and parameters. We present a new network training algorithm that attacks network parameters during training, and promotes robust performance during inference in the face of random parameter variation. Our approach introduces a loss regularization term that penalizes the susceptibility of a network to weight perturbation. We compare against previous approaches for producing parameter insensitivity such as dropout, weight smoothing and introducing parameter noise during training. We show that our approach produces models that are more robust to random mismatch-induced parameter variation as well as to targeted parameter variation. Our approach finds minima in flatter locations in the weight-loss landscape compared with other approaches, highlighting that the networks found by our technique are less sensitive to parameter perturbation. Our work provides an approach to deploy neural network architectures to inference devices that suffer from computational non-idealities, with minimal loss of performance. This method will enable deployment at scale to novel energy-efficient computational substrates, promoting cheaper and more prevalent edge inference.

1 INTRODUCTION

There is increasing interest in NN and ML inference on IoT and embedded devices, which imposes energy constraints due to small battery capacity and untethered operation. Existing edge inference solutions based on CPUs or vector processing engines such as GPUs or TPUs are improving in energy efficiency, but still entail considerable energy cost (Huang et al., 2009). Alternative compute architectures such as memristor crossbar arrays and mixed-signal event-driven neural network accelerators promise significantly reduced energy consumption for edge inference tasks. Novel non-volatile memory technologies such as resistive RAM and phase-change materials (Chen, 2016; Yu & Chen, 2016) promise increased memory density with multiple bits per memory cell, as well as compact compute-in-memory for NN inference tasks (Verma et al., 2019). Analog implementations of neurons and synapses, coupled with asynchronous digital routing fabrics, permit high sparsity in both network architecture and activity, thereby reducing energy costs associated with computation.

However, both of these novel compute fabrics introduce complexity in the form of computational non-idealities, which do not exist for pure synchronous digital solutions. Some novel memory technologies support several bits per memory cell, but with uncertainty about the precise value stored on each cycle (Le Gallo et al., 2018; Wu et al., 2019). Others exhibit significant drift in stored states (Joshi et al., 2020). Inference processors based on analog and mixed-signal devices (Neckar et al., 2019; Moradi et al., 2018; Cassidy et al., 2016; Schemmel et al., 2010) exhibit parameter variation across the surface of a chip, and between chips, due to manufacturing process non-idealities.

Collectively these processes known as "device mismatch" manifest as frozen parameter noise in weights and neuron parameters.

In all cases the mismatch between configured and implemented network parameters degrades the task performance by modifying the resulting mapping between input and output. Existing solutions for deploying networks to inference devices that exhibit mismatch mostly focus on per-device calibration or re-training (Ambrogio et al., 2018; Bauer et al., 2019; Nandakumar et al., 2020). However, this, and other approaches such as few-shot learning or meta learning entail significant per-device handling costs, making them unfit for commercial deployment.

We consider a network to be "robust" if the output of a network to a given input does not change in the face of parameter perturbation. With this goal, network architectures that are intrinsically robust against device mismatch can be investigated (Thakur et al., 2018; Büchel et al., 2021). Another approach is to introduce parameter perturbations during training that promote robustness during inference, for example via random pruning (dropout) (Srivastava et al., 2014) or by injecting noise (Murray & Edwards, 1994; Joshi et al., 2020).

In this paper we introduce a novel solution, by applying adversarial training approaches to parameter mismatch. Most existing adversarial training methods attack the input space. Here we describe an adversarial attack during training that seeks the parameter perturbation that causes the maximum degradation in network response. In summary, we make the following contributions:

- We propose a novel algorithm for gradient-based supervised training of networks that are robust against parameter mismatch, by performing adversarial training in the weight space.

- We demonstrate that our algorithm flattens the weight-loss landscape and therefore leads to models that are inherently more robust to parameter noise.

- We show that our approach outperforms existing methods in terms of robustness.

2 RELATED WORK

Research to date has focused mainly on adversarial attacks in the input space. With an increasing number of adversarial attacks, an increasing number of schemes defending against those attacks have been proposed (Wang et al., 2020; Zhang et al., 2019; Madry et al., 2019; Moosavi-Dezfooli et al., 2018). In contrast, adversarial attacks in parameter space have received little attention. Where parameter-space adversaries have been examined, it has been to enhance performance in semi-supervised learning (Cicek & Soatto, 2019) or to improve robustness to *input-space* adversarial attacks (Wu et al., 2020).

We define "robustness" to mean that the network output should change only minimally in the face of a parameter perturbation — in other words, the weight-loss landscape should be as flat as possible at a loss minimum. Other algorithms that promote flat loss landscapes may therefore also be useful to promote robustness to parameter perturbations.

Dropout (Srivastava et al., 2014) is a widely used method to reduce overfitting. During training, a random subset of units are chosen with some probability, and these units are pruned from the network for a single trial or batch. This results in the network learning to distribute its computation across many units, and acts as a regularization against overfitting.

Entropy-SGD (Chaudhari et al., 2019) is a network optimisation method that minimises the local entropy around a solution in parameter space. This results in a smoothed parameter-loss landscape that should penalize sharp minima.

Adversarial Block Coordinate Descent (ABCD) (Cicek & Soatto, 2019) was proposed in order to complement input-space smoothing with weight-space smoothing in semi-supervised learning. ABCD repeatedly picks half of the network weights and performs one step of gradient ascent on them, followed by applying gradient descent on the other half.

Adversarial Weight Perturbation (AWP) (Wu et al., 2020) was designed to improve the robustness of a network to adversarial attacks in the input space. The authors use Projected Gradient Ascent (PGA) on the network parameters to approximate a worst case perturbation of the weights Θ'. PGA repeatedly computes the gradient of a loss function and updates the parameters in the direction of

the (positive) gradient. After each update, the parameters are projected back onto a ball (e.g. in l^2) around the original parameters to ensure that maximum distance is kept. Having identified an adversarial perturbation in the weight-space, an adversarial perturbation in the input-space is also found using PGA. Finally, the original weights Θ are updated using the gradient of the loss evaluated at the adversarial perturbation Θ'.

TRadeoff-inspired Adversarial DEfense via Surrogate-loss minimization (TRADES) (Zhang et al., 2019) is a method for training networks that are robust against adversarial examples in the input space. The method consists of adding a boundary loss term to the loss function that measures how the network performance changes when the input is attacked. The boundary loss does not take the labels into account, so scaling it by a factor β allows for a principled trade-off between the robustness and the accuracy of the network.

Noise injection during the forward pass (Murray & Edwards, 1994) is a simple method for increasing network robustness to parameter noise. This method adds Gaussian noise to the network parameters during the forward pass and computes weight gradients with respect to the original parameters. This method regularizes the gradient magnitudes of output units with respect to the weights, thus enforcing distributed information processing and insensitivity to parameter noise. We refer to this method as "Forward Noise".

3 METHODS

We use Θ to denote the set of parameters of a neural network $f(x, \Theta)$ that are trainable and susceptible to mismatch. The adversarial weights are denoted Θ^*, where Θ_t^* are the adversarial weights at the t-th iteration of PGA. We denote the PGA-adversary as a function $\mathcal{A}$ that maps parameters Θ to attacking parameters Θ^*. We denote a mini-batch of training examples as X with y being the corresponding ground-truth labels. $\prod_{\mathcal{E}_\zeta^p}(m)$ denotes the projection operator on the ζ-ellipsoid in l^p space. The operator $\odot$ denotes elementwise multiplication.

As shown in (Joshi et al., 2020), the effect of component mismatch on a network parameter can be modelled using a Gaussian distribution where the standard deviation depends linearly on the parameter magnitude. For complex Spiking Neural Networks (SNNs), "network parameters" can refer to additional quantities such as neuronal and synaptic time constants or spiking thresholds. Our training approach can be equally applied to these additional parameters. However, in this paper we restrict ourselves to perturbations in the network weights for simplicity.

We define the value of an individual parameter when deployed on a neuromorphic chip as

$$\Theta^{\text{mismatch}} \sim \mathcal{N}(\Theta, \text{diag}(\zeta|\Theta|)) \tag{1}$$

where ζ governs the perturbation magnitude, referred to as the "mismatch level". The physics underlying the neuronal- and synaptic circuits lead to a model where the amount of noise introduced into the system depends linearly on the magnitude of the parameters. If mismatch-induced perturbations had constant standard deviation independent of weight values, one could use the weight-scale invariance of neural networks as a means to achieve robustness, by simply scaling up all network weights (See Fig. S4). The linear dependence of weight magnitude and mismatch noise precludes this approach.

In contrast to adversarial attacks in the *input space* (Carlini & Wagner, 2016; Moosavi-Dezfooli et al., 2015; Madry et al., 2019; Goodfellow et al., 2015), our method relies on adversarial attacks in *parameter space*. During training, we approximate the worst case perturbation of the network parameters using PGA and update the network parameters in order to mitigate these attacks. To trade-off robustness and performance, we use a surrogate loss (Zhang et al., 2019) to capture the difference in output between the normal and attacked network. Algorithm 1 illustrates the training procedure in more detail.

Unlike adversarial training in the input space, where adversarial inputs can be seen as a form of data augmentation, adversarial training in the parameter space poses the following challenge: Because the parameters that are attacked are the same parameters being optimized, performing gradient descent using the same loss that was used for PGA would simply revert the previous updates and no learning would occur. ABCD circumvents this problem by masking one half of the parameters in the adversarial loop and masking the other half during the gradient descent step. However, this limits the adversary in its power, and requires multiple iterations to be performed in order to update

begin

$\quad \Theta_0^* \longleftarrow \Theta + |\Theta|\epsilon \odot R \,;\, R \sim \mathcal{N}(0, 1)$

$\quad$ **for** $t = 1$ **to** N_{steps} **do**

$\qquad g \longleftarrow \nabla_{\Theta_{t-1}^*} \mathcal{L}_{\text{Rob}}(f(\Theta, X), f(\Theta_{t-1}^*, X))$

$\qquad v \longleftarrow \arg\max\limits_{v:\|v\|_p \leq 1} v^T g$

$\qquad \Theta_t^* \leftarrow \prod_{\mathcal{E}_\zeta^p}(\Theta_{t-1}^* + \alpha \odot v)$

$\quad$ **end**

$\quad \Theta \longleftarrow \Theta - \eta\nabla_\Theta \mathcal{L}_{\text{Nat}}((\Theta, X), y) + \beta\mathcal{L}_{\text{Rob}}(\Theta, \Theta_{N_{\text{steps}}}^*, X)$

end

Algorithm 1: In l_∞, v corresponds to $\text{sign}(g)$ and the step size α is $\frac{|\Theta| \odot \zeta}{N_{\text{steps}}}$. $\prod_{\mathcal{E}_\zeta^p}(m)$ denotes the projection operator on the ζ-ellipsoid in l^p space. In l^∞ this corresponds to $\min(\max(m, \Theta - \epsilon), \Theta + \epsilon)$ with $\epsilon = \zeta \odot |\Theta|$.

all parameters at least once. AWP approached this problem by assuming that the gradient of the loss with respect to the attacking parameters can be used in order to update the original parameters to favor minima in flatter locations in weight-space. However, it is not clear whether this assumption always holds since the gradient of the loss with respect to the attacking parameters is not necessarily the same direction that would lead to a flatter region in the weight loss-landscape.

We approach this problem slightly differently: Similar to the TRADES algorithm (Zhang et al., 2019), our algorithm optimizes a natural (task) loss and a separate robustness loss.

$$\mathcal{L}_{\text{Gen}}(\Theta, X, y) = \mathcal{L}_{\text{Nat}}(\Theta, X, y) + \beta\mathcal{L}_{\text{Rob}}(\Theta, \mathcal{A}(\Theta), X)$$

Using a different loss for capturing the susceptibility of the network to adversarial attacks enables us to simultaneously optimise for performance and robustness, without PGA interfering with the gradient descent step. In our experiments, $\mathcal{L}_{\text{Rob}}$ is defined as

$$\mathcal{L}_{\text{Rob}}(\Theta, \mathcal{A}(\Theta), X) = \text{KL}\left(f(\Theta, X), f(\Theta^*, X)\right) \tag{2}$$

This formulation comes with a large computational overhead since it requires computing the Jacobian $\mathbf{J}_{\Theta^*}(\Theta)$ of a complex recurrent relation between Θ and Θ^*. To make our algorithm more efficient we assume that the Jacobian is diagonal, meaning that $\Theta^* = \Theta + \Delta\Theta$ for some $\Delta\Theta$ given by the adversary. In l_∞, the Jacobian can then be calculated efficiently using (see suppl. material for details):

$$\mathbf{J}_{\Theta^*}(\Theta) = \mathbf{I} + \text{diag}\left[\frac{\text{sign}(\Theta) \odot (\zeta + \epsilon \cdot R_1)}{N_{\text{steps}}} \odot \sum_{t=1}^{N_{\text{steps}}} \text{sign}\left(\nabla_{\Theta_t^*}\mathcal{L}_{\text{Rob}}(f(\Theta, X), f(\Theta_t^*, X))\right)\right]$$

By making this assumption, our algorithm effectively multiplies the original training time by the number of PGA steps, similar to (Wu et al., 2020; Cicek & Soatto, 2019).

Because component mismatch is independently proportional to the magnitude of each parameter, one has to model the space in which the adversary can search for a perturbation using an axis-aligned ellipsoid in l_2 and an axis-aligned box in l_∞. Using an ϵ-ball where the radius depends linearly on the individual parameter sets (Li et al., 2018; Cicek & Soatto, 2019; Wu et al., 2020) would either give the adversary too little or too much attack space. Projecting onto an axis-aligned ellipsoid in l_2 corresponds to solving the following optimization problem (Gabay & Mercier, 1976; Dai, 2006), which does not have a closed-form solution:

$$x^* = \arg\min_x \frac{1}{2}\|m - x\|_2$$
$$\text{s.t. } (x - c)^T W^{-2}(x - c) \leq 1$$

where $W = \text{diag}(|\Theta| \odot \zeta) + \mathbf{I} \cdot \zeta_{\text{const}}$, $c = \Theta$ and $m = \Theta^* + \alpha \odot v$. Because of the computational overhead this would incur, we only consider the l_∞ case in our experiments.

4 RESULTS

The ultra-low power consumption of mixed-signal neuromorphic chips make them suitable for edge-applications, such as always-on voice detection (Cho et al., 2019), vibration monitoring (Gies et al.,

Figure 1: **Our parameter attack is effective at decreasing the performance of a network during inference, and using our attack during training protects a network from later disruption.** (a) A network trained using standard SGD (i.e. $\beta_{\mathrm{rob}} = 0.0$) on the F-MNIST task is disrupted badly by the parameter noise adversary during inference ($\zeta = 0.1$; black curve). (b) When the same network is trained with parameter attacks during training ($\beta_{\mathrm{rob}} = 0.1$), the network is protected from parameter attacks during inference (high accuracy of attacked network; black curve). (c) When trained with standard SGD ($\beta_{\mathrm{rob}} = 0.0$), both random noise (red) and parameter attacks (black) disrupt network performance for increasing attack size ζ. (d) Under our training approach ($\beta_{\mathrm{rob}} = 0.1$), networks are significantly protected against random and adversarial weight perturbations during inference.

2021) or always-on face recognition (Liu et al., 2019). For this reason, we consider two compact network architectures in our experiments: A Spiking Recurrent Neural Network (SRNN) with roughly 65k trainable parameters and a conventional CNN with roughly 500k trainable parameters (see S1 for more information). We trained these models to perform three different tasks:

- Speech command detection of 6 classes (Warden, 2018);
- ECG-anomaly detection on 4 classes (Bauer et al., 2019); and
- Fashion-MNIST (F-MNIST): clothing-image classification on 10 classes (Xiao et al., 2017).

We compared several training and attack methods, beginning with a standard Stochastic Gradient Descent (SGD) approach using the Adam optimizer (Kingma & Ba, 2015) ("Standard"). Learning rate varied by architecture, but was kept constant when comparing training methods on an architecture. We examined networks trained with dropout (Srivastava et al., 2014), AWP (Wu et al., 2020), ABCD (Cicek & Soatto, 2019), and Entropy-SGD (Chaudhari et al., 2019). The adversarial perturbations used in AWP and ABCD were adapted to our mismatch model (i.e. magnitude-dependent in l_∞). We further adapted AWP so that the input data is never attacked.

Unless stated otherwise, a dropout probability of 0.3 was used in the dropout models; the regularization parameter β_{Rob} in our method was set to 0.25 and γ in AWP was set to 0.1. When Gaussian noise was applied to the weights during the forward pass (Murray & Edwards, 1994) a standard deviation of 0.3 was used. For Entropy-SGD, we set the number of inner iterations to 10 with a Langevin learning rate of 0.1. Because Entropy-SGD and ABCD have inner loops, the number of total epochs were reduced accordingly. All other models were trained for the same number of epochs (no early stopping) and the model with the highest validation accuracy was selected.

We trained 168 models in parallel on a CPU cluster, with each model requiring on average 12 hours of compute time on a single CPU with 16 cores and 32Gb RAM.

Figure 2: **Our training method flattens the test weight-loss landscape.** When moving away from the trained weight minimum ($\alpha = 0$) in randomly-chosen directions, we find that our adversarial training method (Beta; Beta+Forward) finds deeper minima (for F-MNIST and Speech tasks) at flatter locations in the cross-entropy test loss landscape. See text for further details, and Fig. S2 for visualisation over several random seeds.

Effectiveness of adversarial weight attack We examined the strength of our adversarial weight attack during inference and training. Standard networks trained using gradient descent alone with no additional regularization (Fig. 1a, "Standard") were disrupted badly by our adversarial attack during inference ($\zeta = 0.1$; final mean test accuracy $91.40\% \rightarrow 17.50\%$), and this was not ameliorated by further training. When our adversarial attack was implemented during training (Fig. 1a, $\beta_{\text{rob}} = 0.1$), the trained network was protected from disruption both during training and during inference (final test accuracy $91.97\% \rightarrow 78.41\%$).

Our adversarial attack degrades network performance significantly more than a random perturbation. Because our adversary uses PGA during the attack, it approximates a worst-case perturbation of the network within an ellipsoid around the nominal weights Θ. We compared the effect of our attack against a random weight perturbation (random point on $\zeta-$ellipsoid) of equal magnitude. For increasing perturbation size during inference (Fig. 1c; ζ), our adversarial attack disrupted the performance of the standard network significantly more than a random perturbation (test acc. $91.40\% \rightarrow 17.50\%$ (attack) vs. $91.40\% \rightarrow 90.63\%$ (random) for $\zeta = 0.1$). When our adversarial attack was applied during training (Fig. 1d; $\beta_{\text{rob}} = 0.1$), the network was protected against both random and adversarial attacks for magnitudes up to $\zeta = 0.7$ and $\zeta = 0.1$, respectively.

Flatness of the weight-loss landscape Under our definition of robustness, the network output should change only minimally when the network parameters are perturbed. This corresponds to a loss surface that is close to flat in weight space. We measured the test weight-loss landscape for trained networks, compared over alternative training methods and for several architectures (Fig. 2). We examined only cross-entropy loss (i.e. task loss) over the test set, and not the adversarial attack loss component (KL divergence loss; see Eq. 2). For each trained network, we chose a random vector $v \sim \mathcal{N}(\mathbf{0}, \zeta|\Theta|)$ and calculated $\mathcal{L}_{\text{Nat}}(f(X_{\text{test}}, \Theta + \alpha \cdot v), y_{\text{test}})$ for many evenly-spaced $\alpha \in [-2, 2]$. This process was repeated 5 times for $\zeta = 0.2$, and the means plotted in Fig. 2. Weight-loss landscapes for the individual trials are shown in Fig. S2.

Our adversarial training approach found minima of trained parameters Θ in flatter areas of the weight-loss landscape, compared with all other approaches examined (flatter curves in Fig. 2). In most cases our training approach also found deeper minima at lower $\mathcal{L}_{\text{cce}}$, reflecting better task performance. These results are reflected in the better generalization performance of our approach (see Table 1). Not surprisingly, dropout and AWP also lead to flatter minima than the Standard network with no regularization. ABCD and Entropy-SGD were not included in Fig. 2 because they did not outperform the Standard model.

Network robustness against parameter mismatch We evaluated the ability of our training method to protect against simulated device mismatch. We introduced frozen parameter noise into models trained with adversarial attack, with noise modelled on that observed in neuromorphic processors (Joshi et al., 2020; Büchel et al., 2021). In these devices, uncertainty associated with each weight parameter is approximately normally distributed around the nominal value, with a standard deviation that scales with the weight magnitude (Eq 1). We measured test accuracy under simulated

Figure 3: **Adversarial attack during training protects networks against random mismatch-induced parameter noise.** Networks were evaluated for the Speech (a), ECG (b) and F-MNIST tasks (c), under increasing levels of simulated mismatch (ζ). Networks trained using standard SGD were disrupted by mismatch levels $\zeta > 0.1$. At all mismatch levels our adversarial training approach performed significantly better in the presence of mismatch (higher test accuracy). Red boxes highlight misclassified examples.

Figure 4: **Our training method protects against task-adversarial attacks in parameter space.** Networks trained under several methods were attacked using a PGA adversary that directly attacked the task performance $\mathcal{L}_{cce}$. Our adversarial training approach (bold; dashed) outperformed all other methods against this attack.

random mismatch for 100 samples across two model instances. A comparison of our method against standard training is shown in Fig. 3. For mismatch levels up to 70% ($\zeta = 0.7$), our approach protected significantly against simulated mismatch for all three tasks examined ($p < 2 \times 10^{-8}$ in all cases; U test). A more detailed comparison between the different models is given in Table 1.

Network robustness against direct adversarial attack on task performance Our training approach improves network robustness against mismatch parameter noise. We further evaluated the robustness of our trained networks against a parameter adversary that directly attacks task performance, by performing PGA on the cross-entropy loss $\mathcal{L}_{Nat}$. Note that this is separate from the adversary used in our training method, which attacks the boundary loss (Eq.2). The AWP method uses the cross-entropy loss to find adversarial parameters during training. Nevertheless, we found that our method consistently outperforms all other compared methods for increasing attack magnitude ζ (Fig. 4). In networks trained with our method, the adversary needed to perform a considerably larger attack to significantly reduce performance (test accuracy $< 70\%$). ABCD and Entropy-SGD were not included in the comparison because they did not outperform the standard network.

Figure 5: **Networks trained with our method are provably more robust than those trained with standard gradient descent or forward noise alone.** We used interval bound propagation to determine the proportion of test samples that are verifiably correctly classified, under increasing weight perturbations ζ. For both the Speech and ECG tasks, computed on the trained SRNNs, our method was provably more robust for $\zeta < 5 \times 10^{-4}$.

Verifiable robustness for SRNNs   We investigated the provable robustness of SRNNs trained using our method using abstract interpretation (Cousot & Cousot, 1977; Gehr et al., 2018; Mirman et al., 2018). In this analysis a function $f(x, \Theta)$ (in our case, a neural network with input x and parameters Θ) is overapproximated using an *abstract domain*. We specify the weights Θ in our network as an interval parameterised by the attack size ζ, spanning $[\Theta - \zeta|\Theta|, \Theta + \zeta|\Theta|]$. Computations through the network are performed on these intervals rather than on discrete values. By propagating the intervals through a network over a test set, we obtain output logits that are also expressed as intervals. The final classification of the network is made using an $\arg\max$ operator. For provability of network performance, we consider that a test sample x is correctly classified when the lower bound of the logit interval for the correct class is the maximum lower bound across all logit intervals, and when the logit interval for the correct class is disjoint from the other logit intervals. When the logit interval for the correct class overlaps with another logit interval, that test sample is not considered to be provably correctly classified.

We examined the proportion of provably correctly classified test samples for the Speech and ECG tasks, under a range of attack sizes ζ, and comparing our approach against standard gradient descent and against training with forward-pass noise only (Fig. 5). We found that our approach is provably more correct over increasing attack size ζ (higher verified test accuracy). Note that interval domain analysis provides a relatively loose bound (Gehr et al., 2018), with the implication that the results here probably underestimate the true performance of our method.

5   DISCUSSION

We proposed a new training approach that includes adversarial attacks on the parameter space during training. Our attack disrupts the behaviour of a network by seeking a small weight perturbation that causes a maximal change in network output, by iteratively applying PGA. During training we jointly optimize a natural- and a robustness loss, where the robustness loss captures the susceptibility of the network to the adversarial attack. We evaluated our method on three tasks (F-MNIST; Speech-commands and ECG analysis), and measured the robustness of our approach against several forms of weight-space perturbation during inference. We compared our approach against several other training methods that could be expected to provide robustness against parameter perturbations.

Our proposed adversarial attack was significantly stronger than random weight perturbations at disrupting the performance of a trained network. Including the adversarial attack during training significantly protected the trained network from weight perturbations during inference. Our approach found minima in the weight-loss landscape that usually corresponded to lower loss values, and were always in flatter regions of the loss landscape. This indicates that our approach found network solutions that are less sensitive to parameter variation, and therefore more robust. Our approach was more robust than several other methods for inducing robustness and good generalisation.

Table 1: **Results of training multiple networks using several methods over three tasks.** Networks were evaluated under different levels of mismatch (ζ). The highest test performance in each row is in **bold**.

CNN

Mismatch	Forward Noise + Beta 0.1			Beta 0.25			Standard			Forward Noise			AWP			Dropout = 0.3		
	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.
Baseline (0.0)	91.88	**0.00**	91.88	92.11	0.22	91.89	91.30	0.15	91.15	92.00	0.02	91.98	92.35	0.12	**92.23**	**92.42**	0.24	92.18
0.1	91.77	0.12	91.29	91.59	0.26	90.91	90.45	0.37	88.80	91.94	**0.09**	91.69	**92.19**	0.16	**91.78**	91.13	0.85	86.50
0.2	**91.62**	**0.16**	**91.19**	90.67	0.42	89.28	87.93	1.03	83.40	**91.63**	**0.16**	91.06	91.42	0.44	89.87	88.71	1.55	80.97
0.3	**91.25**	**0.22**	**90.36**	89.64	0.65	87.10	82.70	2.45	71.99	91.01	0.26	90.01	89.88	0.95	85.11	84.94	3.06	72.97
0.5	**89.36**	**0.73**	**86.84**	85.96	1.87	76.28	61.14	6.92	42.46	87.82	0.88	84.37	82.59	3.66	66.73	71.74	5.84	53.10
0.7	**84.19**	**2.63**	**74.25**	79.39	4.40	59.15	36.93	7.73	20.17	78.48	2.95	69.67	65.38	8.27	40.66	53.91	9.03	22.49

ECG LSNN

Mismatch	Forward Noise + Beta 0.1			Beta 0.25			Standard			Forward Noise			AWP			Dropout = 0.3		
	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.
Baseline (0.0)	99.07	0.34	98.73	99.10	0.07	**99.03**	99.07	**0.04**	**99.03**	**99.25**	0.37	98.88	99.22	0.19	**99.03**	98.10	0.11	97.99
0.1	99.04	0.27	98.36	98.96	0.24	98.28	98.95	0.27	97.76	**99.09**	**0.19**	**98.66**	98.93	0.31	97.69	97.71	0.34	96.72
0.2	98.87	0.35	96.94	98.16	0.71	93.96	97.22	1.46	91.87	**99.01**	**0.26**	**98.06**	97.71	0.97	93.06	96.89	0.87	93.81
0.3	98.45	**0.45**	**96.49**	96.34	1.95	89.33	92.97	4.38	65.30	**98.59**	0.52	95.30	94.60	2.93	81.34	94.85	2.47	85.60
0.5	**94.86**	**2.69**	82.39	86.22	6.66	60.75	76.55	9.61	35.75	94.44	2.86	**82.84**	80.32	8.08	41.94	87.56	6.05	64.10
0.7	**82.02**	**8.40**	**50.22**	70.07	11.16	39.33	58.67	11.44	29.48	80.00	8.70	37.69	63.44	9.61	32.91	74.24	12.58	30.15

Speech LSNN

Mismatch	Forward Noise + Beta 0.5			Beta 0.5			Standard			Forward Noise			AWP			Dropout = 0.3		
	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.	Mean Acc.	Std.	Min.
Baseline (0.0)	81.52	0.05	81.47	**82.48**	**0.00**	**82.48**	80.86	0.03	80.83	81.33	0.14	81.20	81.35	0.12	81.23	79.02	0.36	78.66
0.1	81.33	0.24	80.72	**82.01**	0.31	**81.03**	79.72	0.45	78.53	81.12	0.32	80.18	80.85	0.38	79.71	79.16	0.44	77.88
0.2	80.77	0.35	79.71	**81.24**	0.43	**79.98**	76.96	1.11	72.57	80.10	0.53	78.73	79.24	0.66	77.54	78.58	0.67	75.85
0.3	79.57	0.62	**77.98**	**79.80**	0.67	77.54	72.31	2.00	65.40	78.05	0.88	75.45	76.35	1.23	70.04	77.18	0.96	74.43
0.5	72.67	2.75	**63.85**	**73.40**	2.32	60.91	57.16	4.25	42.07	67.41	3.93	53.50	63.50	4.18	45.92	69.80	3.13	54.75
0.7	58.03	6.57	32.19	**60.23**	**4.66**	**45.49**	40.70	5.72	24.92	49.19	6.98	30.47	45.96	5.61	22.56	55.96	5.74	37.74

To the best of our knowledge, our work represents the first example of interval bound propagation applied to SNNs, and the first application of parameter-space adversarial attacks to promote network robustness against device mismatch for mixed-signal compute.

Our experiments only considered the impact of weight perturbations, and did not examine the influence of uncertainty in other parameters of mixed-signal neuromorphic processors such as time constants or spiking thresholds. Our approach can be adapted to include adversarial attacks in the full network parameter space, increasing the robustness of spiking networks. The technique of interval bound propagation can also be applied to these additional network parameters.

We did not quantize network parameters either during or after training, in this work. This quantization step, ideally performed during training, is required to deploy networks to specialized neuromorphic inference hardware. It is not obvious how our adversarial attacks would interact with quantization during the training process.

Per-device training for a device with known calibrated parameter noise is likely to achieve the highest possible deployed performance on that single device. However, this approach has significant drawbacks. Firstly, each device must be either measured / calibrated accurately — not a trivial requirement — or trained with the device in the forward inference pass of the training loop. Secondly, training must be performed individually for each device, entailing significant logistical problems if the training is conducted in the factory or inside a consumer product. Thirdly, this approach will retain full sensitivity to parameter variation on the device. Parameter drift, which is a known issue for many memristive devices, would therefore degrade performance unless re-training is performed regularly on the deployed device. In contrast, our training approach provides a way to train once for deployment at scale, while being robust to both fabrication mismatch and parameter drift.

Our method improves the performance of neural networks deployed to inference hardware that include computational non-idealities. For example, NN processors with crossbar architectures based on novel memory devices such as RRAM and PCM memristors (Verma et al., 2019) display uncertainty in stored memory values as well as value drift over time (Le Gallo et al., 2018; Wu et al., 2019; Joshi et al., 2020). Analog neurons and synapses in mixed-signal NN processors, for example SNN inference processors (Moradi et al., 2018), exhibit variation in weights and neuron parameters across a processor.

We showed that our training approach finds network solutions that are insensitive to mismatch-induced parameter variation. Our networks can therefore be deployed to inference devices with computational non-idealities with only minimal reduction in task performance, and without requiring per-device calibration or model training. This reduction in per-device handling implies a considerable reduction in expense when deploying at commercial scale. Our method therefore brings low-power neuromorphic inference processors closer to commercial viability.

ETHICS STATEMENTS

The authors declare no conflicts of interest.

REPRODUCIBILITY STATEMENT

All code required to re-train the networks and reproduce all experiments described in this work are provided as supplementary material. Pre-trained networks and all data pre-processing is performed by code in supplementary material.

REFERENCES

Stefano Ambrogio, Pritish Narayanan, Hsinyu Tsai, Robert M. Shelby, Irem Boybat, Carmelo di Nolfo, Severin Sidler, Massimo Giordano, Martina Bodini, Nathan C. P. Farinha, Benjamin Killeen, Christina Cheng, Yassine Jaoudi, and Geoffrey W. Burr. Equivalent-accuracy accelerated neural-network training using analogue memory. *Nature*, 558(7708):60–67, June 2018. ISSN 1476-4687. doi: 10.1038/s41586-018-0180-5. URL https://doi.org/10.1038/s41586-018-0180-5.

F. C. Bauer, D. R. Muir, and G. Indiveri. Real-time ultra-low power ecg anomaly detection using an event-driven neuromorphic processor. *IEEE Transactions on Biomedical Circuits and Systems*, 13 (6):1575–1582, 2019. doi: 10.1109/TBCAS.2019.2953001.

Guillaume Bellec, Darjan Salaj, Anand Subramoney, Robert A. Legenstein, and Wolfgang Maass. Long short-term memory and learning-to-learn in networks of spiking neurons. *CoRR*, abs/1803.09574, 2018. URL http://arxiv.org/abs/1803.09574.

Julian Büchel, Dmitrii Zendrikov, Sergio Solinas, Giacomo Indiveri, and Dylan R. Muir. Supervised training of spiking neural networks for robust deployment on mixed-signal neuromorphic processors, 2021.

Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. *CoRR*, abs/1608.04644, 2016. URL http://arxiv.org/abs/1608.04644.

Andrew S. Cassidy, Jun Sawada, Paul Merolla, John V. Arthur, Rodrigo Alvarez-Icaza, Filipp Akopyan, Bryan L. Jackson, and Dharmendra S. Modha. Truenorth: A high-performance, low-power neurosynaptic processor for multi-sensory perception, action, and cognition. 2016.

Pratik Chaudhari, Anna Choromanska, Stefano Soatto, Yann LeCun, Carlo Baldassi, Christian Borgs, Jennifer Chayes, Levent Sagun, and Riccardo Zecchina. Entropy-SGD: biasing gradient descent into wide valleys. *Journal of Statistical Mechanics: Theory and Experiment*, 2019(12): 124018, dec 2019. doi: 10.1088/1742-5468/ab39d9. URL https://doi.org/10.1088%2F1742-5468%2Fab39d9.

An Chen. A review of emerging non-volatile memory (nvm) technologies and applications. *Solid-State Electronics*, 125:25–38, 2016. ISSN 0038-1101. doi: https://doi.org/10.1016/j.sse.2016.07.006. URL https://www.sciencedirect.com/science/article/pii/S0038110116300867. Extended papers selected from ESSDERC 2015.

Minchang Cho, Sechang Oh, Zhan Shi, Jongyup Lim, Yejoong Kim, Seokhyeon Jeong, Yu Chen, David Blaauw, Hun-Seok Kim, and Dennis Sylvester. 17.2 a 142nw voice and acoustic activity detection chip for mm-scale sensor nodes using time-interleaved mixer-based frequency scanning. In *2019 IEEE International Solid- State Circuits Conference - (ISSCC)*, pp. 278–280, 2019. doi: 10.1109/ISSCC.2019.8662540.

Safa Cicek and Stefano Soatto. Input and weight space smoothing for semi-supervised learning. In *2019 IEEE/CVF International Conference on Computer Vision Workshop (ICCVW)*, pp. 1344–1353, 2019. doi: 10.1109/ICCVW.2019.00170.

Patrick Cousot and Radhia Cousot. Abstract interpretation: A unified lattice model for static analysis of programs by construction or approximation of fixpoints. In *Proceedings of the 4th ACM SIGACT-SIGPLAN Symposium on Principles of Programming Languages*, POPL '77, pp. 238–252, New York, NY, USA, 1977. Association for Computing Machinery. ISBN 9781450373500. doi: 10.1145/512950.512973. URL https://doi.org/10.1145/512950.512973.

Yu-Hong Dai. Fast algorithms for projection on an ellipsoid. *SIAM Journal on Optimization*, 16(4):986–1006, 2006. doi: 10.1137/040613305. URL https://doi.org/10.1137/040613305.

Daniel Gabay and Bertrand Mercier. A dual algorithm for the solution of nonlinear variational problems via finite element approximation. *Computers & Mathematics with Applications*, 2(1): 17–40, 1976. ISSN 0898-1221. doi: https://doi.org/10.1016/0898-1221(76)90003-1. URL https://www.sciencedirect.com/science/article/pii/0898122176900031.

Timon Gehr, Matthew Mirman, Dana Drachsler-Cohen, Petar Tsankov, Swarat Chaudhuri, and Martin Vechev. Ai2: Safety and robustness certification of neural networks with abstract interpretation. In *2018 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18, 2018. doi: 10.1109/SP.2018.00058.

Valentin Gies, Sebastián Marzetti, Valentin Barchasz, Hervé Barthélemy, and Hervé Glotin. Ultra-low power embedded unsupervised learning smart sensor for industrial fault classificatio. In *2020 IEEE International Conference on Internet of Things and Intelligence System (IoTaIS)*, pp. 181–187, 2021. doi: 10.1109/IoTaIS50849.2021.9359716.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In Yee Whye Teh and Mike Titterington (eds.), *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pp. 249–256, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. JMLR Workshop and Conference Proceedings. URL http://proceedings.mlr.press/v9/glorot10a.html.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2015.

S. Huang, S. Xiao, and W. Feng. On the energy efficiency of graphics processing units for scientific computing. In *2009 IEEE International Symposium on Parallel Distributed Processing*, pp. 1–8, 2009. doi: 10.1109/IPDPS.2009.5160980.

Vinay Joshi, Manuel Le Gallo, Simon Haefeli, Irem Boybat, S. R. Nandakumar, Christophe Piveteau, Martino Dazzi, Bipin Rajendran, Abu Sebastian, and Evangelos Eleftheriou. Accurate deep neural network inference using computational phase-change memory. *Nature Communications*, 11(1):2473, May 2020. ISSN 2041-1723. doi: 10.1038/s41467-020-16108-9. URL https://doi.org/10.1038/s41467-020-16108-9.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Manuel Le Gallo, Abu Sebastian, Roland Mathis, Matteo Manica, Heiner Giefers, Tomas Tuma, Costas Bekas, Alessandro Curioni, and Evangelos Eleftheriou. Mixed-precision in-memory computing. *Nature Electronics*, 1(4):246–253, April 2018. ISSN 2520-1131. doi: 10.1038/s41928-018-0054-8. URL https://doi.org/10.1038/s41928-018-0054-8.

Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/a41b3bb3e6b050b6c9067c67f663b915-Paper.pdf.

Qian Liu, Ole Richter, Carsten Nielsen, Sadique Sheik, Giacomo Indiveri, and Ning Qiao. Live demonstration: Face recognition on an ultra-low power event-driven convolutional neural network asic. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pp. 1680–1681, 2019. doi: 10.1109/CVPRW.2019.00213.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks, 2019.

Matthew Mirman, Timon Gehr, and Martin T. Vechev. Differentiable abstract interpretation for provably robust neural networks. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 3575–3583. PMLR, 2018. URL http://proceedings.mlr.press/v80/mirman18b.html.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. *CoRR*, abs/1511.04599, 2015. URL http://arxiv.org/abs/1511.04599.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Jonathan Uesato, and Pascal Frossard. Robustness via curvature regularization, and vice versa. *CoRR*, abs/1811.09716, 2018. URL http://arxiv.org/abs/1811.09716.

S. Moradi, N. Qiao, F. Stefanini, and G. Indiveri. A scalable multicore architecture with heterogeneous memory structures for dynamic neuromorphic asynchronous processors (dynaps). *IEEE Transactions on Biomedical Circuits and Systems*, 12(1):106–122, 2018. doi: 10.1109/TBCAS.2017.2759700.

A.F. Murray and P.J. Edwards. Enhanced mlp performance and fault tolerance resulting from synaptic weight noise during training. *IEEE Transactions on Neural Networks*, 5(5):792–802, 1994. doi: 10.1109/72.317730.

S. R. Nandakumar, Manuel Le Gallo, Christophe Piveteau, Vinay Joshi, Giovanni Mariani, Irem Boybat, Geethan Karunaratne, Riduan Khaddam-Aljameh, Urs Egger, Anastasios Petropoulos, Theodore Antonakopoulos, Bipin Rajendran, Abu Sebastian, and Evangelos Eleftheriou. Mixed-precision deep learning based on computational memory. *Frontiers in Neuroscience*, 14:406, 2020. ISSN 1662-453X. doi: 10.3389/fnins.2020.00406. URL https://www.frontiersin.org/article/10.3389/fnins.2020.00406.

Alexander Neckar, Sam Fok, Ben Benjamin, Terrence Stewart, Aaron Voelker, Chris Eliasmith, Rajit Manohar, and Kwabena Boahen. Braindrop: A mixed-signal neuromorphic architecture with a dynamical systems-based programming model. *Proceedings of the IEEE*, 107:144–164, 01 2019. doi: 10.1109/JPROC.2018.2881432.

J. Schemmel, D. Brüderle, A. Grübl, M. Hock, K. Meier, and S. Millner. A wafer-scale neuromorphic hardware system for large-scale neural modeling. In *2010 IEEE International Symposium on Circuits and Systems (ISCAS)*, pp. 1947–1950, 2010. doi: 10.1109/ISCAS.2010.5536970.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15(56):1929–1958, 2014. URL http://jmlr.org/papers/v15/srivastava14a.html.

C. S. Thakur, R. Wang, T. J. Hamilton, R. Etienne-Cummings, J. Tapson, and A. van Schaik. An analogue neuromorphic co-processor that utilizes device mismatch for learning applications. *IEEE Transactions on Circuits and Systems I: Regular Papers*, 65(4):1174–1184, 2018.

Naveen Verma, Hongyang Jia, Hossein Valavi, Yinqi Tang, Murat Ozatay, Lung-Yen Chen, Bonan Zhang, and Peter Deaville. In-memory computing: Advances and prospects. *IEEE Solid-State Circuits Magazine*, 11(3):43–55, 2019. doi: 10.1109/MSSC.2019.2922889.

Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rklOg6EFwS.

P. Warden. Speech Commands: A Dataset for Limited-Vocabulary Speech Recognition. *ArXiv e-prints*, April 2018. URL https://arxiv.org/abs/1804.03209.

Dongxian Wu, Yisen Wang, and Shutao Xia. Revisiting loss landscape for adversarial robustness. *CoRR*, abs/2004.05884, 2020. URL https://arxiv.org/abs/2004.05884.

Lei Wu, Hongxia Liu, Jiabin Li, Shulong Wang, and Xing Wang. A Multi-level Memristor Based on Al-Doped HfO2 Thin Film. *Nanoscale Research Letters*, 14(1):177, May 2019. ISSN 1556-276X. doi: 10.1186/s11671-019-3015-x. URL https://doi.org/10.1186/s11671-019-3015-x.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

Shimeng Yu and Pai-Yu Chen. Emerging memory technologies: Recent trends and prospects. *IEEE Solid-State Circuits Magazine*, 8(2):43–56, Spring 2016. ISSN 1943-0590. doi: 10.1109/MSSC.2016.2546199.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically principled trade-off between robustness and accuracy. *CoRR*, abs/1901.08573, 2019. URL http://arxiv.org/abs/1901.08573.

SUPPLEMENTARY MATERIAL

SPIKING RNN ARCHITECTURE

The dynamics of the spiking model (Bellec et al., 2018) can be summarised by a set of differential equations (Eq. 3).

$$
\begin{aligned}
\boldsymbol{B}^t &= \boldsymbol{b}^0 + \beta \boldsymbol{b}^t \\
\boldsymbol{o}^t &= \mathbf{1}(\boldsymbol{V}^t > \boldsymbol{B}^t) \text{ unless refractory } t_{\text{refr}} \\
\boldsymbol{b}^{t+1} &= \boldsymbol{\rho}_\beta \boldsymbol{b}^t + (1 - \boldsymbol{\rho}_\beta) \frac{\boldsymbol{o}^t}{\mathrm{dt}} \\
\boldsymbol{I}_{\text{Reset}}^t &= \frac{\boldsymbol{o}^t}{\mathrm{dt}} \boldsymbol{B}^t \mathrm{dt} \\
\boldsymbol{V}^{t+1} &= \boldsymbol{\rho}_V \boldsymbol{V}^t + (1 - \boldsymbol{\rho}_V)(\boldsymbol{I}_{\text{in}} W_{\text{in}} + \frac{\boldsymbol{o}^t}{\mathrm{dt}} W_{\text{rec}}) - \boldsymbol{I}_{\text{Reset}}^t
\end{aligned}
\tag{3}
$$

where $\boldsymbol{\rho}_\beta = \mathrm{e}^{-\mathrm{dt}/\tau_{\text{ada}}}$ and $\boldsymbol{\rho}_V = \mathrm{e}^{-\mathrm{dt}/\tau}$. The variables $\boldsymbol{B}$ describe the spiking thresholds with spike-frequency adaptation. The vector $\boldsymbol{o}^t$ denotes the population spike train at time t. The membrane potentials $\boldsymbol{V}$ have a time constant τ and the adaptive threshold time constant is denoted by τ_{ada}. The speech signals and ECG traces fed into the network are represented as currents $\boldsymbol{I}_{\text{in}}$. Since the derivative of the spiking function with respect to its input is mostly 0 we use a surrogate gradient that is explicitly defined as

$$
\frac{\partial E}{\partial \boldsymbol{V}^t} = \frac{\partial E}{\partial \boldsymbol{z}^t} \frac{\partial \boldsymbol{z}^t}{\partial \boldsymbol{V}^t} = \frac{\partial E}{\partial \boldsymbol{z}^t} d \cdot \max(\mathbf{1} - |\frac{\boldsymbol{V}^t - \boldsymbol{B}^t}{\boldsymbol{B}^t}|, \mathbf{0})
\tag{4}
$$

where E is the error and d is the dampening factor. To get the final prediction of the network, we average the population spike trains along the time-axis $\boldsymbol{z}_{\text{avg}}$ and compute

$$
\begin{aligned}
\boldsymbol{l} &= \text{softmax}(\boldsymbol{z}_{\text{avg}} W_{\text{out}} + b_{\text{out}}) \\
\hat{y} &= \arg\max_i \boldsymbol{l}_i
\end{aligned}
$$

CNN ARCHITECTURE

Our architecture comprises two convolutional blocks ($2 \times [4 \times 4, 64$ channels, MaxPool, ReLU]), followed by three dense layers ($N = 1600, 256, 64$, ReLU) and a softmax layer. All weights and kernels are initialized using the Glorot normal initialisation (Glorot & Bengio, 2010). Using this architecture, we achieved a test accuracy of $\sim 93\%$. Attacked parameters for this network included all the kernel weights, as well as all the dense layer parameters.

DERIVATION OF JACOBIAN

Under the assumption that $\alpha = \frac{\zeta \odot |\Theta|}{N_{\text{steps}}}$ and $p = \infty$, we can rewrite the inner loop of Algorithm 1 to

begin

    $\Theta^* \longleftarrow \Theta + |\Theta|\epsilon \odot R \; ; R \sim \mathcal{N}(0,1)$

    for $t = 1$ **to** N_{steps} **do**

        $\Theta_t^* \leftarrow \Theta_{t-1}^* + \alpha \cdot \text{sign}\left(\nabla_{\Theta_{t-1}^*} \mathcal{L}_{\text{Rob}}(f(\Theta, X), f(\Theta_{t-1}^*, X))\right)$

    end

end

By rewriting Θ^* in the form of $\Theta^* = \Theta + \Delta\Theta$ we get

$$\Theta^* = \Theta + |\Theta|\epsilon \odot R + \alpha \odot \sum_{t=1}^{N_{\text{steps}}} \text{sign}\left(\nabla_{\Theta_{t-1}^*} \mathcal{L}_{\text{Rob}}(f(\Theta, X), f(\Theta_{t-1}^*, X))\right)$$

From this the Jacobian can be easily calculated. Plugging in the defintion for α we get

$$\mathbf{J}_{\Theta^*}(\Theta) = \mathbf{I} + \text{diag}\left[\frac{\text{sign}(\Theta) \odot (\zeta + \epsilon \cdot R_1)}{N_{\text{steps}}} \odot \sum_{t=1}^{N_{\text{steps}}} \text{sign}\left(\nabla_{\Theta_t^*} \mathcal{L}_{\text{Rob}}(f(\Theta, X), f(\Theta_t^*, X))\right)\right]$$

MISMATCH MODEL

To model the parameter noise introduced by component mismatch we used a Gaussian distribution where the mean is the nominal noise-free weight value and the standard deviation depends linearly on the weight value. This model realistically captures the behaviour of parameter mismatch on a mixed-signal neuromorphic SNN inference processor (Moradi et al., 2018). Fig. S1 shows the quantified parameter mismatch recorded directly from neuromorphic HW, over a range of nominal parameter values and for several neuronal and synaptic parameters. The measured mismatch parameter variation follows an approximately Gaussian distribution where the standard deviation depends linearly on the mean.

Figure S1: **Quantification of mismatch on analog neuromorphic hardware.** Parameter values for several weight parameters and membrane time constants were measured for a range of nominal parameter values, using an oscilloscope directly connected to a mixed-signal neuromorphic SNN processor. (**a-c**) Various parameters of the chip follow a Gaussian distribution with increasing width. (**d**) The mismatch standard deviation depends linearly on the nominal value of each parameter.

WEIGHT LOSS-LANDSCAPE VISUALIZATION

We characterized the shape of the weight loss-landscape by plotting the categorical cross entropy loss for varying levels of noise added to the weights of the trained network. In each trial, we picked a random vector $v \sim \mathcal{N}(\mathbf{0}, \zeta|\Theta|)$ and evaluated the categorical cross entropy of the whole test set given the weights $\Theta + \alpha \cdot v$, where $\alpha \in [-2, 2]$ and $\zeta = 0.2$. As we show in Figure S2, the variance of the individual 1D weight loss-landscapes is small.

Table S1 quantifies the flatness of the illustrated weight loss-landscapes. As can be seen, our method combined with adding noise during the forward pass yields the flattest landscapes.

Table S1: **Average slope of estimated 1D weight loss-landscapes.** Slopes were calculated as the mean absolute differences between sample points divided by the sampling distance.

	F-MNIST CNN	ECG SRNN	Speech SRNN
Standard	0.3375	0.1605	0.2702
Beta	0.0480	0.0879	0.0633
Forward Noise	0.0332	**0.0180**	0.1009
Forward Noise + Beta	**0.0190**	0.0187	**0.0540**
Dropout	0.3022	0.0952	0.0707
AWP	0.0841	0.1013	0.1389

Figure S2: **Illustration of the test weight loss-landscape highlighting individual trials to measure the loss landscapes.** See the results text for more details.

ATTACKING KL-DIVERGENCE LOSS DURING INFERENCE

While the adversary in AWP attacks the task loss directly, i.e. max $\mathcal{L}_{\text{cat. cross-entropy}}(f(\Theta^*, X), y)$, the adversary in our training algorithm attacks the KL divergence max $\text{KL}(f(\Theta, X), f(\Theta^*, X))$. This implies that our parameter attack seeks simply to change the response of the network in any way, and is agnostic to the task itself. In the main results we attack the cross-entropy task loss during inference, in order to not give an undue advantage to our training approach. Here we show that our training approach also provides robustness against parameter attack on the cross-entropy loss during inference.

Fig. S3 shows the adversarial robustness of the methods for an adversary that attacks the KL-divergence rather than the cross-entropy loss. When the network is attacked by maximizing the KL-divergence between the normal and attacked network, our adversarially-trained networks are more robust than AWP, SGD and forward-noise. Because the parameter attack used here during inference as well as in the inner optimization loop of the training procedure is the same, this result is expected, and serves as a sanity check that our networks indeed learn to defend against the attack they were trained against.

Figure S3: **Robustness to weight attack targeting KL divergence during inference.** When the network is attacked by maximizing the KL-divergence between the normal and attacked network, our adversarially trained networks are more robust than standard SGD or AWP.

EFFECT OF CONSTANT VERSUS RELATIVE PARAMETER NOISE

As described in the main text, parameter noise that has constant magnitude (for example, Gaussian noise with fixed standard deviation) is trivial to protect against by increasing weight magnitudes. We examined this effect by training MLPs with an adversary that employs Gaussian noise with fixed std. dev. $\epsilon = 0.2$. Figure S4 (right) illustrates the test accuracy of two MLPs trained on F-MNIST over the course of training. Using an inverse weight decay term, the weight-magnitude of one network is forced to increase to 2.0 over the course of training (black crosses, Θ^*). The weight magnitude of the other network (red crosses) is limited during training to 0.2 (red crosses; Θ). One can observe that as the weight magnitude of the increasing magnitude network Θ^* increases, also the robustness to Gaussian noise ($\epsilon = 0.2$) increases (blue), while the performance of the small magnitude network Θ remains poor (cyan).

Figure S4: **Constant magnitude versus magnitude-relative parameter noise.** (left, middle) When parameter noise of constant magnitude (blue) is introduced by the adversarial attack during training, the networks learn to increase the magnitude of the weights to trivially improve robustness to the constant-magnitude attack. When the parameter attack is relative to each parameter magnitude, as in the main text (red), the weight magnitudes do not increase. These networks were trained for a range of β_{rob}, i.e. varying emphasis on robustness.
(right) One can also trivially increase the robustness to fixed-magnitude noise by introducing an inverse weight decay term that causes the weights to increase in magnitude (black, cross marker) while retaining performance. This causes the MLP trained on MNIST to become increasingly robust to fixed-magnitude parameter noise (blue dots; ϵ-test acc., Θ^*). The network where the weight magnitude was not increased over time (red, cross marker) did not improve in terms of robustness (cyan; ϵ-test acc., Θ), although both models perform similarly when there is no parameter noise applied (red and black dots).

EFFECT OF VARYING β_{ROB}

We additionally quantify the trade-off between test loss and robustness of our algorithm by repeating the experiment in Figure 2 at different values of β_{rob}. As shown in Figure S5, increasing β_{rob} flattens the weight loss-landscape, effectively increasing the robustness of the model. To further substantiate this claim, we repeated the experiment of Figure 1 with the same values of β_{rob}. As Figure S7 shows, increasing β_{rob} and therefore increasing the flatness of the landscape yields increased robustness to random, as well as, adversarial perturbations.

We note that, relative to the baseline, the test loss does not consistently increase with increasing values of β_{rob}. We hypothesize that this is due to the increased generalization capability of our networks. To check whether this is indeed the case, we repeated the experiment from Fig. S5 using the loss computed on the training set. As Fig. S6 shows, increasing values of β_{rob} lead to flatter minima and higher loss on the training set, which is the exact trade-off to be expected from the formulation of our loss function. However, the increased generalization capability that follows from a flatter loss-landscape seems to disrupt this trade-off. As a result, when choosing β_{rob} one should aim at choosing the highest value that still yields good performance on the validation set.

Figure S5: **Effect of β_{rob} on the test loss landscape.** Increasing β_{rob} promotes robustness by flattening the test loss landscape. However, increasing β_{rob} does not lead to a systematic rise in loss on the test set.

Figure S6: **Effect of β_{rob} on the training loss landscape.** Weight loss landscape computed on the training set (c.f. Fig. S5). Increasing β_{rob} leads to flatter loss-landscapes (increased robustness) as before, but also a systematic increase in training loss (higher values for cross-entropy loss; note ordering of curves).

We additionally trained the CNN on the F-MNIST data for a range of β_{rob}, and measured the network robustness to attacks of varying magnitude ζ (Fig. S7). We compared the effectiveness of random attack versus adversarial attack during inference, evaluated on the test set. We found that increasing β_{rob} improved the robustness of the network to both random and adversarial attack during inference.

Figure S7: **Increasing β_{rob} during training improves robustness during inference.** The CNN was trained using different values of β_{rob} and evaluated on the test set after the weights were perturbed either randomly (red) or adversarially (black).

WIDE-MARGIN NETWORK ACTIVATIONS

Murray et al. show that adding random forward noise to the weights of a network during the forward pass implicitly adds a regularizer of the form $\Theta_{i,j}^2 \left(\frac{\partial o_{k,l}}{\partial \Theta_{i,j}} \right)^2$ to the network weights (Murray & Edwards, 1994). When sigmoid activation functions are used, this regularizer favors high or low activations. When implementing interval bound propagation for SRNNs, intervals over spiking activity must be computed by passing intervals through the spiking threshold function. As a result, intervals for spiking activity become either $[0, 0]$ for neurons that never emit a spike regardless of weight attack; $[1, 1]$ for neurons that always emit a spike; and $[0, 1]$ for neurons for which activity becomes uncertain in the presence of weight attack. By definition, a robust network should promote bounds $[0, 0]$ and $[1, 1]$, where the activity of the network is unchanged by weight attack. Robust network configurations should therefore avoid states where the membrane potentials of neurons are close to the firing threshold.

To see whether this was also the case for our SRNNs, we investigated the distribution of the membrane potentials on a batch of test examples for a network that was trained with- and without noise during the forward pass. We found that robust networks exhibited a broader distribution of membrane potentials, with comparatively less distribution mass close to the firing threshold (Fig. S8). This indicates that neurons in the robust network spend more time in a "safe" regime where a small change in the weights cannot trigger an unwanted spike, or remove a desired spike.

Figure S8: **Membrane potentials are distributed away from the firing threshold for networks trained with forward noise.** We measured the distribution of membrane potentials in SRNNs trained using standard gradient descent ("Standard"), and in the presence of weight noise injected in the forward pass ("Forward Noise + Beta"). As predicted, networks trained with forward noise have membrane potentials distributed away from the firing threshold. This implies that weight perturbations are less likely to inject or delete a spike erroneously, improving the robustness of the network.