Composite Feature Selection Using Deep Ensembles

Abstract

In many real world problems, features do not act alone but in combination with each other. For example, in genomics, diseases might not be caused by any single mutation but require the presence of multiple mutations. Prior work on feature selection either seeks to identify individual features or can only determine relevant groups from a predefined set. We investigate the problem of discovering groups of predictive features without predefined grouping. To do so, we define predictive groups in terms of linear and non-linear interactions between features. We introduce a novel deep learning architecture that uses an ensemble of feature selection models to find predictive groups, without requiring candidate groups to be provided. The selected groups are sparse and exhibit minimum overlap. Furthermore, we propose a new metric to measure similarity between discovered groups and the ground truth. We test our model on multiple synthetic tasks, semi-synthetic chemistry datasets and image datasets to demonstrate its utility.

1 Introduction

Feature selection is a key problem permeating statistics, machine learning and broader science. Typically in high-dimensional datasets, the majority of features will not be responsible for the target response and thus an important goal is to identify which variables are truly predictive. For example, in healthcare there may be many features (such as age, sex, medical history, etc.) that could be considered, while only a small subset might in fact be relevant for predicting the likelihood of developing a specific disease. By eliminating irrelevant variables, feature selection algorithms can be used to drive discovery, improve model generalisation/robustness, and improve interpretability [16].

However, features often do not act alone but instead in *combination*. In genetics, for instance, it has been noted that understanding the origins of many diseases may require methods able to identify more complex genetic models than single variants [57]. While feature selection might be able to identify a set of features associated with a particular response, the underlying structure of how features interact is not captured. Further, the resulting predictive models can be complex, hard to interpret, and not amenable to the generation of hypotheses that can be experimentally tested [41]. This limits the impact such models can have in furthering scientific understanding across many domains where variables are known to interact, such as genetics [57, 61, 54], medicine [79, 11], and economics [7].

Group feature selection is a generalisation of standard feature selection, where instead of selecting individual features, groups of features are either entirely chosen or entirely excluded. A primary application of group feature selection is when features are jointly measured, for example by different instruments. In such scenarios, groups are readily defined as features measured by the same instrument. A natural question is which instruments give the most meaningful measurements. Group feature selection has also been applied in situations where there is extensive domain knowledge regarding the

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

group structure [64] or where groups are defined by the correlation structure between features (e.g. neighbouring pixels in images are highly correlated). The pervasive issue with current group feature selection methods is that a predetermined grouping *must* be provided, and the groups are selected from the given candidates. In reality, we may not know how to group the variables.

In this paper we seek to solve a related but ultimately different and more challenging problem, which we call *Composite Feature Selection*. We wish to find groups of variables *without* prior knowledge, where each group acts as a separate predictive subset of the features and the overall predictive power is greatest when all groups are used in unison. We call each group of features a composite feature.[1] By imposing this structure on the discovered features, we attempt to isolate pathways from features to the response variable. Discovering *groups* of features offers deeper insights into *why* specific features are important than standard feature selection.

Contributions. (1) We formalise *composite* feature selection as an extension of standard feature selection, defining composite features in terms of linear and non-linear interactions between variables (Sec. 3). (2) We propose a new deep learning architecture for composite feature selection using an ensemble-based approach (Sec. 4). (3) To assess our solution, we introduce a metric for assessing composite feature similarity based on Jaccard similarity. (4) We demonstrate the utility of our model on a range of synthetic and semi-synthetic tasks where the ground truth group features are known (Sec. 5). We see that our model not only frequently recovers the relevant features, but also often discovers the underlying group structure.

2 Related Work

Significant attention has been placed on feature selection (see Appendix B for further discussion of standard feature selection), and several approaches have been extended to select predefined groups instead of individual features. For example, LASSO [67, 73] is a linear method that uses an L1 penalty to impose sparsity among coefficients. Group LASSO [82] generalises this to allow predefined groups to be selected or excluded jointly, rather than single features, by replacing the L1 penalty with L2 penalties on each group. Other feature selection methods, such as SLOPE [10], have been similarly extended to group feature selection to give Group-SLOPE [12]. Further examples of group feature selection using adapted loss functions are SCAD-L2 [84] and hierarchical LASSO [89]. Similarly, Bayesian approaches to feature selection [25] have also been generalised to the group setting [31]. Finally, the Knockoff procedure [8, 15, 35, 51, 65, 70] is a generative procedure that creates fake covariates (knockoffs), obeying certain symmetries under permutations of real and knockoff features. By subsequently carrying out Feature Selection on the combined real and knockoff data, there are guarantees on the False Discovery Rate. Generalisations of the Knockoff procedure to the group setting also exist [21, 90], where symmetries under permutations of entire groups must exist.

The key commonality is that none of these methods *discover* groups, but instead can only *select* groups from a set of predefined candidates. Therefore, while they may be applicable when we can split inputs into groups, they are not able to find groups of predictors on their own. Our work differs from these methods by considering the challenge of finding such groups in the absence of prior knowledge. Additionally, unlike prior work, we do not make assumptions about correlations between features or restrictions on groups, such as requiring that the candidate groups partition the features.

3 Problem Description

Let $\mathbf{X} \in \mathcal{X}^p$ be a p-dimensional signal (such as gene expressions or patient covariates) and $Y \in \mathcal{Y}$ be a response (such as disease traits). Informally, we wish to group features into the maximum number of subsets, $\mathcal{G}_i \subset [p]$, where the predictive power of any single group significantly decreases when any feature is removed, allowing us to separate the groups into different pathways from the signal to the response. Note that we do not enforce assumptions on the groups such as non-overlapping groups or

---

[1]We will often refer to composite features as groups for brevity; in this paper, they refer to the same thing.

every feature being in at least one group. In this section, we begin with a description of traditional feature selection before formalizing composite feature selection.

3.1 Feature Selection

The goal of traditional feature selection is to select a subset, $\mathcal{S} \subset [p]$, of features that are relevant for predicting the response variable. In particular, in the case of embedded feature selection [28], this is conducted jointly with the model selection process.

Let $*$ denote any point not in $\mathcal{X}$ and define $\mathcal{X}_\mathcal{S} = (\mathcal{X} \cup \{*\})^p$. Then, given $\mathbf{X} \in \mathcal{X}^p$, the selected subset of features can be denoted as $\mathbf{X}_\mathcal{S} \in \mathcal{X}_\mathcal{S}$ where $x_{\mathcal{S},k} = x_k$ if $k \in \mathcal{S}$ and $x_{\mathcal{S},k} = *$ if $k \notin \mathcal{S}$. Let $f : \mathcal{X}_\mathcal{S} \to \mathcal{Y}$ be a function in some space $\mathcal{F}$ (such as the space of neural networks) taking subset $\mathbf{X}_\mathcal{S}$ as input to yield Y. Then, selecting relevant features for predicting a response can be achieved by solving the following optimization problem:

$$\underset{f \in \mathcal{F}, \ \mathcal{S} \subset [p]}{\text{minimize}} \ \ \mathbb{E}_{\mathbf{x}, y \sim p_{XY}} \Big[\ell_Y \big(y, f(\mathbf{x}_\mathcal{S}) \big) \Big] \ \ \text{subject to} \ \ |\mathcal{S}| \leq \delta, \tag{1}$$

where δ constrains the number of selected features and $\ell_Y(y, y')$ is a task-specific loss function.

This can be solved by introducing a selection vector $\mathbf{M} = (M_1, \cdots, M_p) \in \{0,1\}^p$, consisting of binary random variables governed by distribution p_M, with realization $\mathbf{m}$ indicating selection of the corresponding features. Then, the selected features given vector $\mathbf{m}$ can be written as

$$\tilde{\mathbf{x}} \triangleq \mathbf{m} \odot \mathbf{x} + (1 - \mathbf{m}) \odot \hat{\mathbf{x}}, \tag{2}$$

where $\odot$ indicates element-wise multiplication and $\hat{\mathbf{x}}$ are the values assigned to features that are not selected (typically $\hat{\mathbf{x}} \equiv 0$ or $\bar{\mathbf{x}}$). (1) can be (approximately) solved by jointly learning the model f and the selection vector distribution p_M based on the following optimization problem:

$$\underset{f, \ p_M}{\text{minimize}} \ \ \mathbb{E}_{\mathbf{x}, y \sim p_{XY}} \mathbb{E}_{\mathbf{m} \sim p_M} \Big[\ell_Y \big(y, f(\tilde{\mathbf{x}}) \big) + \beta \|\mathbf{m}\|_0 \Big], \tag{3}$$

where β is a balancing coefficient that controls the number of features to be selected.

3.2 Composite Feature Selection

The goal of composite feature selection is to not only find the predictive features, but also to group them based on how they are predictive. For example, assume features x_1 and x_2 are only predictive when both are known by the model, but make the same prediction independent of x_3. Then we wish to group x_1, x_2 from x_3. In this section, we define the embedded composite feature selection problem; that is, we want to find a valid model f and groups $\{\mathcal{G}_1, \ldots, \mathcal{G}_N\}$ in parallel. A model is only valid when the group representations are combined in a way where we can view each group as contributing an independent piece of information for the final prediction. A valid model acts on a *set* of groups [83], thus when combining groups, we require order not to matter. Therefore, we must combine the representations using a permutation invariant aggregator.

Let $A : (\prod_i \mathbb{R}^n) \to \mathbb{R}^N$ be a general permutation invariant aggregation function. It is well established that for a specific choice of $\phi : \mathbb{R}^n \to \mathbb{R}^m$ and $\rho : \mathbb{R}^m \to \mathbb{R}^N$, A can be decomposed as $\rho[\sum_i \phi(\cdot)]$ (see [83] for examples). This gives $f(\mathbf{x}) = g\big(\rho\big[\sum_i \phi(f_i(\mathbf{x}_{\mathcal{G}_i}))\big]\big)$, where f_i encodes group i, ρ and ϕ give the permutation invariant aggregation and g is any final non-linear function, softmax for instance. The function composition of ϕ and f_i can be relabelled as $\tilde{f}_i = \phi \circ f_i$, and the composition of g and ρ can be relabelled as $\tilde{\rho} = g \circ \rho$. This leads to $f(\mathbf{x}) = \tilde{\rho}\big[\sum_i \tilde{f}_i(\mathbf{x}_{\mathcal{G}_i})\big]$, this gives a definition for what a valid model structure can be in composite feature selection.

Definition 3.1. The most general valid model for acting on N composite features is given by:

$$f(\mathbf{x}) = \rho\Bigg[\sum_{i=1}^{N} f_i(\mathbf{x}_{\mathcal{G}_i}) \Bigg]. \tag{4}$$

That is, the groups must interact only once, all groups must be included and the interaction is a summation; all other interactions can (and often should) be non-linear.

Depending on the task, a specific permutation invariant aggregation may be chosen (e.g. `Max()`). However, any permutation invariant aggregator can be (approximately) expressed in the form of Def. 3.1; thus, when learning from data, the general structure of Def. 3.1 means that this is not necessary.

The embedded composite feature selection problem can now be phrased in an analogous way to traditional feature selection. Let $*$ denote some point not in $\mathcal{X}$ and define $\mathcal{X}_{\mathcal{G}_i} = (\mathcal{X} \cup \{*\})^p$. Then, given $\mathbf{X} \in \mathcal{X}^p$, the selected group of features is denoted as $\mathbf{X}_{\mathcal{G}_i} \in \mathcal{X}_{\mathcal{G}_i}$ where $x_{\mathcal{G}_i,k} = x_k$ if $k \in \mathcal{G}_i$ and $x_k = *$ if $k \notin \mathcal{G}_i$. Let $f_i : \mathcal{X}_{\mathcal{G}_i} \to \mathcal{Z}$ be a function in $\mathcal{F}$ that takes as input the subset $\mathbf{X}_{\mathcal{G}_i}$ and outputs a latent representation $\mathbf{z}_i$. Then, finding the groups of features can be achieved by solving the optimization problem:

$$\underset{\rho,\, f_i \in \mathcal{F},\, \mathcal{G}_i \subset [p]}{\text{minimize}} \quad \mathbb{E}_{\mathbf{x},y \sim p_{XY}}\left[\ell_Y\left(y, \rho\Big[\sum_{i=1}^{N} f_i(\mathbf{x}_{\mathcal{G}_i})\Big]\right)\right] \qquad \text{subject to} \quad \begin{matrix} |\mathcal{G}_i| \le \delta_i \ \ \forall i, \\ N \ge \Delta, \end{matrix} \tag{5}$$

where $\boldsymbol{\delta}$ constrains the number of selected features in each group and Δ gives the minimum number of groups. This objective leads to multiple smaller groups, rather than one group containing all features, which is consistent with our motivation of the problem.

Continuing to expand from traditional feature selection, we can also extend the solution to the composite setting. For N groups we can introduce a selection *matrix* $M \in \{0,1\}^{N \times p}$, governed by distribution p_M. For a realization $\mathbf{m}$, the selected features from group i are given by

$$\tilde{\mathbf{x}}_i \triangleq \mathbf{m}_i \odot \mathbf{x} + (1 - \mathbf{m}_i) \odot \hat{\mathbf{x}}, \tag{6}$$

where $\mathbf{m}_i$ is the i^{th} row of M. We can approximately solve (5) by solving the optimization problem:

$$\underset{f,\, p_M}{\text{minimize}} \ \ \mathbb{E}_{\mathbf{x},y \sim p_{XY}} \mathbb{E}_{\mathbf{m} \sim p_M}\left[\ell_Y\big(y, f(\mathbf{x})\big) + R_e(\mathbf{m})\right], \tag{7}$$

where $f(\mathbf{x})$ obeys Def. (4) and R_e is a regularisation term which controls how features are selected in each group. R_e should capture both group size (i.e. encourage as few features as possible to be selected) but also the relationships between groups (i.e. groups should be distinct and not redundant).

3.3 Challenges

There are various challenges in solving the composite feature selection problem. While the ultimate task is to find predictive groups of features, there remains the necessity simply to identify predictive features, which is already an NP-hard problem [2]. Composite feature selection not only inherits this property but introduces additional complexity since we can think of each group as solving a separate feature selection problem. Consider the number of potential solutions: in traditional feature selection (assuming not all features are selected), there are $2^n - 2$ ways of selecting a subset from n features; even restricting to at most $m << n$ quickly becomes unfeasible for even modest values of m. In composite feature selection, *every group* has the same number of solutions as traditional feature selection, drastically increasing the total number of possible solutions. A challenge specific to composite feature selection arises when the ground truth group structure contains groups with overlapping features (e.g. feature x_1 interacts independently with both x_2 and x_3). In this scenario, it is difficult to separate these two effects while penalizing the inclusion of additional features.

4 Method: CompFS

In this section, we propose a novel architecture for finding predictive groups of features, which we refer to as **Comp**osite **F**eature **S**election (CompFS). In order to discover groups of features, our model is composed of a set of group selection models and an aggregate predictor. Our approach resembles an ensemble of "weak" feature selection models, where each learner attempts to solve the task using a sparse set of features (Figure 1). These models are then trained in such a way as to discover distinct predictive groups. We first consider the group selection models in more detail before describing how the group selection models are combined and the training procedure.

Figure 1: An illustration of CompFS. We use an ensemble of group selection models to discover composite features and an aggregate predictor to combine these features when issuing predictions.

4.1 Group Selection Models

CompFS is composed of a set of group selection models, each of which primarily aims to solve the traditional feature selection problem specified by (1). We achieve this by solving (3) using a neural network-based approach with stochastic gating of the input features. Each group selection model consists of the following three components (Figure 1):

- *Group Selection Probability*, $\boldsymbol{\pi}_i = (\pi_{1,i}, \cdots, \pi_{p,i}) \in [0,1]^p$, which is a trainable vector that governs the Bernoulli distribution used to generate the gate vector $\mathbf{m}_i$. Each element of the selection probability $\pi_{k,i}$ indicates the importance of the corresponding feature to the target.
- *Group Encoder*, $f_{\theta_i} : \mathcal{X}^p \to \mathcal{Z}$, that takes as input the selected subset of features $\tilde{\mathbf{x}}_i$ and outputs latent representations $\mathbf{z}_i \in \mathcal{Z}$.
- *Group Predictor*, $h_{\phi_i} : \mathcal{Z} \to \mathcal{Y}$, that takes as input the latent representations of the selected subset of features, $\mathbf{z}_i = f_{\theta_i}(\tilde{\mathbf{x}}_i)$, and outputs predictions on the target outcome.

Solving (3) directly is not possible since the sampling step has no differentiable inverse. Instead, we use the relaxed Bernoulli distribution [53, 34] and apply the reparameterization trick as follows.

Formally, given selection probability $\boldsymbol{\pi} = (\pi_1, \cdots, \pi_p)$ and independent Uniform$(0,1)$ random variables $(U_1, \cdots, U_p)$, we can generate a relaxed gate vector $\tilde{\mathbf{m}} = (\tilde{m}_1, \cdots, \tilde{m}_p) \in (0,1)^p$ based on the following reparameterization trick [53]:

$$\tilde{m}_k = \sigma\Big(\frac{1}{\tau}\big(\log \pi_k - \log(1 - \pi_k) + \log U_k - \log(1 - U_k)\big)\Big), \qquad (8)$$

where $\sigma(x) = (1 + \exp(-x))^{-1}$ is the sigmoid function. This relaxation is parameterized by $\boldsymbol{\pi}$ and temperature $\tau \in (0, \infty)$. Further, as $\tau \to 0$, the gate vectors $\tilde{m}_k$ converge to Bernoulli(π_k) random variables. Crucially this is differentiable with respect to $\boldsymbol{\pi}$.

Given group selection probability $\boldsymbol{\pi}_i$, we first sample relaxed Bernoulli random variable $\tilde{\mathbf{m}}_i$ according to (8) and then use $\tilde{\mathbf{m}}_i$ in a gating procedure to select the group of features. The output of the gate is:

$$\tilde{\mathbf{x}}_i = \text{gate}_i(\mathbf{x}) = \tilde{\mathbf{m}}_i \odot \mathbf{x} + (1 - \tilde{\mathbf{m}}_i) \odot \bar{\mathbf{x}}, \qquad (9)$$

where we replace the variables that were not selected by their mean value $\bar{\mathbf{x}}$. The mean is used because in particular tasks a feature having a value of 0 may be particularly meaningful. The gate output $\tilde{\mathbf{x}}_i$ is then fed into the group encoder f_{θ_i} to yield representation $\mathbf{z}_i = f_{\theta_i}(\tilde{\mathbf{x}}_i)$. This representation is finally passed to the group predictor h_{ϕ_i} to produce the prediction for an individual learner, $\hat{y}_i = h_{\phi_i}(\mathbf{z}_i)$.

4.2 Group Aggregation

The final component necessary for CompFS is a way to aggregate the individual group selection models. This is achieved via an overall *predictor*, $h_\phi : \mathcal{Z} \to \mathcal{Y}$, that takes as input the set of latent representations $\{\mathbf{z}_1, \ldots, \mathbf{z}_N\}$ produced by the individual learners and outputs predictions on the target outcome. For simplicity, we apply a linear prediction head to the latent representations and use element-wise summation to aggregate. Thus, the prediction of the ensemble is given by:

$$\hat{y} = h_\phi(\{\mathbf{z}_1, \ldots, \mathbf{z}_N\}) = \rho\Big[\sum_{i=1}^{N} \mathbf{W}_i \mathbf{z}_i + \mathbf{b}_i\Big], \qquad (10)$$

where N is the number of members of the ensemble and ρ is a suitable transformation (e.g. softmax). Note that by using element-wise summation, our model satisfies (4) for acting on composite features.

4.3 Loss Functions

Group Selection Models. The individual learners can be trained to perform (traditional) feature selection (1) by minimizing the following loss function:

$$\mathcal{L}_{\mathcal{G}_i} = \mathbb{E}_{\mathbf{x},y \sim p_{XY}} \left[\ell_Y \left(y, h_{\phi_i}(f_{\theta_i}(\text{gate}_i(\mathbf{x}))) \right) + \beta \langle \boldsymbol{\pi}_i \rangle^2 \right], \tag{11}$$

where ℓ_Y is a suitable loss function for the prediction task (e.g. cross-entropy for classification tasks and MSE for regression tasks) and $\beta \geq 0$ balances the two terms. Note the selections probabilities $\boldsymbol{\pi}_i$ are not regularized with the typical L1 penalty. Instead, we apply an L2 penalty to the mean selection probability $\langle \boldsymbol{\pi}_i \rangle$ for each individual learner. This is justified as follows. Recall the optimization problem given by (5). We desire a solution with the maximal number of predictive groups N, while minimizing the number of selected features per group $\sum_{i=1}^{N} |\mathcal{G}_i|$. The standard L1 penalty term does not achieve this goal since adding an additional feature to either group $\mathcal{G}_i$ or $\mathcal{G}_j$ incurs the same penalty. In contrast, the L2 penalty imposed on $\langle \boldsymbol{\pi}_i \rangle$ penalizes adding extra features to already large groups, favoring the construction of smaller groups over larger ones.

Aggregate Predictor. The aggregate predictor can be trained jointly with the group feature selection models by minimizing a standard prediction loss (where ℓ_Y is the same as in (11)):

$$\mathcal{L}_E = \mathbb{E}_{\mathbf{x},y \sim p_{XY}} \left[\ell_Y \left(y, h_\phi(\{\mathbf{z}_1, \ldots, \mathbf{z}_n\}) \right) \right]. \tag{12}$$

Additional Regularization. If we simply apply the losses given by Eqs. (11), (12), there will be limited (or even no) differentiation among the individual learners and the optimal solution would be for each learner to simply solve the traditional feature selection problem (1). This results in all learners selecting the same features, which does not achieve our aim of discovering groups of predictive features. In order to encourage differentiation between the models, we introduce an additional loss that penalizes the selection of the same features in multiple groups:

$$\mathcal{L}_R = \mathbb{E}_{\mathbf{x},y \sim p_{XY}} \left[\sum_{i=1}^{N} \sum_{j>i} \boldsymbol{\pi}_i \cdot \boldsymbol{\pi}_j \right]. \tag{13}$$

Overall Loss. Combining the above, our overall loss function therefore can be written as follows:

$$\mathcal{L} = \sum_{i=1}^{N} \mathcal{L}_{\mathcal{G}_i} + \beta_E \mathcal{L}_E + \beta_R \mathcal{L}_R, \tag{14}$$

where $\beta_E, \beta_R \geq 0$ are hyperparameters to balance the losses.

Training CompFS with the loss given by (14) is designed to achieve the following: (1) The overall ensemble network should be a good predictor ($\mathcal{L}_E$). (2) Each individual learner should to solve the traditional feature selection problem ($\mathcal{L}_{\mathcal{G}_i}$), which requires the group predictor to be accurate while selecting minimal features. (3) Finally, we want the groups to be distinct and thus discourage highly similar groups ($\mathcal{L}_R$). However, note that we do not exclude the possibility of some overlap of features between groups. The model is end-to-end differentiable, so we train with gradient descent.

Evaluation. During evaluation, only the gating procedure changes. The way features can be selected is chosen by the user. A standard solution which we adopt in this paper is using a threshold λ and calculating the gate vector $\mathbf{m}_i$ as follows: $m_{k,i} = 1$, if $\pi_{k,i} > \lambda$ and 0 otherwise.

5 Experiments

We evaluate CompFS using several synthetic and semi-synthetic datasets where ground truth feature importances and group structure are known. Specific architectural details are given in App. C.

229 Additional information regarding experiments, benchmarks, and datasets can be found in App. D.
230 Additional ablations and sensitivity analysis are in App. A.

231 **Benchmarks.** The primary goal of our experiments is to demonstrate the utility of discovering
232 composite features over traditional feature selection. Our main benchmark is an oracle feature
233 selection method ("Oracle") that perfectly selects the ground truth features but provides no structure,
234 giving all features as one group. We also include comparisons to a linear feature selection method
235 (LASSO) [73] and two non-linear, state of the art approaches, Stochastic Gates (STG) [81] and
236 Supervised Concrete Autoencoder (Sup-CAE) [6]. Finally, we compare with Group LASSO [82],
237 where we enumerate all groups with 1 or 2 features as predefined groups. Note this represents a
238 significant simplification of the task for Group Lasso (see App. G for additional baselines).

239 **Metrics.** Since the ground truth feature groups $\mathcal{G}_1, \ldots, \mathcal{G}_N$ are known, we use True Positive Rate
240 (TPR) and False Discovery Rate (FDR) to assess the discovered features against the ground truth. To
241 assess composite features, i.e. grouping, we define the Group Similarity (G_{sim}) as the normalized
242 Jaccard similarity between ground truth feature groups and the most similar proposed group:

$$G_{sim} = \frac{1}{\max(N, K)} \sum_{i=1}^{N} \max_{j \in [K]} \mathcal{J}(\mathcal{G}_i, \hat{\mathcal{G}}_j), \tag{15}$$

243 where $\mathcal{J}$ is the Jaccard index [33] and $\hat{\mathcal{G}}_1, \ldots, \hat{\mathcal{G}}_K$ are the discovered groups. $G_{sim} \in [0, 1]$, where
244 $G_{sim} = 1$ corresponds to perfect recovery of the ground truth groups, while $G_{sim} = 0$ when none of the
245 correct features are discovered. See App. E for additional details together with examples. We assess
246 the models by seeing if the ground truth features have been correctly discovered, using TPR and FDR.
247 We then see if the underlying grouping has been uncovered (and correct features) using G_{sim}.

5.1 Synthetic Experiments.

249 **Dataset Description.** We begin by evaluating our method on a range of synthetic datasets where
250 the ground truth feature importance is known (Table 1). We generate synthetic datasets by sampling
251 from the Gaussian distribution with initially no correlations across the features ($X \sim \mathcal{N}(0, I)$). We
252 construct binary classification tasks, where the class y is determined by the following decision rules:

- 253 **(Syn1)** $y = 1$ if $x_1 > 0.55$ or $x_2 > 0.55$, 0 otherwise. The ground truth groups are $\{\{1\}, \{2\}\}$.
  254 This task assesses whether the model can separate two features rather than group them together.
- 255 **(Syn2)** $y = 1$ if $x_1 x_2 > 0.30$ or $x_3 x_4 > 0.30$, 0 otherwise. The ground truth groups are
  256 $\{\{1, 2\}, \{3, 4\}\}$. This task requires identifying groups consisting of more than one variable.
- 257 **(Syn3)** $y = 1$ if $x_1 x_2 > 0.30$ or $x_1 x_3 > 0.30$, 0 otherwise. The ground truth groups are
  258 $\{\{1, 2\}, \{1, 3\}\}$. This task investigates whether a model can split the features into two *overlapping*
  259 groups of two, rather than one group with all three features.
- 260 **(Syn4)** $y = 1$ if $x_1 x_4 > 0.30$ or $x_7 x_{10} > 0.30$, 0 otherwise. The ground truth groups are
  261 $\{\{1, 4\}, \{7, 10\}\}$. This task is equivalent to **Syn2**, however, here the features exhibit strong
  262 correlation in collections of 3. This task demonstrates the difficulty of carrying out group feature
  263 selection (and indeed standard feature selection) when the features are highly correlated.

264 The decision rules are created such that there is minimal class imbalance. We use signals with 500
265 dimensions to demonstrate the utility in the high dimensional regime. We use 20000 samples to train
266 and 200 to test. Each experiment is repeated 10 times.

267 **Analysis.** On both Syn1 and Syn2, CompFS achieves high TPR with no false discoveries (0%
268 FDR) and significantly higher G_{sim} than the Oracle. Despite allowing CompFS to discover up to
269 5 groups, CompFS typically finds the correct number of groups (2), demonstrating that it is not
270 necessary for the number of allowed composite features to match the ground truth, which is vital
271 in real-world use cases where this is unknown. Syn3 is significantly more challenging due to the
272 overlapping structure and we observe essentially the same performance as Oracle. Despite finding all
273 the correct features and no false discoveries, CompFS typically finds the union $\{1, 2, 3\}$ rather than
274 the underlying group structure $\{\{1, 2\}, \{1, 3\}\}$. Finally, for Syn4, while CompFS has a relatively
275 high FDR, it frequently finds the ground truth relevant features and groups with similar G_{sim} to Oracle.

Table 1: Performance on Synthetic Datasets, values are recorded with their standard deviations.

DATASET	MODEL	TPR	FDR	G$_{\text{SIM}}$	NO. GROUPS	ACCURACY (%)
SYN1	CompFS(5)	100.0 ± 0.0	0.0 ± 0.0	0.91 ± 0.14	2.2 ± 0.4	98.9 ± 0.5
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	81.8 ± 2.0
	Group LASSO	100.0 ± 0.0	0.0 ± 0.0	0.67 ± 0.00	3.0 ± 0.0	83.8 ± 1.4
	STG	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	97.8 ± 1.4
	Sup-CAE	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	97.8 ± 1.4
SYN2	CompFS(5)	95.0 ± 15.0	0.0 ± 0.0	0.90 ± 0.20	1.8 ± 0.4	95.5 ± 5.4
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	0.0 ± 0.0	0.0 ± 0.0	0.00 ± 0.00	0.0 ± 0.0	52.6 ± 2.9
	Group LASSO	0.0 ± 0.0	0.0 ± 0.0	0.00 ± 0.00	0.0 ± 0.0	52.2 ± 0.9
	STG	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	93.9 ± 2.2
	Sup-CAE	37.5 ± 31.7	42.5 ± 44.2	0.24 ± 0.20	1.0 ± 0.0	61.9 ± 12.8
SYN3	CompFS(5)	100.0 ± 0.0	0.0 ± 0.0	0.68 ± 0.05	1.3 ± 0.5	97.4 ± 1.1
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.67 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	0.0 ± 0.0	0.0 ± 0.0	0.00 ± 0.00	0.0 ± 0.0	56.5 ± 4.0
	Group LASSO	0.0 ± 0.0	0.0 ± 0.0	0.00 ± 0.00	0.0 ± 0.0	54.6 ± 1.3
	STG	100.0 ± 0.0	0.0 ± 0.0	0.67 ± 0.00	1.0 ± 0.0	95.3 ± 1.7
	Sup-CAE	23.3 ± 31.6	66.7 ± 47.1	0.23 ± 0.31	1.0 ± 0.0	62.6 ± 12.6
SYN4	CompFS(5)	90.0 ± 12.2	51.9 ± 13.8	0.47 ± 0.20	2.5 ± 0.7	95.8 ± 1.8
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	0.0 ± 0.0	0.0 ± 0.0	0.00 ± 0.00	0.0 ± 0.0	51.8 ± 3.2
	Group LASSO	0.0 ± 0.0	10.0 ± 31.6	0.00 ± 0.00	0.1 ± 0.3	53.0 ± 1.1
	STG	100.0 ± 0.0	66.7 ± 0.0	0.17 ± 0.00	1.0 ± 0.0	94.2 ± 2.1
	Sup-CAE	72.5 ± 14.2	16.7 ± 14.7	0.39 ± 0.08	1.0 ± 0.0	72.2 ± 13.2

This is a challenging task with significant correlation between features. Despite this, CompFS is able to uncover the underlying group structure, providing additional insight over traditional feature selection. STG typically performs well in terms of traditional feature selection, but scores poorly in terms of G$_{\text{sim}}$ due to not providing any group information.

5.2 Semi-Synthetic Experiments.

Dataset Description. Next, we assess our ability to identify composite features using semi-synthetic molecular datasets. These tasks are analogs of real-world problems, such as identifying biologically active chemical groups; however, the labels are determined by a synthetic "binding logic" so that the ground truth feature relevance is known. We use several of the datasets constructed by [56], some of which were also used by [66].[2] The synthetic "binding logics" are expressed as a combination of molecular fragments that must either be present or absent for binding to occur and are used to label molecules from the ZINC database [32]. Each logic includes up to four functional groups (Table 6). Molecules are featurized using a set of 84 functional groups, where feature $x_i = 1$ if the molecule contains functional group i and 0 otherwise. The specific binding logics are given in App. F.

Table 2: Performance on Chemistry Datasets, values are recorded with their standard deviations.

DATASET	MODEL	TPR	FDR	G$_{\text{SIM}}$	NO. GROUPS	ACCURACY (%)
CHEM1	CompFS(5)	100.0 ± 0.0	0.0 ± 0.0	0.82 ± 0.20	1.9 ± 0.5	100.0 ± 0.0
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	75.8 ± 0.0
	Group LASSO	100.0 ± 0.0	0.0 ± 0.0	0.67 ± 0.00	3.0 ± 0.0	100.0 ± 0.0
	STG	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	Sup-CAE	62.5 ± 13.2	23.3 ± 17.5	0.37 ± 0.07	1.0 ± 0.0	77.8 ± 11.0
CHEM2	CompFS(5)	100.0 ± 0.0	0.0 ± 0.0	0.72 ± 0.24	2.2 ± 0.6	100.0 ± 0.0
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	81.6 ± 0.0
	Group LASSO	100.0 ± 0.0	0.0 ± 0.0	0.40 ± 0.00	5.0 ± 0.0	81.6 ± 0.0
	STG	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	Sup-CAE	66.7 ± 0.0	0.0 ± 0.0	0.42 ± 0.00	1.0 ± 0.0	80.9 ± 9.5
CHEM3	CompFS(5)	100.0 ± 0.0	7.3 ± 11.7	0.62 ± 0.17	2.4 ± 0.5	100.0 ± 0.0
	Oracle	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	LASSO	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	87.4 ± 5.2
	Group LASSO	100.0 ± 0.0	20.0 ± 0.0	0.20 ± 0.00	10.0 ± 0.0	91.5 ± 0.0
	STG	100.0 ± 0.0	0.0 ± 0.0	0.50 ± 0.00	1.0 ± 0.0	100.0 ± 0.0
	Sup-CAE	62.5 ± 13.2	23.3 ± 17.5	0.37 ± 0.07	1.0 ± 0.0	77.8 ± 11.0

---

[2]Data from `https://github.com/google-research/graph-attribution/raw/main/data/all_16_logics_train_and_test.zip`.

Analysis. All methods are able to identify the ground truth relevant features; however, only CompFS provides deeper insights. Unlike for Syn1-4, LASSO correctly selects the ground truth features since the dataset consists of binary variables and thus it is possible to find performant linear models. However, while discovering the correct features, Group LASSO selects all possible combinations of these features, adding no benefit over standard feature selection.

For Chem1-2, CompFS perfectly recovers the group structure in the majority of experiments, leading to high G_{sim} far exceeding traditional feature selection. On Chem3, we occasionally discover additional features that are not part of the binding logic. However, a number of molecular fragments are strongly correlated with the binding logic, even though they are not themselves included. In fact, some features contain information about *multiple* functional groups. For example, esters contain a carbonyl and an ether; both are in the binding logic for Chem3, while ester is not, despite being highly informative, and thus occasionally CompFS incorrectly selects this feature. In spite of this, CompFS achieves significantly higher G_{sim} than even Oracle. This demonstrates the benefit of the grouping discovered by CompFS, even with a modest number of false discoveries. As before, CompFS typically finds the correct number of groups (2), despite being able to discover up to 5 groups, further demonstrating that the number of composite features need not be known *a priori*, which is the case in real-world applications.

5.3 Real-World Data: METABRIC

Dataset Description. Finally, we assess CompFS on a real-world dataset, METABRIC [19, 60], where the ground truth group structure is *unknown*. METABRIC contains gene expression, mutation, and clinical data for 1,980 primary breast cancer samples. We evaluated the ability to predict the progesterone receptor (PR) status of the tissue based on the gene expression data, which consists of measurements for 489 genes.

Table 3: METABRIC performance. We compare CompFS and STG using 25 features to an MLP using all 489 features.

Model	AUC ROC
MLP (All features)	0.869
CompFS(5)	0.830
STG	0.843

Analysis. CompFS suffers limited performance degradation compared to using all features, despite only using 5% of the features (Table 3). Despite imposing a more rigid structural form on how features can interact in the predictive model, STG only had marginally greater predictive power than CompFS. However, CompFS provides greater insight into how the features interact than STG.

We found supporting evidence in the scientific literature for all but 1 of the genes discovered by CompFS (Table 10). In addition, within each group, we found further evidence of the interactions between genes, demonstrating the ability for CompFS to learn informative groups of features. For example, in Group 1, CXCR1 and PEN-2 (the protein encoded by PSENEN) are known to interact [5]. In Group 2, BMP6 encodes a member of the TGF-β superfamily of proteins, and TGF-β triggers activation of SMAD3 [17]. In the same group, MAPK1 activity is dependent on the activity of PRKCQ in breast cancer cells [13], while MAPK1 is also known to interact with MAPT [45], SMAD3 [23], and BMP6 [85]. Additional supporting evidence can be found in Appendix H.

6 Conclusion

In this paper, we introduced CompFS, an ensemble-based approach that tackles the newly proposed challenge of composite feature selection. Using synthetic and semi-synthetic data, we assess our ability to go beyond traditional feature selection and recover deeper underlying connections between variables. CompFS is not without its limitations: as with other methods, points of difficulty arise when the input features are highly correlated, or if predictive composites contain overlapping features. This may be overcome in the future by using correlated gates. Further, as with many traditional feature selection methods, there are no guarantees on false discovery rate using CompFS. This could be tackled by using CompFS to propose possible candidate composite features, and then using the Group Knockoff procedure to ensure these guarantees. More broadly, as with standard feature selection, groups found under composite feature selection must be verified by domain experts (both features but additionally interactions). However, we believe the additional structure provided by composite feature selection could be of significant benefit to a wide variety of practitioners.

References

[1] Wail Al Sarakbi, Sara Reefy, Wen G. Jiang, Terry Roberts, Robert F. Newbold, and Kefah Mokbel. Evidence of a tumour suppressor function for DLEC1 in human breast cancer. *Anticancer Research*, 30(4):1079–1082, 2010.

[2] Edoardo Amaldi and Viggo Kann. On the approximability of minimizing nonzero variables or unsatisfied relations in linear systems. *Theoretical Computer Science*, 209(1):237–260, 1998.

[3] M. Ampuja, E.L. Alarmo, P. Owens, R. Havunen, A.E. Gorska, H.L. Moses, and A. Kallioniemi. The impact of bone morphogenetic protein 4 (BMP4) on breast cancer metastasis in a mouse xenograft model. *Cancer Letters*, 375(2):238–244, 2016.

[4] Sharon Arcuri, Georgia Pennarossa, Fulvio Gandolfi, and Tiziana A. L. Brevini. Generation of trophoblast-like cells from hypomethylated porcine adult dermal fibroblasts. *Frontiers in Veterinary Science*, 8, 2021.

[5] Martina Bakele, Amelie S. Lotz-Havla, Anja Jakowetz, Melanie Carevic, Veronica Marcos, Ania C. Muntau, and Dominik Gersting, Soeren W.and Hartl. An interactive network of elastase, secretases, and PAR-2 protein regulates CXCR1 receptor surface expression on neutrophils. *Journal of Biological Chemistry*, 289(30):20516–20525, 2014.

[6] Muhammed Fatih Balın, Abubakar Abid, and James Zou. Concrete autoencoders: Differentiable feature selection and reconstruction. In *International Conference on Machine Learning (ICML)*, 2019.

[7] Hatice Ozer Balli and Bent E. Sørensen. Interaction effects in econometrics. *Empirical Economics*, 45(1):583–603, 2013.

[8] Rina Foygel Barber and Emmanuel J Candès. Controlling the false discovery rate via knockoffs. *The Annals of Statistics*, 43(5):2055–2085, 2015.

[9] Amir Beck and Marc Teboulle. A fast iterative shrinkage-thresholding algorithm for linear inverse problems. *SIAM Journal on Imaging Sciences*, 2(1):183–202, 2009.

[10] Malgorzata Bogdan, Ewout van den Berg, Weijie Su, and Emmanuel Candes. Statistical estimation and testing via the sorted L1 norm. *arXiv preprint arXiv:1310.1969*, 2013.

[11] Terry Brown. Silica exposure, smoking, silicosis and lung cancer—complex interactions. *Occupational Medicine*, 59(2):89–95, 03 2009.

[12] Damian Brzyski, Alexej Gossmann, Weijie Su, and Małgorzata Bogdan. Group SLOPE - adaptive selection of groups of predictors. *Journal of the American Statistical Association*, 114(525):419–433, 2019.

[13] Jessica Byerly, Gwyneth Halstead-Nussloch, Koichi Ito, Igor Katsyv, and Hanna Y. Irie. PRKCQ promotes oncogenic growth and anoikis resistance of a subset of triple-negative breast cancer cells. *Breast Cancer Research*, 18(1):95, 2016.

[14] Jessica H. Byerly, Elisa R. Port, and Hanna Y. Irie. PRKCQ inhibition enhances chemosensitivity of triple-negative breast cancer by regulating Bim. *Breast Cancer Research*, 22(1):72, 2020.

[15] Emmanuel Candes, Yingying Fan, Lucas Janson, and Jinchi Lv. Panning for gold: 'model-X' knockoffs for high dimensional controlled variable selection. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 80(3):551–577, 2018.

[16] Girish Chandrashekar and Ferat Sahin. A survey on feature selection methods. *Computers & Electrical Engineering*, 40(1):16–28, 2014.

[17] Bijun Chen, Ruoshui Li, Silvia C. Hernandez, Anis Hanna, Kai Su, Arti V. Shinde, and Nikolaos G. Frangogiannis. Differential effects of smad2 and smad3 in regulation of macrophage phenotype and function in the infarcted myocardium. *Journal of Molecular and Cellular Cardiology*, 171:1–15, 2022.

[18] Tianyi Cheng, Peiying Chen, Jingyi Chen, Yingtong Deng, and Chen Huang. Landscape analysis of matrix metalloproteinases unveils key prognostic markers for patients with breast cancer. *Frontiers in Genetics*, 12, 2022.

[19] Christina Curtis, Sohrab P. Shah, Suet-Feung Chin, Gulisa Turashvili, Oscar M. Rueda, Mark J. Dunning, Doug Speed, Andy G. Lynch, Shamith Samarajiwa, Yinyin Yuan, Stefan Gräf, Gavin Ha, Gholamreza Haffari, Ali Bashashati, Roslin Russell, Steven McKinney, METABRIC Group, Anita Langerød, Andrew Green, Elena Provenzano, Gordon Wishart, Sarah Pinder, Peter Watson, Florian Markowetz, Leigh Murphy, Ian Ellis, Arnie Purushotham, Anne-Lise Børresen-Dale, James D. Brenton, Simon Tavaré, Carlos Caldas, and Samuel Aparicio. The genomic and transcriptomic architecture of 2,000 breast tumours reveals novel subgroups. *Nature*, 486(7403):346–352, 2012.

[20] Kun Dai, Hong-Yi Yu, and Qing Li. A semisupervised feature selection with support vector machine. *Journal of Applied Mathematics*, 64:141–158, 2013.

[21] Ran Dai and Rina Barber. The knockoff filter for FDR control in group-sparse and multitask regression. In *International Conference on Machine Learning (ICML)*, 2016.

[22] Mei Dong, Tam How, Kellye C. Kirkbride, Kelly J. Gordon, Jason D. Lee, Nadine Hempel, Patrick Kelly, Benjamin J. Moeller, Jeffrey R. Marks, and Gerard C. Blobe. The type III TGF-β receptor suppresses breast cancer progression. *The Journal of Clinical Investigation*, 117(1):206–217, 2007.

[23] Wei Bin Fang, Iman Jokar, An Zou, Diana Lambert, Prasanthi Dendukuri, and Nikki Cheng. CCL2/CCR2 chemokine signaling coordinates survival and motility of breast cancer cells through smad3 protein- and p42/44 mitogen-activated protein kinase (MAPK)-dependent mechanisms. *Journal of Biological Chemistry*, 287(43):36593–36608, 2012.

[24] Michael Y. Fessing, Ruzanna Atoyan, Ben Shander, Andrei N. Mardaryev, Vladimir V. Botchkarev Jr., Krzysztof Poterlowicz, Yonghong Peng, Tatiana Efimova, and Vladimir A. Botchkarev. BMP signaling induces cell-type-specific changes in gene expression programs of human keratinocytes and fibroblasts. *Journal of Investigative Dermatology*, 130(2):398–404, 2010.

[25] Edward I. George and Robert E. McCulloch. Approaches for bayesian variable selection. *Statistica Sinica*, pages 339–373, 1997.

[26] Christophe Ginestier, Suling Liu, Mark E. Diebel, Hasan Korkaya, Ming Luo, Marty Brown, Julien Wicinski, Olivier Cabaud, Emmanuelle Charafe-Jauffret, Daniel Birnbaum, Jun-Lin Guan, Gabriela Dontu, and Max S. Wicha. CXCR1 blockade selectively targets human breast cancer stem cells in vitro and in xenografts. *The Journal of Clinical Investigation*, 120(2):485–497, 2010.

[27] Santiago M. Gómez Bergna, Abril Marchesini, Leslie C. Amorós Morales, Paula N. Arrías, Hernán G. Farina, Víctor Romanowski, M. Florencia Gottardo, and Matias L. Pidre. Exploring the metastatic role of the inhibitor of apoptosis BIRC6 in breast cancer. *bioRxiv*, 2021.

[28] Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3(1):1157–1182, 2003.

[29] Kai Han, Yunhe Wang, Chao Zhang, Chao Li, and Chao Xu. Autoencoder inspired unsupervised feature selection. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2018.

[30] Xiaofei He, Deng Cai, and Partha Niyogi. Laplacian score for feature selection. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2005.

[31] Daniel Hernández-Lobato, José Miguel Hernández-Lobato, and Pierre Dupont. Generalized spike-and-slab priors for bayesian group feature selection using expectation propagation. *Journal of Machine Learning Research*, 14(7), 2013.

[32] John J. Irwin, Teague Sterling, Michael M. Mysinger, Erin S. Bolstad, and Ryan G. Coleman. ZINC: A free tool to discover chemistry for biology. *Journal of Chemical Information and Modeling*, 52(7):1757–1768, 2012.

[33] Paul Jaccard. The distribution of the flora in the alpine zone. *The New Phytologist*, 11(2):37–50, 1912.

[34] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with Gumbel-Softmax. In *International Conference on Learning Representations (ICLR)*, 2017.

[35] James Jordon, Jinsung Yoon, and Mihaela van der Schaar. KnockoffGAN: Generating knockoffs for feature selection using generative adversarial networks. In *International Conference on Learning Representations (ICLR)*, 2018.

[36] Päivi Järvensivu, Taija Heinosalo, Janne Hakkarainen, Pauliina Kronqvist, Niina Saarinen, and Matti Poutanen. HSD17B1 expression induces inflammation-aided rupture of mammary gland myoepithelium. *Endocrine-Related Cancer*, 25(4):393 – 406, 2018.

[37] Tadashi Kato, Atsushi Yamada, Mikiko Ikehata, Yuko Yoshida, Kiyohito Sasa, Naoko Morimura, Akiko Sakashita, Takehiko Iijima, Daichi Chikazu, Hiroaki Ogata, and Ryutaro Kamijo. FGF-2 suppresses expression of nephronectin via JNK and PI3K pathways. *FEBS Open Bio*, 8(5):836–842, 2018.

[38] Pora Kim, Feixiong Cheng, Junfei Zhao, and Zhongming Zhao. ccmGDB: a database for cancer cell metabolism genes. *Nucleic Acids Research*, 44(D1):D959–D968, 2015.

[39] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[40] Kenji Kira and Larry A. Rendell. A practical approach to feature selection. In *Machine Learning Proceedings*, pages 249–256. 1992.

[41] Theo A. Knijnenburg, Gunnar W. Klau, Francesco Iorio, Mathew J. Garnett, Ultan McDermott, Ilya Shmulevich, and Lodewyk F. A. Wessels. Logic models to predict continuous outputs based on binary inputs with an application to personalized cancer therapy. *Scientific Reports*, 6(1):36812, 2016.

[42] Ron Kohavi and George H. John. Wrappers for feature subset selection. *Artificial Intelligence*, 97(1):273–324, 1997.

[43] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[44] Ismael Lemhadri, Feng Ruan, and Rob Tibshirani. LassoNet: Neural networks with feature sparsity. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2021.

[45] Chad Leugers, Ju Yong Koh, Willis Hong, and Gloria Lee. Tau in MAPK activation. *Frontiers in Neurology*, 4, 2013.

[46] Xinghua Li, Weijiang Liang, Junling Liu, Chuyong Lin, Shu Wu, Libing Song, and Zhongyu Yuan. Transducin (β)-like 1 X-linked receptor 1 promotes proliferation and tumorigenicity in human breast cancer via activation of beta-catenin signaling. *Breast Cancer Research*, 16(5):465, 2014.

[47] Yifeng Li Li, Chih-Yu Chen, and Wyeth W. Wasserman. Deep feature selection: theory and application to identify enhancers and promoters. *Journal of Computational Biology*, 23(5):322–336, 2016.

[48] Faming Liang, Qizhai Li, and Lei Zhou. Bayesian neural networks for selection of drug sensitive genes. *Journal of the American Statistical Association*, 113(523):955–972, 2018.

[49] Ofir Lindenbaum, Uri Shaham, Erez Peterfreund, Jonathan Svirsky, Nicolas Casey, and Yuval Kluger. Differentiable unsupervised feature selection based on a gated laplacian. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[50] Huan Liu and Rudy Setiono. A probabilistic approach to feature selection - a filter solution. In *International Conference on Machine Learning (ICML)*, 1996.

[51] Ying Liu and Cheng Zheng. Deep latent variable models for generating knockoffs. *Stat*, 8(1):e260, 2019.

[52] Huanyu Lu, Yue Guo, Gaurav Gupta, and Xingsong Tian. Mitogen-activated protein kinase (MAPK): New insights in breast cancer. *Journal of Environmental Pathology, Toxicology and Oncology*, 38(1):51–59, 2019.

[53] Chris J. Maddison, Andriy Mnih, and Yee Whye Teh. The Concrete distribution: A continuous relaxation of discrete random variables. In *International Conference on Learning Representations (ICLR)*, 2017.

[54] Ramamurthy Mani, Robert P. St.Onge, John L. Hartman, Guri Giaever, and Frederick P. Roth. Defining genetic interaction. *Proceedings of the National Academy of Sciences*, 105(9):3461–3466, 2008.

[55] Pulak R. Manna, Ahsen U. Ahmed, Shengping Yang, Madhusudhanan Narasimhan, Joëlle Cohen-Tannoudji, Andrzej T. Slominski, and Kevin Pruitt. Genomic profiling of the steroidogenic acute regulatory protein in breast cancer: In silico assessments and a mechanistic perspective. *Cancers*, 11(5), 2019.

[56] Kevin McCloskey, Ankur Taly, Federico Monti, Michael P. Brenner, and Lucy J. Colwell. Using attribution to decode binding mechanism in neural network models for chemistry. *Proceedings of the National Academy of Sciences*, 116(24):11624–11629, 2019.

[57] Sofia Papadimitriou, Andrea Gazzo, Nassim Versbraegen, Charlotte Nachtegael, Jan Aerts, Yves Moreau, Sonia Van Dooren, Ann Nowé, Guillaume Smits, and Tom Lenaerts. Predicting disease-causing variant combinations. *Proceedings of the National Academy of Sciences*, 116(24):11878–11887, 2019.

[58] Ui-Hyun Park, Mi Ran Kang, Eun-Joo Kim, Young-Soo Kwon, Wooyoung Hur, Seung Kew Yoon, Byoung-Joon Song, Jin Hwan Park, Jin-Taek Hwang, Ji-Cheon Jeong, and Soo-Jong Um. ASXL2 promotes proliferation of breast cancer cells by linking ERα to histone methylation. *Oncogene*, 35(28):3742–3752, 2016.

[59] Hanna M. Peltonen, Annakaisa Haapasalo, Mikko Hiltunen, Vesa Kataja, Veli-Matti Kosma, and Arto Mannermaa. Γ-secretase components as predictors of breast cancer outcome. *PLOS ONE*, 8(11), 2013.

[60] Bernard Pereira, Suet-Feung Chin, Oscar M. Rueda, Hans-Kristian Moen Vollan, Elena Provenzano, Helen A. Bardwell, Michelle Pugh, Linda Jones, Roslin Russell, Stephen-John Sammut, Dana W. Y. Tsui, Bin Liu, Sarah-Jane Dawson, Jean Abraham, Helen Northen, John F. Peden, Abhik Mukherjee, Gulisa Turashvili, Andrew R. Green, Steve McKinney, Arusha Oloumi, Sohrab Shah, Nitzan Rosenfeld, Leigh Murphy, David R. Bentley, Ian O. Ellis, Arnie Purushotham, Sarah E. Pinder, Anne-Lise Børresen-Dale, Helena M. Earl, Paul D. Pharoah, Mark T. Ross, Samuel Aparicio, and Carlos Caldas. The somatic mutation profiles of 2,433

breast cancers refine their genomic and transcriptomic landscapes. *Nature Communications*, 7(1):11479, 2016.

[61] Patrick C. Phillips. Epistasis — the essential role of gene interactions in the structure and evolution of genetic systems. *Nature Reviews Genetics*, 9(11):855–867, 2008.

[62] Michael W. Pickup, Laura D. Hover, Eleanor R. Polikowsky, Anna Chytil, Agnieszka E. Gorska, Sergey V. Novitskiy, Harold L. Moses, and Philip Owens. BMPR2 loss in fibroblasts promotes mammary carcinoma metastasis via increased inflammation. *Molecular Oncology*, 9(1):179–191, 2015.

[63] Barbara Maria Piskór, Andrzej Przylipiak, Emilia Dąbrowska, Iwona Sidorkiewicz, Marek Niczyporuk, Maciej Szmitkowski, and Sławomir Ławicki. Plasma level of MMP-10 may be a prognostic marker in early stages of breast cancer. *Journal of Clinical Medicine*, 9(12), 2020.

[64] Franck Rapaport, Emmanuel Barillot, and Jean-Philippe Vert. Classification of arrayCGH data using fused SVM. *Bioinformatics*, 24(13):i375–i382, 2008.

[65] Yaniv Romano, Matteo Sesia, and Emmanuel Candès. Deep knockoffs. *Journal of the American Statistical Association*, 115(532):1861–1872, 2020.

[66] Benjamin Sanchez-Lengeling, Jennifer Wei, Brian Lee, Emily Reif, Peter Wang, Wesley Qian, Kevin McCloskey, Lucy Colwell, and Alexander Wiltschko. Evaluating attribution for graph neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[67] Fadil Santosa and William W. Symes. Linear inversion of band-limited reflection seismograms. *SIAM Journal on Scientific and Statistical Computing*, 7(4):1307–1330, 1986.

[68] Razieh Sheikhpour, Mehdi Agha Sarram, Sajjad Gharaghani, and Mohammad Ali Zare Chahooki. A survey on semi-supervised feature selection methods. *Pattern Recognition*, 64:141–158, 2017.

[69] Prajjal K. Singha, Srilakshmi Pandeswara, Hui Geng, Rongpei Lan, Manjeri A. Venkatachalam, Albert Dobi, Shiv Srivastava, and Pothana Saikumar. Increased smad3 and reduced smad2 levels mediate the functional switch of TGF-β from growth suppressor to growth and metastasis promoter through TMEPAI/PMEPA1 in triple negative breast cancer. *Genes & cancer*, 10(5-6):134, 2019.

[70] Mukund Sudarshan, Wesley Tansey, and Rajesh Ranganath. Deep direct likelihood knockoffs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[71] Mina Takahashi, Fumio Otsuka, Tomoko Miyoshi, Hiroyuki Otani, Junko Goto, Misuzu Yamashita, Toshio Ogura, Hirofumi Makino, and Hiroyoshi Doihara. Bone morphogenetic protein 6 (BMP6) and BMP7 inhibit estrogen-induced proliferation of breast cancer cells by suppressing p38 mitogen-activated protein kinase activation. *Journal of Endocrinology*, 199(3):445 – 455, 2008.

[72] Jiliang Tang, Salem Alelyani, and Huan Liu. Feature selection for classification: A review. *Data classification: Algorithms and applications*, page 37, 2014.

[73] Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.

[74] Nicholas Turner, Alex Pearson, Rachel Sharpe, Maryou Lambros, Felipe Geyer, Maria A. Lopez-Garcia, Rachael Natrajan, Caterina Marchio, Elizabeth Iorns, Alan Mackay, Cheryl Gillett, Anita Grigoriadis, Andrew Tutt, Jorge S. Reis-Filho, and Alan Ashworth. FGFR1 amplification drives endocrine therapy resistance and is a therapeutic target in breast cancer. *Cancer Research*, 70(5):2085–2094, 2010.

[75] Dongfeng Wang, Jian Li, Fengling Cai, Zhi Xu, Li Li, Huanfeng Zhu, Wei Liu, Qingyu Xu, Jian Cao, Jingfeng Sun, and Jinhai Tang. Overexpression of MAPT-AS1 is associated with better patient survival in breast cancer. *Biochemistry and Cell Biology*, 97(2):158–164, 2019.

[76] Dongsheng Wang, Chenglong Zhao, Liangliang Gao, Yao Wang, Xin Gao, Liang Tang, Kun Zhang, Zhenxi Li, Jing Han, and Jianru Xiao. NPNT promotes early-stage bone metastases in breast cancer by regulation of the osteogenic niche. *Journal of Bone Oncology*, 13:91–96, 2018.

[77] Chang-Yuan Wei, Qi-Xing Tan, Xiao Zhu, Qing-Hong Qin, Fei-Bai Zhu, Qin-Guo Mo, and Wei-Ping Yang. Expression of CDKN1A/p21 and TGFBR2 in breast cancer and their prognostic significance. *International Journal of Clinical and Experimental Pathology*, 8(11):14619, 2015.

[78] Michael K. Wendt, Molly A. Taylor, Barbara J. Schiemann, Khalid Sossey-Alaoui, and William P. Schiemann. Fibroblast growth factor receptor splice variants are stable markers of oncogenic transforming growth factor $\beta 1$ signaling in metastatic breast cancers. *Breast Cancer Research*, 16(2):R24, 2014.

[79] Tim Wilson, Tim Holt, and Trisha Greenhalgh. Complexity and clinical care. *BMJ*, 323(7314):685–688, 2001.

[80] Xinxing Wu and Qiang Cheng. Algorithmic stability and generalization of an unsupervised feature selection algorithm. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[81] Yutaro Yamada, Ofir Lindenbaum, Sahand Negahban, and Yuval Kluger. Feature selection using stochastic gates. In *International Conference on Machine Learning (ICML)*, 2020.

[82] Ming Yuan and Yi Lin. Model selection and estimation in regression with grouped variables. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 68(1):49–67, 2006.

[83] Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Ruslan Salakhutdinov, and Alexander Smola. Deep sets. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[84] Lingmin Zeng and Jun Xie. Group variable selection via SCAD-L2. *Statistics*, 48(1):49–66, 2014.

[85] Xin-Yue Zhang, Hsun-Ming Chang, Elizabeth L. Taylor, Rui-Zhi Liu, and Peter C. K. Leung. BMP6 downregulates GDNF expression through SMAD1/5 and ERK1/2 signaling pathways in human granulosa-lutein cells. *Endocrinology*, 159(8):2926–2938, 2018.

[86] Yong-ping Zhang, Wen-ting Na, Xiao-qiang Dai, Ruo-fei Li, Jian-xiong Wang, Ting Gao, Wei-bo Zhang, and Cheng Xiang. Over-expression of SRD5A3 and its prognostic significance in breast cancer. *World Journal of Surgical Oncology*, 19(1):260, 2021.

[87] Jidong Zhao, Ke Lu, and Xiaofei He. Locality sensitive semi-supervised feature selection. *Neurocomputing*, 71:1842—-1849, 2008.

[88] Ting Zhong, Feifei Xu, Jinhui Xu, Liang Liu, and Yun Chen. Aldo-keto reductase 1C3 (AKR1C3) is associated with the doxorubicin resistance in human breast cancer via PTEN loss. *Biomedicine & Pharmacotherapy*, 69:317–325, 2015.

[89] Nengfeng Zhou and Ji Zhu. Group variable selection via a hierarchical lasso and its oracle property. *arXiv preprint arXiv:1006.2871*, 2010.

[90] Guangyu Zhu and Tingting Zhao. Deep-gKnock: Nonlinear group-feature selection with deep neural networks. *Neural Networks*, 135:139–147, 2021.