Physically Consistent 3D Reconstruction of Multiple Interacting Humans from Weak Supervision

Abstract

The three-dimensional reconstruction of multiple interacting humans given a monocular image is crucial for the general task of scene understanding, as often capturing the subtleties of interaction is the very reason for taking a picture. Current 3D human reconstruction methods either treat each person independently, ignoring most of the context, or reconstruct people jointly, but cannot recover interactions correctly when people are in close proximity. In this work, we propose models that learn to reconstruct a variable number of people directly from monocular images. At the core of our methodology stands a novel transformer network that combines person detection responses and multiple learnable visual image features, each encoded as one token. We introduce novel self-collision and interpenetration-collision losses based on a mesh approximation computed by applying decimation operators and rely on self-supervised losses for flexibility and generalisation in-the-wild. We also incorporate self-contact and interaction-contact losses directly into the learning process. We report state-of-the-art quantitative results on common benchmarks even in cases where no 3D supervision is used. Additionally, qualitative visual results show that our reconstructions are plausible in terms of pose and shape and coherent for challenging images, collected in-the-wild, where people are often interacting.

1   Introduction

Reconstructing three-dimensional models of multiple interacting people from images is an important computer vision task with applications in behavior analysis, automatic video analysis of sport events, or collaborative augmented reality applications. As the demands on the depth of analysis increase, beyond qualitative pose, one often seeks to know whether people are in contact or not, what is the nature of that contact, and how long it lasts. As such questions become important, it is clear that very coarse estimates of pose or even shape are no longer sufficient. One needs accurate models of shape and contact with predictable response over time. This is difficult due to the various degree of occlusion that occur, the depth ambiguities particularly given only monocular images (but more generally given that occlusion and self-occlusion for people are frequent), the high degree of variability of even valid human poses, their different scales and underlying spatial image support, ranging from the large body parts like torso or thighs – informed by larger image regions – to hands, with parts typically accounted for by smaller spatial support, comparatively.

Most of the volumetric human pose and shape recovery methods focus on a single person and require detecting the humans in the image and then running the inference model on each positive response. This approach has achieved good results and scales linearly in the number of people in the scene. There are multi people reconstruction methods which either predict 3D pose only and deffer the shape reconstruction step to a later optimization step[1] or rely on an orthographic camera model

[2]. However, it is nontrivial to obtain a realistic 3D scene placement for all the reconstructed human models, so their 3D spatial relations are plausible, and the alignment with the image evidence is good. All aforementioned methods train using full 3D supervision coming from mocap datasets. However, this often lacks scenarios of interactions or fine grained self contact. Recent work such as [3, 4] designed datasets for interaction analysis, with additional interaction signature annotations, and showed that models able to represent those produce more realistic reconstructions. However, they only work in an optimization framework and reconstruct only pairs of people in close interaction. Ideally one would like to be able to precisely model contacts, rely on attention models to identify the important element of interaction, have a framework that can accommodate more than two people and learn such models from data, using only weak supervision.

Our main contributions can be summarized as proposing the following:

- Fast and accurate 3d self collision and interpenetration models for multiple people.

- A novel vision transformer architecture to predict 3D pose and shape for multiple people.

- Weakly supervised models which do not require 3D annotations during training.

- State of the art results on challenging datasets, with favorable performance compared to competing predictive or optimization-based methods.

We propose a hybrid convolutional-transformer where the output of a human detector is combined with high-level convolutional image features. Our prediction is processed by a series of transformer encoder layers that iteratively refine the 3D pose and shape reconstruction estimates for all detected humans in the scene. Decoupling the detection component has the advantage of benefiting from innovations in that space without necessarily paying a performance cost. Multi people 2D human detection models are already quite fast, running close to real time and providing accurate results. Similar to [5] we use a full perspective camera model, which allows us to infer translations for all reconstructed humans in the same camera coordinate system. We propose novel interpenetration and self-collision losses that are amenable to a deep-learning-based training process and work in a weakly-supervised regime.

2 Related Work

The field of 3D human pose and shape reconstruction from images has received increasing attention in recent years. This has been driven by progress in 3D statistical and articulated human body models [6, 7] and advances in 2D [8, 9, 10] and 3D [1, 11] pose estimation. Most reconstruction methods focus on estimating the 3D pose and shape of a single person [5, 12, 13, 14, 15] although, more recently, several papers focused on reconstructing multiple people coherently [2, 16, 1].

Recent work started focusing on modeling inter-human contact [3] or self-contact [4, 17] developing methodology for more principled, contact aware reconstructions and releasing datasets with ground truth interaction [3] and self contact annotations [4]. We use these datasets in our training and evaluation pipeline and with various supervision signals.

Physically plausible human mesh reconstructions require self-collision avoidance for single and multiple interacting people. Prior work related to self-collisions [18, 19, 20, 21] rely on bounding volume hierarchies [22] to detect the set of colliding triangles. We propose novel, efficient and faster human mesh collision losses which are more appropriate for deep learning training pipelines. See §3.4 and our supplementary material for more details.

Advances in differentiable mesh rendering techniques [23, 24, 25] have enabled better image alignment losses [12, 5] and provide better depth supervision signals [2], leading overall to improved automated 3D scene reasoning. Recent innovations in the space of visual transformers [26, 27] have increased the capabilities of neural network architectures for handling image features, and their ability to produce accurate reconstructions for images in-the-wild.

3 Methodology

3.1 Statistical 3D Human Body Models

We use a recently introduced statistical articulated 3D human body model called GHUM [6], to represent the pose and the shape of the human body. The model has been trained end-to-end, in a deep learning framework, using a large corpus of human shapes and motions. The model has generative body shape and facial expressions $\boldsymbol{\beta} = (\boldsymbol{\beta}_b, \boldsymbol{\beta}_f)$ represented using deep variational auto-encoders and generative pose $\boldsymbol{\theta} = (\boldsymbol{\theta}_b, \boldsymbol{\theta}_{lh}, \boldsymbol{\theta}_{rh})$ for the body, left and right hands, respectively, represented as normalizing flows [12]. The pelvis translation and rotation are controlled separately, and represented by a 6D rotation [28] $\mathbf{r} \in \mathbb{R}^{6 \times 1}$ and a translation vector $\mathbf{t} \in \mathbb{R}^{3 \times 1}$ w.r.t the origin $(0, 0, 0)$. The GHUM mesh, $\mathbf{M} = (\mathbf{V}, \mathbf{F})$, consists of a set of vertices $\mathbf{V} \in \mathbb{R}^{10168 \times 3}$ and a set of facets $\mathbf{F} \in \mathbb{R}^{20332 \times 3}$. In experiments we infer the GHUM parameters $(\boldsymbol{\theta}_b, \boldsymbol{\beta}_b, \mathbf{r}, \mathbf{t})$ omitting facial expression parameters $\boldsymbol{\beta}_f$ and the left and right hand pose parameters $\boldsymbol{\theta}_{lh}, \boldsymbol{\theta}_{rh}$, as we focus only on reconstructing the body pose and shape. We also drop the b subscript for convenience.

3.2 Camera Model

We use a perspective projection operator Π characterized by camera intrinsics $\mathbf{C} = [f_x, f_y, c_x, c_y]$ which assumes that the camera coordinate system is aligned with the world reference frame using an identity extrinsic rotation matrix and zero translation. This corresponds to a left handed coordinate system with positive z values forward. All predictions are made in the camera coordinate system. When processing the camera intrinsics for a crop we use the same approach as in [5].

3.3 Architecture

In fig. 1 we show an overview of our proposed hybrid learning architecture for monocular multi-person 3D body pose and shape estimation. We draw inspiration from vision transformers [26], as we also use a hybrid convolutional-transformer architecture, and from [5], as we explore the idea of iteratively refining estimates by relying on cascaded, input-sensitive processing blocks, with homogeneous parameters, as an end-to-end learnable surrogate for non-linear optimization.

Our network receives as input an image $\mathbf{I} \in \mathbb{R}^{W \times H \times 3}$ containing multiple people, together with the pseudo ground-truth camera intrinsics $\mathbf{C} \in \mathbb{R}^{1 \times 4}$ of the image (see § 3.2). We apply a convolutional neural network (CNN) on the input image and extract a downsampled feature map representation $\mathbf{F} \in \mathbb{R}^{\frac{W}{32} \times \frac{H}{32} \times D}$. We flatten the feature map along the spatial dimensions to get a sequence of $N = \frac{W}{32} \times \frac{H}{32}$ tokens. This sequence is linearly embedded by means of matrix $\mathbf{E} \in \mathbb{R}^{D \times D'}$, where D' is the embedding dimensionality. Next, learnable positional embeddings $\mathbf{E}_{pos} \in \mathbb{R}^{N \times D'}$ are added to the sequence. In addition to image feature tokens, we also use a sequence of $N_P = 16$ maximum tokens for the people in the image. We first run an off-the-shelf human detector on the input image and collect the bounding box coordinates for each person index p, $\mathbf{b}^p \in \mathbb{R}^{1 \times 4}$. For each person p, we compute its initial GHUM parameters $\mathbf{s}_0^p = \{\boldsymbol{\theta}_0, \boldsymbol{\beta}_0, \mathbf{r}_0, \mathbf{t}_0^p\}$ where we compute the translation such that the default GHUM mesh projects in the center of the corresponding bounding box $\mathbf{b}^p$. We denote by $\mathbf{S}_0 = [\mathbf{s}_0^1, \dots \mathbf{s}_0^{N_P}]$ the initial state of GHUM parameters for all the people in the image. For each person, we concatenate the bounding person coordinates, the initial GHUM state and the camera intrinsics and construct the sequence of tokens corresponding to the persons in the image $\mathbf{P} \in \mathbb{R}^{N_P \times D_P}$. We linearly project the people token sequence $\mathbf{P}$ by means of matrix $\mathbf{E}_P \in \mathbb{R}^{D_P \times D'}$. The two sequences of tokens are concatenated into a single input sequence $\mathbf{Z}_0$ and iteratively transformed through a single transformer encoder layer [27], TL, for a number of L steps. We collect at each step $l \in \{1 \dots L\}$ a refinement update $\Delta \mathbf{S}_l$ from each transformed representation $\mathbf{Z}_l$, using a shared MLP applied on the corresponding transformed representation of the people token sequence.

$$\mathbf{Z}_0 = [\mathbf{F}_s \mathbf{E} + \mathbf{E}_{pos}, \mathbf{P} \mathbf{E}_P] \tag{1}$$

$$\mathbf{Z}_l = TL(\mathbf{Z}_{l-1}) \tag{2}$$

$$\Delta \mathbf{S}_l = MLP(\mathbf{Z}_l^{N:N+N_P}). \tag{3}$$

The refinement updates $\Delta \mathbf{S}_l$ are added to the initial state GHUM parameters, $\mathbf{S}_0$, as

$$\mathbf{S}_L = \mathbf{S}_0 + \lambda \Sigma_{l=1}^L \Delta \mathbf{S}_l \tag{4}$$

Figure 1: Overview of our proposed architecture to reconstruct the 3D pose and shape of multiple interacting people. Starting from a single input image, we use an off-the-shelf detector to extract the human bounding boxes. We create a sequence of person tokens from these detections to which we attach an initial GHUM state estimate $\mathbf{S}_0$. On a separate branch, starting from the image, we run a backbone convolutional neural network architecture and create an additional sequence of spatial image feature tokens, $\mathbf{F}_s$. We concatenate the two sequence representations and iteratively refine this joint representation through a single transformer encoder layer for a number of L stages. At the end of each stage l, we collect the transformed representation for the token sequence associated with the people and apply an MLP to regress the residual GHUM state estimates $\Delta\mathbf{S}_l$. Our final estimation is given by the weighted sum of all the residual state updates and the initial state. The network is trained weakly-supervised on various datasets with 2D annotations. We use contact and collision losses defined over the recovered geometries to ensure physical plausibility.

where $\mathbf{S}_L = \{\boldsymbol{\Theta}_L, \mathbf{B}_L, \mathbf{R}_L, \mathbf{T}_L\}$ are the final GHUM parameter estimates for all the people detected in the image and λ is a weighting term for the residual estimates.

We train the network by optimizing the following loss function:

$$\mathcal{L} = \mathcal{L}_{sc} + \mathcal{L}_{ic} + \mathcal{L}_{ics} + \mathcal{L}_{scs} + \mathcal{L}_d + \mathcal{L}_{ka} + \mathcal{L}_\theta + \mathcal{L}_\beta \tag{5}$$

where the first 5 loss terms correspond to the physical plausibility of the reconstructed meshes as follows: $\mathcal{L}_{sc}$ and $\mathcal{L}_{ic}$ are the self-collision loss and the interpenetration loss, respectively; $\mathcal{L}_{ics}$ and $\mathcal{L}_{scs}$ correspond to the supervised self-contact [4] and interaction-contact [3] losses; $\mathcal{L}_d$ is the depth-aware ordering loss from [2]. These losses are discussed and explained in more detail in subsequent sections.

We use a standard **keypoint alignment loss**, $\mathcal{L}_{ka}$, that measures the error between the 3D joints from the GHUM reconstructions, projected onto the image plane, $\mathbf{J} = \{\mathbf{J}_i\}_{i=1,\dots,K}$, and the available 2D keypoints annotations in the image $\{\mathbf{j}_i\}_{i=1,\dots,K}$

$$\mathcal{L}_{ka} = \frac{1}{K} \sum_{i=1}^{K} \|\mathbf{j}_i - \Pi\left(\mathbf{J}_i, \mathbf{C}\right)\|_2^2. \tag{6}$$

140 Note that for some datasets we do not have 2D pose annotations available. In that case we supervise
141 with the predictions of an off-the-shelf 2D pose estimator.

142 For **body shape and pose**, we use regularization losses:

$$\mathcal{L}_\theta = \|\boldsymbol{\theta}\|_2^2, \ \ \mathcal{L}_\beta = \|\boldsymbol{\beta}\|_2^2. \tag{7}$$

3.4 Physical Collision for GHUM

144 In our methodology, we use an approximation for the GHUM mesh topology, which we denote
145 by $\hat{\mathbf{M}} = (\hat{\mathbf{V}}, \hat{\mathbf{F}})$. This mesh topology is obtained by applying decimation operators on the default
146 GHUM model resulting in a mesh with $N_{\hat{v}} = 512$ vertices and $N_{\hat{t}} = 1020$ triangles. We refer to this
147 low resolution approximation of the GHUM mesh as PHUM. As $\hat{\mathbf{V}}$ is a subset of the GHUM vertices,
148 this easily allows the PHUM mesh to be reposed and reshaped with respect to the underlying GHUM
149 mesh it approximates. The ICP loss of our approximation (*i.e.* for each vertex on the GHUM mesh not
150 included in PHUM, we compute the distance to the closest point on the PHUM surface) is of 2.8mm.
151 By using PHUM, we drastically reduce the computation cost of our proposed self-collision and
152 interpenetration losses as they are quadratic in the number of vertices. We use generalized winding
153 numbers [29] to rapidly test whether 3D points are inside/outside relative to a closed mesh topology.

154 **Self-collision loss**   Given a GHUM mesh, $\mathbf{M}$, we compute its PHUM approximation $\hat{\mathbf{M}}$. We apply
155 the generalized winding number test $L = \phi_{\hat{\mathbf{M}}}(\hat{\mathbf{V}})$ on its set of vertices $\hat{\mathbf{V}}$, with respect to its own
156 mesh topology $\hat{\mathbf{M}}$ and gather the binary inside/outside labeling $L \in \{0, 1\}^{N_{\hat{v}} \times 1}$. The vertices marked
157 as inside, $\hat{\mathbf{V}}_{L_+}$, with $L_+ = \{l \in L : l = 1\}$, are pushed out of the mesh in the direction of their
158 nearest neighbor vertices, $\text{NN}(\hat{\mathbf{V}}_{L_+}, \hat{\mathbf{M}})$:

$$\mathcal{L}_{sc} = \sum_{l \in L_+} \|\hat{\mathbf{V}}_l - \text{NN}(\hat{\mathbf{V}}_l, \hat{\mathbf{M}})\|_2 \tag{8}$$

159 The nearest neighbors are extruded outside the mesh by a small amount (*i.e.* 5mm) in the direction of
160 their normal before computing the loss, such that inside vertices get pushed outside the mesh. For the
161 GHUM mesh, we have body part labeling information available which is transferred onto PHUM.
162 That is, for each vertex in the mesh we have its associated body part label class from a total of 14
163 body parts. When computing a nearest neighbor vertex we either consider vertices that are exterior or
164 on another body part than the query vertex, and we choose the one with the smallest distance. The
165 body part labeling allows us to avoid situations where an interior vertex can choose to exit the mesh
166 geometry through a vertex from the same body part as itself.

167 **Interpenetration loss**   Interpenetration is straightforward to handle by our representation. Given
168 a pair of meshes $\hat{\mathbf{M}}_1$ and $\hat{\mathbf{M}}_2$, we compute the generalized winding number test for both $L_1 = $
169 $\phi_{\hat{\mathbf{M}}_2}(\hat{\mathbf{V}}_1)$ and $L_2 = \phi_{\hat{\mathbf{M}}_1}(\hat{\mathbf{V}}_2)$. The loss is then given by:

$$\mathcal{L}_{ic} = \sum_{l \in L_{1+}} \|\hat{\mathbf{V}}_{1,l} - \text{NN}(\hat{\mathbf{V}}_{1,l}, \hat{\mathbf{M}}_2)\|_2 + \sum_{l \in L_{2+}} \|\hat{\mathbf{V}}_{2,l} - \text{NN}(\hat{\mathbf{V}}_{2,l}, \hat{\mathbf{M}}_1)\|_2 \tag{9}$$

170 This time, when we compute the nearest neighbor for inside vertices of a mesh, we query from all
171 vertices in the colliding mesh.

172 **Relation to Prior Work**   Whereas in our formulation self-collision and interpenetration collision
173 are handled based on a common representation, in the literature different approaches are popular for
174 each type of collision. For self-collision, most related work [18, 19, 20, 21] uses bounding volume
175 hierarchies (BVH) [22] to detect a list of colliding triangles. Using local conic 3D distance fields,
176 penetrations are penalized by the depth of the intrusion. The run time of just BVH collision detection
177 is around 2.5ms for a single mesh, while the run time of our full self-collision loss, including the
178 generalized winding number computation ϕ, is significantly faster, around 2ms (1 mesh per batch
179 size in this test). Differently from the BVH implementation, we did not write any custom CUDA
180 kernel, but instead rely on standard TensorFlow [30] operations with batch support.

181 For interpenetration collision, the most popular approach [21, 2] is to first voxelize the two meshes
182 and then compute a signed distance field (SDF) for each of them. The SDF of each mesh is queried

by the vertices of the other mesh to compute the loss. The voxelization step takes around 45ms for a mesh and the SDF computation is implemented using a custom CUDA kernel. The running time is more than an order of magnitude higher than our generalized winding number computation and has a considerably more complex implementation.

3.5 Depth-Ordering Loss

We follow the same procedure as in [2] to train using a depth-ordering loss. We use ground-truth instance segmentation masks from COCO [31] during training. For our differentiable mesh rasterizer we use DIRT [24] to render the depth maps, D_k, for each person. We use the depth ordinal loss:

$$\mathcal{L}_d = \sum_{p \in S} \log(1 + \exp(D_{y(p)}(p) - D_{\hat{y}(p)}(p))) \tag{10}$$

where $S = \{p \in I : y(p) > 0, \hat{y}(p) > 0, y(p) \neq \hat{y}(p)\}$, I is the RGB image, $y(p)$ is the index of the person occupying pixel p and $\hat{y}(p)$ is the ground-truth index of the person occupying pixel p.

3.6 Contact Losses

Similarly to [3, 4] we employ contact losses when ground truth annotations are available. For a pair of people, P_1, P_2, in contact in an image I, we define the contact signature $C_{ics}(I, P_1, P_2)$ at the *facet* level [3] as a matrix where $C_{ics}^{f_1,f_2}(I, P_1, P_2) = 1$ if facet $f_1 \in \mathbf{M}(P_1)$ is in contact with facet $f_2 \in \mathbf{M}(P_2)$ and 0 otherwise where $\mathbf{M}(P)$ is the mesh corresponding to person P. The distance between two facets f_1 and f_2 is defined as the Euclidean distance $d(f_1, f_2)$ between the centers of the two facets [3]. We define the following interaction-contact signature loss

$$\mathcal{L}_{ics}(I, P_1, P_2) = \sum_{f_1 \in \mathbf{M}(P_1), f_2 \in \mathbf{M}(P_2)} C_{ics}(I, P_1, P_2) d(f_1, f_2) \tag{11}$$

In a similar fashion, the self contact signature $C_{scp}(I, P)$ [4] of a person P in an image I is defined as $C_{scp}(I, P) = C_{ics}(I, P, P)$, where $C_{scp}^{f_1,f_2}(I, P) = 1$ if facet $f_1 \in \mathbf{M}(P)$ is in contact with facet $f_2 \in \mathbf{M}(P)$. Subsequently, the self-contact signature loss is defined as

$$\mathcal{L}_{scs}(I, P) = \sum_{f_1 \in \mathbf{M}(P), f_2 \in \mathbf{M}(P)} C_{scp}(I, P) d(f_1, f_2) \tag{12}$$

In practice, contact signature matrices are sparse (have less than 100 non zero values) so the computation of $\mathcal{L}_{ics}$ and $\mathcal{L}_{scp}$ while training our models is efficient.

4 Experiments

In this section we offer implementation details regarding the network architectures and training hyperparameters, we describe the datasets used for training and evaluating our models and we present state of the art results on the challenging **Panoptic** [32] and **CHI3D** [3] datasets as well as ablation studies illustrating the importance of each of our proposed losses.

4.1 Implementation details

For all our models we use a ResNet50 [33] backbone pretrained on ImageNet [34]. The network has a total number of 26M parameters, out of which 23M parameters for the backbone and 3M parameters for the transformer layers. We use $L = 4$ stages, an embedding size of 512 and 8 heads for the MultiHeadAttention layer. The network is trained for 150 epochs with a batch size of 32, starting learning rate of $1e - 4$ and exponential decay of 0.98. Our code is implemented in TensorFlow and we employ random scaling, rotation, horizontal flipping and cropping augmentations during training. All images are resized to (480×480) while preserving the original aspect ratio using padding when necessary. All networks are trained on a single V100 GPU with 32GB of memory.

4.2 Datasets

In our experiments, we train weakly supervised on various datasets with 2D supervision in the form of annotated body joints and instance segmentation masks. For some models we use 3D self-contact and person-to-person contact supervision. Each dataset usually contains only a subset of annotation types, so we employ the corresponding losses accordingly.

MPII [35] is an indoor/outdoor image dataset which includes 25K images containing multiple people with approximately 40K 2D pose annotations. We used this dataset only for training using a subset of 10k images.

PoseTrack [36] is an in-the-wildd dataset containing 1.3K video sequences with 2D poses for multiple people annotated across multiple frames. We used the trainval subset of this dataset for training our models selecting a subset of 25K images and 160K 2D pose annotations.

LSP [37] and **LSP Extended** [38] are in-the-wild datasets with single person 2D pose annotations. We used the training subsets consisting of approximately 1K, respectively 10K images with ground truth 2D pose annotations.

COCO [31] is a dataset containing 40K images with multiple people. In total 100K annotated poses were used for training our models. Similarly to [2] the instance person segmentation masks were used for computing the depth-ordering loss, in training only.

FlickrCI3D [3] and **FlickrSC3D** [4] contain in-the-wild images with multiple people engaged in various activities involving human interactions and self contacts. Ground truth interactions and self contact annotations are available for this dataset at facet granularity. These datasets have no annotations for 2D keypoints, so we generate them by running a 2D human pose predictor on each of the images to obtain pseudo ground-truth 2D pose annotations. We use a total of 15K images with more than 25K interactions or self contact annotations for training.

We evaluate on two datasets with ground-truth 3D. We do not train our method on any images from these datasets.

The **Panoptic** studio [32] is an indoor multiple people dataset captured in a multi-view laboratory system. We use the same data selection as in [16, 2] resulting in 9.6K images containing ground truth 3D pose for multiple people in each image. We use this dataset for evaluation purposes only.

CHI3D [3] is an indoor dataset with 3D ground truth joints from mocap containing images from 631 sequences and 4 cameras. Each sequence contains 2 people in various interactions and contact ground-truth annotations exist for each image. We use this dataset for evaluation purposes only.

4.3 Results

We start the evaluation of our models on the challenging **Panoptic** [32] dataset. We follow the evaluation protocol from [16, 1, 2] (without training on any data from the **Panoptic** dataset). We present state of the art results in table 1 showing that our models perform better than other optimization-[16] or inference-based multiple people methods [1, 2].

Method	Haggling	Mafia	Ultimate	Pizza	Mean
Zanfir *et al.* [16]	140.0	165.9	150.7	156.0	153.4
Zanfir *et al.* [1]	141.4	152.3	145.0	162.5	150.3
Jiang *et al.* [2]	129.6	**133.5**	153.0	156.7	143.2
Ours	**121.6**	137.1	**146.4**	**148.0**	**138.3**

Table 1: Performance on the **Panoptic** [32] dataset for pose and shape reconstruction methods focusing on multiple people. All errors represent mean per joint position errors and are reported in mm, relative to the root joint. The evaluation protocol is the same as the one in [16, 1, 2]. Our model achieves lower error compared to optimization- or learning-based approaches.

We continue our evaluation on the **CHI3D** [3] dataset. We did not use this dataset during training. It is formed of sequences of 2 persons performing various actions and ground-truth mocap markers are available only for one of them. We use the same evaluation protocol as in Fieraru *et al.* [3] and we compute the 3D joint error for the prediction which has the highest 2D bounding box overlap with the ground truth. In table 2 we present state of the art results where we compare again against

optimization [3] and inference only [2] methods. We used the publicly available repository when running the model from [2] on the **CHI3D** [3] dataset.

Method		MPJPE	MPVPE	Translation Error	#2D	#3D
Fieraru *et al.* [3]		125.4	–	368.0	N/A	N/A
Jiang *et al.* [2]		136.0	N/A	N/A	100K	300K
Ours (all)		**120.8**	**134.7**	**284.1**	115K	0

Table 2: Performance on the **CHI3D** [3] dataset for multiple person pose and shape reconstruction methods. In columns 2, 3, 4 we show the mean per joint position error (**MPJPE**), the mean per vertex position error (**MPVPE**) and the translation error. All errors are reported in mm and are relative to the root joint. Our method has lower errors compared to the other optimization and inference based methods. We also compare the number of **#2D** and **#3D** annotations used as supervision during the training of the different models. Our models use no **#3D** and achieve better performance on the challenging dataset **CHI3D** [3].

In table 3 we present a series of ablations on the **CHI3D** [3] dataset for the loss components in eq. 5 used during training. The lowest error is achieved when using all of the introduced losses, which supports their individual importance.

Method		MPJPE	MPVPE
Ours (w/o $\mathcal{L}_{ic}$)		122.7	134.9
Ours (w/o $\mathcal{L}_{sc}$)		123.5	137.1
Ours (w/o $\mathcal{L}_{ics}$)		127.1	142.1
Ours (w/o $\mathcal{L}_{scs}$)		125.3	140.0
Ours (all losses)		**120.8**	**134.7**

Table 3: Ablation study on the CHI3D dataset for multiple person pose and shape reconstruction methods. We report mean per joint positional error (**MPJPE**) and mean per vertex positional error (**MPVPE**). All errors are reported in mm and are relative to the root joint. The model trained with all proposed losses $\mathcal{L}_{ic}, \mathcal{L}_{sc}, \mathcal{L}_{ics}, \mathcal{L}_{scs}$ achieves the lowest error.

In figure 2 we show visual reconstructions of our method on in-the-wild photos from the **COCO** validation set. Notice the reconstruction quality even in high occlusion cases (either partial views or occlusion by the environment) and the robustness to the size of the humans in the image, ranging from very far away to very close to the camera. Additionally, in figure 3 we show reconstruction results on samples from the test split of **CHI3D**, with and without using the collision and contact losses. Notice the better physical plausibility when using all losses.

5 Conclusion

To better reconstruct and analyse scenes with multiple interacting people, we have emphasized the importance of contact and attention modeling, and the role of weak supervision for scalability and good generalisation. We have introduced a new transformer-based neural network architecture for multiple person 3D pose and shape estimation from RGB images, which relies on GHUM [6], a generative and articulated full body statistical 3D model for 3D mesh reconstruction. Our network produces physically plausible human mesh reconstructions with realistic scene placement under a fully perspective camera projection model. We also introduce new collision losses uniformly applicable to both self-contacts and inter-person contact, and more efficiently than previously proposed models by an order of magnitude. We demonstrate state-of-the-art 3d human pose and shape reconstruction results on challenging datasets like **CHI3D** [3] or **Panoptic** [32] which contain multiple people involved in complex interactions.

6 Broader Impact

While research is still experimental, in the long run our models can be integrated into systems performing large-scale psycho-social studies of human behavior understanding, under high privacy standards. Our work also has implications in applications as diverse as virtual try-on, AR/VR for digital collaborative environments *etc*. In the case of deploying our models for surveillance purposes or for deep fakes, we consider that they would not be suited because we do not model distinctive personal cues (*e.g.* detailed facial reconstruction).

Figure 2: 3D human pose and shape predictions on the **COCO** validation set (rows 1-5) for in-the-wild images. We show the initial image together with an overlaid reconstruction of the meshes as well as a rendering from a different viewpoint which better illustrates the physical consistency of the reconstructions. Best seen in color.

Figure 3: Visual 3D human pose and shape predictions on the **CHI3D** datasets. On columns 1-3 we show the results of a model which is not using any of the 4 losses $\mathcal{L}_{ic}, \mathcal{L}_{sc}, \mathcal{L}_{ics}, \mathcal{L}_{scs}$ and on columns 4-5 we illustrate the predictions of a model trained using the previously mentioned 4 losses. We observe more physically plausible results. Best seen in color.

References

[1] Andrei Zanfir, Elisabeta Marinoiu, Mihai Zanfir, Alin-Ionut Popa, and Cristian Sminchisescu. Deep network for the integrated 3d sensing of multiple people in natural images. In *NIPS*, 2018.

[2] Wen Jiang, Nikos Kolotouros, Georgios Pavlakos, Xiaowei Zhou, and Kostas Daniilidis. Coherent reconstruction of multiple humans from a single image. In *CVPR*, pages 5579–5588, 2020.

[3] Mihai Fieraru, Mihai Zanfir, Elisabeta Oneata, Alin-Ionut Popa, Vlad Olaru, and Cristian Sminchisescu. Three-dimensional reconstruction of human interactions. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[4] Mihai Fieraru, Mihai Zanfir, Elisabeta Oneata, Alin-Ionut Popa, Vlad Olaru, and Cristian Sminchisescu. Learning complex 3d human self-contact. In *Thirty-Fifth AAAI Conf. on Artificial Intelligence (AAAI'21)*, 2021.

[5] Andrei Zanfir, Eduard Gabriel Bazavan, Mihai Zanfir, William T Freeman, Rahul Sukthankar, and Cristian Sminchisescu. Neural descent for visual 3d human pose and shape. *arXiv preprint arXiv:2008.06910*, 2020.

[6] Hongyi Xu, Eduard Gabriel Bazavan, Andrei Zanfir, Bill Freeman, Rahul Sukthankar, and Cristian Sminchisescu. GHUM & GHUML: Generative 3D human shape and articulated pose models. *CVPR*, 2020.

[7] Matthew Loper, Naureen Mahmood, Javier Romero, Gerard Pons-Moll, and Michael J. Black. SMPL: A skinned multi-person linear model. *(SIGGRAPH)*, 34(6):248:1–16, 2015.

[8] Shih-En Wei, Varun Ramakrishna, Takeo Kanade, and Yaser Sheikh. Convolutional pose machines. In *CVPR*, June 2016.

[9] Zhe Cao, Gines Hidalgo, Tomas Simon, Shih-En Wei, and Yaser Sheikh. Openpose: realtime multi-person 2d pose estimation using part affinity fields. *arXiv preprint arXiv:1812.08008*, 2018.

[10] Natalia Neverova, Riza Alp Guler, and Iasonas Kokkinos. Dense pose transfer. In *(ECCV)*, September 2018.

[11] A.-I. Popa, M. Zanfir, and C. Sminchisescu. Deep multitask architecture for integrated 2d and 3d human sensing. In *CVPR*, 2017.

[12] Andrei Zanfir, Eduard Gabriel Bazavan, Hongyi Xu, Bill Freeman, Rahul Sukthankar, and Cristian Sminchisescu. Weakly supervised 3d human pose and shape reconstruction with normalizing flows. *ECCV*, 2020.

[13] Angjoo Kanazawa, Michael J. Black, David W. Jacobs, and Jitendra Malik. End-to-end recovery of human shape and pose. In *CVPR*, 2018.

[14] Nikos Kolotouros, Georgios Pavlakos, Michael J. Black, and Kostas Daniilidis. Learning to reconstruct 3D human pose and shape via model-fitting in the loop. In *ICCV*, 2019.

[15] Vasileios Choutas, Georgios Pavlakos, Timo Bolkart, Dimitrios Tzionas, and Michael J. Black. Monocular expressive body regression through body-driven attention. In *European Conference on Computer Vision (ECCV)*, 2020.

[16] Andrei Zanfir, Elisabeta Marinoiu, and Cristian Sminchisescu. Monocular 3d pose and shape estimation of multiple people in natural scenes - the importance of multiple scene constraints. In *CVPR*, 2018.

[17] Lea Müller, Ahmed A. A. Osman, Siyu Tang, Chun-Hao P. Huang, and Michael J. Black. On self-contact and human pose. In *Proceedings IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, June 2021.

[18] Luca Ballan, Aparna Taneja, Jürgen Gall, Luc Van Gool, and Marc Pollefeys. Motion capture of hands in action using discriminative salient points. In *ECCV*, 2012.

[19] Dimitrios Tzionas, Luca Ballan, Abhilash Srikantha, Pablo Aponte, Marc Pollefeys, and Juergen Gall. Capturing hands in action using discriminative salient points and physics simulation. *IJCV*, 2016.

[20] Georgios Pavlakos, Vasileios Choutas, Nima Ghorbani, Timo Bolkart, Ahmed A. A. Osman, Dimitrios Tzionas, and Michael J. Black. Expressive body capture: 3d hands, face, and body from a single image. In *CVPR*, 2019.

[21] Mohamed Hassan, Vasileios Choutas, Dimitrios Tzionas, and Michael J. Black. Resolving 3D human pose ambiguities with 3D scene constraints. In *ICCV*, 2019.

[22] Matthias Teschner, Stefan Kimmerle, Bruno Heidelberger, Gabriel Zachmann, Laks Raghupathi, Arnulph Fuhrmann, M-P Cani, François Faure, Nadia Magnenat-Thalmann, Wolfgang Strasser, et al. Collision detection for deformable objects. In *Computer graphics forum*, volume 24, pages 61–81. Wiley Online Library, 2005.

[23] Hiroharu Kato, Yoshitaka Ushiku, and Tatsuya Harada. Neural 3d mesh renderer. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[24] Paul Henderson and Vittorio Ferrari. Learning single-image 3D reconstruction by generative modelling of shape, pose and shading. *International Journal of Computer Vision*, 2019.

[25] Shichen Liu, Tianye Li, Weikai Chen, and Hao Li. Soft rasterizer: A differentiable renderer for image-based 3d reasoning. *The IEEE International Conference on Computer Vision (ICCV)*, Oct 2019.

[26] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[27] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NIPS*, 2017.

[28] Yi Zhou, Connelly Barnes, Jingwan Lu, Jimei Yang, and Hao Li. On the continuity of rotation representations in neural networks. *arXiv preprint arXiv:1812.07035*, 2018.

[29] Alec Jacobson, Ladislav Kavan, and Olga Sorkine-Hornung. Robust inside-outside segmentation using generalized winding numbers. *ACM Transactions on Graphics (TOG)*, 32(4):1–12, 2013.

[30] Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. Software available from tensorflow.org.

[31] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *ECCV*. 2014.

[32] Hanbyul Joo, Hao Liu, Lei Tan, Lin Gui, Bart Nabbe, Iain Matthews, Takeo Kanade, Shohei Nobuhara, and Yaser Sheikh. Panoptic studio: A massively multiview system for social motion capture. In *ICCV*, 2015.

[33] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[34] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR*, 2009.

[35] Mykhaylo Andriluka, Leonid Pishchulin, Peter Gehler, and Bernt Schiele. 2d human pose estimation: New benchmark and state of the art analysis. In *CVPR*, 2014.

[36] M. Andriluka, U. Iqbal, E. Ensafutdinov, L. Pishchulin, A. Milan, J. Gall, and Schiele B. PoseTrack: A benchmark for human pose estimation and tracking. In *CVPR*, 2018.

[37] Sam Johnson and Mark Everingham. Clustered pose and nonlinear appearance models for human pose estimation. In *BMVC*, 2010.

[38] Sam Johnson and Mark Everingham. Learning effective human pose estimation from inaccurate annotation. In *CVPR 2011*, pages 1465–1472. IEEE, 2011.