Look Around and Refer: 2D Synthetic Semantics Knowledge Distillation for 3D Visual Grounding

Abstract

The 3D visual grounding task has been explored with visual and language streams to comprehend referential language to identify targeted objects in 3D scenes. However, most existing methods devote the visual stream to capturing the 3D visual clues using off-the-shelf point clouds encoders. The main question we address in this paper is *"can we consolidate the 3D visual stream by 2D clues synthesized from point clouds and efficiently utilize them in training and testing?"*. The main idea is to assist the 3D encoder by incorporating rich 2D object representations without requiring extra 2D inputs. To this end, we leverage 2D clues, synthetically generated from 3D point clouds, and empirically show their aptitude to boost the quality of the learned visual representations. We validate our approach through comprehensive experiments on Nr3D, Sr3D, and ScanRefer datasets, and we show consistent performance gains compared to the state-of-the-art. Our proposed module, dubbed as Look Around and Refer (LAR), significantly outperforms the state-of-the-art 3D visual grounding techniques on these three benchmarks. Our code will be made publicly available.

1 Introduction

Visiolinguistic modeling has attracted much attention over the past decade due to impact on various areas, including visual question answering [3, 36], 3D scene captioning [7], image-text matching [26, 43], visual relation detection [25], and scenegraph generation [41]. Consequently, understanding natural language utterances and grounding them to real-world scenarios is attractive due to their importance in many real applications, such as robot navigation and interaction in indoor environment [22] [39].

Visual Grounding (VG) has been explored in recent years in the context of 2D [16, 30, 45, 54, 56], extending object detection to a more complex task. However, for real robots to intelligently ground a given utterance on a natural scene in a challenging environment like a crowded indoor or outdoor scene, 3D representations are needed to understand the surrounding environment better. Therefore, 3D visual grounding task have been proposed by ReferIt3D [2] and Scan-Refer [5]. The ReferIt3D [2] introduces two datasets

Figure 1: Overview of our proposed approach, where we aim to localize a referred object given an input utterance and 3D scene. Our novel approach generates 2D synthetic images for each object in the scene by placing virtual cameras surrounding the object. This novel approach enables us to leverage the rich 2D semantics representation without needing authentic extra 2D images not to limit potential application scenarios.

Table 1: Comparison of various 3D visual grounding models. Where GT indicates ground truth boxes are used, Pred. indicates a pretrained detector is used to get the objects proposals. We show that Looking-outside [18] and SAT [51] are using additional inputs such as the over all scene point clouds S_{pc}, and extra 2D images $2D_{Img}$, respectively. O_{pc} refers to object's point cloud.

	Refit3D [2]	Lang. Refer [37]	InstRef [57]	TGNN [17]	Looking outside [18]	D3Net [6]	TransRef3D [13]	3DVG [58]	SAT [51]	Ours
Obj. Proposal	GT	GT	Pred.	Pred.	Pred.	Pred.	GT	Pred.	GT	GT
Lang. Encoder	RNN	DistilBert	GloVE	GloVE	RoBERTa	GRU	DistilBert	GloVE	BERT	BERT
Visual Input	O_{PC}	O_{PC}	$O_{PC}+S_{PC}$	O_{PC}	$O_{PC}+S_{PC}$	O_{PC}	O_{PC}	O_{PC}	$O_{PC}+2D_{Img}$	O_{PC}

containing natural and synthetic language utterances, namely Nr3D and Sr3D, respectively, which aims to determine the referent object from pre-defined objects set for each scene. In contrast, Scan-Refer [5] aims to predict 3D bounding boxes for the referent object based on a given language description and 3D point clouds. Both ScanRefer [5] and ReferIt3D [2] are built on the ScanNet dataset [8]. The critical difference, which made ReferIt3D [2] more challenging, is that in each scene, several object instances belong to the same fine-grained category as the referent, namely distractors.

Due to the sparsity and disorganization of the 3D point clouds, SAT [51] explores utilizing the 2D images provided by the ScanNet dataset [8] during training to assist point-cloud-language joint representation learning. SAT [51] proposes three variants; 1) The baseline, non-SAT, relies only on the 3D point clouds while tackling the grounding task. 2) Utilizing 2D semantics during the training phase only and masking them while inference, we termed it SAT. 3) Utilizing the 2D semantics in both phases, i.e., training and testing, we termed it SAT-GT. However, requiring extra 2D inputs in training or inference limits potential application scenarios. To tackle this drawback, we hypothesized that incorporating synthetic 2D semantics will consolidate the 3D learned representation while not requiring any additional info. To this end, we propose a novel 2D Synthetic Images Generator (SIG) that projects the 3D point clouds into multi-view 2D images, as shown in Figure 1. To the best of our knowledge, LAR is the first method that augment learning of 3D tasks with synthetic 2D semantics. In addition, we propose a novel multi-modal transformer-based architecture. Our proposed architecture, LAR, on Nr3D outperforms SAT [51] by boosting the accuracy by 1.6% while exceeding all existing approaches that did not use any additional information than the 3D point clouds by a wider margin, i.e., 5.0% to the closest one. Also, LAR architecture achieves state-of-the-art results on Sr3D and ScanRefer benchmarks, 59.35% and 54.6%, respectively. Another variant is tailored from our architecture to be compared against SAT-GT, where geometry information and ground-truth class labels are concatenated to the 2D images; synthetic in our case and original images in SAT case. Our LAR architecture outperforms SAT-GT by 11.7%, where we achieved 62% while SAT achieves 50.3%. Our contributions are summarized as follows:

- We propose a novel End-to-End multi-modal transformer-based architecture, LAR, for the 3D visual grounding task that relies only on 3D point clouds, which exploits the synthetic 2D images generated by our SIG module.
- We verify the effectiveness of our LAR architecture throughout extensive experiments with various benchmarks, which show that utilizing our 2D synthetic semantics significantly enhances the results.
- Through detailed analysis, we examine our method's internal behavior and validity.

2 Related Work

Our novel architecture draws success from several areas, including 2D visual grounding, 3D visual grounding, and 2D semantics in 3D tasks.

–**2D visual grounding.** 2D visual grounding is locating an object based on a natural language description. Flickr30k [32] and ReferItGame [20] generated referring expressions for a particular object in an image used to identify which object is being referred to. Prior works [55, 27, 29] have attempted to localize these referred objects based on the given expressions by focusing on the bounding-box level. In contrast, [52, 10] focus on the pixels level. Another 2D visual grounding taxonomy is the one-stage, also known as a single-stage framework, versus the two-stage framework. The single-stage methods [38, 48, 49], fuse the linguistic query with each pixel/patches of the image, and generate a set of possible bounding box candidates. In contrast, the two-stage framework [44, 53, 55] uses the visual image semantics to generate object proposals. Afterward, the grounding

prediction is selected by comparing each proposal to the language query. Consequently, 2D visual grounding methods can guide learning 3D relationships. Driven by this, we explore using 2D synthetic semantics to consolidate the 3D visual stream.

–**3D visual grounding.** Table 1 summarizes the existing 3D visual grounding models whether a ground truth object proposal is used or a pre-trained detector is utilized to generate the proposals. Also, it summarizes whether extra info is used alongside the object's 3D point cloud or not. 3D visual grounding field has undergone extensive research and made considerable progress over the last few years [2, 5, 12, 17, 58, 1, 37, 13, 57, 19, 51, 6, 19]. A 3D visual grounding task uses language instruction along with a 3D scene [8] as input in order to estimate a bounding box that allocates the most relevant object to the provided expression. However, the literature offers several extensions, such as using auxiliary input to improve localizing 3D objects [51]. Previous work [2, 12, 17, 58, 1, 13, 57, 19], focuses on improving the language and 3D scene fusion by adopting a two-stage framework. The first stage outputs 3D object proposals given a 3D point cloud representing a scene. Secondly, visual and linguistic features are fused to compute a confidence score for each 3D object proposal. The first stage could be skipped by directly using the ground-truth proposals instead of predicting them [51] [13] [2]. In contrast, [6, 19, 58] do not assume the access to the ground-truth objects and use an object detector to extract the proposals. Intuitively, if the detector fails, the referring performance will significantly decrease. Therefore, we focus on the main training objective related to the grounding task, which is learning 3D visual-language joint representations by assuming access to the ground-truth boxes. Although we are assuming access to the ground-truth boxes, LAR is compatible with the setting that utilizes detector-generated proposals.

–**2D semantics in 3D tasks.** 2D semantics contains useful information that can be used to detect 3D objects. The representations of visual scenes consist of point clouds, meshes, or volumes, while 2D images consist of pixel grids. Combining the best of two worlds can enhance 3D object localization. Researchers have attempted to solve the 3D detection problem by adopting different ways of representing RGB-D data [34, 47, 23, 15, 40, 24]. By either projecting the 2D image on the 3D scene [34, 47, 24] or fuse both 2D features with the 3D [23, 15, 42, 40], [33]. SAT [51] leveraged 2D semantics to perform the 3D VG task. However, requiring extra 2D inputs limits potential application scenarios. In contrast, in this work, we generate synthetic 2D images during the training phase, which is also used in the inference phase. The synthetic images enable us to consolidate the 3D visual stream by 2D semantics without requiring extra 2D inputs.

3   Look Around and Refer (LAR)

LAR aims to enhance the visual module, which in turn enhances the final objective,i.e., referential accuracy. By incorporating the synthetic 2D semantics alongside the 3D point clouds, LAR inherently captures the correlations between the 2D and the 3D streams. To design a general framework to fit in any 3D application, when the input is 3D point clouds, the need for extra information, such as 2D semantics, should be bypassed. To this end, a 2D synthetic images generator, namely SIG, is introduced, which is discussed in Section 3.1. Then, we demonstrate how to learn robust representations by aligning the generated 2D semantics with the 3D ones by incorporating our SIG module into our proposed architecture, depicted in Section 3.2.

3.1   Look Around: 2D Synthetic Images Generator

LAR exploits synthetic 2D semantics to reinforce the learned 3D representations. Consequently, this section will demonstrate our 2D Synthetic Images Generator (SIG) module that projects arbitrary 3D Point clouds representing an object to a 2D image. First, we will show the essential operations of our module on a single image, then show how we extend it to fulfill a multi-view setup.

A 3D scene, $S \in \mathbb{R}^{N \times 6}$, is represented by N points with spatial and color information, i.e., XYZ, and RGB, respectively. Following the previous works [2] [1] [37] [51], the object proposals x_i^{pc} for each scene are known, either generated by one of the off-the-shelf 3D object detectors or manually annotated. The object proposal $x_i^{pc} \in \mathbb{R}^{N' \times 6}$ is a subset of the whole scene, where $N' < N$ and N' represents the number of points that represent the object i.

Given a scene S and an object proposal x_i^{pc}, our SIG module generates a 2D synthetic image x_i^{img} represents the object i. The main idea is to place a virtual pinhole camera in front of the fed object

Figure 2: Simplified overview of our 2D Synthetic Images Generator (SIG) module. First, we determine the prominent face for each object w.r.t the scene center. Then, the camera is located at a distance d^f from that face, and at distance d^{up} from the room's floor. Finally, we randomly extend the region of interest by ϵ.

proposal, then project its points x_i^{pc} into the 2D plane to generate the corresponding 2D image x_i^{img}. The camera's location should be set carefully to generate a decent image representation for an object i. As shown in part (A) in Figure 2, after excluding the upper and lower faces from the fed object proposal, we get the center of the four remaining faces, then calculate the distance between each face center O_i^l, and the center of the scene O_s, where l ranging from 0 to 3. The nearest face l' from the scene center O_s is the prominent one, colored with blue in Figure 2, which guarantees that we look at the object i from inside the room. After selecting the prominent face l', the camera is located at a distance d^f from that face and at a distance d^{up} from the room's floor; thus, the camera position is interpreted as $Cam_p = [d_x^f, d_y^f, d^{up}]$, as shown in part (B) in Figure 2. Failure cases are shown in Figure 5, when the camera is located outside the room.

To project the points x_i^{pc}, representing object i, from the scene coordinates to the camera coordinates, a transformation matrix $M \in \mathbb{R}^{4 \times 4}$ needs to be defined. Given the camera position Cam_p and the center of the prominent face $O_{l'}$, the transformation matrix M can be interpreted as, $\begin{bmatrix} V^r & V^{up} & V^f & Cam_p \\ 0 & 0 & 0 & 1 \end{bmatrix}$

Where, the camera direction is defined by three vectors; forward vector $V^f \in \mathbb{R}^{3 \times 1}$, right vector $V^r \in \mathbb{R}^{3 \times 1}$, and up vector $V^{up} \in \mathbb{R}^{3 \times 1}$. To direct the camera to the center of the prominent face $O_{l'}$, the forward vector V^f is determined by $\|Cam_p - O_{l'}\|$, where $\|x\|$ means the normal of the vector x. While, the right vector V^r is set to $\|V^f \otimes [0, 0, 1]\|$, where $\otimes$ refer to cross product. As the forward vector V^f and the right vector V^r are orthogonal, thus the cross product between these two vectors will result in the camera up direction $V^{up} = \|V^r \otimes V^f\|$.

Consequently, projecting the 3D point clouds to a 2D image can be interpreted as three operations; converting points from scene coordinates to camera coordinates, then the mapping from camera coordinates to image coordinates, and finally the transformation from image coordinates to pixel coordinates. Thus, by performing a dot product between the 3D point clouds and the transformation matrix M, transforming from scene coordinates x_i^{pc} to camera coordinates x_i^{cam} is achieved. Then, followed by another dot product between the 3D points in the camera coordinates x_i^{cam} and the intrinsic pinhole camera parameters I, the points are projected into image space x_i^{img}. Finally, to further transform points from image space to the pixel space, we divide the 2D spatial coordinates; x, y, for each point by its height information; z, to get homogeneous coordinates in the image plane. Afterwards, the projected 3D point clouds are assigned to a 2D grid map. To mitigate the overfitting effect, we randomly extend the region of interest by ϵ as demonstrated in part (C) at Figure 2.

Point cloud differs from 2D images, where every pixel contains spatial and texture details. Moreover, the object is represented in a view-invariant way, unlike the images that are view-dependent. To mitigate this drawback in the image representation, a multi-view setup is constructed as shown in Figure 1. Where, v cameras are mounted in a circle around the prominent face l'. Algorithm 1, attached in the supplemental materials, demonstrates a pseudo-code for our SIG module.

3.2 Refer: Visiolinguistic Transformer Architecture

We present our approach, depicted in Figure 3, for learning multi-modal representations of a 3D scene associated with language instruction. First, the proposed visual module enriches the 3D representations by utilizing the 2D synthetic images generator, namely the SIG module, described in Section 3.1. Thanks to it, we do not require access to any imagery sensor during training or testing.

Figure 3: Detailed overview of LAR. The Visual Module incorporates rich 3D representation from the extracted 3D object points with the 2D synthetic image features using Visual Transformer. The 2D synthetic images are first extracted by SIG then processed by a shared ConvNext backbone. Simultaneously, language descriptions are transformed into tokens and embedded into a feature vector. Then, the Multi-Modal Module fuses the output of the Visual Module separately by two Transformers. Finally, the output of the Multi-Modal Transformers is processed by a Fusion Transformers.

Then, the multi-modal module learns joint representations targeted to the final task, i.e., referring to an object in the scene based on the language instruction.

–**Visual Module.** Given a 3D scene $S \in \mathbb{R}^{N \times 6}$ combined with agnostic multiple 3D object proposals $x_i^{pc} \in \mathbb{R}^{N' \times 6}$, we aim to classify each object proposal by predicting the semantic labels z. First, for each object i in the scene S, we generate multi-view synthetic 2D images $x_i^{img} \in \mathbb{R}^{v \times H \times W \times 3}$ from the 3D object's point cloud x_i^{pc}, where v is the number of views for each object, H and W are the spatial dimensions for the generated images. Second, we employ PointNet++ [35] as a 3D encoder, producing 3D features $E_i^{pc} \in \mathbb{R}^{1 \times dim_{pc}}$. Hence, the Tiny-ConvNext [28] is adopted as a 2D encoder, that produce $y_i^{img} \in \mathbb{R}^{v \times H' \times W' \times dim_{img}}$. Where H' and W' represent a coarse spatial grid of spatial features, each represented by a dim_{img}. Then, the spatial dimensions are squeezed producing $o_i^{img} \in \mathbb{R}^{v \times dim_{img}}$. Since our 2D encoder encodes multiple views v for the same object i, a fusing mechanism is needed to fuse the views' features. Various possibilities are discussed to settle down on the best fusion mechanism. We can interpret this as a fully connected layer to fully capture the views and cross-channel interactions. In contrast, to learn the views' interactions and neglect the cross-channel relations, a 1D-Conv. could be utilized to avoid involving tremendous parameters as in the fully connected case. Using the 1D-Conv. with $k_{size} = v$ as a fusion layer produce $E_i^{img} \in \mathbb{R}^{1 \times dim_{img}}$, where k_{size} is the kernel size. The fused 2D features E_i^{img} and the 3D features E_i^{pc} are concatenated and fed to a visual transformer, composed of several stacked transformer layers. The visual transformer is utilized to capture the cross-correlation between the 2D and the 3D features outputting refined features, V^{pc} and V^{img}, guided by three weighted auxiliary losses, i.e., alignment loss between V^{pc} and V^{img}, and two visual classification losses.

–**2D semantics.** Inspired by SAT [51], we explore different 2D semantic information types combinations. Where we formulate our 2D semantics as follows:

$$E_i^{2d} = LN(\phi(E_i^{img}, LN(W_1 x_i^{geo}), z_i')) \tag{1}$$

Where, z_i' is the predicted class labels, W_1 are learned projection matrices, LN is layer normalization, and ϕ indicates concatenation. The geometry semantics, $x_i^{geo} \in \mathbb{R}^{1 \times 30}$ represents the bounding box coordinates of object i in the scene space and encode the virtual camera parameters, i.e., intrinsic and extrinsic parameters, used while generating the 2D image x_i^{img}. In contrast, SAT [51] utilizes a ground-truth 2D semantics, where the z_i' denotes the manually annotated class labels, and the E_i^{img} represents the embedding generated from real 2D images captured by imagery sensor [8].

–**Multi-Modal Module.** Using a pre-trained BERT model [11] followed by a language classification head adopted from Referit3D [2], we embed words query Q. After embedding each of the visual features using the aforementioned visual module, we fuse the input modalities Q, V^{pc}, V^{img} simultaneously by using two different transformers; 3D Multi-Modal Transformer and 2D Multi-Modal Transformer. In 3D Multi-Modal Transformer, we jointly encode the two input modalities V^{pc} and Q to understand better the referring expression that captures co-occurrence relationships

between different objects in the scene. Meanwhile, the same words query Q are encoded with V^{img} to enhance context-aware representation. A separate 2D and 3D referring heads are adopted from Referit3D, which are auxiliary tasks. Finally, the output of the multi-modal transformers is processed by a Fusion Transformer that chooses the referred object from the fused features, F^{pc} and F^{img}.

–**Losses.** Two auxiliary losses are employed to optimize the visual module; 3D classification loss $\mathcal{L}_{cls}^{3D}$ and 2D classification loss $\mathcal{L}_{cls}^{2D}$. We adopt Referit3D [2] language classification loss $\mathcal{L}_{cls}^{lang}$. In addition, we explore the effect of adding multiple grounding losses from different semantic levels, i.e., $\mathcal{L}_{Eref}^{3D}$, $\mathcal{L}_{Eref}^{2D}$, $\mathcal{L}_{ref}^{3D}$ and $\mathcal{L}_{ref}^{2D}$ and find that adding losses from both level boosts the grounding accuracy. Where, $\mathcal{L}_{Eref}^{3D}$ and $\mathcal{L}_{Eref}^{2D}$ indicates the early referring heads losses , before the fusion transformer. $\mathcal{L}_{ref}^{3D}$ and $\mathcal{L}_{ref}^{2D}$ refers to the final referring losses. The object correspondence loss $\mathcal{L}_{cor}$ is adopted from SAT [51]. We optimize the whole model in an End-to-End manner, unlike SAT which learns the 2D features E_i^{img} separately, with the following loss function:

$$\mathcal{L} = \lambda_{cls}*(\mathcal{L}_{cls}^{3D}+\mathcal{L}_{cls}^{2D})+\lambda_{Eref}*(\mathcal{L}_{Eref}^{3D}+\mathcal{L}_{Eref}^{2D})+\lambda_{ref}*(\mathcal{L}_{ref}^{3D}+\mathcal{L}_{ref}^{2D})+\lambda_{cor}*\mathcal{L}_{cor}+\lambda_{lang}*\mathcal{L}_{cls}^{lang} \quad (2)$$

where, λ_{cls} is the object classification loss weight, λ_{Eref} is the early referring loss weight, λ_{ref} is the final referring loss weight, λ_{cor} is the object correspondence loss weight, and λ_{lang} is the language classification loss weight.

3.3 Implementation Details

–**Input Configuration.** For the 3D input, we randomly sample 1024 points per proposal from its point cloud segment. Furthermore, for the synthetic 2D input, we follow Algorithm 1, which is scrutinized in Section 3.1. During the testing phase, the camera is set 2 meters away from the prominent face l', i.e., $d^f = 2$, and 1 meter away from the floor, i.e., $d^{up} = 1$. In addition, the region of interest extension ratio ϵ, depicted in Figure 2 part (C), is set to 2%. The generated image is a square with a size of 32 pixels. Five views are generated per object, where the angle θ between each camera is $30°$, demonstrated in Figure 1. Thus the camera is set to the following angles ($0°$,$30°$, $-30°$,$60°$,$-60°$).

–**Network and Training Configuration.** A pre-trained model on the ImageNet dataset [9], Tiny-ConvNext [28], is used to extract the features of our synthetic 2D images. Our 2D backbone is shared across different views. We adopt the same 3D encoder in the previous works [1] [2] [13] [37] [18] [51], PointNet++ [35], to encode the sampled points per proposal. For the language encoder, we adopt the BERT encoder [11] with three layers. We adopted the same transformer architecture used in [51] [50] for our visual, multi-modal, and fusion transformers. All models are trained for 100 epochs from scratch, using the weight initialization strategy described in [14]. As mentioned in SAT [51], the initial learning rate is set to 10^{-4} and decreases by 0.65 every ten epochs . Adam optimizer [21] and mini-batch size of 32 per GPU are used for training all our models. We set the losses weights as follows, $\lambda_{cls} = 5$, $\lambda_{Eref} = 0.5$, $\lambda_{ref} = 5$, $\lambda_{cor} = 10$, and $\lambda_{lang} = 0.5$.

–**Software and Hardware Details.** We use the python augmentation framework, Albumentations [4], for image augmentation. In order to perform an online augmentation while training, we implemented our 2D Synthetic Images Generator (SIG), described at Section 3.1, in a pure Pythonic approach without using any 3D libraries which also fasten the training. Our module is implemented in Python using the PyTorch framework and four Nvidia V100 GPUs.

4 Experiments

Datasets. We evaluate our proposed 3D visual grounding approach, LAR, on three benchmarking datasets, Nr3D [2], Sr3D [2], and ScanRefer [5]. Nr3D, 3D Natural reference dataset [2], consists of 41.5K natural, free-form utterances collected by humans using a referring game between two humans. As opposed to Sr3D [2], which consists of 83,5K synthetic utterances. Unlike Nr3D and Sr3D datasets, ScanRefer does not have the distractors concept making it relatively easier. In addition, it provides 51.5K utterances of 11K objects for 800 3D indoor scenes.

4.1 Ablation studies

We conducted five ablation studies to assess the proposed architecture and to validate the contribution of each component to achieve good performance. These components are: 1) 2D multi-views and 2D

resolution. 2) Types of 2D semantic information. 3) Camera vs. image augmentation 4) Different multi-modal fusion techniques. 5) Different 2D semantic fusion techniques. Where the last two are stated in Appendix 5.

–**2D multi-views and 2D resolution.** To assess our 2D Synthetic Images Generator (SIG), we have deliberately removed the 3D stream, colored with yellow in Figure 3; 3D encoder, 3D heads, and rely only on our generated 2D images only while tackling the referring task. Thus, our architecture is simplified to include only the 2D encoder, 2D multi-modal transformer, and 2D heads. We trained this 2D architecture variant with different image resolutions and multi-view setup combinations. As shown in Table 2, The referring accuracy increased linearly while increasing the image size or increasing the number of views for the projected images. However, our multi-view setup has the dominant effect, whereas using only 64 image resolution with five views surpassing one shot with 128 resolution.

Table 2: Ablation Study of 2D synthetic image resolution and multi-view setup on Nr3D [2].

Image Size	Multi-Views	Encoder	Referit3D [2]		non-SAT [51]	
			Ref. Acc.	Cls. Acc.	Ref. Acc.	Cls. Acc
-	-	3D	35.6	57.4	37.7	59.1
32	1		28.0	47.34	30.9	49.31
64	1	2D	32.0	56.93	33.7	56.14
128	1		**34.4**	**62.15**	**35.5**	**63.32**
32	3		29.7	50.11	31.1	51.40
64	3	2D	32.9	63.20	34.2	64.02
128	3		**35.1**	**64.85**	**36.4**	**65.13**
32	5		31.1	55.18	33.7	56.72
64	5	2D	34.1	64.05	35.6	64.52
128	5		**36.0**	**65.19**	**38.2**	**65.40**

Also, we found that using the combination of five different views, each has 128 resolution, surpassing Referit3D and non-SAT variant, where both use 3D semantics only, which shows the quality of the learned representation via our novel synthetic 2D images generator (SIG).

–**Types of 2D semantic information.** Inspired by SAT [51], we dissect the role of different 2D semantic, following Eq. 1. As shown in Table 3, the first row (a) represents a 3D variant of our architecture where only the 3D encoder, 3D multi-modal transformer, and 3D heads are included. Therefore, this variant mimics the Non-SAT [51] configurations. Starting from row b to row e, our synthetic 2D semantics are incorporated alongside the 3D semantics. Also, we compare against SAT [51] to highlight the critical

Table 3: Comparison between different types of 2D semantics information as in Eq. 1 on Nr3D [2].

	$+x^{geo}$	$+x^{cls}$	$+x^{ROI}$	SAT † [51]		Ours	
				Ref. Acc.	Cls. Acc.	Ref. Acc.	Cls. Acc.
(a)	-	-	-	37.7	59.1	**38.1**	58.2
(b)	-	-	✓	42.3	61.0	**42.2**	**62.2**
(c)	✓	-	✓	46.2	61.0	**46.3**	**63.3**
(d)	-	✓	✓	43.2	61.2	**44.5**	**62.1**
(e)	✓	✓	✓	47.3	60.6	**48.9**	**65.42**

differences in the meaning of each semantic information. ROI in our architecture is the synthetic 2D image generated from the 3d point clouds using our SIG module. In contrast, SAT [51] uses the original ScanNet images during the training phase. Unlike SAT, which uses the ground-truth classification labels during the training and masks them during testing, we use the predicted labels from the 2D classification head z'. Accordingly, we do not need to mask the 2D semantics, as we are using synthetic ones. As shown in row (e), the best accuracy is achieved when we jointly incorporate the three semantic types. We also notice a significant superiority in classification accuracy where our synthetic 2D images assist the 3D classifier in both phases; training and testing.

–**Camera vs Image Augmentation.** We have two kinds of augmentation during training: 1) Image augmentation. 2) Camera augmentation. For image augmentation, we followed the conventional techniques used by the major computer vision applications like horizontal and vertical flipping, blurring, color jitter, random scaling, random shifting, and random cropping. For camera augmentation, we range d^f from 1.5 to 4 meters, d^{up} from 0.5 to 2.5 meters, and ϵ from 2% to 15%. By changing the variables mentioned above, the extrinsic camera parameters are augmented. In addition, random noise is added to the intrinsic camera parameters. Table 4 demonstrates the effect of each

Table 4: Comparison between Camera augmentation and Image augmentation on Nr3D [2].

Cam. Aug.	Img. Aug.	Ref. Acc.	Cls. Acc.
✗	✗	45.9	60.33
✗	✓	48.2	62.69
✓	✗	47.8	63.97
✓	✓	**48.9**	**65.42**

augmentation type alone and the effect of fusing both of them. The best accuracy is achieved by utilizing the two augmentation types.

4.2 Comparison to State-of-the-art

Moreover, we achieve state-of-the-art results on the three well-known 3D visual grounding benchmarks, i.e., Nr3D [2], Sr3D [2], and ScanRefer [5]. By effectively utilizing our 2D synthetic

Table 6: Benchmarking results on Nr3D and Sr3D datasets [2]. All reported techniques are using the ground-truth object proposals. Additional input column emphasize the extra information used besides object's point cloud, where S_{pc} and $2D_{Img}$ indicate the over all scene point clouds and extra 2D images, respectively. The † symbol indicates we retrain the model for a fair comparison.

| Method | Additional Input | Nr3D | | | | | Sr3D | | | | |
		Overall(σ)	Easy	Hard	View-dep.	View-indep.	Overall(σ)	Easy	Hard	View-dep.	View-indep.
ReferIt3D [2]	-	35.6%	43.6%	27.9%	32.5%	37.1%	40.8%	44.7%	31.5%	39.2%	40.8%
Text-Guided-GNNs [17]	-	37.3%	44.2%	30.6%	35.8%	38.0%	45.0%	48.5%	36.9%	45.8%	45.0%
InstanceRefer [57]	S_{pc}	38.8%	46.0%	31.8%	34.5%	41.9%	48.0%	51.1%	40.5%	45.4%	48.1%
3DRefTransformer [1]	-	39.0%	46.4%	32.0%	34.7%	41.2%	47.0%	50.7%	38.3%	44.3%	47.1%
3DVG-Transformer [58]	-	40.8%	48.5%	34.8%	34.8%	43.7%	51.4%	54.2%	44.9%	44.6%	51.7%
FFL-3DOG [12]	-	41.7%	48.2%	35.0%	37.1%	44.7%	-	-	-	-	-
TransRefer3D [13]	-	42.1%	48.5%	36.0%	36.5%	44.9%	57.4%	60.5%	50.2%	49.9%	57.7%
LanguageRefer [37]	-	43.9%	51.0%	36.6%	41.7%	45.0%	56.0%	58.9%	49.3%	49.2%	56.3%
Non-SAT [51]	-	37.7%	44.5%	31.2%	34.1%	39.5%	43.9%	-	-	-	-
SAT [51]	$2D_{Img}$	49.2%	56.3	42.4	46.9	50.4	57.9%	61.2	50.0	49.2	58.3
SAT † [51]	$2D_{Img}$	47.3%	55.8%	41.4%	46.9%	50.4%	56.6%	60.6%	49.7%	48.7%	57.4%
LAR (Ours)	-	**48.9%**±0.2	**58.4%**	**42.3%**	**47.4%**	**52.1%**	**59.35%**±0.1	**63.0%**	**51.2%**	**50.0%**	**59.1%**

images, LAR outperforms all the existing methods, which do not use any additional training dataset, by a large margin of 5.0% and 1.9% on Nr3D and Sr3D, respectively, depicted in Table 6. Where, LanguageRefer [37] achieves 43.9%, while LAR achieves 48.9% on Nr3D. For Sr3D, our model achieves 59.35%, which is a 1.9% increase over TransRefer3D [13]. In addition, for the ScanRefer [2] benchmark, we also achieve state-of-the-art results, by boosting the accuracy by 2.3% from the closest counterpart architecture; SAT [51], mentioned in Table 5.

Table 5: Benchmarking results on ScanRefer [5].

Method	Ref. Acc.
Refit3D	46.9%
non-SAT	48.2%
SAT	53.8%
SAT †	52.3%
Ours	**54.6%**

We retrained SAT [51] for a fair comparison, as we notice difficulties reproducing and verifying SAT results [1]. Although we do not use an extra input during training as SAT, which uses the original ScanNet 2D images [8], we surpass SAT by 1.6%, 2.7%, and 2.3% on Nr3D, Sr3D, and ScanRefer, respectively.

4.3 Discussion and Analysis

First, we will demonstrate our qualitative analysis. Then, we have conducted two experiments to probe the robustness of the representations learned by our proposed module LAR.

–**Qualitative Analysis.** Figure 5 depicts two corner cases in our projection module (SIG). While assigning the projected 3D points into a 2D grid, more than one point may share the exact spatial location on the grid, which means only one will be stored in the grid, and the rest of the points will be discarded. As shown in part (A) in Figure 5, on the left column, the floor overlaps the other objects due to the conflict between points during the assignation step. To overcome this behavior, a simple priority rank is given for each point based on its height. Part (B) shows another failure case, where the prominent face is falsely localized, which causes placing the camera outside the room or inside other objects. Therefore, we localize the prominent face relative to the room center to mitigate this effect. An example of an ambiguous description is shown in Figure 6 part A. The model incorrectly predicts "the chair on the right rather than the chair on the left." The model and the human annotations are occasionally confusing to referring to the objects in the view-dependent description. While successful cases can be seen in Figure 6 part B. For more qualitative visualization, please refer to Appendix 5.

–**Evaluation with Ground-Truth Class Labels.** Table 7 shows another variant, which is tailored from our architecture to be compared against SAT-GT. Where the predicted class labels are replaced by the ground-truth ones. Our LAR architecture outperforms SAT-GT by 12%.

Table 7: Benchmarking results on Nr3D [2], while using the ground truth classification.

Method	Ref. Acc.	Cls. Acc.
SAT-GT	50.3%	61%
Ours	**62%**	**64%**

–**Zero-shot Cameras Dying Testing.** We deliberately drop the cameras during testing to verify the robustness of our learned representations against camera variations. As shown in Figure 4, starting from our best model, which is trained using five cameras, the referring accuracy drops to 44.6% then 40.15%, when we only use three cameras then one camera during testing, respectively. Driven by these results, camera dropout techniques can be invoked to overcome the performance drop, by

---

[1] Referring to issues number 1, 3, and 2 from the official SAT implementation.

Figure 4: Cameras dropout.

Figure 5: Qualitative results for projection corner cases. Part A shows failure in assignation step for the projected 3D points into the 2D grid. Part B, demonstrates failure in the prominent face localization step.

Figure 6: Our qualitative results. Case A shows a successful case. While case B shows a failure due to view-dependent description.

deliberately drop a random camera during the training; replace its input by a duplicate view of another camera.

–**Noisy Cameras Extrinsic and Intrinsic.** Due to the significant improvement introduced by utilizing the camera augmentation, as shown in Table 4, a detailed analysis is conducted to explore the robustness against the camera's variations. Consequently, our 2D synthetic branch learns how to fuse information across different cameras in a data-driven way. Therefore, we can train the model to be robust to noise camera models, as shown in Table 8.

Both cameras dying and noisy parameters experiments could be thought as irrelevant as LAR utilizes virtual cameras. Thus, no camera dropout nor noise can be introduced. However, our SIG module, depicted in Section 3.1, can be utilized in a wide range of applications when these robustness characteristics against such noise are essential for these applications. For instance, in the autonomous driving world, our SIG module can be employed to convert dense lidar point clouds into synthetic

Table 8: Showing LAR robustness against camera augmentation.

Training	Testing	Ref. Acc.	Cls. Acc.
✗	✗	48.2	62.69
✗	✓	46.7	61.32
✓	✗	**48.9**	**65.42**
✓	✓	48.8	65.22

images, which will be used to train an arbitrary neural network that tackles specific tasks (e.g., object segmentation in cocoon setup [31] [46]). Then, the model will be tested using real cameras instead of generating synthetic imagery input from the lidar.

–**Limitations.** Following the standard setup of Referit3D [2], we assume access to the object proposals of each 3D scene, similar to SAT [51], LanguageRefer [37], TransRefer3D [13], and 3DVG-Trans [58]. Therefore, we use the ground-truth proposals in our experiments. Following this assumption, the 3D grounding problem is reformulated as a classification problem, where the model objective is to classify the referred object among the other distractors correctly. However, LAR is compatible with the setting that uses detected-based proposals.

5 Conclusion

We propose an efficient 3D grounding architecture that leverages the 2D knowledge to reinforce the learned 3D representations. To avoid requiring 2D semantics neither during training nor testing, we introduce a 2D synthetic images generator, termed SIG. Our SIG module generates high-quality 2D synthetic images. LAR, 2D Synthetic Semantics Knowledge Distillation for 3D Visual Grounding, consists of two stages, i.e., Visual and Multi-Modal modules. LAR preserves the advantages of distilling the synthetic 2D knowledge to the 3D stream without requiring any additional information. Our experiments show a significant superior performance, where LAR achieves state-of-the-art results across three different 3D grounding benchmarks by outperforming the existing approaches, which do not rely on extra training data, by a wide margin, i.e., 5.0%, 1.9% and 2.3% on Nr3D, Sr3D and ScanRefer, respectively. Hence, despite the unfair comparison with SAT, which uses extra 2D images, LAR surpasses SAT by 1.6%, 2.7%, and 2.3% on Nr3D, Sr3D, and ScanRefer, respectively. Furthermore, we verify the robustness of LAR and its generalization ability via zero-shot experiments to intrinsic and extrinsic camera parameters and dying cameras. More qualitative results are attached in the supplementary materials.

References

[1] Ahmed Abdelreheem, Ujjwal Upadhyay, Ivan Skorokhodov, Rawan Al Yahya, Jun Chen, and Mohamed Elhoseiny. 3dreftransformer: Fine-grained object identification in real-world scenes using natural language. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 3941–3950, 2022.

[2] Panos Achlioptas, Ahmed Abdelreheem, Fei Xia, Mohamed Elhoseiny, and Leonidas Guibas. Referit3d: Neural listeners for fine-grained 3d object identification in real-world scenes. In *European Conference on Computer Vision*, pages 422–440. Springer, 2020.

[3] Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C. Lawrence Zitnick, and Devi Parikh. VQA: visual question answering. *CoRR*, abs/1505.00468, 2015.

[4] Alexander Buslaev, Vladimir I Iglovikov, Eugene Khvedchenya, Alex Parinov, Mikhail Druzhinin, and Alexandr A Kalinin. Albumentations: fast and flexible image augmentations. *Information*, 11(2):125, 2020.

[5] Dave Zhenyu Chen, Angel X Chang, and Matthias Nießner. Scanrefer: 3d object localization in rgb-d scans using natural language. In *European Conference on Computer Vision*, pages 202–221. Springer, 2020.

[6] Dave Zhenyu Chen, Qirui Wu, Matthias Nießner, and Angel X. Chang. D3net: A speaker-listener architecture for semi-supervised dense captioning and visual grounding in rgb-d scans, 2021.

[7] Zhenyu Chen, Ali Gholami, Matthias Niessner, and Angel X. Chang. Scan2cap: Context-aware dense captioning in rgb-d scans. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3193–3203, June 2021.

[8] Angela Dai, Angel X Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. Scannet: Richly-annotated 3d reconstructions of indoor scenes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5828–5839, 2017.

[9] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[10] Jiajun Deng, Zhengyuan Yang, Tianlang Chen, Wengang Zhou, and Houqiang Li. Transvg: End-to-end visual grounding with transformers. *CoRR*, abs/2104.08541, 2021.

[11] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[12] Mingtao Feng, Zhen Li, Qi Li, Liang Zhang, XiangDong Zhang, Guangming Zhu, Hui Zhang, Yaonan Wang, and Ajmal Mian. Free-form description guided 3d visual graph network for object grounding in point cloud. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3722–3731, 2021.

[13] Dailan He, Yusheng Zhao, Junyu Luo, Tianrui Hui, Shaofei Huang, Aixi Zhang, and Si Liu. Transrefer3d: Entity-and-relation aware transformer for fine-grained 3d visual grounding. In *Proceedings of the 29th ACM International Conference on Multimedia*, pages 2344–2352, 2021.

[14] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

[15] Ji Hou, Angela Dai, and Matthias Nießner. 3d-sis: 3d semantic instance segmentation of rgb-d scans, 2019.

[16] Ronghang Hu, Huazhe Xu, Marcus Rohrbach, Jiashi Feng, Kate Saenko, and Trevor Darrell. Natural language object retrieval. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4555–4564, 2016.

[17] Pin-Hao Huang, Han-Hung Lee, Hwann-Tzong Chen, and Tyng-Luh Liu. Text-guided graph neural networks for referring 3d instance segmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 1610–1618, 2021.

[18] Ayush Jain, Nikolaos Gkanatsios, Ishita Mediratta, and Katerina Fragkiadaki. Looking outside the box to ground language in 3d scenes. *arXiv preprint arXiv:2112.08879*, 2021.

[19] Ayush Jain, Nikolaos Gkanatsios, Ishita Mediratta, and Katerina Fragkiadaki. Looking outside the box to ground language in 3d scenes. *CoRR*, abs/2112.08879, 2021.

[20] Sahar Kazemzadeh, Vicente Ordonez, Mark Matten, and Tamara Berg. ReferItGame: Referring to objects in photographs of natural scenes. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 787–798, Doha, Qatar, Oct. 2014. Association for Computational Linguistics.

[21] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[22] Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. Ai2-thor: An interactive 3d environment for visual ai. *arXiv preprint arXiv:1712.05474*, 2017.

[23] Jason Ku, Melissa Mozifian, Jungwook Lee, Ali Harakeh, and Steven Waslander. Joint 3d proposal generation and object detection from view aggregation, 2018.

[24] Jean Lahoud and Bernard Ghanem. 2d-driven 3d object detection in rgb-d images. In *Proceedings of the IEEE international conference on computer vision*, pages 4622–4630, 2017.

[25] Alex H. Lang, Sourabh Vora, Holger Caesar, Lubing Zhou, Jiong Yang, and Oscar Beijbom. Pointpillars: Fast encoders for object detection from point clouds. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12689–12697, 2019.

[26] Kunpeng Li, Yulun Zhang, K. Li, Yuanyuan Li, and Yun Raymond Fu. Visual semantic reasoning for image-text matching. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4653–4661, 2019.

[27] Yongfei Liu, Bo Wan, Xiaodan Zhu, and Xuming He. Learning cross-modal context graph for visual grounding. *CoRR*, abs/1911.09042, 2019.

[28] Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A convnet for the 2020s. *arXiv preprint arXiv:2201.03545*, 2022.

[29] Junhua Mao, Jonathan Huang, Alexander Toshev, Oana Camburu, Alan L. Yuille, and Kevin Murphy. Generation and comprehension of unambiguous object descriptions. *CoRR*, abs/1511.02283, 2015.

[30] Junhua Mao, Jonathan Huang, Alexander Toshev, Oana Camburu, Alan L Yuille, and Kevin Murphy. Generation and comprehension of unambiguous object descriptions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 11–20, 2016.

[31] Jonah Philion and Sanja Fidler. Lift, splat, shoot: Encoding images from arbitrary camera rigs by implicitly unprojecting to 3d. In *European Conference on Computer Vision*, pages 194–210. Springer, 2020.

[32] Bryan A. Plummer, Liwei Wang, Chris M. Cervantes, Juan C. Caicedo, Julia Hockenmaier, and Svetlana Lazebnik. Flickr30k entities: Collecting region-to-phrase correspondences for richer image-to-sentence models. *CoRR*, abs/1505.04870, 2015.

[33] Charles R. Qi, Xinlei Chen, Or Litany, and Leonidas J. Guibas. Imvotenet: Boosting 3d object detection in point clouds with image votes, 2020.

[34] Charles R Qi, Wei Liu, Chenxia Wu, Hao Su, and Leonidas J Guibas. Frustum pointnets for 3d object detection from rgb-d data. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 918–927, 2018.

[35] Charles Ruizhongtai Qi, Li Yi, Hao Su, and Leonidas J Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017.

[36] Mengye Ren, Ryan Kiros, and Richard S. Zemel. Image question answering: A visual semantic embedding model and a new dataset. *CoRR*, abs/1505.02074, 2015.

[37] Junha Roh, Karthik Desingh, Ali Farhadi, and Dieter Fox. Languagerefer: Spatial-language model for 3d visual grounding. In *Conference on Robot Learning*, pages 1046–1056. PMLR, 2022.

[38] Arka Sadhu, Kan Chen, and Ram Nevatia. Zero-shot grounding of objects from natural language queries. *CoRR*, abs/1908.07129, 2019.

[39] Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. Alfred: A benchmark for interpreting grounded instructions for everyday tasks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10740–10749, 2020.

[40] Shuran Song and Jianxiong Xiao. Deep sliding shapes for amodal 3d object detection in rgb-d images, 2016.

[41] Johanna Wald, Helisa Dhamo, Nassir Navab, and Federico Tombari. Learning 3d semantic scene graphs from 3d indoor reconstructions. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[42] Chen Wang, Danfei Xu, Yuke Zhu, Roberto Martín-Martín, Cewu Lu, Li Fei-Fei, and Silvio Savarese. Densefusion: 6d object pose estimation by iterative dense fusion, 2019.

[43] Liwei Wang, Yin Li, Jing Huang, and Svetlana Lazebnik. Learning two-branch neural networks for image-text matching tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(2):394–407, 2019.

[44] Liwei Wang, Yin Li, and Svetlana Lazebnik. Learning two-branch neural networks for image-text matching tasks. *CoRR*, abs/1704.03470, 2017.

[45] Fanyi Xiao, Leonid Sigal, and Yong Jae Lee. Weakly-supervised visual grounding of phrases with linguistic structures. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5945–5954, 2017.

[46] Enze Xie, Zhiding Yu, Daquan Zhou, Jonah Philion, Anima Anandkumar, Sanja Fidler, Ping Luo, and Jose M Alvarez. Mˆ2bev: Multi-camera joint 3d detection and segmentation with unified birds-eye view representation. *arXiv preprint arXiv:2204.05088*, 2022.

[47] Danfei Xu, Dragomir Anguelov, and Ashesh Jain. Pointfusion: Deep sensor fusion for 3d bounding box estimation, 2018.

[48] Zhengyuan Yang, Tianlang Chen, Liwei Wang, and Jiebo Luo. Improving one-stage visual grounding by recursive sub-query construction. *CoRR*, abs/2008.01059, 2020.

[49] Zhengyuan Yang, Boqing Gong, Liwei Wang, Wenbing Huang, Dong Yu, and Jiebo Luo. A fast and accurate one-stage approach to visual grounding. *CoRR*, abs/1908.06354, 2019.

[50] Zhengyuan Yang, Yijuan Lu, Jianfeng Wang, Xi Yin, Dinei Florencio, Lijuan Wang, Cha Zhang, Lei Zhang, and Jiebo Luo. Tap: Text-aware pre-training for text-vqa and text-caption. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8751–8761, 2021.

[51] Zhengyuan Yang, Songyang Zhang, Liwei Wang, and Jiebo Luo. Sat: 2d semantics assisted training for 3d visual grounding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1856–1866, 2021.

[52] Linwei Ye, Mrigank Rochan, Zhi Liu, and Yang Wang. Cross-modal self-attention network for referring image segmentation. *CoRR*, abs/1904.04745, 2019.

[53] Licheng Yu, Zhe Lin, Xiaohui Shen, Jimei Yang, Xin Lu, Mohit Bansal, and Tamara L. Berg. Mattnet: Modular attention network for referring expression comprehension. *CoRR*, abs/1801.08186, 2018.

[54] Licheng Yu, Patrick Poirson, Shan Yang, Alexander C Berg, and Tamara L Berg. Modeling context in referring expressions. In *European Conference on Computer Vision*, pages 69–85. Springer, 2016.

[55] Licheng Yu, Patrick Poirson, Shan Yang, Alexander C. Berg, and Tamara L. Berg. Modeling context in referring expressions. *CoRR*, abs/1608.00272, 2016.

[56] Licheng Yu, Hao Tan, Mohit Bansal, and Tamara L Berg. A joint speaker-listener-reinforcer model for referring expressions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 7282–7290, 2017.

[57] Zhihao Yuan, Xu Yan, Yinghong Liao, Ruimao Zhang, Sheng Wang, Zhen Li, and Shuguang Cui. Instancerefer: Cooperative holistic understanding for visual grounding on point clouds through instance multi-level contextual referring. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1791–1800, 2021.

[58] Lichen Zhao, Daigang Cai, Lu Sheng, and Dong Xu. 3dvg-transformer: Relation modeling for visual grounding on point clouds. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2928–2937, 2021.

A   Appendix

Our Supplemental Material contains the following sections:

- Demonstrate our synthetic images generator algorithm (SIG).
- More ablations.
- Qualitative results.
- Our source code.

A.1   Synthetic Images Generator Algorithm

Algorithm 1, demonstrates a pseudo-code for our SIG module that projects arbitrary 3D Point clouds representing an object to a 2D image.

Algorithm 1 2D Synthetic Images Generator algorithm

Input: x_i^{pc}: Point-cloud for an object i in the scene,
        I: The pinhole camera intrinsic parameters,
        O_s: Scene center.
Output: x_i^{img}: 2D synthetic image that represents the object i.

1: // Get the prominent face:
2: $minDist \leftarrow Dist(O_{l_0}, O_s)$
3: **for** each face **do**
4:     **if** $Dist(O_{l_k}, O_s) <= minDist$ **then**
5:         $l' \leftarrow l_k$
6:         $minDist \leftarrow Dist(O_{l_k}, O_s)$
7:     **end if**
8: **end for**
9: $Cam_p = [d_x^f, d_y^f, d^{up}]$
10: // Build transformation matrix $M \in \mathbb{R}^{4 \times 4}$
11: $V^f \leftarrow \|Cam_p - O_{l'}\|$
12: $V^r \leftarrow \|V^f \otimes [0, 0, 1]\|$
13: $V^{up} \leftarrow \|V^r \otimes V^f\|$
14: $M \leftarrow \begin{bmatrix} V^r & V^{up} & V^f & Cam_p \\ 0 & 0 & 0 & 1 \end{bmatrix}.$
15: $x_i^{cam} \leftarrow Dot(M, x_i^{pc})$
16: $x_i^{img} \leftarrow Dot(I, x_i^{cam})$
17: $x_i^{img} \leftarrow x_i^{cam} / x_i^{cam}[:, 2]$
18: **return** (x_i^{img})

A.2   Ablations Studies

A.2.1   Different 2D semantic fusion techniques.

Driven by the aforementioned results in Table 2, we use five virtual cameras set in a cocoon setup around each object as depicted in Figure 1, and the image resolution is 128. In Table 9, we study two fusion techniques to combine the features generated from the five views. The first method is a simple addition operation, and the second one is a learnable fusion mechanism where a 1D-Conv. is used where its kernel size is set to the number of the views used, i.e., in our case set to five. As expected, the learnable fusion scheme; 1D-Conv., performs better than the none learnable scheme;

addition. Our 2D variant built on top of Referit3D [2] is used in this ablation, where the 2D stream is only used.

Table 9: Comparison between different 2D semantic fusion techniques.

Method	Referring Acc.	Classification Acc.
Addition	35.3	62.7
1D-Conv.	**36**	**64.82**

Table 10: Comparison between different multi-modal fusion techniques.

Method	Referring Acc.	Classification Acc.
Addition	38.8	60.3
1D-Conv.	39.2	60.8
Transformer	**41.9**	**62.2**

A.2.2 Different multi-modal fusion techniques.

In addition, we study three fusion techniques for the 3D, and 2D multi-modal features, M^{pc} and M^{img}, respectively. In this ablation, we only utilize the ROI as the 2D semantic information, set the image resolution to 32, and set the number of multi-views to five. As shown in Table 10, using a transformer while fusing both multi-modal features achieves the best accuracy.

Optionally include extra information (complete proofs, additional experiments and plots) in the appendix. This section will often be part of the supplemental material.

A.3 Quantitative Results

This section analyzes the qualitative results from the successful and the failure cases on the Nr3d dataset. In addition to Figure 7 that shows successful scenarios and Figure 8 that shows failure scenarios, we attach a short video to demonstrate more scenarios.

A.3.1 Successful Scenarios

LAR achieves top-ranking results on both the Nr3D and Sr3D datasets. The results in Figure 7 demonstrate the correct instance localization on the Nr3D datasets only. The ground truth boxes are marked green and our model prediction marked in blue. Our analysis shows that LAR correctly understands the global context based on natural language description. For example, in Figure 7 (a-f), LAR understands relationships, e.g. (behind it, middle of, furthest from ..), which proves that our proposed model understands instance-to-instance and instance-to-background relations. As well as understanding colors and shapes related to language, LAR also can determine the meaning of terms such as "green," Figure 7 (e).

A.3.2 Failure Scenarios

Figure 8 shows representative failure cases of LAR. Despise the incorrect instance localization LAR managed to allocate the instance with the same class as the target. As shown in Figure 8 (d, e), we observed that failure cases require an understanding of "against the wall", 'Facing the windows, "which is determined by camera view dependency. Despite LAR's progress in view-dependent and independent samples, view understanding remains a challenge. Besides, other state-of-the-art models suffer from the same issue. In addition, some LAR failure cases are caused by ambiguous queries. Figure 8 (a,b,c,e, f) shows a complex and compound language description to describe the target instance, which in some cases, both models and human annotators mix up similar objects.

To summarize, We show the effect of using synthetic 2D images, which improves the model instance and context-aware representation. However, our model has limitations due to ambiguous and complex queries. Although some cases remained unsolved, LAR improved progress in the camera view dependency samples. Therefore, we believe our model LAR surpasses existing state-of-the-art by a significant margin.

A.4 Source Code

our source code is attached in the supplementary material, where it contains the source code for our Synthetic Images Generator (SIG), our architecture, training functions, and evaluation functions. For more details regarding our implementation, refer to the Readme file attached with the source code.

LAR(Ours)   GT

(a)
The correct **chair** has a
wall directly **behind it**.

(b)
The correct **pillow** is on the
bed and is in the **middle of**
the others.

(c)
The **trash can furthest**
from a chair.

(d)
Facing the exit door, the
table on the right.

(e)
Green section of
couch directly
below frame.

(f)
The **trash can below** the
sink **on the right**.

Figure 7: Qualitative results of successful cases from our LAR on Nr3d. The ground truth boxes are marked green, and the distractors boxes are displayed in yellow. Our model prediction marked as blue.

LAR (Ours) **GT**

(a)
The **chair** to the **far left hand side** of the taller desk with the computer monitor on it.

(b)
The **desk beneath the clock on the right hand side** of the two desks grouped together.

(c)
The **pillow second from the back** of the row on the **right hand side** of the bed.

(d)
The **box against** the wall.

(e)
Facing the windows the **desk** in the **bottom left** of the room.

(f)
Cabinet attached to the ground.

Figure 8: Qualitative results of failure cases from our LAR on Nr3d. The Ground truth boxes are shown in green, and the distractors boxes are displayed in yellow. The incorrect predictions by our model marked as red.