CAN KERNEL TRANSFER OPERATORS HELP FLOW BASED GENERATIVE MODELS?

ABSTRACT

Flow-based generative models refer to deep generative models with tractable likelihoods, and offer several attractive properties including efficient density estimation and sampling. Despite many advantages, current formulations (e.g., normalizing flow) often have an expensive memory/runtime footprint, which hinders their use in a number of applications. In this paper, we consider the setting where we have access to an autoencoder, which is suitably effective for the dataset of interest. Under some mild conditions, we show that we can calculate a mapping to a RKHS which subsequently enables deploying mature ideas from the kernel methods literature for flow-based generative models. Specifically, we can *explicitly* map the RKHS distribution (i.e., approximate the flow) to match or align with a template/well-characterized distribution, via kernel transfer operators. This leads to a direct and resource efficient approximation avoiding iterative optimization. We empirically show that this simple idea yields competitive results on popular datasets such as CelebA, as well as promising results on a public 3D brain imaging dataset where the sample sizes are much smaller.

1 INTRODUCTION

A flow-based generative model refers to a deep generative model composed using a set of invertible transformations. While GANs and VAEs remain the two dominant generative models in the community, flow based formulations have continually evolved and now offer competitive performance in applications including audio/speech synthesis Kim et al. (2019; 2020), text to speech Miao et al. (2020), photo-realistic image generation Kingma & Dhariwal (2018), and learning cross-domain mappings Mahajan et al. (2020). An important property of such models is the explicit use of a tractable likelihood function, which enables leveraging maximum likelihood principles during training as well as efficient/exact density estimation and sampling. The formulation is invertible by design but this involves higher memory requirements. For example, permitting the bijective mapping to be expressive enough involves increases in the memory footprint Lee et al. (2020); Kim et al. (2019), an issue that is a focus of several recent results Jacobsen et al. (2018); Chen et al. (2016). Moreover, in these models we need to calculate the inverse and backpropagate through all invertible transformations during training. Calculating the inverse incurs a multiplicative increase in cost, usually as a function of the feature dimension, relative to the calculation of the likelihood, an issue addressed to some extent in Dinh et al. (2017); Kingma & Dhariwal (2018).

At a high level, a flow-based generative model bijectively pushes the data density from a source to a target, i.e., from a known simple distribution to an unknown (may be intractable) data distribution. During training, we seek to learn this bijective mapping by maximizing the likelihood of the mapped

Figure 1: Representative generated images (of resolution 128×128) using our proposed algorithm.

training samples. In the generation step, we need the inverse of this mapping (given such an inverse exists) to map from a sample drawn from the known distribution back to the input (data) space. When the known distribution is appropriately chosen (e.g., Gaussian), the Jacobian of the transformation mapping has additional structure (e.g., lower triangular) and immensely facilitates training.

Rationale. The starting point of our work is the existing literature on Koopman and Perron-Frobenius operators Song et al. (2009); Fukumizu et al. (2013); Klus et al. (2020), that offers an arguably easier, optionally *linear*, procedure to push-forward densities. For instance, it is known that *given infinite-dimensional observables of the input measurements*, there exists a **linear** transfer operator that perfectly pushes one probability density to another. Of course, this is not practically beneficial because explicitly constructing such infinite-dimensional observables for the data could be intractable. Nonetheless, results in control theory demonstrate that the idea can still be effective in specific cases, using approximations with either spectral analysis of large but finite number of observable functions Williams et al. (2015) or via a search for potential eigenfunctions using neural networks Li et al. (2017); Lusch et al. (2018). Within the last year, several results describe its potential benefits in machine learning problems as well Li et al. (2020); Azencot et al. (2020).

Can Transfer Operators help? Conceptually, it is not difficult to see how the foregoing idea could potentially help (or simplify) flow-based generative models. In principle, using a transfer operator, one could push-forward the input data distribution to a target distribution of our choice, if both have already been mapped to a sufficiently high dimensional space. If – additionally – the operator could also be inverted, this strategy may, at least, be viable. Of course, several key components are missing. We need to **(a)** assess if setting up a suitable infinite dimensional space is possible, **(b)** identify if we can estimate the transfer operator and then finally, **(c)** check if the procedure works at all.

Infinite dimensional mapping. Mapping input data to infinite dimension spaces (which in this case could serve as the space of observables) is well studied and textbook kernel method ideas may suffice. Further, known results concretely links kernels to infinite width deep neural networks Neal (1994) and exciting results on neural kernels have appeared in the last few years Jacot et al. (2018); Arora et al. (2019). Utilizing these results, a mean embedding on the corresponding Reproducing Kernel Hilbert Space (RKHS) would uniquely identify the distribution in the input space. Therefore, the problem of identifying a nonlinear mapping in the input space reduces to estimating a linear mapping operator between two empirical mean kernel embeddings where recent results on kernel transfer operators Klus et al. (2020) could be relevant or applicable. However, due to the high variability of the data, estimation of the distribution directly in the input space can be difficult. But, if the input space is low-dimensional or otherwise structured, this problem could be mitigated. Fortunately, for many image datasets, one can identify a low-dimensional latent space such that, in theory, the above pipeline could be instantiated, enabling us to learn an operator.

Auto-encoders. Images often lie close to an (unknown) lower dimensional manifold $\mathcal{M} \subset \mathbf{R}^m$ such that $\dim(\mathcal{M}) \ll m$, and operating with densities in a lower dimensional setting is often much easier. VAEs leverage this explicitly via auto-encoders. If the parameterized empirical density is $p_\tau(x)$, in VAEs, we write it as $\int p_\tau(x|z)p(z)dz$ where z is the low dimensional representation with a suitable prior. We then use a decoder distribution $q_{\tau'}(z|x)$ and an encoder distribution $p_\tau(x|z)$ and train the parameters τ and τ'. In practice, $p_\tau(\cdot)$ and $q_{\tau'}(\cdot)$ are assumed to be Gaussian, but it is known that jointly fitting the manifold as well as regressing to a particular prior distribution can be challenging in VAEs Kingma et al. (2016); Dai & Wipf (2019). Now, consider the following approach, where we do not impose a distributional assumption on z. If a well-regularized auto-encoder is able to capture information about the data generating density Alain & Bengio (2014), we can think of z as the input measurements (likely, meaningful representations from the input data) which is subsequently mapped to an infinite dimensional space (of observables of these measurements). Now, if we could push-forward the embedded RKHS distribution to the RKHS mapping of a simpler distribution, similar to flow-based generation, one could easily sample from the simple (e.g., standard normal) distribution and transform it via the learned mapping to samples on the latent space. In summary, instead of explicitly searching for the eigenfunctions, we propose to *Step 1:* embed the density from an auto-encoder into a RKHS, *Step 2:* learn a kernel transfer operator in RKHS in one step. In the remainder of this paper, we will provide the details to operationalize this idea and show that this simple approach, in fact, performs surprisingly well with highly favorable computational properties.

2 PRELIMINARIES

We start with the definition of reproducing kernel Hilbert space (RKHS) and the kernel embedding of probability distributions which are the building blocks of this paper.

Definition 1 (RKHS Aronszajn (1950)). *Given a set $\mathcal{X}$ and $\mathcal{H}$ to be a set of functions $\Phi : \mathcal{X} \to \mathbf{R}$, $\mathcal{H}$ is called a reproducing kernel Hilbert space (RKHS) with corresponding product $\langle ., . \rangle_{\mathcal{H}}$ if there exists a function $k : \mathcal{X} \times \mathcal{X} \to \mathbf{R}$ (called a reproducing kernel) such that (i) $\forall X \in \mathcal{X}, \Phi \in \mathcal{H}, \Phi(X) = \langle \Phi, k(X, .) \rangle_{\mathcal{H}}$ (ii) $\mathcal{H} = span\{k(X, .), X \in \mathcal{X}\}$*

The *kernel mean embedding* can be used to embed a probability measure in a RKHS.

Definition 2 (Mean Embedding Smola et al. (2007)). *Given a probability measure p on $\mathcal{X}$ with an associated RKHS $\mathcal{H}$ equipped with a reproducing kernel k such that $\sup_{X \in \mathcal{X}} k(X, X) < \infty$, the mean embedding of μ in RKHS $\mathcal{H}$, denoted by $\mu_{\mathcal{H}} : \mathcal{X} \to \mathbf{R}$, is defined as $\mu_{\mathcal{H}} = \int k(X, .)p(X)$.*

For a characteristic kernel, the mapping from an input space distribution to its corresponding kernel mean embedding is one-to-one. Thus, two distributions in the input space are identical if and only if their kernel mean embedding matches exactly. This property enables *Maximum Mean Discrepancy (MMD)* for distribution matching. For a finite number of samples $\{X_i\}_{i=1}^{N}$, drawn from the probability measure μ, the mean embedding $\mu_{\mathcal{H}}$ can be estimated using $\hat{\mu_{\mathcal{H}}} = {}^{1}/{}_{N} \sum_{i=1}^{N} k(X_i, .)$.

Our developments are focused on simplifying flow-based generative models,

Definition 3 (Flow-based generative model Dinh et al. (2014)). *A flow-based generative model explicitly learns the data distribution by trying to bijectively map it to a tractable density via invertible transformations. Formally, given a random variable $\mathbf{z}$ following a tractable density, i.e., $\mathbf{z} \sim p_\theta(\mathbf{z})$, a flow-based model learns an invertible mapping f_ϕ such that the data sample $\mathbf{x} = f_\phi(\mathbf{z})$ and the corresponding data distribution, $p_{\widehat{\theta}}(\mathbf{x}) = f_* p_\theta(\mathbf{z})$, where, $f_* = |\frac{dz}{dx}|$ is the push-forward operator.*

3 A SIMPLIFICATION STRATEGY FOR FLOW-BASED GENERATIVE MODELS

Flow-based generative model directly learn the mapping from a known distribution to the target data distribution in the input space through likelihood maximization. During image generation, the fact that data may often lie on or near a low-dimensional manifold is usually not explicitly leveraged. If one could estimate this manifold perfectly, we could uniquely identify a distribution in the input space. But often, the manifold can only be empirically estimated. Our simplifying assumption here is that with some structural or smoothness constraints on the distribution on the latent space, we should still be able to approximately identify the true distribution. VAEs use this intuition to make the latent distribution consistent with a standard normal distribution, and several contemporary works also propose estimating flow on latent spaces Kingma et al. (2016); Mahajan et al. (2020). We will follow this rationale and use an autoencoder – here, benefiting from the reduced variance in the latent space, our approach will learn the mapping from a known distribution to the empirical latent distribution with the expectation that the optimal posterior for likelihood maximization converges to the empirical distribution as the variance is decreased.

Structure of the latent space. We will assume that a suitable auto-encoder is either provided or can be successfully trained from scratch for the data at hand. Given measurements from an input data space, $\mathcal{M}$, we seek to learn a mapping $E : \mathcal{M} \to \mathcal{L} \subset \mathbf{R}^d$, with $d < m$, where $\mathcal{M} \subset \mathbf{R}^m$. Additionally, we also learn the inverse of the mapping E which is denoted by $D : \mathcal{L} \to \mathcal{M}$, i.e., we require $D \circ E = \text{id}$ (identity). Further, we require $\mathcal{L}$ to be a bounded subset of $\mathbf{R}^d$. For simplicity, we model it as a unit hypersphere $\mathbf{S}^{d-1}$. This essentially ensures that $\mathcal{L}$ is **(a)** bounded **(b)** geodesically complete **(c)** geodesically convex space.

Remark 1. A bounded latent space with specified structure provides several benefits over one without any such constraints. First, it guarantees that the Grammian matrix constructed with a (positive-definite) kernel function is bounded, which is required for a valid empirical estimation of the mean embedding in Def. 2 Song et al. (2009). Moreover, the projection onto the hypersphere also helps ensure the positive-definiteness of kernels constructed using the latent representations, that we will use later. At this point, the requirement of geodesic completeness and convexity may not be apparent but these properties will be useful for sample generation.

Figure 2: A description of generative procedure in our method. *(a) schematic of an auto-encoder (b) kernel representations of latent space and noise from prior (c) operator learning and inferencing (d) solve pre-image and decode the generated latent representation to obtain final generation result in data space*

3.1 USING TRANSFER OPERATORS TO ESTIMATE FLOW

If training the auto-encoder provides us a suitably well-structured latent space, as desired, we can now study how the density transfer operators can help transfer a tractable density to the density on the latent space, i.e., *mimicking* the mechanics within a flow-based generative model.

Transfer operators. Let $\{X_t\}_{t\geq0}$ be a stationary and ergodic Markov process defined on $\mathcal{X}$. Then, we can define the transition density function, p_τ (with time lag τ), by

$$P[X_{t+\tau} \in \mathcal{A}|X_t = x] = \int_{\mathcal{A}} p_\tau(y|x)dy, \text{where } \mathcal{A} \text{ is a measurable set on } \mathcal{X}. \quad (1)$$

Let $L^1(\mathcal{X})$ be the space of probability densities. We wish to emulate the dynamical system of interest by instead utilizing a well-known transfer operator, namely the (Ruelle) Perron-Frobenius operator Mayer (1980), where the "transfer" terminology originates from statistical mechanics.

Definition 4 (Perron-Frobenius operator Mayer (1980)). *The Perron-Frobenius (PF) operator $\mathcal{P}$: $L^1(\mathcal{X}) \to L^1(\mathcal{X})$ push-forwards or transfers a probability density $p_t \in L^1(\mathcal{X})$ given the lag τ as $(\mathcal{P}p_t)(y) = \int p_\tau(y|x)p_t(x)dx.$*

Remark 2. If such an operator can be efficiently estimated, we can use it to transfer the tractable probability density to the target distribution whose density is generally unknown. However, since we do not make any distributional assumptions on the target distribution, a linear solution to such dynamics in the input space, in general, may not exist. But notice that performing these operations *after* a mapping to an higher dimensional (linear) space is more sensible. If the dynamical system we wish to emulate involves an action Γ (say, a matrix with positive entries), in other words, the iterates Γ^t, the behavior of the Perron-Frobenius operator must emulate Γ. This statement is exact for certain Markov chains. Further, since we wish to utilize a mapping to a RKHS, we will need to utilize analogous results for kernelized Perron-Frobenius operators Fukumizu et al. (2013).

Definition 5 (Kernel Perron-Frobenius operator Fukumizu et al. (2013)). *Let $X = X_t$ and $Y = X_{t+\tau}$. Let $\mathcal{H}$ (where an element is denoted by Φ_H) and $\mathcal{G}$ (where an element is denoted by Φ_G) be the RKHSs on X and Y respectively. Let the cross-covariance operator $C_{YX} : \mathcal{G} \to \mathcal{H}$ be defined as $C_{YX} = E_{YX}[\Phi_G(y) \otimes \Phi_H(x)]$. Let us also assume that the covariance operator $C_{XX} : \mathcal{H} \to \mathcal{H}$ is defined analogously. Assume that $g \in \mathcal{H}$, the kernel Perron-Frobenius (kPF) operator, denoted by $\mathcal{P}_\epsilon : \mathcal{G} \to \mathcal{H}$, is defined by $C_{XX}\mathcal{P}_k g = C_{YX}g$ (2).*

The above defined kPF operator can be used to transfer $g \in \mathcal{H}$, denoted by (as given in equation 2), $\mathcal{P}_k g = (C_{XX} + \epsilon I)^{-1} C_{YX}g$. Notice that this equation is well-defined only if $\mathcal{G} = \mathcal{H}$. But in our setting, we are interested in transferring a probability density, $p_t \in L^1(X)$. So, *kPF cannot be used directly since g lies on a RKHS and may not be a probability density.* As a solution, it turns out that we can utilize mean embedding as defined in Defn. 2. Thus, given a $p_t \in L^1(X)$, we may first use mean embedding to get the corresponding $\mu_\mathcal{H} \in \mathcal{H}$. Then, the Perron-Frobenius operator for *embedded* densities, denoted by *embedded Perron-Frobenius operator*, $\mathcal{P}_\epsilon$, can be expressed as $\mathcal{P}_\epsilon = C_{YX}(C_{XX} + \epsilon I)^{-1}$. Notice that compared to kPF operator, here we do not need the

assumption of $\mathcal{G} = \mathcal{H}$ and this is due to the reproducing property of kernel (see Klus et al. (2020) section 3.3 for details).

The sample estimate of the embedded Perron-Frobenius operator is given by $\widehat{\mathcal{P}}_\epsilon = \widehat{\mathcal{C}}_{YX}\widehat{\mathcal{C}}_{XX}^{-1} = \Phi_G \left(G_{XX} + N\epsilon I\right)^{-1} \Phi_H^T$ (3), with the terms of the RKHS defined as before. Let $\mathcal{E}$ be the mean embedding operator, the following proposition suggests that mapping p_t with a (nonlinear) transfer operator $\mathcal{P}$ in the input space followed by a mean embedding is equivalent to mapping the mean embedded p_t, or namely μ_t, with $\mathcal{P}_\epsilon$.

Proposition 1 (Klus et al. (2020)). *With the above notations, $\mathcal{E} \circ \mathcal{P} = \mathcal{P}_\epsilon \circ \mathcal{E}$.*

Remark 3. Prop. 1 will help transfer the embedded density using the closed form expression in equation 3. In particular, the commutativity in the proposition justifies the use of mean-embedding followed by the kPF operator instead of estimating a non-linear PF operator in the input space.

With these results, we have all the tools in hand to have almost a single step flow based generative model if we start from a well-structured encoding latent space.

3.2 KERNEL TRANSFER OPERATOR FOR SAMPLE GENERATION

We now present an algorithm for sample generation assuming that a pre-trained auto-encoder is available. For the moment, it also suffices to assume that the choice of a suitable kernel has already been made (we will discuss this shortly). We can now walk through the sample generation process.

Notations. We assume we have N data samples on $\mathcal{M}$ with their respective latent space representation $\{l_i\}$ where the samples will be indexed by i. Let $k_L : \mathcal{L} \times \mathcal{L} \to \mathbf{R}$ be the (bounded) kernel (and the corresponding RKHS $\mathcal{G}$). Let $\{\mathbf{z}_i\} \subset \mathcal{Z}$ be samples from the prior distribution, which we model as a uniform distribution on sphere, $u_{S^{d-1}}$, with $k_Z : \mathcal{Z} \times \mathcal{Z} \to \mathbf{R}$ as the (bounded) kernel (and the corresponding RKHS $\mathcal{H}$). We will construct

$$K_L = [k_L(\mathbf{l}_n, \mathbf{l}_o)] \in \mathbf{R}^{N \times N}; K_Z = [k_Z(\mathbf{z}_i, \mathbf{z}_j)] \in \mathbf{R}^{N \times N}; \mathbf{v} = [k_Z(\mathbf{z}_k, \mathbf{z}^*)] \in \mathbf{R}^N. \quad (4)$$

We can generate a data sample using the following simple steps:

1. Draw a sample $\mathbf{z}^* \sim u_{S^{d-1}}$. Construct $\mathbf{s} = \Phi_G^\top \mathcal{P}_\epsilon \Phi_H^* = K_L K_Z^{-1} \mathbf{v}^t$, where $\Phi_H^* = k(z^*, .)$.

2. Compute the approximate preimage of s given by $X = D\left(\mathrm{gI}(\{\mathbf{l}_j\}_{j=1}^\gamma, \{w_j\}_{j=1}^\gamma)\right)$, where $\{\mathbf{l}_j\}_{j=1}^\gamma$ are the top λ (a hyper-parameter) latent representations and $\{\mathbf{w}_j\}_{j=1}^\gamma$ are the corresponding weighting factors from s. $\mathrm{gI}(., .)$ denotes the geodesic interpolation algorithm described in Fig 4

Generator

(a) Let $\mathbf{z}^*$ be a sample drawn from $u_{S^{d-1}}$. In (3), we post-multiply with $k_Z(\mathbf{z}^*, .)$ to get $\widehat{\mathcal{P}}_\epsilon k_Z(\mathbf{z}^*, .) = \Phi_G \left(G_{XX} + N\epsilon I\right)^{-1} [k_Z(\mathbf{z}_i, \mathbf{z}^*)]^t$ (5), where, **(a)** $G_{XX} = [k_Z(\mathbf{z}_i, \mathbf{z}_j)]$. **(b)** $\Phi_G = [k_L(\mathbf{l}_i, .)]^\top$

(b) We take inner product, $\langle ., . \rangle_\mathcal{G}$ of Φ_G with $\widehat{\mathcal{P}}_\epsilon k_Z(\mathbf{z}^*, .)$ to get
$\langle \Phi_G, \widehat{\mathcal{P}}_\epsilon k_Z(\mathbf{z}^*, .) \rangle = \Phi_G^\top \Phi_G \left(G_{XX} + N\epsilon I\right)^{-1} [k_Z(\mathbf{z}_i, \mathbf{z}^*)]^\top = [k_L(\mathbf{l}_n, \mathbf{l}_o)] \cdot ([k_Z(\mathbf{z}_i, \mathbf{z}_j)] + N\epsilon I)^{-1} [k_Z(\mathbf{z}_k, \mathbf{z}^*)]^\top = K_L (K_Z + N\epsilon I)^{-1} \mathbf{v}^\top$, where $K_L = [k_L(\mathbf{l}_n, \mathbf{l}_o)] \in \mathbf{R}^{N \times N}$ and $K_Z = [k_Z(\mathbf{z}_i, \mathbf{z}_j)] \in \mathbf{R}^{N \times N}$; $\mathbf{v} = [k_Z(\mathbf{z}_k, \mathbf{z}^*)] \in \mathbf{R}^N$.

(c) Notice that both K_Z and $(K_Z + N\epsilon I)^{-1}$ can be pre-computed.

(d) Let $\mathbf{s} = \langle \Phi_G, \widehat{\mathcal{P}}_\epsilon k_Z(\mathbf{z}^*, .) \rangle$. Let $\{\mathbf{l}_j\}_{j=1}^\gamma$ be the latent space representations of γ data samples with largest corresponding entries in $\mathbf{s}$ (in descending order).

(e) Return the generated sample $X = D\left(\mathrm{gI}\left(\{\mathbf{l}_j\}_{j=1}^\gamma, \{w_j\}_{j=1}^\gamma\right)\right)$, here, $w_j = \mathbf{s}_j / \sum_i \mathbf{s}_i$ and $\mathrm{gI}(., .)$ is the geodesic interpolation algorithm (as presented in Fig. 4).

Figure 3: Step by step details of our sample generation algorithm.

Properties. If K_Z is indeed invertible, the empirical mean embedding of samples generated using the proposed algorithm (assuming the preimage is exact) is equal to the empirical mean embedding of the latent representations, indicating a match in distribution. Further, we use weighted Fréchet mean on sphere as approximate preimage of sample in RKHS. Recall that we model $\mathcal{L}$ as a unit hypersphere, $\mathbf{S}^{d-1}$. Therefore, the geodesic interpolation (gI) module uses the geodesic on a hypersphere and iteratively computes the weighted Fréchet mean Fréchet (1948) of top γ latent representations (see Fig. 4). It has the follow-

> **Geodesic Interpolation (gI)**
>
> (a) Let the inputs be $\{\mathbf{l}_i\}_{i=1}^{\gamma} \subset \mathbf{S}^{d-1}$ and $\{w_i\}_{i=1}^{\gamma}$.
> (b) Initialize $\mathbf{m} = \mathbf{l}_1$.
> (c) For $j = 2, \cdots, \gamma$
>   (a) Set $t = w_j / \sum_{k=1}^{j} w_k$, $\quad \theta = \arccos(\mathbf{m}^t \mathbf{l}_j)$.
>   (b) Update
> $$\mathbf{m} = \frac{1}{\sin(\theta)} \left(\mathbf{m} \sin\left((1-t)\theta\right) + \mathbf{l}_j \sin\left(t\theta\right) \right).$$
> (d) Return $\mathbf{m}$ as the output.

Figure 4: The geodesic interpolation algorithm

ing properties: **(i)** the geodesically completeness of the latent space guarantees that the geodesic interpolation is well-defined **(ii)** the geodesic convexity of the latent space guarantees that the output of "gI" algorithm lies on the latent space **(iii)** the "gI" algorithm converges asymptotically to the true solution Salehian et al. (2015).

Choice of Kernels. In order to be able to linearize the dynamics between the prior and the target distribution, one must first identify a set of nonlinear basis functions such that the corresponding dynamics lies in its span. Known results in dynamical systems guarantee the existence of such a linear operator, such as the Koopman operator Koopman (1931), given an infinite set of basis functions. But rather than identifying certain modes that best characterize the dynamics Williams et al. (2015); Brunton et al. (2016) we care most about minimizing the error of the transferred density, and whether the span of functions is rich/expressive enough and can be efficiently computed. The behavior of Radial Basis Function (RBF) and arc-cosine, two standard options in the literature, in our setting can be observed in Fig. 5, where an operator is learned in RKHS to push a uniform distribution on $\mathbf{S}^2$ to the empirical distribution of 10,000 random samples from MNIST wrapped on $\mathbf{S}^2$. Subplot (b) and (c) show the generated samples. Observe that the choice of kernel has a clear influence on the posterior, and a kernel with superior empirical behavior would be desirable.

Figure 5: 10k samples from MNIST dataset (*left to right*) (a) projected on $\mathbf{S}^2$ shown in (θ, ϕ), and 10K generated samples using (b) RBF (c) arccos (d) NTK. Minimum regularization has been applied to all kernels to ensure invertibility. Color of sampled points represents the class of their 'nearest' point in the feature space.

NTK. We use Neural Tangent Kernel (NTK) Jacot et al. (2018) as our embedding kernel due to the following properties: **(a)** NTK, in theory, corresponds to a trained infinitely-wide neural network, and can be non-asymptotically approximated Arora et al. (2019). **(b)** For well-conditioned inputs (i.e., no duplicate points) on the sphere, the positive-definiteness of NTK is guaranteed Jacot et al. (2018), and therefore it can be inverted without the need to regularize (although in practice, due to numerical issues, a weak regularization is sometimes needed). **(c)** Unlike other parametric kernels such as RBF kernels, NTK is less sensitive to hyperparameters, as long as the number of units used is large enough. The embedding of generated samples for MNIST using NTK is also shown in Fig. 5. Observe that the sample distribution is similar to the original distribution.

Nyström's approximation. A known bottleneck with kernel based methods is instantiating a kernel matrix whose size depends on the dataset size. Here, we use use the Nyström's method Nyström (1930) to obtain approximate kernel matrices. More specifically, a kernel matrix $K \in \mathbf{R}^{N \times N}$ can be approximated by $\widetilde{K} = KS\left(S^T K S\right)^{\dagger} S^T K$, where $S \in \mathbf{R}^{N \times s}$ is the sampling matrix. To minimize information loss, we use the RecursiveRLS-Nyström algorithm proposed in Musco & Musco (2017) to sample S. Notice that after the approximation, we only need to store $KS \in \mathbf{R}^{N \times s}$ and $S^T K S \in \mathbf{R}^{s \times s}$ matrices to obtain the Nyström approximation of K, bringing down the memory complexity from $O(N^2)$ to $O(Ns + s^2)$. When $s \ll N$, the savings are significant.

4 EXPERIMENTAL RESULTS

We qualitatively evaluate the proposed generative model on two types of applications, **(a)** datasets with a sufficient number of samples to model the data distribution **(b)** datasets with fewer number of samples so that learning the data distribution is harder . In the first case, we use standard vision datasets, including MNIST, CIFAR10, and CelebA, where the number of data samples is larger than the dimension. In order to handle the more challenging second case, we use a dataset of T1 Magnetic Resonance (MR) images from a public brain imaging project called Alzheimer's Disease Neuro-Imaging Initiative (ADNI).

The purpose of the first set of experiments is to show that the proposed method yields competitive measures compared to other non-adversarial generative methods while enjoying the benefit of *one step* density estimation. In the second setting, our goal is to demonstrate that unlike traditional non-adversarial models, our proposed method produces reasonable sample generation both quantitative and qualitatively.

	MNIST	CIFAR	CelebA
WGAN	6.7	55.2	41.3
WGAN-GP	20.3	55.8	30.3
Vanilla VAE	**13.7**	111.0	52.1
Two-stage VAE	18.3	110.3	44.7
$SRAE_{rand\ interp}$	28.5	**104.7**	64.3
$SRAE_{Glow}$	26.1	110.9	50.9
$SRAE_{RBF\text{-}kPF\ 10k}(ours)$	24.7	124.5	57.7
$SRAE_{NTK\text{-}kPF\ 10k}(ours)$	15.0	123.3	39.9
$SRAE_{NTK\text{-}kPF\ Nyström}(ours)$	15.9	119.4	**39.2**

Table 1: Comparative FID values.

Computer vision datasets: We observe that for images with structured feature spaces, e.g., MNIST and CelebA, the proposed method matches or outperforms other non-adversarial generative models. We evaluate the quality by calculating the Fréchet Inception Distance (FID) Heusel et al. (2017). All models share the same encoder-decoder architecture and trained for 100 epochs. Subscript *10k* indicates the kPF is estimated using 10000 latent points, where *Nyström* indicates approximation using 4000 landmark points from all latent points. Scores for GAN methods are reported from Dai & Wipf (2019). Comparative results are shown in Table 1. On the contrary, on images with less structured features such as CIFAR10, our model performs worse. We suspect that this is due to a non-smooth latent space, and we evaluate this by showing that visually similar images picked by our operators decodes to out-of-distribution (blurred-out) images (see Fig. 7). Here, we use a regularized AE Ghosh et al. (2020) with a latent space restricted to the hypersphere (denoted by SRAE).

Figure 6: Comparison of different sampling techniques using AE trained on CelebA 64x64. *Left to right: (1) Interpolation among 10 random latent points (2) samples of SRAE+Glow (3) samples of two-stage VAE (4) samples of kPF-flow using 10k latent points*

Further, we present qualitative results on CelebA (in Fig. 6), where we compare our kPF based model with other sampling techniques on the latent space. Observe that our model generates comparative visual results with $SRAE_{Glow}$. Hence, when a sufficient number of samples are available, our method performs as good as the alternatives, which is benefit, given the efficient. We present training time comparison and show that our proposed method is about $40\times$ faster as in Fig. 9.

Brain Imaging dataset: In this section, we present results on generating high-resolution ($160 \times 196 \times 160$) 3D brain images from ADNI consists of 183 samples from group AD (diagnosed as Alzheimer's Disease) and 291 samples from group CN (control normals). In this setting (where $n = 474 \ll d = 5017600$), it is often hard to model the data distribution using either variational methods or flow-based methods due to the high variance of the data or the memory-inefficiency of the operations. However, benefiting from the regularized and linear nature of our kernel operator Willoughby (1979); Arora et al. (2020), we can still generate high-quality samples in such resolu-

Figure 7: Generations (in red box) and real images corresponding to the top-5 out of 10 latent representations used in interpolation.

tion that are in-distribution. As before, we present the comparative results with respect to the VAE model. The generated samples presented in Fig. 8 clearly demonstrate that proposed method generates sharper images. To evaluate whether these results are also scientifically meaningful (and not merely visually pleasing), we tested consistency between statistical group difference testing on the real images (groups were AD and CN) and the same testing performed on the generated samples. We performed a FWER corrected two-sample t-test Ashburner & Friston (2000) in a manner consistent with standard practice Ashburner & Friston (2000); Winkler et al. (2014). The results (see Fig 8) show that while there is a deterioration in regions identified to be affected by disease (and different across groups), most of the statistically-significant regions from the test on the original images are preserved in tests performed on the generated images.

Figure 8: **Left.** *Top: data*, generated samples of *Middle: VAE samples, Bottom: kPF samples*. Standard Glow failed to fit into system memory for image of this resolution. **Right.** Statistically significant regions *Top: data, Bottom: samples* are shown in negative log p-value thresholded at $p < 0.01$.

Take-home message: We conclude that due to the kernel approach and one-step formulation of the proposed model, it offers better memory and sample efficiency than other non-adversarial generative methods. This is useful in many tasks, e.g., medical image analysis, where the number of samples is usually much less than the dimension of data. Moreover, in case of datasets with larger number of samples, the proposed method still performs well (and sometimes better) compared to alternatives, with a sizably smaller resource footprint.

5 DISCUSSION

We have shown that when a dataset allows a low-dimensional structured latent space representation, a kernel Perron-Frobenius operator can provide an efficient strategy to simplify flow-based generative models to transfer the density from a known simple distribution to the empirical data distribution. While the algorithmic simplifications proposed here can be variously useful, deriving the density of the posterior given a mean embedding or providing an exact preimage for the generated sample in RKHS remain unresolved at this time. While the problem of deriving the density has been addressed in Schuster et al. (2020), identifying a pre-image can be hard and often ill-posed. We also note that our geodesic interpolation only converges asymptotically to the weighted Fréchet mean which we use as the approximate preimage, and additional improvements on this front are possible.

Figure 9: Training time on MNIST.

REFERENCES

Guillaume Alain and Yoshua Bengio. What regularized auto-encoders learn from the data-generating distribution. *The Journal of Machine Learning Research*, 15(1):3563–3593, 2014.

Nachman Aronszajn. Theory of reproducing kernels. *Transactions of the American mathematical society*, 68(3):337–404, 1950.

Sanjeev Arora, Simon S Du, Wei Hu, Zhiyuan Li, Russ R Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8141–8150. Curran Associates, Inc., 2019. URL http://papers.nips.cc/paper/9025-on-exact-computation-with-an-infinitely-wide-neural-net.pdf.

Sanjeev Arora, Simon S. Du, Zhiyuan Li, Ruslan Salakhutdinov, Ruosong Wang, and Dingli Yu. Harnessing the power of infinitely wide deep nets on small-data tasks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rkl8sJBYvH.

John Ashburner and Karl J Friston. Voxel-based morphometrythe methods. *Neuroimage*, 11(6):805–821, 2000.

Omri Azencot, N. Benjamin Erichson, Vanessa Lin, and Michael W. Mahoney. Forecasting sequential data using consistent koopman autoencoders. 2020. URL https://proceedings.icml.cc/paper/2020/hash/8bd39eae38511daad6152e84545e504d.

Steven L. Brunton, Joshua L. Proctor, and J. Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 113(15):3932–3937, 2016. ISSN 0027-8424. doi: 10.1073/pnas.1517384113. URL https://www.pnas.org/content/113/15/3932.

Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost. *arXiv preprint arXiv:1604.06174*, 2016.

Bin Dai and David Wipf. Diagnosing and enhancing VAE models. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1e0X3C9tQ.

Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation. *arXiv preprint arXiv:1410.8516*, 2014.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=HkpbnH9lx.

Maurice Fréchet. Les éléments aléatoires de nature quelconque dans un espace distancié. In *Annales de l'institut Henri Poincaré*, volume 10, pp. 215–310, 1948.

Kenji Fukumizu, Le Song, and Arthur Gretton. Kernel bayes' rule: Bayesian inference with positive definite kernels. *The Journal of Machine Learning Research*, 14(1):3753–3783, 2013.

Partha Ghosh, Mehdi S. M. Sajjadi, Antonio Vergari, Michael Black, and Bernhard Scholkopf. From variational to deterministic autoencoders. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=S1g7tpEYDS.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 6626–6637. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/7240-gans-trained-by-a-two-time-scale-update-rule-converge-to-a-local-nash-equilibrium.pdf.

Jrn-Henrik Jacobsen, Arnold W.M. Smeulders, and Edouard Oyallon. i-revnet: Deep invertible networks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=HJsjkMb0Z.

Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 8571–8580. Curran Associates, Inc., 2018. URL http://papers.nips.cc/paper/8076-neural-tangent-kernel-convergence-and-generalization-in-neural-networks.pdf.

Hyeongju Kim, Hyeonseung Lee, Woo Hyun Kang, Sung Jun Cheon, Byoung Jin Choi, and Nam Soo Kim. Wavenode: A continuous normalizing flow for speech synthesis. ICML Workshop on Invertible Neural Networks, Normalizing Flows, and Explicit Likelihood Models, 2020. URL https://invertibleworkshop.github.io/accepted_papers/pdfs/11.pdf.

Sungwon Kim, Sang-Gil Lee, Jongyoon Song, Jaehyeon Kim, and Sungroh Yoon. FloWaveNet : A generative flow for raw audio. volume 97 of *Proceedings of Machine Learning Research*, pp. 3370–3378, Long Beach, California, USA, 09–15 Jun 2019. PMLR. URL http://proceedings.mlr.press/v97/kim19b.html.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10215–10224. Curran Associates, Inc., 2018. URL http://papers.nips.cc/paper/8224-glow-generative-flow-with-invertible-1x1-convolutions.pdf.

Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 4743–4751. Curran Associates, Inc., 2016. URL http://papers.nips.cc/paper/6581-improved-variational-inference-with-inverse-autoregressive-flow.pdf.

Stefan Klus, Ingmar Schuster, and Krikamol Muandet. Eigendecompositions of transfer operators in reproducing kernel hilbert spaces. *Journal of Nonlinear Science*, 30(1):283–315, 2020.

Bernard O Koopman. Hamiltonian systems and transformation in hilbert space. *Proceedings of the national academy of sciences of the united states of america*, 17(5):315, 1931.

Sang-gil Lee, Sungwon Kim, and Sungroh Yoon. Nanoflow: Scalable normalizing flows with sublinear parameter complexity. *arXiv preprint arXiv:2006.06280*, 2020.

Qianxiao Li, Felix Dietrich, Erik M. Bollt, and Ioannis G. Kevrekidis. Extended dynamic mode decomposition with dictionary learning: A data-driven adaptive spectral decomposition of the koopman operator. *Chaos: An Interdisciplinary Journal of Nonlinear Science*, 27(10):103–111, 2017. doi: 10.1063/1.4993854. URL https://doi.org/10.1063/1.4993854.

Yunzhu Li, Hao He, Jiajun Wu, Dina Katabi, and Antonio Torralba. Learning compositional koopman operators for model-based control. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=H1ldzA4tPr.

Bethany Lusch, J. Nathan Kutz, and Steven L. Brunton. Deep learning for universal linear embeddings of nonlinear dynamics. *Nature Communications*, 9(1), 2018. doi: 10.1038/s41467-018-07210-0. URL https://doi.org/10.1038/s41467-018-07210-0.

Shweta Mahajan, Iryna Gurevych, and Stefan Roth. Latent normalizing flows for many-to-many cross-domain mappings. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SJxE8erKDH.

Dieter H Mayer. The ruelle-araki transfer operator in classical statistical mechanics. 1980.

C. Miao, S. Liang, M. Chen, J. Ma, S. Wang, and J. Xiao. Flow-tts: A non-autoregressive network for text to speech based on flow. In *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 7209–7213, 2020.

Cameron Musco and Christopher Musco. Recursive sampling for the nystrom method. In *Advances in Neural Information Processing Systems*, pp. 3833–3845, 2017.

Radford M. Neal. Priors for infinite networks. In *Bayesian Learning for Neural Networks*. Springer, 1994. doi: 10.1007/978-1-4612-0745-0_2. URL https://doi.org/10.1007/978-1-4612-0745-0_2.

Evert J Nyström. Über die praktische auflösung von integralgleichungen mit anwendungen auf randwertaufgaben. *Acta Mathematica*, 54(1):185–204, 1930.

Hesamoddin Salehian, Rudrasis Chakraborty, Edward Ofori, David Vaillancourt, and Baba C Vemuri. An efficient recursive estimator of the fréchet mean on a hypersphere with applications to medical image analysis. *Mathematical Foundations of Computational Anatomy*, 3, 2015.

Ingmar Schuster, Mattes Mollenhauer, Stefan Klus, and Krikamol Muandet. Kernel conditional density operators. volume 108 of *Proceedings of Machine Learning Research*, pp. 993–1004, Online, 26–28 Aug 2020. PMLR. URL http://proceedings.mlr.press/v108/schuster20a.html.

Alex Smola, Arthur Gretton, Le Song, and Bernhard Schölkopf. A hilbert space embedding for distributions. In Marcus Hutter, Rocco A. Servedio, and Eiji Takimoto (eds.), *Algorithmic Learning Theory*, pp. 13–31, Berlin, Heidelberg, 2007. Springer Berlin Heidelberg. ISBN 978-3-540-75225-7.

Le Song, Jonathan Huang, Alex Smola, and Kenji Fukumizu. Hilbert space embeddings of conditional distributions with applications to dynamical systems. In *Proceedings of the 26th Annual International Conference on Machine Learning*, ICML '09, pp. 961968, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605585161. doi: 10.1145/1553374.1553497. URL https://doi.org/10.1145/1553374.1553497.

Matthew O. Williams, Ioannis G. Kevrekidis, and Clarence W. Rowley. A datadriven approximation of the koopman operator: Extending dynamic mode decomposition. *Journal of Nonlinear Science*, 25(6), 2015. doi: 10.1007/s00332-015-9258-5. URL https://doi.org/10.1007/s00332-015-9258-5.

Ralph A. Willoughby. Solutions of ill-posed problems (a. n. tikhonov and v. y. arsenin). *SIAM Review*, 21(2):266–267, 1979. doi: 10.1137/1021044. URL https://doi.org/10.1137/1021044.

Anderson M Winkler, Gerard R Ridgway, Matthew A Webster, Stephen M Smith, and Thomas E Nichols. Permutation inference for the general linear model. *Neuroimage*, 92:381–397, 2014.

A   APPENDIX

A.1   ABLATION STUDIES

We present ablation studies on MNIST (Fig. 10), showing importance and different components of our proposed method. Our proposed framework in general consists of **(a)** learning latent space **(b)** estimating transfer operator using kPF. We replace the first part in two ways **(i)** remove AE and directly transfer the distribution from image space to the known distribution **(ii)** replace AE with known invertible basis representation, e.g., mapping onto Fourier basis . In both these cases, we observe that the generation quality deteriorates. Notice that such degradation can be justified due to the lack of smoothness on the input space. Next, we fixed the AE and replace the kPF operator with a normalizing flow model Kingma & Dhariwal (2018) as transfer operator. Observe that the generation quality are comparable between the two methods.

Figure 10: *Top to bottom: no latent space with kPF, (2) interpolation in Fourier space, (3) Glow as transfer operator, (4) kPF as transfer operator*

We further show the advantage of using a regularized AE over a regular one. The regularization scheme we applied is derived from Ghosh et al. (2020), where we apply spectral normalization on all encoder-decoder transformations. Regularization has been shown to lead to smoother latent spaces Alain & Bengio (2014),

	MNIST	CIFAR	CelebA
$SAE_{NTK\text{-}kPF\ 10k}$	22.3	133.6	41.2
$SRAE_{NTK\text{-}kPF\ 10k}$	15.0	123.3	39.9

Table 2: vanilla vs. regularized AE.

and therefore is critical in our interpolation-based sampling approach. The effect of such regularization can be seen in Table 2, where it leads to higher FIDs in all three datasets using smoother latent space.

Take-home message: To summarize, the presented ablation study demonstrates the importance of the latent space as well as the richness of our one-step estimated operator. Moreover, the boundedness and smoothness of the latent space is crucial as can be justified by replacing AE with a Fourier basis or by using a regularized AE.

A.2   ADNI DATASET AND BRAIN IMAGE PROCESSING

Data used in preparation of this article were obtained from the Alzheimers Disease Neuroimaging Initiative (ADNI) database (adni.loni.usc.edu). As such, the investigators within the ADNI contributed to the design and implementation of ADNI and/or provided data but did not participate in analysis or writing of this report. A complete listing of ADNI investigators can be found at: .

The T1 MR brain data we use consists of images from 184 subjects diagnosed with Alzheimers's disease and 292 control normal subjects. Images were first coregisted to a MNI template and segmented to keep only the white matter and grey matter. Then, all images were resliced and resized to $160 \times 196 \times 160$ and rescaled to the range of $[-1, 1]$. Voxel-based morphometry (VBM) was used to obtain the p-value map of data and generated images.