Revisiting Out-of-Distribution Detection: A Simple Baseline is Surprisingly Effective

Abstract

It is an important problem in trustworthy machine learning to recognize out-of-distribution (OOD) inputs which are inputs unrelated to the in-distribution task. Many out-of-distribution detection methods have been suggested in recent years. The goal of this paper is to recognize common objectives as well as to identify the implicit scoring functions of different OOD detection methods. In particular, we show that binary discrimination between in- and (different) out-distributions is equivalent to several different formulations of the OOD detection problem. When trained in a shared fashion with a standard classifier, this binary discriminator reaches an OOD detection performance similar to that of Outlier Exposure. Moreover, we show that the confidence loss which is used by Outlier Exposure has an implicit scoring function which differs in a non-trivial fashion from the theoretically optimal scoring function in the case where training and test out-distribution are the same, but is similar to the one used when training with an extra background class. In practice, when trained in exactly the same way, all these methods perform similarly and reach state-of-the-art OOD detection performance.

1 Introduction

While deep learning has significantly improved performance in many application domains, there are serious concerns for using deep neural networks in applications which are of safety-critical nature. With one major problem being adversarial samples (Szegedy et al., 2014; Madry et al., 2018), which are small imperceptible modifications of the image that change the decision of the classifier, another major problem are overconfident predictions (Nguyen et al., 2015; Hendrycks & Gimpel, 2017; Hein et al., 2019) for images not belonging to the classes of the actual task. Here, one distinguishes between far out-of-distribution data, e.g. different forms of noise or completely unrelated tasks like CIFAR-10 vs. SVHN, and close out-of-distribution data which can for example occur in related image classification tasks where the semantic structure is very similar e.g. CIFAR-10 vs. CIFAR-100. Both are important to be distinguished from the in-distribution but it is conceivable that close out-of-distribution data is the more difficult problem with potentially fatal consequences: in an automated diagnosis system we want that the system recognizes that it "does not know" when a new unseen disease comes in rather than assigning high confidence into a known class leading to fatal treatment decisions. Thus out-of-distribution awareness is a key property of trustworthy AI systems.

One seemingly obvious approach is to use generative models for density estimation to differentiate between in- and out-distribution (Bishop, 1994; Nalisnick et al., 2019; Ren et al., 2019; Nalisnick et al., 2019; Xiao et al., 2020). Recent methods to a certain extent overcome the problem mentioned in Nalisnick et al. (2019) that generative models can assign higher likelihood to distributions on which they have not been trained. Another line of work are score-based methods using an underlying classifier or the internal features of such a classifier, potentially combined with a generative model (Hendrycks & Gimpel, 2017; Liang et al., 2018; Lee et al., 2018c; Hendrycks et al., 2019; Hein et al., 2019). One of the most effective methods up to now is Outlier Exposure (Hendrycks et al., 2019) and work building upon it (Chen et al., 2021; Meinke & Hein, 2020; Mohseni et al., 2020; Augustin et al., 2020; Papadopoulos et al., 2021; Thulasidasan et al., 2021) where a classifier is trained on the in-distribution task and one enforces low confidence as proposed by Lee et al. (2018a) during training on a large and diverse set of out-of-distribution images (Hendrycks et al., 2019) which can be seen as a proxy of all natural images. This approach generalizes well to other out-distributions. Recently, NTOM (Chen et al., 2021) has achieved excellent results for detecting far out-of-distribution

data by adding a background class to the classifier which is trained on samples from the surrogate out-distribution that are mined such that they show a desired hardness for the model. At test time, the output probability for that class is used to decide if an input is to be flagged as OOD. Their ATOM method does the same while also adding adversarial perturbations to the OOD inputs during training. Even though it has been claimed that new approaches outperform Hendrycks et al. (2019), up to our knowledge this has not been shown consistently across different and challenging test out-of-distribution datasets (including close and far out-of-distribution datasets).

The main contributions of this paper are:

- We show that several OOD detection approaches are equivalent to the binary discriminator between in- and out-distribution when analyzing the rankings induced by the Bayes optimal classifier/density.
- We derive the implicit scoring functions for the confidence loss (Lee et al., 2018a) employed by Outlier Exposure (Hendrycks et al., 2019) and for using an additional background class for the out-distribution (Thulasidasan et al., 2021). The confidence scoring function turns out not to be equivalent to the "optimal" scoring function when training and test distributions are the same.
- We show that when training the binary discriminator between in- and out-distribution together with a standard classifier on the in-distribution in a shared fashion, the binary discriminator reaches state-of-the-art OOD detection performance.

However, while we identify that a simple baseline is competitive with the state-of-the-art, the main aim of this paper is a better understanding of the key components of different OOD detection methods and to identify the key properties which lead to SOTA OOD detection performance. All of our findings are supported by extensive experiments on CIFAR-10 and CIFAR-100 with evaluation on various challenging out-of-distribution test datasets.

2 MODELS FOR OOD DATA AND EQUIVALENCE OF OOD DETECTION SCORES

As most work in the literature we consider OOD detection on a compact input domain X where the most important example is image classification where $X = [0,1]^D$. The most popular approach to OOD detection is the construction of an in-distribution-scoring function $f : X \to \mathbb{R} \cup \{\pm\infty\}$ such that $f(x)$ tends to be smaller if x is drawn from an out-distribution than if it is drawn from the in-distribution. There is a variety of different performance metrics for this task, with a very common one being the *area under the receiver-operator characteristic curve* (AUC). The AUC for a scoring function f distinguishing between an in-distribution $p(x|i)$ and an out-distribution $p(x|o)$ is given by

$$\text{AUC}_f\big(p(x|i), p(x|o)\big) = \mathop{\mathbb{E}}_{\substack{x \sim p(x|i) \\ y \sim p(y|o)}} \left[\mathbb{1}_{f(x)>f(y)} + \frac{1}{2}\mathbb{1}_{f(x)=f(y)} \right]. \tag{1}$$

We define an equivalence of scoring functions based on their AUCs and will show that this equivalence implies equality of other employed performance metrics as well.

Definition 1. *Two scoring functions f and g are equivalent and we write $f \cong g$ if*

$$\text{AUC}_f\big(p(x|i), p(x|o)\big) = \text{AUC}_g\big(p(x|i), p(x|o)\big) \tag{2}$$

for all potential distributions $p(x|i)$ and $p(x|o)$.

As the AUC is not dependent on the actual values of f but just on the ranking induced by f one obtains the following characterization of the equivalence of two scoring functions.

Theorem 1. *Two scoring functions f, g are equivalent $f \cong g$ if and only if there exists a strictly monotonously increasing function $\phi : \text{range}(g) \to \text{range}(f)$, such that $f = \phi(g)$.*

Corollary 1. *The equivalence between scoring functions in Def. 1 is an equivalence relation.*

Another metric is the *false positive rate at a fixed true positive rate q*, denoted as FPR@qTPR. A commonly used value for the TPR is 95%. The smaller the FPR@qTPR, the better the OOD discrimination performance.

Lemma 1. *Two equivalent scoring functions $f \cong g$ have the same FPR@qTPR for any pair of in- and out-distributions $p(x|i), p(x|o)$ and for any chosen TPR q.*

In the next section, we use the previous results to show that the Bayes optimal scoring functions of, several proposed methods for out-of-distribution detection are equivalent to the scoring functions of simple binary discriminators.

3 BAYES-OPTIMAL BEHAVIOUR OF BINARY DISCRIMINATORS AND COMMON OOD DETECTION METHODS

In the following we will show that the Bayes optimal function of several existing approaches to OOD detection for unlabeled data are equivalent to a binary discriminator between in- and a (training) out-distribution whereas differences arise when one has labeled data.

3.1 OOD DETECTION FOR METHODS USING UNLABELED DATA ONLY

We first provide a formal definition of OOD detection before we show the equivalence of density estimators resp. likelihood to a binary discriminator.

The OOD problem In order to make rigorous statements about the OOD detection problem we first have to provide the mathematical basis for doing so. We assume that we are given an in-distribution $p(x|i)$ and potentially also a *training* out-distribution $p(x|o)$. At this particular point no labeled data is involved, so both of them are just distributions over X. For simplicity we assume in the following that they both have a density wrt. the Lebesgue measure on $X = [0,1]^d$. We assume that in practice we get samples from the mixture distribution

$$p(x) = p(x|i)p(i) + p(x|o)p(o) = p(x|i)p(i) + p(x|o)(1 - p(i)) \tag{3}$$

where $p(i)$ is the probability that we expect to see in-distribution samples in total. In order to make the decision between in-and out-distribution for a given point x it is then optimal to consider

$$p(i|x) = \frac{p(x|i)p(i)}{p(x)} = \frac{p(x|i)p(i)}{p(x|i)p(i) + p(x|o)p(o)}, \tag{4}$$

which is defined for all $x \in [0,1]^d$ with $p(x) > 0$ (assuming $p(x|i)$ and $p(x|o)$ can be written as densities). If the training out-distribution is also the test out-distribution then this is already optimal but we would like that the approach generalizes to other unseen test out-distributions and thus an important choice is the training out-distribution $p(x|o)$. Note that as $p(i|x)$ is only well-defined for all x with $p(x) > 0$, it is thus reasonable to choose for $p(x|o)$ a distribution with support in $[0,1]^d$, that is $p(x|o) > 0$ for all $x \in [0,1]^d$. In this case we ensure that the criterion with which we perform OOD detection is defined for any possible input x. This is desirable as OOD detection should work for any possible input $x \in X$.

Optimal prediction of a binary discriminator between in- and out-distribution We consider a binary discriminator with model parameters θ between in- and (training) out-distribution, where $\hat{p}_\theta(i|x)$ is the predicted probability for the in-distribution. Under the assumption that $p(i)$ is the probability for in-distribution samples and using cross-entropy (which in this case is the logistic loss up to a constant global factor of $\log(2)$) the expected loss becomes:

$$\min_\theta p(i) \mathop{\mathbb{E}}_{x \sim p(x|i)} [-\log \hat{p}_\theta(i|x)] + p(o) \mathop{\mathbb{E}}_{x \sim p(x|o)} [-\log(1 - \hat{p}_\theta(i|x))] . \tag{5}$$

One can derive that the Bayes optimal classifier minimizing the expected loss has the predictive distribution:

$$\hat{p}_{\theta^*}(i|x) = \frac{p(x|i)p(i)}{p(x|i)p(i) + p(x|o)p(o)} = p(i|x). \tag{6}$$

Thus at least for the training out-distribution a binary classifier based on samples from in- and (training) out-distribution would suffice to solve the OOD detection problem perfectly.

Equivalence of density estimation and binary discrimination for OOD detection In this section we further analyze the relationship of common OOD detection approaches with the binary discriminator between in-and out-distribution. We start with density estimators sourced from generative models. A basic approach that is known to yield relatively weak OOD performance (Nalisnick et al., 2019; Ren et al., 2019; Xiao et al., 2020) is directly utilizing a model's estimate for the density $p(x|i)$ at a sample input x.

An improved density based approach which uses perturbed in-distribution samples as a surrogate training out-distribution is the Likelihood Ratios method (Ren et al., 2019), which proposes to fit a generative model for both the in- and out-distribution and to use the ratio between the likelihoods output by the two models as a discriminative feature.

We show that with respect to the scoring function, the correct density $p(x|i)$ is equivalent to the Bayes optimal prediction of a binary discriminator between the in-distribution and uniform noise. Furthermore, the density ratio $\frac{p(x|i)}{p(x|o)}$ is equivalent to the prediction of a binary discriminator between the two distributions on which the respective models used for density estimation have been trained. Because of this equivalence, we argue that the use of binary discriminators is a simple alternative to these methods because of its easier training procedure. While this equivalence is an asymptotic statement, the experimental comparisons in the appendix show that the methods perform similarly poorly compared to the methods using labeled data.

We first prove the more general case of arbitrary likelihood ratios. In the following we use the abbreviation $\lambda = \frac{p(o)}{p(i)}$ to save space and make the statements more concise.

Lemma 2. *Assume that $p(x|i)$ and $p(x|o)$ can be represented by densities and the support of $p(x|o)$ covers the whole input domain X. Then $\frac{p(x|i)}{p(x|o)} \cong \frac{p(x|i)}{p(x|i)+\lambda p(x|o)}$ for any $\lambda > 0$.*

This means that the likelihood ratio score of two optimal density estimators is equivalent to the in-distribution probability $\hat{p}_{\theta^*}(i|x)$ predicted by a binary discriminator and this is true for any possible ratio of $p(i)$ to $p(o)$. In the experiments below, we show that using such a discriminator has similar performance as the likelihood ratios of the different trained generative models.

For the approaches that try to directly use the likelihood of a generative model as a discriminative feature, this means that their objective is equivalent to training a binary discriminator against uniform noise, whose density is $p_{\text{Uniform}}(x) = p(x|o) = 1$ at any x.

Lemma 3. *Assume that $p(x|i)$ can be represented by a density. Then $p(x|i) \cong \frac{p(x|i)}{p(x|i)+\lambda}$ for any $\lambda > 0$.*

This provides additional evidence why a purely density based approach for many applications proves to be insufficient as an OOD detection score on the complex image domain: it is not reasonable to assume that a binary discriminator between certain classes of natural images on the one hand and uniform noise on the other hand provides much useful information about images from other classes or even about other nonsensical inputs.

3.2 OOD DETECTION FOR METHODS USING LABELED DATA

We first discuss how one can formulate the OOD problem when one has access to labeled data for the in-distribution and we identify the target distribution of OOD detection using a background/reject class. Then we derive the Bayes optimal classifier of the confidence loss (Lee et al., 2018a) as used by the most successful variant of Outlier Exposure (Hendrycks et al., 2019) and discuss the implicit scoring function. In most cases the scoring functions turn out not to be non-equivalent to $p(i|x)$ (which is optimal if training and test out-distribution agree) as they integrate additional information from the classification task.

Bayes optimal solutions for OOD Detection with Background class and confidence loss Outlier Exposure Given a joint in-distribution $p(y,x|i)$ (where $y \in \{1, \dots, K\}$ given that we have K labels) for the labeled in-distribution, there are different ways how to come up with a joint distribution for in- and out-distribution. Interestingly, the different encodings used e.g. in training with a background class (Thulasidasan et al., 2021) vs. training a classifier with confidence loss (Lee et al.,

2018a) together with variants of the employed scoring function lead to methods which unexpectedly can have quite different behavior.

Background class: In this case we just put all out-of-distribution samples into a $K+1$-class which is typically called background/reject class (Thulasidasan et al., 2021). The joint distribution then becomes

$$p(y, x) = \begin{cases} p(y, x|i)p(i) & \text{if } y \in \{1, \ldots, K\}, \\ p(x|o)p(o) & \text{if } y = K+1. \end{cases}$$

We denote by $p(x|i) = \sum_{y=1}^{K} p(y, x|i)$ the marginal in-distribution and note that the marginal distribution of the joint distribution of in- and out-distribution is again given by

$$p(x) = p(x|i)p(i) + p(x|o)p(o).$$

Then we get the conditional distribution

$$p(y|x) = \begin{cases} p(y|x, i)p(i|x) & \text{if } y \in \{1, \ldots, K\}, \\ p(o|x) = 1 - p(i|x) & \text{if } y = K+1. \end{cases}$$

The Bayes optimal solution of training with a background class using any calibrated loss function $L(y, f(x))$, e.g. the cross-entropy loss (Laptev et al., 2016), then yields a Bayes optimal classifier f^* which has a predictive distribution $p_{f^*}(y|x) = p(y|x)$. There are two potential scoring function that come to mind:

$$s_1(x) = 1 - p_{f^*}(K+1|x) \quad \text{and} \quad s_2(x) = \max_{k=1,\ldots,K} p_{f^*}(k|x)$$

The first one, used in Chen et al. (2021); Thulasidasan et al. (2021), is motivated by the fact that $p_{f^*}(K+1|x)$ is directly the predicted probability that the point is from the out-distribution as indeed it holds: $s_1(x) = p(i|x)$ which is the optimal scoring function if training and test out-distribution are equal. On the other hand the maximal predicted probability $\max_{k=1,\ldots,K} p_{f^*}(k|x)$, which is often employed as a scoring function Hendrycks & Gimpel (2017), becomes for the Bayes optimal classifier

$$s_2(x) = p(i|x) \max_{k=1,\ldots,K} p(k|x, i),$$

which is a product of $p(i|x)$ and the maximal conditional probability of some class of the in-distribution (note that s_2 is well defined as $p(i|x)$ is defined if $p(x|o)$ has support everywhere in X and if $p(i|x) > 0$ then also $p(x|i) > 0$). Thus the scoring function $s_2(x)$ integrates additionally to $p(i|x)$ also class-specific information and is thus less dependent on the chosen training out-distribution. In fact, one can see that s_2 only ranks points high if both the binary discriminator *and* the classifier rank the corresponding point high. On the other hand in the case where training and test out-distribution are identical, this scoring function is not equivalent to $p(i|x)$ and thus introduces a bias in the estimation.

Outlier Exposure Hendrycks et al. (2019) with confidence loss (Lee et al., 2018a): we analyze the Bayes optimal solution for the confidence loss (Lee et al., 2018a) that is used by Outlier Exposure (OE) and show that the associated scoring function can be written, similarly to the scoring function $s_2(x)$ for training with a background class, as a function of $p(i|x)$ and $p(y|x, i)$.

The training objective with the confidence loss is in expectation given by

$$\min_{\theta} \; \mathbb{E}_{(x,y) \sim p(x, y|i)} \left[\mathcal{L}_{\text{CE}}(f_\theta(x), y) \right] + \lambda \; \mathbb{E}_{x \sim p(x|o)} \left[\mathcal{L}_{\text{CE}}(f_\theta(x), u^K) \right] , \tag{7}$$

where θ are the model parameters and $f_\theta(x) \in \mathbb{R}^K$ is the model output as logits, and $u^K = (\frac{1}{K}, \ldots, \frac{1}{K})^T$ is the uniform distribution over the K classes of the in-distribution classification task.

In the following theorem we derive the Bayes optimal predictive distribution for this training objective.

Theorem 2. *The predictive distribution $p_{f^*}(y|x)$ of the Bayes optimal classifier f^* minimizing the expected confidence loss is given for $y \in \{1, \ldots, K\}$ as*

$$p_{f^*}(y|x) = p(i|x)p(y|x, i) + \frac{1}{K}\left(1 - p(i|x)\right) . \tag{8}$$

Thus the effective scoring function of using the probability of the predicted class as suggested in Hendrycks & Gimpel (2017); Lee et al. (2018a); Hendrycks et al. (2019) is given by

$$s_3(x) = p(i|x) \max_{y=1,\ldots,K} p(y|x,i) + \frac{1}{K}\big(1 - p(i|x)\big) = p(i|x)\Big[\max_{y=1,\ldots,K} p(y|x,i) - \frac{1}{K}\Big] + \frac{1}{K}.$$

Please note that the term inside the brackets is positive as $\max_{k=1,\ldots,K} p(k|x,i) \geq \frac{1}{K}$. Interestingly, the scoring functions s_2 and s_3 are not equivalent even though they look quite similar. In particular, due to the subtraction of $\frac{1}{K}$ the scoring function s_3 puts more emphasis on the classifier than s_2.

3.3 SEPARATE VERSUS SHARED ESTIMATION OF $p(i|x)$ AND $p(y|x,i)$

So far we have derived that at least from the point of view of the ranking induced by the Bayes optimal solution, OOD detection based on generative methods, likelihood ratios and the background class formulation with the scoring function s_1 is equivalent to a binary classification problem between in- and out-distribution in order to estimate $p(i|x)$. The differences arise mainly in the choice of the training out-distribution $p(x|o)$: i) uniform for generative resp. density based methods, ii) a quite specific out-distribution for likelihood ratios (Ren et al., 2019) and iii) a proxy of the distribution of all natural images (Hendrycks et al., 2019; Thulasidasan et al., 2021).

On the other hand when labeled data is involved we can additionally train a classifier on the in-distribution in order to estimate $p(y|x,i)$. We will then combine the estimates of $p(i|x)$ and $p(y|x,i)$ according to the three scoring functions derived in the previous section and check if the novel OOD detection methods constructed in this way perform similar to the OOD methods from which we derived the corresponding scoring function i) OOD detection with a background class (Thulasidasan et al., 2021) or ii) using Outlier Exposure Hendrycks et al. (2019). This will allow us to differentiate between differences of the employed scoring functions for OOD detection and the estimators for the involved quantities. In this way we foster a more systematic approach to OOD detection.

In the unlabeled case we train simply the binary classifier $p_\theta : [0,1]^d \to \mathbb{R}$ using logistic/cross entropy loss in a class balanced fashion

$$\min_\theta -\frac{1}{N}\sum_{i=1}^{N} \log\big(\hat{p}_\theta(i|x_i^{\text{IN}})\big) - \frac{\lambda}{M}\sum_{j=1}^{M} \log\big(1 - \hat{p}_\theta(i|x_j^{\text{OUT}})\big) , \quad (9)$$

where $(x_i^{\text{IN}})_{i=1}^{N}$ and $(x_j^{\text{OUT}})_{j=1}^{M}$ are samples from the in-distribution and the out-distribution.

In the case where we have labeled data we can additionally solve the classification problem. The obvious approach is to train the binary classifier for estimating $p(i|x)$ and the classifier to estimate $p(y|x,i)$ completely independently. Not surprisingly, we show in Section 4 that this approach works less well. In fact both tasks benefit from each other. Moreover, in training a neural network using a background class or with Outlier Exposure (Hendrycks et al., 2019) we are implicitly using a shared representation for both tasks which improves the results.

Thus we propose to train the binary discriminator of in-versus out-distribution together with the classifier on the in-distribution jointly. Concretely, we use a neural network with $K + 1$ outputs where the first K outputs represent the classifier and the last output is the logit of the binary discriminator. The resulting shared problem can then be written as

$$\min_\theta -\frac{1}{N_b}\sum_{r=1}^{N_b} \log\big(\hat{p}_\theta(i|x_r^{\text{IN}})\big) - \frac{\lambda}{M}\sum_{s=1}^{M} \log\big(1 - \hat{p}_\theta(i|x_s^{\text{OUT}})\big) - \frac{1}{N_c}\sum_{t=1}^{N_c} \log\big(\hat{p}_\theta(y_t^{\text{IN}}|x_t^{\text{IN}})\big) , \quad (10)$$

where $\lambda = \frac{p(o)}{p(i)}$ which is typically set to 1 during training in order to get a class-balanced problem. Note that the in-distribution samples $(x_r^{\text{IN}})_{r=1}^{N_b}$ used to estimate $p(i|x)$ can be a super-set of the labeled examples $(x_t^{\text{IN}}, y_t^{\text{IN}})_{t=1}^{N_c}$ used to train the classifier so that one can potentially integrate unlabeled data - this is an advantage compared to OOD detection with a background class or Outlier Exposure where this is not directly possible. We stress that the loss functions of the classifier and the discriminator act on independent outputs; the functions modelling the two tasks only interact with each other due to the shared network weights up to the final layer. Nevertheless, we see in the next Section 4 that training with a shared representation boosts both the classifier and the binary discriminator.

Table 1: Accuracy on the in-distribution (CIFAR-10/CIFAR-100) and FPR@95%TPR for various test out-distributions of different OOD methods with OpenImages as training out-distribution (results for the test set of OpenImages are not used in the mean FPR). Lower false positive rate is better. All methods except Mahalanobis have been trained using the same architecture, training parameters, schedule and augmentation. s_1, s_2, s_3 are the scoring functions introduced in Section 3.2. Our binary discriminator (BINDISC) resp. the combination with the shared classifier (SHARED COMBI) and the models with background class (BGC) with scoring functions s_2 or s_3 outperform the Mahalanobis detector (Lee et al., 2018b) and are similar to Outlier Exposure (Hendrycks et al., 2019). CelebA makes no sense as test out-distribution for CIFAR-100 as man/woman are classes in CIFAR-100.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-100 FPR	80M FPR	CELA FPR	OPENIM FPR
PLAIN CLASSI	95.16	53.01	47.87	50.00	17.51	65.81	60.43	53.44	76.00	63.71
MAHALANOBIS		36.68	20.97	49.00	0.00	0.00	57.21	48.85	80.71	55.13
OE	95.06	15.20	9.58	0.00	0.00	0.00	54.05	42.33	0.45	3.46
BGC s_1		18.83	2.36	0.00	0.00	0.00	72.00	56.41	1.04	0.05
BGC s_2	95.21	16.52	7.51	0.00	0.05	2.10	55.16	44.57	6.26	1.65
BGC s_3	95.21	16.63	7.69	0.00	0.07	2.36	55.19	44.67	6.41	1.74
SHARED BINDISC		19.56	4.65	0.00	0.00	0.00	77.50	53.93	0.87	0.04
SHARED CLASSI	95.28	29.34	28.00	7.00	2.33	33.04	58.61	47.90	28.54	35.94
SHARED COMBI s_2	95.28	16.00	8.56	0.00	0.00	0.00	58.80	42.79	1.83	0.61
SHARED COMBI s_3	95.28	16.06	9.00	0.00	0.00	0.00	58.68	42.85	1.91	0.66

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-10 FPR	80M FPR	OPENIM FPR
PLAIN CLASSI	77.16	67.57	75.50	78.33	22.60	70.98	80.55	77.43	80.80
MAHALANOBIS		53.88	54.36	66.00	46.43	0.06	85.39	71.01	74.69
OE	77.19	35.03	47.36	0.00	0.67	0.08	84.64	77.42	1.28
BGC s_1		31.14	11.58	0.00	0.00	0.00	93.94	81.29	0.07
BGC s_2	77.61	33.32	37.06	0.00	0.00	0.20	84.50	78.17	1.26
BGC s_3	77.61	33.36	37.27	0.00	0.00	0.20	84.51	78.19	1.27
SHARED BINDISC		31.86	10.77	0.00	0.00	0.00	95.25	85.11	0.08
SHARED CLASSI	77.35	67.23	71.05	5.00	97.70	69.68	82.05	77.89	28.38
SHARED COMBI s_2	77.35	33.01	37.30	0.00	0.00	1.06	82.71	77.01	1.80
SHARED COMBI s_3	77.35	33.06	37.57	0.00	0.00	1.13	82.68	77.01	1.85

4 EXPERIMENTS

We use CIFAR-10 and CIFAR-100 (Krizhevsky & Hinton, 2009) datasets as in-distribution and OpenImages dataset (Krasin et al., 2017) as training out-distribution. The 80 Million Tiny Images (80M) dataset (Torralba et al., 2008) is the de facto standard for training out-distribution aware models that has been adopted by most prior works, but this dataset has been withdrawn by the authors as Birhane & Prabhu (2021) pointed out the presence of offensive images. To be able to compare with other state-of-the-art methods without introducing a potential bias due to dataset selection, we include the evaluation with 80M as training out-distribution in Appendix F. Moreover, we show in the appendix results for the binary discriminator trained with different training out-distributions vs. likelihoods resp. likelihood ratios (Ren et al., 2019) as OOD method.

We use as OOD detection metric the false positive rate at 95% true positive rate, FPR@95%TPR; evaluations with AUC are in Appendix E. We evaluate the OOD detection performance on the following datasets: SVHN (Netzer et al., 2011), resized LSUN Classroom (Yu et al., 2015), Uniform Noise, Smooth Noise generated as described by (Hein et al., 2019), the respective other CIFAR dataset, 80M, and CelebA (Liu et al., 2015). We highlight that none of the listed methods has access

to those test distributions during training or for fine-tuning as we try to assess the ability of an out-distribution aware model to generalize to unseen distributions. The FPR for the OpenImages test set is not included in the Mean AUC, since this distribution *has* been used during training.

The binary discriminators (BINDISC) as well as the classifiers with background class (BGC) and the shared binary discriminator+classifier (SHARED) of $p(i|x)$ and $p(y|x, i)$ are trained on the 40-2 Wide Residual Network (Zagoruyko & Komodakis, 2016) architecture with the same training schedule as used in Hendrycks et al. (2019) for training their Outlier Exposure(OE) models. This includes averaging the loss over batches that are twice as large for the out-distribution. This way we ensure that the differences do not arise due to differences in the training schedules or other important details but only on the employed objectives. In addition to their standard augmentation and normalization, we apply AutoAugment (Cubuk et al., 2019) without Cutout, and we use $\lambda = 1$ where applicable. For the Mahalanobis OOD detector (Lee et al., 2018b), we use the models and code published by the authors and use OpenImages for the fine tuning of input noise and layer weighting regression. We describe the exact details of the training settings and the used dataset splits in Appendix C.

4.1 OUT-DISTRIBUTION AWARE TRAINING WITH LABELED IN-DISTRIBUTION DATA

In Table 1 we compare multiple OOD methods trained with training out-distribution OpenImages and CIFAR-10/100 as in-distribution: confidence of standard training (PLAIN) and OE, MAHALANOBIS detection, classifier with background class (BGC) and the combination of a plain classifier and a binary in-vs-out-distribution classifier with shared representation (SHARED COMBI). As described in Section 2, both BGC and SHARED COMBI can be used in combination with different scoring functions. For BGC, we evaluate all three scoring functions s_1, s_2 and s_3 and for SHARED COMBI we only use s_2 and s_3 as s_1 is equivalent to $p(i|x)$ which is the output of SHARED BINDISC. Additionally, we evaluate OOD detection based on the confidence of the shared classifier (SHARED CLASSI) trained together with SHARED BINDISC.

For CIFAR-10, a first interesting observation is that SHARED CLASSI has remarkably good OOD performance; significantly better than a normal classifier (plain) even though it is just trained using normal cross-entropy loss and so the OOD performance is only due to the regularization enforced by the shared representation with SHARED BINDISC. In fact SHARED BINDISC has already good OOD performance with a mean FPR@95%TPR of 19.56, which is improved by considering scoring function s_2/s_3 in the combination of SHARED BINDISC and SHARED CLASSI which yields very good classification accuracy and mean FPR/AUC. Moreover, interesting are the results of the classifier with background class (BGC) which is the method recently advocated in Thulasidasan et al. (2021). It works very well but the performance depends on the chosen scoring function. Whereas s_1 (output of the background class) is a usable scoring function (mean FPR: 18.83), the maximum probability over the other classes s_2 (mean FPR: 16.52) or the combination in terms of s_3 (mean FPR: 16.63) performs better. In total with the scoring function s_2/s_3 integrating classifier and discriminative information, BGC reaches similar performance to OE (which implicitly also uses s_3 as scoring function). In general, the differences of the methods are relatively minor both in terms of OOD detection and classification accuracy, where the latter is better for all OOD methods compared to the plain classifier; this is most likely explained by better learned representations, see also Hendrycks et al. (2019); Augustin et al. (2020) for similar observations. The results for CIFAR-100 are similar to CIFAR-10, with some reversals of the overall rankings of the compared methods. OE achieves comparable OOD results to BGC s_2/s_3 and SHARED COMBI s_2/s_3. For this in-distribution our BGC s_1 and SHARED BINDISC perform best in terms of OOD performance. Classification test accuracy is slightly higher for BGC and SHARED, but the differences are minor. The experiments with 80M as training out-distribution (Table 7 in Appendix F) confirm these observations.

Overall, as suggested by the theoretical results on the equivalence of the Bayes optimal classifier of OE with the s_3 scoring function of BGC and SHARED COMBI, we observe that even though these methods are derived and in particular trained with quite different objectives, they behave very similar in our experiments. In total we think that this provides a much better understanding where differences of OOD methods are coming from. Regarding the question of which method and scoring function should be used for a given application, the experimental results across datasets and different out-distributions, see Appendix F, suggest that their difference is minor and there is no clear best choice. However, in Appendix B, we describe a potential situation where the s_3 score and in consequence OE is not powerful enough to distinguish in- and out-of-distribution inputs. On the other

hand, in cases where the s_1 score is not very informative as training and test out-distributions largely differ, combining it with the classifier confidences is beneficial; this can be observed in experiments with SVHN as training out-distribution which we show in Appendix G. This is why for an unknown situation, we recommend BGC or SHARED COMBI with the s_2 scoring function as the safest option. However, it is an open question if there are also situations where s_2 is fundamentally inferior to s_3.

4.2 SHARED REPRESENTATION LEARNING FOR THE BINARY DISCRIMINATOR

As highlighted above the shared training of SHARED CLASSI and SHARED BINDISC and their combination SHARED COMBI with s_2/s_3 as scoring functions yields strong OOD detection and test accuracy among all methods. Here, we evaluate the importance of training the binary discriminator and the plain classifier with a shared representation in comparison to training two entirely separate models PLAIN CLASSI and SEPARATE BINDISC and their combination SEPARATE COMBI with scoring function s_3. The results for CIFAR-10 and CIFAR-100 can be found in Table 2. In total, we see that separate training in particular for CIFAR-100 leads to worse results compared to shared training as expected as the binary discriminator and the classifier cannot benefit from each other. An interesting curiosity is that the combination of the separate classifier with the binary discriminator trained in a shared fashion (PLAIN ⊗ SHA DISC) yields almost the same OOD results as SHARED COMBI even though the classifier is significantly worse. Overall, SHARED COMBI performs significantly better when also considering the better classification accuracy which it inherits from SHARED CLASSI.

Table 2: Evaluation (same metrics as in Table 1) of models trained with shared and separate representations. Shared training benefits both the classifier and the binary discriminators.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-100 FPR	80M FPR	CELA FPR	OPENIM FPR
SEPARATE BINDISC		23.49	6.21	0.00	0.00	0.00	83.79	65.77	8.68	0.00
PLAIN CLASSI	95.16	53.01	47.87	50.00	17.51	65.81	60.43	53.44	76.00	63.71
SEPARATE COMBI s_3	95.16	21.40	13.15	0.00	0.00	0.00	59.96	49.78	26.93	0.45
SHARED BINDISC		19.56	4.65	0.00	0.00	0.00	77.50	53.93	0.87	0.04
SHARED CLASSI	95.28	29.34	28.00	7.00	2.33	33.04	58.61	47.90	28.54	35.94
SHARED COMBI s_3	95.28	16.06	9.00	0.00	0.00	0.00	58.68	42.85	1.91	0.66
PLAIN ⊗ SHA DISC s_3	95.16	15.96	8.10	0.00	0.00	0.00	58.48	42.60	2.53	0.70

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-100 FPR	80M FPR	OPENIM FPR
SEPARATE BINDISC		32.50	14.28	0.00	0.00	0.00	96.50	84.22	0.02
PLAIN CLASSI	77.16	67.57	75.50	78.33	22.60	70.98	80.55	77.43	80.80
SEPARATE COMBI s_3	77.16	41.94	69.44	0.00	0.00	24.39	81.15	76.67	0.89
SHARED BINDISC		31.86	10.77	0.00	0.00	0.00	95.25	85.11	0.08
SHARED CLASSI	77.35	67.23	71.05	5.00	97.70	69.68	82.05	77.89	28.38
SHARED COMBI s_3	77.35	33.06	37.57	0.00	0.00	1.13	82.68	77.01	1.85
PLAIN ⊗ SHA DISC s_3	77.16	33.38	37.00	0.00	0.00	5.42	81.33	76.50	2.23

5 CONCLUSION

In this paper we have analyzed different OOD detection methods and have shown that the simple baseline of a binary discriminator between in-and out-distribution is a powerful OOD detection method if trained in a shared fashion with a classifier. Moreover, we have revealed the inner mechanism of Outlier Exposure and training with a background class which unexpectedly use a scoring function which integrates information from $p(i|x)$ *and* $p(y|x,i)$. We think that these findings will allow to build novel OOD methods in a more principled fashion.

6 ETHICS AND REPRODUCIBILITY STATEMENT

In this paper we provide an explanation for the inner workings of established OOD detection methods and propose a novel OOD detection method based on these considerations which outperforms OE in terms of OOD performance and test accuracy. A limitation is that our derived equivalences are based on the Bayes optimal solution and thus are asymptotic statements. Convergence to the Bayes optimal solution can be infinitely slow and the methods can have implicit inductive biases.
The final goal is to have more trustworthy classifiers. One could criticize that the focus on OOD FPR/AUC performance and test accuracy covers just certain aspects and other aspects like calibration of the classifiers, fairness, robustness to corruptions or adversarial attacks play an important role, too. However, apart from the usual dual use problem we see only positive societal aspects of our paper, as it leads to more trustworthy ML methods.

We discuss the problematic situation with the retracted 80 Million Tiny Images (Torralba et al., 2008) dataset – which is used by many previous works in the field – in Appendix F and replace the it with Openimages (Krasin et al., 2017) for training the models in the main paper. For comparability with previous methods, we include evaluations of models trained on 80M in the appendix. We hope that introducing an alternative dataset for natural surrogate OOD training helps the community towards avoiding the retracted dataset in the future, both from an ethical and also a practical perspective, in case 80M becomes fully unavailable.

All experimental details including used hardware are given in Appendix C, and code for training and evaluating out methods as well as weights of the evaluated neural networks are available at `https://anonymous.4open.science/r/OOD_BGC_BinDisc-D7FB`.

REFERENCES

Maximilian Augustin, Alexander Meinke, and Matthias Hein. Adversarial robustness on in-and out-distribution improves explainability. In *ECCV*, 2020.

Abeba Birhane and Vinay Uday Prabhu. Large image datasets: A pyrrhic win for computer vision? In *WACV*, pp. 1537–1547, 2021.

Christopher M Bishop. Novelty detection and neural network validation. *IEEE Proceedings-Vision, Image and Signal processing*, 141:217–222, 1994.

Stephen Boyd, Stephen P Boyd, and Lieven Vandenberghe. *Convex optimization*. Cambridge University Press, 2004.

Jiefeng Chen, Yixuan Li, Xi Wu, Yingyu Liang, and Somesh Jha. Informative outlier matters: Robustifying out-of-distribution detection using outlier mining. In *ECML*, 2021.

Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation strategies from data. In *CVPR*, 2019.

M. Hein, M. Andriushchenko, and J. Bitterwolf. Why ReLU networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *CVPR*, 2019.

D. Hendrycks and K. Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *ICLR*, 2017.

D. Hendrycks, M. Mazeika, and T. Dietterich. Deep anomaly detection with outlier exposure. In *ICLR*, 2019. `https://github.com/hendrycks/outlier-exposure`.

Ivan Krasin, Tom Duerig, Neil Alldrin, Vittorio Ferrari, Sami Abu-El-Haija, Alina Kuznetsova, Hassan Rom, Jasper Uijlings, Stefan Popov, Shahab Kamali, Matteo Malloci, Jordi Pont-Tuset, Andreas Veit, Serge Belongie, Victor Gomes, Abhinav Gupta, Chen Sun, Gal Chechik, David Cai, Zheyun Feng, Dhyanesh Narayanan, and Kevin Murphy. Openimages: A public dataset for large-scale multi-label and multi-class image classification. *Dataset available from https://storage.googleapis.com/openimages/web/index.html*, 2017.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

D. Laptev, N. Savinov, J.M. Buhmann, and M. Pollefeys. TI-pooling: Transformation-invariant pooling for feature learning in convolutional neural networks. In *CVPR*, 2016.

K. Lee, H. Lee, K. Lee, and J. Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. In *ICLR*, 2018a.

K. Lee, H. Lee, K. Lee, and J. Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *NeurIPS*, 2018b. `https://github.com/pokaxpoka/deep_Mahalanobis_detector`.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *NeurIPS*, 2018c.

Shiyu Liang, Yixuan Li, and R Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *ICLR*, 2018.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *ICCV*, 2015.

A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Valdu. Towards deep learning models resistant to adversarial attacks. In *ICLR*, 2018.

Alexander Meinke and Matthias Hein. Towards neural networks that provably know when they don't know. In *ICLR*, 2020.

Sina Mohseni, Mandar Pitale, Jbs Yadawa, and Zhangyang Wang. Self-supervised learning for generalizable out-of-distribution detection. In *AAAI*, 2020.

E. Nalisnick, A. Matsukawa, Y. Whye Teh, D. Gorur, and B. Lakshminarayanan. Do deep generative models know what they don't know? In *ICLR*, 2019.

Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Hybrid models with deep and invertible features. In *ICML*, 2019.

Y. Netzer, T. Wang, A. Coates, A. Bissacco, B. Wu, and A. Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NeurIPS Workshop on Deep Learning and Unsupervised Feature Learning*, 2011.

A. Nguyen, J. Yosinski, and J. Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *CVPR*, 2015.

Aristotelis-Angelos Papadopoulos, Mohammad Reza Rajati, Nazim Shaikh, and Jiamian Wang. Outlier exposure with confidence control for out-of-distribution detection. *Neurocomputing*, 441:138–150, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, pp. 8024–8035, 2019.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *JMLR*, 12:2825–2830, 2011.

Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark A DePristo, Joshua V Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *NeurIPS*, 2019.

Tim Salimans, Andrej Karpathy, Xi Chen, and Diederik P. Kingma. Pixelcnn++: A pixelcnn implementation with discretized logistic mixture likelihood and other modifications. In *ICLR*, 2017.

C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

Sunil Thulasidasan, Sushil Thapa, Sayera Dhaubhadel, Gopinath Chennupati, Tanmoy Bhattacharya, and Jeff Bilmes. An effective baseline for robustness to distributional shift. *arXiv: 2105.07107*, 2021.

Antonio Torralba, Rob Fergus, and William T Freeman. 80 million tiny images: A large data set for nonparametric object and scene recognition. *IEEE PAMI*, 30(11):1958–1970, 2008.

Zhisheng Xiao, Qing Yan, and Yali Amit. Likelihood regret: An out-of-distribution detection score for variational auto-encoder. In *NeurIPS*, 2020.

Fisher Yu, Yinda Zhang, Shuran Song, Ari Seff, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *CoRR*, abs/1506.03365, 2015.

S. Zagoruyko and N. Komodakis. Wide residual networks. In *BMVC*, pp. 87.1–87.12, 2016.

A PROOFS

Theorem 1. *Two scoring functions f, g are equivalent $f \cong g$ if and only if there exists a strictly monotonously increasing function $\phi : \mathrm{range}(g) \to \mathrm{range}(f)$, such that $f = \phi(g)$.*

Proof. Assume that such a function ϕ exists. Then for any pair x, y we have the logical equivalences $g(x) > g(y) \Leftrightarrow f(x) = \phi(g(x)) > \phi(g(y)) = f(y)$ and $g(x) = g(y) \Leftrightarrow f(x) = \phi(g(x)) = \phi(g(y)) = f(y)$. This directly implies that the AUCs are the same, regardless of the distributions.

Assume $f \cong g$. For each $a \in \mathrm{range}(g)$, choose some $\hat{a} \in g^{-1}(a)$. For any pair $x, y \in X$, by regarding the Dirac distributions $p(x|i) = \delta_x$ and $p(x|o) = \delta_y$ that are each concentrated on one of the points, we can infer that $f(x) > f(y) \Leftrightarrow \mathrm{AUC}_f(p(x|i), p(x|o)) = 1 \Leftrightarrow \mathrm{AUC}_g(p(x|i), p(x|o)) = 1 \Leftrightarrow g(x) > g(y)$ and similarly $f(x) = f(y) \Leftrightarrow g(x) = g(y)$. The latter ensures that the function defined as

$$\phi : \mathrm{range}(g) \to \mathrm{range}(f)$$
$$a \mapsto f(\hat{a}) \tag{11}$$

is independent of the choice of $\hat{a}$ and that $f = \phi \circ g$, and the former confirms that ϕ is strictly monotonously increasing. $\qquad\square$

Lemma 1. *Two equivalent scoring functions $f \cong g$ have the same FPR@qTPR for any pair of in- and out-distributions $p(x|i), p(x|o)$ and for any chosen TPR q.*

Proof. We know that a function ϕ as in Theorem 1 exists. Then for any pair x, y, we have the logical equivalences

$$g(x) > g(y) \Leftrightarrow f(x) = \phi(g(x)) > \phi(g(y)) = f(y) \tag{12}$$

and

$$g(x) = g(y) \Leftrightarrow f(x) = \phi(g(x)) = \phi(g(y)) = f(y) . \tag{13}$$

This directly implies that the FPR@qTPR-values are the same, for any $p(x|i), p(x|o)$ and q. $\qquad\square$

Lemma 2. *Assume that $p(x|i)$ and $p(x|o)$ can be represented by densities and the support of $p(x|o)$ covers the whole input domain X. Then $\frac{p(x|i)}{p(x|o)} \cong \frac{p(x|i)}{p(x|i) + \lambda p(x|o)}$ for any $\lambda > 0$.*

Proof. The function $\phi : [0, \infty] \to [0, 1]$ defined by $\phi(x) = \frac{x}{x+\lambda}$ (setting $\phi(\infty) = 1$) fulfills the criterion from Theorem 1 of being strictly monotonously increasing. With

$$\phi\left(\frac{p(x|i)}{p(x|o)}\right) = \frac{\frac{p(x|i)}{p(x|o)}}{\frac{p(x|i)}{p(x|o)} + \lambda\frac{p(x|o)}{p(x|o)}} = \frac{p(x|i)}{p(x|i) + \lambda p(x|o)} \tag{14}$$

for $p(x|o) \neq 0$ and $\phi\left(\frac{p(x|i)}{0}\right) = \phi(\infty) = 1 = \frac{p(x|i)}{p(x|i) + \lambda \cdot 0}$, the equivalence follows. $\qquad\square$

Lemma 3. *Assume that $p(x|i)$ can be represented by a density. Then $p(x|i) \cong \frac{p(x|i)}{p(x|i) + \lambda}$ for any $\lambda > 0$.*

Proof. This is a special case of Lemma 2, by setting $p(x|o) = 1 = p_{\mathrm{Uniform}}(x)$. $\qquad\square$

Theorem 2. *The predictive distribution $p_{f^*}(y|x)$ of the Bayes optimal classifier f^* minimizing the expected confidence loss is given for $y \in \{1, \dots, K\}$ as*

$$p_{f^*}(y|x) = p(i|x)p(y|x, i) + \frac{1}{K}\left(1 - p(i|x)\right) . \tag{8}$$

Proof. Minimizing the loss of Outlier Exposure given in Eq. (7) means solving the optimization problem

$$\min_{p_f(\cdot|x)} \; -p(i|x) \cdot \sum_{k=1}^{K} p(k|x,i) \cdot \log p_f(k|x) - (1 - p(i|x)) \cdot \sum_{k=1}^{K} \frac{1}{K} \cdot \log p_f(k|x)$$

$$\text{subject to} \quad p_f(k|x) \geq 0 \text{ for each } k \in \{1, \ldots, K\} \tag{15}$$

$$\sum_{k=1}^{K} p_f(k|x) = 1 \;,$$

where $p_f(\cdot|x)$ is the model's K-dimensional prediction. For $p(i|x) = 0$ or $p(k|x,i) = 0$, the optimalities of the respective terms are easy to show (applying the common conventions for $0 \log 0$), so we assume that tose are non-zero. The Lagrange function of the optimization problem is

$$L(p_f(\cdot|x), \alpha, \beta) = -p(i|x) \cdot \sum_{k=1}^{K} p(k|x,i) \cdot \log p_f(k|x) - (1 - p(i|x)) \cdot \sum_{k=1}^{K} \frac{1}{K} \cdot \log p_f(k|x)$$

$$- \sum_{k=1}^{K} \alpha_k p_f(k|x) + \beta \left(-1 + \sum_{k=1}^{K} p_f(k|x) \right) \;, \tag{16}$$

with $\beta \in \mathbb{R}$ and $\alpha \in \mathbb{R}_+^K$. Its first derivative with respect to $p_f(k|x)$ for any k is

$$\frac{\partial L}{p_f(k|x)} = -p(i|x) \cdot p(k|x,i) \frac{1}{p_f(k|x)} - (1 - p(i|x)) \cdot \frac{1}{K} \frac{1}{p_f(k|x)} - \alpha_k + \beta$$

$$= -\frac{s^K(k|x)}{p_f(k|x)} - \alpha_k + \beta \;, \tag{17}$$

where we set $s^K(k|x) := p(i|x)p(k|x,i) + \frac{1}{K}\left(1 - p(i|x)\right)$. The second derivative is a positive diagonal matrix for any point of its domain, therefore we find the unique minimum by setting (17) to zero, i.e. at

$$p_f(k|x) = \frac{s^K(k|x)}{\beta - \alpha_k} \;. \tag{18}$$

The dual problem is hence the maximization (with $\alpha_k \geq 0$) of

$$q(\alpha, \beta) = -p(i|x) \cdot \sum_{k=1}^{K} p(k|x,i) \cdot \log \frac{s^K(k|x)}{\beta - \alpha_k} - (1 - p(i|x)) \cdot \sum_{k=1}^{K} \frac{1}{K} \cdot \log \frac{s^K(k|x)}{\beta - \alpha_k}$$

$$- \sum_{k=1}^{K} \alpha_k \frac{s^K(k|x)}{\beta - \alpha_k} + \beta \left(-1 + \sum_{k=1}^{K} \frac{s^K(k|x)}{\beta - \alpha_k} \right)$$

$$= \sum_{k=1}^{K} s^K(k|x) \left(-\log s^K(k|x) + \log(\beta - \alpha_k) + \frac{\beta}{\beta - \alpha_k} - \frac{\alpha_k}{\beta - \alpha_k} \right) - \beta \;;$$

here, α only appears in $\log(\beta - \alpha_k)$ which has a positive factor $s^K(k|x)$, so $\alpha = 0$ maximizes the expression. Noting $\sum_{k=1}^{K} s^K(k|x) = 1$, what remains is $q^0(\beta) = 1 + \log(\beta) - \sum_{k=1}^{K} s^K(k|x) \log s^K(k|x) - \beta$, which is maximized by $\beta = 1$. This means that the dual optimal pair is $p_f(k|x) = s^K(k|x), (\beta = 1, \alpha = 0)$. Slater's condition (Boyd et al., 2004) holds since the feasible set of the original problem is the probability simplex. Thus, $p_{f*}(\cdot|x) = s^K(x)$ is indeed primal optimal. □

B   CONFIDENCE LOSS MODELS AND MODELS WITH A BACKGROUND CLASS OR A BINARY DISCRIMINATOR ARE ONLY EQUIVALENT AFTER s_3 IS APPLIED

Seeing that for both in-distribution accuracy and OOD detection, OE models trained with confidence loss, models with background class and shared classifier/discriminator combinations behave very

similarly, the question arises if the training methods themselves lead to equivalent models. One idea might be that and effect of the confidence loss on the degree of freedom from logit translation invariance could be unfolded to obtain a $K + 1$-dimensional output that contains the same information as a classifier with background class or with and additional binary discriminator output (the latter two are indeed equivalent). This is not the case, as the following example that in certain situations, the s_1 and s_2 scores of background class models and classifier/discriminator combinations are able to separate in- and out-distribution, while the s_3 score and the equivalent confidence loss/OE models cannot.

B.1 EURO COIN CLASSIFIER

As an example where the mentioned non-equivalence would occur, we hypothetically regard the task of classifying photos of 1-Euro coins by the issuing country. Each €1 coin features a common side that is the same for each country and a national side that pictures a unique motive per country. We assume that one side is visible on each photo, and that the training dataset of size $2mK$ is balanced, consisting of $2m$ coin photos with label c for each country $c \in \{1, \dots, K\}$, where m photos show the common side and the other m photos show the informative national side for each country c.

It is easy to see that the Bayes optimal classifier trained with cross-entropy loss on this dataset predicts 100% for the respective country c when shown a photo of the national side of a €1 coin, and predicts $1/K$ for each country when shown the common side of a €1 coin.

Now we compare the behaviour of the different methods given a training out-distribution of poker chips images which are clearly recognizable as not being €1 coins.

A K-class model trained with confidence loss (Lee et al., 2018a) will not make a difference between common side coin images and poker chip images, and in the Bayes optimal case, it will predict the uniform class distribution in both cases. This does not only hold for the prediction of a hypothetical Bayes optimal model: assuming full batch gradient descent and identical sets of m common side training photos for each class, the loss for a common side input is the same as the loss for a poker chip.

On the other hand, a binary discriminator will easily distinguish between poker chips and €1 coins, no matter which side of the coin is shown. The same holds for a model with background class: the score of the class $K + 1$ will be close to 1 for chips and close to 0 for €1 coins.

We conclude that in the described situation, models trained with confidence loss/outlier exposure are not able to sufficiently distinguish in- and out-distribution, while the s_1 scoring function of a classifier with background class or a binary discriminator is suitable for this task.

With the s_2 scoring function, the background class model gives us $s_2(x) = \max_{k=1,\dots,K} p_f(k|x)$, and thus $\frac{(1 - p_f(K+1|x))}{K} \le s_2(x) \le 1 - p_f(K+1|x)$, which means that if $p_f(K+1|x)$ is sufficiently large for in-distribution inputs and sufficiently small for out-of-distribution inputs, s_2 is able to distinguish them independent of inconclusiveness in the first K classes. Similarly, s_2 applied to a binary discriminator with a classifier (shared trained or not) will be able to distinguish common sides of coins and poker chips.

With s_3, on the other hand, common sides of coins and poker chips can no longer be separated. For a classifier/discriminator pair, as defined above, $s_3(x) = p_d(i|x) \left[\max_{y=1,\dots,K} p_c(y|x, i) - \frac{1}{K} \right] + \frac{1}{K}$. If on the common side of a coin the classifier predicts uniform $\frac{1}{K}$, we have $s_3(x) = \frac{1}{K}$ no matter what the discriminator $p_d(i|x)$ predicts. On poker chips with discriminator prediction $p_d(i|x) = 1$, we also get $s_3(x) = 1$. For background class models, $s_3(x) = \max_{k=1,\dots,K} p_f(k|x) + \frac{1}{K} p_f(K+1|x)$ also yields $\frac{1}{K}$ for a common side where the prediction over the K in-distribution classes is uniform and for a poker chips, where $p_f(K + 1|x) = 1$. The fact that in this coin scenario when scored with s_3, background class and classifier/discriminator combinations have the same problem as confidence loss/OE is not surprising considering their equivalence shown in Theorem 2.

C EXPERIMENTAL DETAILS

C.1 TRAINING

For training our models, we build upon the code of Hendrycks et al. (2019) which they have available at `https://github.com/hendrycks/outlier-exposure` and borrow their general architecture and training settings. Concretely, we use 40-2 Wide Residual Network (Zagoruyko & Komodakis, 2016) models with normalization based on the CIFAR datasets and a dropout rate of 0.3. They are trained for 100 epochs with an initial learning rate of 0.1 that decreases following a cosine annealing schedule. Unless mentioned otherwise, each training step uses a batch of size 128 for the in-distribution and a batch of size 256 for the training out-distribution. The optimizer uses stochastic gradient descent with a Nesterov momentum of 0.9. Weight decay is set to $5 \cdot 10^{-4}$. The deep learning framework we use is PyTorch (Paszke et al., 2019), and for evaluating we use the scikit-learn (Pedregosa et al., 2011) implementation of the AUC. Our code is available at `https://anonymous.4open.science/r/OOD_BGC_BinDisc-D7FB`.

For evaluating the Mahalanobis detector, we use the code by the authors of Lee et al. (2018b) provided at `https://github.com/pokaxpoka/deep_Mahalanobis_detector`. The input noise levels and regression parameters are chosen on the available out-distribution OpenImages and are 0.0014 for CIFAR-10 and 0.002 for CIFAR-100.

All experiments were run on Nvidia V100 GPUs of an internal cluster of our institution, using up to 4 GB GPU memory (batch sizes in:128/out:256), with no noticeable difference between ours and the compared OE Hendrycks et al. (2019) runs.

C.2 DATASETS

We train our models with the train splits of CIFAR-10 and CIFAR-100 Krizhevsky & Hinton (2009) (MIT license) which each consist of 50,000 labeled images, and evaluate on their test splits of 10,000 samples. As training out-distribution we use OpenImages v4 (Krasin et al., 2017) (images have a CC BY 2.0 license); the training split that we employ here consists of 8,945,291 images of different sizes, which get resized to 32×32 pixels, and we test on 10,000 from the official validation split. For training with 80 Million Tiny Images (80M) (Torralba et al., 2008) in Appendix F (no license, see links in Appendix F), we use data from the beginning of the sequentialized dataset, and evaluate on a test set of 30,080 images starting at index 50,000,000. A subset of CIFAR images contained in 80M is excluded for training and evaluation. Further image datasets used for evaluation are SVHN (Netzer et al., 2011) (free for non-commercial use) with 26,032 samples, LSUN (Yu et al., 2015) Classroom (no license) with 300 samples, and CelebA (Liu et al., 2015) (available for non-commercial research purposes only) with 19,962 test samples. Uniform and Smooth Noise (Hein et al., 2019) are sampled, the latter by generating uniform noise and smoothing it using a Gaussian filter with a width that is drawn uniformly at random in $[1, 2.5]$. Each datapoint is then shifted and scaled linearly such that the minimal and maximal pixel values are 0 and 1, respectively. For both noises, we evaluate 30,080 inputs.

D EXPERIMENTS COMPARING DENSITY ESTIMATION AND BINARY DISCRIMINATORS

D.1 UNLABELED IN-DISTRIBUTION DATA AVAILABLE FOR TRAINING

We want to answer the following questions: How does estimating the in-distribution density compare to simply employing a binary discriminator between the in-distribution and uniform noise with respect to the task of out-of-distribution detection? Can other density based models be substituted for potentially easier to handle binary discriminators against a suitable (semi-)synthetic out-distribution? As generative models, we use a standard likelihood VAE, a likelihood PixelCNN++ and additionally compare with a Likelihood Regret VAE (Xiao et al., 2020). The binary classifier is trained to separate real data from uniform noise, thus none of the methods presented in this section make use of 80M or any other surrogate distribution. The results for OOD detection in terms of AUC for all methods are presented in Table 3.

Comparing the OOD detection performance of the binary discriminator trained against uniform noise with both VAE models, we asses that neither model is suitable for reliably detecting inputs from unknown out-distributions.

Following the theoretical analysis from the previous sections, the likelihood models and our binary classifier are able to perfectly separate the in-distribution data from uniform noise. This is expected as those methods are trained on that particular task of separating CIFAR-10 from uniform noise, whereas the LH Regret VAE with modified train objective has worse performance on uniform noise. It appears as if the training objective of the binary classifier seems to be too easy as the training and validation loss converge to almost zero in the first few epochs of training. However, the ability to separate uniform noise from real images does not generalize to other test distributions as both methods fail to achieve good out-of-distribution detection performance on the other test distributions. We note that while the score features from the likelihood models and the binary classifier are in expectation equivalent, both methods behave quite different on the test datasets (except for uniform noise). This is not surprising, as the probability of drawing real images from the uniform distribution is so small that neither training method properly regularizes the model's behaviour on those particular image manifolds. Thus the results are artifacts of random fluctuation and no method clearly outperforms the other one, for example the binary classifier is better at separating CIFAR-10 from SVHN whereas the likelihood VAE significantly outperforms the binary classifier on LSUN. Similar fluctuations also exist between the two variational auto encoders and PixelCNN++, but in conclusion none of those methods is able to generalize to more specialized unseen distributions.

Table 3: AUC for CIFAR-10 vs. various out-distributions of different methods that have access to only unlabelled CIFAR-10 data during training. Shown are the scores obtained from the likelihoods of the PixelCNN++ from Ren et al. (2019),

MODEL	MEAN AUC	SVHN AUC	LSUN AUC	CELEBA AUC	SMOOTH AUC	C-100 AUC	OPEN AUC	80M AUC	UNI AUC
LH PIXELCNN++	57.05	07.14	89.02	57.77	77.93	52.96	70.52	43.99	100.00
LH VAE	57.97	20.98	83.03	48.05	91.67	51.32	55.62	55.09	100.0
LH REGRET VAE	52.24	87.36	35.73	70.69	14.84	53.03	50.81	53.21	94.11
BINDISC UNIFORM	45.90	71.22	34.67	35.07	47.13	47.32	44.70	41.17	100.00

D.2 LIKELIHOOD RATIOS AS A BINARY DISCRIMINATOR

In Section 3.1, we discussed that for the Bayes optimal solutions of their training objectives, the ratio of the likelihoods of two density estimators for different distributions is as an OOD detection scoring function equivalent to the prediction of a binary discriminator between the two distributions. In order to find out which role this equivalence plays in practise, we train a binary discriminator between CIFAR-10 as in-distribution and the background distribution obtained by mutating 10% of the pixles of in-distribution images as described in Ren et al. (2019). In Table 4, we compare the OOD detection performance of this discriminator with likelihood ratios estimated with PixelCNN++ (Salimans et al.,

2017) as trained with the code of Ren et al. (2019) setting L_2 regularization as 10, and with the numbers taken from Xiao et al. (2020) given for their VAE models. Even though we use the code and hyperparameter settings of Ren et al. (2019), the AUC we obtain for SVHN as out-distribution differs significantly from their reported 93.1%. We observe that all three methods struggle with detecting inputs from several out-distributions and thus we do not consider them as reliable out-of-distribution detection methods.

Table 4: AUROC for CIFAR-10 vs. various out-distributions. The Likelihood Ratio Ren et al. (2019) PixelCNN++ models were trained with their code. For the VAE, we cite the numbers of Xiao et al. (2020), as indicated by *. We also show a binary discriminator between CIFAR-10 and the background distribution of Ren et al. (2019).

MODEL	MEAN	SVHN	LSUN	UNI	SMOOTH	C-100	OPEN	CELEBA	80M
LHRATIO PIXELCNN++	64.77	12.57	88.85	100.00	89.55	53.60	74.50	58.26	40.87
LHRATIO VAE*		26.5*	63.2*	100.0*				44.7*	
BINDISC	58.81	55.07	66.10	100.00	44.43	47.05	57.20	48.48	52.16

E EVALUATIONS WITH THE AUC DETECTION METRIC

Complementing the evaluations of the FPR@95TPR metric presented in the main paper, Tables 5 and 6 show the AUC (AUROC) values of the same models as in Tables 1 and 2, respectively. The observations on the strngths of the different methods and scoring functions discussed in Section 4 also hold for the AUC evaluations, which is not surprising since the AUC and FPR@95TPR metrics are closely related.

Table 5: Accuracy on the in-distribution (CIFAR-10/CIFAR-100) and **AUC** for various test out-distributions of the different OOD methods with OpenImages as training out-distribution for which the FPRs are shown in Table 1.

		IN-DISTRIBUTION: CIFAR-10								
MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-100 AUC	80M AUC	CELA AUC	OPENIM AUC
PLAIN CLASSI	95.16	91.85	93.52	92.94	97.04	92.84	89.61	91.30	85.70	84.81
MAHALANOBIS		91.63	96.34	92.39	100.00	99.82	86.78	89.41	76.67	84.81
OE	95.06	97.28	98.49	99.99	99.99	99.99	90.03	92.53	99.91	99.43
BGC s_1	95.21	95.02	99.48	100.00	99.99	99.95	79.64	86.37	99.74	99.97
BGC s_2	95.21	97.22	98.90	100.00	99.99	99.67	90.47	92.41	99.11	99.73
BGC s_3	95.21	97.21	98.87	100.00	99.98	99.62	90.47	92.41	99.08	99.71
SHARED BINDISC	95.28	92.51	98.77	100.00	99.89	99.93	68.34	80.81	99.80	99.95
SHARED CLASSI	95.28	95.49	96.10	98.60	99.06	96.09	90.09	92.35	96.18	93.57
SHARED COMBI s_2	95.28	97.26	98.66	100.00	99.93	99.94	89.71	92.84	99.72	99.88
SHARED COMBI s_3	95.28	97.26	98.62	100.00	99.93	99.94	89.75	92.85	99.71	99.88
		IN-DISTRIBUTION: CIFAR-100								
MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-10 AUC	80M AUC		OPENIM AUC
PLAIN CLASSI	77.16	82.13	82.33	79.13	96.03	81.36	76.14	77.80		75.80
MAHALANOBIS		85.88	88.69	87.56	90.08	99.91	70.78	78.26		77.51
OE	77.19	90.37	89.54	99.98	99.03	99.68	75.95	78.03		99.67
BGC s_1	77.61	88.41	97.38	99.99	99.70	99.79	60.51	73.11		99.93
BGC s_2	77.61	90.47	90.50	99.99	99.87	99.75	74.88	77.82		99.64
BGC s_3	77.61	90.46	90.46	99.99	99.88	99.74	74.88	77.82		99.64
SHARED BINDISC	77.35	84.62	97.44	99.99	99.70	99.68	47.82	63.13		99.93
SHARED CLASSI	77.35	82.06	82.72	99.05	72.73	84.14	75.76	77.99		93.54
SHARED COMBI s_2	77.35	90.74	91.74	99.99	99.59	99.54	75.50	78.10		99.57
SHARED COMBI s_3	77.35	90.73	91.69	99.99	99.57	99.53	75.50	78.10		99.57

Table 6: **AUC** evaluation of the models trained with shared and separate representations from Table 2.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-100 AUC	80M AUC	CELA AUC	OPENIM AUC
PLAIN CLASSI	95.16	91.85	93.52	92.94	97.04	92.84	89.61	91.30	85.70	84.81
SEPARATE BINDISC		89.03	96.42	100.00	99.97	99.99	58.60	72.36	95.87	99.99
SEPARATE COMBI s_3	95.16	96.40	98.16	100.00	99.98	99.99	89.64	91.35	95.70	99.94
SHARED BINDISC	95.28	92.51	98.77	100.00	99.89	99.93	68.34	80.81	99.80	99.95
SHARED CLASSI	95.28	95.49	96.10	98.60	99.06	96.09	90.09	92.35	96.18	93.57
SHARED COMBI s_3	95.28	97.26	98.62	100.00	99.93	99.94	89.75	92.85	99.71	99.88
PLAIN ⊗ SHA DISC s_3	95.16	97.26	98.67	100.00	99.91	99.93	89.78	92.95	99.58	99.87

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN	SVHN	LSUN	UNI	SMOOTH	C-10	OPENIM	80M
PLAIN CLASSI	77.16	82.13	82.33	79.13	96.03	81.36	76.14	77.80	75.80
SEPARATE BINDISC		84.30	94.68	100.00	99.81	99.64	50.06	61.62	99.98
SEPARATE COMBI s_3	77.16	88.95	84.49	99.99	99.88	96.06	75.83	77.45	99.82
SHARED BINDISC	77.35	84.62	97.44	99.99	99.70	99.68	47.82	63.13	99.93
SHARED CLASSI	77.35	82.06	82.72	99.05	72.73	84.14	75.76	77.99	93.54
SHARED COMBI s_3	77.35	90.73	91.69	99.99	99.57	99.53	75.50	78.10	99.57
PLAIN ⊗ SHA DISC s_3	77.16	90.79	91.99	99.99	99.80	98.85	75.87	78.23	99.50

F   EXPERIMENTS WITH 80 MILLION TINY IMAGES AS TRAINING OUT-DISTRIBUTION

Since the 80 Million Tiny Images (Torralba et al., 2008) dataset was retracted by the authors – their statement can be read at `http://groups.csail.mit.edu/vision/TinyImages/`[1] – as a reaction to Birhane & Prabhu (2021) exposing the presence of offensive and prejudicial images in the dataset, a good "surrogate surrogate" training out-distribution for the CIFAR-10/CIFAR-100 in-distribution has to our knowledge not yet been established. In the main paper, we employ OpenImages (Krasin et al., 2017) as a replacement, and for completeness and comparison to the originals of OE and NTOM/ATOM, below we show and discuss the results obtained with the retracted 80M dataset which is commonly used in OOD detection literature.

The training procedure of our methods again follows that of OE, and for the 80M experiments we do not add AutoAugment, in order to stay as close as possible to the original. For the established methods we compare to, we use the original weights of their published models; the Plain and Outlier Exposure (OE) models were retrieved from the repository of the authors of OE (`https://github.com/hendrycks/outlier-exposure`), and for NTOM and ATOM (Chen et al., 2021) we use their code `https://github.com/jfc43/informative-outlier-mining` to evaluate their DenseNet models (their best models). We finetune the Mahalanobis detector on 80M with the same procedure as described above; the optimal input noise level for 80M is 0.0005 for both CIFAR in-distributions.

For CIFAR-10, as already seen with OpenImages as training out-distribution, the OOD detection performance of SHARED CLASSI is much better than that of the plain classifier. .In fact SHARED BINDISC has already very good OOD performance with a mean FPR of 7.56 and mean AUC of 97.90 which is only improved by considering scoring function s_2/s_3 in the combination of SHARED BINDISC and SHARED CLASSI which yields the best performance in classification accuracy and mean AUC.

The classifier with 80M as background class (BGC) works very well for all scoring functions and reaches SOTA performance similar to/better than OE. Both BGC/SHARED COMBI with s_2/s_3 perform particularly well on the challenging close out-distributions CIFAR-100 and OpenImages (which are the data sets where NTOM/ATOM perform significantly worse). However, as already observed with OpenImages as training out-distribution the differences of the methods are minor both in terms of classification accuracy.

The results for CIFAR-100 are again qualitatively similar to those for CIFAR-10. NTOM/ATOM now show worse mean AUC results which are mainly due to worse results for the close out-distributions CIFAR-10 and OpenImages, but better mean FPR@95%TPR, which is explained by their excellent detection of LSUN Classroom, where the other methods work quite well in terms of AUC but still make quite many errors at the 95%TPR threshold. OE again achieves comparable OOD results to the other evaluated methods. Our SHARED COMBI s_2/s_3 performs best in terms of OOD performance and test accuracy but again differences are minor.

The conclusions are similar to those drawn for OpenImages in the main paper. Comparing the results, it is clear that 80M still works somewhat better than OpenImages, so for the CIFAR in-distributions, the search for an ethically acceptable replacement of 80M that allows for equal or improved results continues. The consistent similarities between the examined methods over the different datasets suggest that the methods and scoring functions would be similarly viable with such an alternative training OOD dataset.

---

[1] Archived statement: `https://web.archive.org/web/20210415160225/http://groups.csail.mit.edu/vision/TinyImages/`

Table 7: Accuracy on the in-distribution (CIFAR-10/CIFAR-100) and **FPR@95%TPR** for various test out-distributions of different OOD methods with **80 Million Tiny Images** as training out-distribution (shown results for test set of 80M are not used for computing the mean FPR). Lower false positive rate is better. CelebA makes no sense as test out-distribution for CIFAR-100 as it contains man/woman as classes. All methods except NTOM/ATOM have been trained using the same architecture and training parameters/schedule. s_1, s_2, s_3 are the scoring functions introduced in Section 3.2. Our binary discriminator (BINDISC) resp. the combination with the shared classifier (SHARED COMBI) performs similar/better than Outlier Exposure (Hendrycks et al., 2019).

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-100 FPR	OPENIM FPR	CELA FPR	80M FPR
PLAIN CLASSI	94.84	64.62	48.33	52.67	75.69	62.58	62.91	66.38	83.79	60.53
MAHALANOBIS		41.15	40.19	50.00	0.00	0.17	58.66	58.36	80.69	53.42
NTOM	95.42	8.21	1.06	0.33	0.00	0.00	29.61	26.15	0.30	4.90
ATOM	95.20	7.76	0.69	0.33	0.00	0.00	27.80	25.26	0.25	4.44
OE	95.74	8.27	1.96	2.00	0.00	0.06	26.12	27.07	0.71	5.96
BGC s_1		7.47	0.83	1.33	0.00	0.00	24.75	25.19	0.19	4.43
BGC s_2	95.63	7.42	0.98	1.33	0.00	0.00	24.13	25.33	0.20	4.95
BGC s_3	95.63	7.49	1.05	1.33	0.00	0.00	24.26	25.57	0.21	4.82
SHARED BINDISC		7.56	0.67	1.67	0.00	0.00	24.70	25.58	0.31	4.57
SHARED CLASSI	96.08	15.71	6.29	13.00	0.07	0.13	37.07	40.48	12.95	19.47
SHARED COMBI s_2	96.08	7.47	0.71	1.33	0.00	0.00	24.15	25.72	0.35	4.79
SHARED COMBI s_3	96.08	7.44	0.73	1.33	0.00	0.00	23.95	25.70	0.35	4.84

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-10 FPR	OPENIM FPR	80M FPR
PLAIN CLASSI	75.96	82.26	84.33	80.00	98.99	65.81	81.97	82.47	80.17
MAHALANOBIS		47.89	64.58	63.67	0.00	2.77	81.39	74.93	69.79
NTOM	74.88	32.63	24.67	10.00	0.00	0.00	90.58	70.52	40.78
ATOM	75.06	34.60	37.78	8.67	0.00	0.30	89.80	71.02	40.29
OE	76.73	34.89	34.41	24.00	1.10	4.96	79.77	65.09	45.59
BGC s_1		34.79	35.73	23.00	0.00	0.07	81.61	68.31	45.76
BGC s_2	75.82	35.86	40.36	26.67	0.00	0.45	79.50	68.21	47.72
BGC s_3	75.82	35.91	40.53	26.67	0.00	0.42	79.54	68.28	47.46
SHARED BINDISC		32.74	25.16	22.00	0.00	0.00	82.47	66.83	44.50
SHARED CLASSI	76.52	44.86	56.96	57.00	0.06	0.22	79.55	75.37	65.50
SHARED COMBI s_2	76.52	32.71	25.70	23.67	0.00	0.00	80.95	65.93	44.87
SHARED COMBI s_3	76.52	32.72	25.79	23.67	0.00	0.00	80.90	65.98	44.96

Table 8: Accuracy on the in-distribution (CIFAR-10/CIFAR-100) and **AUC** (AUROC) for various test out-distributions of different OOD methods with **80 Million Tiny Images** as training out-distribution (shown results for test set of 80M are not used for computing the mean AUC). The relative performance of the different methods measured in AUC is similar to what we observed with the FPR@95%TPR measure in Table 7.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-100 AUC	OPENIM AUC	CELA AUC	80M AUC
PLAIN CLASSI	94.84	85.75	91.91	91.63	87.69	78.27	87.83	83.23	79.43	88.01
MAHALANOBIS		91.12	94.34	91.98	100.00	99.51	88.08	84.92	79.17	89.65
NTOM	95.42	97.32	99.59	99.79	99.97	99.84	92.19	89.96	99.89	98.72
ATOM	95.20	97.42	99.63	99.76	99.93	99.60	92.89	90.30	99.85	98.55
OE	95.74	97.64	99.48	99.48	99.46	99.64	94.80	90.91	99.71	98.50
BGC s_1		97.94	99.64	99.58	99.96	99.98	94.84	91.65	99.92	98.78
BGC s_2	95.63	97.95	99.60	99.52	99.97	99.98	95.03	91.65	99.92	98.65
BGC s_3	95.63	97.95	99.58	99.52	99.97	99.98	95.04	91.64	99.92	98.70
SHARED BINDISC		97.90	99.74	99.60	99.94	99.96	94.75	91.42	99.87	98.77
SHARED CLASSI	96.08	96.57	98.77	97.78	99.87	99.68	93.40	88.70	97.80	96.42
SHARED COMBI s_2	96.08	97.96	99.73	99.58	99.95	99.96	95.13	91.48	99.85	98.73
SHARED COMBI s_3	96.08	97.96	99.73	99.58	99.95	99.96	95.14	91.48	99.85	98.73

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-10 AUC	OPENIM AUC	80M AUC
PLAIN CLASSI	75.96	77.48	71.38	76.89	78.14	88.36	75.33	74.60	75.92
MAHALANOBIS		87.75	85.96	87.20	100.00	99.16	75.45	78.74	79.76
NTOM	74.88	88.49	96.20	97.31	99.79	99.94	62.44	75.24	88.41
ATOM	75.06	88.02	93.68	97.51	99.98	98.46	63.47	75.02	88.44
OE	76.73	91.72	94.06	95.58	99.06	98.84	79.53	83.31	88.43
BGC s_1		92.04	94.42	95.47	99.99	99.73	79.15	83.46	89.19
BGC s_2	75.82	91.54	93.32	94.64	99.95	99.63	79.29	82.41	88.11
BGC s_3	75.82	91.53	93.30	94.62	99.94	99.62	79.29	82.40	88.23
SHARED BINDISC		91.84	95.90	95.69	99.79	99.94	76.56	83.19	89.25
SHARED CLASSI	76.52	88.16	86.28	87.61	99.97	99.90	77.00	78.23	81.72
SHARED COMBI s_2	76.52	92.03	95.50	95.43	99.96	99.98	78.46	82.86	88.69
SHARED COMBI s_3	76.52	92.03	95.49	95.42	99.97	99.98	78.46	82.85	88.67

G   EXPERIMENTS WITH SVHN AS TRAINING OUT-DISTRIBUTION

In order to examine the effect of a training out-distribution that relatively far away from the in-distribution, we show experiments with SVHN as out-distribution in Tables 9 and 10. The OOD detection performance of these methods is much worse than with the closer OpenImages and 80M training out-distributions. In most cases, combinations s_2 and s_3/OE which implicitly or explicitly use the classifier confidence lead to better OOD detection than using the binary discriminator/s_1. We also do not observe a beneficial effect on test accuracy for the methods that use SVHN compared to plain, which is to be expected as the representations learned from SVHN are hardly useful for the in-distribution task.

Table 9:   **FPR@95%TPR** for CIFAR-10/CIFAR-100 as in-distribution with **SVHN** as training out-distribution.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-100 FPR	80M FPR	OPENIM FPR	CELA FPR	SVHN FPR
PLAIN CLASSI	94.84	64.62	48.33	52.67	75.69	62.58	62.91	66.38	83.79	60.53
OE	94.80	63.73	54.33	92.01	41.27	60.55	55.91	65.52	76.51	0.03
BGC s_1	94.51	54.31	53.00	100.00	0.51	55.16	39.28	64.36	67.87	0.00
BGC s_2	94.51	62.98	58.33	98.53	18.73	62.27	57.47	67.35	78.16	0.02
BGC s_3	94.51	63.08	58.33	98.52	19.18	62.34	57.63	67.39	78.16	0.02
SHARED BINDISC	94.71	72.95	95.67	100.00	5.81	77.04	66.75	85.17	80.22	0.00
SHARED CLASSI	94.71	48.39	54.33	0.00	17.99	62.34	57.37	67.05	79.64	0.57
SHARED COMBI s_2	94.71	46.27	55.00	0.00	6.74	60.84	55.15	66.50	79.65	0.02
SHARED COMBI s_3	94.71	46.31	55.00	0.00	6.84	60.90	55.26	66.53	79.65	0.02

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-10 FPR	80M FPR	OPENIM FPR	SVHN FPR
PLAIN CLASSI	75.96	82.26	84.33	80.00	98.99	65.81	81.97	82.47	80.17
OE	75.78	73.89	81.33	99.47	15.93	83.32	80.30	83.01	0.04
BGC s_1	75.21	77.16	96.33	100.00	3.35	91.05	80.55	91.68	0.00
BGC s_2	75.21	74.53	80.00	98.49	21.49	83.14	80.52	83.54	0.07
BGC s_3	75.21	74.53	80.00	98.49	21.50	83.14	80.53	83.54	0.07
SHARED BINDISC	75.97	82.08	99.33	100.00	10.04	95.00	91.21	96.89	0.00
SHARED CLASSI	75.97	83.46	78.67	100.00	76.67	82.36	79.99	83.08	0.44
SHARED COMBI s_2	75.97	78.66	78.67	100.00	47.73	82.44	79.93	83.20	0.07
SHARED COMBI s_3	75.97	78.66	78.67	100.00	47.78	82.43	79.92	83.17	0.07

Table 10: **AUC** for CIFAR-10/CIFAR-100 as in-distribution with **SVHN** as training out-distribution.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-100 AUC	80M AUC	OPENIM AUC	CELA AUC	SVHN AUC
PLAIN CLASSI	94.84	85.75	91.91	91.63	87.69	78.27	87.83	83.23	79.43	88.01
OE	94.80	88.37	91.72	91.33	91.20	88.26	89.55	82.97	83.59	100.00
BGC s_1	94.51	83.58	89.43	58.34	99.80	85.44	90.28	78.01	83.76	100.00
BGC s_2	94.51	89.62	91.50	91.14	97.60	88.72	89.98	82.96	85.40	100.00
BGC s_3	94.51	89.60	91.50	91.14	97.54	88.71	89.96	82.96	85.40	100.00
SHARED BINDISC	94.71	58.47	37.27	38.61	98.85	55.19	65.66	48.61	65.12	100.00
SHARED CLASSI	94.71	90.14	90.20	99.70	97.44	88.50	89.68	82.97	82.51	99.80
SHARED COMBI s_2	94.71	90.18	89.74	99.67	99.00	88.49	89.87	82.43	82.09	100.00
SHARED COMBI s_3	94.71	90.19	89.76	99.68	98.97	88.50	89.87	82.46	82.12	100.00

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-10 AUC	80M AUC	OPENIM AUC	SVHN AUC
PLAIN CLASSI	75.96	77.48	71.38	76.89	78.14	88.36	75.33	74.60	75.92
OE	75.78	78.86	75.93	73.53	97.02	75.37	76.57	74.74	99.99
BGC s_1		66.60	67.45	24.51	99.37	68.50	73.82	65.97	100.00
BGC s_2	75.21	77.38	76.04	67.25	96.28	74.83	75.86	74.01	99.98
BGC s_3	75.21	77.38	76.04	67.25	96.27	74.83	75.86	74.01	99.98
SHARED BINDISC		55.60	34.81	53.23	98.03	49.00	54.57	43.93	100.00
SHARED CLASSI	75.97	72.04	80.31	41.57	83.32	75.64	76.58	74.81	99.90
SHARED COMBI s_2	75.97	72.95	80.23	41.34	89.21	75.59	76.57	74.75	99.99
SHARED COMBI s_3	75.97	72.94	80.23	41.34	89.18	75.59	76.57	74.75	99.99

H THE EFFECT OF VARYING λ

We investigate the effect of choosing the training hyperparameter λ, which is the factor of the respective loss on the out-of-distribution samples and represents $\frac{p(o)}{p(i)}$ during training. We evaluate models trained with Outlier Exposure Hendrycks et al. (2019), background class and shared training of binary discriminator and classifier, all scored with s_3 (the implicit scoring function of OE). Note that in Section 4, the OE, BGC and SHARED models trained with $\lambda = 1.0$.

In Tables 11 and 12 we see that for CIFAR-10 the differences between different choices of λ are minor with no clear favorite, but setting $\lambda = 2.0$ tends to be too high. For CIFAR-100, the differences are much larger. Here, choosing λ too small can have a severe negative effect on the detection of the otherwise relatively to detect far out-distributions SVHN, Uniform Noise and Smooth Noise. Regarding the numbers for both in-distribution datasets, using $\lambda = 1$ is a considerate default choice.

Table 11: Effect of varying λ during training for OE (Hendrycks et al., 2019), the s_3 scoring function for models with background class and SHARED COMBI s_3. Shown are test accuracy and **FPR@95%TPR** with **OpenImages** as training out-distribution.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-100 FPR	80M FPR	CELA FPR	OPENIM FPR
OE λ=0.1	95.36	14.34	13.31	0.00	0.25	0.03	48.37	36.65	1.77	12.60
OE λ=0.25	95.31	16.17	19.64	0.00	0.00	0.05	51.77	40.21	1.55	7.74
OE λ=0.5	95.27	15.98	16.23	0.00	0.07	0.01	53.06	41.72	0.79	4.85
OE λ=1.0	95.06	15.20	9.58	0.00	0.00	0.00	54.05	42.33	0.45	3.46
OE λ=2.0	95.19	15.98	12.93	0.00	0.00	0.00	55.99	42.68	0.26	1.67
BGC s_3 λ=0.1	95.38	16.21	18.93	0.00	0.12	1.05	52.43	39.42	1.53	9.56
BGC s_3 λ=0.25	95.27	15.83	12.76	0.00	0.04	0.03	54.06	43.26	0.66	5.43
BGC s_3 λ=0.5	95.23	15.14	9.33	0.00	0.09	0.04	52.97	42.79	0.74	3.19
BGC $s_3$$\lambda$=1.0	95.21	16.63	7.69	0.00	0.07	2.36	55.19	44.67	6.41	1.74
BGC s_3 λ=2.0	95.28	17.45	8.72	0.00	0.00	0.00	59.02	48.09	6.31	0.71
SC s_3 λ=0.1	95.20	16.49	15.22	0.00	0.27	0.00	54.30	43.97	1.69	10.46
SC s_3 λ=0.25	95.21	16.17	15.32	0.00	0.15	0.04	54.60	42.59	0.53	5.19
SC s_3 λ=0.5	95.25	16.02	9.21	0.00	0.09	0.00	55.72	45.55	1.56	2.75
SC s_3 λ=1.0	95.28	16.06	9.00	0.00	0.00	0.00	58.68	42.85	1.91	0.66
SC s_3 λ=2.0	95.26	17.04	9.33	0.00	0.00	0.00	58.20	45.81	5.92	0.68

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN FPR	SVHN FPR	LSUN FPR	UNI FPR	SMOOTH FPR	C-10 FPR	80M FPR	OPENIM FPR
OE λ=0.1	77.28	52.35	70.29	1.00	28.58	56.15	82.44	75.64	17.94
OE λ=0.25	76.96	46.40	60.70	0.00	9.24	48.89	83.01	76.59	6.01
OE λ=0.5	77.22	36.43	53.12	0.00	0.15	4.62	82.86	77.84	4.23
OE λ=1.0	77.19	35.03	47.36	0.00	0.67	0.08	84.64	77.42	1.28
OE λ=2.0	76.95	33.25	37.04	0.00	0.00	1.70	83.28	77.48	0.86
BGC s_3 λ=0.1	76.87	41.23	67.39	1.00	5.97	13.81	82.44	76.76	15.70
BGC s_3 λ=0.25	77.05	42.05	49.94	0.00	17.07	25.41	82.34	77.55	7.47
BGC s_3 λ=0.5	77.17	36.14	43.90	0.00	10.54	3.70	82.86	75.86	3.76
BGC $s_3$$\lambda$=1.0	77.61	33.36	37.27	0.00	0.00	0.20	84.51	78.19	1.27
BGC s_3 λ=2.0	77.26	32.60	35.34	0.00	0.00	0.00	82.69	77.57	1.20
SC s_3 λ=0.1	77.35	58.54	62.07	0.33	92.62	37.44	82.05	76.74	14.17
SC s_3 λ=0.25	76.96	41.34	63.29	0.00	10.24	14.34	82.68	77.50	7.22
SC s_3 λ=0.5	76.64	49.63	49.55	0.00	44.78	43.85	82.30	77.31	1.97
SC s_3 λ=1.0	77.35	33.06	37.57	0.00	0.00	1.13	82.68	77.01	1.85
SC s_3 λ=2.0	76.63	34.09	39.56	0.00	0.00	5.21	82.57	77.18	1.04

Table 12: Effect of varying λ during training for OE (Hendrycks et al., 2019), the s_3 scoring function for models with background class and SHARED COMBI s_3. Shown are test accuracy and **AUC** (AUROC) with **OpenImages** as training out-distribution.

IN-DISTRIBUTION: CIFAR-10

MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-100 AUC	80M AUC	CELA AUC	OPENIM AUC
OE λ=0.1	95.36	97.49	97.96	99.96	99.84	99.93	91.25	93.81	99.70	97.86
OE λ=0.25	95.31	97.15	96.93	99.98	99.98	99.93	90.59	92.91	99.74	98.71
OE λ=0.5	95.27	97.19	97.53	99.99	99.95	99.99	90.29	92.73	99.87	99.20
OE λ=1.0	95.06	97.28	98.49	99.99	99.99	99.99	90.03	92.53	99.91	99.43
OE λ=2.0	95.19	97.19	97.99	99.99	99.99	100.00	89.89	92.56	99.93	99.67
BGC s_3 λ=0.1	95.38	97.37	97.32	99.99	99.93	99.63	91.18	93.74	99.78	98.39
BGC s_3 λ=0.25	95.27	97.43	98.25	100.00	99.96	99.98	90.85	93.09	99.91	99.13
BGC s_3 λ=0.5	95.23	97.44	98.62	100.00	99.93	99.98	90.80	92.84	99.89	99.48
BGC s_3 λ=1.0	95.21	97.21	98.87	100.00	99.98	99.62	90.47	92.41	99.08	99.71
BGC s_3 λ=2.0	95.28	97.10	98.71	100.00	99.98	100.00	89.93	91.94	99.11	99.86
SC s_3 λ=0.1	95.20	97.29	97.87	99.99	99.91	99.98	90.69	92.82	99.77	98.32
SC s_3 λ=0.25	95.21	97.33	97.90	99.99	99.91	99.97	90.57	93.08	99.92	99.17
SC s_3 λ=0.5	95.25	97.34	98.68	100.00	99.95	100.00	90.39	92.56	99.78	99.57
SC s_3 λ=1.0	95.28	97.26	98.62	100.00	99.93	99.94	89.75	92.85	99.71	99.88
SC s_3 λ=2.0	95.26	97.13	98.59	100.00	100.00	99.99	89.95	92.25	99.13	99.88

IN-DISTRIBUTION: CIFAR-100

MODEL	ACC.	MEAN AUC	SVHN AUC	LSUN AUC	UNI AUC	SMOOTH AUC	C-10 AUC	80M AUC	OPENIM AUC
OE λ=0.1	77.28	87.38	83.69	99.79	94.79	91.50	76.08	78.43	95.73
OE λ=0.25	76.96	88.31	86.94	99.98	97.74	90.74	76.11	78.35	98.51
OE λ=0.5	77.22	89.82	87.22	99.98	99.74	98.95	75.39	77.64	98.94
OE λ=1.0	77.19	90.37	89.54	99.98	99.03	99.68	75.95	78.03	99.67
OE λ=2.0	76.95	90.56	91.42	99.99	99.78	99.08	75.51	77.58	99.76
BGC s_3 λ=0.1	76.87	88.86	83.41	99.87	98.35	97.37	75.97	78.21	95.99
BGC s_3 λ=0.25	77.05	89.29	89.10	99.99	97.13	95.91	75.96	77.68	98.08
BGC s_3 λ=0.5	77.17	90.17	90.07	99.99	97.99	99.07	75.49	78.42	99.04
BGC s_3 λ=1.0	77.61	90.46	90.46	99.99	99.88	99.74	74.88	77.82	99.64
BGC s_3 λ=2.0	77.26	90.83	91.74	99.99	99.72	99.80	75.72	78.02	99.67
SC s_3 λ=0.1	77.35	86.08	85.56	99.95	84.55	93.24	75.27	77.89	96.74
SC s_3 λ=0.25	76.96	88.76	85.08	99.98	97.73	97.17	75.11	77.51	98.31
SC s_3 λ=0.5	76.64	88.42	88.80	99.99	94.61	93.94	75.63	77.52	99.51
SC s_3 λ=1.0	77.35	90.73	91.69	99.99	99.57	99.53	75.50	78.10	99.57
SC s_3 λ=2.0	76.63	90.54	91.24	99.99	99.86	98.93	75.30	77.91	99.74