# Robust Claim Verification Through Fact Detection

## Abstract

Claim verification can be a difficult task, even for humans. In this paper, we propose a method to improve automated claim verification through short fact extraction from evidence to enhance reasoning abilities. We use Large Language Models (LLMs) to generate short factual statements from evidence and then label these facts based on their relevance to the claim. We then add a relevant fact-detection task (FactDetect) to the claim verification task as a multi-tasking approach to improve performance and explainability.

Our method improves the supervised claim verification model by 15% on the F1 score when evaluated on SciFact (Wadden et al., 2020) and demonstrates competitive results on other challenging scientific claim verification datasets. We also demonstrate that FactDetect can be adjusted to the LLMs as a prompting strategy for verdict prediction. We show that incorporating FactDetect in relatively smaller LLMs such as Llama2-13B and Vicuna-13B can improve the verification performance significantly on the SciFact dataset. however, experiments and analysis on different larger LLMs indicate that there is substantial room for improvement in incorporating FactDetect on the claim verification task.

Figure 1: Three-step process of short fact generation from evidence sentences. 1) First we use LLM to generate matching phrases between claim and evidence. ) Using the extracted phrases from **claim** we design a question generation to generate questions from the claim and the given phrase. 3) The generated matching phrase from **evidence** is concatenated with the question generated from **claim** for short fact generation.

## 1 Introduction

Due to the proliferation of disinformation in many online platforms such as social media, automated claim verification has become an important task in natural language processing (NLP). "Claim verification" refers to predicting the verdict for a claim (supported, contradicted) given the evidence that has been extracted from a corpus of documents (Thorne et al., 2018; Wadden et al., 2022a; Guo et al., 2022).

Claim verification can be challenging for several reasons. First, the available human-annotated data is limited, resulting in limited performance by current trained models. The task is even harder for scientific claim verification where the claim and the corresponding evidence belong to specific scientific domains: verification of scientific claims generally requires specialized knowledge of the scientific background, numerical reasoning, and statistics (Wadden et al., 2020). A key challenge in developing automated argumentation systems lies in accurately representing the subtleties of argumentation. This includes the capacity to change a verdict from 'supported' to 'refuted' when a new claim in the test set potentially negates the evidence, in contrast to approving it in the training set.

Human-based reasoning for this task requires making a meaningful connection between the claim and evidence by decomposing the claim and relevant evidence into smaller pieces and performing reasoning (Pan et al., 2023). A few studies proposed approaches for reasoning (Pan et al., 2023; Liangming Pan, 2021; Dai et al., 2022; Lee et al., 2021). Question-answering (i.e., asking questions from claim or evidence, retrieving the answer from each component, and utilizing the answer for the downstream task) is one of the approaches used for improving reasoning and explanation in claim verification tasks (Liangming Pan, 2021; Dai et al., 2022). Intuitively a question asked from a supported or contradicted claim should be *answerable* by the corresponding evidence and the answer provided by evidence can provide important factual information for veracity prediction.

Motivated by these reasoning approaches, we introduce FactDetect, an effective add-on task that enhances the state-of-the-art trained models – as well as LLMs – to learn to reason by analyzing and detecting key concise facts from the evidence. FactDetect comprises: a) short fact generation through a four-step process of matching key-phrase extraction, question generation, evidence-based question answering, and QA-to-sentence generation; b) weakly labeling short facts based on their importance given the claim; and, c) utilizing these facts in a multi-task learning-based training of a claim verification model or as an extra step to improve the performance of LLMs for zero-shot claim-verification. An overview of the fact-generation process is given in Figure 1.

We evaluate FactDetect in two variations of multi-task-based finetuning of claim verification models and zero-shot claim verification through LLMs on four scientific claim-verification datasets of SciFact (Wadden et al., 2020), Covid-Fact (Saakyan et al., 2021), HealthVer (Sarrouti et al., 2021) and Scifact-Open (Wadden et al., 2022a).

The contributions of this study are:

1. We introduce FactDetect, a simple yet effective approach for condensing evidence sentences into shorter sentences derived from relevance to the claim.

2. Our extensive experiments show that FactDetect can be easily adapted to claim-verification models to improve their reasoning ability.

3. Augmenting FactDetect generated short facts for a multi-task prompting approach is useful in smaller LLMs whereas it shows less effective in larger LLMs.

## 2  Background

Automated claim verification means determining the veracity of a claim, typically by retrieving likely relevant documents and searching for evidence within them. The key objective is to ascertain if the evidence either *SUPPORTS* or *CONTRADICTS* the claim in question. Various datasets have been proposed to facilitate research in this area in different domains: e.g., FEVER (Thorne et al., 2018) is a Wikipedia-based claim verification dataset. Claim verification in the scientific domain has also been proposed in recent years to facilitate research in this complex domain (Wadden et al., 2022a, 2020; Saakyan et al., 2021; Sarrouti et al., 2021; Kotonya and Toni, 2020; Diggelmann et al., 2020). These datasets, despite their value, often have limited training data due to the high cost of creation, impacting the reasoning capabilities and robustness of claim verification methods.

In addressing these challenges, the literature shows significant advances in models for verifying scientific claims through reasoning. One notable strategy is the *generation* of explanations. Prior studies have explored using attention mechanisms to identify key evidence segments (Popat et al., 2017; Cui et al., 2019; Yang et al., 2019; Jolly et al., 2022). Recently, the integration of LLMs in explanation generation has been investigated. For example, ProgramFC (Pan et al., 2023) uses LLMs to generate reasoning programs that can be used to guide fact-checking and FORK (Wang and Shu, 2023) leverages the in-context learning ability of LLMs to generate First Order Logic-Guided reasoning over a set of knowledge-grounded question-and-answer pairs to make veracity predictions without using annotated evidence.

Our work diverges from these methodologies as we propose an add-on task to enhance the robustness and reasoning ability of existing models. This is achieved through a novel data augmentation strategy, which improves the connection between claims and evidence by focusing on learning critical, relevant short facts essential for effective claim verification.

```
Instructions: Extract RELEVANT keyphrase pairs from CLAIM and
EVIDENCE that determine the verdict.
There can be more than one relevant keyphrase pair. OUTPUT each
key phrase pair in a JSON format.

Input: CLAIM: <Cellphones can be unhealthy for kids and kids are
spending a lot of time on their phones.> EVIDENCE: <According to
the research published in the Journal of Behaviour Addiction,
overuse of smartphones is associated with various mental health
concerns such as anxiety depression, and low self-esteem. >
```

```
Output:[{"claim_phrase": Unhealthy for kids, "evidence_phrase":
various mental health concerns}, {"claim_phrase": Spending a lot of
time on their phone, "evidence_phrase": overuse of smartphones},
{"claim_phrase": Cellphones unhealthy for kids, "evidence_phrase":
Smartphones associated with mental health concerns}]
```

Figure 2: Example of the prompting method for extracting $(a_i^c, a_i^e) \in \mathcal{A}$. Since there can be multiple phrase pairs that are important for claim verification, we aim to extract all of them using this approach.

## 3 Methodology

We introduce FactDetect, a novel approach designed to enhance the performance of claim verification solutions by leveraging automatically generated short facts extracted from the evidence. FactDetect is a versatile tool that can be integrated into various claim verification methods, improving the robustness and reasoning capabilities of existing models. The core of FactDetect relies on weakly labeled short facts, which are categorized as either *important* for verifying a given claim or *not important* for that purpose, which are used to train a multi-task learning-based model for importance detection and claim verification.

### 3.1 Definition

Here, we formally define the primary task of fact generation and labeling: Given a claim statement ($c$) and corresponding evidence statement ($e$), our objective is to generate concise "facts" from the $e$. We denote this set of facts by $\mathcal{F}_e = \{f1, \ldots, f_m\}$. Each fact is subsequently labeled as either "important" or "not important," denoted as $y_{f_i} \in \{important, not\ important\}$.

It is crucial to emphasize that these facts are intentionally designed to be shorter in length compared to the original evidence ($e$). They serve as distilled pieces of information extracted from the broader context of the evidence. These succinct facts are intended to capture essential details or insights within the evidence, making them more manageable for claim verification tasks.

We next elaborate on the processes of short fact generation and weak labeling.

### 3.1.1 Short Fact Generation

To generate short facts from the evidence ($e$), we adopt a three-step approach.

**1) Phrase matching**: Initially, we extract matching phrases from both the claim ($c$) and the evidence, treating these phrases as potential answers to questions ($\mathcal{A} = (a_1^c, a_1^e), \ldots, (a_n^c, a_n^e)$). Phrases that "match" refers to a pair of phrases that convey similar meaning and/or are semantically similar. To accomplish this, we employ LLM Vicuna-13B (Chiang et al., 2023) for short fact generation. Importantly, we do not restrict the LLM to follow specific phrase rules such as length restrictions, using only entities or nouns, ensuring the capture of diverse answer pairs more likely to be relevant. An example of answer pair extraction from $c$ and $e$ is given in Figure 2.

**2) Question Generation**: Once the answer pairs are identified, we proceed to create concise questions. For each answer $a_i^c$ from the claim $c$, we formulate a question ($q_i$). We do not incorporate the corresponding answer from the evidence ($a_i^e$) in generating $q_i$. The underlying rationale is that if a question posed with a claim has an answer within the claim itself and can also be answered by evidence, that answer becomes crucial in predicting the verdict. Conversely, if the question cannot be answered by the evidence, there is no meaningful connection between the evidence and the claim based on that answer. For example, from Figure 2, the first claim phrase results in the question *What is the effect of cellphones for the kids?*.

**3) Short Fact Generation**: Finally, We generate short fact sentences by pairing each question ($q_i$) with its corresponding evidence-based answer ($a_i^e$) which was extracted in the first step. These questions along with the answers are then converted into full sentences $f_i$. For example, the previous question and answer results in *Cellphones cause various mental health concerns for the kids.*.

### 3.2 Weak labeling

Labeling each generated fact as "important" or "not important" is a crucial step in the FactDetect process. We incorporate a new reasoning-infused strategy to label the generated facts. To do this we first focus on the "reasonability" of the generated questions from the previous step. Here, we query the LLM to determine if a question ($q_i$) can be answered simultaneously by both the claim ($c$) and the evidence ($e$). If the answer is affirmative,

| Dataset | Corpus | Train | | Dev | | Test | |
|---|---|---|---|---|---|---|---|
| | | Claims | CE pairs | Claims | CE pairs | Claims | CE pairs |
| SciFact-Open | 500K | – | – | – | – | 279 | 460 |
| Scifact | 14K | 809 | 564 | 300 | 209 | 300 | – |
| HealthVer | 322 | 1393 | 3340 | 230 | 508 | 230 | 599 |

Table 1: Statistics of datasets used in our experiments. Claim Evidence pairs (CE pairs) for each dataset are provided. Scifact test set is not included with gold-labeled evidence sentences therefore the CE pairs are not reported for this dataset.

the sentence $f_i$ generated from pairing $q$ and the evidence-based answer ($a_i^e$) is added to the candidate answers $\mathcal{A}_c$. This step is crucial for two reasons: 1) it serves to eliminate any unsuccessful question generations that can occur with LLMs (e.g., the failures can be due to the inconsistent and hallucinated generations), and 2) it helps FactDetect to extract the most important question-answer pairs for claim verification. After extracting those candidates we label a short fact sentence $f_i$ as "important" if the cosine similarity between $f_i$ and the claim $c$ and $f_i$ and evidence $e$ exceeds a predefined threshold ($t$) and "not important" if not. More specifically:

$$sim(f_i, c, e) = \gamma \cos(f_i, c) + \gamma \cos(f_i, e) \quad (1)$$

$$y_{f_i} = \begin{cases} \text{"important"} & \text{if } sim(f_i, c, e) \geq t \\ \text{"not important"} & \text{otherwise} \end{cases}$$

Here $\alpha$ is a hyperparameter and $\cos(.)$ is calculated using the Sentence Transformers (Reimers and Gurevych, 2019) embedding of $f_i$, $c$ and $e$.

### 3.3 Joint Claim Verification and Fact Detection Framework

Because of the success of the full context training of claim verification tasks within state-of-the-art models such as MULTIVERS (Wadden et al., 2022b), PARAGRAPHJOINT (Li et al., 2021), and ARSJOINT (Zhang et al., 2021), we propose a similar enhancement approach. Our framework revolves around performing full context predictions by concatenating the claim ($c$), title ($t$), gold evidence ($e$), and all the facts in $\mathcal{F}_e$ with a special separator token to separate each fact in $\mathcal{F}_e$.

Our approach employs a multi-tasking-based strategy where the model is jointly trained to minimize a multitask loss defined as follows:

$$L = L_{cv} + \alpha L_{fact} \quad (2)$$

where $L_{cv}$ represents the cross-entropy loss associated with predicting the overall claim verification task. Specifically, we predict $y(c, e)$ where:

$$y(c, e) \in \{SUPPORTED, CONTRADICTED, NEI\} \quad (3)$$

by adding a classification head on the $$ token. In addition, $L_{fact}$ denotes the binary cross-entropy loss for predicting whether each fact ($f_i$) is important to the claim ($c$) or not, and $\alpha$ is a hyperparameter. During inference, we only predict $y(c, e)$, setting aside the fact detection part.

### 3.4 Zero-shot prediction with LLMs

In addition to the full fine-tuning approach just presented, we introduce a zero-shot approach where we augment FactDetect generated short fact sentences $\mathcal{F}_|$ into the prompt for claim verification through fact-detection: given $c$, $e$ and $\mathcal{F}_e$ we first ask an LLM to detect the most important facts and then, by making a connection between these important facts and $c$ and $e$, we ask it to predict the verdict $y(c, e)$.

Let $\mathcal{M}$ be a language model and $\mathcal{P}$ be the prompt. The $\mathcal{P}$ for the test inputs is generated by concatenating $c$, $e$ and $\mathcal{F}_e$ as follows:

Claim: $c$ Evidence: $c$ Facts: $\mathcal{F}_e$

We first ask the LLM to output *important facts* and then predict the verdict. i.e., $p(y(c, e)|\mathcal{M}(\mathcal{P}))$

## 4 Experiments

We evaluate the effect of including FactDetect within different claim verification models and encoders. To evaluate this, we first explain the datasets used and introduce the baseline models we compared to our approach.

### 4.1 Datasets

**SciFact** (Wadden et al., 2020) consists of expert annotated scientific claims from biomedical literature with their corresponding evidence sentences

| Setting | Model | HealthVer | | | SciFact | | | SciFact-Open | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | F1/Acc | P | R | F1/Acc | P | R | F1/Acc | P | R |
| **Few shot** | RoBERTa-Large | 38.7/34.7 | 39.1 | 38.3 | 37.0/43.0 | 36.3 | 37.8 | 36.3/30.1 | 35.8 | 36.8 |
| | RoBERTa-Large+FactDetect | 27.6/23.0 | 22.4 | 35.8 | 34.0/38.6 | 33.5 | 34.8 | 32.5/27.2 | 31.0 | 34.1 |
| | Longformer | 27.8/21.7 | 25.3 | 30.7 | 42.4/39.3 | 43.0 | 41.8 | 36.2/36.9 | 36.4 | 36.0 |
| | Longformer + FactDetect | 33.7/25.2 | 34.0 | 33.4 | 41.6/ 55.3 | 37.4 | 46.8 | 34.3/42.0 | 28.2 | 43.6 |
| **Full** | RoBERTa-Large | 43.9/28.6 | 52.0 | 37.9 | 48.5/64.6 | 43.3 | 55.2 | 38.1/45.1 | 30.7 | **50.1** |
| | RoBERTa-Large+FactDetect | 45.3 /25.6 | 61.0 | 36.0 | 50.8/66.5 | 58.1 | 45.2 | **40.6 / 46.0** | 35.1 | 48.2 |
| | Longformer | 53.1/35.7 | 58.1 | 49.1 | 54.7/49.3 | 63.5 | 49.0 | 40.4/27.2 | 50.2 | 33.7 |
| | Longformer + FactDetect | **56.2/44.7** | 59.2 | 53.0 | **63.0/65.0** | 67.2 | 59.2 | 40.4/38.4 | 34.4 | 40.3 |

Table 2: Overall performance comparison between different baselines without and with (+FactDetect) multi-task learning incorporating FactDetect. SciFact-Open is trained on SciFact training dataset therefore the results of the final column are always in a zero-shot setting. The best results for each dataset are highlighted in bold and the best results within each pair (with and without FactDetect) are underlined.

that were retrieved from abstracts. *SUPPORTED* claims are human-generated using citation sentences in abstracts and *CONTRADICTED* claims are negations of original claims.

**SciFact-Open** (Wadden et al., 2022a) constitutes a test collection specifically crafted for the assessment of scientific claim verification systems. In addition to the task of verifying claims against evidence within the SciFact domain, this dataset contains evidence originating from a vast scientific corpus of 500,000 documents.

**HealthVer** (Sarrouti et al., 2021) is a compilation of COVID-19-related claims from real-world scenarios that have been subjected to fact-checking using scientific articles. Unlike most available datasets where *CONTRADICTED* claims are usually just the negation of the SUPPORTED ones, in this dataset *CONTRADICTED* claims are themselves extracted from real-world claims. The claims in this dataset are more challenging and complex compared to other datasets.

More detailed statistics of the datasets are given in Table 1.

## 4.2 Baselines

We evaluate FactDetect in two settings: 1) supervised models and 2) unsupervised models. In supervised models, we either train the state-of-the-art models on *few-shot* or *full* training settings. For *un*supervised models, we use several best-performing LLMs for a *zero-shot* and *few-shot* prompting where we compare FactDetect prompting with different prompting strategies. For few-shot, we train on $k = 45$ training samples.

### 4.2.1 Supervised Baselines

We incorporate FactDetect as an add-on for a multi-task learning-based approach on two transformer-based encoders. We train the supervised models on NVIDIA RTX8000 GPU and overall model parameters do not exceed 1B. We set the learning rate to $2e - 5$ and save the best model in 20 epochs.

**Longformer** (Beltagy et al., 2020) With the self-attention mechanism incorporated into this model and its ability to process long sequences, we use this encoder to concatenate short reasoning sentences into the claim along with additional context provided in the title (if any).

**RoBERTa-Large** (Liu et al., 2019) RoBERTa has proven to be an effective Language model to be used for training different classification tasks. We use this model as a base encoder in our experiments for this claim verification task.

### 4.2.2 Unsupervised baselines

LLMs serve as a robust source of knowledge and demonstrate impressive outcomes in various downstream tasks, especially in contexts where zero-shot and few-shot learning are employed. However, the effectiveness of these models heavily depends on the methods used to prompt their responses. Consequently, we evaluate state-of-the-art prompting methods both specific to the claim verification task and also general task approaches, and compare them to our FactDetect augmented prompting method.

**Vanilla**: We engage LLMs to assess the truthfulness of claims based on provided evidence and to offer justifications for their verdicts. This process is carried out without integrating any extra knowl-

| Datasets | | SciFact | | SciFact-Open | | HealthVer | |
| --- | --- | --- | --- | --- | --- | --- | --- |
| Metrics | | F1 | F1 /wo NEI | F1 | F1 /wo NEI | F1 | F1 /wo NEI |
| FlanT5-XXL | Vanilla | 69.0 | 83.1 | 67.4 | 88.6 | 51.3 | 61.2 |
| | CoT | 53.7 | 69.2 | 60.3 | 84.9 | 45.1 | 59.5 |
| | FactDetect | 62.5 | 79.4 | 54.0 | 81.2 | 44.6 | 63.4 |
| Llama2-13B | Vanilla | 19.8 | 41.0 | 24.0 | 39.0 | 29.0 | 59.5 |
| | CoT | 34.6 | 44.8 | 31.0 | 45.4 | 44.8 | 64.3 |
| | FactDetect | 39.0 | 57.0 | 35.2 | 38.0 | 55.4 | 63.9 |
| Vicuna-13B | Vanilla | 47.5 | 58.5 | 42.8 | 63.4 | 35.8 | 58.7 |
| | CoT | 47.3 | 66.1 | 52.2 | 73.4 | 44.7 | 54.7 |
| | FactDetect | 54.4 | 69.3 | 49.0 | 66.8 | 40.0 | 61.0 |
| GPT-3.5 | Vanilla | 64.5 | 72.5 | 63.0 | 80.4 | 50.9 | 68.0 |
| | CoT | 69.8 | 81.8 | 62.9 | 84.5 | 52.1 | 67.9 |
| | FactDetect | 70.6 | 83.0 | 55.0 | 81.4 | 53.9 | 68.6 |
| GPT-4 | Vanilla | **86.2** | **92.3** | 72.9 | 90.7 | 47.8 | 72.1 |
| | CoT | 83.2 | 88.1 | **79.0** | 96.1 | 44.1 | 70.7 |
| | FactDetect | 74.3 | 86.3 | 70.1 | **98.0** | **54.0** | **75.0** |
| ProgramFC | | – | 45.0 | – | 78.0 | – | 62.9 |

Table 3: Using the in-context learning capabilities of LLMs we evaluate the effectiveness of different prompting strategies in 5 LLMs. We report results both with *NOT ENOUGH INFO* (NEI) data samples and without them. The best-performing strategy for each LLM is underlined and overall the best results are highlighted in bold for each dataset.

edge or employing a specific strategy.

**Chain of Thought (CoT)** (Wei et al., 2022) This popular approach involves breaking down the task into a series of logical steps presented to LLMs via prompts for the given context. We use this approach by providing the claim and evidence as input and the instructions and asking it to reason via *let's think step by step*.

**ProgramFC** (Pan et al., 2023) is a newly introduced approach that converts complex claims into sub-claims which are then used to generate reasoning programs using LLMs that are executed and used for guiding the verification. We utilize the closed-book setting of this method with N=1. This approach is built for only two-label datasets where claims are either SUPPORTED or CONTRADICTED by evidence.

We compare these strategies in FlanT5-XXL (Chung et al., 2022), GPT-3.5, GPT-4, Llama2-13B (Touvron et al., 2023), and Vicuna-13B (Chiang et al., 2023). We perform experiments in few-shot promoting ($k = 5$).

### 4.3 Main Results

#### 4.3.1 Supervised setup

We first report the results of *supervised* baselines with and without FactDetect augmentation in their training process in Table 2. We experiment with few-shot and full training setups. We observe that incorporating FactDetect into the Longformer and RoBERTa-Large encoders achieves the best performance in all three datasets (in bold). Specifically in the Full training setup, the average improvement in F1 when adding FactDetect to Longformer is 5.8% for HealthVer and 15.2% for SciFact. Longformer + FactDetect in the few-shot setting also improves the F1 score for HealthVer by 21.0%. However, overall we do not see a consistent performance improvement in the few-shot setting which suggests that FactDetect benefits from a larger training dataset. As mentioned earlier, the results of SciFact-Open dataset are reported in a zero-shot setting (with model trained on SciFact training dataset), resulting in lower performance. Additionally, SciFact-Open receives less benefit from FactDetect than other datasets even in the cases where it does improve results. We suspect that this is due to the

| Strategy | Input | Generated Output |
|---|---|---|
| Vanilla | **Claim:** A study from the Journal of Hospital Infection found that wearing a face covering slashed the risk of infection by 24% for a simple cotton covering and up to 99% for a professional, medical-grade filtration mask
**Evidence:** This study 1) illustrates transmission routes of (SARS-CoV-2); 2) addresses controversies surrounding the mask … and necessity of wearing the mask would effectively interrupt the transmission of infectious diseases in both hospital settings and community settings; and 3) provides suggestion that the public should wear the mask during COVID-19 pandemic... | **Verdict**: Not Enough Info
**Ground Truth:** Supported |
| CoT | **Claim:** A study of COVID-19 patients in the Netherlands did not find the disease to be associated with cytokine storm, as previously suggested.
**Evidence:** Patients with COVID-19 who require ICU admission might have the cytokine storm.
*Let's Think Step by Step* | **Explanation:** The evidence states that patients with COVID-19 who require ICU admission might have the cytokine storm. This contradicts the claim … did not find the disease to be associated with cytokine storm.
**Verdict:** Contradicted
**Ground Truth:** Contradicted |
| FactDetect | **Claim:** As the novel coronavirus sweeps the globe, those with high blood pressure are at heightened risk for more severe complications should they contract Covid-19.
**Evidence:** In this case-control Mexican study we found that obesity represents the strongest predictor for Covid-19 followed by diabetes and hypertension in both sexes and chronic renal failure in females only
**Facts:** 1- preexisting comorbidities such as hypertension diabetes and cardiovascular disease are associated with a greater severity and higher fatality rate of covid19
2- Hypertension may be an independent risk factor for all-cause mortality in patients with covid. | **Relevant Facts:** [preexisting comorbidities such as hypertension diabetes and cardiovascular disease are associated with greater severity and higher fatality rate of covid19]
**Explanation:** These facts are important to verify the claim because they provide related supporting facts for the input claim which states that those with high blood pressure are at heightened risk for more severe complications should they contract Covid-19.
**Verdict**: Supported
**Ground Truth:** Supported |

Table 4: Example prompts used for extracting predictions from GPT-4 and their corresponding outputs.

more complex nature of the dataset, with its having unique claims that are both *SUPPORTED* and *CONTRADICTED* by different evidence sentences. It should be noted that the reported results were obtained from a single-run experiment.

Figure 3: Comparison in Macro F1 score for SciFact dataset between FactDetect-generated short facts and directly generating short facts.

### 4.3.2 Unsupervised setup

We additionally evaluate the performance of LLMs for the claim-verification task with FactDetect providing additional context for zero-shot claim verification. We used GPT-3.5 to generate programs for ProgramFC and extracted the verification with FlanT5-XL as described by Chung et al. (2022). We experimented with this model in two-label settings (*SUPPORTED* and *CONTRADICTED*) because the original model is designed in binary verification mode. For a fair comparison, we report binary classification results in all our experiments. The results are reported in Table 3. We observe that FactDetect substantially improves the performance of Llama2-13B in all three datasets compared to the best-performing baseline with an average performance gain of $14\%$ in the F1 score. Similarly FactDetect shows improvements for GPT-3.5 in SciFact and HealthVer. Interestingly, FlanT5-XXL outperforms other prompting methods in the Vanilla setting. We suspect one main reason for this result is

| Example | Direct | FactDetect |
|---|---|---|
| **Claim:** *Antiretroviral therapy reduces rates of tuberculosis across a broad range of CD4 strata.* 
 **Evidence:** *Antiretroviral therapy is strongly associated with a reduction in the incidence of tuberculosis in all baseline CD4 count categories: (1) less than 200 cells/μl (hazard ratio [HR] \dots, and (4) any CD4 count (HR 0.35, 95$\%$ CI 0.28 to 0.44). CONCLUSIONS Antiretroviral therapy is strongly associated with a reduction in the incidence of tuberculosis across all CD4 count strata.* | • antiretroviral therapy is strongly associated with a reduction in the incidence of tuberculosis in a baseline cd 4 count categories :(1)less than 200cell s/μl (hazard ratio hr 0.16 
 • 95$\%$confidence interval ci 0.07to 0.36) 
 • (2) 200 to 350cell s/μl (hr 0.34 | • antiretroviral therapy is strongly associated with a reduction in the incidence of tuberculosis in all baseline cd4 count categories |
| **Claim:** *Autologous transplantation of mesenchymal stem cells causes a higher rate of opportunistic infections than induction therapy with anti-interleukin-2 receptor antibodies.* 
 **Evidence:** *Also, during the 1-year follow-up, combined analysis of MSC-treated groups revealed a significantly decreased risk of opportunistic infections than the control group (hazard ratio, 0.42; 95$\%$ CI, 0.20-0.85, P=.02) .., and better estimated renal function at 1 year.* | • during the 1-year follow –up 
 • combined analysis of m s c - treat e d group s revealed a significantly decreased risk of opportunistic infections than the control group (hazard ratio 
 • 0.42;95%ci 0.20-0.85 
 • p =.02) 
 • conclusion among patients undergoing renal transplant | • combined analysis of MSC-treated groups revealed significantly decreased risk of opportunistic infections than the control group. |

Figure 4: Example of generated sentences using Direct and FactDetect based approach.

that we directly augment the output of short fact generation into the prompt as a list of sentences and ask the LLM to first extract the most important sentence among them for claim verification. Note that since this approach is fully unsupervised, there is a chance of hallucination which can directly impact the performance of the LLM.

### 4.3.3 Effectiveness of FactDetect

One main question to answer here is whether the three-step approach is better compared to directly generating short fact sentences from evidence. To answer this question, we experiment and compare two short fact generation approaches. The first approach is the Direct approach, where we ask Vicuna-13B to generate short sentences from evidence $e$ (we give 5 examples as few-shot prompting). The second approach is generating short facts using FactDetect. We collect the short sentences for each piece of evidence in a claim-evidence (CE) pair, for the SciFact dataset (dev set) and run experiments in the unsupervised setup. Macro F1 score comparisons between Direct and FactDetect-augmented predictions are given in Figure 3.

Overall, FactDetect-augmented prompts are performing better compared to the Direct approach. These results suggest the usefulness of the three-step approach compared to the baseline sentence generation approach. We also show the qualitative results of short facts generated from FactDetect and Direct approach in Table 4.

## 5 Limitations

One significant drawback of our method is the reliance on LLMs for producing short fact sentences throughout the entire process. Despite employing Vicuna-13B, which is among the top open-source LLMs available, the factual accuracy and overall quality of the generated content are bounded by the capabilities of this particular model. Consequently, any inaccuracies or hallucinations from the model could impact the effectiveness of the end-to-end claim verification system. Overcoming this obstacle is a crucial direction for future research.

## 6 Conclusion and Future Work

In this work, we propose FactDetect, an effective short fact generation technique, through a three-step approach for comprehensive and high-quality condensed small sentences derived from evidence. With the relevance-based weak-labeling approach this framework can be added to any state-of-the-art claim verification model as a multi-task learning method to boost reasoning. The effectiveness of FactDetect has been demonstrated in both fine-tuned and prompt-based models, as indicated by our results. Our results suggest that FactDetect incorporated claim-verification task in a supervised setting consistently improves performance on average by $10.5\%$ in full training setup whereas it appears to suffer in few- or zero-shot settings. We also showed that when augmented with LLMs, we see limited capability and one explanation for this result is the quality of the generated sentences.

## 7 Ethics Statement

**Biases.** We acknowledge the possibility of bias in generated outputs from the trained LLM. However, this is beyond our control.

**Potential Risks.** Our approach can be used for automated fact-checking. However, they could also be used by malicious actors to manipulate and attack fact-checking models. A possible future direction is to detect such malicious actions before deployment.

**Environmental Impact.** Training and using LLMs involves considerable computational resources, including the necessity for GPUs or TPUs during training or inference which can have an impact on the environment. However, we trained our datasets on relatively smaller language models with less than 1B parameters and we used LLMs for inference only which has negligible negative effect on the environment.

## References

Iz Beltagy, Matthew E. Peters, and Arman Cohan. 2020. Longformer: The long-document transformer. *arXiv:2004.05150*.

Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. 2023. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality.

Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. 2022. Scaling instruction-finetuned language models. *arXiv preprint arXiv:2210.11416*.

Limeng Cui, Kai Shu, Suhang Wang, Dongwon Lee, and Huan Liu. 2019. Defend: A system for explainable fake news detection. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, CIKM '19, page 2961–2964, New York, NY, USA. Association for Computing Machinery.

Shih-Chieh Dai, Yi-Li Hsu, Aiping Xiong, and Lun-Wei Ku. 2022. Ask to know more: Generating counterfactual explanations for fake claims. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 2800–2810.

Thomas Diggelmann, Jordan Boyd-Graber, Jannis Bulian, Massimiliano Ciaramita, and Markus Leippold. 2020. Climate-fever: A dataset for verification of real-world climate claims.

Zhijiang Guo, Michael Schlichtkrull, and Andreas Vlachos. 2022. A survey on automated fact-checking. *Transactions of the Association for Computational Linguistics*, 10:178–206.

Shailza Jolly, Pepa Atanasova, and Isabelle Augenstein. 2022. Generating fluent fact checking explanations with unsupervised post-editing. *Information*, 13(10).

Neema Kotonya and Francesca Toni. 2020. Explainable automated fact-checking for public health claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7740–7754, Online. Association for Computational Linguistics.

Minwoo Lee, Seungpil Won, Juae Kim, Hwanhee Lee, Cheoneum Park, and Kyomin Jung. 2021. Crossaug: A contrastive data augmentation method for debiasing fact verification models. In *Proceedings of the 30th ACM International Conference on Information Knowledge Management*, CIKM '21. Association for Computing Machinery.

Xiangci Li, Gully A Burns, and Nanyun Peng. 2021. A paragraph-level multi-task learning model for scientific fact-verification. In *SDU@ AAAI*.

Wenhan Xiong Min-Yen Kan William Yang Wang Liangming Pan, Wenhu Chen. 2021. Zero-shot fact verification by claim generation. In *The Joint Conference of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP 2021)*, Online.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Liangming Pan, Xiaobao Wu, Xinyuan Lu, Anh Tuan Luu, William Yang Wang, Min-Yen Kan, and Preslav Nakov. 2023. Fact-checking complex claims with program-guided reasoning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6981–7004, Toronto, Canada. Association for Computational Linguistics.

Kashyap Popat, Subhabrata Mukherjee, Jannik Strötgen, and Gerhard Weikum. 2017. Where the truth lies: Explaining the credibility of emerging claims on the web and social media. In *Proceedings of the 26th International Conference on World Wide Web Companion*, pages 1003–1012.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.

Arkadiy Saakyan, Tuhin Chakrabarty, and Smaranda Muresan. 2021. Covid-fact: Fact extraction and verification of real-world claims on covid-19 pandemic. *arXiv preprint arXiv:2106.03794*.

Mourad Sarrouti, Asma Ben Abacha, Yassine M'rabet, and Dina Demner-Fushman. 2021. Evidence-based fact-checking of health-related claims. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 3499–3512.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. 2018. FEVER: a large-scale dataset for fact extraction and VERification. In *NAACL-HLT*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. Fact or fiction: Verifying scientific claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7534–7550, Online. Association for Computational Linguistics.

David Wadden, Kyle Lo, Bailey Kuehl, Arman Cohan, Iz Beltagy, Lucy Lu Wang, and Hannaneh Hajishirzi. 2022a. SciFact-open: Towards open-domain scientific claim verification. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 4719–4734, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

David Wadden, Kyle Lo, Lucy Lu Wang, Arman Cohan, Iz Beltagy, and Hannaneh Hajishirzi. 2022b. MultiVerS: Improving scientific claim verification with weak supervision and full-document context. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 61–76, Seattle, United States. Association for Computational Linguistics.

Haoran Wang and Kai Shu. 2023. Explainable claim verification via knowledge-grounded reasoning with large language models. *arXiv preprint arXiv:2310.05253*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

Fan Yang, Shiva K. Pentyala, Sina Mohseni, Mengnan Du, Hao Yuan, Rhema Linder, Eric D. Ragan, Shuiwang Ji, and Xia (Ben) Hu. 2019. Xfake: Explainable fake news detector with visualizations. In *The World Wide Web Conference*, WWW '19, page 3600–3604, New York, NY, USA. Association for Computing Machinery.

Zhiwei Zhang, Jiyi Li, Fumiyo Fukumoto, and Yanming Ye. 2021. Abstract, rationale, stance: a joint model for scientific claim verification. *arXiv preprint arXiv:2110.15116*.

## A  Example Appendix

This is a section in the appendix.