Look What I Made It Do - Modeling Nonverbal Agent Behavior Manually From Literature: The ModelIT Method

ABSTRACT

Nonverbal behavior of socially interactive agents (SIAs) is often automatically generated and identical across all users. This approach, though economic, might have counterproductive effects when designing applications for diverse and vulnerable populations. Also, it might negatively impact research validity and diminish the effectiveness of SIA-based interventions. This paper presents arguments for and proposes a method to model nonverbal behavior in SIAs. The ModelIT method enables researchers to ground the modelling of nonverbal behaviors in psychological theories. It aims at establishing a standardized and replicable method that promotes open science practices and facilitates the creation of tailored SIAs. It is a step towards barrier-free and accessible SIA applications across diverse populations. The necessity, guidelines, and limitations of the ModelIT method are thoroughly addressed.

CCS CONCEPTS

• **Human-centered computing → HCI design and evaluation methods**; **Interaction design process and methods**; **Accessibility design and evaluation methods**.

KEYWORDS

Socially Interactive Agents, Nonverbal Behavior, Method, Replicability

ACM Reference Format:
. 2023. Look What I Made It Do - Modeling Nonverbal Agent Behavior Manually From Literature: The ModelIT Method. In *Proceedings of International Conference on Multimodal Interaction (ICMI '23)*. ACM, New York, NY, USA, 5 pages. https://doi.org/XXXXXXX.XXXXXXX

1 INTRODUCTION

Nonverbal behavior plays a fundamental role in human interaction, enriching and underlining communication [12]. While humans primarily engage with other humans, in recent years these interactions include objects such as computers. In the context of human-computer interaction (HCI), the study of nonverbal behavior has garnered increased attention, particularly when it involves socially interactive agents (SIAs) that possess an embodied and humanoid presence. While for specialized interpersonal tasks, humans primarily engage with other humans, SIAs are becoming more and more capable of entering these spaces and performing these tasks. In a world with a rising shortage of specialists, embodied SIAs are the

future of health-care [16, 29], teaching [7], coaching [36, 37], and many more previously human-dominated fields targeting divers user groups with diverse needs. Vulnerable populations (e.g., people in in-patient facilities) make up a huge target audience for SIA applications, such as therapy-accompanying SIAs that helps users identify and evaluate automatic thoughts [39].

Though modelling of nonverbal SIA behavior has been an important research focus for years [32], there exists no standardized approach, how to model the nonverbal SIA behavior for users with diverse needs (e.g., diverse and vulnerable populations). These needs have to be identified, extracted, carefully operationalized, implemented, and validated to create SIAs that can now successfully support their intended population. Therefore, this paper aims to establish and advocate for a standardized method, the ModelIT method, for extracting nonverbal cues from literature and applying them to SIA animation. The goal is to create specialized and optimized SIAs that can confidently serve their intended purpose. It is a step towards barrier-free and equality-focused applications. The proposed ModelIT method seeks to minimize subjective biases, ensure maximum objectivity, and increase replicability, while considering current limitations of available technical tools.

2 BACKGROUND

2.1 Nonverbal Behavior in Human-Human-Interaction

Nonverbal behavior, including posture, movements, and facial expressions [25], serves several important functions in human-human interaction [26]. It is a fundamental part of building rapport [40], eliciting trust [19], and establishing how a person is perceived [11]. Nonverbal behavior has been studied as a whole for a long time, but in recent years research has also focused on the many existing interpersonal differences [6, 8, 13] identifying specific needs of different populations.

2.1.1 Clinical and neurodiverse populations. The display as well as the interpretation of nonverbal cues differ greatly when focusing on clinical or neurodiverse populations. Nonverbal behaviors that are, in general, assessed as rather positive, can be perceived as negative. For example, eye contact is usually associated with social presence [10] and is therefore used to build trust and signify active listening to the interaction partner [14]. However, autistic people can find direct eye contact uncomfortable [34]. Consequently, nonverbal behavior should be actively adapted when interacting with an autistic person with that specific need to make them feel more comfortable.

2.1.2 Culturally diverse populations. Nonverbal behavior patterns and their communicated meaning also vary significantly between different cultures [22]. This should be taken into account during interactions with individuals from different cultural backgrounds, as failure to do so can lead to miscommunication. In some Asian countries like China, shaking one's head is a nonverbal cue for "yes". It is also seen as rude to contradict another person [23],

whereas in many central European countries, a head-shake means "no" and contradicting is a normal part of an interaction. These two differences by themselves and especially together can easily generate conflict if one of the interaction partners is not aware.

2.2 Nonverbal Behavior in Human-SIA-Interaction

Socially Interactive Agents (SIAs) are virtually or physically embodied agents. They are capable of socially intelligent autonomous communication with human users and other agents. This is executed with a wide range of multi-modal behaviors [20]. As humans tend to interact with machines similarly as with humans, the principles of human-human-interaction can be applied to human-SIA interaction [33]. Users expect their SIA partner to act and react in certain ways and attribute human characteristics accordingly [24].

The expression of nonverbal behavior in SIAs influences how they are perceived by a user [35]. The modelling of nonverbal SIA behavior has been an important research focus for years [32]. It stays relevant to this day as human behavior is complex and the technology becomes more sophisticated. The standard procedures of modelling nonverbal SIA behavior should therefore also be periodically reconsidered.

Automatic generation of nonverbal behavior has been commonly used in the field of SIAs [35]. Many SIA systems utilize pre-programmed algorithms to automatically generate gestures, facial expressions, body movements, and other nonverbal cues. While this approach guarantees a consistent user-experience, it does not really address the many interpersonal differences in human interaction. Those differences become more relevant the more SIA applications exist for a broader spectrum of people.

2.2.1 Clinical and neurodiverse populations. Eye contact is generally associated with social presence [10]. Therefore SIAs are often modelled to seek eye contact with their user to build trust. When autistic people interact with a SIA designed that way, this effect could be completely lost. The effectiveness of the application can be compromised. This makes an explicitly different modeling of eye gaze essential, especially for the various applications of SIAs designed for autistic people [30]. This is only one use-case where standardized nonverbal behavior can be counterproductive and possibly discriminatory. It has the potential to compromise the validity of research and impact real-life applications.

2.2.2 Culturally diverse populations. Culturally varying nonverbal behavior patterns must be considered when developing SIA applications that are used interculturally. Consequently a SIA-application designed with a North American user-base in mind, might completely lose its functionality when implemented for a Syrian refugee program.

2.3 Attachment Style

Attachment styles were first observed in children [1] and characterized as collections of internal working models influencing new relationships and one's self-perception [21, 38]. Adult attachment [17] introduced a mapping of those existing attachment style categories onto adults. There are several different systems of categorization,

that have been used. There is often a general distinction between secure and insecure attachment [1]. The latter can be subdivided into different types of insecure attachment. A prominent categorization of insecure attachment is: dismissing, preoccupied, and unresolved [9]. There are also continual dimensions to measure attachment style [5]. Those dimensions are attachment anxiety and attachment avoidance and a person can have high or low scores on either. Based in these scores, four categories can be discerned: secure (low anxiety, low avoidance), preoccupied (high anxiety, low avoidance), dismissing (low anxiety, high avoidance), and fearful (high anxiety, high avoidance). The attachment style of a person influences their nonverbal behavior in attachment related situations [3]. Securely attached people generate intimacy easily [2]. Individuals with high attachment anxiety use anger in attachment related situations [27] while people with high attachment avoidance employ distancing strategies [28].

3 THE MODELIT METHOD

The ModelIT method is a method for a standardized modeling of nonverbal behavior in SIAs. It can be applied to a specific use-case that defines the characteristics of the SIA and the possible needs of the specific user population. It consists of five steps that lead from an abstract to an applied level: (1) literature review; (2) nonverbal behavior extraction; (3) nonverbal cue operationalization; (4) nonverbal cue implementation; and (5) validation.

These five steps are a necessary concretisation process because nonverbal cues are frequently not defined in an applicable way in existing literature. Especially when designing a SIA for a specific population, most nonverbal behavior is extremely complex and only vaguely described over a vast quantity of research papers. For example, people with high attachment anxiety regulate distress by seeking closeness [2]. This cannot be directly implemented into an animation but has to undergo a concretisation process to be actually usable.

In this work, the baseline behavior of the SIA has been manually authored. However, given the possibility to express such rules with a formalism that can be programmatically interpreted, it is straightforward to foresee an automatic behaviour modeling by employing a rule-based inference system [31].

3.1 Literature Review

This step involves conducting an in-depth review of existing literature on nonverbal behavior, social interaction, and relevant fields of the examined use-case. The goal is to gather a comprehensive understanding of the different types of nonverbal behaviors to extract the nonverbal behavior from. There are several well-documented ways of finding papers for literature reviews and meta-analyses [18]. The scientific criteria utilised in these strategies should also be applied here. They should be well documented for future replicability (e.g., which websites were used, which search words, date of search). The result of the literature review will provide the foundational knowledge required for the subsequent steps.

3.2 Nonverbal Behavior Extraction

After collecting all relevant papers, the specific nonverbal behavior has to be identified and extracted. This requires taking relevant

quotes about, e.g., facial expressions, body movements, gestures, and eye contact directly from papers to preserve nuanced details as accurately as possible. Those are then categorized and described in a spreadsheet with corresponding citations in a structured and standardized manner. This constitutes an abstraction process, as it consists of abstract concepts, which have to be concretised before an implementation into a SIA is possible.

3.3 Nonverbal Cue Operationalization

After extracting nonverbal behaviors, the next step is to operationalize them into actionable nonverbal cues for the SIA. The challenge hereby is to accurately depict the collected research findings. This includes taking the research quotes, transforming abstract behavior into concrete movements and add them to the spreadsheet, which constitutes another abstraction. Afterwards, the spreadsheet contains the abstract nonverbal behavior and the respective concrete movements in a transparent and well structured way.

3.4 Nonverbal Cue Implementation

The list of operationalized nonverbal cues can now be implemented for the specific used animation system. The cues should be examined one by one and individually translated into available animations. This can be challenging and tedious because many existing SIA animation systems only have predefined fixed animations. They need to be individually evaluated whether they actually convey the intended meaning. For example, an animation called "puzzled" is not necessarily categorized by users as puzzled. The end result should be a spreadsheet with directly usable animations and rules as to how to use them. The actual animation process can now easily be done while following the predefined rules.

3.5 Validation

The last step consists of validating the resulting SIA behavior. This step is crucial to actually test the intended effect of customized SIAs. Two separate types of validation should be considered: validation of the accuracy of the nonverbal behavior (experts) and validation of the function of the nonverbal behavior (target population).

4 APPLICATION OF THE MODELIT METHOD

The ModelIT method was applied to the modeling of nonverbal behavior of SIAs that represent people with different attachment styles. The following section does not show the documentation process exhaustively, but it exemplifies the ModelIT method step by step and highlights its importance.

4.1 Literature Review

The goal of the literature review was finding nonverbal behavior of different attachment styles. The first step was implementing a search strategy. Search terms were for example: "attachment style nonverbal", "attachment presentation nonverbal", "attachment style behavior", "adult attachment behavior",... The used sites were "Web of Science" and "GoogleScholar". As one important filter, it was decided to only use nonverbal behavior of attachment style in adults and not children. The chosen categorization system for the SIA was: secure, dismissing, and preoccupied. Importantly, the approach was to utilize literature referring to every attachment style classification

Figure 1: ModelIT method

system. This strategy was adopted to extract as much information as possible since this particular field of study is not very big. The classification systems are comparable and therefore convertible into each other. The literature review only consisted of collecting usable papers and the different attachment style classification systems were integrated into one coherent taxonomy in a later step. However, it is crucial to note that in different scenarios, such comparability may not hold, necessitating comprehensive documentation of inclusion/exclusion criteria.

4.2 Nonverbal Behavior Extraction

The result of the literature review was a list of papers with information about nonverbal behavior for the dimensions attachment anxiety (high) and attachment avoidance (high/low) as well as the categories secure attachment, insecure attachment generally, preoccupied attachment, and dismissing attachment. Those categories were laid out in a spreadsheet and the nonverbal behavior was sorted into this framework quoting directly from the literature.

4.3 Nonverbal Cue Operationalization

The step from abstract nonverbal behavior to concrete movements is very complex due to the nature of the preexisting literature. Nonverbal behavior is often not precisely defined and categorized into replicable movements. They mostly describe nonverbal concepts, that are very ambivalent and need to be operationalized and formalized. A dismissing attachment style for example is associated with less movement in general and less movement complexity [3]. On an abstract level this is a very conceivable concept. But applying it to modelling the behavior of a SIA quickly shows its complexity. The first step is defining a standard frequency this behavior varies from. In this instance, the standard is the secure attachment style. Then you have to decide which movements will be shown less: full body movements, hand movements, head movements, or every kind of movement? Movement complexity is also ambivalent and could apply to many facets and types of movements. Therefore its

Table 1: Example: ModelIt spreadsheet for high Attachment Avoidance

Reference	Extraction	Operationalization	Application
Mikulincer & Shaver (2005) [28]	"blunted affect"	smiles without teeth	emot.smile (not emot.happy)
		neutral facial expression as baseline	emot.bored as baseline
		low frequency of facial expression changes	emot.bored > 80 percent of the time
		only small movements	sad03 (sigh, tiny head-shake, no full-body movement)
Fraley & Shaver (1998) [15]	"frequent avoidant behaviors"	turning away	lookto.right80.01
		looking away from the user	lookat.07.01
		keeping distance hand movement	number.handl.5
		avoiding eye contact	eye contact < 50 percent of the time

modelling has to be standardized. In our case, we chose the standard movement sequences for the secure attachment style and then searched for similar movements with less intensity (e.g., "shrugging motion" as shoulder movement with simultaneous arm movement vs. just shoulder movement). Quantifying "intensity" while working with fixed animations is difficult, and should rely on the consensus of several people within and outside of the direct.

People with generally insecure attachment tend to show discrepancies between verbal content and nonverbal behavior [3]. Therefore there need to be content markers in the spoken text which then have to be contradicted in the nonverbal behavior. This becomes especially complicated when considering the intercultural differences. In a German context a discrepancy is created when the SIA says "yes" while shaking their head. But this would vanish for a Bulgarian SIA, since shaking one's head symbolizes "yes".

The nonverbal markers of attachment style only present themselves in attachment related situations [3]. This needs to be addressed by defining those attachment related situations and labelling them in the action/interaction. This has to done based on attachment style research. The SIA should only display the defined behavior in those labelled sections of the action/interaction.

4.4 Nonverbal Cue Implementation

Every operationalized nonverbal cue on the spreadsheet was matched with available animations in Vuppetmaster[1] – a tool for modelling SIA behavior. This resulted in a detailed and comprehensible spreadsheet that was used to animate videos of SIAs displaying nonverbal behavior of secure, dismissing, or preoccupied attachment.

4.5 Validation

Firstly it must be validated that e.g., dismissingly attached people actually behave in this way. This should be done by experts like psychotherapists and associates of people with dismissing attachment. Secondly, the likeability and trustworthiness of the agents must be validated and rated by people with dismissing attachment.

5 DISCUSSION

In this paper, the five-steps ModelIT method is proposed to model nonverbal behavior in SIAs: (1) literature review; (2) nonverbal behavior extraction; (3) nonverbal cue operationalization; (4) nonverbal cue implementation; and (5) validation. It gives researchers a strong theoretical foundation and transparent guide to ground their modeling of nonverbal behavior in psychological theories.

5.1 Limitations and Future Work

Often, there is not much information about nonverbal behavior of specific populations in the scientific literature. And, even if there is information about it, it may be vague and/or ambivalent. Therefore, they have to be carefully examined and evaluated when operationalizing them into actionable cues. This should be done as transparently as possible, documenting each consideration and whether it is research-based or consensus-based. A possible other way to gather information about nonverbal behaviors of specific populations is to interview subject matter experts that interact frequently with the specific population. These can be, e.g., therapists working with autistic people. Based on the interview data, the nonverbal cues can be operationalized, applied in SIAs and validated.

Despite best efforts to produce a standardized procedure, it can still (though less) be impacted by human biases. Especially when the team of people modelling the SIA is homogeneous (e.g., concerning cultural background, gender identity,...). This must be counteracted with the proposed thorough documentation making human error at least traceable and therefore (hopefully) solvable. Every modelling of internal states such as feelings through facial expressions is inherently problematic. Feelings are not directly and distinctly identifiable through facial expressions [4], yet they are necessary heuristics for modelling SIAs.

This approach to modelling nonverbal behavior is more time-consuming than automatic generation. But output of the ModelIT method can be used to employ a rule-based inference system for automatic behavior modeling [31]. Additionally, the benefit especially while working with vulnerable populations justifies the additional cost and time investment. Likewise, when working towards a less biased world by considering cultural differences.

6 CONCLUSION

In this day and age, there is a growing need for careful nonverbal modelling to further a barrier-free and intercultural world. Interpersonal differences need to be considered in order to minimize biases and transparent documentation is an essential step towards open science and accessible SIA applications. Therefore, this paper introduced the ModelIT method for modelling appropriate nonverbal behavior in SIAs, enhancing their ability to engage with specific user populations that have been overlooked for too long.

ACKNOWLEDGMENTS

This work is funded by . Thanks to ████████ for making the Taylor Swift joke that turned into the title of this paper.

---

[1] https://vuppetmaster.de/

REFERENCES

[1] Mary D Salter Ainsworth, Mary Catherine Blehar, Everett Waters, and Sally Nichols Wall. 1978. *Patterns of attachment: A psychological study of the strange situation.* Lawrence Erlbaum.

[2] Ravin Alaei, Germain Lévêque, Geoff MacDonald, and Nicholas O Rule. 2020. Accuracy and bias in first impressions of attachment style from faces. *Journal of Personality* 88, 5 (2020), 940–949.

[3] Uwe Altmann, Catharina Friemann, Theresa S Frank, Mareike C Sittler, Désirée Schoenherr, Sashi Singh, Susan Schurig, Bernhard Strauss, and Katja Petrowski. 2021. Movement and emotional facial expressions during the adult attachment interview: Interaction effects of attachment and anxiety disorder. *Psychopathology* 54, 1 (2021), 47–58.

[4] Lisa Feldman Barrett, Ralph Adolphs, Stacy Marsella, Aleix M Martinez, and Seth D Pollak. 2019. Emotional expressions reconsidered: Challenges to inferring emotion from human facial movements. *Psychological science in the public interest* 20, 1 (2019), 1–68.

[5] Kim Bartholomew and Leonard M Horowitz. 1991. Attachment styles among young adults: a test of a four-category model. *Journal of personality and social psychology* 61, 2 (1991), 226.

[6] Diane S Berry and Jane Sherman Hansen. 2000. Personality, nonverbal behavior, and interaction quality in female dyads. *Personality and Social Psychology Bulletin* 26, 3 (2000), 278–292.

[7] Chirag Bhuvaneshwara, Manuel Anglet, Bernhard Hilper, Lara Chehayeb, Ann-Kristin Meyer, Daksitha Withanage Don, Dimitra Tsovaltzi, Patrick Gebhard, Antje Biermann, Sinah Auchtor, Nils Lauinger, Andreas Kaiser, Fabian Kersting, and Gregor Mehlmann. 2023. MITHOS-Mixed Reality Interactive Teacher Training System for Conflict Situations at School. In *Proceedings of the International Society of the Learning Sciences*.

[8] Carola Bloch, Ralf Tepest, Mathis Jording, Kai Vogeley, and Christine M Falter-Wagner. 2022. Intrapersonal synchrony analysis reveals a weaker temporal coherence between gaze and gestures in adults with autism spectrum disorder. *Scientific Reports* 12, 1 (2022), 20417.

[9] J Bolwby. 1973. Attachment and Loss. Vol. 2: Separation, anxiety and anger.

[10] Yevgenia Bondareva, Lydia Meesters, and Don Bouwhuis. 2006. Eye contact as a determinant of social presence in video communication. In *Proceedings of the 20th International Symposium on Human Factors in Telecommunication.*

[11] Bella M. Depaulo and Howard S. Friedman. 1998. Nonverbal communication. In *The Handbook of Social Psychology*, Daniel T. Gilbert, Susan T. Fiske, and Gardner Lindzey (Eds.). McGraw-Hill, 3–40.

[12] Paul Ekman and Wallace V Friesen. 1969. The repertoire of nonverbal behavior: Categories, origins, usage, and coding. *semiotica* 1, 1 (1969), 49–98.

[13] Hans-Ulrich Fisch, Siegfried Frey, and Hans-Peter Hirsbrunner. 1983. Analyzing nonverbal behavior in depression. *Journal of abnormal psychology* 92, 3 (1983), 307.

[14] Mălureanu Flavia and Luiza Enachi-Vasluianu. 2016. The importance of elements of active listening in didactic communication: a student's perspective. In *CBU International Conference Proceedings*, Vol. 4. 332–335.

[15] R Chris Fraley and Phillip R Shaver. 1998. Airport separations: A naturalistic study of adult attachment dynamics in separating couples. *Journal of personality and Social Psychology* 75, 5 (1998), 1198.

[16] Patrick Gebhard, Tanja Schneeberger, Michael Dietz, Elisabeth André, and Nida ul Habib Bajwa. 2019. Designing a Mobile Social and Vocational Reintegration Assistant for Burn-out Outpatient Treatment. In *Proceedings of the 19th ACM International Conference on Intelligent Virtual Agents*. Association for Computing Machinery, 13–15. https://doi.org/10.1145/3308532.3329460

[17] Cindy Hazan and Phillip R. Shaver. 1987. Romantic love conceptualized as an attachment process. *Journal of personality and social psychology* 52, 3 (1987), 511–24.

[18] Sascha Kraus, Matthias Breier, Weng Marc Lim, Marina Dabić, Satish Kumar, Dominik Kanbach, Debmalya Mukherjee, Vincenzo Corvello, Juan Piñeiro-Chousa, Eric Liguori, et al. 2022. Literature reviews as independent studies: guidelines for academic practice. *Review of Managerial Science* 16, 8 (2022), 2577–2595.

[19] Gale Lucas, Giota Stratou, Shari Lieblich, and Jonathan Gratch. 2016. Trust me: multimodal signals of trustworthiness. In *Proceedings of the 18th ACM international conference on multimodal interaction*. 5–12.

[20] Birgit Lugrin. 2021. Introduction to Socially Interactive Agents. In *The Handbook on Socially Interactive Agents: 20 Years of Research on Embodied Conversational Agents, Intelligent Virtual Agents, and Social Robotics. Volume 1: Methods, Behavior, Cognition*, Birgit Lugrin, Catherine Pelachaud, and David Traum (Eds.). Association for Computing Machinery, 77–104. https://doi.org/10.1145/3477322.3477326

[21] Mary Main, Nancy Kaplan, and Jude Cassidy. 1985. Security in infancy, childhood, and adulthood: A move to the level of representation. *Monographs of The Society for Research in Child Development* 50 (1985), 66–104.

[22] David Matsumoto and Hyisung C Hwang. 2016. The cultural bases of nonverbal communication. In *APA handbook of nonverbal communication*. American Psychological Association, 77–101.

[23] David Matsumoto and Hyi Sung Hwang. 2013. Cultural influences on nonverbal behavior. *Nonverbal communication: Science and application* (2013), 97–120.

[24] Margaret McRorie, Ian Sneddon, Gary McKeown, Elisabetta Bevacqua, Etienne De Sevin, and Catherine Pelachaud. 2011. Evaluation of four designed virtual agent personalities. *IEEE Transactions on Affective Computing* 3, 3 (2011), 311–322.

[25] Albert Mehrabian. 1968. Some referents and measures of nonverbal behavior. *Behavior Research Methods & Instrumentation* 1, 6 (1968), 203–207.

[26] Albert Mehrabian. 2017. *Nonverbal communication.* Routledge.

[27] Mario Mikulincer. 1998. Attachment working models and the sense of trust: An exploration of interaction goals and affect regulation. *Journal of personality and social psychology* 74, 5 (1998), 1209.

[28] Mario Mikulincer and Phillip R Shaver. 2005. Attachment theory and emotions in close relationships: Exploring the attachment-related dynamics of emotional reactions to relational events. *Personal relationships* 12, 2 (2005), 149–168.

[29] Madison Milne-Ives, Caroline de Cock, Ernest Lim, Melissa Harper Shehadeh, Nick de Pennington, Guy Mole, Eduardo Normando, and Edward Meinert. 2020. The effectiveness of artificial intelligence conversational agents in health care: systematic review. *Journal of medical Internet research* 22, 10 (2020), e20346.

[30] Jacqueline Nadel, Ouriel Grynszpan, and Jean-Claude Martin. 2022. Autism and socially interactive agents. In *The Handbook on Socially Interactive Agents: 20 years of Research on Embodied Conversational Agents, Intelligent Virtual Agents, and Social Robotics Volume 2: Interactivity, Platforms, Application*, Birgit Lugrin, Catherine Pelachaud, and David Traum (Eds.). Association for Computing Machinery, 437–462.

[31] Ken Pedersen. 1989. *Expert Systems Programming: Practical Techniques for Rule-Based Systems.* John Wiley & Sons, Inc., USA.

[32] Catherine Pelachaud, Carlos Busso, and Dirk Heylen. 2021. Multimodal behavior modeling for socially interactive agents. In *The Handbook on Socially Interactive Agents: 20 Years of Research on Embodied Conversational Agents, Intelligent Virtual Agents, and Social Robotics Volume 1: Methods, Behavior, Cognition.* 259–310.

[33] Byron Reeves and Clifford Nass. 1996. *The Media Equation : How People Treat Computers, Television, and New Media Like Real People and Places.* Cambridge University Press.

[34] M Roy and D Wolfgang. 2015. Eye contact in adult patients with Asperger syndrome. *Fortschritte der Neurologie-psychiatrie* 83, 5 (2015), 269–275.

[35] Carolyn Saund and Stacy Marsella. 2021. Gesture generation. In *The Handbook on Socially Interactive Agents: 20 years of Research on Embodied Conversational Agents, Intelligent Virtual Agents, and Social Robotics Volume 1: Methods, Behavior, Cognition.* 213–258.

[36] Tanja Schneeberger, Patrick Gebhard, Tobias Baur, and Elisabeth André. 2019. PARLEY: a transparent virtual social agent training interface. In *Proceedings of the 24th International Conference on Intelligent User Interfaces: Companion.* 35–36.

[37] Tanja Schneeberger, Naomi Sauerwein, Manuel S. Anglet, and Patrick Gebhard. 2021. Stress Management Training Using Biofeedback Guided by Social Agents. In *Proceedings of the 26th International Conference on Intelligent User Interfaces.* Association for Computing Machinery, 564–574. https://doi.org/10.1145/3397481.3450683 *Honorable Mention*.

[38] Felix D Schönbrodt and Jens B Asendorpf. 2012. Attachment dynamics in a virtual world. *Journal of Personality* 80, 2 (2012), 429–463.

[39] Kazuhiro Shidara, Hiroki Tanaka, Hiroyoshi Adachi, Daisuke Kanayama, Yukako Sakagami, Takashi Kudo, and Satoshi Nakamura. 2022. Automatic thoughts and facial expressions in cognitive restructuring with virtual agents. *Frontiers in Computer Science* 4 (2022), 762424.

[40] Linda Tickle-Degnen and Robert Rosenthal. 1990. The nature of rapport and its nonverbal correlates. *Psychological inquiry* 1, 4 (1990), 285–293.