Relational Causal Models with Cycles: Representation and Reasoning

Abstract

Causal reasoning in relational domains is fundamental to studying real-world social phenomena in which individual units can influence each other's traits and behavior. Dynamics between interconnected units can be represented as an instantiation of a relational causal model; however, causal reasoning over such instantiation requires additional templating assumptions that capture feedback loops of influence. Previous research has developed lifted representations to address the relational nature of such dynamics but has strictly required that the representation has no cycles. To facilitate cycles in relational representation and learning, we introduce relational σ-separation, a new criterion for understanding relational systems with feedback loops. We also introduce a new lifted representation, *σ-abstract ground graph* which helps with abstracting statistical independence relations in all possible instantiations of the cyclic relational model. We show the necessary and sufficient conditions for the completeness of σ-AGG and that relational σ-separation is sound and complete in the presence of one or more cycles with arbitrary length. To the best of our knowledge, this is the first work on representation of and reasoning with relational causal models with cycles.

Keywords: Representation, Cycles, Relational Causal Model

1. Introduction

Causal reasoning over relational systems is central to understanding real-world social phenomena, such as social influence and information diffusion. For example, a well-known study by Christakis and Fowler (2007) investigates whether obesity is contagious in a population where each person's eating habits can affect their friends and family and vice-versa. Similarly, several real-world problems in epidemiology and computational social science encounter such mutual influence and interaction among human subjects. For example, effect of vaccination in mother and child (Shpitser, 2015; VanderWeele et al., 2012), time spent online by users in social network (Sherman and Shpitser, 2018), influence of diet in family members (Ogburn et al., 2014), justices influencing each other in supreme court decisions (Ogburn et al., 2020) are all examples of mutual influence. Studying such phenomena requires causal reasoning over complex interactions between interconnected entities. However, causal questions of mutual influence can be hard to answer due to the lack of appropriate causal representations and reasoning mechanisms that can capture the cycles and feedback loops introduced by mutual influence.

The development of *relational causal models*, which generalize over causal models, was an important step towards capturing interactions between non-IID instances (Maier et al., 2013b,a; Lee and Honavar, 2015; Bhattacharya et al., 2020). Relational models involve multiple types of interacting entities with probabilistic dependencies among their attributes. Maier et al. (2013b) developed a lifted causal representation named *abstract ground graph (AGG)* that abstracts over all instantiations of a relational model. AGG enables reasoning about causal queries in relational causal models

Figure 1: Example of relational model with feedback loop. Rectangle, rhombus and oval shapes represent entity, relationship and attributes respectively. Arrows refer to relational dependence.

and relational causal discovery. However, existing relational causal models assume acyclicity and cannot capture feedback loops. Figure 1 shows an example of a relational model where employees develop products and product quality depends on the performance levels of employees. The fact that product quality can also affect employee performance introduces a feedback loop in the graphical representation that cannot be reasoned about with existing representations.

In this work, we define a new abstract representation, σ-*abstract ground graph* (σ-AGG) which generalizes over cyclic relational models. In order to reason about relational queries in σ-AGG, we introduce *relational σ-separation* and provide proofs for its soundness and completeness for all instantiations of a relational model. The implications of this new representation are twofold. First, it can lead the way for reasoning about causal effects like contagion represented in relational models. Second, the abstract representation and its identified properties will lay a foundation for causal structure learning from relational models with cycles. We show the necessary and sufficient conditions for the completeness of σ-AGG by first resolving an open problem on the completeness of AGG. Finally, we discuss the Markov condition of relational σ-separation and its implications.

2. Related Work

Maier et al. (2013b) proposed a sound and complete abstract representation for relational data with multiple entities and relationships. They defined an abstract representation of relational dependence called abstract ground graph based on the assumption that the underlying relational model is acyclic. Moreover, they introduced relational d-separation, a new criterion to reason about statistical independence in all the instantiations of a relational model. They proved the soundness and completeness of relational d-separation. The AGG and associated relational d-separation criterion together allows a formal basis of causal analysis in relational systems. The same authors proposed a constraint-based causal structural learning algorithm called RCD (Maier et al., 2013a) which is first of its kind.

Lee and Honavar (2015) presented a critical view on the generalizability of AGG where they constructed a counterexample which shows how AGG can fail to abstract all d-separation relationships in the ground graphs. They also identified a shortcoming of the necessary conditions for considering a intersection variable and provided a revised set of conditions. In a different work, Lee and Honavar (2020) proposed a new abstract representation of relational causal models called the unrolled graph which guarantees a weaker sense of completeness. However, neither of the two groups of work moved away from the assumption of acyclicity. As a result their developments are not directly applicable to relational models with cycles or feedback loops. Alternatively, *chain graphs* have been used for representing systems with pairwise feedback loops (Lauritzen and Richardson,

2002; Dawid, 2010; Ogburn et al., 2020). There is no prior work that focuses on representation and reasoning of relational models with cycles or feedback loops of arbitrary length.

Existing research on representation and reasoning about systems with cycles is based on propositional variables, not relational ones. Spirtes (1995) showed that, in general case, without any specific assumption regarding the nature of dependence (linear, polynomial etc.), the d-separation relations in a directed cyclic graph are not sufficient to entail all the corresponding conditional independence relations. Forré and Mooij (2017) introduced σ-separation, an alternative formulation for which the corresponding Markov property is shown to hold in a very general setting. According to them, the σ-separation Markov property seems appropriate for a wide class of cyclic structural causal models with non-linear functional relationships between non-discrete variables.

3. Preliminaries

In this section we introduce the necessary terminology to discuss representation and abstraction of cyclic relational models.

3.1. Directed Cyclic Graphs

A Directed Cyclic Graph (DCG) is a graph $\mathcal{G} = \langle \mathcal{V}, \mathcal{E} \rangle$ with nodes $\mathcal{V}$ and edges $\mathcal{E} \subseteq \{(u, v) : u, v \in V, u \neq v\}$ where (u, v) is an ordered pair of nodes. We will denote a directed edge $(u, v) \in \mathcal{E}$ as $u \rightarrow v$ or $v \leftarrow u$, and call u a parent of v. In this work, we restrict ourselves to DCG as the causal graphical model.

A walk between two nodes $u, v \in \mathcal{V}$ is a tuple $\langle v_0, e_1, v_1, e_2, v_2, ..., e_n, v_n \rangle$ of alternating nodes and edges in $\mathcal{G}(n \geq 0)$, such that $v_0, ..., v_n \in \mathcal{V}$, and $e_1, ..., e_n \in \mathcal{E}$, starting with node $v_0 = u$ and ending with node $v_n = v$ where the edge e_k connects the two nodes v_{k-1} and $v_k \in \mathcal{G}$ for all $k = 1, ..., n$. If the walk contains each node at most once, it is called a *path*. A *directed walk (path)* from $v_i \in \mathcal{V}$ to $v_j \in \mathcal{V}$ is a walk (path) between v_i and v_j such that every edge e_k on the walk (path) is of the form $v_{k-1} \rightarrow v_k$, i.e., every edge is directed and points away from v_i.

We get the *ancestors* of node v_j by repeatedly following the path(s) through the parents: $AN_{\mathcal{G}}(v_j) := \{v_i \in V : v_i = v_0 \rightarrow v_1 \rightarrow ... \rightarrow v_n = v_j \in \mathcal{G}\}$. Similarly, we define the *descendants* of $v_i : DE_{\mathcal{G}}(v_i) := v_j \in \mathcal{V} : v_i = v_0 \rightarrow v_1 \rightarrow ... \rightarrow v_n = v_j \in \mathcal{G}$. Each node is an ancestor and descendant of itself. A directed cycle is a directed path from v_i to v_j such that in addition, $v_j \rightarrow v_i \in \mathcal{E}$. All nodes on directed cycles passing through $v_i \in \mathcal{V}$ together form the strongly connected component $SC_{\mathcal{G}}(v_i) := AN_{\mathcal{G}}(v_i) \cap DE_{\mathcal{G}}(v_i)$ of v_i.

3.2. σ-separation

The idea of σ-separation follows from d-separation, a fundamental notion in DAGs which was first introduced by Pearl (1988):

Definition 1 (d-**separation**) *A walk $\langle v_0...v_n \rangle$ in DCG $G = \langle \mathcal{V}, \mathcal{E} \rangle$ is σ-blocked by $C \subseteq V$ if:*

1. *its first node $v_0 \in C$ or its last node $v_n \in C$, or*

2. *it contains a collider $v_k \notin AN_{\mathcal{G}}(C)$, or*

3. *it contains a non-collider $v_k \in C$.*

If all paths in $\mathcal{G}$ between any node in set $A \subseteq \mathcal{V}$ and any node in set $B \subseteq \mathcal{V}$ are d-blocked by a set $C \subseteq \mathcal{V}$, we say that A is d-separated from B by C, and we write $A \overset{d}{\underset{\mathcal{G}}{\perp\!\!\!\perp}} B | C$.

Spirtes (1995); Neal (2000) show that, without any specific assumption regarding the nature of dependence (linear, polynomial etc.), the d-separation relations are not sufficient to entail all the corresponding conditional independence relations in a directed cyclic graph. In a recent work, an alternative formulation called σ-separation is introduced which holds for a very general graphical settings (Forré and Mooij, 2017). Here we consider a simplified version of the formal definition of σ-separation:

Definition 2 (σ-separation) *(Forré and Mooij, 2017)*
 A walk $\langle v_0 ... v_n \rangle$ in DCG $G = \langle \mathcal{V}, \mathcal{E} \rangle$ is σ-blocked by $C \subseteq V$ if:

1. *its first node $v_0 \in C$ or its last node $v_n \in C$, or*

2. *it contains a collider $v_k \notin AN_{\mathcal{G}}(C)$, or*

3. *it contains a non-collider $v_k \in C$ that points to a neighboring node on the walk in another strongly connected component (i.e., $v_{k-1} \to v_k \to v_{k+1}$ with $v_{k+1} \notin SC_{\mathcal{G}}(v_k)$, $v_{k-1} \leftarrow v_k \leftarrow v_{k+1}$ with $v_{k-1} \notin SC_{\mathcal{G}}(v_k)$ or $v_{k-1} \leftarrow v_k \to v_{k+1}$ with $v_{k-1} \notin SC_{\mathcal{G}}(v_k)$ or $v_{k+1} \notin SC_{\mathcal{G}}(v_k)$).*

If all paths in $\mathcal{G}$ between any node in set $A \subseteq \mathcal{V}$ and any node in set $B \subseteq \mathcal{V}$ are σ-blocked by a set $C \subseteq \mathcal{V}$, we say that A is σ-separated from B by C, and we write $A \overset{\sigma}{\underset{\mathcal{G}}{\perp\!\!\!\perp}} B | C$.

3.3. σ-faithfulness

σ-faithfulness refers to the property which states that all statistical dependencies found in the distribution generated by a given causal structure model is entailed in the graphical model in the form of σ-separation.

Definition 3 (σ-faithfulness) *Given $\mathcal{X}_A$, $\mathcal{X}_B$, $\mathcal{X}_C$ as the distributions of variables A, B, C respectively in solution $\mathcal{X}$ of a causal model $\mathcal{M}$, σ-faithfulness states that if $\mathcal{X}_A$ and $\mathcal{X}_B$ are conditionally independent given $\mathcal{X}_C$, then A and B are σ-separated by C in the corresponding possibly cyclic graphical model $\mathcal{G}$ of $\mathcal{M}$.*

3.4. Relational Causal Models (RCM)

We adopt the definition of relational causal model used by previous work on relational causal discovery (Maier et al., 2013a; Lee and Honavar, 2020). We denote random variables and their realizations with uppercase and lowercase letters respectively, and bold to denote sets. We use a simplified Entity-Relationship model to describe relational data following previous work (Heckerman et al., 2007). A relational schema $\mathcal{S} = \langle \mathcal{E}, \mathcal{R}, \mathcal{A}, card \rangle$ represents a relational domain where $\mathcal{E}$, $\mathcal{R}$ and $\mathcal{A}$ refers to the set of entity, relationship and attribute classes respectively. It includes a cardinality function that constrains the number of times an entity instance can participate in a relationship. Figure 2a shows an example relational model that describes a simplified production system. The model

(a) Relational Causal Model   (b) Ground graph

Figure 2: Example of relational causal model and its corresponding ground graph. The arrows represent relational dependencies.

consists of two entity classes (Employee and Product), and one relationship class (Develops). The entity class Employee has two attributes, performance and salary. The entity class Product also has two attributes: quality and profit. The cardinality constraints are shown with crow's feet notation—an employee can develop multiple products and a product can be developed by multiple employees.

A *relational skeleton s* is an instantiation of the relational schema $\mathcal{S}$, represented by an undirected graph of entities and relationships. We denote the set of all skeletons for schema $\mathcal{S}$ as $\sum_{\mathcal{S}}$. Given a relational schema, we can specify relational paths, which intuitively correspond to ways of traversing the schema. For the schema shown in Figure 2a, possible paths include $[Employee, Develops, Product]$ (the products an employee develops), as well as $[Employee, Develops, Product, Develops, Employee]$ (other employees who develops the same product). *Relational variables* consist of a relational path and an attribute that can be reached through that path. For example, the relational variable $[Employee, Develops, Product].Quality$ corresponds to the quality of the product that an employee develops. The first item in the relational path corresponds to the *perspective* of the relational variable. The relational variable $[Employee, Develops, Product].Quality$ is represented from the perspective of $Employee$. A terminal set, $P|_{i_k}$ is the terminal item on the relational path $P = [I_j, ..., I_k]$ consisting of instances of class $I_k \in \mathcal{E} \cup \mathcal{R}$.

A relational causal model $\mathcal{M} = \langle \mathcal{S}, \mathcal{D} \rangle$, is a collection of relational dependencies defined over schema $\mathcal{S}$. *Relational dependencies* consist of two relational variables, cause and effect. As an example, consider the following relational dependency $[Product, develops, Employee].Performance \rightarrow [Product].Quality$ which states that the quality of a product is affected by the performance of employees developing that product. In Figure 2a, the arrows represents relational dependencies. Note that, all causal dependencies are defined with respect to a specific perspective.

3.5. Ground Graph and Abstract Ground Graph

A realization of a relational model $\mathcal{M}$ with a relational skeleton is referred as the *ground graph* $GG_{\mathcal{M}}$. It is a directed graph consisting attributes of entities in the skeleton as nodes and relational dependencies among them as edges. A single relational model is actually a template for a set of possible ground graphs based on the given schema. A ground graph has the same semantic as a graphical model. Given a relational model $\mathcal{M}$ and a relational skeleton s, we can construct a ground graph $GG_{\mathcal{M}_s}$ by applying the relational dependencies as specified in the model to the specific instances of the relational skeleton. Figure 2b shows the ground graph for the model of Figure 2a.

An *abstract ground graph* (AGG) is an abstract representation that captures the dependencies among relational variables as a directed graph by generalizing dependencies in any possible ground

graph. There are two types of nodes exist in an AGG, relational variables and intersection variables. Intersection variables are constructed from pairs of relational variables with non-empty intersections (Maier et al., 2013b). Edges between a pair of nodes of AGG exists if the instantiations of those constituting relational variables contain a dependent pair in all ground graphs. We define $\overline{\boldsymbol{W}}$ as the set of nodes augmented with their corresponding intersection nodes for the set of relational variables $\overline{\boldsymbol{W}}$: $\overline{\boldsymbol{W}} = \boldsymbol{W} \cup \bigcup_{W \in \boldsymbol{W}} \{W \cap W' | W \cap W'$ is an intersection node in $\sigma\text{-AGG}_{\mathcal{M}_s}\}$.

3.6. Relational d-separation

Relational model describes a template for many possible instantiations of a relational schema. In order to reason about conditional independence facts entailed in all instances of a given relational template, Maier et al. (2013b) develop a relational counterpart for graphical d-separation criteria. Two sets of relational variables $\boldsymbol{X}$ and $\boldsymbol{Y}$ from a given perspective are said to be d-separated by another set $\boldsymbol{Z}$ if and only if the terminal sets of $\boldsymbol{X}$ and $\boldsymbol{Y}$ are d-separated by the terminal set of $\boldsymbol{Z}$ from the given perspective in all possible ground graphs of the given model. Maier et al. (2013b) introduce AGG as a means to reason about relational d-separation queries from a given perspective. The soundness and completeness of relational d-separation for AGG relies on the following assumptions:

A 1 *The relational model is acyclic.*

A 2 *There are no unobserved confounders in the relational model.*

Here, soundness refers to the fact that any d-separation relationship found in AGG implies corresponding d-separation relationship in all ground graphs it represents whereas completeness claims that the d-separation facts that hold across all ground graphs are also entailed by d-separation on the AGG. The soundness of relational d-separation under AGG is already proved by Maier et al. (2013b). However, the conditions under which completeness holds have been an open question since Lee and Honavar (2015) show that the initial formulation of Maier et al. (2013b) is not complete. We resolve this question in Section 4.4 and show that AGG is also complete under certain realistic assumptions.

4. Relational Systems With Cycles

In this section, we develop definitions for cyclic relational causal models (RCM) and an abstract representation that allows causal reasoning and discovery. We introduce a criterion for abstracting cyclic RCMs and provide proofs for its correctness.

4.1. Cyclic RCM

A RCM is cyclic when the set of relational dependencies form one or more arbitrary length cycles.

Definition 3 (Cyclic RCM) *A relational model $\mathcal{M} = (\mathcal{S}, \mathcal{D})$ is said to be cyclic if the set of relational dependencies $\mathcal{D}$ constructs one or more directed cycles of arbitrary length.*

Cycles in RCM imply that the ground graphs are no longer guaranteed to be DAGs and they can contain cycles as well. In order to facilitate this, we propose a revised definition of relational dependency provided by Maier et al. (2013b) by relaxing the restriction of having different attribute classes for cause and effect.

(a) Ground Graph   (b) σ-AGG

Figure 3: Ground graph and σ-AGG for the cyclic relational model shown in Figure 1.

Definition 4 (Relational Dependency) *A relational dependency* $[I_j, ..., I_k].X' \rightarrow [I_j].X$ *is a directed probabilistic dependence from any attribute class* X' *to* X *through the relational path* $[I_j, ..., I_k]$ *such that* $I_j, ..., I_k \in \mathcal{E} \cup \mathcal{R}$, $X, X' \in \mathcal{A}$. *Note that it is possible to have* $X = X'$.

Figure 1 shows an example relational model with cyclic dependencies. Here we see a pair of dependencies $[Product, Develops, Employee].Performance \rightarrow [Product].quality$ and $[Product].Quality \rightarrow [Product, Develops, Employee].Performance$ which are inverse to each other and forms a feedback loop. The work by Maier et al. (2013b) is not sufficient to reason about conditional independence relationships in the ground graphs of such relational models since it is defined specifically for acyclic models. This motivates us to introduce a new criterion that enables abstraction of relational queries with cyclic dependencies over all ground graphs.

4.2. Relational σ-separation

Conditional independence facts are only useful when they hold across all ground graphs that are consistent with the model. Maier et al. (2013b) show that relational d-separation is sufficient to achieve that for acyclic models. However, such abstraction is not possible for cyclic models since the correctness of d-separation is not guaranteed for cyclic graphical models (Spirtes, 1995; Neal, 2000). In this work, we propose the following definition of relational σ-separation specifically for (possibly) cyclic relational models:

Definition 5 (Relational σ-separation) *Let* X, Y, *and* Z *be three distinct sets of relational variables with the same perspective* $B \in \mathcal{E} \cup \mathcal{R}$ *defined over relational schema* $\mathcal{S}$. *Then, for relational model structure* $\mathcal{M}$, X *and* Y *are σ-separated by* Z *if and only if, for all skeletons* $s \in \sum_{\mathcal{S}}$, $X|_b$ *and* $Y|_b$ *are σ-separated by* $Z|_b$ *in ground graph* $GG_{\mathcal{M}_s}$ *for all* $b \in s(B)$.

The definition directly follows from the definition of relational d-separation. If there exists even one skeleton and faithful distribution represented by the relational model for which $X \not\perp\!\!\!\perp Y|Z$, then $X|_b$ and $Y|_b$ are not σ-separated by $Z|_b$ for $b \in s(B)$.

Figure 3a shows an example ground graph with a pairwise feedback loop. According to d-separation the following independence holds: $Alice.Salary \overset{d}{\perp\!\!\!\perp} Bob.Salary \,|\, \{Alice.Performance, Laptop.Quality\}$. However, according to σ-separation it doesn't hold, rather it enforces a stricter conditioning: $Alice.Salary \overset{\sigma}{\perp\!\!\!\perp} Bob.Salary \,|\, \{Alice.Performance, Laptop.Quality, \quad Bob.Performance\}$ which makes more intuitive sense.

4.3. σ-Abstract Ground Graph

We refer to the lifted representation for cyclic relational models as σ-*abstract ground graph* or σ-AGG. A σ-AGG is constructed using the same *extend* method used to construct AGG (Maier et al., 2013b).

Definition 6 (σ-Abstract Ground Graph) *An abstract ground graph σ-$AGG_{\mathcal{M}} = (V, E)$ for relational model structure $\mathcal{M} = (\mathcal{S}, \mathcal{D})$, perspective $B \in \mathcal{E} \cup \mathcal{R}$, and hop threshold $h \in \mathbb{N}^0$ is a directed graph that abstracts the dependencies $\mathcal{D}$ for all ground graphs $GG_{\mathcal{M}_s}$, where $s \in \sum_{\mathcal{S}}$. The σ-$AGG_{\mathcal{M}_s}$ is a directed cyclic graph with the following nodes and edges:*

1. *$V = RV \cup IV$, where*

    (a) *RV is the set of relational variables with a path of length at most h + 1.*

    (b) *IV are intersection variables between pairs of relational variables that could intersect*

2. *$E = RVE \cup IVE$, where*

    (a) *$RVE \subset RV \times RV$ are the relational variable edges*

    (b) *$IVE \subset (IV \times RV) \cup (RV \times IV)$ are the intersection variable edges. This is the set of edges that intersection variables "inherit" from the relational variables that they were created from*

Since the construction of an AGG and a σ-$AGG_{\mathcal{M}_s}$ is identical, they share mostly identical properties as defined by Maier et al. (2013b) for AGG. The main difference being the existence of cycles. Consequently, the goal of σ-$AGG_{\mathcal{M}_s}$ is to reason about relational σ-separation queries instead of relational d-separation.

4.4. Soundness and Completeness of Relational σ-separation

In order to discuss soundness and completeness of relational σ-separation we first address the open problem of necessary conditions for the completeness of relational d-separation. Previous work has shown that the original claim of completeness of relational d-separation by Maier et al. (2013a) cannot be guaranteed for any relational model (Lee and Honavar, 2015). A counterexample has been developed as well. In this work, we show that relational d-separation is complete under the following assumption:

A 3 *The degree of any entity in the relational skeleton is greater than 1.*

We first introduce the following lemma that establishes necessary conditions for AGGs to be realizable in ground graphs. This result may be of independent interest, since it corrects a known deficiency in the original presentation of relational d-separation (Maier et al., 2013b; Lee and Honavar, 2015).

Lemma 1 *Under assumption 3, every abstract ground graph can be realized as a ground graph. That is, for every acyclic relational model $\mathcal{M}$ and skeleton $s \in \sum_{\mathcal{S}}$ any relational variable in $AGG_{\mathcal{M}_s}$ has non-empty terminal sets in some ground graph $GG_{\mathcal{M}_s}$.*

Proof

We first consider the conditions under which empty terminal sets can occur, resulting in an AGG that is unrealizable in the ground graphs. There are two necessary and sufficient conditions for empty terminal sets to appear in all ground graphs corresponding to an AGG. First, there must be at least one intersection variable present in the AGG. If no intersection variable exist in the AGG, then the completeness proof of relational d-separation by Maier et al. (2013b) holds. The second condition is that the intersection must be on a path consisting of only one-to-one relationships. In order to understand this condition, lets look at an example with the following relational paths from a hypothetical relational model which is a generalization of the counterexample given by Lee and Honavar (2015) [1]:

- $P = [E_i, \ldots, R_j, \ldots, E_k]$

- $Q = [E_i, \ldots, R_j, \ldots, R_m, E_k, \ldots, E_q]$

- $S = [E_i, \ldots, R_j, \ldots, R_m, \ldots, E_s]$

- $S' = P + [R_m, \ldots, E_s]$

where E_i, E_k, E_q, E_s are some entity classes, R_j, R_m are relationship classes, "$\ldots$" are arbitrary valid sequences of entities and relationships, and $+$ represents the concatenation of relational paths. Let's assume two relational dependencies exist in the given model, $P.X \rightarrow Q.Y$ and $S.Z \rightarrow Q.Y$ where X, Y, Z are attributes of corresponding entity classes. By definition, the corresponding edges $P.X \rightarrow Q.Y, S.Z \rightarrow Q.Y$ appear in the AGG. Since S and S' are intersectable an additional edge $S.Z \cap S'.Z \rightarrow Q.Y$ also appears in the AGG. Such a model can be realized in many possible ground graphs. However, if we restrict the relationships to be strictly one-to-one, then there is only one skeleton structure possible to satisfy the relational dependencies at the cost of $S'.Z$ having empty terminal sets since an intance of R_m can connect to only one instance of E_k. If we allow many-to-many relationships then we can always construct a skeleton where an instance of R_m connects to two instances of E_k to produce non-empty terminal sets for both Q and S'.

Since assumption 3 prohibits the second condition, it essentially implies that any relational variable in $\mathrm{AGG}_{\mathcal{M}_s}$ results into non-empty terminal sets in corresponding ground graphs for every acyclic relational model $\mathcal{M}$ and skeleton $s \in \sum_{\mathcal{S}}$ which completes the proof for Lemma 1. ∎

The following proposition establishes the completeness of AGG for relational d-separation.

Proposition 1 *AGG is sound and complete for relational d-separation under assumption 3.*

Proof Following lemma 1, the original proof of soundness and completeness of relational d-separation by Maier et al. (2013b) directly applies which proves proposition 1. ∎

The correctness of our approach to relational σ-separation relies on several facts which are similar to the case for AGG: (1) σ-separation is valid for directed cyclic graphs; (2) ground graphs are directed cyclic graphs; and (3) σ-AGGs are directed cyclic graphs that represent exactly the edges that could appear in all possible ground graphs. Note that we no longer need assumption 1,

---

1. The complete counterexample and figure explaining it is given in the Appendix

but assumptions 2 and 3 are adopted from relational d-separation. Using the previous definitions and lemmas, the following additional assumptions and sequence of results proves the correctness of our approach to identifying independence in cyclic relational models.

A 4 *The given cyclic relational model structure is σ-faithful.*

Theorem 1 *The rules of σ-separation are sound and complete for cyclic directed graphs.*

Proof Forré and Mooij (2017) show that for quite general structural equation models HEDGes[2] always follow a directed global Markov property based on σ-separation which completes the proof for soundness since directed cyclic graphs are subsets of HEDGes. The completeness claim is already covered by Assumption 4. ∎

Theorem 2 *For every cyclic relational model structure $\mathcal{M} = (\mathcal{S}, \mathcal{D})$ and skeleton $s \in \sum_{\mathcal{S}}$ such that relational variables involved in $\mathcal{D}$ are non-empty, the ground graph $GG_{\mathcal{M}_s}$ is a cyclic directed graph.*

Proof

Let's assume for contradiction that there exists an acyclic ground graph g which is a realization of a given cyclic relational model $\mathcal{M} = (\mathcal{S}, \mathcal{D})$ and skeleton $s \in \sum_{\mathcal{S}}$. According to the definition of ground graphs, the edges of ground graphs are directly constructed based on the relational dependencies of the model. Definition 3 states that a cyclic RCM consists of one or more cycles formed by the relational dependencies. Assume a cycle in cyclic RCM is formed by the pair of relational dependencies as follows: a) $P.j \rightarrow Q.k$, and b) $Q.k \rightarrow P.j$ where P and Q are relational paths from some perspective b and i, j refers to two attribute classes. By construction of g there must be two nodes a, b in g corresponding to $P.j$ and $Q.k$ respectively. Moreover, the definition of ground graph requires two edges $a \rightarrow b$ and $b \rightarrow a$ to be present in the ground graph. But such a pair of edges constructs a cycle which is contradictory to the initial claim. Thus, the ground graph g must be cyclic. ∎

Theorem 3 *For every cyclic relational model structure $\mathcal{M}$ and perspective $B \in \mathcal{E} \cup \mathcal{R}$, the σ-$AGG_{\mathcal{M}_s}$ is sound and complete for all ground graphs $GG_{\mathcal{M}_s}$ with skeleton $s \in \sum_{\mathcal{S}}$.*

The proof follows from the proof of soundness and completeness of AGG (Maier et al., 2013b). The complete proof is provided in the Appendix.

Theorem 4 *The abstract ground graph σ-$AGG_{\mathcal{M}_s}$ is a cyclic directed graph if and only if the underlying relational model structure is cyclic.*

Proof

Let $\mathcal{M}$ be an arbitrary (possibly) cyclic relational model structure, and let $B \in \mathcal{E} \cup \mathcal{R}$ be an arbitrary perspective. It is clear by Definition 6 that every edge in the abstract ground graph σ-$AGG_{\mathcal{M}_s}$ is directed by construction.

---

2. The definition of HEDG is provided in the Appendix

Assume for contradiction that no cycles exists in σ-AGG$_{\mathcal{M}_s}$ even if the relational dependencies form one or more cycles. Now assume the following two dependencies are part of the given relational model $\mathcal{M}$: 1. $[I_j, ..., I_k].X \rightarrow [I_j].Y \in D$, 2. $[I_j].Y \rightarrow [I_j, ..., I_k].X \in D$ where $I_j, ..., I_k \in \mathcal{E} \cup \mathcal{R}$. By Definition 6, all edges inserted in σ-AGG$_{\mathcal{M}_s}$ are drawn from some dependency in $\mathcal{M}$ and edges in σ-AGG$_{\mathcal{M}_s}$ are constructed for all the dependencies in D. As a result there must be corresponding edges in the σ-AGG$_{\mathcal{M}_s}$ for both dependencies that form a cycle, which contradicts the assumption.

Now, assume that a σ-AGG$_{\mathcal{M}_s}$ is acyclic even if the underlying relational model structure is cyclic. Using the same argument as above we can say that the edges in the σ-AGG$_{\mathcal{M}_s}$ constructed based on the dependencies in $\mathcal{D}$. If a cycle exists in the σ-AGG$_{\mathcal{M}_s}$ it directly implies the existence of a cycle in the relational model structure which leads to a contradiction. Thus the proof completes from both directions.

∎

Theorem 5 *Relational σ-separation is sound and complete for σ-AGG. Let $\mathcal{M}$ be a (possibly) cyclic relational model structure, and let $\boldsymbol{X}$, $\boldsymbol{Y}$, and $\boldsymbol{Z}$ be three distinct sets of relational variables defined over relational schema $\mathcal{S}$. Then, $\overline{\boldsymbol{X}}$ and $\overline{\boldsymbol{Y}}$ are σ-separated by $\overline{\boldsymbol{Z}}$ on the abstract ground graph σ-AGG$_{\mathcal{M}_s}$ if and only if for all skeletons $s \in \sum_{\mathcal{S}}$ and for all perspectives $b \in s(B)$, $\boldsymbol{X}|_b$ and $\boldsymbol{Y}|_b$ are σ-separated by $\boldsymbol{Z}|_b$ in ground graph $GG_{\mathcal{M}_s}$.*

Proof

We must show that σ-separation on an abstract ground graph implies σ-separation on all ground graphs it represents (soundness) and that σ-separation facts that hold across all ground graphs are also entailed by σ-separation on the abstract ground graph (completeness). The proof follows from the proof of soundness and completeness of AGG (Maier et al., 2013b).

Soundness:

Assume that $\overline{\boldsymbol{X}}$ and $\overline{\boldsymbol{Y}}$ are σ-separated by $\overline{\boldsymbol{Z}}$ on σ-AGG$_{\mathcal{M}_s}$. Assume for contradiction that there exists an item instance b such that $\boldsymbol{X}|_b$ and $\boldsymbol{Y}|_b$ are not σ-separated by $\boldsymbol{Z}|_b$ in the ground graph $GG_{\mathcal{M}_s}$ for some arbitrary skeleton s. Then, there must exist a σ-connecting path p from some $x \in \overline{\boldsymbol{X}}|_b$ to some $y \in \overline{\boldsymbol{Y}}|_b$ given all $z \in \overline{\boldsymbol{Z}}|_b$. By Theorem 3, σ-AGG$_{\mathcal{M}_s}$ is complete, so all edges in $GG_{\mathcal{M}_s}$ are captured by edges in σ-AGG$_{\mathcal{M}_s}$. So, path p must be represented from some node in $\{N_x | x \in N_x|_b\}$ to some node in $\{N_y | y \in N_y|_b\}$, where N_x, N_y are nodes in σ-AGG$_{\mathcal{M}_s}$. If p is σ-connecting in $GG_{\mathcal{M}_s}$, then it is σ-connecting in σ-AGG$_{\mathcal{M}_s}$, implying that $\overline{\boldsymbol{X}}$ and $\overline{\boldsymbol{Y}}$ are not σ-separated by $\overline{\boldsymbol{Z}}$. So, $\boldsymbol{X}|_b$ and $\boldsymbol{Y}|_b$ must be σ-separated by $\boldsymbol{Z}|_b$.

Completeness:

Assume that $\boldsymbol{X}|_b$ and $\boldsymbol{Y}|_b$ are σ-separated by $\boldsymbol{Z}|_b$ in the ground graph $GG_{\mathcal{M}_s}$ for all skeletons s for all $b \in s(B)$. Assume for contradiction that $\overline{\boldsymbol{X}}$ and $\overline{\boldsymbol{Y}}$ are not σ-separated by $\overline{\boldsymbol{Z}}$ on σ-AGG$_{\mathcal{M}_s}$. Then, there must exist a σ-connecting path p for some relational variable $X \in \overline{\boldsymbol{X}}$ to some $Y \in \overline{\boldsymbol{Y}}$ given all $Z \in \overline{\boldsymbol{Z}}$. By Theorem 3, σ-AGG$_{\mathcal{M}_s}$ is sound, so every edge in σ-AGG$_{\mathcal{M}_s}$ must correspond to some pair of variables in some ground graph. So, if p is σ-connecting in σ-AGG$_{\mathcal{M}_s}$, then there must exist some skeleton s such that p is σ-connecting in $GG_{\mathcal{M}_s}$ for some $b \in s(B)$, implying that σ-separation does not hold for that ground graph. So, $\overline{\boldsymbol{X}}$ and $\overline{\boldsymbol{Y}}$ must be σ-separated by $\overline{\boldsymbol{Z}}$ on σ-AGG$_{\mathcal{M}_s}$.

∎

Maier et al. (2013b) show that relational d-separation is equivalent to the Markov condition on acyclic relational models. However, it doesn't hold for cyclic relational model. Here, we show how relational σ-separation is equivalent to the Markov condition on cyclic relational models.

Definition 7 (Relational σ-separation Markov Property) *Let X, Y, Z be relational variables for perspective $B \in \mathcal{E} \cup \mathcal{R}$ defined over relational schema $\mathcal{S}$. For any solution $(\mathcal{X}, \epsilon)$ of a relational model $\mathcal{M}$ which follows a simple SCM,*

$$X \overset{\sigma}{\underset{\mathcal{M}}{\perp\!\!\!\perp}} Y | Z \implies \mathcal{X}_X \underset{\mathbb{P}_{\mathcal{M}}(\mathcal{X})}{\perp\!\!\!\perp} \mathcal{X}_Y | \mathcal{X}_Z$$

if and only if for $\forall x \in X|_b$, $\forall y \in Y|_b$, $\forall z \in Z|_b$

$$x \overset{\sigma}{\underset{GG_{\mathcal{M}}}{\perp\!\!\!\perp}} y | z \implies \mathcal{X}'_x \underset{\mathbb{P}_{GG_{\mathcal{M}}}(\mathcal{X}')}{\perp\!\!\!\perp} \mathcal{X}'_y | \mathcal{X}'_z$$

in ground graph $GG_{\mathcal{M}_s}$ for all skeletons $s \in \sum_{\mathcal{S}}$ and for all $b \in s(B)$ where $(\mathcal{X}', \epsilon')$ refers to the solution of the SCM corresponding to the ground graphs.

In other words, σ-separation of two relational variables X and Y given a third relational variable Z would imply X and Y are conditionally independent given Z if and only if, for all instances of X, Y, Z in all possible ground graphs, the same condition holds. For directed cyclic graphs, the global directed Markov property [3] holds for σ-separation (Forré and Mooij, 2017; Mooij et al., 2020). Since ground graphs of cyclic RCM are directed cyclic graphs and σ-separation on σ-AGG$_{\mathcal{M}_s}$ is sound and complete (by Theorem 5), we can conclude that relational σ-separation is equivalent to the relational Markov property.

5. Conclusion

Cycles or feedback loops are common elements of many real-world system. Unfortunately, it is hardly studied in the field of causal inference primarily because it breaks the nice properties of directed acyclic graphs. As a result, cycles and feedback loops are mostly avoided in the domain of relational causal model. In this study, we take a step forward to bridge this gap by developing an abstract representation and a criterion to reason about statistical relationships in relational models with or without cycles under a general framework. We show that the new criterion called σ-separation can consistently capture the statistical independence relationships of all possible instantiations of a relational causal model. We believe that this work will open the door for further development including but not limited to causal structure learning of relational models with cycles.

---

3. Definition given in appendix

References

Rohit Bhattacharya, Daniel Malinsky, and Ilya Shpitser. Causal inference under interference and network uncertainty. In *Uncertainty in Artificial Intelligence*, pages 1028–1038. PMLR, 2020.

N. A. Christakis and J. H. Fowler. The spread of obesity in a large social network over 32 years. *NEJM*, 357(4):370–379, 2007.

A Philip Dawid. Beware of the dag! In *Causality: objectives and assessment*, pages 59–86. PMLR, 2010.

Patrick Forré and Joris M Mooij. Markov properties for graphical models with cycles and latent variables. *arXiv preprint arXiv:1710.08775*, 2017.

D. Heckerman, C. Meek, and D. Koller. Probabilistic entity-relationship models, prms, and plate models. *Introduction to statistical relational learning*, pages 201–238, 2007.

Steffen L Lauritzen and Thomas S Richardson. Chain graph models and their causal interpretations. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 64(3):321–348, 2002.

Sanghack Lee and Vasant Honavar. Towards robust relational causal discovery. In *Uncertainty in Artificial Intelligence*, pages 345–355. PMLR, 2020.

Sanghack Lee and Vasant G Honavar. Lifted representation of relational causal models revisited: Implications for reasoning and structure learning. In *ACI@UAI*, 2015.

Marc Maier, Katerina Marazopoulou, David Arbour, and David Jensen. A sound and complete algorithm for learning causal models from relational data. *arXiv preprint arXiv:1309.6843*, 2013a.

Marc Maier, Katerina Marazopoulou, and David Jensen. Reasoning about independence in probabilistic models of relational data. *arXiv preprint arXiv:1302.4381*, 2013b.

Joris M Mooij, Sara Magliacane, and Tom Claassen. Joint causal inference from multiple contexts. *Journal of Machine Learning Research,*, 2020.

Radford M Neal. On deducing conditional independence from d-separation in causal graphs with feedback (research note). *Journal of Artificial Intelligence Research*, 12:87–91, 2000.

Elizabeth L Ogburn, Tyler J VanderWeele, et al. Causal diagrams for interference. *Statistical science*, 29(4):559–578, 2014.

Elizabeth L Ogburn, Ilya Shpitser, and Youjin Lee. Causal inference, social networks and chain graphs. *Journal of the Royal Statistical Society: Series A (Statistics in Society)*, 183(4):1659–1676, 2020.

Judea Pearl. *Probabilistic Reasoning in Intelligent Systems: Networks of Plausible Inference*. Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 1988.

Eli Sherman and Ilya Shpitser. Identification and estimation of causal effects from dependent data. *Advances in neural information processing systems*, 2018:9446, 2018.

Ilya Shpitser. Segregated graphs and marginals of chain graph models. *Advances in Neural Information Processing Systems*, 28:1720–1728, 2015.

Peter L Spirtes. Directed cyclic graphical representations of feedback models. *Proceedings of the Eleventh Conference on Uncertainty in Artificial Intelligence*, 1995.

Tyler J VanderWeele, Eric J Tchetgen Tchetgen, and M Elizabeth Halloran. Components of the indirect effect in vaccine trials: identification of contagion and infectiousness effects. *Epidemiology (Cambridge, Mass.)*, 23(5):751, 2012.

Figure 4: Construction of the counterexample by Lee and Honavar (2015). The notations inside the circles/rhombus refer to instances of the corresponding entity/relationship classes which are mentioned outside the shapes. The dashed lines represent relational dependencies. The dotted line represents a hypothetical connection that can nullify the counterexample under assumption 3.

.

Appendix A. Preliminaries

A.1. Directed Graphs with Hyperedges (HEDGes)

A directed graph with hyperedges or hyperedged directed graph (HEDG) is a tuple $G = (\mathcal{V}, \mathcal{E}, \mathcal{H})$, where $(\mathcal{V}, \mathcal{E})$ is a directed graph (with or without cycles) and $\mathcal{H}$ a simplicial complex over the set of vertices $\mathcal{V}$ of $\mathcal{G}$. A simplicial complex $\mathcal{H}$ over $\mathcal{V}$ is a set of subsets of $\mathcal{V}$ such that: 1) all single element sets $\{v\}$ are in $\mathcal{H}$ for $v \in \mathcal{V}$, and 2) if $F \in \mathcal{H}$ then also all subsets $F' \subseteq F$ are elements of $\mathcal{V}$.

The general directed global Markov property (gdGMP) for the HEDGes is stated as follows:

Definition 8 (gdGMP) *For all subsets $X, Y, Z \subseteq V$ we have the implication:*

$$X \overset{\sigma}{\underset{G}{\perp\!\!\!\perp}} Y | Z \implies X \underset{P_v}{\perp\!\!\!\perp} Y | Z$$

A.2. Counterexample by Lee and Honavar (2015)

The following counterexample shows that AGG is not complete for relational d-separation.

Example. Let $\mathcal{S} = \langle \mathcal{E}, \mathcal{R}, \mathcal{A}, card \rangle$ be a relational schema such that: $\mathcal{E} = \{E_i\}_{i=1}^5$; $\mathcal{R} = \{R_j\}_{j=1}^3$ with $R_1 = \langle E_1, E_2, E_4 \rangle$, $R_2 = \langle E_2, E_3 \rangle$, $R_3 = \langle E_3, E_4, E_5 \rangle$; $\mathcal{A} = \{E_2 : \{Y\}, E_3 : \{X\}, E_5 : \{Z\}\}$; and $\forall_{R \in \mathcal{R}} \forall_{E \in \mathcal{E}} \, card(R, E) = one$. Let $\mathcal{M} = \langle \mathcal{S}, \mathcal{D} \rangle$ be a relational model with

$$\mathcal{D} = \{D_1.X \to [I_Y].Y, D_2.Z \to [I_Y].Y\}$$

such that $D_1 = [E_2, R_2, E_3, R_3, E_4, R_1, E_2, R_2, E_3]$ and $D_2 = [E_2, R_2, E_3, R_3, E_5]$. Let $P.X, Q.Y, S.Z, S'.Z$ be four relational variables of the same perspective $B = E_1$ where their relational paths are distinct where

- $P = [E_1, R_1, E_2, R_2, E_3]$,

- $Q = [E_1, R_1, E_4, R_3, E_3, R_2, E_2]$,

- $S = [E_1, R_1, E_4, R_3, E_5]$,

- $S' = [E_1, R_1, E_2, R_2, E_3, R_3, E_5]$

Given the above example, Lee and Honavar (2015) make two claims:

Claim 1. $(\overline{P.X} \not\perp \overline{S'.Z} | \overline{Q.Y})_{AGG_\mathcal{M}}$

Claim 2. There is no $s \in \sum_\mathcal{S}$ and $b \in s(B)$ such that $(P.X|_b \not\perp S'.Z|_b | Q.Y|_b)_{GG_{\mathcal{M}_s}}$

Figure 4 shows the general pattern discussed in Section 4.4 regarding the construction of the counterexample by Lee and Honavar (2015).

Appendix B. Proofs

The proof for Theorem 3 is given as follows:

Proof

Let $\mathcal{M} = (\mathcal{S}, \mathcal{D})$ be an arbitrary cyclic relational model structure and $B \in \mathcal{E} \cup \mathcal{R}$ an arbitrary perspective.

Soundness: To prove that σ-AGG$_{\mathcal{M}_s}$ is sound, we must show that for every edge $P_k.X \to P_j.Y$ in σ-AGG$_{\mathcal{M}_s}$, there exists a corresponding edge $i_k.X \to i_j.Y$ in the ground graph $GG_{\mathcal{M}_s}$ for some skeleton $s \in \sum_\mathcal{S}$, where $i_k \in P_k|_b$ and $i_j \in P_j|_b$ for some $b \in s(B)$. There are three subcases, one for each type of edge in an abstract ground graph:

(a) Let $[B, ..., I_k].X \to [B, ..., I_j].Y \in RVE$ be an arbitrary edge in σ-AGG$_{\mathcal{M}_s}$ between a pair of relational variables. Assume for contradiction that there exists no edge $i_k.X \to i_j.Y$ in any ground graph:

$$\forall s \in \Sigma_\mathcal{S}, \forall i_k \in [B, ..., I_k]|_b, \forall i_j \in [B, ..., I_j]|_b$$
$$(i_k.X \to i_j.Y \notin GG_{\mathcal{M}_\mathcal{S}})$$

By Definition 6 for σ-AGG$_{\mathcal{M}_s}$, if $[B, ..., I_k].X \to [B, ..., I_j].Y \in RVE$, then the model must have dependency $[I_j, ..., I_k].X \to [I_j].Y \in \mathcal{D}$ such that $[B, ..., I_k] \in extend([B, ..., I_j], [I_j, ..., I_k])$. So, by the definition of ground graphs, there is an edge from every $i_k.X$ to every $i_j.Y$, where i_k is in the terminal set for i_j along $[I_j, ..., I_k]$. Therefore, there exists a ground graph $GG_{\mathcal{M}_s}$ such that $i_k.X \to i_j.Y \in GG_{\mathcal{M}_s}$, which contradicts the assumption.

(b) Let $P_1.X \cap P_2.X \to [B, ..., I_j].Y \in IVE$ be an arbitrary edge in σ-AGG$_{\mathcal{M}_s}$ between an intersection variable and a relational variable, where $P_1 = [B, ..., I_m, ..., I_k]$ and $P_2 = [B, ..., I_n, ..., I_k]$ with $I_m \neq I_n$. By Definition 6, if the σ-abstract ground graph has edge $P_1.X \cap P_2.X \to [B, ..., I_j].Y \in IVE$, then either $P_1.X \to [B, ..., I_j].Y \in RVE$ or $P_2.X \to [B, ..., I_j].Y \in RVE$. Then, as shown in case (a), there exists an $i_j \in [B, ..., I_j]|b$ such that $i_k.X \to i_j.Y \in GG_{\mathcal{M}_s}$, which contradicts the assumption.

(c) Let $[B, ..., I_k].Y \to P_1.X \cap P_2.X \in IVE$ be an arbitrary edge in σ-AGG$_{\mathcal{M}_s}$ between an intersection variable and a relational variable, where $P_1 = [B, ..., I_m, ..., I_j]$ and $P_2 = [B, ..., I_n, ..., I_j]$ with $I_m \neq I_n$. The proof follows case (b) to show that there exists a skeleton $s \in \sum_\mathcal{S}$ and $b \in s(B)$ such that for all $i_k \in [B, ..., I_k]|_b$ there exists an $i_j \in P_1 \cap P_2|_b$ such that $i_k.X \to i_j.Y \in GG_{\mathcal{M}_s}$.

Completeness: To prove that the σ-abstract ground graph σ-AGG$_{\mathcal{M}_s}$ is complete, we show that for every edge $i_k.X \to i_j.Y$ in every ground graph $GG_{\mathcal{M}_s}$ where $s \in \sum_\mathcal{S}$, there is a set of

corresponding edges in σ-$\text{AGG}_{\mathcal{M}_s}$. Specifically, the edge $i_k.X \to i_j.Y$ yields two sets of relational variables for some $b \in s(B)$, namely $\boldsymbol{P_k.X} = \{P_k.X | i_k \in P_k|_b\}$ and $\boldsymbol{P_j.Y} = \{P_j.Y | i_j \in P_j|_b\}$. Note that all relational variables in both $\boldsymbol{P_k.X}$ and $\boldsymbol{P_j.Y}$ are nodes in σ-$\text{AGG}_{\mathcal{M}_s}$, as are all pairwise intersection variables. We show that for all $P_k.X \in \boldsymbol{P_k.X}$ and for all $P_j.Y \in \boldsymbol{P_j.Y}$ either (a) $P_k.X \to P_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$ (b) $P_k.X \cap P'_k.X \to P_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$ where $P'_k.X \in \boldsymbol{P_k.X}$, or (c) $P_k.X \to P_j.Y \cap P'_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$ where $P'_j.Y \in \boldsymbol{P_j.Y}$.

Let $s \in \sum_{\mathcal{S}}$ be an arbitrary skeleton, let $i_k.X \to i_j.Y \in GG_{\mathcal{M}_s}$ be an arbitrary edge drawn from $[I_j, ..., I_k].X \to [I_j].Y \in \mathcal{D}$, and let $P_k.X \in P_k.X, P_j.Y \in P_j.Y$ be an arbitrary pair of relational variables.

(a) If $P_k \in extend(P_j, [I_j, ..., I_k])$, then $P_k.X \to P_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$ by Definition 6.

(b) If $P_k \notin extend(P_j, [I_j, ..., I_k])$, but $\exists P'_k \in extend(P_j, [I_j, ..., I_k])$ such that $P'_k.X \in P_k.X$, then $P'_k.X \to P_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$, and $P_k.X \cap P'_k.X \to P_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$ by Definition 6.

(c) If $\forall P \in extend(P_j, [I_j, ..., I_k])(P.X \notin Pk.X)$, then $\exists P'_j$ such that $i_j \in P'_j|_b$ and $P_k \in extend(P'_j, [I_j, ..., I_k])$. Therefore, $P'_j.Y \in P_j.Y, P_k.X \to P'_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$, and $P_k.X \to P'_j.Y \cap P_j.Y \in \sigma$-$\text{AGG}_{\mathcal{M}_s}$ by Definition 6.

■