Non-Parallel Text Style Transfer with Self-Parallel Supervision

Abstract

The performance of existing text style transfer models is severely limited by the non-parallel datasets on which the models are trained. In non-parallel datasets, no direct mapping exists between sentences of the source and target style; the style transfer models thus only receive weak supervision of the target sentences during training, which often leads the model to discard too much style-independent information, or utterly fail to transfer the style.

In this work, we propose LaMer, a novel text style transfer framework based on large-scale language models. LaMer first mines the roughly parallel expressions in the non-parallel datasets with scene graphs, and then employs MLE training, followed by imitation learning refinement, to leverage the intrinsic parallelism within the data. On two benchmark tasks (sentiment & formality transfer) and a newly proposed challenging task (political stance transfer), our model achieves qualitative advances in transfer accuracy, content preservation, and fluency. Further empirical and human evaluations demonstrate that our model not only makes training more efficient, but also generates more readable and diverse expressions than previous models.

1 Introduction

Text style transfer (TST) models learn how to transfer the style of text from source to target while preserving the style-independent content (John et al., 2019; Fu et al., 2018). Existing TST methods perform well when transferring simple styles, such as sentiment; however, they tend to do a poor job on more abstract and subtle styles, such as formality and political stance (Lee et al., 2021; Fu et al., 2019b).

The lack of parallel datasets is one of the main bottlenecks for text style transfer tasks. Parallel datasets contain pairwise sentences that only differ in specific styles, while non-parallel datasets typically contain a large corpora of sentences with different styles, without direct one-to-one mapping between sentences (Fu et al., 2019a; Krishna et al., 2020). In real-world settings, it is much easier to construct non-parallel datasets by collecting large quantities of non-parallel sentences with different styles; conversely, carefully-aligned parallel TST datasets are much more costly to construct, usually requiring human annotation, and are thus scarce.

Figure 1: Red and blue circles represent the source and target texts respectively. (a) Existing methods crucially ignore the inherit parallelism within the data. (b) Our method first mines (roughly) parallel expressions, then learns how to transfer style with the self-supervision from the parallel expressions.

This discrepancy between the availability of parallel and non-parallel datasets for style transfer tasks prompts researchers to develop TST models for non-parallel datasets. However, these methods are less than ideal. As demonstrated in Figure 1 (a), they tend to learn the mapping between source and target styles on the original randomly mapped sentence pairs, but fail to take into account the inherent parallelism within the data (Dai et al., 2019; Luo et al., 2019; Shen et al., 2017). Current methods either rely on surface-level classification of tokens as style- or content-bearing (Li et al.,

2018a; Castro et al., 2017; Karadzhov et al., 2017), or separate content and style vectors in latent space (John et al., 2019; Liu et al., 2020; Wang et al., 2019). Once style and content have been separated, they then swap styles leaving the content unchanged. However, surface-level split is not reliable when the style cannot be extracted at the token level; latent-space disentanglement could also fail due to a lack of pairwise supervision and results in discarding too much style-independent content. More recent work pivot to use pseudo parallels as pairwise supervision. For example, Jin et al. (2019) inspired by parallel data construction in machine translation (Hu et al., 2019; Grégoire & Langlais, 2018), construct pseudo parallels via iterative matching and back-translation. The iterative generation procedure is rather time consuming; however, training additional translation systems for TST could also be costly, which may introduce unnecessary bias towards TST models training.

This paper presents LaMer, a novel self-supervised text style transfer framework built upon recent text-to-text language models (LMs). As illustrated in Figure 1 (b), rather than accepting the random mapping in the given non-parallel dataset, we first align sentences from source and target styles based on their scene graphs, and then run conditional MLE training on LM to maximize the probability of generating (roughly) parallel style sentences. As a final refinement step, we deploy reinforced imitation learning with contrastive loss on the aligned data to further reward the best transfer demonstration and penalize the others. In comparison with existing methods, LaMer fully exploits the intrinsic parallelism within non-parallel data and innovatively applies the transfer learning power of large-scale LMs to boost text-style transfer performance.

Our contributions can be outlined as follows:

- We present a language model based text style transfer framework, LAMER, that achieves significant advances in two existing benchmark TST tasks and one newly proposed challenging TST task. Human evaluations further confirm that LaMer generation is not only more readable but also richer in diverse expressions than previous methods.

- We propose a new challenging text style transfer task, *Political Stance Transfer*, and release a benchmark dataset, which includes news sentence-pairs describing the same fact but from opposite political stances (i.e., *liberal* and *conservative*). The stances of the sentences are labeled by expert human editors.

- As part of LaMer, we introduce a simple but powerful method to create parallel corpora from non-parallel data. We show that this method can be used as a general treatment to improve existing TST models. Given the abundance of non-parallel corpora for different TST tasks, this method has the potential to greatly impact the field of TST.

Our code and data will be released after publication with the MIT license. For reviewing purposes, we have included the code and data in the supplementary.

2 APPROACH

LaMer is comprised of three main steps. First, we mine (roughly) parallels target style expressions for each of the source style sentences based on their LM-based sentence embeddings and scene graphs (§2.2). Second, we deploy MLE training on the text-to-text LM BART (Lewis et al., 2020b) to maximize the probability of generating such roughly parallel sentences in target style (§2.3). Finally, we use imitation learning to further refine the generation with the self-supervision from the mined parallel demonstrations (§2.4).

2.1 NOTATION AND PROBLEM STATEMENT

For the task of binary text style transfer (src ↔ tgt), We denote the source and target style datasets as $\mathcal{D}^{\text{src}}$ and $\mathcal{D}^{\text{tgt}}$, which contain M and N sentences expressing two different styles respectively (i.e., $\mathcal{D}^{\text{src}} = \{s_1^{\text{src}}, s_2^{\text{src}}, ...s_M^{\text{src}}\}$, $\mathcal{D}^{\text{tgt}} = \{s_1^{\text{tgt}}, s_2^{\text{tgt}}, ...s_N^{\text{tgt}}\}$). We also denote the tokens in source and target sentences as $\{x_1, x_2, ..., x_t\} \in s_i^{\text{src}}$ and $\{y_1, y_2, ..., y_t\} \in s_j^{\text{tgt}}$, for given source and target sentences s_i^{src} and s_j^{tgt}. Given an input sentence s^{src} of the source style, an ideal style transfer model should be able to generate an appropriate, fluent target sentence $\hat{s}^{\text{tgt}}$, which is of the target style while maintaining the style-independent content.

Existing methods learn a mapping $f_{\text{random}} : \mathcal{D}^{\text{src}} \to \mathcal{D}^{\text{tgt}}$ without considering the self-parallelism between $\mathcal{D}^{\text{src}}$ and $\mathcal{D}^{\text{tgt}}$; LaMer, however, works on the assumption that $m(\leq M)$ sentences in $\mathcal{D}^{\text{src}}$ have n parallels in $\mathcal{D}^{\text{tgt}}$. The number of parallels n for each of the m sentences is variant but no more than N. Therefore, the goal of LaMer can be framed as first identifying a parallel subset of the original non-parallel dataset and learning a mapping on this dataset: $f_{\text{parallel}} : \mathcal{D}_m^{\text{src}} \to \mathcal{D}_n^{\text{tgt}}(m \leq M, n \leq N)$.

2.2 Mining (Roughly) Parallel Sentences

Figure 2: An example of aligned parallels by our scene graph based method. We _underline_ the scene entities and annotate how we compute d_{Order} and d_{Exist} with $\hat{s}^{\text{tgt+}}$ and $\hat{s}^{\text{tgt-}}$.

In this work, we argue that the *non-parallel* text style transfer datasets have inherent property of *parallelism*. We outline in the following three major strategies to mine roughly parallel sentences:

Random (RD). For each sentence $s^{\text{src}} \in \mathcal{D}^{\text{src}}$, randomly pick k sentences from $\mathcal{D}^{\text{tgt}}$ as parallels. This method mainly serves as an ablation to show the effectiveness of other strategies.

Sentence Embedding (S-Emb.). Sentences that only differ in linguistic style should have higher semantic similarity than other unrelated sentences. As a more advanced strategy, we leverage off-the-shelf LMs (e.g., RoBERTa (Liu et al., 2019)) to mine semantically similar sentences. We first encode every sentence in $\mathcal{D}^{\text{src}}$ and $\mathcal{D}^{\text{tgt}}$ with their embeddings extracted from an LM. Then, for each sentence $s^{\text{src}} \in \mathcal{D}^{\text{src}}$, we pick k most similar sentences from $\mathcal{D}^{\text{tgt}}$ through cosine similarity as parallels.

S-Emb. + Scene Alignment Score (S-Emb. + SAS). We add a scene graph based alignment step to the sentence embedding method to leverage shared entities between source and target sentences. Scene graph extraction has been successfully used in computer vision (Venugopalan et al., 2015; Chen et al., 2020b) to guide (Yang et al., 2020; Pan et al., 2020) or judge (Anderson et al., 2016) diverse caption generation. Inspired by the CV example and the observation that scene graphs of sentences with similar content but different styles tend to have overlapping nodes, our algorithm highlights the shared entities (nodes) of the sentence scene graph by running the scene graph parser released by Wu et al. (2019)[1], which outputs mined scenes graphs in **subject-relation-object** triplets. In our case, we only consider the end nodes of these triplets (which are ***subj.*** and ***obj.***) as the *scenes entities*. Figure 2 shows an example of mined sentences and corresponding scenes entities.

Let $|\mathbf{e}(s^{\text{src}})|$ and $|\mathbf{e}(s^{\text{tgt}})|$ be the number of scene entities extracted from the source and target style sentence, and $|\mathbf{e}(s^{\text{src} \cap \text{tgt}})|$ be the number of their overlaps, we compute $\underline{S}$cene $\underline{A}$lignment $\underline{S}$core (SAS) as:

$$\text{SAS}(s^{\text{src}}||s^{\text{tgt}}) = \frac{1}{|s^{\text{tgt}}|} \cdot \frac{(1 + \beta^2) \cdot \text{precision} \cdot \text{recall}}{\beta^2 \cdot \text{precision} + \text{recall}}, \tag{1}$$

where precision $(= \frac{|\mathbf{e}(s^{\text{src} \cap \text{tgt}})|}{|\mathbf{e}(s^{\text{tgt}})|})$ and recall $(= \frac{|\mathbf{e}(s^{\text{src} \cap \text{tgt}})|}{|\mathbf{e}(s^{\text{src}})|})$ describe the portion of target and source entities that are part of the overlap, and positive real factor β is chosen such that recall is considered β times as important as precision in a specific domain. We also normalize SAS by the length of s^{tgt}, since longer target sentence candidates are more likely to have higher SAS.

SAS serves as a complementary alignment metric to further filter the parallel sentences picked by the previous sentence-embedding-based metric. The complete procedure of S-Emb. + SAS alignment is:

1. Encode each sentence in $\mathcal{D}^{\text{src}}$ and $\mathcal{D}^{\text{tgt}}$ as sentence embeddings via a pre-trained LM.

2. Compute cosine similarity between all sentence pairs (s_i, s_j) where $s_i \in \mathcal{D}^{\text{src}}$ and $s_j \in \mathcal{D}^{\text{tgt}}$. Pick the k most similar sentences $s_j^{(k)}$ from $\mathcal{D}^{\text{tgt}}$ as parallel candidates for s_i.

---

[1]The scene graph parser can be found here: https://github.com/vacancy/SceneGraphParser

3. For each sentence $s_i \in \mathcal{D}^{\text{src}}$ and its parallel candidates $s_j^{(k)}$, compute pairwise SAS by Equation 1. Pick those s_j whose SAS scores (with respect to s_i) are above a threshold p as the final parallel sentences to s_i.

From empirical observations, we found that the selection of p and k is task-specific and has crucial effects on the performance of LaMer. We explore the outcomes of different choices of k and p in §3.3. Though SAS alignment LaMer relies on entity alignment for mining parallel corpora, other alignment mechanisms, such as (multilingual) LM alignment (i.e., the S-Emb. method) can potentially be used for transfer cases where entities may not be shared across styles (such as ancient v.s. modern English (Xu et al., 2012), or even multilingual text style transfer (Krishna et al., 2021)).

2.3 CONDITIONAL TOKEN-LEVEL MLE TRAINING

After mining parallel sentences for a source sentence s^{src}, from our corpus, we take the source sentence s^{src} as the condition, and preform a conditional token-level MLE training on the mined parallels in the manner of standard autoregressive pre-training. Assuming for a certain source sentence s^{src} we have n target parallels mined in the previous step (i.e., $s^{\text{src}} \rightarrow \{s_1^{\text{tgt}}, s_2^{\text{tgt}}, ...s_n^{\text{tgt}}\}, n \leq N$), the MLE loss can be computed as:

$$J_{\text{MLE}} = -\sum_{i=1}^{n} \sum_{t=1}^{|s_k^{\text{tgt}}|} y_t^{(i)} \log \text{LM}(y_{1:t-1}|s^{\text{src}}), \tag{2}$$

where $y_t^i \in s_i^{\text{tgt}}$ denotes the i-th step ground truth token belonging to the i-th target parallel sentence. $\text{LM}(y_{1:t-1}|s^{\text{src}})$ is the LM output at t-th step (a distribution on the vocabulary) given the source text and previous generation. We choose BART Lewis et al. (2020b) as the LM, which is already pre-trained on several text-to-text tasks, and concatenate the source and target text with tokens pre-defined by BART as input data. At each step, with the supervision of ground truth target tokens $y_t^{(i)}$, we minimize the MLE loss only at the target part. The LM is thus trained to maximize the probability of generating tokens $\hat{y}_t$ approaching to $y_t^{(i)}$.

Though the results produced are reasonable, solely relying on MLE training has several defects. First, MLE treats all parallels of a certain source equally without penalizing low-quality demonstrations, which not only makes the model less robust on noisy data, but also possible to be misled by negative samples during local optimization. Second, token-level MLE does not pay special attention to scene entities shared between the source and target, which we found take up the main portion in the human written references (as demonstrated in §A.3). We are thus motivated to further improve the performance using the self-supervision from the parallels.

2.4 REINFORCED IMITATION LEARNING BY CONTRAST

For all the mined target style parallels s^{tgt} of s^{src}, we denote the one that has the highest similarity score (with S-Emb.) or has the highest SAS (with S-Emb. + SAS) as the expert demonstration $s^{\text{tgt+}}$, while the others are set as $s^{\text{tgt-}}$.

In the formulation of reinforcement learning, at each step t, the policy π_θ observes the state $y_{1:t-1}$ (partially generated text), takes an action $a_t = y_t$ (pick a token), and transits to the next state $y_{1:t}$. In the context of TST tasks, the policy can be interpreted as the LM-based generation model: $\hat{\pi} \sim \text{LM}(a_t|y_{1:t-1}, s^{\text{src}})$, and the set of $s^{\text{tgt+}}$ can be seen as the trajectory derived from an expert policy π^+, while $s^{\text{tgt-}}$ is produced by an amateur policy π^-. The goal of this step imitation learning can thus be framed as learning a policy that has more probability to behave like π^+ rather than π^-, which can be achieved by minimizing the contrastive loss:

$$J_{\text{IL}} = \max(\psi^* [\pi^+, \hat{\pi}] - \psi^* [\pi^-, \hat{\pi}] + \Delta, 0), \tag{3}$$

where $\psi^*(\cdot)$ is the distance measurement of two policies in terms of semantic coherence $d_{\text{SEM}}(\cdot)$ and scene preservation $d_{\text{PSV}}(\cdot)$, such that $\psi^*(\cdot) = d_{\text{SEM}}(\cdot) + d_{\text{PSV}}(\cdot)$; and Δ is a hyperparameter that controls the contrasting margin. The general form is inspired by the triplet loss (Schroff et al., 2015)

and recent *in-batch* constrastive learning (Gao et al., 2021): we encourage the learned policy $\hat{\pi}$ to be more similar to the expert one π^+ than the amateur one π^- by at least margin Δ. $d_{\text{SEM}}(\cdot)$ and $d_{\text{PSV}}(\cdot)$ are detailed below.

Sequence-level Semantic Coherence   For sequence $\hat{s}$ generated under current learning policy $\hat{\pi}$ and a certain target style demonstration s^{tgt}, we encode them using bi-directional LM RoBERTa (Liu et al., 2019), which is widely used as sentence encoder in related work (Reimers & Gurevych, 2019; Li et al., 2020). Then, we take their negative cosine similarity as the distance for semantic coherence: $d_{\text{SEM}} = -\frac{\text{emb}_{\hat{s}}^{\text{T}} \cdot \text{emb}_{s^{\text{tgt}}}}{\|\text{emb}_{\hat{s}}\| \|\text{emb}_{s^{\text{tgt}}}\|}$. Lower value in d_{SEM} means the learned policy $\hat{\pi}$ can produce similar quality sequences in terms of semantics as target style demonstrations. It is a sequence-level measurement since the encoding is based on the whole sentence.

Token-level Scene Preservation   In our context, legitimate target style parallels should preserve most scene entities that appear in source style sentences. To explicitly promote the content preservation performance of the current policy, we introduce a token-level distance d_{PSV}. We first extract scene entities from $s^{\text{tgt}+}$ and each of the $s^{\text{tgt}-}$, and then measure the differences in both the order of appearance of the entities and the existence of the entities. Taking $s^{\text{tgt}+}$ as an example (similar calculation is done on each of the $s^{\text{tgt}\text{-}}$), we compute: $d_{\text{PSV}+} = \alpha d_{\text{Order}+} + (1-\alpha) d_{\text{Exist}+} = \alpha \|\vec{e}(s^{\text{tgt}+}), \vec{e}(s^{\text{src}})\|_{\text{Lev.}} + (1-\alpha)\|\vec{e}(s^{\text{tgt}+}) - \vec{e}(s^{\text{tgt}+ \cup \text{ src}})\|_H^2$, where $\vec{e}(\cdot)$ means the extracted scene entities, $\vec{e}(\cdot)$ is its one-hot encoded vector, $\|\vec{x}, \vec{y}\|_{\text{Lev.}}$ measures Levenshtein distance (Yujian & Bo, 2007), one type of edit distance, and for vectors $\vec{e}(s^{\text{src}})$ and $\vec{e}(s^{\text{tgt}})$, we compute their hamming distance[3] (Norouzi et al., 2012). Lower $d_{\text{Order}+}$ means the appearing order of $\vec{e}(s^{\text{src}})$ resemble $\vec{e}(s^{\text{tgt}+})$. Similarly, lower $d_{\text{Exist}+}$ means $\vec{e}(s^{\text{src}})$ and $\vec{e}(s^{\text{tgt}+})$ are mostly overlapped. Similar procedure applies to $d_{\text{PSV}-}$ as well. We present more details about how we compute these distances in §A.4.

2.4.1 POLICY GRADIENT BY REINFORCE

We choose the REINFORCE algorithm (Williams, 1992) to optimize the current policy π_θ. As shown in Equation 4, we use greedy decoding results as the baseline (Rennie et al., 2017), and sampling decoding for the exploration step, which mimics the *actor-critic* manner in reinforcement learning (Fujimoto et al., 2018; Haarnoja et al., 2018). The policy gradient can thus be presented as:

$$\nabla_\theta J(\theta) = -\mathbb{E}_{\pi_\theta}\left[\nabla_\theta \log \pi_\theta \cdot (J_{\text{IL}}^{\text{sample}}(s^{\text{tgt}+}, s^{\text{tgt}\text{-}}) - J_{\text{IL}}^{\text{greedy}}(s^{\text{tgt}+}, s^{\text{tgt}\text{-}}))\right], \tag{4}$$

where $J_{\text{IL}}^{\text{sample}}$ and $J_{\text{IL}}^{\text{greedy}}$ can be both calculated by Equation 3. We take the difference of two the mode rewards as the advantage, feeding into the REINFORCE algorithm to optimize our policy π_θ. Finally, the output policy π_θ is able to generate style transferred sequences resembling the expert demonstrations $s^{\text{tgt}+}$. More details about the complete loop of policy gradient can be found in §A.5

Discussion: Imitation Learning, Reward-based RL, and MLE.   Framing token-by-token text generation as a sequential decision-making process, many models choose reinforcement learning (RL) as the training strategy because of its superior performance in discrete action space optimization (Vinyals et al., 2019; Silver et al., 2017). By directly setting indifferentiable evaluation metrics such as BLEU (Papineni et al., 2002) or ROUGE (Lin, 2004) as the reward function (Xu et al., 2018; Gong et al., 2019) or using domain-specific reward such as trained discriminator outputs (Lin et al., 2020; Scialom et al., 2020), existing RL-based methods show promising results in both generation quality (Chen et al., 2020a; Li et al., 2018b) and diversity (Li et al., 2016).

In the context of TST tasks, however, instead of reward-based RL, we argue imitation learning (IL) is a better choice, since: 1) Compared with fixed environment settings like chess games, it is challenging to design a uniform reward fitting a variety of source style text that can produce meaningful guidance towards contextually correct and semantically coherent direction during generation. 2) It is also unnecessary to calculate an elaborately designed reward. The roughly parallel target style sentences mined in the alignment step can naturally serve as expert demonstrations. They are high-quality and cost-free, which can greatly improve the sampling and learning efficiency of RL optimization.

---

[2]α controls the weights assigned to d_{Order} and d_{Exist}. We use $\alpha = \{0.4, 0.3, 0.1\}$ for the three TST tasks.

[3]Hamming norm $\|\vec{v}\|_H$ is defined as the number of non-zero entries of vector $\vec{v}$.

A common obstacle of IL is known as *covariate shift* (Ross & Bagnell, 2010), which means IL can provide a relatively good performance for the test cases similar to the demonstrations (used for policy training), but it could still suffer from bad generalization for cases it never meets during training, as the number of demonstrations is finite. Similar problems called *exposure bias* (Bengio et al., 2015; Ranzato et al., 2016) also exists in MLE when the supervised data is scarce. We claim our token-level MLE training on LMs can somewhat mitigate such problems, since the large-scale LMs are already pre-trained on huge quantities of data across many domains *as a prior*.

3 EXPERIMENTS

3.1 DATASETS AND EXPERIMENTAL SETUP

Sentiment Transfer. We use the Yelp reviews dataset collected by Shen et al. (2017) which contains 250k negative sentences and 380k positive sentences, organized in non-parallel fashion. Li et al. (2018a) released a small test set that has 500 human written references for both target sentiments, and they are already one-on-one aligned with the source sentiment sentences.

Formality Transfer. A more challenging TST task is to modify the formality of a given sentence. We use the GYAFC dataset (Rao & Tetreault, 2018), which contains formal and informal sentences from two domains. In this paper, we choose the Family Relationship domain, which consists of about 52k training sentences, 5k development sentences, and 2.5k test sentences. Different from the Yelp dataset, the test set of GYAFC has four human written references for each source style test case. Our evaluation results for this task are reported as the average against the four references.

Political Stance Transfer. News outlets reporting the same event naturally meet the requirement of style transfer data, which is aligned in content but different in style. We leverage Allsides.com[4] as an aggregator, where outlets reporting the same events with different political stances are already organized and labeled by expert human editors. In total, we collect 2,298 full-length news articles from 6/1/2012 to 4/1/2021 in pairs of liberal-conservative leaning. Though the data seems parallel at the article level, in this work we focus on sentence level TST. We further split the articles into about 56k sentence pairs as a non-parallel dataset for training (detailed in §A.2). These titles are written by expert writers from liberal- or conservative-learning media outlets, and aligned by the Allsides editors. For ethical consideration, we manually examined the articles to removing those containing sensitive topics (such as hate speech). To adhere to the outlets' TOS, we will release our dataset as links to the articles (instead of the text), with the appropriate code to extract the content for training purposes. A closer comparison of our proposed novel dataset with another political stance TST dataset (Voigt et al., 2018) can be found in §A.1.

The detailed statistics of all three benchmark datasets and our experimental setup can be found in §A.3. We have discussed the hyperparameter selection for the best performing LaMer in §3.3.

3.2 MAIN RESULTS ON TEXT STYLE TRANSFER PERFORMANCE

TST models should be able to transfer source style sentence to a target style, while maintaining the style-independent content as much as possible. Most existing works evaluate their methods with transfer accuracy (ACC; classification accuracy) and content-preservation (BLEU-*ref*; token overlaps with reference). In this work, besides using ACC and BLEU-*ref*, we also report more advanced metrics–SIM and FL introduced by Krishna et al. (2020)–to further evaluate our method.

LaMer has the best overall performance. Table 1 shows the main results comparing LaMer with eight popular TST models on the three benchmark datasets. Following prior art, in addition to the independent ACC and BLEU score[5], we report their geometric mean (GM) as an overall metric of style transfer performance (Lee et al., 2021; Luo et al., 2019). We also consider inverse PINC scores (Chen & Dolan, 2011)—i-PINC—as a complementary metric of BLEU. i-PINC counts the n-gram overlaps after removing the tokens shared between source and target style sentences, and thus properly penalizes the Input Copy method (i-PINC = 0).

---

[4] https://www.allsides.com/story/admin
[5] We use BLEU-*ref*, which computes average n-gram BLEU (n ranges from 1 to 4).

Table 1: LaMer achieves best overall performance in three TST tasks. CAE (Shen et al., 2017), DelRetrGen (Li et al., 2018a), DualRL (Luo et al., 2019), Style Transformer (Dai et al., 2019), Deep Latent Seq (He et al., 2020) are popular TST models *not* built on LMs. TSF-DelRetGen (Sudhakar et al., 2019), IMaT (Jin et al., 2019), and STRAP (Krishna et al., 2020) are recent LM-based TST models. For ablation, Input Copy directly copies the source style sentence as the transfer output. GM: Geometric Mean of Transfer Accuracy (ACC) and BLEU. *i*-PINC measures net transfer ability by not counting words that can be directly copied from the source style sentence, as discussed in §3.2. We color (■ ■ ■) the best overall results, and underline those that obtain the second best.

	■ Sentiment SAS = 0.73				■ Formality SAS = 0.29				■ Political Stance SAS = 0.30			
Existing Methods	ACC	BLEU	**GM**	*i*-**PINC**	ACC	BLEU	**GM**	*i*-**PINC**	ACC	BLEU	**GM**	*i*-**PINC**
Input Copy (*ref.*)	7.4	61.7	21.4	0	1.9	54.6	10.2	0	7.5	17.8	11.6	0
CAE	70.5	6.0	20.6	1.2	39.5	35.8	37.6	5.9	31.5	5.1	12.7	1.4
DelRetrGen	65.4	11.8	27.8	4.8	61.9	14.8	30.3	6.6	93.8	3.5	18.1	6.2
Dual RL	85.6	21.2	42.5	4.0	71.1	31.9	47.9	7.2	91.8	8.1	27.3	5.7
Style Transformer	93.6	17.1	40.0	5.2	72.2	32.7	48.6	4.1	48.6	7.3	18.8	1.1
Deep Latent Seq	87.9	18.7	40.5	7.3	80.5	18.5	38.6	6.1	85.8	20.8	42.2	3.0
LM-based												
TSF-DelRetGen	89.5	31.7	53.3	4.5	79.3	17.4	37.1	7.3	65.8	23.7	39.5	2.9
IMaT	95.9	22.5	46.5	3.3	72.1	28.2	45.1	12.7	82.9	19.5	40.2	5.3
STARP	92.3	32.5	54.8	6.4	75.4	32.6	49.6	9.7	84.3	21.3	42.4	5.0
Ours: LaMer												
w/. RD	97.1	19.8	43.8	2.5	64.2	20.4	36.2	5.5	75.9	10.1	27.7	6.1
w/. S-Emb.	90.1	40.6	60.5	5.6	65.1	33.8	46.9	10.9	78.2	22.1	41.6	9.2
w/. S-Emb. + SAS	97.0	34.1	57.5	9.6	76.5	39.2	54.8	13.3	82.7	30.5	50.2	13.6

Compared with existing methods, LaMer is the best performing method in terms of overall metric GM, and shows particularly strong *net* transfer ability (since *i*-PINC does not count duplicated tokens between s^{src} and s^{tgt}). Among the three mining strategies we proposed in §2.2, the S-Emb. + SAS seems to offer the best performance boosting in terms of content preservation, but shows no clear advantage on style control accuracy. When comparing LaMer with the three LM-based models, we find the advantage of LaMer mainly comes from the gain in content preservation (BLEU), which demonstrates the effectiveness of our scene graph alignment.

Table 2: Few-shot performance on Formality TST (only 1% training data available) of LaMer and other LM-based baselines. We also include a zero-shot TST method built on GPT-3 (Reif et al., 2021) for reference. We annotate standard deviation next to the results as well.

Training Data (%)	1% (0% for GPT3)				100%			
Method	ACC	SIM	FL	$J_{A,S,F}$	ACC	SIM	FL	$J_{A,S,F}$
TSF-DelRetGen	$16.5_{1.4}$	$5.5_{1.9}$	$90.3_{0.1}$	$2.6_{1.1}$	$54.1_{1.4}$	$30.5_{0.8}$	$98.9_{0.1}$	$29.7_{0.5}$
IMaT	$35.9_{0.4}$	$22.1_{0.2}$	$23.0_{0.4}$	$3.2_{0.7}$	$59.5_{1.2}$	$39.7_{1.1}$	$99.6_{0.1}$	$37.4_{0.2}$
STARP	$37.7_{0.7}$	$12.5_{0.9}$	$70.4_{0.2}$	$5.3_{0.4}$	$67.7_{1.2}$	$72.5_{1.1}$	$90.4_{0.7}$	$45.5_{1.2}$
Ours: LaMer	$48.8_{0.4}$	$27.4_{0.6}$	$89.8_{0.1}$	$\mathbf{13.5_{0.3}}$	$66.4_{0.5}$	$74.3_{0.3}$	$97.8_{0.1}$	$\mathbf{53.2_{0.1}}$
GPT-3 prompt TST	$10.2_{0.6}$	$17.1_{1.1}$	$98.0_{0.2}$	$6.5_{0.4}$	–	–	–	–

Table 3: Compared with other baselines, LaMer requires neither extra data nor training additional models.

Ext. Resource?	Data	Model
TSF-DelRetGen	✓	✓
IMaT	✓	✗
STARP	✓	✓
Ours: LaMer	✗	✗
GPT-3 prompt TST	✗	✗

LaMer is robust in few-shot settings. LaMer learns the inherent parallelism within the unsupervised data, which could be challenging in data scarce cases. Recent works have explored the limits of TST in few-shot settings (Riley et al., 2021; Krishna et al., 2021), we conduct similar studies by limiting the available training data (to 1%), aiming to answer whether or not LaMer can still provide comparable performance as others. We consider LM-based baselines which show strong results in Table 1. We also compare with a zero-shot prompt-based TST baseline built upon GPT-3 (Reif et al., 2021) for reference. For evaluation metrics, we use the recently proposed *J*-score framework (including ACCuracy, SIMilarity, and FLuency) (Krishna et al., 2020), which solves many of the

Figure 3: Effect on performance when choosing different k and p for S-Emb. + SAS alignment. We also annotate (with a star) the recommended settings which reaches best balance between style control accuracy and content preservation BLEU score.

issues in existing metrics [6]. As shown in Table 2, we find that LaMer achieves great performance (J-score) in few-shot cases, partially because other baselines rely on external systems trained on ample data;[7] In extreme data hungry cases, the compromised external modules would propagate errors to following parts as they are coupled. LaMer, instead, requires neither extra data nor additional training on external systems (See Table 3), but fully leverages the self-supervision hidden in the unsupervised data, which achieves robust performance even in few-shot scenarios.

IL refinement is crucial for LaMer content preservation. As shown in Table 4, the BLEU score for LaMer drops substantially when the imitation learning refinement stage is totally removed (No IL, MLE only), and we find this drop is higher for challenging style tasks (such as political stance transfer), partially because the quality variance of their demonstrations is higher, i.e., a further guidance towards good demonstrations will make a big difference. We also conducted further ablation studies on components of IL: In general, removing d_{Order} seems to cause greater performance drop in formality TST, while d_{Exist} seems important to successful political stance TST. Removing all scene preservation distance sub-components (i.e., IL (d_{SEM})) leads to noticeable performance deterioration across all three TST tasks. We take these ablation study results as evidence that the technologies we propose for LaMer are all crucial.

Table 4: Further ablation on components of LaMer imitation learning (IL). d_{SEM}: semantic coherence distance, d_{Order} and d_{Exist} are sub-components of scene preservation distance d_{PSV}. Removing all IL modules (MLE only) will cause severe drop in content preservation (BLEU), especially for challenging TST tasks (Formality and Political Stance TST).

	Sentiment		Formality		Political Stance	
Ablation on LaMer IL	ACC	BLEU	ACC	BLEU	ACC	BLEU
IL ($d_{\text{SEM}} + d_{\text{Order}} + d_{\text{Exist}}$)	97.0	34.1	76.5	39.2	93.4	18.5
IL ($d_{\text{SEM}} + d_{\text{Order}}$)	95.5 ($\downarrow$1.5)	34.4 ($\uparrow$0.3)	74.7 ($\downarrow$1.8)	37.7 ($\downarrow$1.5)	93.2 ($\downarrow$0.2)	15.8 ($\downarrow$2.7)
IL ($d_{\text{SEM}} + d_{\text{Exist}}$)	96.5 ($\downarrow$0.5)	33.9 ($\downarrow$0.2)	72.6 ($\downarrow$3.9)	34.1 ($\downarrow$5.1)	92.7 ($\downarrow$0.7)	17.1 ($\downarrow$1.4)
IL (d_{SEM})	95.1 ($\downarrow$1.9)	33.3 ($\downarrow$0.8)	71.9 ($\downarrow$4.6)	32.5 ($\downarrow$6.7)	89.9 ($\downarrow$0.5)	13.9 ($\downarrow$4.6)
No IL (MLE Only)	93.1 ($\downarrow$3.9)	33.2 ($\downarrow$0.9)	68.7 ($\downarrow$7.8)	27.2 ($\downarrow$12.0)	89.8 ($\downarrow$0.6)	8.8 ($\downarrow$9.7)

3.3 CONFIGURING LAMER

The filtering parameter p and k are hyperparameters that are crucial for the construction of roughly parallel datasets. Thus, for all three TST tasks, we evaluate LaMer performance given different combination of p and k, as shown in Figure 3. We find there is a approximate trade-off relationship between style control accuracy and content preservation BLEU score: In general, higher k (more parallels) seems to improve accuracy but normally has lower BLEU, while for a fixed k, a proper p can be reached empirically. We annotate the recommended settings of p and k for the three TST

---

[6]E.g., BLEU score can be artificially high when directly copying source style sentence as the target style generation, and perplexity is unbounded and discourages creative TST generation.

[7]E.g., TSF-DelRetGen requires training a classifier to locate style-carrying spans of text. STARP fine-tunes a GPT-2 model to learn how to paraphrase. IMaT trains a plain Seq2Seq model from scratch as an LM (not pre-trained).

tasks we studied in this work. We provide some generation samples of LaMer (and other methods) in Table 8 of §A.6. As an interesting observation, we find the alignment procedure of LaMer can benefit other methods (as shown in Table 11 of §A.8).

3.4 HUMAN EVALUATION

We conducted human evaluation to answer: 1) *"How good is LaMer's SAS alignment?"*, and 2) *"How is the quality of the style-transferred sentences?"* (The exact questions and procedures are details in §A.7.). We recruited 212 participants from MTurk. Most annotators agreed that SAS-aligned pairs share similar style-independent content (Table 5). We conducted several one-way ANOVAs to test the difference among the seven baselines and LaMer (political stance TST results shown in Table 6; see Table 9 for sentiment TST and Table 10 for formality TST in §A.7). LaMer was significantly better than next-best in all three perspectives ($p < .05$), and had the most ratings that where ≥ 5.

Table 5: Effectiveness of SAS alignment for mining weakly parallel sentences. Similarity: *"How much the mined pairs are similar in style-independent content?"* SAS Align: *"How well SAS scores reflect such similarity?"* Ratings are on a 7 point scale. All$_{\geq 4}$: The ratio for which the ratings are ≥ 4 for both questions.

TST Tasks	Similarity Mean$_{SD}$	SAS Mean$_{SD}$	All$_{\geq 4}$
Sentiment	$5.42_{1.36}$	$5.56_{1.17}$	88%
Formality	$5.58_{1.14}$	$5.74_{1.09}$	82%
Political	$5.45_{1.17}$	$5.43_{1.16}$	74%

Table 6: Human evaluations on the political stance transfer task (on a 7 point scale). We **bold** the highest average rating. LaMer was rated significantly higher than the underline{next-best} method ($p < .05$). All$_{\geq 5}$: The ratio for which the ratings are ≥ 5 for all three perspectives.

◾ Political Stance	Style		Content		Readability		
Methods	Mean	SD	Mean	SD	Mean	SD	All$_{\geq 5}$
CAE	4.91	1.59	4.85	1.58	5.04	1.68	12%
DelRetrGen	5.14	1.60	4.93	1.63	4.96	1.60	11%
Dual RL	5.15	1.37	4.87	1.59	5.15	1.53	27%
Style Transformer	5.31	1.19	5.34	1.36	5.18	1.40	28%
Deep Latent Seq	5.42	0.57	5.29	1.20	5.30	1.26	25%
TSF-DelRetGen	4.87	0.65	5.23	1.14	5.20	1.13	15%
STARP	5.33	1.25	5.31	1.40	5.43	1.07	21%
Ours: LaMer	**5.59**	1.17	**5.44**	1.11	**5.56**	1.05	37%

4 RELATED WORK

Other Text Style Transfer Methods. Besides the baselines we have studies in the paper, we notice there are other TST methods focusing on either latent vector manipulation (Liu et al., 2020; Wang et al., 2019; John et al., 2019) or surface level editing (Castro et al., 2017; Karadzhov et al., 2017; Mansoorizadeh et al.). LaMer differs from them as it is learning to transfer with self-supervision mined from the unsupervised data, without complicated manipulation or editing.

NLG by Searching for References. To provide expert demonstrations to enhance LM generation, recent work attempt to retrieve related documents from external resources (e.g., Wikipedia) as training data augmentations (Lewis et al., 2020c; Guu et al., 2020; Lee et al., 2019; Lewis et al., 2020a). LaMer does not rely on any external resources, but mines parallel demonstrations from the training data itself, and thus is easier to deploy and alleviates potential bias.

5 CONCLUSION

We have proposed LaMer, a self-supervised text style transfer method built on large-scale LMs. LaMer demonstrates the potential of leveraging self-parallelism within large non-parallel corpora, which can guide efficient TST models development or even LM design. On three diverse TST tasks, we show that LaMer performs better than eight existing methods while being robust to data scarcity. Human evaluations further validate the advantage of our model compared to existing baselines.

Future work of LaMer could study how to extend to multilingual scenarios, or transfer the style that essentially changes the form of language (e.g., ancient v.s. modern English). One could also investigate combining the alignment module of LaMer with the text2text LM in one model, and jointly train to further boost the performance.

6 ETHICS AND REPRODUCIBILITY STATEMENT

The goal of LaMer is to provide a simple but efficient general-purpose text style transfer framework by leveraging large-scale pre-trained LMs. LaMer can generate text in a specified target style given source style input, which can serve as a useful tool for social good. For example, LaMer can assist language formalization (formality transfer), enable data anonymization (writing style transfer), or depolarize politically biased text (political stance transfer), via transferring the identifiable style of the input text.

The performance of LaMer depends on the pre-trained LM, which means that the generation of LaMer can be affected by certain societal biases found in the pre-trained LM it is based on (e.g., BART) (Blodgett et al., 2020). Other negatives such as abusive language (Hancock et al., 2020), hate speech (Kennedy et al., 2018), and dehumanization (Mendelsohn et al., 2020) are also prevalent in the language data for LM pre-training. When deployed in real-world settings, LaMer may increase the risk of reinforcing and propagating polarizing and toxic language in public space through people's dissemination (Waseem et al., 2017). Moreover, the generated text of LaMer could potentially be included in the next iteration of large-scale LM training data collection, which may amplify offensive stereotypes and overtly abusive views in the future LMs.

Though LaMer was developed as an "neutral" tool mainly for research purposes, it can also be used in malicious ways such as generating sophisticated spam in a particular style "disguise", which we strongly discourage. Due to the lack of fact checking systems as a safety measure, LaMer is at the risk of generating seemingly coherent but counterfactual text in a certain target style, which could further undermine social trust in computer-mediated forms of communication [6]. We thus recommend the users of LaMer to integrate necessary safety checks into the actual systems.

In addition, our experiments and analysis are done when source and target style sentences are both in English, and therefore we do not claim that our findings will generalize across all languages, although our framework has the potential to be extended to other languages with necessary modifications.

Though it's beyond the scope of this paper and our individual ability to address all above-mentioned complications, we strongly encourage users of our system (and other TST models and systems based on pre-trained language models) to acknowledge and beware of these issues.

For reproducibility, we attach our code, evaluation scripts, and sample generation with our submission to aid reviewing. The full political stance transfer dataset we proposed will be made publicly available after review process.

REFERENCES

Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould. Spice: Semantic propositional image caption evaluation. In *European conference on computer vision*, pp. 382–398. Springer, 2016.

Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pp. 1171–1179, 2015. URL https://proceedings.neurips.cc/paper/2015/hash/e995f98d56967d946471af29d7bf99f1-Abstract.html.

Su Lin Blodgett, Solon Barocas, Hal Daumé III, and Hanna Wallach. Language (technology) is power: A critical survey of "bias" in NLP. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5454–5476, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.485. URL https://www.aclweb.org/anthology/2020.acl-main.485.

Daniel Castro, Reynier Ortega, and Rafael Muñoz. Author masking by sentence transformation—notebook for pan at clef 2017. In *CLEF 2017 Evaluation Labs and Workshop–Working Notes Papers*, pp. 11–14, 2017.

David Chen and William Dolan. Collecting highly parallel data for paraphrase evaluation. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pp. 190–200, Portland, Oregon, USA, 2011. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P11-1020.

Liqun Chen, Ke Bai, Chenyang Tao, Yizhe Zhang, Guoyin Wang, Wenlin Wang, Ricardo Henao, and Lawrence Carin. Sequence generation with optimal-transport-enhanced reinforcement learning. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 7512–7520. AAAI Press, 2020a. URL https://aaai.org/ojs/index.php/AAAI/article/view/6249.

Shizhe Chen, Qin Jin, Peng Wang, and Qi Wu. Say as you wish: Fine-grained control of image caption generation with abstract scene graphs. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 9959–9968. IEEE, 2020b. doi: 10.1109/CVPR42600.2020.00998. URL https://doi.org/10.1109/CVPR42600.2020.00998.

Ning Dai, Jianze Liang, Xipeng Qiu, and Xuanjing Huang. Style transformer: Unpaired text style transfer without disentangled latent representation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 5997–6007, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1601. URL https://www.aclweb.org/anthology/P19-1601.

Yao Fu, Yansong Feng, and John P. Cunningham. Paraphrase generation with latent bag of words. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 13623–13634, 2019a. URL https://proceedings.neurips.cc/paper/2019/hash/5e2b66750529d8ae895ad2591118466f-Abstract.html.

Yao Fu, Hao Zhou, Jiaze Chen, and Lei Li. Rethinking text attribute transfer: A lexical analysis. In *Proceedings of the 12th International Conference on Natural Language Generation*, pp. 24–33, Tokyo, Japan, 2019b. Association for Computational Linguistics. doi: 10.18653/v1/W19-8604. URL https://www.aclweb.org/anthology/W19-8604.

Zhenxin Fu, Xiaoye Tan, Nanyun Peng, Dongyan Zhao, and Rui Yan. Style transfer in text: Exploration and evaluation. In Sheila A. McIlraith and Kilian Q. Weinberger (eds.), *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pp. 663–670. AAAI Press, 2018. URL https://www.aaai.org/ocs/index.php/AAAI/AAAI18/paper/view/17015.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1582–1591. PMLR, 2018. URL http://proceedings.mlr.press/v80/fujimoto18a.html.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*, 2021.

Hongyu Gong, Suma Bhat, Lingfei Wu, JinJun Xiong, and Wen-mei Hwu. Reinforcement learning based text style transfer without parallel training corpus. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 3168–3180, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1320. URL https://www.aclweb.org/anthology/N19-1320.

Francis Grégoire and Philippe Langlais. Extracting parallel sentences with bidirectional recurrent neural networks to improve machine translation. In *Proceedings of the 27th International Conference on Computational Linguistics*, pp. 1442–1453, Santa Fe, New Mexico, USA, 2018. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/C18-1122.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Ming-Wei Chang. Retrieval augmented language model pre-training. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 3929–3938. PMLR, 2020. URL http://proceedings.mlr.press/v119/guu20a.html.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1856–1865. PMLR, 2018. URL http://proceedings.mlr.press/v80/haarnoja18b.html.

Jeffrey T Hancock, Mor Naaman, and Karen Levy. Ai-mediated communication: definition, research agenda, and ethical considerations. *Journal of Computer-Mediated Communication*, 25(1):89–100, 2020.

Junxian He, Xinyi Wang, Graham Neubig, and Taylor Berg-Kirkpatrick. A probabilistic formulation of unsupervised text style transfer. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=HJlA0C4tPS.

J. Edward Hu, Rachel Rudinger, Matt Post, and Benjamin Van Durme. PARABANK: monolingual bitext generation and sentential paraphrasing via lexically-constrained neural machine translation. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pp. 6521–6528. AAAI Press, 2019. doi: 10.1609/aaai.v33i01.33016521. URL https://doi.org/10.1609/aaai.v33i01.33016521.

Zhijing Jin, Di Jin, Jonas Mueller, Nicholas Matthews, and Enrico Santus. IMaT: Unsupervised text attribute transfer via iterative matching and translation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3097–3109, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1306. URL https://www.aclweb.org/anthology/D19-1306.

Vineet John, Lili Mou, Hareesh Bahuleyan, and Olga Vechtomova. Disentangled representation learning for non-parallel text style transfer. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 424–434, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1041. URL https://www.aclweb.org/anthology/P19-1041.

Georgi Karadzhov, Tsvetomila Mihaylova, Yasen Kiprov, Georgi Georgiev, Ivan Koychev, and Preslav Nakov. The case for being average: A mediocrity approach to style masking and author obfuscation. In *International Conference of the Cross-Language Evaluation Forum for European Languages*, pp. 173–185. Springer, 2017.

Brendan Kennedy, Drew Kogon, Kris Coombs, Joseph Hoover, Christina Park, Gwenyth Portillo-Wightman, Aida Mostafazadeh Davani, Mohammad Atari, and Morteza Dehghani. A typology and coding manual for the study of hate-based rhetoric. *PsyArXiv. July*, 18, 2018.

Kalpesh Krishna, John Wieting, and Mohit Iyyer. Reformulating unsupervised style transfer as paraphrase generation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 737–762, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.55. URL https://www.aclweb.org/anthology/2020.emnlp-main.55.

Kalpesh Krishna, Deepak Nathani, Xavier Garcia, Bidisha Samanta, and Partha Talukdar. Few-shot controllable style transfer for low-resource settings: A study in indian languages. *ArXiv preprint*, abs/2110.07385, 2021. URL https://arxiv.org/abs/2110.07385.

Dongkyu Lee, Zhiliang Tian, Lanqing Xue, and Nevin L. Zhang. Enhancing content preservation in text style transfer using reverse attention and conditional layer normalization. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 93–102, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.8. URL https://aclanthology.org/2021.acl-long.8.

Kenton Lee, Ming-Wei Chang, and Kristina Toutanova. Latent retrieval for weakly supervised open domain question answering. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 6086–6096, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1612. URL https://www.aclweb.org/anthology/P19-1612.

Mike Lewis, Marjan Ghazvininejad, Gargi Ghosh, Armen Aghajanyan, Sida Wang, and Luke Zettlemoyer. Pre-training via paraphrasing. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020a. URL https://proceedings.neurips.cc/paper/2020/hash/d6f1dd034aabde7657e6680444ceff62-Abstract.html.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7871–7880, Online, 2020b. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.703. URL https://www.aclweb.org/anthology/2020.acl-main.703.

Patrick S. H. Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020c. URL https://proceedings.neurips.cc/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html.

Jingjing Li, Zichao Li, Lili Mou, Xin Jiang, Michael R. Lyu, and Irwin King. Unsupervised text generation by learning from search. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/7a677bb4477ae2dd371add568dd19e23-Abstract.html.

Jiwei Li, Will Monroe, Alan Ritter, Dan Jurafsky, Michel Galley, and Jianfeng Gao. Deep reinforcement learning for dialogue generation. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 1192–1202, Austin, Texas, 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1127. URL https://www.aclweb.org/anthology/D16-1127.

Juncen Li, Robin Jia, He He, and Percy Liang. Delete, retrieve, generate: a simple approach to sentiment and style transfer. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1865–1874, New Orleans, Louisiana, 2018a. Association for Computational Linguistics. doi: 10.18653/v1/N18-1169. URL https://www.aclweb.org/anthology/N18-1169.

Zichao Li, Xin Jiang, Lifeng Shang, and Hang Li. Paraphrase generation with deep reinforcement learning. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language*

Processing, pp. 3865–3878, Brussels, Belgium, 2018b. Association for Computational Linguistics. doi: 10.18653/v1/D18-1421. URL https://www.aclweb.org/anthology/D18-1421.

Alexander Lin, Jeremy Wohlwend, Howard Chen, and Tao Lei. Autoregressive knowledge distillation through imitation learning. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6121–6133, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.494. URL https://www.aclweb.org/anthology/2020.emnlp-main.494.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, 2004. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W04-1013.

Dayiheng Liu, Jie Fu, Yidan Zhang, Chris Pal, and Jiancheng Lv. Revision in continuous space: Unsupervised text style transfer without adversarial learning. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 8376–8383. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/6355.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019. URL https://arxiv.org/pdf/1907.11692.pdf.

Fuli Luo, Peng Li, Jie Zhou, Pengcheng Yang, Baobao Chang, Xu Sun, and Zhifang Sui. A dual reinforcement learning framework for unsupervised text style transfer. In Sarit Kraus (ed.), *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI 2019, Macao, China, August 10-16, 2019*, pp. 5116–5122. ijcai.org, 2019. doi: 10.24963/ijcai.2019/711. URL https://doi.org/10.24963/ijcai.2019/711.

Muharram Mansoorizadeh, Taher Rahgooy, Mohammad Aminiyan, and Mahdy Eskandari. Author obfuscation using wordnet and language models—notebook for pan at clef 2016.

Julia Mendelsohn, Yulia Tsvetkov, and Dan Jurafsky. A framework for the computational linguistic analysis of dehumanization. *Frontiers in artificial intelligence*, 3:55, 2020.

Mohammad Norouzi, David J. Fleet, and Ruslan Salakhutdinov. Hamming distance metric learning. In Peter L. Bartlett, Fernando C. N. Pereira, Christopher J. C. Burges, Léon Bottou, and Kilian Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 25: 26th Annual Conference on Neural Information Processing Systems 2012. Proceedings of a meeting held December 3-6, 2012, Lake Tahoe, Nevada, United States*, pp. 1070–1078, 2012. URL https://proceedings.neurips.cc/paper/2012/hash/59b90e1005a220e2ebc542eb9d950b1e-Abstract.html.

Boxiao Pan, Haoye Cai, De-An Huang, Kuan-Hui Lee, Adrien Gaidon, Ehsan Adeli, and Juan Carlos Niebles. Spatio-temporal graph for video captioning with knowledge distillation. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 10867–10876. IEEE, 2020. doi: 10.1109/CVPR42600.2020.01088. URL https://doi.org/10.1109/CVPR42600.2020.01088.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia, Pennsylvania, USA, 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL https://www.aclweb.org/anthology/P02-1040.

Marc'Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. Sequence level training with recurrent neural networks. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL http://arxiv.org/abs/1511.06732.

Sudha Rao and Joel Tetreault. Dear sir or madam, may I introduce the GYAFC dataset: Corpus, benchmarks and metrics for formality style transfer. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 129–140, New Orleans, Louisiana, 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1012. URL https://www.aclweb.org/anthology/N18-1012.

Emily Reif, Daphne Ippolito, Ann Yuan, Andy Coenen, Chris Callison-Burch, and Jason Wei. A recipe for arbitrary text style transfer with large language models. *ArXiv preprint*, abs/2109.03910, 2021. URL https://arxiv.org/abs/2109.03910.

Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3982–3992, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1410. URL https://www.aclweb.org/anthology/D19-1410.

Steven J. Rennie, Etienne Marcheret, Youssef Mroueh, Jerret Ross, and Vaibhava Goel. Self-critical sequence training for image captioning. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 1179–1195. IEEE Computer Society, 2017. doi: 10.1109/CVPR.2017.131. URL https://doi.org/10.1109/CVPR.2017.131.

Parker Riley, Noah Constant, Mandy Guo, Girish Kumar, David Uthus, and Zarana Parekh. TextSETTR: Few-shot text style extraction and tunable targeted restyling. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 3786–3800, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.293. URL https://aclanthology.org/2021.acl-long.293.

Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 661–668. JMLR Workshop and Conference Proceedings, 2010.

Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2015, Boston, MA, USA, June 7-12, 2015*, pp. 815–823. IEEE Computer Society, 2015. doi: 10.1109/CVPR.2015.7298682. URL https://doi.org/10.1109/CVPR.2015.7298682.

Thomas Scialom, Paul-Alexis Dray, Sylvain Lamprier, Benjamin Piwowarski, and Jacopo Staiano. Discriminative adversarial search for abstractive summarization. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 8555–8564. PMLR, 2020. URL http://proceedings.mlr.press/v119/scialom20a.html.

Tianxiao Shen, Tao Lei, Regina Barzilay, and Tommi S. Jaakkola. Style transfer from non-parallel text by cross-alignment. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 6830–6841, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/2d2c8394e31101a261abf1784302bf75-Abstract.html.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

Akhilesh Sudhakar, Bhargav Upadhyay, and Arjun Maheswaran. "transforming" delete, retrieve, generate approach for controlled text style transfer. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3269–3279, Hong Kong, China, 2019.

Association for Computational Linguistics. doi: 10.18653/v1/D19-1322. URL https://www.aclweb.org/anthology/D19-1322.

Subhashini Venugopalan, Marcus Rohrbach, Jeffrey Donahue, Raymond J. Mooney, Trevor Darrell, and Kate Saenko. Sequence to sequence - video to text. In *2015 IEEE International Conference on Computer Vision, ICCV 2015, Santiago, Chile, December 7-13, 2015*, pp. 4534–4542. IEEE Computer Society, 2015. doi: 10.1109/ICCV.2015.515. URL https://doi.org/10.1109/ICCV.2015.515.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Rob Voigt, David Jurgens, Vinodkumar Prabhakaran, Dan Jurafsky, and Yulia Tsvetkov. RtGender: A corpus for studying differential responses to gender. In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*, Miyazaki, Japan, 2018. European Language Resources Association (ELRA). URL https://www.aclweb.org/anthology/L18-1445.

Ke Wang, Hang Hua, and Xiaojun Wan. Controllable unsupervised text attribute transfer via editing entangled latent representation. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 11034–11044, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/8804f94e16ba5b680e239a554a08f7d2-Abstract.html.

Zeerak Waseem, Thomas Davidson, Dana Warmsley, and Ingmar Weber. Understanding abuse: A typology of abusive language detection subtasks. In *Proceedings of the First Workshop on Abusive Language Online*, pp. 78–84, Vancouver, BC, Canada, 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-3012. URL https://www.aclweb.org/anthology/W17-3012.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Hao Wu, Jiayuan Mao, Yufeng Zhang, Yuning Jiang, Lei Li, Weiwei Sun, and Wei-Ying Ma. Unified visual-semantic embeddings: Bridging vision and language with structured meaning representations. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pp. 6609–6618. Computer Vision Foundation / IEEE, 2019. doi: 10.1109/CVPR.2019.00677. URL http://openaccess.thecvf.com/content_CVPR_2019/html/Wu_Unified_Visual-Semantic_Embeddings_Bridging_Vision_and_Language_With_Structured_Meaning_CVPR_2019_paper.html.

Jingjing Xu, Xu Sun, Qi Zeng, Xiaodong Zhang, Xuancheng Ren, Houfeng Wang, and Wenjie Li. Unpaired sentiment-to-sentiment translation: A cycled reinforcement learning approach. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 979–988, Melbourne, Australia, 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1090. URL https://www.aclweb.org/anthology/P18-1090.

Wei Xu, Alan Ritter, Bill Dolan, Ralph Grishman, and Colin Cherry. Paraphrasing for style. In *Proceedings of COLING 2012*, pp. 2899–2914, Mumbai, India, December 2012. The COLING 2012 Organizing Committee. URL https://aclanthology.org/C12-1177.

Xu Yang, Chongyang Gao, Hanwang Zhang, and Jianfei Cai. Hierarchical scene graph encoder-decoder for image paragraph captioning. In *MM '20: The 28th ACM International Conference on Multimedia, Virtual Event / Seattle, WA, USA, October 12-16, 2020*, pp. 4181–4189, 2020. doi: 10.1145/3394171.3413859. URL https://doi.org/10.1145/3394171.3413859.

Li Yujian and Liu Bo. A normalized levenshtein distance metric. *IEEE transactions on pattern analysis and machine intelligence*, 29(6):1091–1095, 2007.

A APPENDIX

A.1 COMPARING WITH ANOTHER POLITICAL STANCE DATASET

Transferring political stance has also been studied in Voigt et al. (2018), where the author also collected a dataset for political stance TST. Comparing with their dataset, we found ours has following differences:

Language Formality: Their dataset is composed of comments on Facebook posts from members of the United States Senate and House, while our dataset consists of sentences from news articles written by professional reporters belonging to well-known media outlets (CNN, Fox News, etc.). The text in the dataset of Voigt et al. (2018) tends to be more casual and oral (e.g., *"congrats , lee !"*). Conversely, the text in our dataset is generally more formal and well-formed.

Completeness: Their dataset does not contain the original post to which the comments are responding, which causes some potential ambiguity on its political stance labels especially when the comment is generic (e.g., *"happy birthday jerry : -)"*). Most of the sentences in our dataset are complete statements of certain facts. We also conducted an extra distillation step (described in Appendix A in the supplementary document) to only keep the sentences that are salient to the article's stance label.

Coverage: The comments in Voigt et al. (2018) are mainly from 2017-2018, while our dataset collects nearly 10-year of articles from 6/1/2012 to 4/1/2021, which covers a wider range of societal issues and events. In the released version of our data we will add the time stamps to the sentences for customized filtering.

A.2 SENTENCE DISTILLATION FOR CONSTRUCTING POLITICAL STANCE DATASET

As mentioned in Section 3.1 of the paper, the articles collected from Allsides.com are already manually aligned (based on their political ideology) by Allsides editors. We collected a total of 2,298 full-length news articles from opposite ideologies (i.e., *liberal* and *conservative*) grouped by events. To create a sentence-level TST dataset for political stance transfer, we split the articles into sentences and took their article-level ideologies (as assigned by the editors) as their sentence-level stance labels. However, we found that not all sentences explicitly exhibit the stance label inherited from their corresponding articles, so we implemented an additional distillation step to select those sentences that are salient with respect to their assigned political stance.

Assuming we have an article with N sentences $X = \{x_1, x_2, ..., x_N\}$ and the title of the article x_{title}, we aim to find the subset of sentences $D_{\text{distill}} \subset X$ which all explicitly exhibit the assigned political stance. To better describe our approach, we first introduce two concepts: (1) stance saliency, and (2) distillation cost.

Stance Saliency. We compute the stance saliency v_i for each sentence $x_i \in X \backslash D_{\text{distill}}$, which is a measure of how well x_i exhibits a certain political stance. D_{distill} is the set of sentences already picked our distilled set. We assume that the stance exhibited in x_{title} matches that of the article (as assigned by the editors), Thus, we define stance saliency v_i as the similarity between x_i and the union of x_{title} and D_{distill}, which is:

$$v_i := \text{LCS}(x_i, x_{\text{title}} \cup D_{\text{distill}}), \tag{5}$$

where $\text{LCS}(\cdot)$ is longest common sequence between the two input sequences. However, this metric is biased towards longer sentences as they can have more tokens matched with the title. We address this issue through the intriduction of a distilation cost, described below.

Distillation Cost. We assign a distillation cost w_i to each sentence x_i in an article. The cost is simply the length of the sentence:

$$w_i := |x_i|. \tag{6}$$

Note that for both concepts our computation is based on lower-cased and lemmatized sentence tokens. We use λ to denote the ratio of the sentences to be picked as distilled sentences in an article consisting of N sentences, and define $W_{\max} = \lambda \cdot \sum_{i=0}^{N} w_i$ as the maximum distillation cost allowed.

Now that for each sentence we have a stance saliency and a distillation cost, we aim to choose a set of sentences as the distillation which have the highest possible sum of saliency for which the sum of distillation costs is not greater than $W_{\max}$. Given a function $\phi(x_i) = \{1, 0\}$ where 1 corresponds to sentence x_i being picked for the distilled set and 0 means otherwise, the objective of distillation can be expressed as:

$$\max \sum_{i=1}^{N} v_i \cdot \phi(x_i) , \quad \text{s.t.} \sum_{i=1}^{N} w_i \cdot \phi(x_i) \leq W_{\max} . \tag{7}$$

This is actually a NP-complete combinatorial optimization problem, called the Knapsack problem, which we solve using dynamic-programming (DP). In general, the distillation strategy aggressively picks sentences of high stance saliency while keeping the cost of distillation from exceeding the mask cost limitation $W_{\max}$. The procedure is demonstrated in Algorithm 1 below.

Algorithm 1: Sentence Distillation for Political Stance Dataset

Input: article title x_{title}, article sentences X, distillation ratio λ.

▷ Initialization
Init current distillation set D_{distill} as $\varnothing$;
Init current distillation cost W_{distill} with $|x_{\text{title}}|$;

▷ Multiple Rounds of Distillation
while $W_{distill} \leq W_{max}$ **do**
    Compute v_i for each $x_i \in X \setminus D_{\text{distill}}$ with x_{title} and D_{distill} (by Equation 1);
    Compute w_i for each x_i (by Equation 2);
    Find best distillation strategy $\{\phi(x_i)\}$ via DP with v_i, w_i and W_{distill} (see Alg. 2);

    ▷ Update Distillation Results Every Step
    Update current distillation set $D_{\text{distill}} = D_{\text{distill}} \cup \{x_i\}$ whose $\phi(x_i) = 1$;
    Update current distillation cost W_{distill} in terms of updated D_{distill};
end
return distillation sentences set D_{distill};

Note that we initialize W_{distill} with the length of title. At every iteration of the loop we solve the DP problem with the limit set by current W_{distill}, which is a variable that estimates how many sentences are already in the distillation set (no more than $W_{\max}$). The DP-based algorithm used in Algorithm 1 for finding the best distillation strategy is shown is Algorithm 2 below.

A.3 Statistics our All Three Datasets, and Experimental Setup

We present more statistical details of all three datasets in Table 7. All of our experiments were run on a single RTX-2080 GPU, with batch size 4 and 2/3/2 epochs for LaMer in the above three TST tasks. Following previous work, we choose style control accuracy (ACC), BLEU score as our main metrics. ACCs are judged by a pre-trained RoBERTa (Liu et al., 2019) classifier with F1 = {0.97, 0.86, 0.93} using the training data of the three TST tasks. About the J-score we calculate in few-shot experiments, we use the models released by the author[8].

A.4 Additional Details about Token-level Scene Preservation

In this section, we provide additional details regarding how we compute the token-level scene preservation d_{PSV}. Figure 4 shows an example sentiment transfer task. For a given positive (source style) sentence s^{src} and its corresponding negative (target style) parallels s^{tgt}, we first extract their

---

[8]The evaluation scripts, and pre-trained models can be found here: http://style.cs.umass.edu/

Training Data (S-Emb. + SAS)	■ Sentiment		■ Formality		■ Political Stance	
	positive	negative	formal	informal	liberal	conservative
# Sent Pairs	553,430		93,157		36,307	
# Scene Entities	742,136	777,839	145,731	133,779	194,032	272,071
Avg. Sent Len	7.32	7.58	11.52	11.05	19.39	24.75
Avg. # Scene Ent. / Sent	1.34	1.41	1.56	1.44	5.34	7.49
Avg. # Scene Ent.$^{\text{src} \cap \text{tgt}}$ (vs. RD)	0.95 (0.73)		0.49 (0.02)		0.96 (0.10)	
Avg. SAS (vs. RD)	0.72 (0.55)		0.29 (0.01)		0.25 (0.01)	
Human Reference	positive	negative	formal	informal	liberal	conservative
# Sent Pairs	500		1020		525	
# Scene Entities	964	905	1,467	1,388	2,915	3,012
Avg. Sent Len	9.90	9.80	10.9	9.35	10.30	11.19
Avg. # Scene Ent. / Sent	1.93	1.81	1.44	1.36	5.58	5.76
Avg. # Scene Ent.$^{\text{src} \cap \text{tgt}}$	1.53		0.55		1.78	
Avg. SAS	0.73		0.29		0.30	

Table 7: Data statistics for the three TST tasks in this work: Sentiment, Formality, and Political Stance Transfer. We compare the S-Emb. + SAS aligned data (the upper part), with the human-annotated reference file (the bottom part). Notice that after alignment, the SAS of training data becomes much closer to that of human reference, which demonstrates we successfully align the non-parallel data into parallel form (comparable to the human reference). Among the three TST datasets, we find the political stance TST has the longest sentence length (see Avg. Sent Len), and more scene entities involved on average (see Avg. # Scene Ent. / Sent). Human written references also reveal similar statistics (see the lower part of the table), which will potentially increase the difficulty for entity-matched transfer. We thus consider the political stance TST as a more challenging task than the other two.

Algorithm 2: DP-based Best Distillation Strategy Search

Input: stance saliency v_i, distill cost w_i, and current cost limit W_{distill}.
Record the number of stance saliency $M = |v_i|$;
Init DP-table $T[M + 1][W_{\text{distill}} + 1]$ with all 0;
for $i = 1, 2, \ldots, M$ **do**
    for $j = 1, 2, \ldots, W_{distill}$ **do**
        if $j - w_{i-1} < 0$ **then**
            $T[i][j] = T[i - 1][j]$;
            Record distillation picking choice $\phi(x_i)$;
        else
            $T[i][j] = \max(T[i - 1][j],$
            $T[i - 1][j - w_{i-1}] + v_{i-1})$;
            Record distillation picking choice $\phi(x_i)$;
        end
    end
end
$\{\phi(x_i)_{i=1}^{M}\} \leftarrow$ backtracking via records;
return best distillation strategy $\{\phi(x_i)_{i=1}^{M}\}$;

---

scene entities using the method by Wu et al. (2019) (Figure 4 (a)), and based on these entities we compute two distances d_{Order} and d_{Exist} as sub-components of d_{PSV}.

For d_{Order}, as shown in Figure 4 (b), we compare each of the s^{tgt} entities with the s^{src} entities, and measure how much s^{tgt} needs to be edited to make the two sets of entities from opposite styles identical to each other. As mentioned in the paper, we use the Levenshtein distance as the edit distance; whose set of edits operation is: 1) insertion of a single token, 2) deletion of a single token, and 3) substitution of a single token. Each of these operations has unit cost, so the Levenshtein distance is equal to the minimum number of operations required to transform target style entities to source style entities.

Figure 4: (a) extraction of scene entities (underlined) from source sentence and parallel target sentences. Sentences with a + correspond to $s^{\text{tgt+}}$, and those with a - correspond to $s^{\text{tgt-}}$ (i.e., expert and amateur demonstrations for imitation learning); (b) entity appearing order (d_{Order}, computed by edit distance); and (c) entity existence (d_{Exist}, computed by hamming distance).

As shown in Figure 4 (c), we calculate another distance component, d_{Exist}, via hamming distance to emphasize the the difference between the sets of entities in source and target sentences. We first get the union of the entities from a pair of source and target sentences; based on the union set, we can obtain the corresponding binary vector representations of both style entities: 1 means the entity exists in a certain style sentence, and 0 otherwise. Note the binary vectors for each of the sentences will be the same length (since it corresponds to the union of entities). Hamming distance measures the difference between source and target sentences on the shared entities set (this was shown to be an upper bound on the Levenshtein distance). Though there are overlaps between this metric and d_{Order}, we use this metric to *emphasize* the difference in scene entities.

A.5 MORE DETAILS ABOUT POLICY GRADIENT

We detail our policy gradient algorithm in Algorithm 3. Note that $J_{\text{IL}}^{\text{safe}}$ is a safe-reward threshold. If the greedy policy can already reach this threshold the policy will not be updated. Empirically we set $J_{\text{IL}}^{\text{safe}}$ to $\{0.8, 0.6, 0.4\}$ for the three TST tasks (sentiment, formality, and political stance).

Algorithm 3: Imitating Learning of LaMer

Input: current policy π_θ, expert policy trajectory $s^{\text{tgt+}}$,
and amateur policy trajectory $s^{\text{tgt-}}$
Output: a learned policy π_θ approaching to expert
policy π^+

▷ Get baseline via Greedy Decoding
$\hat{s}_{\text{greedy}} \leftarrow \arg\max \hat{\pi} \sim \text{LM}(a_t|y_{1:t-1})_{t \in [1,T]}$;
Compute $J_{\text{IL}}^{\text{greedy}}$ with $\hat{s}_{\text{greedy}}$, $s^{\text{tgt+}}$, and $s^{\text{tgt-}}$ by Eq. 3;

if $J_{IL}^{greedy} \leq J_{IL}^{safe}$ **then**
    ▷ No Optimization on Already Good Policies
    Skip current step Imitation Learning;

▷ Exploration by Sampling Decoding
while $i \leq$ max exploration steps **do**
    $\hat{s}_{\text{sample}}^{(i)} \leftarrow$ sampling $\hat{\pi} \sim \text{LM}(a_t|y_{1:t-1})_{t \in [1,T]}$;
    Compute $J_{\text{IL}}^{\text{sample}}$ with $\hat{s}_{\text{sample}}^{(i)}$, $s^{\text{tgt+}}$, and $s^{\text{tgt-}}$ by
    Eq. 3;

▷ Optimize Policy by REINFORCE
Compute policy gradient as
$\nabla_\theta J(\theta) = -\mathbb{E}_{\pi_\theta} \left[\nabla_\theta \log \pi_\theta \cdot (J_{\text{IL}}^{\text{sample}} - J_{\text{IL}}^{\text{greedy}}) \right]$;
Update policy with policy gradient by taking K steps
SGD (via Adam);
return $\pi_\theta \rightarrow \pi^+$

We choose the REINFORCE algorithm (Williams, 1992) to optimize the current policy π_θ. One known issue of the vanilla REINFORCE method is the instability of its optimization because of the high variance of the gradients. A common remedy is to add a baseline function (i.e., a parameterized value-network whose purpose is to estimate the unbiased future behavior of current policy (Ranzato et al., 2016)). Rennie et al. (2017) introduce a better approach that estimates the baseline at test time. They use the greedy decoding results as the baseline in their *self-critic* sequence training algorithm. We adopt their method to provide the baseline, and add an exploration step using sampling decoding. As shown in Algorithm 1, by iteratively switching between these two modes, we calculate corresponding contrastive losses defined by Equation 3, and take the difference of two modes losses as the advantage, feeding into the REINFORCE algorithm to optimize our policy π_θ. Finally, the output policy π_θ is able to generate style transferred sequences resemble the expert demonstrations $s^{\text{tgt+}}$.

A.6 Error Analysis, and Additional Generation Samples of LaMer

In the introduction of the main paper, we briefly discuss the pitfalls of existing TST models. Table 8 shows actual generation samples from these methods to further highlight their weaknesses. We take the sentiment transfer task—which was used by all models in their evaluations—and pick a *negative* source style sentence carrying the style in an implicit way (i.e., there are no salient token-level cues exhibiting negative sentiment[9]). All TST models should generate a transferred positive sentence.

Source Style (*negative*)	you 'll have zero appetite after the first bite .
Reference Target Style (*positive*)	*you 'll be wanting more after the first bite !*
CAE Shen et al. (2017) (Latent Disentanglement)	*you 'll be back for the first bite !* ($+$ semantically coherent; $-$ missing content)
DelRetrGen Li et al. (2018a) (Token-level Editing)	*i love this place .* ($+$ carrying target style; $-$ generic generation)
Style Transformer Dai et al. (2019) (Transformer Self-Attention)	*you 'll have often appetite after the first friends .** ($+$ content preserved; $-$ semantically incoherent)
Deep Latent Seq He et al. (2020) (LM Prior + Latent Parallel Seq.)	*you 'll have family appreciated the first time with the first time .** ($+$ content preserved; $-$ unrelated illusion)
Ours: LaMer (Self-Supervision + LM IL)	*you 'll eat until you feel full after the first bite .*

Table 8: Comparing LaMer with several well-known STS methods on a sample of *negative → positive* sentiment transfer task. We denote the strength ($+$) and weakness ($-$) of the transfer outputs. * corresponds to generations that are taken from the author-released outputs files.

---

[9]E.g., *"zero appetite"* does not have a direct opposite expression like *"one appetite"*. Thus, in this case *negative* style cannot be interpreted at the token level.

As can be seen in the table, CAE (Shen et al., 2017) suffers from discarding too much style-independent content. When the style cannot be interpreted at the token level, DelRetrGen (Li et al., 2018a) results in generic generation since it is difficult to transfer implicit styled sentence through token-editing. From our empirical observation, Style Transformer (Dai et al., 2019) typically generates sentences with low readability. Deep Latent Seq (He et al., 2020) tends to generate unrelated text (e.g., *"...family appreciated..."*) and sometimes text with low readability (e.g., *"...the first time with the first time..."*). This is partially because their assumption that TST datasets can be aligned in latent space is too strong.

We have included sample generations from LaMer for the test sets of all three tasks with our code submission.

A.7 ADDITIONAL DETAILS ABOUT HUMAN EVALUATION

We provide more details about our human evaluation in this section. The results on sentiment TST are shown in Table 9 and those of formality TST are shown in Table 10.

Details About Participants and Compensation. Participants (N=212) were all from the United States and above 18 years old. Participants were required to have a HIT approval rate greater than 95%. The average age of the participants was 34.95 years-old (SD=9.90, Median=32). 141 of the participants (66.5%) were male, and 71 female (33.5%). Participants received 14.41 years of education on average (SD=4.46, Median=16). When asked to self-report their party affiliation, 52.4% participants self-reported as Democratic, 35.3% participants were self-reported Republicans, and 12.3% participants identified as independent. Each participant was compensated 1 USD per task. The average completion time per questionnaire was about 7.6 minutes as reported by the platform, which results in a $7.9/hr wage, above the regional and federal minimum wage.

Details About Human Evaluation Procedure. We evaluate the style transferred sentences generated by baselines and our LaMer. The sentences are picked from the test set generations for the three tasks. Each participant was asked to read two sets of sentences (one set containing a source style sentence, corresponding human-written target style sentence as ground-truth, and eight versions of target style sentences generated by seven existing methods and LaMer for comparison). After reading each set, they were asked to rate how well the generated sentences did in style control, readability, and content preservation on a 7-point Likert scales. For example, for content preservation, they were asked *"How much do you agree with the following statement (1- Strongly disagree to 7- Strongly agree): The machine-generated target style text preserves the context of the source style text well (i.e. they talk about the same thing).".* Higher ratings correspond to better performance.

Table 9: Human judgement results (on a 7-point scale) of seven existing methods and LaMer on sentiment transfer task. We **bold** the highest average rating. SD: Standard Deviation.

■ Sentiment	Style		Content		Readability	
Methods	Mean	SD	Mean	SD	Mean	SD
CAE (Shen et al., 2017)	5.09	1.49	4.79	1.56	4.84	1.50
DelRetrGen (Li et al., 2018a)	4.94	1.62	4.73	1.63	5.05	1.39
Dual RL (Luo et al., 2019)	5.43	1.40	4.89	1.73	5.10	1.40
Style Transformer (Dai et al., 2019)	5.09	1.55	4.71	1.56	5.04	1.50
Deep Latent Seq (He et al., 2020)	4.89	1.79	4.63	1.76	5.05	1.49
TSF-DelRetGen (Sudhakar et al., 2019)	4.66	1.35	4.73	1.24	5.30	1.13
STARP (Krishna et al., 2020)	**5.50**	1.20	4.65	1.40	5.33	1.20
Ours: LaMer	5.45	1.21	**4.91**	1.71	**5.43**	1.18

A.8 DISCUSSION ON LAMER'S EFFICIENCY

We are curious about whether existing methods that suffer from lack of direct supervision can take the advantage of aligned datasets. In Table 11, we use the same aligned datasets used by LaMer (added aligned by RD as for ablation), to train three exiting systems by one epoch. Of note, all these methods benefit in different perspectives. For example, DelRetrGen (Li et al., 2018a) makes large

Table 10: Human judgement results (on a 7-point scale) of seven existing methods and LaMer on formality transfer task. We **bold** the highest average rating. SD: Standard Deviation.

■ Formality	Style		Content		Readability	
Methods	Mean	SD	Mean	SD	Mean	SD
CAE (Shen et al., 2017)	5.17	1.59	5.09	1.67	4.89	1.64
DelRetrGen (Li et al., 2018a)	5.19	1.57	4.91	1.65	4.86	1.62
Dual RL (Luo et al., 2019)	5.49	1.27	5.13	1.29	5.36	1.31
Style Transformer (Dai et al., 2019)	5.25	1.38	5.22	1.37	5.26	1.37
Deep Latent Seq (He et al., 2020)	5.22	1.52	5.30	1.46	5.17	1.47
TSF-DelRetGen (Sudhakar et al., 2019)	4.86	1.25	5.23	1.24	5.20	1.49
STARP (Krishna et al., 2020)	5.33	1.21	4.65	1.37	5.39	1.20
Ours: LaMer	**5.50**	1.23	5.45	1.29	**5.39**	1.21

Source Sent. (*positive*)	fun place to catch a game on tv and catch up w/ people .			
Human Ref. (*negative*)	loud place to catch a game on tv and try to catch up w/ people			
Methods	**Sample Generation**	**ACC**	**BLEU**	**PPL**
CAE ($\approx$ 15h 49min)				
w/. RD	a nice place to go on a game and the staff on us .	10.6	15.4	71.3
w/. S-Emb.	fun place to dine and helped me to support people .	26.3	24.7	53.5
w/. S-Emb. + SAS	not fancy place and always a great place to get .	35.4	26.0	39.6
DelRetrGen ($\approx$ 27h 13min)				
w/. RD	but i 'm not sure that is .	6.6	1.4	1371.4
w/. S-Emb.	"i 'm not a fan , but i love this place !	4.4	2.6	18.44
w/. S-Emb. + SAS	the place is also horrible .	97.3	18.9	15.63
Style Transformer ($\approx$ 12h 21min)				
w/. RD	fun place to catch a game on tv loud on game on ...	25.3	26.2	1241.9
w/. S-Emb.	bad place to catch a game on tv a to a to a ...	22.6	26.5	801.3
w/. S-Emb. + SAS	bad place to catch a game on tv game on a tv	45.8	29.3	948.9
Ours:LaMer (S-Emb. + SAS)				
1/10 Epoch ($\approx$ 10min)	i've been here to catch a game.	66.3	30.4	12.0
1/2 Epoch ($\approx$ 45min)	this place is terrible to catch a game.	79.9	34.2	11.3
1 Epoch ($\approx$ 1h 34min)	terrible place for anybody looking to catch a game on tv.	98.0	37.9	10.61

Table 11: Our alignment procedure can even boost the performance of existing methods. All trained with one epoch, we study their learning efficiency compared with our method: LaMer obtains the best result on this sentiment transfer task, and is robust to data scarcity.

improvements in style control accuracy, BLEU score, and fluency (PPL). Most prior work emphasize their advances in performance, but do not consider learning efficiency. In the same one epoch setting, LaMer achieves the best performance compared with others. Meanwhile, when further decreasing the training data size to 1/10 of the original, LaMer can still produce acceptable results, better than most of other methods trained with the whole epoch, mainly because LaMer is LM-based. Combining all these key factors for efficient learning, LaMer can serve as a general-purpose TST model for either data rich or data scarce cases.