# Permutation-Invariant Variational Autoencoder for Graph-Level Representation Learning

## Abstract

Recently, there has been great success in applying deep neural networks on graph structured data. Most work, however, focuses on either node- or graph-level supervised learning, such as node, link or graph classification or node-level unsupervised learning (e.g., node clustering). Despite its wide range of possible applications, graph-level unsupervised learning has not received much attention yet. This might be mainly attributed to the high representation complexity of graphs, which can be represented by $n!$ equivalent adjacency matrices, where $n$ is the number of nodes. In this work we address this issue by proposing a permutation-invariant variational autoencoder for graph structured data. Our proposed model indirectly learns to match the node ordering of input and output graph, without imposing a particular node ordering or performing expensive graph matching. We demonstrate the effectiveness of our proposed model on various graph reconstruction and generation tasks and evaluate the expressive power of extracted representations for downstream graph-level classification and regression.

## 1 Introduction

Graphs are an universal data structure that can be used to describe a vast variety of systems from social networks to quantum mechanics [1]. Driven by the success of Deep Learning in fields such as computer vision and natural language processing, there has been an increasing interest in applying deep neural networks on non-Euclidean, graph structured data as well [2, 3]. Most notably, generalizing Convolutional Neural Networks and Recurrent Neural Networks to arbitrarily structured graphs for supervised learning has lead to significant advances on task such as molecular property prediction [4] or question-answering [5]. Research on unsupervised learning on graphs mainly focused on node-level representation learning, which aims at embedding the local graph structure into latent node representations [6, 7, 8, 9, 10]. Usually, this is achieved by adopting an autoencoder framework where the encoder utilizes e.g., graph convolutional layers to aggregate local information at a node level and the decoder is used to reconstruct the graph structure from the node embeddings. Graph-level representations are usually extracted by aggregating node-level features into a single vector, which is common practice in supervised learning on graph-level labels (e.g., molecular property prediction) [4]. Unsupervised learning of graph-level representations, however, has not yet received much attention, despite its wide range of possible applications, such as feature extraction, pre-training for graph-level classification/regression tasks, graph matching or similarity ranking. This might be mainly attributed to the high representation complexity of graphs arising from their inherent invariance with respect to the ordering of nodes within the graph. In general, a graph with $n$ nodes, can be represented by $n!$ equivalent adjacency matrices, each corresponding to a different node ordering. Since the general structure of a graph is invariant to the order of their individual nodes, a graph-level representation should not depend on the order of the nodes in the input representation of a graph, i.e. two isomorphic graphs should always be mapped to same representation.

Figure 1: Network architecture of the proposed model. Input graph is depicted as fully connected graph (dashed lines for not direct neighbours) with the additional embedding node $v_0$ and edges to it (black color). Different node and edge types are represented by different colors and real edges by solid lines between nodes. Transformations parameterized by a neural network are represented by block arrows.

This poses a problem for most neural network architectures which are by design not invariant to the order of their inputs. Even if carefully designed in a permutation invariant way (e.g., Graph Neural Networks with a final node aggregation step), there is no straight-forward way to train an autoencoder network, due to the ambiguous reconstruction objective, requiring the same discrete ordering of input and output graphs to compute the reconstruction loss.

How can we learn a permutation-invariant graph-level representation utilizing a permutation-variant reconstruction objective? In this work we tackle this question proposing a graph autoencoder architecture that is by design invariant to the ordering of nodes in a graph. We address the order ambiguity issue by training alongside the encoder and decoder model an additional *permuter* model that assigns to each input graph a permutation matrix to align the input graph node ordering with the node ordering of the reconstructed graph.

## 2 Method

### 2.1 Notations and Problem Definition

An undirected Graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ is defined by the set of $n$ nodes $\mathcal{V} = \{v_1, \ldots, v_n\}$ and edges $\mathcal{E} = \{(v_i, v_j)|v_i, v_j \in \mathcal{V}\}$. We can represent a graph in matrix form by its node features $\mathbf{X}_\pi \in \mathbb{R}^{n \times d_v}$ and adjacency matrix $\mathbf{A}_\pi \in \{0,1\}^{n \times n}$ in the node ordering $\pi \in \Pi$, where $\Pi$ is set of all $n!$ permutations over $\mathcal{V}$. We define the permutation matrix $\mathbf{P}$ that reorders nodes from ordering $\pi$ to ordering $\pi'$ as $\mathbf{P}_{\pi \to \pi'} = (p_{ij}) \in \{0,1\}^{n \times n}$, with $p_{ij} = 1$ if $\pi(i) = \pi'(j)$ and $p_{ij} = 0$ everywhere else. Since Graphs are invariant to the ordering of their nodes, note that

$$\mathcal{G}_\pi = \mathcal{G}(\mathbf{X}_\pi, \mathbf{A}_\pi) = \mathcal{G}(\mathbf{P}_{\pi \to \pi'} \mathbf{X}_\pi, \mathbf{P}_{\pi \to \pi'} \mathbf{A}_\pi \mathbf{P}_{\pi \to \pi'}^\top) = \mathcal{G}(\mathbf{X}_{\pi'}, \mathbf{A}_{\pi'}) = \mathcal{G}_{\pi'}, \quad (1)$$

where $\top$ is the transpose operator. Let us now consider a dataset of graphs $\mathbf{G} = \{\mathcal{G}^{(i)}\}_{i=0}^N$ we would like to represented in a low-dimensional continuous space. We can adopt a latent variable approach and assume that the data is generate by a process $p_\theta(\mathcal{G}|\mathbf{z})$, involving an unobserved continuous random variable $\mathbf{z}$. Following the work of Kingma and Welling [11], we approximate the intractable posterior by $q_\phi(\mathcal{G}|\mathbf{z}) \approx p_\theta(\mathcal{G}|\mathbf{z})$ and minimize the lower bound on the marginal likelihood of graph $G^{(i)}$:

$$\log p_\theta(\mathcal{G}^{(i)}) \geq \mathcal{L}(\phi, \theta; \mathcal{G}^{(i)}) = -\text{KL}\left[q_\phi(\mathbf{z}|\mathcal{G}^{(i)})||p_\theta(\mathbf{z})\right] + \mathbb{E}_{q_\phi(\mathbf{z}|\mathcal{G}^{(i)})}\left[\log p_\theta(\mathcal{G}^{(i)}|\mathbf{z})\right], \quad (2)$$

where the Kullback–Leibler ( KL) divergence term regularizes the encoded latent codes of graphs $\mathcal{G}^{(i)}$ and the second term enforces high similarity of decoded graphs to their encoded counterparts. As graphs can be completely described in matrix form by their node features and adjacency matrix, we can parameterize $q_\phi$ and $p_\theta$ in Eq. (2) by neural networks that encode and decode node features

67 $\mathbf{X}_\pi^{(i)}$ and adjacency matrices $\mathbf{A}_\pi^{(i)}$ of graphs $\mathcal{G}^{(i)}$. However, as graphs are invariant under arbitrary
68 node re-ordering, the latent code $\mathbf{z}$ should be invariant to the node ordering $\pi$:

$$q_\phi(\mathbf{z}|\mathcal{G}_\pi) = q_\phi(\mathbf{z}|\mathcal{G}_{\pi'}), \text{ for all } \pi, \pi' \in \Pi. \tag{3}$$

69 This can be achieved by parameterizing the encoder model $q_\phi$ by a permutation invariant function.
70 However, if the latent code $\mathbf{z}$ does not encode the input node ordering $\pi$, input graph $\mathcal{G}_\pi$ and decoded
71 graph $\hat{\mathcal{G}}_{\pi'}$ are no longer necessarily in the same order, as the decoder model has no information
72 about the node ordering of the input graph. Hence, the second term in Eq. (2) cannot be optimized
73 anymore by minimizing the reconstruction loss between encoded graph $\mathcal{G}_\pi$ and decoded graph $\hat{\mathcal{G}}_{\pi'}$ in
74 a straight-forward way. They need to be brought in the same node ordering first. We can rewrite the
75 expectation in Eq. (2) using Eq. (1):

$$\mathbb{E}_{q_\phi(\mathbf{z}|\mathcal{G}_\pi^{(i)})} \left[ \log p_\theta(\mathcal{G}_\pi^{(i)}|\mathbf{z}) \right] = \mathbb{E}_{q_\phi(\mathbf{z}|\mathcal{G}_\pi^{(i)})} \left[ \log p_\theta(\mathbf{P}_{\pi'\to\pi}\mathcal{G}_{\pi'}^{(i)}|\mathbf{z}) \right]. \tag{4}$$

76 Since the ordering of the decoded graph $\pi'$ is subject to the learning process of the decoder and
77 thus unknown in advance, finding $\mathbf{P}_{\pi'\to\pi}$ is not trivial. In [12], the authors propose to use ap-
78 proximate graph matching to find the permutation matrix $\mathbf{P}_{\pi'\to\pi}$ that maximizes the similarity
79 $s(X_\pi, \mathbf{P}_{\pi'\to\pi}\hat{X}_{\pi'}; A_\pi, \mathbf{P}_{\pi'\to\pi}\hat{A}_{\pi'}\mathbf{P}_{\pi'\to\pi}^\top)$, which involves up to $O(n^4)$ re-ordering operations at
80 each training step in the worst case [13].

## 2.2 Permutation-Invariant Variational Graph Autoencoder

82 In this work we propose to solve the reordering problem in Eq. (4) implicitly by inferring the
83 permutation matrix $\mathbf{P}_{\pi'\to\pi}$ from the input graph $\mathcal{G}_\pi$ by a model $g_\psi(\mathbf{P}|\mathcal{G}_\pi)$. We train this *permuter*
84 model jointly with the encoder model $q_\phi(\mathbf{z}|\mathcal{G})$ and decoder model $p_\theta(\mathcal{G}|\mathbf{z})$, optimizing:

$$\mathcal{L}(\phi,\theta;\mathcal{G}^{(i)}) = -\text{KL} \left[ q_\phi(\mathbf{z}|\mathcal{G}^{(i)})||p_\theta(\mathbf{z}) \right] + \mathbb{E}_{q_\phi(\mathbf{z}|\mathcal{G}^{(i)}),\, g_\psi(\mathbf{P}|\mathcal{G}^{(i)})} \left[ \log p_\theta(\mathbf{P}\mathcal{G}^{(i)}|\mathbf{z}) \right]. \tag{5}$$

85 Intuitively, the permuter model has to learn how the ordering of nodes in the graph generated by
86 the decoder model will differ from a specific node ordering present in the input graph. During the
87 learning process, the decoder will learn its own canonical ordering that, given a latent code $z$, it will
88 always reconstruct a graph in. The permuter learns to transform/permute this canonical order to a
89 given input node ordering. For this, the permuter predicts for each node $i$ of the input graph a score
90 $s_i$ corresponding to its probability to have a low node index in the decoded graph. By sorting the
91 input nodes indices by their assigned scores we can infer the output node ordering and construct the
92 respective permutation matrix $\mathbf{P}_{\pi\to\pi'} = (p_{ij}) \in \{0,1\}^{n\times n}$, with

$$p_{ij} = \begin{cases} 1, & \text{if } j = \text{argsort}(s)_i \\ 0, & \text{else} \end{cases} \tag{6}$$

93 to align input and output node ordering. Since the argsort operation is not differentiable, we utilizes
94 the continuous relaxation of the argsort operator proposed in [14, 15]:

$$\mathbf{P} \approx \hat{\mathbf{P}} = \text{softmax}(\frac{-d(\text{sort}(s)\mathbb{1}^\top, \mathbb{1}s^\top)}{\tau}), \tag{7}$$

95 where the softmax operator is applied row-wise, $d(x,y)$ is the $L_1$-norm and $\tau \in \mathbb{R}_+$ a temperature-
96 parameter. By utilizing this continuous relaxation of the argsort operator, we can train the permuter
97 model $g_\psi$ in Eq. (5) alongside the encoder and decoder model with stochastic gradient descent. In
98 order to push the relaxed permutation matrix towards a real permutation matrix (only one 1 in every
99 row and column), we add to Eq. (5) a row- and column-wise entropy term as additional penalty term:

$$C(\mathbf{P}) = \sum_i H(\overline{\mathbf{p}}_{i,\cdot}) + \sum_j H(\overline{\mathbf{p}}_{\cdot,j}), \tag{8}$$

100 with Shannon entropy $H(x) = -\sum_i x_i \log(x_i)$ and normalized probabilities $\overline{\mathbf{p}}_{i,\cdot} = \frac{\mathbf{p}_{i,\cdot}}{\sum_j \mathbf{p}_{i,j}}$.

101 **Propositions 1.** *A square matrix $\mathbf{P}$ is a real permutation matrix if and only if $C(\mathbf{P}) = 0$ and the*
102 *doubly stochastic constraint $p_{ij} \geq 0 \, \forall(i,j)$, $\sum_i p_{ij} = 1 \, \forall j$, $\sum_j p_{ij} = 1 \, \forall i$ holds.*

103 **Proof.** *See Appendix A.*

104 By enforcing $\hat{\mathbf{P}} \to \mathbf{P}$, we ensure that no information about the graph structure is encoded in $\hat{\mathbf{P}}$ and
105 that the decoder model can generate valid graphs during inference, without the need of applying a
106 specific permutation matrix $\hat{\mathbf{P}}$ to it. At this point it should also be noted, that our proposed framework
107 can easily be generalized to arbitrary sets of elements, although we focus this work primarily on sets
108 of nodes and edges defining a graph.

**Graph Isomorphism problem.** Equation (5) gives us means to train an autoencoder framework with a permutation invariant encoder that maps a graph $f : \mathcal{G} \to \mathcal{Z}$ in an efficient manner. Such an encoder will always map two topologically identical graphs (even with different node order) to the same representation $z$. Consequently, the question arises, if we can decide for a pair of graphs if they are topologically identical. This is the well-studied *graph isomorphism problem* for which no polynomial-time algorithm is known yet [16, 17]. As mentioned above, in our framework, two isomorphic graphs will always be encoded to the same representation. Still, it might be that two non-isomorphic graphs will be mapped to the same point (non-injective). However, if the decoder is able to perfectly reconstruct both graphs (which is easy to check since the permuter can be used to bring the decoded graph in the input node ordering), two non-isomorphic graphs must have a different representation $z$. If two graphs have the same representation and the reconstruction fails, the graphs might still be isomorphic but with no guarantees. Hence, our proposed model can solve the graph isomorphism problem at least for all graphs it can reconstruct.

## 2.3 Details of the Model Architecture

In this work we parameterize the encoder, decoder and permuter model in Eq. (5) by neural networks utilizing the self-attention framework proposed by Vaswani et al. [18] on directed messages representing a graph. Figure 1, visualizes the architecture of the proposed permutation-invariant variational autoencoder. In the following, we describe the different parts of the model in detail.

**Graph Representation by Directional Messages.** In general, most graph neural networks can be thought of as so called Message Passing Neural Networks (MPNN) [19]. The key idea of MPNNs is the aggregation of neighbourhood information by passing and receiving messages of each node to and from neighbouring nodes in a graph. We adopt this view and represent graphs by its messages between nodes. We represent a graph $\mathcal{G}(\mathbf{X}, \mathbf{E})$, with node features $X \in \mathbb{R}^{n \times d_v}$ and edge features $E \in \mathbb{R}^{n \times n \times d_e}$, by its message matrix $\mathbf{M} = (m_{ij}) \in \mathbb{R}^{n \times n \times d_m}$:

$$m_{ij} = \sigma \left( [x_i || x_j || e_{ij}] \, \mathbf{W} + \mathbf{b} \right), \tag{9}$$

with non-linearity $\sigma$, concatenation operator $||$ and trainable parameters $\mathbf{W}$ and $\mathbf{b}$. Note, that nodes in this view are represented by *self-messages* $\mathrm{diag}(\mathbf{M})$, messages between non-connected nodes exists, although the presence or absence of a connection might be encoded in $e_{ij}$, and if $\mathbf{M}$ is not symmetric, edges have an inherent direction.

**Self-Attention on Directed Messages.** We follow the idea of aggregating messages from neighbours in MPNNs, but utilize the self-attention framework proposed by Vaswani et al. [18] for sequential data. Our proposed model comprises multiple layers of multi-headed scaled-dot product attention. One attention head is defined by:

$$\mathrm{Attention} \, (\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \mathrm{softmax} \left( \frac{\mathbf{Q} \mathbf{K}^\top}{\sqrt{d_k}} \right) \mathbf{V} \tag{10}$$

with queries $\mathbf{Q} = \mathbf{M} \mathbf{W}^Q$, keys $\mathbf{K} = \mathbf{M} \mathbf{W}^K$, and values $\mathbf{V} = \mathbf{M} \mathbf{W}^V$ and trainable weights $\mathbf{W}^Q \in \mathbb{R}^{d_m \times d_q}$, $\mathbf{W}^K \in \mathbb{R}^{d_m \times d_k}$ and $\mathbf{W}^V \in \mathbb{R}^{d_m \times d_v}$. For multi-headed self-attention we concatenate multiple attention heads together and feed them to a linear layer with $d_m$ output features. Since the message matrix $\mathbf{M}$ of a graph with $n$ nodes comprises $n^2$ messages, attention of all messages to all messages would lead to a $O(n^4)$ complexity. We address this problem by letting messages $m_{ij}$ only attend on incoming messages $m_{ki}$, reducing the complexity to $O(n^3)$. We achieve this by representing $\mathbf{Q}$ as a $(m \times n \times d)$ tensor and $\mathbf{K}$ and $\mathbf{V}$ by a transposed $(n \times m \times d)$ tensor, resulting into a $(m \times n \times m)$ attention tensor, with number of nodes $m = n$ and number of features $d$. That way, we can efficiently utilize batched matrix multiplications in Eq. (10), in contrast to computing the whole $(n^2 \times n^2)$ attention matrix and masking attention on not incoming messages out.

**Encoder** To encode a graph into a fixed-sized, permutation-invariant, continuous latent representation, we add to input graphs a dummy node $v_0$, acting as an embedding node. To distinguish the embedding node from other nodes, we add an additional node and edge type to represent this node and edges to and from this node. After encoding this graph into a message matrix $\mathbf{M}$ as defined in Eq. (9), we apply $L$ iterations of self-attention to update $\mathbf{M}$ and accumulate the graph structure in the embedding node, represented by the self-message $m_{0,0}$. Following [11], we utilize

the reparameterization trick and sample the latent representation $\mathbf{z}$ of a graph by sampling from a multivariate normal distribution:

$$\mathbf{z} \sim \mathbb{N}(f_\mu(m_{0,0}), f_\sigma(m_{0,0})\mathbf{I}), \tag{11}$$

with $f_\mu : m_{0,0} \to \mu \in \mathbb{R}^{d_z}$ and $f_\sigma : m_{0,0} \to \sigma \in \mathbb{R}^{d_z}$, parameterized by a linear layer.

**Permuter** To predict how to re-order the nodes in the output graph to match the ordering of nodes in the input graph, we first extract node embeddings represented by self-messages on the main diagonal of the encoded message matrix $m_{i,i} = \text{diag}(\mathbf{M}^{(\mathbf{L})})$ for $i > 0$. We score these messages by a function $f_s : m_{i,i} \to s \in \mathbb{R}$, parameterized by a linear layer and apply the soft-sort operator (see Section 2.2) to retrieve the permutation matrix $\hat{\mathbf{P}}$.

**Decoder** We initialize the message matrix for the decoder models input with the latent representation $\mathbf{z}$ at each entry. To break symmetry and inject information about the relative position/order of nodes to each other, we follow [18] and define position embeddings

$$\text{PE(pos)}_i = \left\{ \begin{array}{ll} \sin(\text{pos}/10000^{2i/d_z}), & \text{for even } i \\ \cos(\text{pos}/10000^{2i/d_z}), & \text{for odd } i \end{array} \right. \tag{12}$$

We add to each entry in the message matrix $m_{i,j}$ the concatenated position embeddings $[\text{PE}(i)||\text{PE}(j)]$. Since the self-attention based decoder model is permutation equivariant, we can move the permutation operation in Eq. (5) in front of the decoder model and directly apply it to the position embedding sequence (see Figure 1). After $L$ iterations of self-attention on the message matrix $\mathbf{M}$, we extract node features $x_i \in \mathbf{X}$ and edge features $e_{i,j} \in \mathbf{E}$ by a final linear layer:

$$x_i = m_{i,i}\mathbf{W}^v + \mathbf{b}^v \qquad e_{i,j} = 0.5 \cdot (m_{i,j} + m_{j,i})\mathbf{W}^e + \mathbf{b}^e, \tag{13}$$

with learnable parameters $\mathbf{W}^v \in \mathbb{R}^{d_m \times d_v}$, $\mathbf{W}^e \in \mathbb{R}^{d_m \times d_e}$, $\mathbf{b}^v \in \mathbb{R}^{d_v}$ and $\mathbf{b}^e \in \mathbb{R}^{d_e}$.

**Overall Architecture** We now describe the full structure of our proposed method using the ingredients above (see Figure 1). Initially, the input graph is represented by the directed message matrix $\mathbf{M}_{enc}^{(0)}$, including an additional graph embedding node $v_0$. The encoder model performs $L$ iterations of self-attention on incoming messages. Next, diagonal entries of the resulting message matrix $\mathbf{M}_{enc}^{(L)}$ are extracted. Message $m_{0,0}$, representing embedding node $v_0$, is used to condition the normal distribution, graph representation $\mathbf{z}$ is sampled from. The other diagonal entries $m_{i,i}$ are fed into the permuter model. Message $m_{i,i}$ are transformed into scores and sorted by the Soft-Sort operator to retrieve the permutation matrix $\hat{\mathbf{P}}$. Next, position embeddings (in Figure 1 represented by single digits) are re-ordered by applying $\hat{\mathbf{P}}$ and added by the sampled graph embedding $\mathbf{z}$. The resulting node embeddings are used to initialize message matrix $\mathbf{M}_{dec}^{(0)}$ and fed into the decoding model. After $L$ iterations of self-attention, diagonal entries are transformed to node features $\mathbf{X}$ and off-diagonal entries to edge features $\mathbf{E}$ to generate the output graph. In order to train and infer on graphs of different size, we pad all graphs in a batch with empty nodes to match the number of nodes of the largest graph. Attention on empty nodes is masked out at all time. To generate graphs of variable size, we train alongside the variational autoencoder an additional multi-layer perceptron to predict the number of atoms of graph from its latent representation $\mathbf{z}$. During inference, this model informs the decoder on how many nodes to attend to.

**Key Architectural Properties** Since no position embeddings are added to the input of the encoders self-attention layers, accumulated information in the single embedding node $v_0$ ($m_{0,0}$) is invariant to permutations of the input node order. Hence, the resulting graph embedding is permutation invariant. This is in stark contrast to classical graph autoencoder frameworks [8, 20, 21], that encode whole graphs effectively by concatenating all node embeddings which order permutes equivalently with the input node ordering. As no information about the node order is encoded in the graph embedding, the decoder learns its own (canonical) node order (each specific graph is deterministically decoded in). The input node order does not influence the decoded node order. As the decoder is based on permutation equivariant self-attention layers, this canonical order is completely defined with respect to the sequence of position embeddings used to initialize the decoders input. If the sequence of position embeddings is permuted, the decoded node order permutes equivalently. Thus, by predicting the right

Table 1: Negative log likelihood (NLL) and area under the receiver operating characteristics curve (ROC-AUC) for reconstruction of the adjacency matrix of graphs from different families. We compare our proposed method (PIGAE) with Graph Autoencoder (GAE) [8] and results of Graphite and Graph Autoencoder (GAE*) reported in [20].

| MODELS | ERDOS-RENYI | | BARABASI-ALBERT | | EGO | |
|---|---|---|---|---|---|---|
| | NLL | ROC-AUC | NLL | ROC-AUC | NLL | ROC-AUC |
| **PIGAE** | **20.5 ± 0.9** | **98.3 ± 0.1** | **27.2 ± 0.9** | **96.7 ± 0.2** | **23.4 ± 0.5** | **97.8 ± 0.3** |
| GAE | 186 ± 3 | 57.9 ± 0.1 | 199 ± 3 | 57.4 ± 0.1 | 191 ± 4 | 59.1 ± 0.1 |
| GAE* | 222 ± 8 | - | 236 ± 15 | - | 197 ± 2 | - |
| GRAPHITE | 196 ± 1 | - | 192 ± 2 | - | 183 ± 1 | - |

permutation matrix, input and output ordering can be align to correctly calculate the reconstruction loss. Input to the permuter model $[m_{1,1}, \ldots, m_{n+1,n+1}]$ is equivariant to permutations in the input node order (due to the equivaraint self-attention layers in the encoder). Since the permuter model itself is also permutation equivariant (node-wise linear layer), resulting permutation matrices $\mathbf{P}$ are equivariant to permutations in the input node order. Consequently, if the model can correctly reconstruct a graph in a particular node order, it can do it for all $n!$ input node orders.

## 3 Related Works

**Unsupervised Representation Learning on Graphs**  Most existing research on unsupervised graph representation learning focuses on *node-level* representation learning and can be broadly categorized in either shallow methods based on matrix factorization [22, 23, 24, 25] or random walks [26, 27], and deep methods based on Graph Neural Networks (GNN) [2, 3]. Kipf and Welling [8] proposed a graph autoencoder (GAE), reconstructing the adjacency matrix by taking the dot product between the latent node embeddings encoded by a GNN. Grover et al. [20] build on top of the GAE framework by parameterizing the decoder with additional GNNs, further refining the decoding process. Although *graph-level* representations in GAE-like approaches can be constructed by concatenating all node-level representations, note, that as a consequence they are only permutation-equivariant and not permutation invariant. Samanta et al. [21] proposed a GAE-like approach, which parameters are trained in a permutation-invariant way, following [28] utilizing breadth-first-traversals with randomized tie breaking during the child-selection step. However, as graph-level representations are still constructed by concatenation of node-level embeddings, this method still encodes graphs only in a permutation-equivariant way.
Research on *graph-level* representations has mainly focused on supervised learning, e.g., graph-level classification by applying a GNN followed by a node feature aggregation step (e.g., mean or max pooling) [4]. Research on graph-level unsupervised learning has not yet received much attention and existing work is only based on contrastive learning approaches. Narayanan et al. [29] adapted the *doc2vec* method from the field of natural language processing to represent whole graphs by a fixed size embedding, training a *skipgram* method on rooted subgraphs (*graph2vec*). Bai et al. [30] proposed a *siamese* network architecture, trained on minimizing the difference between the Euclidean distance of two encoded graphs and their graph editing distance. Recently, Sun et al. [31], adapted the *Deep InfoMax* architecture [32] to graphs, training on maximizing the mutual information between graph-level representations and representations of sub-graphs of different granularity (*InfoGraph*). Although these contrastive learning approaches can be designed to encode graphs in a permutation invariant way, they cannot be used to reconstruct or generate graphs from such representations.

**Deep Generative Models for Graphs**  Besides methods based on variational autoencoders [8, 20, 12], graph generative models have also been recently proposed based on generative adversarial neural networks [33, 34] and deep auto-regressive models [35, 28]. Moreover, due to its high practical value for drug discovery, many graph generating methods have been proposed for molecular graphs [36, 37, 38, 39, 21]. Although, generative models can be trained in a permuation invaraint way [36, 21], those models can not be used to extract graph representations.

To the best of our knowledge, our work proposes the first approach for non-contrastive permutation-invariant graph-level representation learning, that can also be used for graph generative modeling.

Figure 2: a) Euclidean distance over graph editing distance, averaged over 1000 Barabasi-Albert graphs with $m = 2$. b) t-SNE projection of representations from ten different graph families with different parameters. Example graphs are shown for some of the clusters. c) Legend of t-SNE plot explaining colours and symbols. Graph family abbreviations: Binomial (B), Binomial Ego (BE), Barabasi-Albert (BA), Geometric (G), Regular (R), Powerlaw Tree (PT), Watts-Strogatz (WA), Extended Barabasi-Albert (EBA), Newman-Watts-Strogatz (NWA), Dual-Barabasi-Albert (DBA).

## 4 Experimental Evaluation

We perform experiments on synthetic generated graphs and molecular graphs from the public datasets QM9 and PubChem. At evaluation time, predicted permutation matrices are always discretized to ensure their validity. For more details on training, see Appendix C.

### 4.1 Synthetic Data

**Graph Reconstruction**    In the first experiment we evaluate our proposed method on the reconstruction performance of graphs from graph families with a well-defined generation process. Namely, Erdos-Renyi graphs [40], with an edge probability of $p = 0.5$, Barabasi-Albert graphs [41], with $m = 4$ edges preferentially attached to nodes with high degree and Ego graphs. For each family we uniformly sample graphs with 12-20 nodes. The graph generation parameters match the ones reported in [20], enabling us to directly compare to Graphite. As additional baseline we compare against the Graph Autoencoder (GAE) proposed by Kipf and Welling [8]. As Grover et al. [20] only report negative log-likelihood estimates for their method Graphite and baseline GAE we also reevaluate GAE and report both negative log-likelihood (NLL) estimates for GAE to make a better comparison to Graphite possible (accounting for differences in implantation or the graph generation process). In Table 1 we show the evaluation metrics on a fixed test set of 25000 graphs for each graph family. On all four graph datasets our proposed model significantly outperforms the baseline methods, reducing the NLL error in three of the four datasets by approximately one magnitude.

**Qualitative evaluation**    To evaluate the representations learned by our proposed model, we trained a model on a dataset of randomly generated graphs with variable number of nodes from ten different graph families with different ranges of parameters (see Appendix B for details). Next, we generated a test set of graphs with a fixed number of nodes from these ten different families and with different fixed parameters. In total we generated graphs in 29 distinct settings. In Figure 2, we visualized the t-SNE projection [42] of the graph embeddings, representing different families by colour and different parameters within each family by different symbols. In this 2-D projection, we can make out distinct clusters for the different graph sets. Moreover, clusters of similar graph sets tend to cluster closer together. For example, Erdos-Renyi graphs form for each edge probability setting (0.25, 0.35, 0.5) a distinct cluster, while clustering in close proximity. As some graph families with certain parameters result in similar graphs, some clusters are less separated or tend to overlap. For example,

Table 2: Classification Accuracy of our method (PIGAE), InfoGraph (IG), Shortest Path Kernel (SP) and Weisfeiler-Lehman Sub-tree Kernel (WL) on graph class prediction.

| PIGAE | IG | SP | WL |
|---|---|---|---|
| **0.83 ± 0.01** | 0.75 ± 0.02 | 0.50 ± 0.02 | 0.73 ± 0.01 |

the Dual-Barabasi-Albert graph family, which attaches nodes with either $m_1$ or $m_2$ other nodes, naturally clusters in between the two Barabasi-Albert graph clusters with $m = m_1$ and $m = m_2$.

**Graph Editing Distance** A classical way of measuring graph similarity is the so called *graph editing distance* (GED) [43]. The GED between two graphs measures the minimum number of graph editing operations to transform one graph into the other. The set of operations typically includes inclusion, deletion and substitution of nodes or edges. To evaluate the correlation between similarity in graph representation and graph editing distance, we generated a set of 1000 Barabasi-Albert ($m = 3$) graphs with 20 nodes. For each graph we successively substitute an existing edge by a new one, creating a set of graphs with increasing GED with respect to the original graph. In Figure 2, we plot the mean Euclidean distance between the root graphs and their 20 derived graphs with increasing GED. We see a strong correlation between GED and Euclidean distance of the learned representations. In contrast to classical GAEs, random permutations of the edited graphs have no effect on this correlation (see Appendix D for comparison).

**Graph Isomorphism and Permutation Matrix** To empirical analyse if our proposed method detects isomorphic graphs, we generated for 10000 Barabasi-Albert graphs a randomly permuted version and a variation only one graph editing step apart. For all graphs the Euclidean distance between original graph and edited graph was at least greater than 0.3. The randomly permuted version always had the same embedding. Even for graphs out of training domain (geometric graphs with 128 nodes) all isomorphic and non-isomorphic graphs could be detected. Additionally, we investigated how well the permuter model can assign a permutation matrix to graph. As the high reconstruction performance in Table 1 suggest, most of the time, correct permutation matrices are assigned (See Appendix E for a more detailed analysis). We find that permutation matrices equivalently permute with the permutation of the input graph (See Appendix E).

**Graph Classification** In order to quantitatively evaluate how meaningful the learned representations are, we evaluate the classification performance of a Support Vector Machine (SVM) on predicting the correct graph set label (29 classes as defined above) from the graph embedding. As baseline we compare against SVMs based on two classical graph kernel methods, namely Shortest Path Kernel (SP) [44] and Weisfeiler-Lehman Sub-tree Kernel (WL) [45] as well as the recently proposed contrastive learning model InfoGraph (IG) [31]. In Table 2 we report the accuracy for each model and find the SVM based on representations from our proposed model to significantly outperform all baseline models.

### 4.2 Molecular Graphs

Next, we evaluate our proposed model on molecular graphs from the QM9 dataset [46, 47]. This datasets contains about 134 thousand organic molecules with up to 9 heavy atoms (up to 29 atoms/nodes including Hydrogen). Graphs have 5 different atom types (C, N, O, F and H), 3 different formal charge types (-1, 0 and 1) and 5 differ bond types (no-, single-, double-, triple- and aromatic bond). Moreover, the dataset contains an energetically favorable conformation for each molecule in form of Cartesian Coordinates for each atom. We transform these coordinates to an (rotation-invariant) Euclidean distance matrix and include the distance information as additional edge feature to the graph representation (More details in Appendix F).

**Graph Reconstruction and Generation** We define a holdout set of 10,000 molecules and train the model on the rest. Up on convergence, we achieve on the hold out set a balanced accuracy of 99.93% for element type prediction, 99.99% for formal charge type prediction and 99.25% for edge type prediction (includs prediction of non-existence of edges). Distances between atoms are reconstructed with a root mean squared error of 0.33Å and a coefficient of determination of $R^2 = 0.94$.

| Dataset | PIGAE (ours) | ECFP |
|---------|--------------|------|
| Classification (ROC-AUC ↑) | | |
| BACE | $0.824 \pm 0.005$ | $0.82 \pm 0.02$ |
| BBBP | $\mathbf{0.81 \pm 0.04}$ | $0.78 \pm 0.03$ |
| Regression (MSE ↓) | | |
| ESOL | $\mathbf{0.10 \pm 0.01}$ | $0.25 \pm 0.02$ |
| LIPO | $\mathbf{0.34 \pm 0.02}$ | $0.39 \pm 0.02$ |

Table 3: Downstream performance for molecular property prediction tasks.

Figure 3: Example Molecular conformations sampled around original graph representation.

In the field of computational chemistry and drug discovery, the generation of energetically reasonable conformations for molecules is a topic of great interest [48]. Since our model is trained on approximating the data generating process for molecules and their conformations, we can utilize the trained model to sample molecular conformations. To retrieve a set of conformations, we encode a query molecule into its latent representation and randomly sample around this point by adding a small noise and decode the resulting representations. We utilize *Multidimensional Scaling* (MDS) [49] to transform a decoded distance matrix back to Cartesian Coordinates. In Figure 3, we show examples of molecular conformations sampled from the trained model. Under visual inspection, we find that sampled conformations differ from encoded conformations, while still being energetically reasonable (e.g., rotation along rotatable bonds while avoiding clashes between atoms).

**Molecular Property Prediction**   Finally, we evaluate the learned representations for molecular property prediction. In order to accurately represent molecular graphs from different parts of the chemical space, we train our proposed model on a larger dataset retrieved from the public PubChem database [50]. We extracted organic molecules with up to 32 heavy atoms, resulting into a set of approximately 67 million compounds (more details in Appendix F). We evaluate the representations of the trained model based on the predictive performance of a SVM on two classification and two regression tasks from the MoleculeNet benchmark [51]. We compare representations derived from our pre-trained model with the state-of-the-art Extended Connectivity Fingerprint molecular descriptors (radius=3, 2048 dim) [52]. For each task and descriptor, the hyperparameter $C$ of the SVM was tuned in a nested cross validation. The results are presented in Table 3. Descriptors derived from our pre-trained model seem to represent molecular graphs in a meaningful way as they outperform the baseline on average in three out of four tasks.

## 5   Conclusion, Limitations and Future Work

In this work we proposed a permutation invariant autoencoder for graph-level representation learning. By predicting the relation (permutation matrix) between input and output graph ordering, our proposed model can directly be trained on node and edge feature reconstruction, while being invariant to a distinct node ordering. This poses, to the best of our knowledge, the first method for non-contrastive graph-level representation learning and might be an important step towards more powerful representation learning methods on graph structured data or sets in general. We demonstrate the effectiveness of our method in encoding graphs into meaningful representations and evaluate its competitive performance in various experiments. Although we propose a way of reducing the computational complexity by only attending on incoming messages in our directed message self-attention framework, in its current state, our proposed model is limited in the number of nodes a graph can consist of. However, recently, much work has been done on more efficient and sparse self-attention frameworks [53, 54, 55]. In future work, we aim at building up on this work to scale our proposed method to larger graphs. Moreover, we will investigate further into the generative performance of the proposed model, as this work was mainly concerned with its representation learning capability.

# References

[1] William L Hamilton, Rex Ying, and Jure Leskovec. Representation learning on graphs: Methods and applications. *arXiv preprint arXiv:1709.05584*, 2017.

[2] Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 34 (4):18–42, 2017.

[3] Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and S Yu Philip. A comprehensive survey on graph neural networks. *IEEE transactions on neural networks and learning systems*, 2020.

[4] David K Duvenaud, Dougal Maclaurin, Jorge Iparraguirre, Rafael Bombarell, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P Adams. Convolutional networks on graphs for learning molecular fingerprints. *Advances in neural information processing systems*, 28:2224–2232, 2015.

[5] Yujia Li, Daniel Tarlow, Marc Brockschmidt, and Richard Zemel. Gated graph sequence neural networks. *arXiv preprint arXiv:1511.05493*, 2015.

[6] Shaosheng Cao, Wei Lu, and Qiongkai Xu. Deep neural networks for learning graph representations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30, 2016.

[7] Daixin Wang, Peng Cui, and Wenwu Zhu. Structural deep network embedding. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 1225–1234, 2016.

[8] Thomas Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308v*, 2016.

[9] Jiezhong Qiu, Yuxiao Dong, Hao Ma, Jian Li, Kuansan Wang, and Jie Tang. Network embedding as matrix factorization: Unifying deepwalk, line, pte, and node2vec. In *Proceedings of the eleventh ACM international conference on web search and data mining*, pages 459–467, 2018.

[10] Shirui Pan, Ruiqi Hu, Guodong Long, Jing Jiang, Lina Yao, and Chengqi Zhang. Adversarially regularized graph autoencoder for graph embedding. *arXiv preprint arXiv:1802.04407*, 2018.

[11] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[12] Martin Simonovsky and Nikos Komodakis. Graphvae: Towards generation of small graphs using variational autoencoders. In *International Conference on Artificial Neural Networks*, pages 412–422. Springer, 2018.

[13] Minsu Cho, Jian Sun, Olivier Duchenne, and Jean Ponce. Finding matches in a haystack: A max-pooling strategy for graph matching in the presence of outliers. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2083–2090, 2014.

[14] Sebastian Prillo and Julian Eisenschlos. Softsort: A continuous relaxation for the argsort operator. In *International Conference on Machine Learning*, pages 7793–7802. PMLR, 2020.

[15] Aditya Grover, Eric Wang, Aaron Zweig, and Stefano Ermon. Stochastic optimization of sorting networks via continuous relaxations. *arXiv preprint arXiv:1903.08850*, 2019.

[16] Michael R Garey. A guide to the theory of np-completeness. *Computers and intractability*, 1979.

[17] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

[18] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008, 2017.

[19] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. *arXiv preprint arXiv:1704.01212*, 2017.

[20] Aditya Grover, Aaron Zweig, and Stefano Ermon. Graphite: Iterative generative modeling of graphs. In *International conference on machine learning*, pages 2434–2444. PMLR, 2019.

[21] Bidisha Samanta, Abir De, Gourhari Jana, Vicenç Gómez, Pratim Kumar Chattaraj, Niloy Ganguly, and Manuel Gomez-Rodriguez. Nevae: A deep generative model for molecular graphs. *Journal of machine learning research. 2020 Apr; 21 (114): 1-33*, 2020.

[22] Amr Ahmed, Nino Shervashidze, Shravan Narayanamurthy, Vanja Josifovski, and Alexander J Smola. Distributed large-scale natural graph factorization. In *Proceedings of the 22nd international conference on World Wide Web*, pages 37–48, 2013.

[23] Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps and spectral techniques for embedding and clustering. In *Nips*, volume 14, pages 585–591, 2001.

[24] Shaosheng Cao, Wei Lu, and Qiongkai Xu. Grarep: Learning graph representations with global structural information. In *Proceedings of the 24th ACM international on conference on information and knowledge management*, pages 891–900, 2015.

[25] Mingdong Ou, Peng Cui, Jian Pei, Ziwei Zhang, and Wenwu Zhu. Asymmetric transitivity preserving graph embedding. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 1105–1114, 2016.

[26] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 701–710, 2014.

[27] Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 855–864, 2016.

[28] Jiaxuan You, Rex Ying, Xiang Ren, William Hamilton, and Jure Leskovec. Graphrnn: Generating realistic graphs with deep auto-regressive models. In *International Conference on Machine Learning*, pages 5708–5717. PMLR, 2018.

[29] Annamalai Narayanan, Mahinthan Chandramohan, Rajasekar Venkatesan, Lihui Chen, Yang Liu, and Shantanu Jaiswal. graph2vec: Learning distributed representations of graphs. *arXiv preprint arXiv:1707.05005*, 2017.

[30] Yunsheng Bai, Hao Ding, Yang Qiao, Agustin Marinovic, Ken Gu, Ting Chen, Yizhou Sun, and Wei Wang. Unsupervised inductive graph-level representation learning via graph-graph proximity. *arXiv preprint arXiv:1904.01098*, 2019.

[31] Fan-Yun Sun, Jordan Hoffmann, Vikas Verma, and Jian Tang. Infograph: Unsupervised and semi-supervised graph-level representation learning via mutual information maximization. *arXiv preprint arXiv:1908.01000*, 2019.

[32] R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. *arXiv preprint arXiv:1808.06670*, 2018.

[33] Hongwei Wang, Jia Wang, Jialin Wang, Miao Zhao, Weinan Zhang, Fuzheng Zhang, Xing Xie, and Minyi Guo. Graphgan: Graph representation learning with generative adversarial nets. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

[34] Nicola De Cao and Thomas Kipf. Molgan: An implicit generative model for small molecular graphs. *arXiv preprint arXiv:1805.11973*, 2018.

[35] Yujia Li, Oriol Vinyals, Chris Dyer, Razvan Pascanu, and Peter Battaglia. Learning deep generative models of graphs. *arXiv preprint arXiv:1803.03324*, 2018.

[36] Jiaxuan You, Bowen Liu, Rex Ying, Vijay Pande, and Jure Leskovec. Graph convolutional policy network for goal-directed molecular graph generation. *arXiv preprint arXiv:1806.02473*, 2018.

[37] Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Junction tree variational autoencoder for molecular graph generation. In *International Conference on Machine Learning*, pages 2323–2332. PMLR, 2018.

[38] Rafael Gómez-Bombarelli, Jennifer N Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, Ryan P Adams, and Alán Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. *ACS central science*, 4(2):268–276, 2018.

[39] Rocío Mercado, Tobias Rastemo, Edvard Lindelöf, Günter Klambauer, Ola Engkvist, Hongming Chen, and Esben Jannik Bjerrum. Graph networks for molecular design. *Machine Learning: Science and Technology*, 2020.

[40] Paul Erdős and Alfréd Rényi. On the evolution of random graphs.

[41] Albert-László Barabási and Réka Albert. Emergence of scaling in random networks. *science*, 286(5439):509–512, 1999.

[42] Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

[43] Alberto Sanfeliu and King-Sun Fu. A distance measure between attributed relational graphs for pattern recognition. *IEEE transactions on systems, man, and cybernetics*, (3):353–362, 1983.

[44] Karsten M Borgwardt and Hans-Peter Kriegel. Shortest-path kernels on graphs. In *Fifth IEEE international conference on data mining (ICDM'05)*, pages 8–pp. IEEE, 2005.

[45] Nino Shervashidze, Pascal Schweitzer, Erik Jan Van Leeuwen, Kurt Mehlhorn, and Karsten M Borgwardt. Weisfeiler-lehman graph kernels. *Journal of Machine Learning Research*, 12(9), 2011.

[46] Lars Ruddigkeit, Ruud Van Deursen, Lorenz C Blum, and Jean-Louis Reymond. Enumeration of 166 billion organic small molecules in the chemical universe database gdb-17. *Journal of chemical information and modeling*, 52(11):2864–2875, 2012.

[47] Raghunathan Ramakrishnan, Pavlo O Dral, Matthias Rupp, and O Anatole Von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific data*, 1(1):1–7, 2014.

[48] Paul CD Hawkins. Conformation generation: the state of the art. *Journal of Chemical Information and Modeling*, 57(8):1747–1756, 2017.

[49] Joseph B Kruskal. *Multidimensional scaling*. Number 11. Sage, 1978.

[50] Sunghwan Kim, Paul A Thiessen, Evan E Bolton, Jie Chen, Gang Fu, Asta Gindulyte, Lianyi Han, Jane He, Siqian He, Benjamin A Shoemaker, et al. Pubchem substance and compound databases. *Nucleic acids research*, 44(D1):D1202–D1213, 2016.

[51] Zhenqin Wu, Bharath Ramsundar, Evan N Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S Pappu, Karl Leswing, and Vijay Pande. Moleculenet: a benchmark for molecular machine learning. *Chemical science*, 9(2):513–530, 2018.

[52] David Rogers and Mathew Hahn. Extended-connectivity fingerprints. *Journal of chemical information and modeling*, 50(5):742–754, 2010.

[53] Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*, 2019.

[54] Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International Conference on Machine Learning*, pages 3744–3753. PMLR, 2019.

[55] Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. *arXiv preprint arXiv:2001.04451*, 2020.