Sparsely Changing Latent States for Prediction and Planning in Partially Observable Domains

Abstract

A common approach to prediction and planning in partially observable domains is to use recurrent neural networks (RNNs), which ideally develop and maintain a latent memory about hidden, prediction-relevant, generative factors. We hypothesize that many of these hidden factors in the physical world are constant over time, changing only sparsely. We propose Gated L_0 Regularized Dynamics (GateL0RD), a novel recurrent architecture that incorporates the inductive bias to maintain stable, sparsely changing latent states. The bias is implemented by means of a novel internal gating function and a penalty on the L_0 norm of latent state changes. We demonstrate that GateL0RD can compete with or outperform state-of-the-art RNNs in different partially observable temporal prediction and planning tasks, especially when long-term memorization is required. GateL0RD tends to encode the underlying generative factors of the environment, ignores spurious temporal dependencies, and generalizes better, which translates to improved performance in model-based planning. Moreover, we show that the resulting latent states can be easily interpreted, which is a step towards better explainability in RNNs.

1 Introduction

When does the meeting start? Where are my car keys? Is the stove turned off? Humans memorize lots of information over extended periods of time. In contrast, classical planning methods assume that the state of the environment is fully observable at every time step [1]. This assumption does not hold for realistic applications, where generative processes are only indirectly observable or entities are occluded. Planning in such Partially Observable Markov Decision Processes (POMDP) is a challenging problem, because suitably-structured memory is required for decision making.

Recurrent neural networks (RNNs) are often used to deal with partial observability [2–4]. They encode past observations by maintaining latent states, which are iteratively updated. However, continuously updating the latent state causes past information to get quickly "washed out". Long-Short Term Memory networks (LSTM, [5]) and Gated Recurrent Units (GRU, [6]) deal with this problem by using internal gates. However, they cannot leave their latent states completely unchanged, because small amounts of information continuously leak through the sigmoidal gating functions. Additionally, inputs need to mostly pass through the latent state to affect the output, making it hard to disentangle observable from unobservable information within their latent states.

Our hypothesis is that many generative latent factors in the physical world are constant over extended periods of time. Thus, there might not be the need to update memory at every time step. For example, consider dropping an object: If the drop-off point as well as some latent generative factors, such as gravity and aerodynamic object properties, are known, iteratively predicting the fall can be reasonably accomplished by a non-recurrent process. Similarly, when an agent stores a key in an opaque box, it is sufficient to memorize that the key is inside this box. However, latent factors typically do change

significantly and systematically at particular points in time. For example, the aerodynamic properties of an object change drastically when the falling object shatters on the floor, and the location of the key changes systematically when the agent removes it from the box. If the latent factors are known, a Markovian process can generate fairly accurate predictions. Typically, though, relevant latent factors are unknown and our memory needs to learn to encode them suitably.

Very similar propositions have been made for human cognition. Humans tend to perceive their stream of sensory information in terms of events [7–11]. Event Segmentation Theory (EST) [11] postulates a set of active predictive event models, which encode event-respective aspects over extended periods of time and switch individually at event transitions. To learn about the transitions and consolidate associated latent event encodings, measurements of surprise and other significant changes in predictive model activities have been proposed as suitable event segmentation biases [11–14].

In accordance to EST and our sparsely changing latent factor assumption, we introduce Gated L_0 Regularized Dynamics (GateL0RD). GateL0RD applies L_0-regularized gates, inducing an inductive learning bias to encode piecewise constant latent state dynamics. GateL0RD thus becomes able to memorize task-relevant information over long periods of time. The main contributions of this work can be summarized as follows. (i) We introduce a stochastic, rectified gating function for controlling latent state updates, which we regularize towards sparse updates using the L_0 norm. (ii) We demonstrate that our network achieves predictions that are as accurate or better than predictions by state-of-the-art RNNs in various partially-observable problems with piecewise constant dynamics. (iii) We also show that the inductive bias leads to better generalization under distributional shifts. (iv) Lastly, we show that the latent states can be easily interpreted by humans.

2 Background

Let $f_\theta : \mathcal{X} \times \mathcal{H} \to \mathcal{Y} \times \mathcal{H}$ be a recurrent neural network (RNN) with learnable parameters θ mapping inputs[1] $\boldsymbol{x}_t \in \mathcal{X}$ and $\boldsymbol{h}_t \in \mathcal{H}$ the latent (hidden) state to the output $\hat{\boldsymbol{y}}_t \in \mathcal{Y}$ and updated latent states $\boldsymbol{h}_{t+1}$. The training dataset $\mathcal{D}$ consists of sequences of input-output pairs $d = [(\boldsymbol{x}_1, \boldsymbol{y}_1), \dots, (\boldsymbol{x}_T, \boldsymbol{y}_T)]$ of length T.

In this paper, we consider the prediction and control of systems that can be described by partially observable Markov decision processes (POMDP) with state space $\mathcal{S}$, action space $\mathcal{A}$, observations space $\mathcal{O}$, and deterministic hidden transitions $\mathcal{S} \times \mathcal{A} \to \mathcal{S}$. We consider the prediction of sequences generated from a POMDP with [2] $\mathcal{X} = \mathcal{O} \times \mathcal{A}$ and $\mathcal{Y} = \mathcal{O}$. For control, we use model-predictive control using shooting methods [15] that optimize the actions using the predictive model.

3 L_0-regularization of latent state changes

We want the RNN f_θ to solve the prediction task defined by $\mathcal{D}$, while maintaining piecewise constant latent states over time. The network creates a dynamics of latent states $\boldsymbol{h}_t$ when applied to a sequence: $(\hat{\boldsymbol{y}}_t, \boldsymbol{h}_t) = f_\theta(\boldsymbol{x}_t, \boldsymbol{h}_{t-1})$ starting from some $\boldsymbol{h}_0$. The most suitable measure to determine how much a time-series is piecewise constant is the L_0 norm applied to temporal changes. With the change in latent state as $\boldsymbol{\Delta h}_t = \boldsymbol{h}_{t-1} - \boldsymbol{h}_t$ we define the L_0-loss as

$$\mathcal{L}_{L_0}(\boldsymbol{\Delta h}) = \|\boldsymbol{\Delta h}\|_0 = \sum_{j=1} \mathbb{I}(\Delta h^j \neq 0), \tag{1}$$

which penalizes the **number of non-zero entries** of the vector of latent state changes $\boldsymbol{\Delta h}$.

The regularization loss from Eq. 1 can be combine in the usual way with the task objective to yield the overall learning objective $\mathcal{L}$ of the network:

$$\mathcal{L}(\mathcal{D}, \theta) = \mathbb{E}_{d \sim \mathcal{D}} \Big[\sum_t \mathcal{L}_{\text{task}}(\hat{\boldsymbol{y}}_t, \boldsymbol{y}_t) + \lambda \mathcal{L}_{L_0}(\boldsymbol{\Delta h}_{t+1}) \Big] \tag{2}$$

---

[1]Notation: Bold lowercase letters denote vectors (e.g., $\boldsymbol{x}$). Vector dimensions are denoted by superscript (e.g. $\boldsymbol{x} = [x^1, x^2, \dots, x^n] \in \mathbb{R}^n$). Time or other additional information is denoted by subscript (e.g., $\boldsymbol{x}_t$).

[2]We treat the prediction of time series without any actions as a special case of the POMDP with $\mathcal{A} = \emptyset$.

with $(\hat{\boldsymbol{y}}_t, \boldsymbol{h}_t) = f_\theta(\boldsymbol{x}_t, \boldsymbol{h}_{t-1})$. The task-dependent loss $\mathcal{L}_{\text{task}}(\cdot, \cdot)$ can be, for instance, the mean-squared error for regression or cross-entropy loss for classification. The hyperparameter λ controls the trade-off between the task-based loss and the desired latent state regularization.

Unfortunately, we cannot directly minimize this loss using gradient-based techniques, such as stochastic gradient descent (SGD), due to the non-differentiability of the L_0-term. However, Louizos et al. [16] propose a way to learn L_0 regularization of the learnable parameters of a neural network with SGD. They achieve this by using a set of stochastic gates controlling the parameters' usage. Each learnable parameter θ^j that is subject to the L_0 loss is substituted by a gated version $\theta'^j = \Theta(s^j)\theta^j$ where $\Theta(\cdot)$ is the Heaviside step function ($\Theta(s) = 0$ if $s \leq 0$ and 1 otherwise) and $\boldsymbol{s}$ is determined by a distribution $q(\boldsymbol{s}|\boldsymbol{\nu})$ with learned parameters $\boldsymbol{\nu}$. Thus, θ'^j is only non-zero if $s^j > 0$. This allows to rewrite the L_0 loss (Eq. 1) for θ' as:

$$\mathcal{L}_{L_0}(\boldsymbol{\theta'}, \boldsymbol{\nu}) = \|\boldsymbol{\theta'}\|_0 = \sum_j \Theta(s^j) \qquad \text{with } \boldsymbol{s} \sim q(\boldsymbol{s}; \boldsymbol{\nu}), \qquad (3)$$

where parameters $\boldsymbol{\nu}$ influence sparsity and are affected by the loss.

To tackle the problem of non-differentiable binary gates, we can use a smooth approximation as a surrogate [16–18]. Alternatively, we can substitute its gradients during the backward pass, for example using the straight-through estimator [19], which treats the step function as a linear function during the backward pass, or approximate its gradients as in the REINFORCE algorithm [20]. We we will employ a variation of the straight-through estimator.

To transfer this approach to regularize the latent state dynamics in an RNN, we require an internal gating function $\Lambda(\cdot) \in [0, 1]$, which controls whether the latent state is updated or not. For instance:

$$\boldsymbol{h}_t = \boldsymbol{h}_{t-1} + \Lambda(\boldsymbol{s})\boldsymbol{\Delta}\tilde{\boldsymbol{h}}_{t-1} \qquad \text{with } \boldsymbol{\Delta}\tilde{\boldsymbol{h}}_{t-1} = \tilde{\boldsymbol{h}}_t - \boldsymbol{h}_{t-1} \qquad (4)$$

where $\tilde{\boldsymbol{h}}$ is the proposed new latent state and s is a stochastic variable depending on the current input and previous latent state and the parameters, i.e. $\boldsymbol{s}_t \sim q(\boldsymbol{s}_t; \boldsymbol{x}_t, \boldsymbol{h}_{t-1}, \boldsymbol{\nu})$. For brevity, we merge the parameters $\boldsymbol{\nu}$ into the overall parameter set, i.e. $\boldsymbol{\nu} \subset \boldsymbol{\theta}$. For computing Eq. 2 we need to binarize the gate by applying the step function $\Theta(\Lambda(s))$. Thus we can rewrite Eq. 2 as

$$\mathcal{L}(\mathcal{D}, \theta) = \mathbb{E}_{d \sim \mathcal{D}}\Big[\sum_t \mathcal{L}_{\text{task}}(\hat{\boldsymbol{y}}_t, \boldsymbol{y}_t) + \lambda \sum_t \Theta(\Lambda(\boldsymbol{s}_t)) \Big]. \qquad (5)$$

LSTMs and GRUs use deterministic sigmoidal gates for Λ in Eq. 4 to determine how to update their latent state. However, it is not straight forward to apply this approach to them (detailed in Suppl. A). Thus, we instead introduce a novel RNN, that merges components from GRUs and LSTMs, to implement the proposed L_0 regularization of latent state changes while still allowing the network to make powerful predictions. We name our network Gated L_0 Regularized Dynamics (GateL0RD).

4 GateL0RD

The core of GateL0RD implements the general mapping $(\hat{\boldsymbol{y}}_t, \boldsymbol{h}_{t+1}) = f_\theta(\boldsymbol{x}_t, \boldsymbol{h}_t)$ using three functions, or subnetworks: (1) a *recommendation network* r, which proposes a new candidate latent state, (2) a *gating network* g, which determines how the latent state is updated, and (3) an *output function*, which computes the output based on the updated latent state and the input. The network is systematically illustrated in Fig. 1a.

The overall processing is described by the following equations:

$$\boldsymbol{s_t} \sim \mathcal{N}(g(\boldsymbol{x}_t, \boldsymbol{h}_{t-1}), \boldsymbol{\Sigma}) \qquad \text{(sample gate input)} \qquad (6)$$
$$\Lambda(\boldsymbol{s}) := \max(0, \tanh(\boldsymbol{s})) \qquad \text{(new gating function)} \qquad (7)$$
$$\boldsymbol{h}_t = \boldsymbol{h}_{t-1} + \Lambda(\boldsymbol{s_t}) \odot (r(\boldsymbol{x}_t, \boldsymbol{h}_{t-1}) - \boldsymbol{h}_{t-1}) \qquad \text{(update or keep latent state)} \qquad (8)$$
$$\hat{\boldsymbol{y}}_t = p(\boldsymbol{x}_t, \boldsymbol{h}_t) \odot o(\boldsymbol{x}_t, \boldsymbol{h}_t), \qquad \text{(compute output)} \qquad (9)$$

where $\odot$ denotes element-wise multiplication (Hadamard product).

(a) Illustration of the core of GateL0RD.   (c) Θ with its substitution   (d) Overall GateL0RD

Figure 1: (a) GateL0RD with its three subnetworks. The *gating function* controls the latent state update (red), the *recommendation function* computes a new latent state (blue) and the output function computes the output (purple). (b) Gate-activation function Λ (ReTanh). (c) Heaviside step function Θ and its gradient estimator. (d) Overall architecture with input preprocessing (f_{pre}), postprocessing of the network output (f_{post}), and a hidden state initialization network (f_{init}).

We start with the control of the latent state in Eq. 8. Following Eq. 4, a new latent value is proposed by the *recommendation function* $r(\boldsymbol{x}_t, \boldsymbol{h}_{t-1})$ and the update is "gated" by $\Lambda(\boldsymbol{s})$. Importantly, if $\Lambda(\boldsymbol{s}) = \boldsymbol{0}$ no change to the latent state occurs. Note that the the update Eq. 8 is in principle equivalent to the latent state update in GRUs [6], for which it is typically written as $\boldsymbol{h}_t = \Lambda(\boldsymbol{s}) \odot r(\boldsymbol{x}_t, \boldsymbol{h}_{t-1}) + (1 - \Lambda(\boldsymbol{s})) \odot \boldsymbol{h}_{t-1}$ with $\Lambda(\boldsymbol{s})$ a deterministic sigmoidal gate.

Because we aim for piecewise constant latent states, the gating function Λ defined in Eq. 7 needs to be able to output exactly zero. A potential choice would be the Heaviside function, i.e. either copy the new latent state or keep the old one. This, however, does not allow any multiplicative computation. So a natural choice is to combine the standard sigmoid gate of RNNs with the step-function: $\Lambda(\boldsymbol{s}) = \max(0, \tanh(\boldsymbol{s}))$ which we call ReTanh (rectified tanh)[3]. Figure 1b shows the activation function Λ depending on its input. The gate is closed ($\Lambda(s^i) = 0$) for all inputs $s^i \leq 0$. Naturally, a closed gate results in a latent state that remains constant in dimension i, i.e., $h_t^i = h_{t-1}^i$. On the other hand, for $s^i > 0$ the latent state is interpolated between the proposed new value and the old one, as done in LSTMs and GRUs.

The next puzzle piece is the input to the gate. Motivated from the L_0 regularization in Eq. 1 we use a stochastic input. However, in our RNN setting, it should depend on the current situation. Thus, we use a Gaussian distribution for q with the mean determined by the *gating network* $g(\boldsymbol{x}_t, \boldsymbol{h}_{t-1})$ as defined in Eq. 6. We chose a fixed diagonal covariance matrix $\boldsymbol{\Sigma}$, which we set to $\Sigma^{i,i} = 0.1$. To train our network using backpropagation, we implement the sampling using the *reparametrization trick* [21]. Accordingly, we introduce a noise variable ϵ and compute the gate activation as

$$\boldsymbol{s}_t = g(\boldsymbol{x}_t, \boldsymbol{h}_{t-1}) + \boldsymbol{\epsilon} \qquad \text{with } \boldsymbol{\epsilon} \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{\Sigma}). \qquad (10)$$

During testing we set $\boldsymbol{\epsilon} = \boldsymbol{0}$ to achieve maximally accurate predictions.

Finally the output $\hat{\boldsymbol{y}}$ is computed from the inputs and the new latent state $\boldsymbol{h}_t$ in Eq. 9. Inspired by LSTMs [5], the output is determined by a multiplication of a normal branch ($p(\boldsymbol{x}_t, \boldsymbol{h}_t)$) and a sigmoidal gating branch ($o(\boldsymbol{x}_t, \boldsymbol{h}_t)$). We thus enable both additive as well as multiplicative effects of $\boldsymbol{x}_t$ and $\boldsymbol{h}_t$ on the output, enhancing the expressive power of the piecewise constant latent states.

In our implementation, all subnetworks are MLPs. r, f use a $\tanh$ output activation; o uses a sigmoid; g has a linear output. f, o are one-layer networks. By default, r, g are one-layer networks. However, when comparing against deep (stacked) RNNs, we increase the number of layers of r and g to up to three (cf. Suppl. B).

The loss defined in Eq. 5 is appropriate, but we still simplify the regularization term $\Theta(\Lambda(\boldsymbol{s}))$. We only want to penalize that the gate is open. With our implementation of Λ the same loss value is obtained when considering just $\Theta(\boldsymbol{s})$. Thus, we end up with

$$\mathcal{L}(\mathcal{D}, \boldsymbol{\theta}) = \mathbb{E}_{d \sim \mathcal{D}} \Big[\sum_t \mathcal{L}_{\text{task}}(\hat{\boldsymbol{y}}_t, \boldsymbol{y}_t) + \lambda \sum_t \Theta(\boldsymbol{s}_t) \Big]. \qquad (11)$$

---

[3]Note that $\tanh(s) = 2 \cdot \text{sigmoid}(s) - 1$.

GateL0RD is fully differentiable except for the Heaviside step function in Equation 11. A simple approach to deal with discrete variables is to approximate the gradients of the undifferentiable function by a differentiable estimator [18, 19]. In contrast to previous approaches, we substitute the gradients of the Heaviside function Θ by the derivative of the ReLU-function (see Fig. 1c):

$$\frac{\partial \Theta(x)}{\partial x} = \begin{cases} 1 & \text{if } x > 0, \\ 0 & \text{otherwise.} \end{cases} \tag{12}$$

In this way, if a gate is open, gradient information is available to enable learning to close the gate. If the gate is already closed, the gradients of the L_0-regularization are exactly zero and do not affect the weights controlling this gate. In Suppl. C.2 we analyze the effect of the gradient estimator.

We found that the performance of GateL0RD, and also those of other RNNs, can be improved if the network input is preprocessed by an MLP $f_{\mathrm{pre}}(\boldsymbol{x}_t)$ and similarly when its output is postprocessed by an MLP $f_{\mathrm{post}}(\hat{\boldsymbol{y}}_t)$ (i.e. a readout layer) before computing the loss. The latent state $\boldsymbol{h}_0$ of GateL0RD could be initialized by $\boldsymbol{0}$. However, improvements are achieved if the latent state is instead initialized by a context network f_{init}, a shallow MLP that sets $\boldsymbol{h}_0$ based on the first input [22, 23]. The full architecture with pre-, postprocessing and hidden state initialization is illustrated in Fig. 1d.

5 Related Work

Loss-based regularization of latent updates: For latent state regularization, Krueger and Memisevic [24] have proposed using an auxiliary loss term that punishes the change in L_2-norms of the latent state, which results in piecewise constant norms but not dynamics of the hidden states.

Temporal latent state regularization: To structure latent state updates, the Clockwork RNN [25] partitions the hidden neurons of an RNN into separate modules, where each module operates at its own predefined frequency. Along similar lines, Phased LSTMs [26] use gates that open periodically. The update frequency does not depend on the world state, but only on a predefined time scale.

Binarized update gates: Closely related to our ReTanh, Skip RNNs [27] use a binary gate to determine latent state update decisions. Similarly, Gumbel-Gate LSTMs [28] replace sigmoid input and forget gates with stochastic, binary gates, approximated by a Gumbel-Softmax estimator [18]. Selective-Activation RNNs (SA-RNNs) [29] modify a GRU by masking the latent state with deterministic, binary gate and also incentivize sparsity. However, for GRUs the network output corresponds to the networks' latent state, thus, a piecewise constant latent state will result in piecewise constant outputs. All of these models were designed for classification or language processing tasks – none were applied on regression problems in a POMDP setup we consider here.

Attention-based latent state updates: Sparse latent state updates can also be achieved using attention [30–32]. Neural Turing Machines (NTMs) [30] use an attention mechanism to update an external memory block. Thereby, the attention mechanism can focus on particular locations within the memory and only modify those within an update. However, sparsity of memory updates is not incentivized. Recurrent Independent Mechanisms (RIMs) [33] use a set of recurrent cells that only sparsely interact with the environment and one another through competition and a bottleneck of attention. For RIMs the sparsity of the latent state changes is predefined via a hyperparameter that sets the number of active cells, as opposed to our L_0 loss, which implements a soft constraint.

Transformers: Transformers [32] omit memory altogether, processing a complete sequence for every output at once using key-based attention. While this avoids problems arising from maintaining a latent state, their self-attention mechanism comes with high computational cost. Transformers have shown breakthrough success in natural language processing. However, it remains challenging to train them for planning or reinforcement learning applications in partially-observable domains [34].

6 Experiments

Our experiments offers answers to the following questions: (a) Does GateL0RD generalize better to out-of-distribution inputs in partially observable domains than other commonly used RNNs? (b) Does GateL0RD's update strategy enable the long-term memorization of information? (c) Is GateL0RD's developing memory structure well-suited for model-based planning in POMDPs? Accordingly, we demonstrate GateL0RD's ability to generalize from a 1-step prediction regime to autoregressive

| (a) Billiard Ball | (b) Robot Remote Control | (c) Shepherd | (d) Fetch Pick&Place |

Figure 2: Simulations used to test GateL0RD. (a)-(c) are continuous 2d-simulation and control tasks: (a) predicting a ball trajectory; (b) triggering the control of a simple robot; (c) memorizing a sheep position to capture it. While (d) is the Fetch Pick&Place environment of OpenAI Gym.

N-step prediction and its prediction robustness when facing action rollouts from different synthetic policies. We then reveal precise memorization abilities. We evaluate the generalization and memorization abilities both in terms of prediction accuracy as well as model-based planning performance. Finally, we examine exemplary latent state codes demonstrating their explainability.

In our experiments we compare GateL0RD to LSTMs [5], GRUs [6], and Elman RNNs [35]. We use the architecture shown in Fig. 1d for all networks, only replacing the core f_θ. At time t the networks received as an input $x_t = (o_t, a_t)$ with observations $o_t \in \mathcal{O}$ and actions $a_t \in \mathcal{A}$ and were trained to predict the change in observation, i.e. $y_t = \Delta o_{t+1}$. During testing the next observational inputs were generated autoregressively as $\hat{o}_{t+1} = o_t + \hat{y}_t$. The networks were trained using Adam [36], with learning rates and layer numbers determined via grid search for each network type individually (detailed in Appendix B.1). Each experiment was run with 10 random initializations.

We evaluate GateL0RD in four partially observable scenarios, shown in Fig. 2. In the **Billiard Ball** scenario a single ball, simulated in a realistic physics simulator, is shot on a pool table with low friction from a random position in a random direction with randomly selected velocity (Fig. 2a). The time series contain only the positions of the ball. This is the only considered scenario without actions.

Robot Remote Control is a continuous control problem where an agent moves according to the two-dimensional actions a_t (Fig. 2b). Once the agent reaches a fixed position (terminal), a robot in another room is also controlled by the actions. The observable state o_t is composed of the agent's position and the robot's position. Thus, whether the robot is controlled or not is not observable. When planning, the goal is to move the robot to a particular goal position (orange square).

Shepherd is a challenging continuous control problem that requires long-term memorization (Fig. 2c). Here, the agent's actions a_t are the two movement directions and a grasp action controlling whether to pick up or drop the cage. A sheep starts at the top of the scene moving downwards with a fixed randomly generated velocity. The sheep is occluded by the wall, which masks its position from the observation. If the agent reaches the lever, a gate inside the wall opens, and the sheep appears again at the same horizontal position at the open gate. The goal is to get the sheep to enter the previously placed cage. The challenge is to memorize the sheep's horizontal position exactly over a potentially long time, to be able to predict where the sheep will reappear. The seven-dimensional observation o_t is composed of the height of the occluder and the positions of all entities.

Fetch Pick&Place (OpenAI Gym v1, [37]) is a benchmark reinforcement learning task where a robotic manipulator has to move a box, which is randomly placed on a table (Fig. 2d). In our modified setting,[4] the observable state o_t is composed of the gripper- and object position, the offset between object and gripper, and the relative positions of the fingers along the gripper. The four-dimensional actions a_t control the position of the gripper and opening the fingers.

6.1 Learning autoregressive predictions

First, we consider the problem of autoregressive N-step prediction in the **Billiard Ball** scenario. Here, during testing the networks receive the first two ball positions as input and predict a sequence of 50 ball positions. We first train the RNNs using *teacher forcing*, whereby the real inputs are fed to the networks. Figure 3a shows the prediction error for autoregressive predictions over epochs. Only GateL0RD, with latent state regularization ($\lambda = 0.001$) is able to achieve reasonable predictions using this setup. The other RNNs seem to learn to continuously update their estimates of the ball's

---

[4]We omit all velocities and the rotation of the object to make the scenario partially observable.

Figure 3: Billiard Ball results: Prediction errors when trained using teacher forcing (a), or using scheduled sampling (b). GateL0RD's prediction error (c) and mean number of latent state updates (d) for different values of λ. Shaded areas depict the standard deviation.

velocity based on the real inputs. GateL0RD's sparse update strategy punishes continuous updates, thus learning to update the velocity estimation only when required, that is, when the ball collides with walls or drops into pockets. As a result, GateL0RD's predictions are more accurate during testing, when the inputs are generated by the network itself.

The problems of RNNs learning autoregressive prediction are well known [38, 39]. A simple countermeasure is *scheduled sampling* [38], where each input is stochastically determined to be either the last network's output or the real input. The probability of using the network output increases over time. While the prediction accuracy of all RNNs improves when trained using scheduled sampling, GateL0RD ($\lambda = 0.001$) still achieves the lowest mean prediction error (see Fig. 3b).

How does the regularization affect the prediction? Figure 3c shows the prediction error for GateL0RD for different setting of λ. While a small regularization ($\lambda = 0.001$) leads to the highest accuracy in this scenario, similar predictions are obtained for different strengths ($\lambda \in [0, 0.01]$). Naturally, overly strong regularization ($\lambda = 0.1$) leads to degraded performance. Figure 3d shows the average latent state changes per sequence (computed as $\mathbb{E}_{i,t}(\Theta(s_t^i))$). As indented, λ directly affects how often GateL0RD's latent state is updated: a higher value results in fewer latent state changes.

6.2 Generalization across policies

Particularly when priorities change or an agent switches behavior, different spurious temporal correlations can occur in the resulting sensorimotor timeseries data. Consequently, predictive models are needed that generalize across those correlations. We use the **Robot Remote Control** scenario to investigate this aspect. The training data is generated by performing rollouts with 50 time steps of a policy that produces random but linearly magnitude-increasing actions. The actions' magnitude in the training data is positively correlated with time, which is a spurious correlation that does not alter the underlying transition function of the environment in any way. We test the networks using data generated by the same policy (*test set*) and generated by a policy that samples uniformly random actions (*generalization set*). We evaluate the networks on predicting the sequence of observations given the initial observation and a sequence of actions. Besides, we use the trained RNNs for model-predictive control (MPC) using iCEM [15], a random shooting method that iteratively optimizes its actions to move the robot to the given goal position.

As shown in Fig. 4a, GateL0RD ($\lambda = 0.001$), outperforms all other RNNs on the test set. When tested on the generalization data, the prediction errors of the GRU and LSTM networks even increase over the course of training and only GateL0RD is able to maintain a reasonable prediction. Figure 4c shows the MPC performance. GateL0RD yields the highest success rate, whereas improvement in the other networks is much slower (Elman RNN, GRU) or even decreases (LSTM).

Note that the lack of generalization is not primarily caused by the choice of hyperparameters: even when the learning rate of the other RNNs was determined based on the lowest validation error on the generalization set, GateL0RD still outperformed them (additional experiment in Suppl. D.2) Instead, GateL0RD's better performance is likely because it only encodes unobservable information within its latent state $\boldsymbol{h}_t$, as shown exemplarily in Fig. 4d (bottom row). The latent state remains constant and only one dimension changes once the agent starts to control the robot's position (middle row) through its actions. Because the other RNNs also encode observable information, such as actions, within their latent state, they are more negatively affected by distributional shifts and spurious dependencies.

Figure 4: Robot Remote Control results: Prediction error on the test set (a) and on the generalization set (b). Success rate for MPC (c). Shaded areas show standard deviation (a-b) or standard error (c). Exemplary generalization sequence (d) showing the agent's positions (top), the robot's positions (middle) with GateL0RD's predictions shown as dots, and GateL0RD's latent states (bottom).

6.3 Long-term memorization

We hypothesized that GateL0RD's latent state update strategy fosters the exact memorization of unobservable information, which we examine in the **Shepherd** task. We test the RNNs' when predicting sequences of 100 observations given the first two observations and a sequence of actions. Again, we use the trained models for MPC using iCEM [15], aiming at catching the sheep by first placing a cage and then pulling a lever. This is particularly challenging to plan, because the sheep's horizontal position needs to be memorized before it is occluded for quite some time (> 30 steps), to be able to accurately predict and thus place the cage at the sheep's future position.

Figure 5a shows the prediction errors during training. GateL0RD ($\lambda = 0.001$) continuously achieves a lower prediction error than the other networks. Apparently, it is able to accurately memorize the sheep's future position while occluded. To investigate the memorization we consider the situation occurring during planning: the sequence of (past) observations is fed into the network and the prediction error of the sheep's horizontal position at the time of reappearance is evaluated (Fig. 5b). Only GateL0RD reliably learns to predict where the sheep will appear when the lever is activated. GRU and Elman RNNs do not noticeably improve in predicting the sheep's position. LSTMs take much longer to improve their predictions and do not reliably reach GateL0RD's level of accuracy. This is also reflected in the success rate when the networks are used for MPC (Fig. 5c). Only GateL0RD manages to solve this challenging task with a mean success rate over 50%.

6.4 Explainability of the latent states

Lastly, we analyze the latent representations of GateL0RD, starting with **Billiard Ball**. Figure 6a shows one exemplary ball trajectory in white and the prediction in red. Inputs for which at least one gate opened are outlined in black. Figure 6b shows the corresponding latent states h_t relative to the initial latent state h_0. GateL0RD updates two dimensions of its latent states around the points of collisions to account for the changes in x- and y-velocity of the ball. For $\lambda = 0.01$ we find on average only two latent state dimensions change per sequence (see Suppl Suppl. D.1), which hints at

Figure 5: Shepherd results: Prediction error for 100-step predictions (a) and 1-step prediction errors of the sheep's $x-$position at the time step of reappearance (b). Success rate for capturing the sheep using MPC (c). Shaded areas show standard deviation (a-b) or standard error (c).

Figure 6: Example sequences: (a) Billiard Ball trajectory with real positions shown in white, provided inputs in blue, predicted positions (GateL0RD, $\lambda = 0.01$) in red (saturation increasing with time). The inputs for which at least one gate opened are outlined in black. (b) The latent states for the trajectory for GateL0RD, GRU, and LSTM. (c) Fetch Pick&Place sequence with real (solid) and predicted (dotted) positions of gripper (top) and object (middle) and GateL0RD's latent states (bottom). Latent states are shown relative to initialization, i.e. $\boldsymbol{h}_t - \boldsymbol{h}_0$.

a tendency to encode x- and y-velocity using separate latent dimensions. In contrast, the exemplary latent states of the GRU and LSTM shown in Fig. 6b are not as easily explainable.

For **Robot Remote Control**, GateL0RD ($\lambda = 0.001$) updates only its latent state once it controls the robot (see Fig. 4d and Suppl. D.4). Thus, the latent state clearly encodes control over the robot. For the other RNNs such a clear representation is typically not achieved (see Suppl. D.4).

Finally, we investigate if explainability of the latent states can also be achieved for more complex, high-dimensional POMDPs, using **Fetch Pick&Place**. Sequences of 50 time steps were generated using APEX [40], i.e. a policy guided model-predictive control method, trained to move the object to a randomly selected target position. Figure 15 shows one sequence of positions of gripper (top) and object (middle) and the latent state of GateL0RD for $\lambda = 0.001$ (bottom). Between time step 7-12 the object is grasped and lifted by the gripper. During this grasping event, the latent states smoothly change, hinting at an encoding of 'object transportation' using only one dimension. Note that for this scenario a slightly higher prediction accuracy is achieved for a lower λ, which, however, results in a more convoluted latent state (see Suppl. D.5). Thus, in this scenario, explainability and prediction accuracy are to some degree opposing and λ needs to be chosen based on the application priorities.

7 Discussion

We have introduced a novel RNN architecture (GateL0RD), which implements an inductive bias to develop sparsely changing latent states. The bias is realized by a gating mechanism, which minimizes the L_0 norm of latent updates. In several empirical evaluations, we quantified and analyzed the performance of GateL0RD on various prediction tasks, which naturally contain piecewise constant, unobservable states. The results support our hypothesis that networks with piecewise constant latent states can generalize better to distributional shifts of the inputs, ignore spurious time dependencies, and are able to precisely memorize information. This translates into improved performance in planning and control tasks in POMDPs, as we showed in an off-policy setting, where the generalization to out-of-distribution inputs is particularly important [41]. Moreover, we demonstrated that the latent space becomes interpretable, which is important for explainability reasons.

Our approach introduces an additional hyperparameter, which controls the trade-off between prediction error and latent space constancy. When chosen in favor of explainability, it can reduce the in-distribution performance while improving its generalization abilities. When the underlying system has continuously changing latent states, our regularization is counterproductive. Nevertheless, we find that our unregularized network still performs well in such cases.

Our sparsity-biased gating mechanism segments sequences into chunks of constant latent activation. These segments tend to encode unobservable, behavior-relevant states of the environment, such as if an object is currently 'under control'. Hierarchical planning and control methods require suitable, temporally-extended encodings, such as options [42, 43]. Thus, a promising direction for future work is to exploit the discrete hidden dynamics of GateL0RD for hierarchical, event-predictive planning.

References

[1] Richard S. Sutton and Andrew G. Barto. *Reinforcement learning: An introduction*. MIT press, Cambridge, MA, second edition edition, 2018.

[2] Matthew J. Hausknecht and Peter Stone. Deep recurrent Q-learning for partially observable MDPs. *arXiv preprint arXiv:1507.06527*, 2015. URL http://arxiv.org/abs/1507.06527.

[3] Maximilian Igl, Luisa Zintgraf, Tuan Anh Le, Frank Wood, and Shimon Whiteson. Deep variational reinforcement learning for POMDPs. In *International Conference on Machine Learning*, pages 2117–2126. PMLR, 2018.

[4] Pengfei Zhu, X. Li, and P. Poupart. On improving deep reinforcement learning for pomdps. *arXiv preprint arXiv:1804.06309*, 2017. URL http://arxiv.org/abs/1804.06309.

[5] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

[6] Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014. URL https://arxiv.org/abs/1412.3555.

[7] Dare A. Baldwin and Jessica E. Kosie. How does the mind render streaming experience as events? *Topics in Cognitive Science*, 13(1):79–105, 2021. doi: https://doi.org/10.1111/tops.12502.

[8] Martin V. Butz, Asya Achimova, David Bilkey, and Alistair Knott. Event-predictive cognition: A root for conceptual human thought. *Topics in Cognitive Science*, 13(1):10–24, 2021. doi: https://doi.org/10.1111/tops.12522.

[9] Gina R. Kuperberg. Tea with milk? A hierarchical generative framework of sequential event comprehension. *Topics in Cognitive Science*, 13:256–298, 2021. doi: 10.1111/tops.12518.

[10] Gabriel A. Radvansky and Jeffrey M. Zacks. *Event cognition*. Oxford University Press, 2014.

[11] Jeffrey M. Zacks, Nicole K. Speer, Khena M. Swallow, Todd S. Braver, and Jeremy R. Reynolds. Event perception: a mind-brain perspective. *Psychological bulletin*, 133(2):273–293, 2007. doi: 10.1037/0033-2909.133.2.273.

[12] Martin V. Butz. Towards a unified sub-symbolic computational theory of cognition. *Frontiers in Psychology*, 7(925), 2016. doi: 10.3389/fpsyg.2016.00925.

[13] Anna C. Schapiro, Timothy T. Rogers, Natalia I. Cordova, Nicholas B. Turk-Browne, and Matthew M. Botvinick. Neural representations of events arise from temporal community structure. *Nat Neurosci*, 16(4):486–492, April 2013. ISSN 1097-6256. URL http://dx.doi.org/10.1038/nn.3331.

[14] Yeon Soon Shin and Sarah DuBrow. Structuring memory through inference-based event segmentation. *Topics in Cognitive Science*, 13:106–127, 2021. doi: 10.1111/tops.12505.

[15] Cristina Pinneri, Shambhuraj Sawant, Sebastian Blaes, Jan Achterhold, Joerg Stueckler, Michal Rolınek, and Georg Martius. Sample-efficient cross-entropy method for real-time planning. In *Conference on Robot Learning 2020*, 2020. URL https://corlconf.github.io/paper_217.

[16] Christos Louizos, Max Welling, and Diederik P. Kingma. Learning sparse neural networks through l_0 regularization. In *International Conference on Learning Representations (ICLR)*, 2018. URL https://openreview.net/forum?id=H1Y8hhg0b.

[17] Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. In *International Conference on Learning Representations*, ICLR'17, 2017.

[18] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *International Conference on Learning Representations*, ICLR'17, 2017.

[19] Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

[20] Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

[21] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, ICLR'14, 2014.

[22] Nima Mohajerin and Steven L Waslander. State initialization for recurrent neural network modeling of time-series data. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pages 2330–2337. IEEE, 2017.

[23] Jimmy Ba, Volodymyr Mnih, and Koray Kavukcuoglu. Multiple object recognition with visual attention. In *International Conference on Learning Representations*, ICLR'15, 2015.

[24] David Krueger and Roland Memisevic. Regularizing rnns by stabilizing activations. *arXiv preprint arXiv:1511.08400*, 2015. URL https://arxiv.org/abs/1511.08400.

[25] Jan Koutnik, Klaus Greff, Faustino Gomez, and Juergen Schmidhuber. A clockwork rnn. In Eric P. Xing and Tony Jebara, editors, *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pages 1863–1871, Bejing, China, 22–24 Jun 2014. PMLR. URL http://proceedings.mlr.press/v32/koutnik14.html.

[26] Daniel Neil, Michael Pfeiffer, and Shih-Chii Liu. Phased lstm: Accelerating recurrent network training for long or event-based sequences. In *Advances In Neural Information Processing Systems*, pages 3882–3890, 2016.

[27] Víctor Campos, Brendan Jou, Xavier Giró-i Nieto, Jordi Torres, and Shih-Fu Chang. Skip rnn: Learning to skip state updates in recurrent neural networks. In *International Conference on Learning Representations*, ICLR'18, 2018.

[28] Zhuohan Li, Di He, Fei Tian, Wei Chen, Tao Qin, Liwei Wang, and Tieyan Liu. Towards binary-valued gates for robust LSTM training. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 2995–3004. PMLR, 10–15 Jul 2018.

[29] Thomas Hartvigsen, Cansu Sen, Xiangnan Kong, and Elke Rundensteiner. Learning to selectively update state neurons in recurrent networks. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management*, pages 485–494, 2020.

[30] Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. *arXiv preprint arXiv:1410.5401*, 2014.

[31] Dzmitry Bahdanau, Kyung Hyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In *3rd International Conference on Learning Representations, ICLR 2015*, 2015.

[32] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

[33] Anirudh Goyal, Alex Lamb, Jordan Hoffmann, Shagun Sodhani, Sergey Levine, Yoshua Bengio, and Bernhard Schölkopf. Recurrent independent mechanisms. In *9th International Conference on Learning Representations (ICLR 2021)*, May 2021. URL https://openreview.net/pdf?id=mLcmdlEUxy-.

[34] Emilio Parisotto, Francis Song, Jack Rae, Razvan Pascanu, Caglar Gulcehre, Siddhant Jayakumar, Max Jaderberg, Raphael Lopez Kaufman, Aidan Clark, Seb Noury, et al. Stabilizing transformers for reinforcement learning. In *International Conference on Machine Learning*, pages 7487–7498. PMLR, 2020.

[35] Jeffrey L. Elman. Finding structure in time. *Cognitive Science*, 14(2):179–211, 1990. ISSN 0364-0213. doi: https://doi.org/10.1016/0364-0213(90)90002-E. URL https://www.sciencedirect.com/science/article/pii/036402139090002E.

[36] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, ICLR'14, 2014.

[37] Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI gym. *arXiv preprint arXiv:1606.01540*, 2016.

[38] Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015. URL https://proceedings.neurips.cc/paper/2015/file/e995f98d56967d946471af29d7bf99f1-Paper.pdf.

[39] Anirudh Goyal Lamb, Alex M, Ying Zhang, Saizheng Zhang, Aaron C Courville, and Yoshua Bengio. Professor forcing: A new algorithm for training recurrent networks. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/16026d60ff9b54410b3435b403afd226-Paper.pdf.

[40] Cristina Pinneri, Shambhuraj Sawant, Sebastian Blaes, and Georg Martius. Extracting strong policies for robotics tasks from zero-order trajectory optimizers. In *International Conference on Learning Representations*, ICLR'21, 2021.

[41] Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

[42] Richard S. Sutton, Doina Precup, and Satinder Singh. Between MDPs and semi-MDPs: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1): 181–211, 1999. ISSN 0004-3702. doi: https://doi.org/10.1016/S0004-3702(99)00052-1. URL https://www.sciencedirect.com/science/article/pii/S0004370299000521.

[43] Andrew G Barto and Sridhar Mahadevan. Recent advances in hierarchical reinforcement learning. *Discrete event dynamic systems*, 13(1):41–77, 2003.

[44] Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *Proceedings of the 30th International Conference on International Conference on Machine Learning - Volume 28*, ICML'13, page III–1310–III–1318. JMLR.org, 2013.