# Using Action-Level Metrics to Report the Performance of Multi-Step Keyboards

Category: Research

## ABSTRACT

Computer users commonly use multi-step text entry methods on handheld devices and as alternative input methods for accessibility. These methods require performing multiple actions simultaneously (chorded) or in a specific sequence (constructive) to produce input. However, evaluating these methods is difficult since traditional performance metrics were designed explicitly for non-ambiguous, uni-step methods (e.g., QWERTY). They fail to capture the actual performance of a multi-step method, and do not provide enough detail to aid in design improvements. Here, we present three new action-level performance metrics: UnitER, UA, and UnitCX. They account for the error rate, accuracy, and complexity of multi-step chorded and constructive methods. They describe the multiple inputs that comprise typing a single character: action-level metrics observe actions performed to type one character, while conventional metrics look into the whole character. In a longitudinal study, we used these metrics to identify probable causes of slower text entry and input errors with two existing multi-step methods. Consequently, we suggest design changes to improve learnability and input execution.

**Index Terms:** Human-centered computing—Empirical studies in HCI; Human-centered computing—Usability testing; Human-centered computing—User studies

## 1 INTRODUCTION

Most existing text entry performance metrics were designed to characterize uni-step methods that map one action (a key press or a tap) to one input. However, there are also multi-step constructive and chorded methods. These require the user to perform a predetermined set of actions either in a specific sequence (pressing multiple keys in a particular order) or simultaneously (pressing multiple keys at the same time). Examples of constructive methods include multi-tap [13] and Morse code [16, 33]. Chorded methods include braille [3] and stenotype [18]. Many text entry methods used for accessibility are either chorded or constructive. However, current metrics for analyzing the performance of text entry techniques were designed for uni-step methods, such as the standard desktop keyboard. Due to the fundamental difference in their input process, these metrics often fail to accurately illustrate participants' actions in user studies evaluating the performance of multi-step methods.

Table 1: Conventional ER and action-level UnitER for a constructive method (Morse code).

|  | | | | | | | ER (%) | UnitER (%) |
|---|---|---|---|---|---|---|---|---|
| Presented Text | q | u | i | c | k | **l** | y | | |
|  | --.- | ..- | .. | -.-. | -.- | **.-..** | -.-- | 14.28 | 7.14 |
| Transcribed Text | q | u | i | c | k | **j** | y | | |
|  | --.- | ..- | .. | -.-. | -.- | **.---** | -.-- | | |
| Presented Text | q | u | i | c | k | **l** | y | | |
|  | --.- | ..- | .. | -.-. | -.- | **.-..** | -.-- | 14.28 | 3.57 |
| Transcribed Text | q | u | i | c | k | **p** | y | | |
|  | --.- | ..- | .. | -.-. | -.- | **.--.** | -.-- | | |

To address this, we present a set of revised and novel performance metrics that account for the multi-step nature of chorded and constructive text entry techniques by analyzing the actions required to enter a character rather than the final output. We posit that while conventional metrics are effective in reporting the overall speed and accuracy, a set of action-level metrics can provide extra details about the user's input actions. For designers of multi-step methods, this additional insight is crucial for evaluating the method, identifying its pain points, and facilitating improvements. More specifically, conventional error rates fail to capture learning within chords and sequences. For instance, if entering a letter requires four actions in a specific order, with practice, users may learn some of these actions and the corresponding sub-sequences. Conventional metrics ignore partially correct content by counting each incorrect letter as one error, giving the impression that no learning has occurred. UnitER, in contrast, accounts for this and provides designers with an understanding of (1) whether users learned some actions or not and (2) which actions were difficult to learn, thus can be replaced.

Table 1 illustrates this phenomenon using Morse code for entering *"quickly"*, with one character error (*"l"*) in each attempt. The conventional error rate (ER) is 14.28% for each attempt. One of our proposed action-level metrics, UnitER, gives a deeper insight by accounting for the entered input sequence. It yields an error rate of 7.14% for the first attempt (with two erroneous dashes), and an improved error rate of 3.57% for the second attempt (with only one erroneous dash). The action-level metric shows that learning has occurred with a minor improvement in error rate, but this phenomenon is omitted in the ER metric, which is the same for both attempts.

The remainder of this paper is organized as follows. We start with a discussion on the existing, commonly used text entry performance metrics, then elaborate on our motivations. This is followed with a set of revised and new performance metrics targeted at multi-step input techniques. We proceed to validate the metrics in a longitudinal study evaluating one constructive and one chorded input techniques. The results demonstrate how the new metrics provide a deeper insight into action-level interactions. Researchers identify factors compromising the performance and learning of a multi-step keyboard, and suggest changes to address the issues.

## 2 RELATED WORK

Conventional metrics for text entry speed include characters per second (CPS) and words per minute (WPM). These metrics represent the number of resulting characters entered, divided by the time spent performing input. Text entry researchers usually transform CPS to WPM by multiplying by a fixed constant (60 seconds, divided by a word length of 5 characters for English text entry) rather than recalculating the metrics [6]. A common error metric, keystrokes per character (KSPC), is the ratio of user actions, such as keystrokes, to the number of characters in the final output [21,34]. Although this metric was designed primarily to measure the number of attempts at typing each character accurately [21], many researchers have used it to represent a method's potential entry speed as well [22,36], since techniques that require fewer actions are usually faster. Some researchers have also customized this metric to fit the need of their user studies. The two most common variants of this metric are gesture per character (GPS) [8, 39, 40] and actions per character (APC) [39], which extend keystrokes to include gestures and other actions, respectively. Error rate (ER) and minimum string distance (MSD) are metrics that measure errors based on the number of incorrect characters in the final output [6]. Another metric, erroneous keystrokes

Table 2: Performance metrics used to evaluate chorded and constructive keyboards in recent user studies.

| | Technique | Speed | Accuracy | Low Level | $R^2$ |
|---|---|---|---|---|---|
| Chorded | Twiddler [20] | WPM | ER | *NA* | Yes |
| | BrailleType [27] | WPM | MSDER | *NA* | *NA* |
| | ChordTap [38] | WPM | ER | *NA* | Yes |
| | Chording Glove [30] | WPM | MSD ER | *NA* | *NA* |
| | Two-handed [41] | WPM | ER | *NA* | *NA* |
| Construct. | Mutitap [12] | WPM | ER | *NA* | *NA* |
| | Reduced Qwerty [14] | WPM | *NA* | *NA* | *NA* |
| | JustType [24] | WPM | *NA* | *NA* | *NA* |
| | UOIT [2] | WPM | TER | *NA* | *NA* |

Table 3: Performance metrics used to evaluate *"x"* for chorded (Twiddler) and constructive (Morse) methods.

| Technique | Correct input for '*x*' | Actual input for '*x*' | ER | UnitER |
|---|---|---|---|---|
| Twiddler [20] | M**R**00 | M**0R**0 | 100 | 50 |
| Morse code [33] | -..- | -..**.** | 100 | 25 |

(EKS) [6], considers the number of incorrect actions performed in an input episode. None of these metrics considers error correction efforts, thus Soukoreff and MacKenzie [34] proposed the total error rate (TER) metric that combines two constituent errors metrics: corrected error rate (CER) and not-corrected error rate (NER). The former measures the number of corrected errors in an input episode and the latter measures the number of errors left in the output.

Accessibility text entry systems mainly use constructive or chorded techniques. Morse code is a constructive text entry system that was named one of the "Top 10 Accessibility Technologies" by RESNA [29]. In 2018, this entry system was integrated into Android phones as an accessibility feature for users with motor impairments [37]. Users of Morse code can tap on one or two keys to enter short sequences of keystrokes representing each letter of the alphabet. This method reduces the dexterity required to enter text, compared to the ubiquitous QWERTY keyboard. Braille is a tactile representation of language used by individuals with visual impairments. Braille keyboards [25, 26, 35] contain just six keys so that users do not need to search for buttons; instead, users can keep their hands resting across the keys. To produce each letter using this system, users must press several of these keys simultaneously.

Little work has focused on performance metrics for such multi-step input techniques. Sarcar et al. [31] proposed a convention for calculating the most common performance metrics for constructive techniques, which considers both the input and the output streams. Grossman et al. [15] defined "soft" and "hard" errors for two-level input techniques, where errors at the first level are considered "soft" and errors at the second level are considered "hard". [1] Seim et al. [32] used a dynamic time warping (DTW) algorithm [17] to measure the accuracy of chorded keystrokes on a piano keyboard. Similar to the Levenshtein distance [19], it measures the similarity between two sequences, but accounts for variants in time or speed. Table 2 shows the performance metrics used to evaluate recent chorded and constructive text entry techniques.

## 3 MOTIVATION

### 3.1 Partial Errors and Predictions

Users can make partial errors in the process of performing a chord or a sequence of actions. To enter *"x"*, a Twiddler [20] user could incorrectly perform the chord *"M0R0"* instead of *"MR00"*, and a Morse code user could incorrectly perform the sequence *"-..."* instead of *"-..-"* (Table 3). In both cases, user actions would be partially correct. However, typical error metrics ignore this detail by considering the complete sequence as one incorrect input. Hence, they yield the same value as when users enter no correct information. In reality, users may have learned, and made fewer mistakes within a chord or

a sequence. Not only does this show an incomplete picture of user performance, it also fails to provide the means to fully explore learning of the text entry method. More detailed metrics of multi-step keyboard interaction can facilitate improved input method design through a better understanding of the user experience. These data can also train algorithms to predict and compensate for the most common types of errors.

### 3.2 Correction Effort

Prior research [4] shows that correction effort impacts both performance and user experience, but most current error metrics do not represent the effort required to fix errors with constructive techniques. With uni-step character-based techniques, one error traditionally requires two corrective actions: a backspace to delete the erroneous character, and a keystroke to enter the correct one [7]. Suppose two users want to input *"-..-"* for the letter *"x"*. One user enters *"-..."*, the other enters *"...-"*. Existing error metrics consider both as one erroneous input. However, correcting these may require different numbers of actions. If a technique allowed users to change the direction of a gesture mid-way [5], the errors would require one and five corrective actions, respectively. If the system only allowed the correction of one action at a time, then the former would require two and the latter would require five corrective actions. In contrast, if the system does not allow the correction of individual actions within a sequence, both would require five corrective actions. Hence, error correction relies on the correction mechanism of a technique, the length of a sequence, and the position and type of error (insertion, deletion, or substitution). Existing metrics fail to capture this vital detail in both chorded and constructive text entry techniques.

### 3.3 Deeper Insights into Limitations

The proposed metrics aim to give quantitative insights into the learning and input of multi-step text entry techniques. Insights, such as tapping locations affecting speed, might seem like common sense, but action-level metrics can also provide similar insights for less straight-forward interactions, such as breath puffs, tilts, swipes, etc. Although some findings might seem unsurprising for experts, the proposed metrics will benefit the designers of new techniques aimed at multi-step text entry and would complement their efforts and insights.

The new metrics can facilitate design improvements by quantifying the design choices. Conventional metrics identify difficult and erroneous letters, while our UnitER, UA and UnitCX indicate what is contributing towards it. The action-level metrics can help us to identify difficult-to-enter sequences, so they can be assigned to infrequent characters or avoided altogether. For example, UnitER, UA can show that target users are having difficulty in performing the long-press action of a three-action input sequence for some character. Designers then can replace the long-press action with an easier one for particular group of people (e.g., to physical button press) to reduce error rate for that letter.

## 4 NOTATIONS

In the next section, we propose three new action-level metrics for evaluating multi-step text entry techniques. For this, we use the following notations.

---

[1] With two-level techniques, users usually perform two actions to select the desired character, for example, the first action to specify the region and the second to choose the character.

- Presented text (*PT*) is the text presented to the user for input, $|PT|$ is the length of *PT*, $PT_i$ is the *i*th character in PT, $pt_i$ is the sequence of actions required to enter the *i*th character in *PT*, and $|pt_i|$ is the length of $pt_i$.

- Transcribed text (*TT*) is the text transcribed by the user, $|TT|$ is the length of *TT*, $TT_i$ is the *i*th character in *TT*, $tt_i$ is the sequence of actions performed by the user to enter the *i*th character in *TT*, and $|tt_i|$ is the length of $tt_i$.

- Minimum string distance (MSD) measures the similarity between two sequences using the Levenshtein distance [19]. The "distance" is defined as the minimum number of primitive operations (*insertion, deletion, and substitution*) needed to transform a given sequence (*TT*) to the target sequence (*PT*) [21].

- Input time (*t*) is the time, in seconds, the user took to enter a phrase (*TT*).

- An action is a user action, including a keystroke, gesture, tap, finger position or posture, etc. Action sequence (AS) is the sequence of all actions required to enter the presented text. |AS| is the length of AS. We consider all sub-actions within a chord as individual actions. For example, if a chord requires pressing three keys simultaneously, then it is composed of three actions.

## 5 SPEED METRICS

### 5.1 Input per Second (IPS)

We present IPS, a variant (for convenience of notation) of the commonly used CPS metric [40] to measure the entry speeds of multi-step techniques.

$$\text{IPS} = \frac{|\text{AS}|}{t} \qquad (1)$$

IPS uses the length of the action sequence $|AS|$ instead of the length of transcribed text $|TT|$ to account for all multi-step input actions. It is particularly useful to find out if the total number of actions needed for input is affecting performance or not.

## 6 PROPOSED ACTION-LEVEL METRICS

### 6.1 Unit Error Rate (UnitER)

The first of our novel metrics, unit error rate (UnitER) represents the average number of errors committed by the user when entering one input unit, such as a character or a symbol. This metric is calculated in the following three steps:

#### 6.1.1 *Step 1: Optimal Alignment*

First, obtain an optimal alignment between the presented (*PT*) and transcribed text (*TT*) using a variant of the MSD algorithm [23]. This addresses all instances where lengths of presented ($|PT|$) and transcribed text ($|TT|$) were different.

$$\text{MSD}(a,b) = \begin{cases} |b|, & \text{if } a = \text{""} \\ |a|, & \text{if } b = \text{""} \\ 0, & \text{if } a = b, \\ S \end{cases} \qquad (2)$$

where *S* is defined as

$$S = \min \begin{cases} \text{MSD}(a[1:\,],b[1:\,]) & \text{if } a[0] = b[0], \\ \text{MSD}(a[1:\,],b) + 1, \\ \text{MSD}(a,b[1:\,]) + 1, \\ \text{MSD}(a[1:\,],b[1:\,]) + 1. \end{cases} \qquad (3)$$

If multiple alignments are possible for a given MSD between two strings, select the one with the least number of insertions and deletions. If there are multiple alignments with the same number of insertions and deletions, then select the first such alignment. For example, if the user enters *"qucehkly"* (*TT*) instead of the target word *"quickly"* (*PT*), then $\text{MSD}(PT,TT) = 3$ and the following alignments are possible:

```
quic--kly   quic-kly   qui-ckly   qu-ickly
qu-cehkly   qucehkly   qucehkly   qucehkly
```

Here, a dash in the top sequence represents an *insertion*, a dash in the bottom represents a *deletion*, and different letters in the top and bottom represents a *substitution*. Our algorithm selects the highlighted alignment.

#### 6.1.2 *Step 2: Constructive vs. Chorded*

Because the sequence of performed actions is inconsequential in chorded methods, sort both the required ($pt_i$) and the performed actions ($tt_i$) using any sorting algorithm to obtain consistent MSD scores. Action sequences are not sorted for constructive methods since the order in which they are performed is vital for such methods.

#### 6.1.3 *Step 3: Minimum String Distance*

Finally, apply the MSD algorithm [21] to measure the minimum number of actions needed to correct an incorrect sequence.

$$\text{UnitER} = \frac{\sum_{i=1}^{|\overline{TT}|} \frac{\text{MSD}(\overline{pt_i},\overline{tt_i})}{\max(|\overline{pt_i}|,|\overline{tt_i}|)}}{|\overline{TT}|} \times 100\% \qquad (4)$$

Here, $|\overline{TT}|$ is the length of the aligned transcribe text (same as $|\overline{PT}|$), and $\overline{pt_i}$ and $\overline{tt_i}$ are the sequence of actions (sorted for chorded techniques in *Step 2*) required and performed, respectively, to enter the *i*th character in *TT*.

This step requires certain considerations about the presence of *insertion* and *deletion* in the optimal alignment. If the $i-$th character of the aligned presented text $|\overline{TT}|$ has a deletion, then MSD of the corresponding $i-$th character is 100%. But when $|\overline{PT}|$ has an *insertion*, a misstroke error is assumed, as it is the most common cause of *insertions* [11]. A misstroke errors occur when the user mistakenly strokes (or taps) an incorrect key. However, the question remains: To which character do we attribute the insertion? For this, we propose comparing the MSD-s of current $TT_i$ to the neighboring letters of $PT_i$ (which are different for different layouts), and attributing it to the one with the lowest MSD. If there is a tie, attributed it to the right neighbor $PT_i + 1$. We propose this simplification, since it is difficult to determine the exact cause of an *insertion* in such a scenario.

This metric can be used to measure error rate of a specific character, in which case, Equation 5 considers only the character under investigation, where *c* is the character under investigation and *Total(c)* is the total occurrence of *c* in the transcribed text.

$$\text{UnitER}(c) = \frac{\sum_{i=1}^{|\overline{TT}|} \frac{\text{MSD}(\overline{pt_i},\overline{tt_i})}{\max(|\overline{pt_i}|,|\overline{tt_i}|)} \text{ (if } PT_i = c)}{Total(c)} \qquad (5)$$

### 6.2 Unit Accuracy (UA)

Unit accuracy (UA) is the opposite and simply a convenient reframing of UnitER. Instead of error rate, UA represents the accuracy rate of a unit. Also, unlike UnitER, the values of UA range between 0 and 1 inclusive to reflect the action-level nature of the metric (i.e., 0%–100%). UA can be used for a specific character *c* as well, using Equation 7.

$$\text{UA} = \frac{100 - \text{UnitER}}{100} \qquad (6)$$

$$\text{UA}(c) = \frac{100 - \text{UnitER}(c)}{100} \qquad (7)$$

### 6.3 Unit Complexity (UnitCX)

Apart from speed and accuracy, we also propose the following novel metric to measure an input unit's complexity. For this, each action in a unit (such as a character or a symbol) is categorized into different difficulty levels, represented by the continuous values from 0 to 1.

$$\text{UnitCX} = \frac{\left(\sum_{n=1}^{|tt_i|} \frac{d(a_n)}{|TT|}\right) - d_{\min}}{d_{\max} - d_{\min}} \tag{8}$$

Here, $d(a_n)$ signifies the difficulty level of the $n-$th action in $tt_i$, and $d_{\min}$ and $d_{\max}$ are the minimum and maximum difficulty levels of all actions within or between text entry techniques. This yields a normalized unit complexity value, ranging from 0 to 1. The difficulty level of an action is based on a custom convention, considering the posture and ergonomics, memorability, and the frequency of the letters [10]. However, more sophisticated methods are available in the literature [9,42].

## 7 EXPERIMENT: VALIDATION

We validated the effectiveness of our proposed metrics by applying them to data collected from a longitudinal user study. This study evaluated one constructive and one chorded text entry technique. Although we conducted a comparative study, out intent was to demonstrate how the proposed metrics can provide deeper insights into the techniques' performance and limitations, specifically with respect to learning.

## 8 APPARATUS

We used a Motorola Moto G$^5$ Plus smartphone (150.2 $\times$ 74 $\times$ 7.7 mm, 155 g) at 1080 $\times$ 1920 pixels in the study (Fig. 3). The virtual multi-step keyboards used in the study were developed using the default Android Studio 3.1, SDK 27. The keyboards logged all user actions with timestamps and calculated all performance metrics directly.

## 9 CONSTRUCTIVE METHOD: MORSE CODE

We received the original code from the authors of a Morse code keyboard [16] to investigate the performance of a constructive keyboard. It enables users to enter characters using sequences of dots (.) and dashes (-) [33]. The keyboard has dedicated keys for dot, dash, backspace, and space (Fig. 1). To enter the letter "R", represented by ".-." in Morse code, the user presses the respective keys in that exact sequence, followed by the SEND key, which terminates the input sequence. The user presses the NEXT key to terminate the current phrase and progress to the next one.

Figure 1: The Morse code inspired constructive keyboard used in the experiment.

## 10 CHORDED METHOD: SENORITA

We received the original code from the authors of the chorded keyboard Senorita [28]. It enables users to enter characters using eight keys (Fig. 2). The most frequent eight letters in English appear on the top of the key labels, and are entered with only one tap of their respective key. All other letters require simultaneous taps on two keys (with two thumbs). For example, the user taps on the "E"

and "T" keys together to enter the letter "H". The keyboard provides visual feedback to facilitate learning. Pressing a key with one thumb highlights all available chords corresponding to that key, and right-thumb keys have a lighter shade than left-thumb keys (Fig. 2, right).

Figure 2: The Senorita chorded keyboard used in the experiment. It enables users to enter text by pressing two keys simultaneously using the thumbs. Pressing a key highlights all available chords for the key (right).

## 11 PARTICIPANTS

Ten participants, aged from 18 to 37 years ($M$ = 26.1, $SD$ = 5.6), took part in the experiment. Six identified as male, four as female. None identified as non-binary. Eight were right-handed, one was left-handed, and the other was ambidextrous. They all used both hands to hold the device and their thumbs to type. All participants were proficient in English. Six rated themselves as *Level 5: Functionally Native* and four as *Level 4: Advanced Professional* on the Interagency Language Roundtable (ILR) scale [1]. All participants were experienced smartphone users, with on average 9.3 years' experience ($SD$ = 1.8). None of them had prior experience with any chorded methods, but eight had used a constructive method in the past (either multi-tap or pinyin). None had experience with the keyboards used in the study. They all received US $50 for volunteering.

## 12 DESIGN

We used a within-subjects design, where the independent variables were input method and session. The dependent variables were the IPS, APC, ER, and UnitER metrics. In summary, the design was as follows.

> 10 participants $\times$
> 5 sessions (different days) $\times$
> 2 input methods (constructive vs. chorded, counterbalanced) $\times$
> 10 English pangrams
> = 1,000 phrases, in total.

## 13 PROCEDURE

To study learning of all letters of the English alphabet, we used the following five pangrams during the experiment, all in lowercase.

> quick brown fox jumps over the lazy dog
> the five boxing wizards jump quickly
> fix problem quickly with galvanized jets
> pack my red box with five dozen quality jugs
> two driven jocks help fax my big quiz

Participants were divided into two groups, one started with the constructive method and the other started with the chorded method. This order was switched on each subsequent session. Sessions were scheduled on different days, with at most a two-day gap in between. In each session, participants entered one pangram ten times with one method, and then a different pangram ten times with the other method. Pangrams were never repeated for a method. There was a

Figure 3: Two volunteers entering text using: (left) the Morse code constructive keyboard with the assistance of a cheat-sheet, and (right) the Senorita chorded keyboard.

mandatory 30–60 minutes break between the conditions to mitigate the effect of fatigue. During the first session, we demonstrated both methods to participants and collected their consent forms. We asked them to complete a demographics and mobile usage questionnaire. We allowed them to practice with the methods, where they entered all letters (A–Z) until they felt comfortable with the methods. Participants were provided with a cheat-sheet for Morse code that included all combinations (Fig. 3, left) as Morse code relies on memorization of those. For Senorita we did not provide a cheat-sheet as the keyboard provides visual feedback by displaying the characters (i.e., it has a "built-in cheat sheet"). The experiment started shortly after that, where a custom app presented one pangram at a time, and asked participants to enter it "as fast and accurately as possible". Once done, they pressed the NEXT key to re-enter the phrase. Logging started from the first tap and ended with the last. Error correction was intentionally disabled to exclude correction efforts from the data to observe the UnitER metric. Subsequent sessions used the same procedure, excluding practice and questionnaire.

## 14 RESULTS

A Shapiro-Wilk test and a Mauchly's test revealed that the assumption of normality and sphericity were not violated for the data, respectively. Hence, we used a repeated-measures ANOVA for all analysis.

### 14.1 Input per Second (IPS)

An ANOVA identified a significant effect of session on IPS for both the constructive method ($F_{4,36} = 17.16, p < .0001$) and the chorded method ($F_{4,36} = 28.26, p < .0001$). On average, constructive and chorded yielded 1.29 ($SD = 0.38$) and 1.02 ($SD = 0.29$) IPS, respectively. Fig. 4 top displays IPS for both methods in all sessions. The commonly used WPM metric yielded comparable statistical results for both the constructive method ($F_{4,36} = 17.32, p < .0001$) and the chorded method ($F_{4,36} = 27.69, p < .0001$).

### 14.2 Actions per Character (APC)

An ANOVA identified a significant effect of session on APC for constructive ($F_{4,36} = 2.84, p < .05$) and chorded methods ($F_{4,36} = 6.52, p < .0005$). Average APC for constructive and chorded methods were 2.58 ($SD = 0.13$) and 1.49 ($SD = 0.02$), respectively. Fig. 4 bottom displays APC for both methods in all sessions.

### 14.3 Error Rate (ER)

Error rate (ER) is a commonly used error metric, which is traditionally calculated as the ratio of the total number of incorrect characters in the transcribed text to the length of the transcribed text [6]. An ANOVA identified a significant effect of session on ER for constructive ($F_{4,36} = 2.86, p < .05$), but not for chorded

Figure 4: Average IPS for the two methods in all sessions (top) and average APC for the two methods in all sessions (bottom). Note the scale on the vertical axis.

($F_{4,36} = 1.79, p = .15$). On average, constructive and chorded methods yielded 6.05% ($SD = 10.11$) and 2.46% ($SD = 4.65$) ER, respectively. Fig. 5 top displays ER for both methods in all sessions. Another widely used error metric, TER [34], yielded comparable result for the constructive method ($F_{4,36} = 3.33, p < .05$) and the chorded method ($F_{4,36} = 1.51, p = .22$).

### 14.4 Unit Error Rate (UnitER)

An ANOVA failed to identify a significant effect of session on UnitER for both constructive ($F_{4,36} = 2.14, p = .09$) and chorded ($F_{4,36} = 0.12, p = .97$). On average, UnitER for constructive and chorded methods were 1.32 ($SD = 2.2$) and 0.91 ($SD = 2.1$). Fig. 5 bottom displays UnitER for both methods in all sessions.

## 15 DISCUSSION

There was a significant effect of session on IPS for both methods, which suggests that entry speed improved for both methods with practice. Accordingly, entry speed per session correlated well with the power law of practice [9] for both constructive ($R^2 = 0.98$) and chorded ($R^2 = 0.95$) methods, see Fig. 4 top. As stated earlier, the commonly used WPM [6] metric yielded comparable statistical results. There was a significant effect of session on APC for the two techniques. This may seem odd just by looking at Fig. 4 bottom, where both the lines appear flat. However, a Tukey-Kramer Multiple-Comparison test revealed that sessions 1 and 2 were significantly different for constructive, while sessions 1, 4, and 5 were different for chorded. Similar trends were observed for UnitCX, and the commonly used KSPC metric. We failed to identify any reason for this phenomenon.

Interestingly, there was a significant effect of session on ER for constructive, but not for chorded. Accordingly, ER per session correlated well with the power law of practice [9] for the constructive method ($R^2 = 0.94$), see Fig. 5 top. This and the fact that IPS improved over session for chorded suggest that participants learned to type faster with the method while maintaining a consistent error rate. Additional data is needed to fully investigate it. There was

Figure 5: Average ER for the two methods in all sessions (top) and average UnitER for the two methods in all sessions (bottom). Note the scale on the vertical axis.

no significant effect of session on UnitER for either method. Yet, UnitER per session correlated well with the power law of practice [9] for constructive ($R^2 = 0.94$), see Fig. 5 bottom. Regardless of not reaching statistical significance, this metric provides useful details, as we will demonstrate in the following section, since unlike high-level text entry metrics that only looks at the differences in the output, action-level metrics accounts for similarities in actions.

## 16  ACTION-LEVEL ANALYSIS

The above discussion demonstrates that the proposed metrics (on the whole text) complement the conventional metrics by facilitating a discussion of the methods' speed and accuracy in general. In this section, we demonstrate how the proposed metrics shed further light on these methods' performance and limitations.

To investigate which letters may have hampered text entry speed and accuracy, we first calculated UnitER for each letter. Because the letters do not appear the same number of times, we normalized the values based on each letter's total appearance in the study. We then identified the letters that were both difficult to enter and learn to input accurately (henceforth "Not Learned"), and the letters that were difficult to enter but relatively easier to learn to input accurately (henceforth "Learned"). For this, we compared the average UnitER of each letter from the first three sessions to the last two sessions. The "Learned" included the letters that demonstrated a significant improvement in UnitER from the first to the last sessions. In contrast, the "Not Learned" included the letters that consistently yielded higher UnitER in all sessions.

### 16.1  Constructive Method

Table 4 displays the top four Not Learned and the Learned letters from the Morse code keyboard. For better visualization, we calculated Unit Accuracy (UA) for these letters using simple transformation given by eq. 7 and fitted them to power law of practice [9] to identify any trends, see Fig. 6.

Fig. 6 (top) illustrates the high inconsistency in UA across the Not Learned letters. However, for the Learned group (Fig. 6 bottom),

Table 4: Action-Level representation of the difficult to enter and learn (Not Learned) and difficult to enter but easier to learn letters (Learned) for the constructive method.

| Not Learned | Sequence | Learned | Sequence |
|---|---|---|---|
| z | --.. | g | --. |
| h | .... | p | .--. |
| s | ... | x | -..- |
| c | -.-. | q | --.- |

Figure 6: (top) Average Unit Accuracy (UA) of the letters z, h, s, c per session with power trendlines. Trends for the letters show decreasing UA across sessions, indicating that learning was not occuring, (bottom) average UA of the letters g, p, x, q per session with power trendlines. Trends for these letters show increasing UA as the sessions progressed, indicating learning.

there is a prominent upward trend. Evidently, participants were learning these letters even in the last session, suggesting that performance with these letters would have continued to increase if the study lasted longer. We performed multiple comparisons between the letters to find the cause of entry difficulty, as well as the factors that facilitated learning. We identified the following trends that may have contributed towards the aforementioned trends.

Analysis revealed that participants were having difficulty differentiating between the letters that required similar actions to enter. For instance, it was difficult for them to differentiate between h ("....") and s ("..."), and k ("-.-") and c ("-.-."), presumably because their corresponding actions are very similar. A deeper analysis of the action-level errors revealed that participants frequently entered an extra dot when typing "k", resulting in the letter "c", and vice versa. This error totaled 23% of all UnitER for "c". Participants also made similar mistakes for other Not Learned letters. For example, they entered s ("...") instead of h ("....") and vice versa, resulting in 50% of all UnitER for "h" and 30% of all UnitER for "s". This information is vital. It helps the designer of a constructive method assign sufficiently different actions to frequent letters to avoid confusion,

likely resulting in increased speed and accuracy.

An interesting observation is that participants tend to enter an extra dot or dash when these actions are repeated. For example, participants often entered "---.", "---.-" or similar patterns for z ("-
-.."), resulting in 17% of all UnitER in "z". Likewise, participants entered additional dots when entering g ("--."), such as z ("--.."), which resulted in 20% of all UnitER for "g". Similar errors were committed for other letters as well. These details are useful, since the designer can compensate by reducing the number of repeated actions for frequent letters.

### 16.2 Chorded Method

Table 5 displays the top four Not Learned and the Learned letters for the Senorita keyboard. Like the constructive method, we calculated UA for these letters using Equation 7 and fitted them to power law of practice [9] to identify any trends, see Fig. 8. We observed that, like the constructive method, trends for all Learned letters were increasing, suggesting the occurrence of learning across the techniques. Participants were learning these letters even in the last session. This might indicate that the performance of these letters would have been much better if the study lasted longer. Multiple comparisons between action-level actions per letter identified the following trends that may have contributed towards the aforementioned trends.

Table 5: Action-Level representation of the difficult to enter and learn (Not Learned) and difficult to enter but easier to learn letters (Learned) for the chorded method.

| Not Learned letter | Chord | Learned letter | Chord |
|---|---|---|---|
| q | rs | x | ir |
| p | er | d | eo |
| m | en | f | io |
| z | rt | l | at |

Letters 'q', 'p', and 'z' have the 'r' key in their chord ('r', 'er', and 'rt', respectively), which is the furthest key from the right side. We speculate that it is difficult to learn, and be fast and accfurate if letter has "r" in a chord pair, because "r" and "s" are the furthest letters from the edges (Fig. 7). Keys near the center of the screen are more difficult to reach than those at the edge. Relevantly, four letters with improving trendlines ('x', 'd', 'f', and 'l') have chord pairs that are close to the screen edge. This detail may encourage designers to place the most frequent letters toward the edge of the device.

Figure 7: The user stretching her thumb to reach the letter "s" (left) and the letter "r" (right).

### 16.3 Time Spent per Letter

We compared the above analysis with the time spent to perform the sequences and chords for each letter in the last two sessions. The purpose was to further validate the metrics by studying if the letters that took additional time to enter correspond well to the Not Learned letters. Fig. 9a illustrates all difficult letters (highlighted in red and green) identified for the constructive method. One can see the correlation between UnitER and the time spent to enter the sequence of these letters. This suggests that these letters require higher cognitive and motor effort to enter. Similarly, Fig. 9 (b)

Figure 8: (top) Average Unit Accuracy (UA) of the letters q, p, m, z per session with power trendlines. Trends for the letters show decreasing UA across sessions, indicating that learning was not occurring, (bottom) average UA of the letters x, d, f, l per session with power trendlines. Trends for these letters show increasing UA as the sessions progressed, indicating learning.

illustrates all difficult letters (highlighted in red and green) identified for the chorded method. One can see that the chords (q, v, p, g, z, j) required more time than taps (s, e, n, o, r, i, t, a). However, the chords that are composed of the keys closer to the boundaries were much faster (e.g., h, u, l, etc.). This further strengthens the argument of the previous section.

## 17 CONCLUSION

In this paper, we proposed a trio of action-level performance metrics (UnitER, UA, and UnitCX) aimed at multi-step text entry techniques that account and compensate for the constructive and chorded input process. We validated these metrics in a longitudinal study involving one constructive and one chorded technique. In our presentation, we used existing techniques such as Morse [33] and Senorita [28], not to change their mapping or design, but to amply demonstrate how can the newly proposed metrics be applied for different multi-step techniques and to give a deeper insight into possible limitations of the techniques with an emphasis on learning. None of the metrics would give the conclusions automatically, but they could point towards limitations. Our UnitER helped us to investigate specific erroneous characters, while conventional metrics failed to identify them. The results of this study demonstrate how the proposed metrics provide a deeper understanding of action-level error behaviors, particularly the difficulties in performing and learning the sequences and chords of the letters, facilitating the design of faster and more accurate multi-step keyboards. Although, there is no formal method to analyze action-level actions of multi-step method, it is likely that veteran text entry researchers perform similar analysis on user study data. However, this work provides a formal method, that will enable researchers new to the area to perform these analyses, as well as

Figure 9: (top) Average UnitER of all letters vs. the time spent to perform the sequence for those letters for constructive method, (bottom) average UnitER of all letters vs. the time spent to perform the chords for those letters with the chorded method.

facilitate better comparison between methods from the literature.

## 18 FUTURE WORK

We intend to combine the insights gained from the proposed action-level metrics, particularly the most error-prone characters and the types of errors frequently committed in the sequence or chord of these characters, with machine learning approaches to make multi-step keyboards adapt to human errors. Such a system can also use language models to provide users with more effective auto-correction and word suggestion techniques.

## REFERENCES

[1] Irl, interagency language roundtable language skill level descriptions, 2020.

[2] T. AbuHmed, K. Lee, and D. Nyang. Uoit keyboard: A constructive keyboard for small touchscreen devices. *IEEE Transactions on Human-Machine Systems*, 45(6):782–789, Dec 2015. doi: 10.1109/THMS. 2015.2449309

[3] AmericanFoundationfortheBlind. What is braille, 2020.

[4] A. S. Arif, S. Kim, W. Stuerzlinger, G. Lee, and A. Mazalek. Evaluation of a smart-restorable backspace technique to facilitate text entry error correction. In *Proceedings of the 2016 CHI Conference on Human Factors in Computing Systems*, CHI '16, p. 5151–5162. Association for Computing Machinery, New York, NY, USA, 2016. doi: 10.1145/ 2858036.2858407

[5] A. S. Arif, M. Pahud, K. Hinckley, and B. Buxton. Experimental study of stroke shortcuts for a touchscreen keyboard with gesture-redundant keys removed. In *GI '14 Proceedings of Graphics Interface 2014*, pp. 43–50. Canadian Information Processing Society, May 2014. Michael A. J. Sweeney Award for Best Student Paper.

[6] A. S. Arif and W. Stuerzlinger. Analysis of text entry performance metrics. In *2009 IEEE Toronto International Conference Science and Technology for Humanity (TIC-STH)*, pp. 100–105, Sep. 2009. doi: 10. 1109/TIC-STH.2009.5444533

[7] A. S. Arif and W. Stuerzlinger. Predicting the cost of error correction in character-based text entry technologies. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '10, p. 5–14. Association for Computing Machinery, New York, NY, USA, 2010. doi: 10.1145/1753326.1753329

[8] A. S. Arif and W. Stuerzlinger. User adaptation to a faulty unistroke-based text entry technique by switching to an alternative gesture set. In *Proceedings of Graphics Interface 2014*, pp. 183–192. 2014.

[9] X. Bi, B. A. Smith, and S. Zhai. Multilingual touchscreen keyboard design and optimization. *Human–Computer Interaction*, 27(4):352–382, 2012. doi: 10.1080/07370024.2012.678241

[10] T. M. E. Club. Digraph frequency (based on a sample of 40,000 words), 2020.

[11] D. R. Gentner, J. T. Grudin, S. Larochelle, D. A. Norman, and D. E. Rumelhart. *A Glossary of Terms Including a Classification of Typing Errors*, pp. 39–43. Springer New York, New York, NY, 1983. doi: 10. 1007/978-1-4612-5470-6_2

[12] J. Gong, B. Haggerty, and P. Tarasewich. An enhanced multitap text entry method with predictive next-letter highlighting. In *CHI '05 Extended Abstracts on Human Factors in Computing Systems*, CHI EA '05, p. 1399–1402. Association for Computing Machinery, New York, NY, USA, 2005. doi: 10.1145/1056808.1056926

[13] J. Gong and P. Tarasewich. Alphabetically constrained keypad designs for text entry on mobile devices. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '05, p. 211–220. Association for Computing Machinery, New York, NY, USA, 2005. doi: 10.1145/1054972.1055002

[14] N. Green, J. Kruger, C. Faldu, and R. St. Amant. A reduced qwerty keyboard for mobile text entry. In *CHI '04 Extended Abstracts on Human Factors in Computing Systems*, CHI EA '04, p. 1429–1432. Association for Computing Machinery, New York, NY, USA, 2004. doi: 10.1145/985921.986082

[15] T. Grossman, X. A. Chen, and G. Fitzmaurice. Typing on glasses: Adapting text entry to smart eyewear. In *Proceedings of the 17th International Conference on Human-Computer Interaction with Mobile Devices and Services*, MobileHCI '15, p. 144–152. Association for Computing Machinery, New York, NY, USA, 2015. doi: 10.1145/ 2785830.2785867

[16] A.-M. Gueorguieva, G. Rakhmetulla, and A. S. Arif. Enabling Input on Tiny/Headless Systems Using Morse Code. Technical report, Dec. 2020. arXiv: 2012.06708.

[17] K. Huang, T. Starner, E. Do, G. Weinberg, D. Kohlsdorf, C. Ahlrichs, and R. Leibrandt. Mobile music touch: Mobile tactile stimulation for passive learning. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '10, p. 791–800. Association for Computing Machinery, New York, NY, USA, 2010. doi: 10.1145/ 1753326.1753443

[18] X. Lee. Stenotype machine, 2019.

[19] V. I. Levenshtein. Binary codes capable of correcting deletions, insertions, and reversals. In *Soviet physics doklady*, vol. 10, pp. 707–710, 1966.

[20] K. Lyons, T. Starner, D. Plaisted, J. Fusia, A. Lyons, A. Drew, and E. W. Looney. Twiddler typing: One-handed chording text entry for mobile phones. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '04, p. 671–678. Association for Computing Machinery, New York, NY, USA, 2004. doi: 10.1145/ 985692.985777

[21] I. S. MacKenzie. Kspc (keystrokes per character) as a characteristic of text entry techniques. In F. Paternò, ed., *Human Computer Interaction with Mobile Devices*, pp. 195–210. Springer Berlin Heidelberg, Berlin, Heidelberg, 2002.

[22] I. S. MacKenzie, H. Kober, D. Smith, T. Jones, and E. Skepner. Letter-wise: Prefix-based disambiguation for mobile text input. In *Proceedings of the 14th Annual ACM Symposium on User Interface Software and Technology*, UIST '01, p. 111–120. Association for Computing Machinery, New York, NY, USA, 2001. doi: 10.1145/502348.502365

[23] I. S. MacKenzie and R. W. Soukoreff. A character-level error analysis technique for evaluating text entry methods. In *Proceedings of the Second Nordic Conference on Human-Computer Interaction*, NordiCHI

'02, p. 243–246. Association for Computing Machinery, New York, NY, USA, 2002. doi: 10.1145/572020.572056

[24] I. S. Mackenzie, S. X. Zhang, and R. W. Soukoreff. Text entry using soft keyboards. *Behaviour & Information Technology*, 18(4):235–244, 1999. doi: 10.1080/014492999118995

[25] S. Mascetti, C. Bernareggi, and M. Belotti. Typeinbraille: A braille-based typing application for touchscreen devices. In *The Proceedings of the 13th International ACM SIGACCESS Conference on Computers and Accessibility*, ASSETS '11, p. 295–296. Association for Computing Machinery, New York, NY, USA, 2011. doi: 10.1145/2049536. 2049614

[26] J. Oliveira, T. Guerreiro, H. Nicolau, J. Jorge, and D. Gonçalves. Brailletype: Unleashing braille over touch screen mobile phones. In P. Campos, N. Graham, J. Jorge, N. Nunes, P. Palanque, and M. Winckler, eds., *Human-Computer Interaction – INTERACT 2011*, pp. 100–107. Springer Berlin Heidelberg, Berlin, Heidelberg, 2011.

[27] J. Oliveira, T. Guerreiro, H. Nicolau, J. Jorge, and D. Gonçalves. Brailletype: Unleashing braille over touch screen mobile phones. In P. Campos, N. Graham, J. Jorge, N. Nunes, P. Palanque, and M. Winckler, eds., *Human-Computer Interaction – INTERACT 2011*, pp. 100–107. Springer Berlin Heidelberg, Berlin, Heidelberg, 2011.

[28] G. Rakhmetulla and A. S. Arif. Senorita: A chorded keyboard for sighted, low vision, and blind mobile users. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems*, CHI '20, p. 1–13. Association for Computing Machinery, New York, NY, USA, 2020. doi: 10.1145/3313831.3376576

[29] RESNA. Resna, 2020.

[30] R. Rosenberg and M. Slater. The chording glove: a glove-based text input device. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 29(2):186–191, May 1999. doi: 10. 1109/5326.760563

[31] S. Sarcar, A. S. Arif, and A. Mazalek. Metrics for bengali text entry research. *arXiv preprint arXiv:1706.08205*, 2017.

[32] C. Seim, T. Estes, and T. Starner. Towards passive haptic learning of piano songs. In *2015 IEEE World Haptics Conference (WHC)*, pp. 445–450, June 2015. doi: 10.1109/WHC.2015.7177752

[33] R. T. Snodgrass and V. F. Camp. *Radio Receiving for Beginners*. New York: MacMillan, 1922.

[34] R. W. Soukoreff and I. S. MacKenzie. Metrics for text entry research: An evaluation of msd and kspc, and a new unified error metric. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '03, p. 113–120. Association for Computing Machinery, New York, NY, USA, 2003. doi: 10.1145/642611.642632

[35] C. Southern, J. Clawson, B. Frey, G. Abowd, and M. Romero. An evaluation of brailletouch: Mobile touchscreen text entry for the visually impaired. In *Proceedings of the 14th International Conference on Human-Computer Interaction with Mobile Devices and Services*, MobileHCI '12, p. 317–326. Association for Computing Machinery, New York, NY, USA, 2012. doi: 10.1145/2371574.2371623

[36] K. Tanaka-Ishii, Y. Inutsuka, and M. Takeichi. Entering text with a four-button device. In *Proceedings of the 19th International Conference on Computational Linguistics - Volume 1*, COLING '02, p. 1–7. Association for Computational Linguistics, USA, 2002. doi: 10. 3115/1072228.1072377

[37] C. Welch. Google's gboard keyboard now lets you communicate through morse code on both android and ios, 2018.

[38] D. Wigdor and R. Balakrishnan. A comparison of consecutive and concurrent input text entry techniques for mobile phones. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '04, p. 81–88. Association for Computing Machinery, New York, NY, USA, 2004. doi: 10.1145/985692.985703

[39] J. O. Wobbrock. Measures of text entry performance. *Text entry systems: Mobility, accessibility, universality*, pp. 47–74, 2007.

[40] J. O. Wobbrock, B. A. Myers, and J. A. Kembel. Edgewrite: A stylus-based text entry method designed for high accuracy and stability of motion. In *Proceedings of the 16th Annual ACM Symposium on User Interface Software and Technology*, UIST '03, p. 61–70. Association for Computing Machinery, New York, NY, USA, 2003. doi: 10.1145/ 964696.964703

[41] K. Yatani and K. N. Truong. An evaluation of stylus-based text entry methods on handheld devices studied in different user mobility states. *Pervasive and Mobile Computing*, 5(5):496 – 508, 2009. doi: 10.1016/j .pmcj.2009.04.002

[42] X. Yi, C. Yu, W. Shi, X. Bi, and Y. Shi. Word clarity as a metric in sampling keyboard test sets. In *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems*, CHI '17, p. 4216–4228. Association for Computing Machinery, New York, NY, USA, 2017. doi: 10.1145/3025453.3025701