You are caught stealing my winning lottery ticket! Making a lottery ticket claim its ownership

Abstract

Despite tremendous success in many application scenarios, the training and inference costs of using deep learning are also rapidly increasing over time. The lottery ticket hypothesis emerges as a promising framework to leverage a special sparse subnetwork (i.e., *winning ticket*) instead of a full model for both training and inference, that can lower both costs without scarifying the performance. The main resource bottleneck of LTH is however the extraordinary cost to find the sparse mask of the winning ticket. That makes the found winning ticket become a valuable asset to the owners, highlighting the necessity of protecting its copyright. Our setting adds a new dimension to the recently soaring interest in protecting against the intellectual property (IP) infringement of deep models and verifying their ownerships, since they take owners' resources to develop or train. While existing methods explored encrypted weights or predictions, we investigate a unique way to leverage sparse topological information to perform *lottery verification*, by developing several graph-based signatures that can be embedded as credentials. By further combining trigger set-based methods, our proposal can work in both white-box and black-box verification scenarios. Through extensive experiments, we verify the effectiveness of lottery verification in diverse models (ResNet-20s, ResNet-18, ResNet-50) on CIFAR-10 and CIFAR-100. Specifically, our verification is shown to be robust to removal attacks such as model fine-tuning and pruning, as well as several ambiguity attacks. All codes are included in our supplement.

1 Introduction

Deep neural networks (DNNs) have dramatically raised the state-of-the-art performance in various fields. However, the over-parameterization of DNNs becomes a non-negligible problem. The number of parameters now is often on a billion scale, which significantly increases the inference cost when using these models. A promising field that emerged recently explores a new scheme for pruning the model without sacrificing performance. The core idea is to identify the sparsity pattern ahead of training (or in its early stage) and train a sparse network from scratch. It has been hypothesized [1] that DNNs contain sparse networks named *winning tickets* that can be trained to match the test accuracy of the full model. These winning tickets have even better inference performance while potentially reduce the computational footprints, making them a promising solution for efficient machine learning.

However, finding winning tickets is a non-trivial task: it needs a training-prune-retraining cycle for several times [1], which is burdensome and computation-consuming. Although other works [2, 3, 4] have shown that sparsity might emerge at the initialization or at the early stage of training, the iterative magnitude pruning (IMP) still outperforms these alternatives by clear margins [5]. Yet the powerful IMP method requires multiple rounds of train-prune-train process on the original training set, which is even much more expensive than training a dense network. That makes a winning ticket found a valuable asset to the owners, highlighting the necessity of protecting the winning tickets' copyright.

Advanced works [6, 7, 8, 9] have shown that deep networks are vulnerable to intellectual property infringement. For example, one can use transfer learning to adapt a trained model onto a new task, or use model compression techniques to create a new sparse model based on the target model. Fortunately, in recent years the ownership verification problem has been frequently addressed and many methods have been proposed. The key idea is to embed verifiable information, or called signatures, into models' weights [6, 10, 11] or predictions [7] without visibly affecting the original performance. By extracting the embedded information from models, one can verify the ownership of models and hence protect the intellectual

Original Mask   **Mask w. Signature**

Figure 1: Example of embedding signatures into the original sparse structural mask. These visualizations are projected from 4D tensors. Dark entries are the pruned elements. Note that the sparsity of subnetworks is unchanged after encoding credentials.

properties. For the methods that embed information in weights, additional weights regularizers are often used to push the weights following certain patterns, such as signs presenting 0-1 bits. As for the prediction methods, a special training set, which is often called *trigger* set, is used as additional training data. The model trained upon the original data and the trigger set can generate desired prediction labels for the given trigger set while preserving the performance on the original training set. However, those general methods did not take the model's possible properties into account, leaving considerable room for improving their gains in sparse network cases.

On protecting the IP of winning tickets, we investigate a novel way to leverage **sparse structural information** for ownership verification (Fig. 1). This structural information embedded in winning tickets is a good "credential" for ownership verification since the winning ticket at extreme sparsity is naturally robust to fine-tuning and pruning attacks. The winning ticket at extreme sparsity cannot be pruned further otherwise the inference performance will drop (hence losing its "value"). Meanwhile, fine-tuning the winning tickets can only tune the weights, but the sparsity pattern will not be changed. However, there remain some key questions to answer: *How to formulate the ownership verification process under the context of lottery ticket hypothesis? What kind of structural information should be used? How to inject user-specific information into the structure of winning tickets?* We present answers to these questions in this paper. We summarize our findings as follows:

- We formulate the lottery verification problem and define two different protection scenarios. We show that even without specific protection, the extremely sparse winning ticket can partly claim its ownership because of the critical role of its sparse structure in the final inference performance.

- We further propose a new mask embedding method that is capable of embedding ownership "signatures" in the subnetwork's sparse structural connectivity (Fig. 1), without much affecting its performance. The signature is robust, e.g., it can be extracted and decoded even after pruning or fine-tuning attacks. Combined further with the trigger set-based method, our mask embedding method can work under both white-box and black-box verification frameworks.

- We investigate several different verification schemes, *i.e.,* separate masks, embedding signatures, embedding signatures with trigger set, for protecting the IP of extreme winning tickets. We show that these schemes are robust to the common removal and ambiguity attacks, as well as a new type of "add-on" attacks. The extensive experiment results comprehensively the competence on protecting the winning tickets. For example, on ResNet-20s our verification framework can resist fine-tuning attack intrinsically, pruning attack under all level of pruning ratios, as well as add-on attack under all level of attack ratios.

2   Related Work

Pruning and Lottery Ticket Hypothesis.   Pruning algorithms can be roughly classified into two types: pruning *after* training and pruning *before* training. Conventional pruning after algorithms assign scores to individual weights and remove weights with the lowest scores [12]. There are a great number of scoring algorithms of this kind, including weights magnitude [13, 14], Taylor coefficients [15, 16, 17, 18], and some variants [19, 20]. Pruning before training methods also play important roles in the community. For example, Iterative Magnitude Pruning [1] which prunes weights with lowest magnitude is widely used in recent literature, which however requires multiple cycles of training and pruning process [12], making it sometimes tedious in practical use. Pruning-at-initialization methods alleviate such cost by prune initial weights such as observing initial gradients of weights [2, 3], but the quality of sparse networks found by these methods are mediocre in return.

A rising field of sparse networks is the lottery ticket hypothesis [1], which hypothesizes the existence of a sparse network in dense networks that can be trained to match the test accuracy of dense networks in isolation. It was later verified that the original hypothesis was too strong, and early rewind techniques [21] help scale up the original version. Later on, the lottery ticket hypothesis and its variants have been explored and extended to various fields such as image generation [22, 23], natural language processing [24, 25], and reinforcement learning [26]. However, it is currently non-trivial to find winning tickets, especially at high sparsity since multiple train-prune-train processes are required, which emphasize the practical value of protecting the found sparse networks.

Ownership Verification. Ownership verification has drawn attention from both the industry and academia because of the obvious importance of IPs. Many works have been proposed to address IP protection. One most popular way is to use watermarking algorithm: [6] proposed to embed watermarks in the form of bits into deep networks' weights by an additional regularization term. [10] embedded information into model weights by regularizing on the signs of weights. Besides watermarking on weights, [7, 27] proposed to embed watermarks in the labels of certain examples in a *trigger set*, which makes it possible to extract watermarks through a service interface without directly accessing the models' weights (black-box setting). Following somehow different pathways, [28] proposed a passport-based approach that encodes signatures with special passport layers. [11] proposed passport-embedded normalization whose parameters are associated with signatures. However, none of these methods leverages structural information for ownership verification besides assuming general dense networks. For sparse networks, the sparse mask patterns represent the key information and vary across models and tasks.

3 The Lottery Ticket Claims its Ownership

3.1 The Lottery Ticket Hypothesis

❶ **Sparse Masks, Subnetworks and Winning Tickets.** We define a neural network parameterized by $\mathbf{W}$ as $\mathbb{N}[\mathbf{W}](\cdot)$. With a slight abuse of notion, we define a subnetwork of $\mathbb{N}[\mathbf{W}]$ as $\mathbb{N}[\mathbf{W}, \mathbf{M}] := \mathbb{N}[\mathbf{W} \odot \mathbf{M}](\cdot)$ where $\mathbf{M}$ is a sparse mask whose shape is the same as $\mathbf{W}$ but the value of each entry in which can only be either 0 or 1. Given $\mathbf{W}_0$ the initialization of $\mathbb{N}$, if $\mathbb{N}[\mathbf{W}_0, \mathbf{M}]$ can be **re-trained** to *match* the test performance of the dense model training from $\mathbb{N}[\mathbf{W}_0]$, we call $\mathbb{N}[\mathbf{W}_0, \mathbf{M}]$ a **winning ticket**. The term re-train above is used to distinguish between the training process to find the winning ticket. The criterion for matching can be set as, e.g., no lower than 1% than dense models' performance. ❷ **Sparsity Comparison.** The sparsity of a sparse mask $\mathbf{M}$ can be defined as $\mathrm{spar}(\mathbf{M}) := \|\mathbf{M}\|_0 / \|\mathbf{M} + 1\|_0$ where $\|\cdot\|_0$ represents the non-zero values of the input matrix, and the relative sparsity can be defined as $\mathrm{rspar}(\mathbf{M}_1, \mathbf{M}_2) := \mathrm{spar}(\mathbf{M}_1) / (\mathrm{spar}(\mathbf{M}_2) + \epsilon)$. We call a sparse mask $\mathbf{M}_1$ is *sparser* than $\mathbf{M}$ if and only if $\|\mathbf{M}_1\|_0 < \|\mathbf{M}\|_0$. A *sub-mask* $\mathbf{M}_2$ is a mask that has the same shape as $\mathbf{M}$ satisfying that all the elements in $\mathbf{M} - \mathbf{M}_2$ are non-negative. ❸ **Extremely Sparse Condition.** Given a sparsity difference threshold t, we call $\mathbb{N}[\mathbf{W}_0, \mathbf{M}_e]$ an **extremely sparse winning ticket** if $\mathbb{N}[\mathbf{W}_0, \mathbf{M}_e]$ can match the performance of $\mathbb{N}[\mathbf{W}_0]$, but pruning the model (*i.e.*, increase the sparsity of $\mathbf{M}_e$) $t \times 100\%$ further cannot produce a winning ticket. In our experiments, we set t to be 0.01.

3.2 Verification Framework for Extremely Sparse Winning Tickets

A ownership verification framework for extremely sparse winning tickets can be formulated as a tuple $\mathcal{V} = (ME, WE, F, V, I)$, each item of which is a process:

- A *mask embedding* process $ME(\mathbf{M}_0, \mathbf{s})$ (optionally) for sparse masks. $\mathbf{s}$ is an optional string that can be encoded into masks. The output of this process is a new mask $\mathbf{M}$. $\mathbf{M}$ can either be a mask with $\mathbf{s}$ embedded, or contains other structural information that are useful for ownership verification. We call the verification method with $ME(\mathbf{M}_0, \mathbf{s})$ enabled a "mask-based" method.

- A *weight embedding* process $WE(\mathbf{D}_{\mathrm{tr}}, \mathbf{T}, \mathbf{s}, \mathbb{N}[\cdot], L, \mathbf{W}_0, \mathbf{M})$, which is a learning process for the lottery ticket model. $\mathbf{D}_{\mathrm{tr}} = \{\mathbf{x}, y\}$ is the training dataset, $\mathbf{T} = \{\mathbf{T}_x, \mathbf{T}_y\}$ is an optional trigger set provided to the training process, $\mathbf{s}$ is an optional signature for the weights embedding process. L is the loss function for model training (usually the cross-entropy loss), $N[\cdot]$ defines the model structure, $\mathbf{W}_0$ is the initialization of weights and $\mathbf{M}$ is the sparse mask for model. The output of E is a model $\mathbb{N}$ with sparse weights $\mathbf{W} \odot \mathbf{M}$ where $\mathbf{W}$ represents the trained weights. The trigger set $\mathbf{T}$ (or/and) the signature $\mathbf{s}$ are embedded in $\mathbf{W} \odot \mathbf{M}$ after this process, and can be verified with the verification process introduced next.

- A *fidelity evaluation* process $F(\mathbb{N}[\cdot], \mathbf{W}, \mathbf{M}, \mathbf{D}_{te}, \mathcal{A}_f, \epsilon_f)$ is to evaluate whether the performance discrepancy of model $\mathbb{N}[\cdot]$ is less than a pre-defined threshold ϵ_f, *i.e.*, $|\mathcal{A}(\mathbb{N}[\mathbf{W}, \mathbf{M}], \mathbf{D}_{tr}) - \mathcal{A}_f| < \epsilon_f$, in which $\mathcal{A}(\cdot, \cdot)$ is the inference performance on the test dataset $\mathbf{D}_{te}$, and $\mathcal{A}_f$ is a target inference performance associated with the model.

- A *verification* process $V(\mathbb{N}[\cdot], \mathbf{W}, \mathbf{M}, \mathbf{T}, \mathbf{s}, \epsilon_s)$ checks whether the sparse mask $\mathbf{M}$ or the trigger set $\mathbf{T}$ can be successfully verified for a given model $\mathbb{N}[\cdot]$. For the mask-based methods, the process is to check if $\mathbf{M}$ and $\mathbf{s}$ matches by evaluating $N[\cdot, \mathbf{M}]$ on $\mathbf{D}_{te}$ to see if the performance gap is smaller than a pre-defined threshold ϵ_s, and(or) extract information in $\mathbf{M}$ and compare it with $\mathbf{s}$. For the trigger set-based methods, an inference is first executed on the trigger set images $\mathbf{T}_x$, and then the prediction will be compared with trigger set labels $\mathbf{T}_y$ to see if the false detection rate is lesser than a threshold ϵ_s [28].

- An *invert* process $I(N[\mathbf{W}, \mathbf{M}], \mathbf{T}, \mathbf{s})$ exists and will enable a successful ambiguity attack [28] if: a) a set of new trigger set $\mathbf{T}'$, a new signature $\mathbf{s}'$, or a new mask $\mathbf{M}'$ can be reverse-engineered for the given mask $\mathbf{M}$ and weights $\mathbf{W}$. b) the forged $\mathbf{T}', \mathbf{s}', \mathbf{M}'$ can be verified with respect to $\mathbf{M}$ and $\mathbf{W}$. c) the fidelity evaluation outcome $F(\mathbb{N}[\cdot], \mathbf{W}, \mathbf{M}', \mathbf{D}_{te}, \mathcal{A}_t, \epsilon_f)$ remains True.

The high-level definitions above are general and can work with any concrete implementations. We will introduce several methods that use sparse structural information in the next following sections.

3.3 Structural Information As Signatures

Our motivation is originated from the nature of winning tickets that the sparse structure of winning tickets is critical to their performance. Since the sparse masks found by the iterative pruning method outperform other pruning methods by clear margins [5], incorrect masks will lead to degraded test accuracy. In the next few sections we demonstrate how to use the sparse structure of extreme winning tickets, *i.e.*, both the sparse masks and weights, to perform ownership verification under different verification schemes. The ownership verification can be performed in two different scenarios: (a) protecting the sparse masks of the extremely sparse winning tickets; and (b) protecting the trained extremely sparse winning tickets.

3.3.1 Protecting the Sparse Masks: Splitting Signature from Sparse Model

Such sparse masks play a crucial role in achieved outstanding generalization [1] and transferability [25, 29], and thus draws our attention to prevent them from being illegal distributed or used. Given a fixed initialization, correct masks are essential for training the extremely sparse winning tickets to match the performance of the dense network. If we split the sparse masks into two parts, neither part is intact and correct so neither can be trained to match the performance of the dense model with the given initialization. Recall the mechanism of one lock can be unlocked by one key generally, we adopt the concept of keys and locks and propose a new ownership verification method for the masks of extremely sparse winning tickets.

Denote the sparse mask of extremely sparse winning ticket by $\{\mathbf{M}_l\}_{l=1}^N$ and the weights by $\{\mathbf{W}_l\}_{l=1}^N$, where N is the number of layers. To sparsify a model, $\{\mathbf{M}_l\}_{l=1}^N$ is applied to the model's weight $\{\mathbf{W}_l\}_{l=1}^N$ by conducting an element-wise product ($\{\mathbf{W}_l \odot \mathbf{M}_l\}_{l=1}^N$). Our goal is to find *key masks i.e.*, sub-masks $\{\mathbf{M}_l^s\}_{l=1}^N$ that contain as few "1"s as possible while the performance of the sparse network with the *locked masks*, *i.e.*, the remaining masks, degrade as much as possible. Fewer "1" in key masks reduce the cost of storing, distributing, and using the key masks, and the performance degradation will accentuate the need for correct key masks.

We next describe the algorithms needed to discover key masks. An algorithm is used to split the masks of extremely sparse winning tickets ($\{\mathbf{M}_l\}_{l=1}^N$) into key masks $\{\mathbf{M}_l^s\}_{l=1}^N$ and locked masks under the constraint of $\mathrm{rspar}(\{\mathbf{M}_l^s\}_{l=1}^N, \{\mathbf{M}_l\}_{l=1}^N) < n_s$. n_s is a hyper-parameter controlling the relative sparsity of the key masks. Score functions aree used to decide which part should be split into the key masks. The pipeline is described in Algorithm 1.

We study several score functions in our experiments: 1. One-Shot Magnitude (OMP): the absolute values of each weight; 2) Edge-Weight-Product (EWP) [30] which measures the importance of paths from models' input to output. The EWP score is defined as the multiplication of weights along the paths; 3) Edge betweenness centrality (Betweenness). The edge betweenness centrality measures the importance of each edge inside a graph. For convolutional layers, we define the weight of each "edge" to be the summation of absolute values of each element; and 4) random scoring.

Algorithm 1: Splitting Key Masks

input : A sets of masks $\mathbf{M} = \{\mathbf{M}_l\}_{l=1}^{N}$, initialization weights $\mathbf{W} = \{\mathbf{W}_l\}_{l=1}^{N}$, number of non-zero elements n, and a function $\texttt{score}(\cdot)$ for scoring.

output : Key masks $\{\mathbf{M}_l^s\}_{l=1}^{N}$ and locked masks $\{\mathbf{M}_l - \mathbf{M}_l^s\}_{l=1}^{N}$

1 Derive the score matrices by applying $\text{score}(\cdot)$ over $\{\mathbf{W}_l \odot \mathbf{M}_l\}_{l=1}^{N}$ and get $\{\mathbf{S}_l\}_{l=1}^{N}$

2 Set the values of entries in $\{\mathbf{S}_l\}_{l=1}^{N}$ to negative infinity if the corresponding entries at the same position in $\{\mathbf{W}_l \odot \mathbf{M}_l\}_{l=1}^{N}$ is zero (*i.e.*, already pruned).

3 Calculate the n^{th} largest number across the score matrix $\{\mathbf{S}_l\}_{l=1}^{N}$ and record it as T.

4 Set $\mathbf{M}_l^s \leftarrow I_{\mathbf{M}_l > T}$ and let the key masks be $\{\mathbf{M}_l^s\}_{l=1}^{N}$. The comparison between $\mathbf{M}_l$ and T ($\mathbf{M}_l > T$) is performed element-wise.

3.3.2 Protecting the Trained Tickets: Embedding Signature into Sparsity Masks

Another scenario is to protect the trained extremely sparse winning ticket since a superior performance on certain large-scale datasets usually comes with huge economic and ecological cost. Although directly splitting the masks provides a solution to the ownership verification problem, it has some drawbacks. It delivers extra cost to users since they need to recover the masks. Such a method is also intrusive and requires additional responsibility from the users' side for storing the key masks safely. To render the extreme winning tickets capable of self-verification and free of key masks , we propose a novel pruning method that is able to "absorb" secret information (*e.g.*, signatures) into models' sparse masks. The core concept is to enforce the sparsity masks to follow certain "0-1" patterns, which can be extracted from masks and further decoded back to the original form of information.

A function $\texttt{encode}(\cdot)$ is used to transform a string $\mathbf{s}$ into a matrix $\mathbf{M}_s \in \{0, 1\}^{d_1 \times d_2}$ which we call *signature mask*. Our goal is to embed $\texttt{encode}(\mathbf{s})$ into the sparsity masks $\{\mathbf{M}_l\}_{l=1}^{N}$. One critical question is where to embed the signature mask $\mathbf{M}_s$. Empirically, low-level convolutional layers are less sparser, which means they are more unlikely to be pruned. Therefore, information embedded in the low-level convolutional layers is more difficult to be removed if using the pruning method. Based on such observation, we decide to embed $\mathbf{M}_s$ in low-level convolutional layers. To minimize mask changes, we first find a region in $\{\mathbf{M}_l\}$ with the highest similarity with $\mathbf{M}_s$ and tune the sub-mask of that region. For masks that have a dimension of two, we directly replace the region with $\mathbf{M}_s$; for masks that have a dimension of more than two, we raise their dimension by using random connections. Our detailed workflow is shown in Algorithm 2.

The choices of function $\texttt{encode}(\cdot)$ are various but there is one common choice in our daily life: QR code [31]. QR code has multiple advantages: 1) QR code is naturally seen as a pattern with only zeros and ones; 2) QR code has the ability to correct the error if the code is dirty or damaged. For example, the H correction level can tolerate up to 30% of error [31]; 3) QR codes can be small in size which can be easily fit into sparse masks. The size of the QR code generated can be as small as 21×21 while the numbers of channels in convolutional kernels in deep learning models are typically greater than 21, showing an abundant space for fitting the QR code in inside models' sparsity masks; and 4) The QR code **without** the finder, alignment and version patterns is imperceptible when fitted into sparse masks since there are no "regular" patterns left. Based on these merits, we choose $\texttt{encode}(\cdot)$ to be the QR code generation function. Specifically, the $\texttt{encode}$ function we use will return a QR code without finder, alignment and version patterns. When extracting the code, the above patterns will be added back for decoding the credential information behind the QR code.

Algorithm 2: Embed Signature Into Sparse Masks

input : A set of masks $\mathbf{M} = \{\mathbf{M}_l\}_{l=1}^{N}$, a signature $\mathbf{s}$

output : A set of masks with signature embedded $\{\mathbf{M}_l^e\}_{l=1}^{N}$

1 Calculate $\mathbf{M}_s \leftarrow \texttt{encode}(\mathbf{s})$.

2 Squeeze each $\mathbf{M}_l$ into a two-dimensional matrix $\mathbf{M}_l^f$ by setting $(\mathbf{M}_l^f)_{ij} = \mathbb{I}_{\|(\mathbf{M}_l)_{ij}\|_0 > 0}$.

3 Calculate the similarity (percentage of matched 0-1 patterns) between each $\mathbf{M}_l^f$ and $\mathbf{M}_s$ and name the one with the largest similarity $\mathbf{M}_{max}^f$.

4 Change the dimension of $\mathbf{M}_s$ and fit it into $\mathbf{M}_{max}^f$ to the region where the similarity is the largest.

3.4 Ownership Verification with Sparse Structural Information

Next, we propose three different verification schemes based on sparse structural information, as summarized in Table A9. Under our unique context, we further introduce a new *Add-on Attacks* which aims to create ambiguity against lottery verification by "recovering" several pruned weights and manipulating the sparsity patterns. More details can be found in Appendix A1.

Scheme $\mathcal{V}_1$: Distribute the extreme winning tickets with key masks. Scheme $\mathcal{V}_1$ is designed to protect the sparsity masks. We separate the sparsity mask $\mathbf{M}$ into two parts: $\mathbf{M}_l$ and $\mathbf{M}_s$, where l/s subscripts denote "large"/"small", respectively. The small mask is sparser than the large one, which is used as the key mask while the large counterpart is the locked mask. We apply these two masks on weights and get two separate parts $(\mathbf{W} \odot \mathbf{M}_l, \mathbf{W} \odot \mathbf{M}_s)$. Before re-training, legitimate users should merge the two weights by adding them up to recover the original sparse weights $\mathbf{W} \odot \mathbf{M}$. The ownership can be automatically verified by the inference performance, since an incorrect provided mask-weight pair will deteriorate accuracies after re-training.

Scheme $\mathcal{V}_2$: Embed signatures in sparse masks. We apply the signature mask embedding method we proposed to embed credentials into the extreme winning ticket. Then we train it and dispatch the trained model to legitimate users. No further action is required at the users' side. For the verification process, one can use extract the signature from the sparse model and validate the ownership of the extreme winning tickets. Compared with Scheme $\mathcal{V}_1$, Scheme $\mathcal{V}_2$ is more user-friendly since no extra action is performed at the users' side. The application scenarios of Scheme $\mathcal{V}_1$ and $\mathcal{V}_2$ are also different: the latter focus on protecting the trained weights. It also shows great defense ability towards removal and ambiguity attacks. However, this scheme works under the white-box verification setting only, which means that access to models' weights has to be assumed. To overcome that assumption, we combine Scheme $\mathcal{V}_2$ with a trigger set-based method and propose Scheme $\mathcal{V}_3$ in the next section.

Scheme $\mathcal{V}_3$: Combining trigger set-based methods. Scheme $\mathcal{V}_3$ is more sophisticated than Scheme $\mathcal{V}_2$ as a set of trigger images and labels are used during the (re-)training process. With the help of this trigger set, Scheme $\mathcal{V}_3$ is now capable of black-box verification. By using remote calls of service APIs, the owner can first probe and claim the ownership in a black-box regime, and further request a white-box verification if the black-box mode has raised a red flag. The white-box verification part for Scheme $\mathcal{V}_3$ remains the same as Scheme $\mathcal{V}_2$.

4 Experiments

In this section, we will list the details of our experiments and show the results to prove the effectiveness of our ownership verification methods, as well as the robustness to removal attacks (model pruning and fine-tuning) and ambiguity attacks (fake paths, fake code, and add-on attacks).

General Settings. We use three networks architectures (ResNet-20s, ResNet-18 and ResNet-50) and two benchmarks (CIFAR-10 [32] and CIFAR-100 [32]) in our experiments. For all experiment, we follow the same (re-)training and testing protocol. The optimizer we use is an SGD optimizer with a momentum factor of 0.9 and a weight decay factor of 1e-4 for ResNet-20s and ResNet-18, and 5e-4 for ResNet-50. We train the model for 182 epochs with an initial learning rate of 0.1 and we decay the learning rate at 91^{st} and 136^{th} epoch by 0.1. We use a late rewinding technique that rewinds the weight to the 3^{rd} checkpoint. More results on ResNet-50 are deferred to Appendix A3.

4.1 Finding Extreme Tickets

To find extreme tickets, we need to perform multiple rounds of the train-prune-retrain process. Once the test performance of the currently trained model cannot match the performance of the dense model, we revert the pruning process back for one time and reduce the pruning ratio. The choices of pruning ratio of weights are $[0.2, 0.1, 0.05, 0.1]$. The results are shown in Table 1. We also report the pruning specification which includes the remaining weights of the extreme winning tickets, as well as the pruning times for each pruning rate we choose.

Table 1: Performance of dense models and extremely sparse winning tickets, and the pruning specification. The performance are expressed in terms of the test accuracy of the dense model and the extremely sparse winning ticket. The pruning specification includes the proportion of remaining weight as well as the number of pruning with four different pruning ratios (in brackets).

Model	Dataset	Performance	Pruning Specification
ResNet-20s	CIFAR-10	91.67%,91.66%	19.369% (5,1,8,1)
ResNet-20s	CIFAR-100	66.36%,66.39%	19.901% (6,0,4,7)
ResNet-18	CIFAR-10	93.67%,93.60%	1.236% (18,3,0,6)
ResNet-18	CIFAR-100	72.44%,72.59%	2.251% (17,0,0,0)

Notice that ResNet-20s needs at least 15 times of pruning before we find the extreme winning tickets, and for ResNet-18 such number increases to 17. Numerous pruning rounds exemplify the effort to find the extremely sparse winning ticket and emphasizes the importance to protect them again.

4.2 Effectiveness of Different Schemes

Scheme $\mathcal{V}_1$ To verify that models without correct key masks cannot be trained to match the performance of the dense models, we conduct experiments that i) directly re-train the models with initialization weights; and ii) directly use the trained model to inference but without the key masks on ResNet-20s and ResNet-18. Fig. 2 show that results of directly re-train the model. It can be seen that more "1"s in key masks can increase the performance divergence. Different splitting functions do not make an essential difference, showing a wide range of the choices of `score` functions.

Figure 2: Effectiveness of Scheme $\mathcal{V}_1$: Re-training without key masks generated by four methods: Betweenness, EWP, OMP, Random (Paths). The x-axis is the relative sparsity w.r.t the extreme winning ticket.

Scheme $\mathcal{V}_2$ To show that our proposal can embed information into models' sparse structures without significantly harming models' performance, we conduct experiments to compare the performance of the sparse model before and after a signature string is embedded. Table 2 shows that the performance of the sparse model with the string embedded is only slightly lower than the original extremely sparse winning ticket, which has demonstrated that using Scheme $\mathcal{V}_2$ and our mask embedding method endows owners the ability to embed information at the cost of little performance.

Table 2: Effectiveness of Scheme $\mathcal{V}_2$: performance of extreme winning tickets after QR codes are embedded. We study two different models and compare their inference performance before and after the QR code is embedded. The performance after embedding and the performance drop are reported (in brackets).

Model	Accuracy after embedding	
	CIFAR-10	CIFAR-100
ResNet-20s	91.37% ($\downarrow$ 0.29%)	66.14% ($\downarrow$ 0.25%)
ResNet-18	93.56% ($\downarrow$ 0.11%)	72.35% ($\downarrow$ 0.24%)

Table 3: Effectiveness of Scheme $\mathcal{V}_3$: ResNet-20s on CIFAR-10 and CIFAR-100. ESWT is the abbreviation of **E**xtremely **S**parse **W**inning **T**ickets. We re-train the two extremely sparse winning tickets with QR code embedded found with the trigger set enabled.

Model	Test Accuracy	
	CIFAR-10	CIFAR-100
ESWT	91.66% (16.0%)	66.36% (0.0%)
ESWT + $\mathbf{M}_s$ + $\mathbf{T}$	91.46% (91.0%)	65.39% (90.0%)

Scheme $\mathcal{V}_3$ Under Scheme $\mathcal{V}_3$, we use a set of trigger images during the re-training of extremely sparse winning tickets. The inference performance on the original task (*i.e.*, CIFAR-10 or CIFAR-100) should not be greatly affected with trigger sets enabled. We report the inference performance in Table 3. From the table, we can see that the performance only drops 0.2% on CIFAR-10 and 0.97% on CIFAR-100 for ResNet-20s, while the detection rater of the trigger set images are high (91.0% on CIFAR-10 and 90.0% on CIFAR-100). At the same time, the extremely sparse winning ticket trained from CIFAR-10 and CIFAR-100 without a trigger set can only achieve 16.0% and 0.0%, respectively. This suggests that the Scheme $\mathcal{V}_3$ we propose can work as expected, *i.e.,* perform significantly better on the trigger set while not harming the performance on the original task.

4.3 Robustness Against Removal Attacks

Fine-tuning Attacks   Fine-tuning the model can only change the values of weights while not changing the sparse structure of extreme winning tickets. As a consequence, Scheme $\mathcal{V}_2$ and $\mathcal{V}_3$ is resistant to fine-tuning attacks under the white-box verification setting.

For Scheme $\mathcal{V}_1$, users are required to provide the key masks to recover the correct masks, and then re-train the extremely sparse winning ticket or directly use the trained ticket for inference. One key property we need to verify is that attackers cannot bypass the key masks by fine-tuning the model on a new benchmark. To this end, we conduct transfer experiments after splitting the key masks out. On CIFAR-100, we train the model with the locked mask generated on the extremely sparse winning

ticket identified on CIFAR-10; on CIFAR-10, we conduct a similar experiment with the locked mask from CIFAR-100. The results are shown in Table 4. From the table, we can see that even transferring the sparse mask cannot bypass the requirement of key masks. The performance gaps between the transferred model and the extremely sparse winning ticket found on each set are greater than 3% on both datasets, much higher than the 1% criterion we set for matching performance. Such big gaps prove that the model after fine-tuning (transferring) attacks is not useful in practice.

Table 4: Fine-tuning Attacks on Scheme $\mathcal{V}_1$: Transferring extreme winning tickets of ResNet-20s found on CIFAR-10/100. 10→100 means transferring from CIFAR-10 to CIFAR-100 and vice versa. The percentage inside brackets denotes the relative sparsity of the key mask w.r.t the extremely sparse winning ticket.

Model	Test Accuracy	
	10→100	100→10
OMP (5%)	59.80%	87.66%
EWP (5%)	60.27%	88.21%
Betweenness (5%)	59.61%	87.22%

Table 5: Pruning Attacks on Scheme $\mathcal{V}_3$: Performance of ResNet-20s on CIFAR-10/100 after pruning with different pruning ratios. The accuracy on CIFAR-10/100 are shown outside the brackets and the accuracy on trigger images are inside the brackets.

Model	Accuracy	
	CIFAR-10	CIFAR-100
Original model	91.46% (91.0%)	65.39% (90.0%)
Pruning 5%	91.33% (89.0%)	64.78% (91.0%)
Pruning 10%	90.66% (90.0%)	62.96% (73.0%)
Pruning 20%	87.86% (81.0%)	50.14% (16.0%)
Pruning 50%	33.04% (18.0%)	8.56% (0.00%)

We also have conducted experiments to study if the black-box verification mode of Scheme $\mathcal{V}_3$ can resist fine-tuning attacks. We first re-train an extremely sparse winning ticket under Scheme $\mathcal{V}_3$ on CIFAR-10, and then we fine-tune the trained model on CIFAR-100. The experiment results are shown in Appendix A3. The test accuracy on the images in the trigger set remains high after fine-tuning, showing that the black-box verification mode of Scheme $\mathcal{V}_3$ is resistant to all removal attacks.

Model pruning   Pruning the model under Scheme $\mathcal{V}_1$ is meaningless since pruning the model cannot recover the full masks back. So we focus on Scheme $\mathcal{V}_2$ and $\mathcal{V}_3$ exclusively for model pruning attacks, *i.e.,* focus on protecting the trained weights. Pruning the trained model leaves more "0" in the trained model which might change the extracted QR code and make it unable to decode. To study if our model can resist the pruning attack, we conduct experiments with different pruning methods (one-shot magnitude and random pruning) and different pruning ratios (5%, 10%, 20%, 30%, 50%).

In Table 6 we show the inference performance after pruning, and we also show the QR code extracted on ResNet-20s from masks in Figure 3. We can see that the performance of the pruned model will degrade dramatically after 20% percent of one-shot magnitude pruning, and 5% percent of random pruning. The QR code extracted from the ResNet-20s can be decoded even after 20% percent of one-shot magnitude pruning, and the QR code extracted from ResNet-18 can be decoded after 10% percent pruning. More visualization results are deferred to Appendix A3.

Table 6: Inference performance of extremely sparse winning tickets on ResNet-20s and ResNet-18 after model pruning attacks under different pruning methods and pruning ratios. OMP stands for one-shot magnitude pruning. The numbers in brackets stand for the pruning ratios.

Method (Percent)	Performance	
	CIFAR-10	CIFAR-100
Scheme $\mathcal{V}_2$	91.37%	72.35%
OMP (5%)	91.25%	72.27%
OMP (10%)	90.72%	71.42%
OMP (20%)	88.03%	69.51%
OMP (30%)	80.08%	60.31%
OMP (50%)	36.62%	9.24%
Random Pruning (5%)	60.87%	58.23%
Random Pruning (10%)	30.49%	22.67%
Random Pruning (20%)	11.95%	3.23%
Random Pruning (30%)	12.05%	1.0%
Random Pruning (50%)	10.00%	1.0%

Table 7: Summary of different types of ambiguity attacks. We show the specification of each attack, *i.e.*, the accessibility of each component to attackers, the attack methods, and the targeted schemes.

Attack name	Attackers can access	How to attack	Attack Scheme
$fake_1$	$\mathbf{W} \odot \mathbf{M}_l$	Forge $\mathbf{W} \odot \mathbf{M}_s$	Scheme $\mathcal{V}_1$
$fake_2$	$\mathbf{W} \odot \mathbf{M}$	Add noise $\mathbf{W}_{noise} \odot \mathbf{M}_{noise}$	Scheme $\mathcal{V}_2$ and $\mathcal{V}_3$
$fake_3$	$\mathbf{W} \odot \mathbf{M}$ and $\texttt{encode}(\cdot)$	Replace $\mathbf{M}_s$	Scheme $\mathcal{V}_2$ and $\mathcal{V}_3$

Table 8: Test accuracy and remaining weights after add-on attacks under different rates on ResNet-20s, with the matching condition and the decode-ability of the QR code extracted from the masks.

Add-on Rate	Test Accuracy (% r_{remain})	Decode-able?	Match?
0%	91.53% (19.369%)	✓	✓
0.5%	91.04% (19.789%)	✓	✓
1%	90.23% (20.179%)	✓	✗
2%	86.64% (21.009%)	✗	✗
5%	79.49% (23.386%)	✗	✗
10%	71.06% (27.402%)	✗	✗

4.4   Resilience Against Ambiguity Attacks

In this section, we will evaluate the robustness against ambiguity attacks, summarized in Table 7.

Scheme $\mathcal{V}_1$ (*fake*$_1$: Attackers can access $\mathbf{W} \odot \mathbf{M}_l$ only) The goal of *fake*$_1$ is to forge a new key mask $\mathbf{M}'_s$ with new underlying weights $\mathbf{W}'$. As the attacker has no prior information on $(\mathbf{W} \odot \mathbf{M}_s)$,

Original   Prune 5%   Prune 10%   Prune 20%   Prune 30%   Prune 50%

Figure 3: QR code extracted from ResNet-20s under pruning attacks with different ratios. The code extracted under 5% and 10% pruning ratio can be easily decoded into a readable string "signature", and the code under 20% pruning ratio can be decoded into "signature" with tools at https://github.com/merricx/qrazybox/.

the forging process can only be performed randomly. From Figure 4 we can see that such an attack method is not practical as the performance gap is much greater than $\epsilon_f(=1\%)$ after using random key masks. For example, if we adopt OMP as the scoring function to construct the key masks, we only need a key mask of around 10% relatively sparsity to make the model resistant to random attacks.

Figure 4: Random attacks on Scheme $\mathcal{V}_1$. The x-axis is the relative sparsity of the key masks. The solid/dashed lines represent the performance **before/after** random attacks.

Scheme $\mathcal{V}_2$ and $\mathcal{V}_3$ (*fake$_2$*: Attackers can access $\mathbf{W} \odot \mathbf{M}$ but not knowing $\texttt{encode}(\cdot)$) One might use add-on attacks and try to "contaminate" the information we embed in the sparse mask. Specifically, we randomly add noises to the position where the weights are pruned. We test with add-on rates ranging from 0% to 10%, since a 10% efficiency gap will harm the value of attacking the model. The results are shown in Table 8 and Figure 5. From the table, we can see that introducing merely 1% of noise to the trained model will un-match the attacked model (*i.e.,* the performance gap becomes greater than 1%). For the add-on rates that are smaller than 1%, the QR code embedded in the sparse mask can still be decoded into a normal string. Such results prove that both Scheme $\mathcal{V}_2$ and $\mathcal{V}_3$ are resistant to attack *fake$_2$*.

Original   Add 0.5%   Add 1%   Add 2%   Add 5%   Add 10%

Figure 5: Visualization of QR code extracted and processed@ under different add-on rates.

(*fake$_3$*: Attackers can access $\mathbf{W} \odot \mathbf{M}$ and $\texttt{encode}(\cdot)$) If the attacker knows the $\texttt{encode}$ function for generating the $\mathbf{M}_s$, a similar but fake signature mask $\mathbf{M}'_s$ which contains a different signature can be generated in the same way. However as shown in Figure 1, without the finder, alignment and version patterns one can hardly tell which part belongs to a QR code. Even if the attacker know the position where the code is embedded (namely an insider attack [28]), directly replace the embedded region with new signature mask $\mathbf{M}'_s$ and $\mathbf{W}'$ (noise) will also considerably degrade the performance of the attacked model since a large amount of "incorrect" weights are settled. For example, for ResNet-20s on CIFAR-10, the test accuracy of the attacked model will decrease from 91.37% to 57.00%, which is nearly a 50% degradation in performance.

5 Conclusion and Discussion of Broad Impact

LTH offers superior sparse models through burdensome explorations, serving as an intriguing yet expansive solution for resource-constrained applications. It motivates the necessity of protecting the copyright of these precious winning tickets. We investigate a brand new verification technique by leveraging the sparse structural information, which embeds signatures into lottery tickets' typologies. Extensive results verify our proposal's effectiveness and robustness against diverse malicious attacks.

This work is scientific in nature and brings positive societal impacts. Note that every second, giant and start-up companies have invested billions of dollars to identify superior yet light-weight compact deep neural networks virtually. We believe our new *lottery verification* mechanism can assist both industry and academia in defending their interests from illegal distribution or usage.

References

[1] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2018.

[2] Namhoon Lee, Thalaiyasingam Ajanthan, and Philip HS Torr. Snip: Single-shot network pruning based on connection sensitivity. *arXiv preprint arXiv:1810.02340*, 2018.

[3] Chaoqi Wang, Guodong Zhang, and Roger Grosse. Picking winning tickets before training by preserving gradient flow. In *International Conference on Learning Representations*, 2019.

[4] Haoran You, Chaojian Li, Pengfei Xu, Yonggan Fu, Yue Wang, Xiaohan Chen, Richard G. Baraniuk, Zhangyang Wang, and Yingyan Lin. Drawing early-bird tickets: Toward more efficient training of deep networks. In *8th International Conference on Learning Representations*, 2020.

[5] Jonathan Frankle, Gintare Karolina Dziugaite, Daniel M Roy, and Michael Carbin. Pruning neural networks at initialization: Why are we missing the mark? *arXiv preprint arXiv:2009.08576*, 2020.

[6] Yusuke Uchida, Yuki Nagai, Shigeyuki Sakazawa, and Shin'ichi Satoh. Embedding watermarks into deep neural networks. In *Proceedings of the 2017 ACM on International Conference on Multimedia Retrieval*, pages 269–277, 2017.

[7] Yossi Adi, Carsten Baum, Moustapha Cisse, Benny Pinkas, and Joseph Keshet. Turning your weakness into a strength: Watermarking deep neural networks by backdooring. In *27th {USENIX} Security Symposium ({USENIX} Security 18)*, pages 1615–1631, 2018.

[8] Jialong Zhang, Zhongshu Gu, Jiyong Jang, Hui Wu, Marc Ph Stoecklin, Heqing Huang, and Ian Molloy. Protecting intellectual property of deep neural networks with watermarking. In *Proceedings of the 2018 on Asia Conference on Computer and Communications Security*, pages 159–172, 2018.

[9] Haoyu Ma, Tianlong Chen, Ting-Kuei Hu, Chenyu You, Xiaohui Xie, and Zhangyang Wang. Undistillable: Making a nasty teacher that cannot teach students. *arXiv preprint arXiv:2105.07381*, 2021.

[10] Bita Darvish Rouhani, Huili Chen, and Farinaz Koushanfar. Deepsigns: An end-to-end watermarking framework for ownership protection of deep neural networks. In *Proceedings of the Twenty-Fourth International Conference on Architectural Support for Programming Languages and Operating Systems*, pages 485–497, 2019.

[11] Jie Zhang, Dongdong Chen, Jing Liao, Weiming Zhang, Gang Hua, and Nenghai Yu. Passport-aware normalization for deep model protection. *Advances in Neural Information Processing Systems*, 33, 2020.

[12] Hidenori Tanaka, Daniel Kunin, Daniel L Yamins, and Surya Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. *Advances in Neural Information Processing Systems*, 33, 2020.

[13] Steven A Janowsky. Pruning versus clipping in neural networks. *Physical Review A*, 39(12):6600, 1989.

[14] Song Han, Jeff Pool, John Tran, and William J Dally. Learning both weights and connections for efficient neural network. In *NIPS*, 2015.

[15] Michael C Mozer and Paul Smolensky. Skeletonization: A technique for trimming the fat from a network via relevance assessment. In *Advances in neural information processing systems*, pages 107–115, 1989.

[16] Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pages 598–605, 1990.

[17] Babak Hassibi and David G Stork. *Second order derivatives for network pruning: Optimal brain surgeon*. Morgan Kaufmann, 1993.

[18] Pavlo Molchanov, Stephen Tyree, Tero Karras, Timo Aila, and Jan Kautz. Pruning convolutional neural networks for resource efficient inference. *arXiv preprint arXiv:1611.06440*, 2016.

[19] Xin Dong, Shangyu Chen, and Sinno Jialin Pan. Learning to prune deep neural networks via layer-wise optimal brain surgeon. *arXiv preprint arXiv:1705.07565*, 2017.

[20] Ruichi Yu, Ang Li, Chun-Fu Chen, Jui-Hsin Lai, Vlad I Morariu, Xintong Han, Mingfei Gao, Ching-Yung Lin, and Larry S Davis. Nisp: Pruning networks using neuron importance score propagation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9194–9203, 2018.

[21] Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In *International Conference on Machine Learning*, pages 3259–3269. PMLR, 2020.

[22] Neha Mukund Kalibhat, Yogesh Balaji, and Soheil Feizi. Winning lottery tickets in deep generative models, 2021.

[23] Xuxi Chen, Zhenyu Zhang, Yongduo Sui, and Tianlong Chen. {GAN}s can play lottery tickets too. In *International Conference on Learning Representations*, 2021.

[24] Trevor Gale, Erich Elsen, and Sara Hooker. The state of sparsity in deep neural networks. *arXiv*, abs/1902.09574, 2019.

[25] Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Zhangyang Wang, and Michael Carbin. The lottery ticket hypothesis for pre-trained bert networks, 2020.

[26] Haonan Yu, Sergey Edunov, Yuandong Tian, and Ari S. Morcos. Playing the lottery with rewards and multiple languages: lottery tickets in rl and nlp. In *8th International Conference on Learning Representations*, 2020.

[27] Erwan Le Merrer, Patrick Perez, and Gilles Trédan. Adversarial frontier stitching for remote neural network watermarking. *Neural Computing and Applications*, 32(13):9233–9244, 2020.

[28] Lixin Fan, Kam Woh Ng, and Chee Seng Chan. Rethinking deep neural network ownership verification: Embedding passports to defeat ambiguity attacks. 2019.

[29] Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Michael Carbin, and Zhangyang Wang. The lottery tickets hypothesis for supervised and self-supervised pre-training in computer vision models. *arXiv preprint arXiv:2012.06908*, 2020.

[30] Shreyas Malakarjun Patil and Constantine Dovrolis. Phew: Paths with higher edge-weights give "winning tickets" without training data, 2020.

[31] Tan Jin Soon. Qr code. *Synthesis Journal*, 2008:59–78, 2008.

[32] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.