Look where you look! Saliency-guided Q-networks for visual RL tasks

Abstract

Deep reinforcement learning policies, despite their outstanding efficiency in simu-
lated visual control tasks, have shown disappointing ability to generalize across
disturbances in the input training images. Changes in image statistics or distract-
ing background elements are pitfalls that prevent generalization and real-world
applicability of such control policies. We elaborate on the intuition that a good
visual policy should be able to identify which pixels are important for its decision,
and preserve this identification of important sources of information across images.
This implies that training of a policy with small generalization gap should focus
on such important pixels and ignore the others. This leads to the introduction of
saliency-guided Q-networks (SGQN), a generic method for visual reinforcement
learning, that is compatible with any value function learning method. SGQN vastly
improves the generalization capability of Soft Actor-Critic agents and outperforms
existing state-of-the-art methods on the Deepmind Control Generalization bench-
mark, setting a new reference in terms of training efficiency, generalization gap,
and policy interpretability.

1 Introduction

Deploying reinforcement learning (RL) [Sutton and Barto, 2018] algorithms in real-life situations
requires overcoming a number of still open challenges. Among these is the ability for the trained
control policies to focus their attention on causal state features and ignore confounding factors
[Machado et al., 2018, Henderson et al., 2018]. In visual RL tasks, this implies for instance being able
to ignore the background and other distracting factors, even when they might be somehow correlated
with progress within the task at hand. Despite a very active trend of research on the topic of closing
the generalization gap for RL agents [Cobbe et al., 2019, 2020, Song et al., 2019, Hansen et al., 2021,
Hansen and Wang, 2021], current algorithms are still rather brittle when it comes to filtering out such
distracting factors, which hinders their applicability to real-life scenarios.

In the present work, we propose a novel method which encourages the agent to identify efficiently
crucial input pixels, and strengthen the policy's dependency on those pixels. In plain words, we
encourage the agent to pay attention to, and be self-aware of where it looks in input images, in
order to make its decision policy more focused on important areas and less sensitive to ambiguous
or distracting pixels. This intention is expressed within the generic method of saliency-guided
Q-networks (SGQN), which can be applied on any approximate value iteration based, deep RL
algorithm. SGQN relies on two core mechanisms. First, it regularizes the value function learning
process with a consistency term that encourages the value function to depend in priority on pixels
that are identified as decisive. The second mechanism pushes the agent to be self-aware of which
pixels are responsible for making decisions, and encode this information within the extracted features.
This second mechanism translates to a self-supervised learning objective, where the agent trains to
predict its own Q-value's saliency maps. In turn, this improves the regularization of the value function

38 learning phase, which provide better labels for the self-supervised learning phase, overall resulting in
39 a virtuous improvement circle.

40 SGQN is a simple, generic method, that permits many variants in the way the two core mechanisms
41 are implemented. In the present paper, we demonstrate that applying SGQN to soft actor-critic
42 agents [Haarnoja et al., 2018] dramatically enhances their quality on the DMControl generaliza-
43 tion benchmark [Hansen and Wang, 2021], a standard evaluation benchmark for generalization in
44 continuous actions RL. SGQN already improves the training efficiency of such agents in domains
45 without distractions. But most importantly, it sets a new state-of-the-art in terms of generalization
46 performance, in particular in especially difficult benchmarks where previous methods suffered from
47 confounding factors. As a side benefit, it also provides explanations of its own decisions at run time,
48 under the form of interpretable attribution maps, with no overhead cost and no need to compute ad
49 hoc saliency maps, which is another desirable property in the pursuit of deployable RL.

50 Section 2 of this paper introduces the necessary background and state-of-the-art in closing the
51 generalization gap in RL, as well as attribution methods, leading to the key intuitions underpinning
52 SGQN. Section 3 introduces the method itself and implements it within soft actor-critic agents.
53 Section 4 evaluates SGQN's training efficiency, generalization capabilities, and policy interpretability.
54 It also discusses the different design choices made along the way and some foreseeable limitations.
55 Section 5 summarizes and concludes this paper.

2   Background and related work

Reinforcement learning (RL). RL [Sutton and Barto, 2018] considers the problem of learning a
decision making policy for an agent interacting over multiple time steps with a dynamic environment.
At each time step, the agent and environment are described through a state $s \in \mathcal{S}$, and an action
$a \in \mathcal{A}$ is performed; then the system transitions to a new state s' according to probability $\mathcal{P}(s'|s,a)$,
while receiving reward $\mathcal{R}(s,a)$. The tuple $M = (\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R})$ forms a Markov Decision Process
(MDP) [Puterman, 2014], which is often complemented with the knowledge of an initial state
distribution $p_0(s)$. A decision making policy parameterized by θ is a function $\pi_\theta(a|s)$ mapping states
to distributions over actions. Training a reinforcement learning agent consists in finding the policy
that maximizes the discounted expected return $J(\pi_\theta) = \mathbb{E}[\sum_{t=0}^{\infty} \gamma^t \mathcal{R}(s_t, a_t)]$.

Poor generalization in RL. Despite the recent progress of (deep) RL algorithms in solving complex
tasks, a number of studies have pointed out their poor generalization capabilities. Using a grid-world
maze environment, Zhang et al. [2018c] demonstrate the ability of deep RL agents to memorize a
non-trivial number of training levels with completely random rewards. Using attribution methods,
Song et al. [2019] highlight what they define as *observational overfitting* i.e., the propensity of
RL agents to base their decision on background uninformative elements observed during training,
instead of the semantic pieces of information one could intuitively expect such as object positions or
relations. Zhang et al. [2018a] measure the generalization error in continuous control environments
by training and testing agents on different sets of seeds. Zhao et al. [2019] define generalization in
RL as robustness to a distribution of environments, and samples environments from this distribution
to learn a robust policy. Overall, these works illustrate the lack of generalization abilities of vanilla
deep RL algorithms, either to states that were not encountered during training, or to variations in the
transition dynamics. In the present work, we aim to shape the policy learning process, so that it relies
on meaningful features that permit such generalization and robustness.

Evaluating generalization in RL. Under the impetus of these works and the need for benchmarks
with separate training and testing environments [Whiteson et al., 2011, Machado et al., 2018, Hender-
son et al., 2018], original benchmarks for evaluating the generalization capacities of RL agents have
been designed. Packer et al. [2018] propose a modified version from control problems in OpenAI
Gym [Brockman et al., 2016] and Roboschool [Schulman et al., 2017] that lets the user change the
system dynamics. Machado et al. [2018] propose a modified version of the ALE environments [Belle-
mare et al., 2013] allowing one to change modes and difficulties. Without modifying the underlying
transition model, Zhang et al. [2018b], Grigsby and Qi [2020], Stone et al. [2021] add distracting
elements (e.g., addition of real images or videos in the background, change of colors) to the ALE
environments and the Deepmind control suite. Even if the modifications to the original environments
do not alter the semantic information, they already appear to be challenging for agents prone to
observational overfitting. Cobbe et al. [2019, 2020], Juliani et al. [2019] use procedural content

generation to design highly randomized sets of environments with different level layouts, game assets, and objects locations, letting the user study robustness to several independent variation factors. One may note that the diversification of learning environments is in itself a first practical way to induce generalization [Tobin et al., 2017, Cobbe et al., 2019, 2020] and also permits curriculum-based learning [Jiang et al., 2021]. Nevertheless, when the diversity of training scenarios is lacking, three sets of methods are generally employed, as detailed below.

Regularization. Farebrother et al. [2018], Cobbe et al. [2019, 2020] demonstrated the beneficial effects of popular regularization methods from the supervised learning literature. Igl et al. [2019] mitigate the adverse effect that classical regularization may have on the gradient quality with selective noise injection and combine it with an information bottleneck regularization. Inspired by mixup [Zhang et al., 2018d], Wang et al. [2020] use mixtures of observations to stimulate linearity in the policy's outputs in-between states.

Data augmentation. Laskin et al. [2020a] evidence the benefits of image augmentations for both off-policy and on-policy algorithms by augmenting image observations processed by the agent during training. Yarats et al. [2020] average both the value function and its target over multiple image transformations. Raileanu et al. [2021] combine the previous method with UCB [Auer, 2002] to pick the most promising augmentation, and apply it to PPO [Schulman et al., 2017]. Fan et al. [2021] use weak data augmentation to train an expert without hindering its performance and distill its policy to a student trained with substantial data augmentation. Besides augmentations of raw inputs, other augmentations operate directly within the agents' network. Lee et al. [2020] introduces a random convolutions layer at the earliest level of the agent's network to modify the *texture* of the visual observations. Zhou et al. [2020] adapt mixup [Zhang et al., 2018d] with style statistics encoded in early instance normalization layers to increase data diversity. Bertoin and Rachelson [2022] apply channel-consistent local permutations of the feature map to induce robustness to spatial spurious correlations. Finally, data augmentation can also be used in an auxiliary loss to promote invariance to distributional shift in representations. Hansen and Wang [2021] propose a soft-data augmentation method (SODA) by adding an auxiliary self-supervised learning phase to SAC [Haarnoja et al., 2018], similar to BYOL [Grill et al., 2020].

Representation learning. Higgins et al. [2017b] demonstrate zero-shot adaptation to unseen configurations in testing environments, using a β-VAE [Higgins et al., 2017a] to learn disentangled representations. Fan and Li [2021] jointly maximize the mutual information between sequences of observations to remove the task-irrelevant information. Wang et al. [2021] extract, using visual attention, the observation foreground to provide background invariant inputs to the policy learner. Raileanu and Fergus [2021] separate the actor from the critic in the agent's network architecture and add an adversarial auxiliary objective on the actor's representations to remove the information needed to estimate the value function that is not irrelevant to a general policy. Zhang et al. [2020] train an encoder to project states so that their distances match with the bisimulation distances in state space. Other recent works use behavioral similarities combined with contrastive learning [Agarwal et al., 2020] or clustering [Mazoure et al., 2022] to map behaviorally similar observations to similar representations.

Attributing decisions to inputs. Although not directly aiming at generalization, a related topic is that of *attribution*, where one wishes to identify which parts of an input are responsible for major changes in the output of a function. Intrinsically, computing attributions boils down to computing (some transformation of) the gradient of the function's output with respect to the input's components. Computational graphs of differentiable functions, such as neural networks, are particularly suited to computing attributions by using the back propagation algorithm [Simonyan et al., 2014, Springenberg et al., 2015, Smilkov et al., 2017, Selvaraju et al., 2017, Chattopadhay et al., 2018]. When these methods are applied to images, one obtains a map which is known as a *saliency map* or *attribution map*. Such attribution maps indicate which input pixels are determining for a policy's output (or the Q-value of action a) and thus permit interpretation of the function itself, rather than its point-wise decision alone. Mousavi et al. [2016], Greydanus et al. [2018], Atrey et al. [2020] have used saliency maps to analyze and explain the behavior of RL agents. Rosynski et al. [2020] indicates in particular that guided backpropagation [Springenberg et al., 2015] provides good visualizations of RL policies across a span of environments. Most existing works, however, only exploit saliency maps as tools for interpretation. Closely related to our contribution is that of Ismail et al. [2021], who incorporate attributions into their training process in supervised learning. They construct a binary mask from the saliency map by keeping only pixels above a certain quantile. Their procedure iteratively uses this

mask to remove features with small and potentially noisy gradients while maximizing the similarity of model outputs for both masked and unmasked inputs.

This contribution. The rationale of the method we introduce in the next section is to encourage the agent to generalize to new states, based on which pixels are identified as important decision factors. For this purpose, we perform pixel-level masking on the input image, depending on the computed attribution, and regularize the value function learning process with the difference in Q-values. This way, we encourage the value function to focus specifically on the pixels with high attribution. Leveraging data augmentation, self-supervised learning methods have demonstrated their ability to induce features that are insensitive to lighting, background, and high-frequency noise. The method we propose does not directly use data augmentation in the value function or policy update phase. Instead, it is introduced during an auxiliary phase where the augmented state's encoding is used to predict the attribution mask of the original state. This way, the encoder is encouraged to preserve information that is useful for predicting which pixels were important in the agent's decision-making. A parallel with SODA can thus be made by considering that the projector used in the BYOL objective is here replaced by a surrogate of the derivative of the value function, allowing to refine the quality of the projection and to learn which pixels and visual features are consistently important across states to predict the Q-values. The value function regularization and the self-supervised learning objective are mutually beneficial: the former outputs sharper saliency maps from the value function, that serve as better labels for the auxiliary self-supervised learning task, which in turn induces better features and better attributions. In short, we encourage the agent to pay attention to where it is looking, with the intention that this triggers more efficient learning and more interpretable output.

3   Saliency-guided Q-networks

We propose a generic saliency-guided Q-networks (SGQN) method, for visual deep reinforcement learning. In a nutshell, SGQN considers the application of the binarized attribution map as a mask over the input state and regularizes the value function learning objective with a consistency term between the Q-values of the masked and the original state images. It also defines an auxiliary self-supervised learning task that aims to match a prediction of the attribution map on an augmented image, with the attribution map of the original image. Such an auxiliary task orients the gradient descent towards features that are shared across states, as illustrated by the work of Hansen and Wang [2021]. SGQN can be combined with any value function learning objective, any attribution map computation technique, any image augmentation method for self-supervised learning, and is suited for both discrete and continuous actions. We first present SGQN as a generic enhancement of approximate value iteration methods. Then we derive a specific version built on SAC [Haarnoja et al., 2018] and on the guided backpropagation algorithm [Springenberg et al., 2015].

A vast number of deep RL algorithms belong to the family of approximate value iteration methods. Such methods build a sequence of $(Q_n)_{n \in \mathbb{N}}$ and $(\pi_n)_{n \in \mathbb{N}}$ functions that aim to asymptotically tend to Q^* and π^*. Q_{n+1} is defined as a minimizer of $L_Q = \|Q - T^{\pi_n}Q_n\|$, where T^{π_n} is the Bellman evaluation operator with respect to π_n. Then π_{n+1} is defined by applying a *greediness* operator $\mathcal{G}$ to Q_{n+1} and the process is iterated. Geist et al. [2019] showed how one could introduce regularization within the expression of L_Q, yielding the class of regularized MDPs. The classical DQN algorithm [Mnih et al., 2015] approximates the solution to L_Q by taking a number of gradient steps with respect to a target network Q_n and uses an $\arg\max$ greediness operator. When actions are continuous, actor-critic methods introduce a surrogate model of the Q_{n+1}-greedy policy, under the form of an actor network $\pi_{n+1} = \mathcal{G}(Q_{n+1})$ obtained by gradient ascent. In what follows, we denote by $L_Q(\theta)$ the loss minimized by a generic learning procedure for Q_θ, based on the Bellman operator, independently of whether it is regularized, uses double critics, etc. Similarly, we note $L_\pi(\theta)$ the loss minimized to yield a greedy policy π_θ, when applicable.

We denote by $M(Q, s, a)$ an attribution map for $Q(s, a)$, in the space of images $\mathcal{S}$. Vanilla grad [Simonyan et al., 2014] for instance will compute such a map under the form $M(Q, s, a) = \partial Q(s, a)/\partial s$, while guided backpropagation [Springenberg et al., 2015] will mask out negative gradients, yielding a different attribution map. We note $M_\rho(Q, s, a)$ the binarized value attribution map where $M_\rho(Q, s, a)_j = 1$ if attribution pixel $M(Q, s, a)_j$ belongs to the ρ-quantile of highest values for $M(Q, s, a)$, and 0 otherwise.

Figure 1: SGQN losses. The L_{SL} self-supervised loss trains f_θ so that $M_\theta(f_\theta(\tau(s)), a)$ predicts $M_\rho(Q_\theta \circ f_\theta, s, a)$. In turn, the L_C consistency loss pushes $Q_\theta \circ f_\theta$ to only depend on salient pixels.

The proposed method is built on a classical Q-network architecture. The value function is divided into 2 parts: an encoder $f_\theta : \mathcal{S} \to \mathcal{Z}$ and a Q-function $Q_\theta : \mathcal{Z} \times \mathcal{A} \to \mathbb{R}$ built on top of this encoder. We add a decoder function M_θ after the features encoder f_θ, such that $M_\theta(f_\theta(s), a)$ aims to predict the attribution map of $Q_\theta(f_\theta(s), a)$. Many algorithms require defining double critics [Fujimoto et al., 2018] or target networks f_ψ and Q_ψ which are often updated with an exponential moving average of θ [Polyak and Juditsky, 1992]. We omit them here for clarity, although their introduction in SGQN is straightforward. When needed, a policy head $\pi_\theta : \mathcal{Z} \to \mathcal{A}$ is built on top of the encoder f_θ to define the actor network. The backbone architecture and training process are summarized in Figure 1.

The SGQN training procedure involves two alternating phases: the critic update phase and the self-supervised learning auxiliary phase. The critic update follows the classical critic loss $L_Q(\theta)$, enhanced with a *consistency regularization objective* $L_C(\theta) = \mathbb{E}_{s,a}[[Q_\theta(f_\theta(s), a) - Q_\theta(s \odot M_\rho(Q_\theta \circ f_\theta, s, a), a)]^2]$, where $\odot$ denotes the Hadamard product. This loss function encourages the Q-network $Q_\theta \circ f_\theta$ to make its decision based in priority on the salient pixels in $M(Q, s, a)$, hence promoting consistency between the masked and original images. The new critic objective function is thus defined as $L_Q(\theta) + \lambda L_C(\theta)$. During the self-supervised learning phase, given a generic image augmentation function τ, the parameters of f_θ are updated so that $(f_\theta(\tau(s)), a)$ contains enough information to accurately reconstruct the attribution mask $M_\rho(Q_\theta, s, a)$. This defines a self-supervised learning objective function $L_{SL}(\theta) = \mathbb{E}_{s,a}[BCE(M_\theta(f_\theta(\tau(s)), a), M_\rho(Q_\theta, s, a)]$, where BCE is the binary cross entropy loss, which could be replaced by any other measure of discrepancy between attribution maps.

The interplay between these two phases acts as a virtuous circle. The consistency regularization loss, similar to that of Ismail et al. [2021], pushes the network to focus its decision on a selected set of pixels (hence relying on the assumption that initial saliency maps are reasonably good). This enhances the contrast between pixels in the gradient image, and thus yields sharp saliency maps, even before binarization. These maps serve as a target labels during the self-supervised learning phase; since they are less noisy than without the consistency loss, they provide a stronger incentive to encode the information of which pixels are important, within f_θ. In turn, as exemplified by Hansen and Wang [2021] and Grill et al. [2020], the features obtained by the self-supervised learning procedure tend to be insensitive to background, noise, or exogenous conditions, and provide features that are shared across observations. These features benefit from the better labels (less irrelevant pixels in the attribution map). Finally, this helps provide good pixel attributions that will be used in the minimization of the consistency loss during the critic phase.

Note that the thresholding operation performed to obtain M_ρ is not strictly necessary, either in the consistency loss or in the self-supervised learning one. Instead of a hard thresholding, one could turn to a normalization of the attribution map, such as a softmax for instance. Such a soft-attribution image remains fully compatible with SGQN. The choice to keep the thresholded ρ-quantile mask is motivated by the arguments of Ismail et al. [2021] who extensively study such variations and conclude to the benefits of this binarized mask. One could also remark that SGQN does not require to use the target network during the self-supervised learning phase, which contrasts with the choices of SODA or BYOL and makes the method somewhat more versatile.

(a) Training   (b) "*Video easy*" distribution shift   (c) "*Video hard*" distribution shift

Figure 2: Examples of training and testing environments

Algorithm 1 presents the pseudo-code of combining SGQN with SAC, yielding an SG-SAC algorithm. Note that, for the sake of simplicity, we write θ for the full set of network parameters, which are thus shared by the encoder, the Q-value head, the policy head, and the attribution reconstruction head.

Algorithm 1: Saliency-guided SAC (changes to SAC in blue)

Parameters: frequency of auxiliary updates N_{SL}, attribution quantile value ρ, learning rate α, data augmentation function τ.

for *each interaction time step* **do**

$\quad a, s' \sim \pi_\theta(\cdot \mid f_\theta(s)), \mathcal{P}(\cdot \mid s, a)$ `// Sample a transition`

$\quad \mathcal{B} \leftarrow \mathcal{B} \cup \{(s, a, \mathcal{R}(s, a), s')\}$ `// Add transition to replay buffer`

$\quad \{s_i, a_i, r(s_i, a_i), s'_i\}_{i \in [1,N]} \sim \mathcal{B}$ `// Sample a mini-batch of transitions`

$\quad \theta \leftarrow \theta - \alpha \nabla_\theta L_Q(\theta) + \lambda L_C(\theta)$ `// Critic update phase`

$\quad \theta \leftarrow \theta - \alpha \nabla_\theta L_\pi(\theta)$ `// Actor update`

$\quad$ Every N_{SL} steps: $\theta \leftarrow \theta - \alpha \nabla_\theta L_{SL}(\theta)$ `// Self-supervised learning`

Note: L_Q and L_π are as defined by Haarnoja et al. [2018], temperature update, double critics and target network updates are omitted here for clarity.

---

4 Experimental results and discussion

This section evaluates SGQN's training efficiency, generalization capabilities, and policy interpretability. It also discusses the different design choices made along the way. We compare our approach with current state-of-the-art methods for generalization in continuous actions RL (RAD [Laskin et al., 2020b], SODA [Hansen and Wang, 2021], SVEA [Hansen et al., 2021]) on five environments from the DMControl Generalization Benchmark (DMControl-GB) [Hansen and Wang, 2021]. The DMControl-GB presents a variety of vision-based continuous control tasks based on the Deepmind control suite. Agents are trained in a fixed background environment and evaluated under two challenging distribution shifts, consisting in replacing the training background with natural videos. Figure 2 illustrates the effects of both domain shifts. All the compared methods herein are variants of SAC, for which we use the same architecture for all agents. These methods all use data augmentation in one of their stages. Following the experimental protocol of the competing approaches, we used a random overlay augmentation [Hansen and Wang, 2021] with the Places365 dataset [Zhou et al., 2017] for all the methods except for RAD, for which we used a random crop, as it is reported as producing the best results [Laskin et al., 2020b]. We trained all agents for $500\,000$ steps using the vanilla training environment with no visual variation. Appendix A and B summarize all the hyperparameters, network architectures, and implementation choices used for this benchmark. Appendix C include extra experimental results.

SGQN improves value iteration in the training domain. We first compare the performance in the training domain, with no visual distractions, of SAC and SGQN, on five environments from the DMControl-GB (Figure 3). The SGQN agents outperform, by a considerable margin, the SAC agents both in terms of asymptotic performance and sample efficiency on 4 out of the 5 environments. In addition to obtaining better results, the variance of the agents trained with SGQN is also significantly lower than that of the agents trained with SAC, demonstrating that the enhancements employed in SGQN have a beneficial effect on the stability of the training.

SGQN improves generalization. We assess the zero-shot generalization ability of SGQN on the *video easy* and *video hard* benchmarks from the DMControl-GB. The easy version only replaces the background of the training image with a distracting image, while the hard version also replaces the

Figure 3: Comparison of SAC and SGQN training learning curves

Benchmark	Environment	SAC	RAD	SODA	SVEA	SGQN	Δ
Easy	Walker walk	245 ± 165	608 ± 92	771 ± 66	828 ± 66	$\mathbf{910 \pm 24}$	$\mathbf{+82(10\%)}$
	Walker stand	389 ± 131	879 ± 64	965 ± 7	966 ± 5	$\mathbf{955 \pm 9}$	$\mathbf{-11(1\%)}$
	Ball in cup	192 ± 157	363 ± 158	$939 \pm -$	908 ± 55	$\mathbf{950 \pm 24}$	$\mathbf{+11(1\%)}$
	Cartpole	474 ± 26	391 ± 66	678 ± 120	702 ± 80	$\mathbf{717 \pm 35}$	$\mathbf{+15(2\%)}$
	Finger spin	152 ± 8	334 ± 54	535 ± 52	537 ± 11	$\mathbf{609 \pm 61}$	$\mathbf{+72(13\%)}$
	Average	292 ± 157	515 ± 158	777 ± 10	785 ± 55	$\mathbf{828 \pm 24}$	$\mathbf{+(5\%)}$
Hard	Walker walk	122 ± 47	80 ± 10	312 ± 32	385 ± 63	$\mathbf{739 \pm 21}$	$\mathbf{+354(92\%)}$
	Walker stand	231 ± 57	229 ± 45	736 ± 132	747 ± 43	$\mathbf{851 \pm 24}$	$\mathbf{+104(14\%)}$
	Ball in cup	101 ± 37	98 ± 40	$381 \pm -$	498 ± 174	$\mathbf{782 \pm 57}$	$\mathbf{+284(57\%)}$
	Cartpole	153 ± 22	117 ± 22	339 ± 87	392 ± 37	$\mathbf{526 \pm 41}$	$\mathbf{+134(34\%)}$
	Finger spin	25 ± 6	15 ± 6	221 ± 48	174 ± 39	$\mathbf{540 \pm 53}$	$\mathbf{+319(144\%)}$
	Average	127 ± 37	108 ± 40	396 ± 163	437 ± 174	$\mathbf{688 \pm 57}$	$\mathbf{+(57\%)}$

Table 1: Performance on *video easy* and *video hard* testing levels. Δ = difference with second best.

ground and the shadows (Figure 2). We report the average sum of rewards after $500\,000$ training steps for the *video easy* benchmark in the top part of Table 1. Agents trained with SGQN outperform agents trained with other state-of-the-art methods on all tasks but one (where it is on par with other agents), thus demonstrating the generalization capabilities induced by the method. By removing the ground and shadows, the *video hard* benchmark causes a larger, and more confusing distributional shift and is, therefore, more challenging. The bottom part of Table 1 reports the performance of all methods on this benchmark. All the competitors of SGQN experience a radical decrease in their generalization performance. SGQN is significantly less impacted and outperforms all its competitors with an average margin over the second-best of 57% on all environments, and a gain range of 14 to 144% across environments. Figure 4 reports the evolution of each agent's score on the *video hard* environments, along training. If SODA and SVEA are performing well when the ground and shadow information is still present, removing it leads to a drastic drop in their performance. SGQN is less sensitive to this change, notably through the consistency loss, which encourages agents to make decisions based on the subsets of pixels they deem most interesting. Overall, the interplay of the two phases of SGQN seems to be key to a major leap forward in terms of generalization gap in difficult environments, setting a new reference state-of-the-art.

Figure 4: Performance on *video hard* testing levels.

SGQN yields sharp saliency maps. We use guided backpropagation to visually compare the SGQN agents' ability to discriminate the essential information with that of other agents. Figure 5 shows an example of the binarized attribution maps for all agents in a *video hard* state. While the other agents seem to be disturbed by background elements and retain some dependency on background pixels in their decision, the attributions of the agent trained with SGQN are precisely located on the important information, hence suggesting better generalization potential.

| (a) Observation | (b) SAC | (c) RAD | (d) SODA | (e) SVEA | (f) SGQN |

Figure 5: Example of attributions in *video hard* levels

SGQN is interpretable by design. In all our experiments, we trained the SGQN agents using guided
backpropagation. We emphasize that any other attribution method could be used instead. Some of
these methods are expensive and require several forward (or backward) passes within the network
(e.g., RISE [Petsiuk et al., 2018], or the work of Fel et al. [2021]) to yield attribution maps which
explain the agent's decision. In contrast, SGQN's auxiliary phase trains a predictor to estimate the
most important pixels according to the chosen attribution method. Therefore, this predictor is a
surrogate of the attribution method used during training. It allows identifying the essential image
features that condition the agent's decision in the same forward pass as the prediction of the action
itself, without incurring the cost of one or several costly additional backward or forward passes.
Figure 6 illustrates the proximity between the actual saliency map and the attribution surrogate model
M_θ. This makes SGQN both self-aware (of its own saliency maps) and intrinsically interpretable
from a human perspective, with no computational overhead at evaluation time.

| (a) Observation | (b) $M(Q_\theta, s, a)$ | (c) $s \odot M_\rho(Q_\theta, s, a)$ | (d) $M_\theta(s, a)$ |

Figure 6: True and surrogate saliency maps in a *video hard* level

Ablation study. SGQN relies on two enhancements of vanilla approximate value iteration: the
auxiliary self-supervised learning phase and the consistency regularization term in the critic's loss. We
perform an ablation study to assess their individual contribution and Table 2 reports the average sum
of rewards in the training domain and for zero-shot generalization in all environments. Individually,
each of these features greatly improves both training and zero-shot generalization performance on all
environments. The auxiliary self-supervised learning phase provides the most significant performance
gains over vanilla SAC. The average training performance on all environments of agents trained with
this auxiliary objective is more than 87% higher than that of agents trained with vanilla SAC. The
same applies to the performance in zero-shot generalization, which increases by more than 141% on
video easy and by more than 182% on *video hard* environments. One can note that agents trained
with our self-supervised learning objective also outperform SODA agents (Table 1) on 4 out of 5
video easy environments and on 3 out of 5 *video hard* environments. Recall that SODA relies on
the BYOL [Grill et al., 2020] self-supervised feature learning procedure, whose target labels differ
notably from those proposed herein. The reported performance, compared to that of SODA suggests
that attribution maps constitute a good labeling function that could be considered in the more general
context of self-supervised learning. To a slightly lesser extent, adding the consistency loss to SAC
also significantly improves its performance. The average score obtained improves by more than 49%
on the training domain and by 86% and 166% respectively on the *video easy* and *video hard* domains.
Similarly to the results obtained by Ismail et al. [2021] in supervised learning, the regularization
of the critic's loss with the consistency term sharpens the attribution maps obtained (Figure 7). In
SGQN, these fine-grained attributions provide higher quality labels to the auxiliary self-supervised
learning phase, thus yielding significant performance improvements in training (+94% on average,
range up to +242%), *video easy* generalization (+183% on average, range up to +399%), and *video
hard* generalization (+440% on average, range up to +1977%).

Environment	benchmark	SAC	SAC+Consistency	SAC+Self learning	SGQN
Walker walk	train	287 ± 165	$449 \pm 100 (+\mathbf{56}\%)$	$934 \pm 28 (+\mathbf{225}\%)$	$937 \pm 12 (+\mathbf{226}\%)$
	easy	245 ± 165	$423 \pm 96 (+\mathbf{73}\%)$	$844 \pm 53 (+\mathbf{244}\%)$	$910 \pm 24 (+\mathbf{271}\%)$
	hard	122 ± 47	$344 \pm 87 (+\mathbf{182}\%)$	$226 \pm 48 (+\mathbf{85}\%)$	$739 \pm 21 (+\mathbf{505}\%)$
Walker stand	train	467 ± 162	$857 \pm 120 (+\mathbf{84}\%)$	$957 \pm 11 (+\mathbf{105}\%)$	$960 \pm 9 (+\mathbf{106}\%)$
	easy	389 ± 131	$846 \pm 107 (+\mathbf{117}\%)$	$944 \pm 14 (+\mathbf{143}\%)$	$955 \pm 12 (+\mathbf{145}\%)$
	hard	231 ± 57	$696 \pm 150 (+\mathbf{201}\%)$	$769 \pm 32 (+\mathbf{233}\%)$	$851 \pm 24 (+\mathbf{268}\%)$
Ball in cup	train	284 ± 329	$755 \pm 261 (-\mathbf{8}\%)$	$967 \pm 1 (+\mathbf{240}\%)$	$971 \pm 7 (+\mathbf{242}\%)$
	easy	192 ± 157	$440 \pm 214 (+\mathbf{129}\%)$	$705 \pm 43 (+\mathbf{267}\%)$	$959 \pm 6 (+\mathbf{399}\%)$
	hard	101 ± 37	$190 \pm 63 (+\mathbf{88}\%)$	$203 \pm 122 (+\mathbf{100}\%)$	$778 \pm 75 (+\mathbf{670}\%)$
Cartpole	train	861 ± 9	$836 \pm 33 (-\mathbf{3}\%)$	$703 \pm 82 (-\mathbf{20}\%)$	$815 \pm 35 (-\mathbf{14}\%)$
	easy	477 ± 30	$661 \pm 112 (+\mathbf{39}\%)$	$534 \pm 54 (+\mathbf{12}\%)$	$716 \pm 35 (+\mathbf{50}\%)$
	hard	154 ± 25	$261 \pm 235 (+\mathbf{69}\%)$	$294 \pm 7 (+\mathbf{91}\%)$	$526 \pm 41 (+\mathbf{242}\%)$
Finger spin	train	309 ± 12	$392 \pm 128 (+\mathbf{26}\%)$	$571 \pm 10 (+\mathbf{85}\%)$	$618 \pm 56 (+\mathbf{100}\%)$
	easy	157 ± 8	$343 \pm 88 (+\mathbf{92}\%)$	$468 \pm 29 (+\mathbf{281}\%)$	$609 \pm 61 (+\mathbf{287}\%)$
	hard	26 ± 6	$201 \pm 74 (+\mathbf{673}\%)$	$209 \pm 59 (+\mathbf{681}\%)$	$540 \pm 53 (+\mathbf{1977}\%)$
Average	train	442 ± 283	$658 \pm 246 (+\mathbf{49}\%)$	$826 \pm 170 (+\mathbf{87}\%)$	$860 \pm 137 (+\mathbf{94}\%)$
	easy	292 ± 164	$542 \pm 221 (+\mathbf{86}\%)$	$704 \pm 199 (+\mathbf{141}\%)$	$829 \pm 146 (+\mathbf{183}\%)$
	hard	127 ± 77	$338 \pm 201 (+\mathbf{166}\%)$	$359 \pm 258 (+\mathbf{182}\%)$	$686 \pm 139 (+\mathbf{440}\%)$

Table 2: Ablation study. Percentages indicate variations compared to vanilla SAC.

(a) Observation   (b) Without consistency loss   (c) With consistency loss

Figure 7: Comparison of SGQN attributions with and without consistency loss

5 Conclusion

The ability to filter out confounding variables is a long-standing goal in machine learning. For visual reinforcement learning, it is a pre-requisite for real-world deployment of learned policies, since we want to avoid at all costs situations where an agent makes the wrong decision due to distracting visual factors. In this work, we introduced saliency-guided Q-networks (SGQN), a generic method for visual reinforcement learning, that is compatible with any value function learning method. SGQN relies on the positive interaction of two core mecanisms of self-supervised learning and attribution consistency that jointly encourage the RL agent to be self-aware of the decisive factors that condition its value function. We implement an SGQN agent based on the soft actor-critic algorithm, and evaluate it on the DMControl generalization benchmark. This agent displays a dramatically more efficient behavior than vanilla SAC on the various environments it is trained on. Most importantly, the policy it learns closes the generalization gap on environments that include confusing and distracting visual features, setting a new reference in terms of generalization performance. Since they rely on self-awareness of important pixels, SGQN agents are also very interpretable, in the sense that they provide a prediction of their own saliency maps, with no computational overhead.

The introduction of SGQN is an exciting milestone in RL generalization, and we wish to conclude this contribution by highlighting some limitations and perspectives for research that we believe are beneficial to the community. Attribution maps seem to be an efficient proxy for encouraging causal relationships within policies, but they are strongly grounded in an anthropomorphic point of view of what a visual policy should be. Extending their definition to more abstract notions of attribution is still a challenge and begs for important contributions, both theoretical and algorithmic. Similarly, such attribution maps appear to be relevant self-supervised learning targets, in order to learn good features for RL agents. Exploring whether this still holds for different tasks than RL is an open question. It is likely that one could design variations of SGQN that perform better than SG-SAC. The extension of SGQN agents to discrete action agents (e.g. DQN), or policy gradient methods (e.g. PPO) is a promising perspective in itself. Although generic and grounded in sound algorithmic mechanisms, the losses introduced by SGQN lack a formal connection to some measure of the generalization gap. Such a connection could provide insights to better self-aware, explainable agents with improved generalization capabilities. Finally, using SGQN as a building brick, among all those required to bridge the gap between simulation and real-world applications, is an exciting perspective.

References

Rishabh Agarwal, Marlos C Machado, Pablo Samuel Castro, and Marc G Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. In *International Conference on Learning Representations*, 2020.

Akanksha Atrey, Kaleigh Clary, and David Jensen. Exploratory not explanatory: Counterfactual analysis of saliency maps for deep reinforcement learning. In *International Conference on Learning Representations*, 2020.

Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3:397–422, 2002.

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

David Bertoin and Emmanuel Rachelson. Local feature swapping for generalization in reinforcement learning. In *International Conference on Learning Representations*, 2022.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Aditya Chattopadhay, Anirban Sarkar, Prantik Howlader, and Vineeth N Balasubramanian. Grad-cam++: Generalized gradient-based visual explanations for deep convolutional networks. In *IEEE winter conference on applications of computer vision (WACV)*, pages 839–847, 2018.

Karl Cobbe, Oleg Klimov, Chris Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. In *International Conference on Machine Learning*, pages 1282–1289, 2019.

Karl Cobbe, Chris Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *International conference on machine learning*, pages 2048–2056, 2020.

Jiameng Fan and Wenchao Li. Dribo: Robust deep reinforcement learning via multi-view information bottleneck. *arXiv preprint arXiv:2102.13268*, 2021.

Linxi Fan, Guanzhi Wang, De-An Huang, Zhiding Yu, Li Fei-Fei, Yuke Zhu, and Animashree Anandkumar. Secant: Self-expert cloning for zero-shot generalization of visual policies. In *International Conference on Machine Learning*, 2021.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. In *NeurIPS Deep Reinforcement Learning Workshop*, 2018.

Thomas Fel, Rémi Cadène, Mathieu Chalvidal, Matthieu Cord, David Vigouroux, and Thomas Serre. Look at the variance! efficient black-box explanations with sobol-based sensitivity analysis. *Advances in Neural Information Processing Systems*, 34, 2021.

Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International conference on machine learning*, pages 1587–1596, 2018.

Matthieu Geist, Bruno Scherrer, and Olivier Pietquin. A theory of regularized markov decision processes. In *International Conference on Machine Learning*, pages 2160–2169, 2019.

Samuel Greydanus, Anurag Koul, Jonathan Dodge, and Alan Fern. Visualizing and understanding atari agents. In *International conference on machine learning*, pages 1792–1801, 2018.

Jake Grigsby and Yanjun Qi. Measuring visual generalization in continuous control from pixels. *arXiv preprint arXiv:2010.06740*, 2020.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Valko Michal. Bootstrap your own latent-a new approach to self-supervised learning. *Advances in Neural Information Processing Systems*, 33: 21271–21284, 2020.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870, 2018.

Nicklas Hansen and Xiaolong Wang. Generalization in reinforcement learning by soft data augmentation. In *International Conference on Robotics and Automation*, 2021.

Nicklas Hansen, Hao Su, and Xiaolong Wang. Stabilizing deep q-learning with convnets and vision transformers under data augmentation. In *Conference on Neural Information Processing Systems*, 2021.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2017a.

Irina Higgins, Arka Pal, Andrei Rusu, Loic Matthey, Christopher Burgess, Alexander Pritzel, Matthew Botvinick, Charles Blundell, and Alexander Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. In *International Conference on Machine Learning*, pages 1480–1490, 2017b.

Maximilian Igl, Kamil Ciosek, Yingzhen Li, Sebastian Tschiatschek, Cheng Zhang, Sam Devlin, and Katja Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. *Advances in Neural Information Processing Systems*, 32:13978–13990, 2019.

Aya Abdelsalam Ismail, Hector Corrada Bravo, and Soheil Feizi. Improving deep learning interpretability by saliency guided training. *Advances in Neural Information Processing Systems*, 34, 2021.

Minqi Jiang, Edward Grefenstette, and Tim Rocktäschel. Prioritized level replay. In *International Conference on Machine Learning*, pages 4940–4950, 2021.

Arthur Juliani, Ahmed Khalifa, Vincent-Pierre Berges, Jonathan Harper, Hunter Henry, Adam Crespi, Julian Togelius, and Danny Lange. Obstacle tower: A generalization challenge in vision. *Control, and Planning. arXiv e-prints*, 2019.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, pages 5639–5650, 2020a.

Misha Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *Advances in Neural Information Processing Systems*, 33, 2020b.

Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. In *International Conference on Learning Representations*, 2020.

Marlos C. Machado, Marc G. Bellemare, Erik Talvitie, Joel Veness, Matthew J. Hausknecht, and Michael Bowling. Revisiting the arcade learning environment: Evaluation protocols and open problems for general agents. *Journal of Artificial Intelligence Research*, 61:523–562, 2018.

Bogdan Mazoure, Ahmed M Ahmed, R Devon Hjelm, Andrey Kolobov, and Patrick MacAlpine. Cross-trajectory representation learning for zero-shot generalization in RL. In *International Conference on Learning Representations*, 2022.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Sajad Mousavi, Michael Schukat, Enda Howley, Ali Borji, and Nasser Mozayani. Learning to predict where to look in interactive environments using deep recurrent q-learning. *arXiv preprint arXiv:1612.05753*, 2016.

Charles Packer, Katelyn Gao, Jernej Kos, Philipp Krähenbühl, Vladlen Koltun, and Dawn Song. Assessing generalization in deep reinforcement learning. *arXiv preprint arXiv:1810.12282*, 2018.

Vitali Petsiuk, Abir Das, and Kate Saenko. RISE: Randomized input sampling for explanation of black-box models. In *29th British Machine Vision Conference*, 2018.

Boris T Polyak and Anatoli B Juditsky. Acceleration of stochastic approximation by averaging. *SIAM Journal on Control and Optimization*, 30(4):838–855, 1992.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Roberta Raileanu and Rob Fergus. Decoupling value and policy for generalization in reinforcement learning. In *International Conference on Machine Learning*, pages 8787–8798, 2021.

Roberta Raileanu, Maxwell Goldstein, Denis Yarats, Ilya Kostrikov, and Rob Fergus. Automatic data augmentation for generalization in reinforcement learning. *Advances in Neural Information Processing Systems*, 34, 2021.

Matthias Rosynski, Frank Kirchner, and Matias Valdenegro-Toro. Are gradient-based saliency maps useful in deep reinforcement learning? In *"I Can't Believe It's Not Better!" NeurIPS workshop*, 2020.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pages 618–626, 2017.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. In *Workshop at International Conference on Learning Representations*, 2014.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. Smoothgrad: removing noise by adding noise. *arXiv preprint arXiv:1706.03825*, 2017.

Xingyou Song, Yiding Jiang, Stephen Tu, Yilun Du, and Behnam Neyshabur. Observational overfitting in reinforcement learning. In *International Conference on Learning Representations*, 2019.

J Springenberg, Alexey Dosovitskiy, Thomas Brox, and M Riedmiller. Striving for simplicity: The all convolutional net. In *ICLR (workshop track)*, 2015.

Austin Stone, Oscar Ramirez, Kurt Konolige, and Rico Jonschkowski. The distracting control suite–a challenging benchmark for reinforcement learning from pixels. *arXiv preprint arXiv:2101.02722*, 2021.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pages 23–30. IEEE, 2017.

Kaixin Wang, Bingyi Kang, Jie Shao, and Jiashi Feng. Improving generalization in reinforcement learning with mixture regularization. In *NeurIPS*, 2020.

Xudong Wang, Long Lian, and Stella X Yu. Unsupervised visual attention and invariance for reinforcement learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6677–6687, 2021.

Shimon Whiteson, Brian Tanner, Matthew E Taylor, and Peter Stone. Protecting against evaluation overfitting in empirical reinforcement learning. In *IEEE symposium on adaptive dynamic programming and reinforcement learning (ADPRL)*, pages 120–127, 2011.

Denis Yarats, Ilya Kostrikov, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*, 2020.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *arXiv preprint arXiv:1806.07937*, 2018a.

Amy Zhang, Yuxin Wu, and Joelle Pineau. Natural environment benchmarks for reinforcement learning. *arXiv preprint arXiv:1811.06032*, 2018b.

Amy Zhang, Rowan Thomas McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. In *International Conference on Learning Representations*, 2020.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018c.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018d.

Chenyang Zhao, Olivier Sigaud, Freek Stulp, and Timothy M Hospedales. Investigating generalisation in continuous deep reinforcement learning. *arXiv preprint arXiv:1902.07015*, 2019.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

Kaiyang Zhou, Yongxin Yang, Yu Qiao, and Tao Xiang. Domain generalization with mixstyle. In *International Conference on Learning Representations*, 2020.