Private and Non-private Uniformity Testing for Ranking Data

Abstract

We study the problem of uniformity testing for statistical data that consists of rankings over m items where the alternative class is restricted to Mallows models with single parameter. Testing ranking data is challenging because of the size of the large domain that is factorial in m, therefore the tester needs to take advantage of some structure of the alternative class. We show that uniform distribution can be distinguished from Mallows model with $O(m^{-1/2})$ samples based on simple pairwise statistics, which allows us to test uniformity using only two samples, if m is large enough. We also consider uniformity testing with central and locally differential private (DP) constraints. We present a central DP algorithm that requires $O\left(\max\{1/\epsilon_0, 1/\sqrt{m}\}\right)$ where ϵ_0 is the privacy budget parameter. Interestingly, our uniformity testing algorithm is straightforward to apply in the local DP scenario by its nature, since it works with binary statistics that is extracted from the ranking data. We carry out large-scale experiments, including $m = 10000$, to show that these testing algorithms scales very gracefully with the number of items.

1 Introduction

Testing whether the data conforms with a model is a fundamental problem in data analysis with large number of applications in machine learning and data science. A special case of testing is the uniformity testing, i.e. to distinguish between the case that an unknown distribution which is accessible via samples, is uniform versus ϵ-far from uniform. Uniformity testing of discrete distribution has long history with several applications, and it is well-understood [25, 11, 10, 3] as well as under privacy constraint [4, 1, 2].

In this paper, we assume that the statistical data consists of rankings over m items. The testing problem which we will study is to decide whether the data is generated from the uniform distribution over rankings, i.e. the probability of observing any ranking is $1/m!$, or from a distribution that is ϵ far from the uniform distribution in terms of total variation distance. In general, this testing problem cannot be tackled based on polynomial sample complexity, because the domain size is $m!$ for ranking data. Therefore we make further assumption on the alternative hypothesis class. We assume that the alternative hypothesis class is the single parameter Mallows model which is introduced by [23] and also known as the exponential family on rankings. This model class is widely used in ranking and machine learning. The model has two parameters, the *central ranking* $\pi_0 \in \mathcal{S}_m$ and the *spread parameter* $\phi \in [0, 1]$. Based on these, the probability of observing a ranking $\pi \in \mathcal{S}_m$ is proportional to $\phi^{d(\pi, \pi_0)}$, where d is a ranking distance, such as the number of discordant pairs, a.k.a Kendall's tau distance. There are many applications of the Mallows model in Machine Learning, to name a few, label ranking [22], online learning [8], recommendation systems [26, 21], clustering [24]. We will propose two tests to tackle uniformity testing with Mallows model as alternative class of ranking

distributions: one of these tests works with two samples when m is large enough, and a more general one which has $O(1/\sqrt{m})$ sample complexity and works with arbitrary m.

There are several applications where the data to be analyzed contains sensitive information. However, the data owner is willing to release some results of analysis based on the data, without revealing information of the individuals. It may thus be of importance to guarantee that working with sensitive data needed to test a statistical hypothesis protects sensitive information about the individual records in the dataset. Differential privacy (DP) is one of the most commonly used privacy preserving framework [14, 16] which has been adopted by several companies including Google [17], and Apple [12]. Differential privacy requires that the output of an algorithm has to be statistically close on two similar datasets D and D' that differ in the value of one element which a ranking in our case. We consider the two most common version of DP: central and local DP. In the central model, a trusted curator stores the database, and she runs the algorithm which has DP guaranty to analyze the sensitive data and then the output of the analysis, i.e. accept or reject in case of hypothesis testing, is released to the public [15]. Several alternatives to the central model have been proposed that relax the requirement that the users trust the curator to store their private data, for example local DP. In the local model, each user adds noise to her own data and responds to the analyst directly [18]. Interestingly, our uniformity testing algorithms can be easily applied in the LDP setting. We can summarize our main results as follows:

- We devise a uniformity test which works based on two samples when m is large enough (Subsection 4.1)
- We introduce an uniformity test which is able to test uniformity with arbitrary m and its sample complexity is of order $m^{-1/2}$ (Subsection 4.2)
- In the central DP setting, one can apply a simple reduction approach which consists of drawing $\lceil 1/\epsilon_0 \rceil$ batches of data, and run a non-DP algorithm on one of the batch selected uniformly at random. This approach works well when m large enough, since the uniformity testing can be solved based on two samples. However, we devise a uniformity test for the central DP setting which has better sample complexity than the reduction approach with data batches for small and medium m. This result is presented in Section 5.
- We devise a local DP algorithm as an easy extension of our non-private algorithm, in Sec. 6.
- We demonstrate the versatility of our algorithm running with large m, including $m = 10000$ on synthetic data, and we show that for large m very small deviation form the uniform can be detected with high confidence based on two samples in Section 7.

2 Related Work

Testing uniformity is one of the most fundamental problem in computer science. Goldreich and Ron [20] considered first uniformity testing problem as a property testing, however with L2 distance. Paninski [25] came up with a coincidence-based approach that used total variation distance with a sample complexity $O(\sqrt{d}/\epsilon^2)$ where d is the domain size, and it was shown to be optimal by with a restriction that $\epsilon \in \Omega(d^{-1/4})$. The test statistic used by this optimal test is based on number of bins into which just one sample has fallen. In principle, this test can be applied to ranking data, since the test statistic is easy to compute. Nevertheless, the lower bound of this test, which is $\Omega(\sqrt{d}/\epsilon^2)$, suggests that it is not the proper choice of method even for ranking data with small m, since $d = m!$. The result of Paninski [25] was strengthen further by several authors including [11, 10, 3] so as the lower bound does work for general ϵ and matching algorithms are also provided. The plug-in based tests, for example [10], do estimate the distribution empirically and then it makes a decision by thresholding the total variation distance between the uniform distribution and the empirical estimate. Surprisingly, this test is optimal for all $\epsilon, \delta > 0$. To adapt this test to our setup is out of question since the test statistic which is the total variation distance is already challenging to compute for ranking data. Therefore, one needs to come up with a uniformity test that takes advantage of the structure of the alternative hypothesis.

Testing with differential privacy has a solid literature as well. Jayadev Acharya and his colleagues studied uniformity testing with privacy constraint in depth. In [4], the central DP model is analysed and shown that it can be tackled with $\Theta\left(\frac{\sqrt{d}}{\epsilon^2 \epsilon_0} + \frac{\sqrt{d}}{\epsilon \sqrt{\epsilon_0}} + \frac{d^{1/3}}{\epsilon^{4/3} \epsilon_0^{2/3}} + \frac{1}{\epsilon \epsilon_0}\right)$ samples where ϵ_0 is the privacy budget parameter. Local private uniformity test is analyzed in [1] and had found that it can

89 be tackled with $\Theta(k/(\epsilon \cdot \epsilon_0)^2)$ samples. In a recent work [2], uniformity testing in local differential
90 private setting was analysed with a special attention to the impact of the public randomness.

3 Ranking model, Testing, Privacy

3.1 Single Parameter Mallows Model

93 The Mallows model or, more specifically, Mallows ϕ-distribution is a parametrized, distance-based
94 probability distribution that belongs to the family of exponential distributions $\mathcal{R} = \{\mathcal{M}_{\phi,\pi} \mid \phi \in$
95 $[0,1], \pi \in \mathcal{S}_m\}$ with probability mass function $p_{\phi,\pi_0}(\pi) = \phi^{d(\pi,\pi_0)}/Z(\phi,\pi_0)$ where ϕ and π_0 are
96 the parameters of the model: $\pi_0 \in \mathcal{S}_m$ is the location parameter also called center ranking and
97 $\phi \in [0,1]$ the spread parameter. Moreover, $d(\cdot,\cdot)$ is a distance metric on permutations, which for
98 our paper will be the Kendall tau distance, that is, the number of discordant item pairs $d_K(\pi,\pi') =$
99 $\sum_{1 \leq i < j \leq m} \mathbb{I}\{(\pi(i) - \pi(j))(\pi'(i) - \pi'(j)) < 0\}$. The normalization factor in the definition of the
100 model is equal to $Z(\phi,\pi_0) = \sum_{\pi \in S_n} p_{\phi,\pi_0}(\pi)$. When the distance metric d is the Kendall tau
101 distance we have the identity $Z(\phi,\pi_0) = Z(\phi) = \prod_{i=1}^{m-1} \sum_{j=0}^{i} \phi^j$.

3.2 Testing and Uniformity Testing

103 We assume a parametric family of ranking distribution $\mathcal{R} = \{\mathcal{M}_\theta | \theta \in \Omega\}$ where Ω denotes the set of
104 parameters. The observation consists of n rankings $\mathcal{D}_n = \{\pi_1, \ldots, \pi_n\}$ from a ranking distribution
105 $\mathcal{M}$. The null hypothesis is $H_0 : \mathcal{M} \in \mathcal{R}_0$ where $\mathcal{R}_0 \subset \mathcal{R}$. As an alternative hypothesis, we consider
106 $H_1 : \mathcal{M} \in \mathcal{R}_1 (\subset \mathcal{R})$ such that $\mathcal{R}_0 \cap \mathcal{R}_1 = \emptyset$. Then the test is a function $f : \mathbb{S}_M^n \mapsto \{0,1\}$ where 0
107 corresponds to the acceptance, and 1 to the rejection. The input of the *tester* or *testing algorithm* is a
108 tolerance parameter $\epsilon > 0$ and significance parameter $\delta \in (0,1)$, and we assume that the tester has
109 sample access of the unknown distribution $\mathcal{M} \in \mathcal{R}$. By definition, an (ϵ,δ) testing algorithm outputs
110 a sample size n and a test function $f : \mathbb{S}_M^n \mapsto \{0,1\}$ such that, generating $\mathcal{D}_n$ from $\mathcal{M}$, we have the
111 following guaranties for f:

    1. if the null hypothesis H_0 is true, then it outputs reject ($f(\mathcal{D}_n) = 1$) with probability at most
       δ, i.e. $\mathbb{E}[f(\mathcal{D}_n)] \leq \delta$
    2. if $\mathcal{M} \in \mathcal{R}_1$ such that $d_{\text{TV}}(\mathcal{M},\mathcal{R}_0) > \epsilon$, then it outputs reject ($f(\mathcal{D}_n) = 1$) with probability
       at least $1 - \delta$ where $d_{\text{TV}}(\mathcal{M},\mathcal{R}_i) = \inf_{\mathcal{M}' \in \mathcal{R}_i} d_{\text{TV}}(\mathcal{M},\mathcal{M}')$

116 The testing problem at hand is called *uniformity testing*, when the null hypothesis is *simple* and
117 consists of only the uniform distribution over the domain $\mathbb{S}_m$. More concretely, in this study, we
118 assume that the null hypothesis is the uniform model, which is itself a Mallows model with $\phi = 1$,
119 thus $H_0 : \mathcal{M} \in \mathcal{R}_0 = \{\mathcal{M}_{1,\pi_0}\}$. The alternative hypothesis class contains those Mallows models that
120 are ϵ-far from the uniform distribution, i.e. $H_1 : \mathcal{M} \in \mathcal{R}_1 = \{\mathcal{M}_{\phi,\pi} : d_{TV}(\mathcal{M}_{1,\pi_0}, \mathcal{M}_{\phi,\pi}) > \epsilon\}$.

3.3 Differential Privacy

122 We will consider the uniformity testing problem under also privacy constraint. We will work with two
123 different privacy notions: central and local differential privacy. In case of central differential privacy
124 (CDP), the data is gathered at a so-called *curator* who is trusted, and the curator runs the tester which
125 is required to output a response that is not too sensitive to small changes in the input. Small changes
126 can be defined in many different ways for ranking data. We assume that the granularity of the data is
127 whole rankings. With this in hand, we can define the notion of CDP as follows.

Definition 1 (Central DP Property.)**.** *A randomized algorithm $\mathcal{A}$ with domain $\mathcal{S}_m^n$ is (ϵ_0,δ_0)-*
differential private if for all $S \subset Range(\mathcal{A})$ and for all pairs of inputs $\mathcal{D} = \{\pi_1, \ldots, \pi_n\}$ and
$\mathcal{D}'$ that differs from $\mathcal{D}$ in a single ranking, it holds that

$$\mathbf{P}(\mathcal{A}(\mathcal{D}) \in S) \leq e^{\epsilon_0} \mathbf{P}(\mathcal{A}(\mathcal{D}') \in S) + \delta_0$$

131 *If $\delta = 0$, the guarantee is called pure differential privacy.*

132 We will also work with a more appealing privacy notion which is often called locally differential
133 privacy (LDP). LDP is a stronger privacy guaranty than CDP in a sense that the data is required to be
134 privatized before the tester can observe it. More detailed, the data is assumed to be distributed among

peers and the peers add noise to the data which noise can be modelled as a conditional distribution, a.k.a. mechanism, $W(\mathbf{z}|\pi)$ for some output space $\mathbf{z} \in \mathcal{Z}$. The tester only observers the privatized data $(\mathbf{z}_1, \ldots, \mathbf{z}_k)$, so in this case it has no access to the original data as it is to be the case in CDP. The notion of LDP therefore can be formalized as a condition on $W(.|.)$.

Definition 2 (Locally differentially private.). *A mechanism* $W : \mathcal{S}_m \times \mathcal{Z} \to (0,1]$ *is* ϵ_0-*locally differentially private if* W *satisfies*

$$\max_{\mathbf{z} \in \mathcal{Z}} \max_{\pi, \pi' \in \mathcal{S}_m} \log \frac{W(\mathbf{z}|\pi)}{W(\mathbf{z}|\pi')} \leq \epsilon_0$$

We assume that each peer has the same mechanism, however there are several setup which assumes that the mechanism can be different for different peers. If public randomness is used by the tester, then the LDP guaranty is extended so as the worst-case log likelihood is computed over the domain of the public random process.

Definition 3 (Locally differentially private with public randomness). *A set of mechanisms* $W_u :$ $\mathcal{S}_m \times \mathcal{Z} \to (0,1]$ *indexed by* U *which is the domain of the public random process, is* ϵ_0-*locally differentially private if it holds that*

$$\max_{u \in U} \max_{\mathbf{z} \in \mathcal{Z}} \max_{\pi, \pi' \in \mathcal{S}_m} \log \frac{W_u(\mathbf{z}|\pi)}{W_u(\mathbf{z}|\pi')} \leq \epsilon_0 \ .$$

4 Non-Private Uniformity Testing

4.1 Testing Uniformity of Mallows Models with Two Samples

First we present a simple algorithm which draws two samples π_1 and π_2 and applies only if ϕ_ϵ is bounded away from 1 by $\Omega(1/m)$. The algorithm computes the Kendall tau distance of π_1 and π_2. Under the null hypothesis, $d_K(\pi_1, \pi_2) \geq m(m-1)/4 - O(\sqrt{m^3 \ln(1/\delta)})$, with probability at least $1 - \delta$, because the distribution is uniform. Under the alternative hypothesis, $d_K(\pi_1, \pi_2) \leq 2\phi_\epsilon m/(1 - \phi_\epsilon) + O(\sqrt{m^3 \ln(1/\delta)})$, with probability at least $1 - \delta$, because the distribution is concentrated around some central ranking. We shall refer to this algorithm as 2SAMP and it is defined in Algorithm 1. We show that if $\phi_\epsilon \leq 1 - \Omega(1/m)$, we can distinguish between the two cases by sufficiently large confidence.

Theorem 4. *For all* $\delta > 0$, *if* $\phi_\epsilon \leq 1 - \frac{8}{m+7-\sqrt{12 \ln(2/\delta)m}}$, *then Algorithm* 2SAMP, *defined in Algorithm 1, uses 2 samples and is an* (ϵ, δ)-*uniformity test of Mallows models.*

The proof is deferred to Appendix A. An alternative way of interpreting the guarantee presented above is that for all m and ϕ_ϵ, with $m > \frac{9}{1-\phi_\epsilon} - 7$, Algorithm 2SAMP is a (ϵ, δ)-test for uniformity with significance δ and power under an alternative model with spread parameter ϕ at least $1 - 2e^{-(m+7-\frac{9}{1-\phi_\epsilon})^2/(12m)}$. We should also emphasize that we cannot test uniformity with less than 2 samples, even for very large values of ϵ, since it is impossible to tell whether a single sample is uniformly distributed or not.

Algorithm 1 2SAMP: Uniformity Test with Two Samples

1: **Input:** significance $\delta > 0$, tolerance $\epsilon > 0$
2: Fix any $\pi_0 \in S_m$ and let $\phi_\epsilon = \sup_{\phi \in [0,1]} \{d_{TV}(\mathcal{M}_{1,\pi_0}, \mathcal{M}_{\phi,\pi_0}) > \epsilon\}$
3: **if** $\phi_\epsilon > 1 - \frac{8}{m+7-\sqrt{12 \ln(2/\delta)m}}$ **then**
4:      Output $\perp$ $\triangleright$ ϕ_ϵ too close to 1
5: Take 2 samples which are denoted by $\pi_1, \pi_2 \in S_m$
6: **If** $d_K(\pi_1, \pi_2) > \frac{m(m-1)}{4} - \sqrt{\frac{m^3 \ln(1/\delta)}{12}}$ **Then** Accept **Else** Reject

---

4.2 General Uniformity Testing Algorithm

Algorithm 2SAMP works only when $\phi_\epsilon \leq 1 - \Omega(1/m)$, or equivalently, assuming a fixed ϕ_ϵ, when m is large enough. Hence, we present Algorithm 2, which tests uniformity for arbitrary ϕ_ϵ

169 and m. The idea is to consider the relative positions of $m/2$ disjoint random pairs of items in

170 $k = \Theta\left(\frac{1}{\mu^2}\sqrt{\frac{\ln(1/\delta)}{m}}\right)$ samples, where $\mu = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}}$. Under the alternative hypothesis H_1 with

171 any fixed central ranking π^*, for any pair of items i and j, with $\pi^*(j) = \pi^*(i) \geq m/8$, μ is a

172 lower bound on the bias towards observing i before j in a random ranking from H_1 (if m is large

173 enough, a random item pairing results in $m_1 \approx m/8$ such item pairs, with high probability). We

174 define the random variables $X_{i(i+1)}^\ell$ to be 1, if i precedes $i+1$ in sample π_ℓ, and -1, otherwise.

175 $Y_{i(i+1)} = \left(\frac{1}{\sqrt{k}}\sum_{\ell=1}^k X_{i(i+1)}^\ell\right)^2$ accounts for the deviation of the pair i and $i+1$ from uniformity.

176 Under the null hypothesis, the expectation and the variance of $Y_{i(i+1)}$ are $O(1)$. Under the alternative

177 hypothesis, $\mathbb{E}[Y_{i(i+1)}] = \Omega(k\mu^2)$ and $\mathbb{V}[Y_{i(i+1)}] = O(k\mu^2)$. Moreover, the random variables

178 $Y_{12}, Y_{34}, \cdots, Y_{(m-1)m}$ are mutually independent, because they concern the relative positions of

179 disjoint item pairs in the samples. Therefore, $Y = Y_{12} + Y_{34} + \cdots + Y_{(m-1)m}$ should be $O(m)$,

180 under the null hypothesis, and $\Omega(mk\mu^2)$, under the alternative hypothesis. The following is proven

181 in Appendix B and shows that we can distinguish between the two cases with adequate confidence.

Algorithm 2 Uniformity Test (UNIF)

1: **Input:** significance $\delta > 0$, tolerance $\epsilon > 0$

2: Let $\pi_0 \in S_m$ be chosen uniformly at random and renumber the items so that $\pi_0 = (1, \ldots, m)$

3: Let $\phi_\epsilon = \sup_{\phi \in [0,1]}\{d_{TV}(\mathcal{M}_{1,\pi_0}, \mathcal{M}_{\phi,\pi_0}) > \epsilon\}$ $\triangleright$ ϕ_ϵ does not depend on π_0

4: Let $\mu = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}}$ and $m_1 = m/8 - \sqrt{m\ln(2/\delta)/16}$.

5: Take $k = 1 + \left\lceil \frac{1}{\mu^2}\left(\frac{12m\ln(2/\delta)}{m_1^2} + 10\sqrt{\frac{m\ln(2/\delta)}{m_1^2}}\right)\right\rceil$ samples $\mathcal{D}_k$.

6: Let $\pi_1, \ldots, \pi_k \in S_m$ denote the samples

7: Let $X_{i(i+1)}^\ell = 1$, if $i \succ_{\pi_\ell} i+1$, and -1 otherwise.

8: Let $Y_{i(i+1)} = \left(\frac{1}{\sqrt{k}}\sum_{\ell=1}^k X_{i(i+1)}^\ell\right)^2$ for all item pairs $i(i+1)$

9: Let $Y = Y_{12} + Y_{34} + \cdots + Y_{(m-1)m}$

10: **If** $Y < m/2 + 2\sqrt{m\ln(1/\delta)}$ **Then** Accept **Else** Reject

---

182 **Theorem 5.** *For all $\delta, \epsilon > 0$, Algorithm 2 with $k = \Theta\left(\frac{1}{\mu^2}\sqrt{\frac{\ln(1/\delta)}{m}}\right)$ samples, where $\mu = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}}$,*

183 *is an (ϵ, δ)-finite confidence uniformity test of Mallows models.*

184 Algorithm 2 exploits a tradeoff between the bias μ towards the right order of i and $i+1$ and the

185 values of ϕ_ϵ and m. If m is so small that $m_1 = m/8 - \sqrt{m\ln(2/\delta)/16}$ becomes much smaller than

186 m, the gain in the sample complexity due to raising ϕ_ϵ to $m/8$ in $1/\mu^2$ may be counterbalanced

187 by the increase in sample complexity due to m/m_1^2. Then, we can apply the same analysis with

188 $\mu' = \frac{1-\phi_\epsilon}{1+\phi_\epsilon}$, essentially regarding all $i(i+1)$ pairs as consisting of consecutive elements in π_0. Then,

189 under the alternative hypothesis, $\mathbb{E}[Y] = m(1 + (k-1)\mu'^2)/2$, which gives a sample complexity of

$$k = 1 + \left\lceil \frac{(1+\phi_\epsilon)^2}{(1-\phi_\epsilon)^2}\left(\frac{48\ln(1/\delta)}{m} + 16\sqrt{\frac{\ln(1/\delta)}{m}}\right)\right\rceil$$

190 for Algorithm 2. More generally, in the proof of Theorem 5, we can optimize the sample complexity

191 by trading off the exponent of ϕ_ϵ in μ against the size of m_1, for specific values of ϕ_ϵ and m.

5 Central DP uniformity test

193 The most natural approach to make a testing algorithm differentially private is to add Laplace noise to

194 the test statistic. The variance of the noise should be proportional to the sensitivity of the test statistic,

195 which ensures that small change in the input data does not change drastically the output of the tester.

196 This intuition is formalized in [16, Theorem 3.6]. Accordingly, one can add Laplace noise to the test

197 statistic Y which is computed in line 9 of Algorithm 2. What remains is to compute the sensitivity

198 of Y with respect to the input. Assume that we are given two datasets $\mathcal{D}_k$ and $\mathcal{D}_k'$ that consist of k

rankings and differ from each other in one ranking. Then, the sensitivity of the test statistic computed for $\mathcal{D}_k$ and $\mathcal{D}'_k$ is $|Y(\mathcal{D}_k) - Y(\mathcal{D}'_k)| \leq 2m$. This calculation is presented in Claim 10 in the Appendix. Therefore, if we add a Laplace noise $Z \sim \mathbf{Lap}\,(2m/\epsilon_0)$ to Y in line 9 of Algorithm 2, our algorithm becomes $(\epsilon_0, 0)$-differentially private. However, note that $\mathbb{V}\,[\mathbf{Lap}\,(2m/\epsilon_0)] = 8\,(2m/\epsilon_0)^2$, which is much larger than the variance $\mathbb{V}\,[Y] \leq m$ of the test statistic of Algorithm 2. Consequently, this noise results in a large increase of sample complexity. For sake of completeness, this approach is presented in Algorithm 4, in Appendix C. The only change with respect to (non-private) Algorithm 2 is that there is an extra Laplace noise added to the test statistic in line 7 and the rejection threshold has updated accordingly.

The sample complexity of Algorithm 2 is $O\big(1/\mu^2\sqrt{\ln(1/\delta)/m}\big)$, whereas the privatized test requires $O\left(m\sqrt{\ln 1/\delta}/(\mu^2\epsilon_0)\right)$. This means that the naive approach results in an increase in the sample complexity by a factor of $m^{3/2}/\epsilon_0$. Next, we try to bring this variance down with a truncation technique applied to Laplace noise.

In Claim 10, it becomes apparent that the sensitivity of the test statistic Y is proportional to the value of the following sum of independent Rademacher random variables $\left|\frac{4}{k}\sum_{i=1}^{m/2}\sum_{\ell=1}^{k}X_{(2i-1),2i}^{\ell}\right|$, which can be up to $2m$. To control the variance (and the sample complexity) of the privatized test statistic, we deal with the case where the value of this sum is $\Omega(\sqrt{m/k})$ separately. This is the intuition behind Algorithm 3, which is inspired by [9, Algorithm 1], and distinguishes between different cases. In particular, if the value of the Laplace noise happens to be high, Algorithm 3 returns a random response, while if $\left|\frac{4}{k}\sum_{i=1}^{m/2}\sum_{\ell=1}^{k}X_{(2i-1),2i}^{\ell}\right| = \Omega(\sqrt{m/k})$, the algorithm rejects. Otherwise, the algorithms performs a randomized version of the uniformity test called UNIF, defined in Algorithm 2. In this case, we show that the sensitivity of the test statistic (and thus, the sample complexity) can be upper bounded reasonably well. We refer to the DP algorithm as TRUNC, which is defined in Algorithm 3.

Algorithm 3 Central DP Uniformity Test (TRUN)

1: **Input:** significance $\delta > 0$, tolerance $\epsilon > 0$, DP parameter ϵ_0
2: Sample $Z \sim \mathbf{Lap}\left(\frac{4}{k\delta\epsilon_0}\right)$
3: **if** $|Z| > \frac{4}{k\delta\epsilon_0}\ln\frac{1}{\delta}$ **then** $\triangleright$ True with probability at most δ
4:     Output Accept or Reject with equal probability
5: Let $\pi_0 \in S_m$ be chosen uniformly at random and renumber the items so that $\pi_0 = (1, \ldots, m)$
6: Let $\phi_\epsilon = \sup_{\phi \in [0,1]}\{d_{TV}(\mathcal{M}_{1,\pi_0}, \mathcal{M}_{\phi,\pi_0}) > \epsilon\}$
7: Let $\mu = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}}$ and $m_1 = m/8 - \sqrt{m\ln(2/\delta)/16}$.
8: Take k samples $\mathcal{D}_k = \{\pi_1, \ldots, \pi_k\}$, where k is as in Theorem 6.
9: Let $X_{i(i+1)}^{\ell} = 1$, if $i \succ_{\pi_\ell} i+1$, and -1 otherwise.
10: **if** $\left|\frac{2}{mk}\sum_{i=1}^{m/2}\sum_{\ell=1}^{k}X_{(2i-1),2i}^{\ell} + Z\right| > \sqrt{\frac{2\ln(2/\delta)}{mk}} + \frac{4}{\delta k\epsilon_0}\ln\frac{1}{\delta}$ **then**
11:     Reject
12: **else**
13:     Let $Y_{i(i+1)} = \left(\frac{1}{\sqrt{k}}\sum_{\ell=1}^{k}X_{i(i+1)}^{\ell}\right)^2$ for all item pairs $i(i+1)$
14:     Let $Y = Y_{12} + Y_{34} + \cdots + Y_{(m-1)m}$
15:     $B \sim \mathbf{Bernoulli}\,(p)$ where $p = \min\left\{1, \frac{16(Y-m/2)}{m\mu^2(k-1)}\right\}$
16:     **If** B=1 **Then** Accept **Else** Reject

Theorem 6. *For all $\delta, \epsilon, \epsilon_0 > 0$, Algorithm 3 with $\mu = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}}$ and*

$$k = \Theta\left(\max\left\{\frac{1}{\mu^2}\left(\frac{1}{\delta^{3/2}\sqrt{m}} + \frac{1}{\delta^3 m}\right), \frac{\ln^{1/3}(1/\delta)}{\mu^{4/3}m^{1/3}\epsilon_0^{2/3}\delta^{2/3}}, \frac{\sqrt{\ln(1/\delta)}}{\mu\epsilon_0\delta}\right\}\right)$$

samples is an $(\epsilon_0, 0)$-differentially private (ϵ, δ)-uniformity test of Mallows models.

225 Theorem 6 has some interesting consequences. First, privacy comes for free in some parameter
226 regime since the first term of the sample complexity, which is dominant if ϕ_ϵ is close to 1 and m is not
227 so large, does not depend on the privacy parameter ϵ_0. Second, the sample complexity of TRUNC is
228 worse than the simple *bucketing approach* for other parameter regimes. The bucketing approach is a
229 folklore result to convert non-private algorithms to private ones. It consists of running a non-private
230 algorithm on $\lceil 1/\epsilon_0 \rceil$ number of data batches in parallel, and return one of the outcomes selected
231 uniformly at random. This approach is $(\epsilon_0, 0)$-differentially private and has sample complexity
232 $\lceil 1/\epsilon_0 \rceil$ times that of the non-private algorithm (see e.g., [9, Theorem 2] for the precise reduction
233 approach). Combining UNIF with the bucketing approach, we obtain a $(\epsilon_0, 0)$-differentially private
234 algorithm with sample complexity $O\big(\max\{1/(\mu^2 \epsilon_0)\sqrt{\ln(1/\delta)/m}, 2/\epsilon_0\}\big)$. The bucketing approach
235 is very efficient in our uniformity testing setup, because the sample complexity is of order $m^{-1/2}$
236 for the non-private algorithm. So, the bucketing approach requires $O(1/\epsilon_0)$ samples, if m is large
237 enough. On the other hand, TRUNC can be superior when ϕ_ϵ is close to 1 and m is not so large, in
238 which case the first term of Theorem 6 becomes dominant, as our experimental evidence also justifies.

6 Local differential privacy (LDP)

240 Algorithm 2 can easily extended so as it satisfies the LDP constraint, since it extracts a binary
241 sequence from the rankings in Line 7 of Algorithm 2. Adding randomized response (RR) to this bit
242 sequence componentwisely results in an simple LDP uniformity testing algorithm. Let us denote
243 the conditional probability of RR by $W(.|.)$, for which $W(-1|-1) = W(+1|+1) = \frac{e^\gamma}{e^\gamma+1}$ and
244 $W(-1|+1) = W(+1|-1) = \frac{1}{e^\gamma+1}$. As a consequence, if all $X_{i(i+1)}^\ell$ are passed through a channel
245 $W(.|.)$ with $\gamma = 2\epsilon_0/m$, then the LDP guarantee is satisfied. To see that, we consider two rankings
246 π and π', for which $f_{\pi_0}(\pi) = (-1, \ldots, -1)$ and $f_{\pi_0}(\pi') = (1, \ldots, 1)$ for a fixed π_0. Then

$$\log \frac{\mathbf{P}((1,\ldots,1)|\pi)}{\mathbf{P}((1,\ldots,1)|\pi')} = \frac{m}{2} \log \frac{\frac{e^\gamma}{e^\gamma+1}}{\frac{1}{e^\gamma+1}} = \frac{m\gamma}{2} = \epsilon_0$$

247 We present our LDP uniformity testing algorithm so as it requires public/shared randomness in the
248 form of a random ranking that is sent to each peer beforehand. The curator algorithm is defined in
249 Algorithm 5, and the peer algorithms in Algorithm 6, in Appendix F. The LDP algorithm is based on
250 Algorithm 2 and uses the same test statistic. If public randomness is available, we can implement
251 Algorithm 2 with random item pairing and $\mu_0 = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}} \cdot \frac{e^\gamma-1}{e^\gamma+1}$, which leads to an improved sample
252 complexity, if ϕ_ϵ is close to 1 and m is relatively large. If only private randomness is available, we
253 implement Algorithm 2 with a fixed item pairing and $\mu'_0 = \frac{1-\phi_\epsilon}{1+\phi_\epsilon} \cdot \frac{e^\gamma-1}{e^\gamma+1}$ (see also the discussion after
254 Theorem 5 on how the choice of item pairing affects the value of μ and the sample complexity). The
255 analysis is essentially identical to the proof of Theorem 5, since the mean value and the variance of
256 the test statistic are $m/2$ and at most m, respectively, under H_0, and are given by the same functions
257 of μ (or μ'_0), under H_1. The only essential difference is the decrease of μ (or μ'_0) by a factor of $\frac{e^\gamma-1}{e^\gamma+1}$,
258 to account for the randomized response. The discussion above is summarized by the following:

259 **Theorem 7.** *For all $\delta, \epsilon, \epsilon_0 > 0$ and $\gamma = 2\epsilon_0/m$, Algorithm 5 and Algorithm 6 form an (ϵ, δ)-finite*
260 *confidence uniformity test and $(\epsilon_0, 0)$-locally differentially private for Mallows modesls with sample*
261 *complexity:*

262 • $k = \Theta\left(\frac{1}{\mu_0^2}\sqrt{\frac{\ln(1/\delta)}{m}}\right)$, *where $\mu_0 = \frac{1-\phi_\epsilon^{m/8}}{1+\phi_\epsilon^{m/8}} \cdot \frac{e^\gamma-1}{e^\gamma+1}$, if m-bit public randomness is used and*
263 *a random ranking is sent by the curator algorithm to each peer.*

264 • $k = \Theta\left(\frac{1}{\mu_0'^2}\sqrt{\frac{\ln(1/\delta)}{m}}\right)$. *where $\mu'_0 = \frac{1-\phi_\epsilon}{1+\phi_\epsilon} \cdot \frac{e^\gamma-1}{e^\gamma+1}$, if only private randomness is used.*

265 Since for $\gamma = 2\epsilon_0/m$, $\frac{e^\gamma-1}{e^\gamma+1} \approx \frac{2\epsilon_0}{m}$, the dependence of the sample complexity of our LDP algorithm
266 on ϵ_0 is $\Theta(1/\epsilon_0^2)$ and on m is $\Theta(m^{3/2})$.

7 Experiments

We shall present synthetic experiments to assess the performance of the proposed tests. We assess the power of these tests which is the probability of the rejection for various spread parameter ϕ. Every testing algorithm we presented has a tolerance parameter ϵ and significance δ. We used $\delta = 0.05$ in every case. The tolerance parameter ϵ does have impact only on the sample size of the testing algorithms. Instead of setting ϵ to a certain value, we plotted the power of the algorithms with various sample size. In this way, we could compare the performance of the testing algorithms based on the same number of samples as input. Each result we report here are computed based on 1000 repetitions. The central ranking of each model which the random samples are generated from, is selected uniformly at random in each each run independently.

7.1 Uniformity testing based on 2 samples

In the first set of experiments, we compare the uniformity testing algorithm based on two samples, called 2SAMP which is defined in Algorithm 1 and the more general algorithm, called UNIF which is defined in Algorithm 2 running with two rankings as input. We assess the power of these tests which is the probability of the rejection for various spread parameter ϕ. The results are plotted in Figure 1. The 2SAMP algorithm does work already for $m = 100$ and it consistently outperforms UNIF based on two rankings. This can explained by the fact that 2SAMP computes pairwise statistic, which is the Kendall distance, based on each pair of items, whereas UNIF takes into account only the independent pairs. It is worth to emphasize that these tests can detect very small deviation from the uniform for large m. More concretely, it is detected with zero error, i.e. power is equal to 1, when the spread parameter deviates from 1 with a margin of 2×10^{-5} in case of $m = 10000$.

Figure 1: Power function of 2SAMP introduced in Subsection 4.1 and UNIF introduced in Subsection 4.2 with various parameters of the alternative model. The spread parameter of the underlying Mallows model is shown on the x-axis.

7.2 Uniformity testing in general with arbitrary m

Testing uniformity was one of the motivation of Mallows when he came up with his model (see Section 11 in [23]). Mallows assumed that the central ranking is known and proposed a asymptotic test based on the normal approximation of the sufficient statistic of his model. Even if there is no guaranty of how good this normal approximation is, it seems reasonable when the central ranking is fixed, since the distribution of the sufficient statistics is symmetric due to the fact that Mahonian numbers are symmetric, i.e. $N_k = N_{m(m-1)/2-k}$ where N_k is the kth Mahonian number of order m. One can compute the mean and variance of sufficient statistic based on [19] as $\mathbb{E}_{\pi \sim \mathcal{M}_{1,\pi_0}}[T_{\pi_0}(\pi)] = \sum_{i=0}^{M} \frac{iN_i}{m!} = \frac{m(m-1)}{4}$ and $\mathbb{V}_{\pi \sim \mathcal{M}_{1,\pi_0}}[T_{\pi_0}(\pi)] = \frac{m(2m+5)(m-1)}{72}$. This approximate solution is easy to use, since uniformity testing boils down to testing equality of expectation of normal distributions with known variance. Here we consider a more general testing problem where we do not assume that the central ranking is known and fixed. We refer to this approach as Mallows approximate test (MA). In this test, the normal approximation seems not so accurate as Figure 2 shows. The power of the test converges to 1 very slowly as ϕ is getting far from zero. Algorithm UNIF achieves a power that is close to one much faster.

7.3 Uniformity testing with privacy

In this set of experiments, we compare the performance of the presented DP algorithms including the following three of them: (1) bucketed UNIF which consists of running the UNIF algorithm on $\lceil 1/\epsilon_0 \rceil$ batches of data indpendently and take the output of one of the runs uniformly at random. We refer to this approach as BUNIF. (2) We run the DP algorithm with truncated Laplace noise that is defined in Algorithm 3 which we refer to as TRUNC. (3) We run also the locally differentially

Figure 2: Power function of MA and UNIF algorithms with various number of items $m \in \{10, 100, 1000, 10000\}$ and various sample size $n \in \{10000, 100, 2, 2\}$, respectively.

private algorithm which is defined in Subsection 6. We set $\epsilon_0 = 0.33$ thus the BUNIF power curve corresponds to the UNIF power curve with $1/3$ of the sample complexity. The power curves of

Figure 3: Power function of BUNIF, TRUNC and LDP algorithms with various number of items $m \in \{10, 100, 500, 1000\}$ and various sample size. We set the sample size for central DP algorithms, i.e. BUNIF and TRUNC, to $n \in \{10000, 1000, 1000, 100\}$, respectively. In case of LDP, the sample size was set to $n = \{100k, 200k, 300k, 300k\}$. The privacy budget ϵ_0 was set to $1/3$.

the algorithms are shown in Figure 3. Note that the TRUNC does outperforms BUNIF when ϕ is close to 1, since in that case μ is very close to 1 and the first term is the dominating one in Theorem 6. Nevertheless, the power of BUNIF algorithm converges faster to 1 when the underlying model getting farther from the uniformity. In general, the DP algorithms requires much more samples than the non-private algorithms. This difference is much more pronounced in case of LDP. However, local differential privacy is well known to provide some of the strongest privacy guarantees as it is impossible for an adversary to know the true ranking from the output of the channel.

8 Conclusion and Future Work

We introduced uniformity testing algorithm with a sample complexity upper bound of order $O(1/\sqrt{m})$ for ranking data when the alternative model class is constituted by the single parameter Mallows model. The proposed methods can work based on 2 samples, when m is large enough. We also devised testing algorithms in the central and local differential privacy framework. We demonstrated the versatility of these testers on synthetic data. We found that they are scalable, since they could handle large m including $m = 10000$, and are able to detect non-uniformity with very small error, i.e. $1 - \phi \approx 10^{-5}$ difference could be detected with zero error based on two samples when $m = 10000$.

One open question is to provide lower bounds on the sample complexity of uniformity testing of Mallows models. It turned out that this is a very challenging problem in the non-private case since, for example, using information theoretic lower bounding technique based on LeCam's theorem, one needs to upper bound KL divergence $\mathrm{KL}(\mathcal{M}_{\phi_\epsilon, \pi_0}, \mathcal{M}_{1, \pi_0}) = \ln^2 \phi_\epsilon \nabla^2 \ln Z(\xi)$ where $\xi \in [\ln \phi_\epsilon, 0]$. For doing so, one needs to have an upper bound for the difference of ϕ_ϵ from 1 in terms of ϵ and m. Note that ϕ_ϵ depends on the total variation distance, thus it seems unavoidable to get a bound for $Z(\phi_\epsilon)$ as well, which is a very hard nut to crack. So we leave this lower bound as future work. Nevertheless, note that with $m = 2$, the single parameter Mallows class includes the class of Bernoulli distributions, thus the lower bounds that are devised for private uniformity testing of Bernoulli distributions also apply to private uniformity testing of Mallows models. More concretely, [5] showed that testing Bernoulli with parameter in a central DP setting cannot be done using $o(1/\epsilon_0)$ which implies that our central DP algorithm has optimal dependency on the privacy budget parameter. On the other hand, [6] showed that in the LDP setting, a lower bound on the sample complexity of testing is $\Omega(1/\epsilon_0^2)$. Theorem 7 matches this lower bound when $m = 2$, since then $e^\gamma - 1 \approx \epsilon_0$ and the sample complexity bound is $O(1/\epsilon_0^2)$ in this case. Lastly, a natural extension of our work is to consider more fine grained atom in the privacy setting, namely one might want to protect each pair of the data instead of whole rankings.

References

[1] Jayadev Acharya, Clement Canonne, Cody Freitag, and Himanshu Tyagi. Test without trust: Optimal locally private distribution testing. In Kamalika Chaudhuri and Masashi Sugiyama, editors, *Proceedings of the Twenty-Second International Conference on Artificial Intelligence and Statistics*, volume 89 of *Proceedings of Machine Learning Research*, pages 2067–2076. PMLR, 16–18 Apr 2019.

[2] Jayadev Acharya, Clément L. Canonne, Yanjun Han, Ziteng Sun, and Himanshu Tyagi. Domain compression and its application to randomness-optimal distributed goodness-of-fit. In *Conference on Learning Theory, COLT 2020, 9-12 July 2020, Virtual Event [Graz, Austria]*, pages 3–40, 2020.

[3] Jayadev Acharya, Ashkan Jafarpour, Alon Orlitsky, and Ananda Suresh. A competitive test for uniformity of monotone distributions. In Carlos M. Carvalho and Pradeep Ravikumar, editors, *Proceedings of the Sixteenth International Conference on Artificial Intelligence and Statistics*, volume 31 of *Proceedings of Machine Learning Research*, pages 57–65, Scottsdale, Arizona, USA, 29 Apr–01 May 2013. PMLR.

[4] Jayadev Acharya, Ziteng Sun, and Huanyu Zhang. Differentially private testing of identity and closeness of discrete distributions. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pages 6879–6891, 2018.

[5] Jayadev Acharya, Ziteng Sun, and Huanyu Zhang. Differentially private testing of identity and closeness of discrete distributions. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, page 6879–6891, Red Hook, NY, USA, 2018. Curran Associates Inc.

[6] Jayadev Acharya, Ziteng Sun, and Huanyu Zhang. Hadamard response: Estimating distributions privately, efficiently, and with little communication. In Kamalika Chaudhuri and Masashi Sugiyama, editors, *Proceedings of the Twenty-Second International Conference on Artificial Intelligence and Statistics*, volume 89 of *Proceedings of Machine Learning Research*, pages 1120–1129. PMLR, 16–18 Apr 2019.

[7] Róbert Busa-Fekete, Dimitris Fotakis, Balázs Szörényi, and Manolis Zampetakis. Optimal learning of mallows block model. *CoRR*, 2019.

[8] Róbert Busa-Fekete, Eyke Hüllermeier, and Balázs Szörényi. Preference-based rank elicitation using statistical models: The case of Mallows. In *ICML*, volume 32 of *JMLR Workshop and Conference Proceedings*, pages 1071–1079. JMLR.org, 2014.

[9] Bryan Cai, Constantinos Daskalakis, and Gautam Kamath. Priv'it: Private and sample efficient identity testing. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, pages 635–644, 2017.

[10] Ilias Diakonikolas, Themis Gouleakis, John Peebles, and Eric Price. Sample-optimal identity testing with high probability. *Electron. Colloquium Comput. Complex.*, 24:133, 2017.

[11] Ilias Diakonikolas, Daniel M. Kane, and Vladimir Nikishkin. Testing identity of structured distributions. In *Proceedings of the Twenty-Sixth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2015, San Diego, CA, USA, January 4-6, 2015*, pages 1841–1854, 2015.

[12] Apple Inc. Differential Privacy Team. Learning with privacy at scale. 2017.

[13] Devdatt Dubhashi and Alessandro Panconesi. *Concentration of Measure for the Analysis of Randomized Algorithms*. Cambridge University Press, USA, 1st edition, 2009.

[14] Cynthia Dwork. Differential privacy: A survey of results. In *Theory and Applications of Models of Computation, 5th International Conference, TAMC 2008, Xi'an, China, April 25-29, 2008. Proceedings*, volume 4978 of *Lecture Notes in Computer Science*, pages 1–19. Springer, 2008.

[15] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pages 265–284. Springer, 2006.

[16] Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, 9(3–4):211–407, August 2014.

[17] Úlfar Erlingsson, Vasyl Pihur, and Aleksandra Korolova. Rappor: Randomized aggregatable privacy-preserving ordinal response. In *Proceedings of the 2014 ACM SIGSAC Conference on Computer and Communications Security*, CCS '14, page 1054–1067, 2014.

[18] Alexandre Evfimievski, Johannes Gehrke, and Ramakrishnan Srikant. Limiting privacy breaches in privacy preserving data mining. In *Proceedings of the twenty-second ACM SIGMOD-SIGACT-SIGART symposium on Principles of database systems*, pages 211–222, 2003.

[19] M. A. Fligner and J. S. Verducci. Distance based ranking models. *Journal of the Royal Statistical Society. Series B (Methodological)*, 48(3):359–369, 1986.

[20] Oded Goldreich and Dana Ron. On testing expansion in bounded-degree graphs. *Electron. Colloquium Comput. Complex.*, 7(20), 2000.

[21] Guy Lebanon and Yi Mao. Non-parametric modeling of partially ranked data. In *Advances in Neural Information Processing Systems 20, Proceedings of the Twenty-First Annual Conference on Neural Information Processing Systems, Vancouver, British Columbia, Canada, December 3-6, 2007*, pages 857–864, 2007.

[22] Tyler Lu and Craig Boutilier. Effective sampling and learning for mallows models with pairwise-preference data. *J. Mach. Learn. Res.*, 15(1):3783–3829, 2014.

[23] C. Mallows. Non-null ranking models. *Biometrika*, 44(1):114–130, 1957.

[24] Marina Meila and Le Bao. An exponential model for infinite rankings. *Journal of Machine Learning Research*, 11:3481–3518, 2010.

[25] Liam Paninski. A coincidence-based test for uniformity given very sparsely sampled discrete data. *IEEE Trans. Inf. Theory*, 54(10):4750–4755, 2008.

[26] Mingxuan Sun, Guy Lebanon, and Paul Kidwell. Estimating probabilities in recommendation systems. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2011, Fort Lauderdale, USA, April 11-13, 2011*, pages 734–742, 2011.