Modeling Sequential Sentence Relation to Improve Cross-lingual Dense Retrieval

Abstract

Recently multi-lingual pre-trained language models (PLM) such as mBERT and XLM-R have achieved impressive strides in cross-lingual dense retrieval. Despite its successes, they are general-purpose PLM while the multilingual PLM tailored for cross-lingual retrieval is still unexplored. Motivated by an observation that the sentences in parallel documents are approximately in the same order, which is universal across languages, we propose to model this sequential sentence relation to facilitate cross-lingual representation learning. Specifically, we propose a multilingual PLM called masked sentence model (MSM), which consists of a sentence encoder to generate the sentence representations, and a document encoder applied to a sequence of sentence vectors from a document. The document encoder is shared for all languages to model the universal sequential sentence relation across languages. To train the model, we propose a masked sentence prediction task, which masks and predicts the sentence vector via a hierarchical contrastive loss with sampled negatives. Comprehensive experiments on four cross-lingual retrieval tasks show MSM significantly outperforms existing advanced pre-training models, demonstrating the effectiveness and stronger cross-lingual retrieval capabilities of our approach. Code and model will be available.

1 Introduction

Cross-lingual retrieval (also including multi-lingual retrieval) is becoming increasingly important as new texts in different languages are being generated every day, and people query and search for the relevant documents in different languages (Zhang et al., 2021b; Asai et al., 2021a). This is a fundamental and challenging task and plays an essential part in real-world search engines, for example, Google and Bing search which serve hundreds of countries across diverse languages. In addition, it's also a vital component to solve many cross-lingual downstream problems, such as open-domain question answering (Asai et al., 2021a) or fact checking (Huang et al., 2022).

With the rapid development of deep neural models, cross-lingual retrieval has progressed from translation-based methods (Nie, 2010), cross-lingual word embeddings (Sun & Duh, 2020), and now to dense retrieval built on the top of multi-lingual pre-trained models (Devlin et al., 2019; Conneau et al., 2019). Dense retrieval models usually adopt pretrained models to encode queries and passages into low-dimensional vectors, so its performance relies on the representation quality of pretrained models, and for multilingual retrieval it also calls for cross-lingual capabilities.

Models like mBERT (Devlin et al., 2019), XLMR (Conneau et al., 2019) pre-trained with masked language model task on large multilingual corpora, have been applied widely in cross-lingual retrieval (Asai et al., 2021a;b; Shi et al., 2021) and achieved promising performance improvements. However, they are general pre-trained models and not tailored for dense retrieval. Except for the direct application, there are some pre-trained methods tailored for monolingual retrieval. Lee et al. (2019) and Gao & Callan (2021) propose to perform contrastive learning with synthetic query-document pairs to pre-train the retriever. They generate pseudo pairs either by selecting a sentence and its context or by cropping two sentences in a document. Although showing improvements, these approaches have only been applied in monolingual retrieval and the generated pairs by hand-crafted rules may be low-quality and noisy. In addition, learning universal sentence representations across languages is more challenging and crucial than monolingual, so better multilingual pre-training for retrieval needs to be explored.

In this paper, we propose a multilingual PLM to leverage sequential sentence relation across languages to improve cross-lingual retrieval. We start from an observation that the parallel documents should each contain approximately the same sentence-level information. Specifically, the sentences in parallel documents are approximately in the same order, while the words in parallel sentences are usually not. It means the sequential relation at sentence-level are similar and universal across languages. This idea has been adopted for document alignment (Thompson & Koehn, 2020; Resnik, 1998) which incorporates the order information of sentences. Motivated by it, we propose a novel Masked Sentence Encoder (MSM) to learn this universal relation and facilitate the isomorphic sentence embeddings for cross-lingual retrieval. It consists of a sentence encoder to generate sentence representations, and a document encoder applied to a sequence of sentences in a document. The document encoder is shared for all languages and can learn the sequential sentence relation that is universal across languages. In order to train MSM, we adopt a sentence-level masked prediction task, which masks the selected sentence vector and predicts it using the output of the document encoder. Distinct from MLM predicting tokens from pre-built vocabulary, we propose a hierarchical contrastive loss with sampled negatives for sentence-level prediction.

We conduct comprehensive experiments on 4 cross-lingual dense retrieval tasks including Mr. TyDi, XOR Retrieve, Mewsli-X and LAReQA. Experimental results show that our approach achieves state-of-the-art retrieval performance compared to other advanced models, which validates the effectiveness of our MSM model in cross-lingual retrieval. Our in-depth analysis demonstrates that the cross-lingual transfer ability emerges for MSM can learn the universal sentence relation across languages, which is beneficial for cross-lingual retrieval. Furthermore, we perform ablations to motivate our design choices and show MSM works better than other counterparts.

2 RELATED WORK

Multi-lingual Pre-trained Models. Recently the multilingual pre-trained models (Lample & Conneau, 2019; Conneau et al., 2019; Huang et al., 2019) have empowered great success in different multilingual tasks (Liang et al., 2020; Hu et al., 2020). Multilingual BERT (Devlin et al., 2019) is a transformer model pre-trained on Wikipedia using the multi-lingual masked language model (MMLM) task. XLM-R (Conneau et al., 2019) further extends the corpus to a magnitude more web data with MMLM. XLM (Lample & Conneau, 2019) proposes the translation language model (TLM) task to achieve cross-lingual token alignment. Unicoder (Huang et al., 2019) presents several pre-training tasks upon parallel corpora and ERNIE-M (Ouyang et al., 2021) learns semantic alignment by leveraging back translation. XLM-K (Jiang et al., 2022) leverages the multi-lingual knowledge base to improve cross-lingual performance on knowledge-related tasks. InfoXLM (Chi et al., 2021), HiCTL (Wei et al., 2020), and LABSE (Feng et al., 2022) encourage bilingual alignment via InfoNCE based contrastive loss. These models usually focus on cross-lingual alignment leveraging bilingual data, while it's not fit for cross-lingual retrieval that calls for semantic relevance between query and passage. There is few explore on how to improve pre-training tailored for cross-lingual retrieval, which is exactly what our model addresses.

Cross-lingual Retrieval. Cross-lingual (including multi-lingual) retrieval is a cross-field of information retrieval and multilingual which is becoming increasingly important in the community and impacting our lives in real-world applications. In the past, multi-lingual retrieval relied on community-wide evaluation datasets at TREC, CLEF, and NCTIR, such as CLEF 2000-2003 collection (Ferro & Silvello, 2015). They usually comprise only a small number of queries (at most a few dozen) with relevance judgments, which are insufficient for dense retrieval. Recently, more large scale cross-lingual retrieval datasets (Zhang et al., 2021b; Ruder et al., 2021) have been proposed to promote cross-lingual retrieval research, such as Mr. TyDi (Asai et al., 2021a) proposed in open-QA domain, Mewsli-X (Ruder et al., 2021) for news entity retrieval, etc.

The technique of the cross-lingual retrieval field has progressed from translation-based methods (Nie, 2010; Shi et al., 2021) to cross-lingual word embeddings by neural models (Sun & Duh, 2020), and now to dense retrieval built on the top of multi-lingual pre-trained models (Devlin et al., 2019; Conneau et al., 2019). Asai et al. (2021a;b) modify the bi-encoder retriever to be equipped with mBERT model, which plays an essential part in the open-QA system. Zhang et al. (2021b) find mBERT has cross-lingual transfer ability in multi-lingual retrieval and Li et al. (2021) proposes a new fine-tuning method using multi-stage knowledge distillation with query translation. However,

Figure 1: The general framework of masked sentence model (MSM), which has a hierarchical model architecture including the sentence encoder and the document encoder. The masked sentence prediction task predicts the masked sentence vector p_t, given the original vector h_t as the positive anchor, via a hierarchical contrastive loss.

most of the existing work directly adopts mBERT and focuses on fine-tuning a specific task, while ours targets pre-training and conducts evaluations on diverse benchmarks.

Dense Retrieval. Dense retrieval (Karpukhin et al., 2020; Lee et al., 2019; Qu et al., 2021; Xiong et al., 2020) (usually monolingual here) typically utilizes bi-encoder model to encode queries and passages into low-dimensional representations. With the advancements in PLM, it usually adopts pre-trained models like BERT (Devlin et al., 2019) as the text encoders. Recently there have been several directions explored in the pre-training tailored for dense retrieval: utilizing the hyperlinks between the Wikipedia pages (Ma et al., 2021; Zhou et al., 2022), synthesizing query-passage datasets for pre-training (Oğuz et al., 2021; Reddy et al., 2021), and auto-encoder-based language models that force the better representations (Lu et al., 2021; Ma et al., 2022). Among them, there is a popular direction that leverage the correlation of intra-document text pairs for the pre-training. Lee et al. (2019) and Chang et al. (2020) propose Inverse Close Task (ICT) treats a sentence as pseudo-query and the concatenated context as the pseudo-passage for contrastive pre-training. Another way is cropping two sentence spans (we call them CROP in short) from a document as positive pairs (Giorgi et al., 2021; Izacard et al., 2021), including Wu et al. (2022a); Iter et al. (2020) that use neighboring sentences and Gao & Callan (2021) that adopts two non-overlapping spans.

In summary, the existing pre-training methods for IR usually construct pseudo query-passage pairs from the corpus link, synthesized data, or the same document. The most relevant to ours are ICT and CROP, which generate two views of a document for contrastive learning. However, the correlation of the pseudo pair is coarse-granular and even not guaranteed. In contrast, ours utilizes a sequence of sentences in a document and models the universal sentence relation across languages via an explicit document encoder, resulting in better representation for cross-lingual retrieval.

3 METHODOLOGY

In this section, we first present the model architecture in a hierarchical style. Then, we introduce the masked sentence prediction pre-training task and training objective for our model.

3.1 HIERARCHICAL MODEL ARCHITECTURE

As illustrated in Figure.1, our Masked Sentence Encoder (MSM) has a hierarchical architecture that contains the Sentence Encode and the Document Encoder. The document encoder is applied to the sentence vectors generated by the sentence encoder from a sequence of sentences in a document.

Sentence Encoder. Given a document containing a sequence of sentences $\mathcal{D} = (S_1, S_2, ..., S_N)$ in which S_i denote a sentence in document, and each sentence contains a list of words. As shown in 1, our model contains two encoders in a hierarchical style: the sentence encoder extracts the sentence representations for the sequence in a document, and the document encoder is to model the

sentence relation and predict the masked sentences. First, we adopt a transformer-based encoder as our sentence encoder. Then as usual the sentence is passed through the embedding layer and transformer layers, and we take the last hidden state of the CLS token as the sentence representation. Note that all the sentence encoders share the parameters and we can get N sentence vectors $\mathcal{D}_H = (h_1, h_2, ..., h_N)$ respectively. In this task, we just encoder the complete sentences without the mask to get thorough sentence representations.

Document Encoder. Then the sentence-level vectors run through the document encoder, which has similar transformer-based architecture. Considering the sentences have sequential order in a document, the sentence position is also taken into account and it doesn't have token type embedding. After equipped with sentence position embeddings, we encode them through document encoder layers to get document-level context aware embeddings $\mathcal{D}_P = (p_1, p_2, ..., p_N)$. In order to train our model, we apply the sentence-level mask to the sentence vectors for our masked sentence prediction task. Specifically, $\mathcal{D}_H = (h_1, h_2, ..., h_N)$ are the original sentence vectors encoded by the sentence encoder, and we mask selected sentence vector h_t to $[mask]$ token and keep other the original ones. The original sentence vector h_t is seen as the positive anchor for the output vector p_t of document encoder corresponding to $[mask]$. Considering a document that contains N sentences, we mask each sentence in turn and keep the others the original, to get N pairs of p_t and h_t. It is effective to get as many samples as possible at the same time for efficient training.

There are some models also adopting a hierarchical transformer-based model (Zhang et al., 2019; Santra et al., 2021). For example, HiBERT (Zhang et al., 2019) uses a multi-level transformer-based model for document summarization, while it applies the mask to the words and includes a decoder for autoregressive pre-training. Poolingformer (Zhang et al., 2021a) proposes a two-level pooling attention schema for long document modeling but can't be applied for retrieval. They mainly adopt token-level MLM and targets document understanding, while ours focuses on masked sentence prediction and is directed at cross-lingual retrieval.

3.2 MASKED SENTENCE PREDICTION TASK

In order to model the sentence relation, we propose a masked sentence prediction task that aligns masked sentence vectors p_t with corresponding original h_t via the hierarchical contrastive loss. Distinct from Masked Language Model which can directly compute cross-entropy loss between masked tokens and pre-built vocabulary, our model lacks a sentence-level vocabulary. Here we propose a novel hierarchical contrastive loss on sentence vectors to address it. Contrastive learning has been shown effective in sentence representation learning (Karpukhin et al., 2020; Gao et al., 2021), and our model modifies the typical InfoNCE loss (Oord et al., 2018) to a hierarchical contrastive loss for the masked sentence prediction task. As shown in Figure.1, for masked sentence vectors p_t, the positive anchor is original h_t and we collect two categories of negatives: (a) Cross-Doc Negatives are the sentence vectors from different documents, i.e. $h_k^{\mathcal{C}}$, which can be seen as random negatives as usual. (b) Intra-Doc Negatives are the sentence vectors in a same document generated by sentence encoder, i.e. $h_j^{\mathcal{I}}, j \neq t$. Then the masked sentence vectors p_t with them are passed through the projection layer, and the output vectors are involved in the hierarchical contrastive loss as:

$$\mathcal{L}_{msm}(p_t, \{h_t^{\mathcal{I}}, h_1^{\mathcal{I}}, \ldots, h_{|\mathcal{I}|}^{\mathcal{I}}, h_1^{\mathcal{C}}, \ldots, h_{|\mathcal{C}|}^{\mathcal{C}}\})$$

$$= -\log \frac{e^{\text{sim}(p_t, h_t^{\mathcal{I}})}}{e^{\text{sim}(p_t, h_t^{\mathcal{I}})-} + \sum_{j=1, j \neq t}^{|\mathcal{I}|} e^{\text{sim}(p_t, h_j^{\mathcal{I}})-\mu\alpha} + \sum_{k=1}^{|\mathcal{C}|} e^{\text{sim}(p_t, h_k^{\mathcal{C}})}} \quad (1)$$

In the previous study (Gao & Callan, 2021), two sampled views or sentences of the same document are often seen as a positive pair to leverage their correlation. However, it limits the representation capability for it encourages the alignment between two views, just as a coarse-grained topic model (Yan et al., 2013). In contrast, we treat them as Intra-Doc Negatives, which could help the model to distinguish sentences from the same document to learn fine-grained representations. The intra-doc samples usually have closer semantic relation than cross-doc ones and directly treating them as negatives could hurt the uniformity of embedding space. To prevent this negative impact, we set the dynamic bias subtracted from their similarity scores. As seen in Eq.1, the dynamic bias is $-\mu\alpha$ in which μ is a hyper-parameter and α is computed as:

$$\alpha = \left(\frac{\sum_{j=1, j \neq t}^{|\mathcal{I}|} \text{sim} \left(p_t, h_j^{\mathcal{I}} \right)}{|\mathcal{I}| - 1} - \frac{\sum_{k=1}^{|\mathcal{C}|} \text{sim} \left(p_t, h_k^{\mathcal{C}} \right)}{|\mathcal{C}|} \right) .detach() \qquad (2)$$

It represents the gap between the average similarity score of Intra-Doc Negatives and them from Cross-Doc Negatives. Subtracting the dynamic bias can tune the high similarity of intra-doc negatives to the level of cross-doc negatives, which can also be seen as interpolation to generate soft samples. Note that we only use the value but do not pass the gradient, so we adopt the detach function after computation. Our experimental result in Sec.5.4 validates that the hierarchical contrastive loss is beneficial for representation learning in our model.

Considering the expensive cost of pre-training from scratch, we initialize the sentence encoder with pre-trained XLM-R weight and solely the document encoder from scratch. To prevent gradient back propagated from the randomly initialized document encoder from damaging sentence encoder weight, we adopt MLM task to impose a semantic constraint. Therefore our total loss consists of a token-level MLM loss and a sentence-level contrastive loss:

$$\mathcal{L} = \mathcal{L}_{msm} + \mathcal{L}_{mlm} \qquad (3)$$

After pre-training, we discard the document encoder and leave the sentence encoder for fine-tuning, which also provides a direct comparison to the original pre-trained model. It is worth mentioning that our MSM also coincides with the auto-encoders based on bottleneck theory (Lu et al., 2021; Li et al., 2020): the sentence encoder press the sentence semantics into CLS token, and the document encoder leverage the limited information to reconstruct the masked sentence vector, thus enforcing an information bottleneck on the sentence encoder for better representation quality.

4 EXPERIMENTS SETUP

4.1 EVALUATION DATASETS

We evaluate our model with other counterparts on 4 popular datasets: Mr. TyDi is for query-passage retrieval, XOR Retrieve is cross-lingual retrieval for open-domain QA, Mewsli-X and LAReQA are for language-agnostic retrieval.

Mr. TyDi (Zhang et al., 2021b) It aims to evaluate cross-lingual passage retrieval with dense representations. Mr. TyDi is a multi-lingual benchmark dataset for mono-lingual query passage retrieval in eleven typologically distinct languages. Given a question in language L, the model should retrieve relevant texts in language L that can respond to the query. As the original paper suggests, we take MRR@100 and Recall@100 for evaluation.

XOR Retrieve (Asai et al., 2021a) XOR QA is proposed for multilingual open-domain QA, which consists of three sub-tasks: XOR-Retrieve, XOR-English Span, and XOR-Full. We take the XOR-Retrieve for the evaluation of pre-trained models: given a question in L (e.g., Korean), the task is to retrieve English passages that can answer the query. Following Asai et al. (2021a), we calculate the recall by computing the fraction of the questions for which the minimal answer is included in the top n tokens selected, and take R@2kt and R@5kt (kilo-tokens) as the reported metrics.

Mewsli-X (Ruder et al., 2021) Mewsli-X is built on top of Mewsli (Multilingual Entities in News, linked) (Botha et al., 2020). Given a contextual entity mention, it requires retrieving the entity's description from a multilingual candidate pool to link to its entry in a language-agnostic knowledge base. We follow the setting of XTREME-R (Ruder et al., 2021), which builds Mewsli-X consisting of 15K mentions in 11 languages: given a mention in context, it is to retrieve the correct target entity description from a candidate pool ranging over 1M candidates across 50 languages.

LAReQA (Roy et al., 2020) Language Agnostic Retrieval Question Answering is a retrieval task in which each query has target answers in multiple languages, and models require retrieving all correct answers from the candidate pool regardless of language. Following Ruder et al. (2021), we use the LAReQA XQuAD-R dataset which consists of 13,090 questions, each of which has 11 target answers (in 11 different languages) within 13,014 candidate answer sentences.

Table 1: Retrieval performance comparison on four benchmark datasets. The best performing models are marked bold and the results unavailable are left blank. * mean the results are borrowed from published papers: † from Zhang et al. (2022), ‡ from Asai et al. (2021a), § from Ruder et al. (2021), while others are evaluated using the same pipeline by us for a fair comparison.

Model	Mr. TyDi		XOR Retrieve		Mewsli-X	LAReQA
	MRR@100	R@100	R@2k	R@5k	mAP@20	mAP@20
Cross-lingual zero-shot transfer (models are fine-tuned on English data)						
mBERT*	34.4†	73.4†	-	-	38.6‡	21.6‡
mBERT	33.0	69.7	31.6	42.3	39.0	24.5
XLMR	37.7	72.7	30.6	39.3	39.7	29.3
MSM	**44.7**	**78.6**	**34.9**	**44.7**	**41.5**	**33.5**
Multi-lingual fine-tune (models are fine-tuned on the multi-lingual data if available)						
mBERT*	59.1†	87.1†	38.8§	48.0§	-	-
mBERT	57.6	87.9	48.3	57.0	-	-
XLMR	58.5	87.8	45.1	53.9	-	-
MSM	**60.5**	**89.0**	**48.6**	**57.3**	-	-

4.2 IMPLEMENTATION DETAILS

For the pre-training stage, we adopt a 12-layers transformer sentence encoder initialized from the XLMR base weight, and a 2-layers transformer document encoder trained from scratch. We use a learning rate of 4e-5 and Adam optimizer with a linear warm-up. Following Wenzek et al. (2019), we collect a clean version of Common Crawl (CC) including a 2,500GB multi-lingual corpus covering 108 languages, which is the same as XLMR. Note that we only train on Common Crawl without any bilingual translation data. To limit the memory consumption during training, we limit the length of each sentence to 64 words (longer parts are truncated) and split documents with more than 32 sentences into smaller with each containing at most 32 sentences. The rest settings mainly follow the original XLMR's in FairSeq. We conduct pre-training on 8 A100 GPUs for about 200k steps.

For the fine-tuning stage, we mainly follow the hyper-parameters of the original paper for the Mr. TyDi and XOR Retrieve tasks separately. And for Mewsli-X and LAReQA tasks, we mainly follow the settings of XTREME-R using its open-source codebase. Note that we didn't tune the hyper-parameters and mainly adopted the original settings using the same pipeline for a fair comparison. More details of fine-tuning hyper-parameters refer to Appendix.A.1.

5 EXPERIMENT RESULTS

5.1 EVALUATION SETTINGS

Cross-lingual Zero-shot Transfer. This setting is most widely adopted for the evaluation of multilingual scenarios with English as the source language, as many tasks only have labeled train data available in English. Concretely, the models are fine-tuned on English labeled data and then evaluated on the test data in the target languages. It also facilitates evaluation as models only need to be trained once and can be evaluated on all other languages. For Mr. TyDi dataset, the original paper adopt the Natural Questions data (Kwiatkowski et al., 2019) for fine-tuning while later Zhang et al. (2022) suggests fine-tuning on MS MARCO for better results, so we fine-tune on MARCO when compared with best-reported results and on NQ otherwise. For XOR Retrieve, we fine-tune on NQ dataset as the original paper (Asai et al., 2021a). For Mewsli-X and LAReQA, we follow the settings in XTREME-R, where Mewsli-X on a predefined set of English-only mention-entity pairs and LAReQA on the English QA pairs from SQuAD v1.1 train set.

Multi-lingual Fine-tune. For the tasks where multi-lingual training data is available, we additionally compare the performance when jointly trained on the combined training data of all languages. Following the setting of Mr. TyDi and XOR Retrieve, we pre–fine-tune models as in Cross-lingual Zero-shot Transfer and then fine-tune on multi-lingual data if available. For the Mewsli-X and LAReQA, there is no available multi-lingual labeled data.

Table 2: Cross-lingual zero-shot transfer retrieval performance on Mr. TyDi dataset. We report MRR@100 and Recall@100 on the test sets of Mr. TyDi after finetuning on NQ dataset.

Method	Metrics	AR	BN	EN	FI	ID	JA	KO	RU	SW	TE	TH	AVG
mBERT	MRR@100	28.7	33.4	28.1	24.0	32.0	24.3	21.8	29.0	18.7	14.5	19.3	24.9
	Recall@100	68.3	79.3	76.1	65.0	74.1	65.3	57.9	69.2	51.7	46.1	54.0	64.3
XLMR	MRR@100	30.8	30.2	27.1	23.5	33.5	23.5	26.6	25.7	24.0	26.6	36.3	28.0
	Recall@100	72.3	78.4	74.3	67.0	79.8	66.5	64.7	65.0	57.2	72.7	84.6	71.1
CROP	MRR@100	28.8	31.6	22.7	24.1	29.5	20.2	22.7	24.5	29.0	21.7	33.2	26.2
	Recall@100	72.4	80.6	74.2	69.5	81.2	62.5	61.6	65.8	69.7	80.3	81.2	72.6
ICT	MRR@100	31.5	36.1	20.6	24.8	33.8	23.9	21.6	24.5	30.3	19.3	36.9	27.5
	Recall@100	76.2	85.1	67.0	69.4	82.4	68.6	61.0	69.2	74.7	71.2	88.2	73.9
MSM	MRR@100	37.9	39.4	29.9	27.7	38.3	28.0	26.8	28.5	32.1	43.1	42.0	**34.0**
	Recall@100	77.3	82.9	73.6	70.5	83.5	67.9	61.8	68.6	69.9	83.5	84.9	**74.9**

Table 3: Cross-lingual zero-shot transfer results on XOR Retrieve task. We report R@2k and R@5 metrics on the test sets.

Method	Metrics	AR	BN	FI	JA	KO	RU	TE	AVG
mBERT	R@2k	31.1	26.6	38.5	32.4	38.6	24.9	29.1	31.6
	R@5k	44.1	36.2	48.1	41.5	48.1	38.4	39.5	42.3
XLMR	R@2k	39.9	25.7	41.1	27.8	31.9	22.4	25.2	30.6
	R@5k	49.6	34.9	50.0	34.9	41.8	30.4	34.0	39.3
CROP	R@2k	45.4	32.9	42.4	23.7	33.3	24.9	30.1	33.2
	R@5k	53.8	42.8	49.4	34.0	42.1	31.6	38.8	41.8
ICT	R@2k	41.6	35.9	43.9	27.8	34.0	24.5	27.8	33.6
	R@5k	52.5	46.1	51.6	39.0	42.8	32.9	38.5	43.3
MSM	R@2k	47.9	32.6	44.9	24.1	35.8	25.3	34.0	**34.9**
	R@5k	58.4	41.8	51.9	36.9	44.6	37.6	42.1	**44.7**

5.2 MAIN RESULTS

In this section, we evaluate our model on diverse cross-lingual and multi-lingual retrieval tasks and compare it with other strong pre-training baselines. Multilingual BERT (Devlin et al., 2019) pre-trained on multilingual Wikipedia using MLM and XLMR (Conneau et al., 2019) extend to a magnitude more web data for 100 languages. Both of them are widely adopted in multilingual scenarios including NLU tasks and cross-lingual retrieval (Zhang et al., 2021b).

We report the main results in Table.1, and provide more detailed results in Appendix A.2. The effectiveness of our multilingual pre-training method appears clearly as MSM achieves significantly better performance than its counterparts. (1) No matter whether in the cross-lingual zero-shot transfer or multi-lingual fine-tune settings, the performance trend is consistent and MSM achieves impressive improvements on all the tasks, which demonstrates the effectiveness of our proposed MSM. (2) Under the setting of cross-lingual zero-shot transfer, it shows that our MSM outperforms other models by a large margin. Compared to strong XLM-R, MSM improves 7% MRR@100 on Mr. TyDi, 4.3% R@2k on XOR Retrieve, 1.8% mAP@20 of Mewsli-X, and 4.2% mAP@20 of LAReQA. (3) Under the setting of multi-lingual fine-tuning, the performance can be further improved by fine-tuning on multi-lingual train data and MSM can achieve the best results. However, there usually doesn't exist available multi-lingual data (such as Mewsli-X and LAReQA), especially for low-resource languages, and in this case MSM can achieve more gains for its stronger cross-lingual ability.

5.3 RESULTS ACROSS LANGUAGES

As shown in the Tab.2 and Tab.3, we provide detailed results across languages for Mr. TyDi and XOR Retrieve after fine-tuning on NQ datasets. We also reproduced another two strong baselines proposed for monolingual retrieval, i.e. ICT and CROP. We extend them to multi-lingual corpora under the same setting for a fair comparison. We follow the original setting in Lee et al. (2019) to reproduce ICT and for CROP we adopt the setting in Wu et al. (2022a).

Table 4: Performance comparison of zero-shot cross-lingual retrieval when setting individual document encoder (and projection head) for English and other languages. *OTHS* means the average of languages except for *EN*.

Method	Metrics	AR	BN	FI	ID	JA	KO	RU	SW	TE	TH	EN	OTHS	AVG
XLMR	MRR@100	30.8	30.2	23.5	33.5	23.5	26.6	25.7	24.0	26.6	36.3	27.1	28.1	28.0
	Recall@100	72.3	78.4	67.0	79.8	66.5	64.7	65.0	57.2	72.7	84.6	74.3	70.8	71.1
Share All	MRR@100	37.9	39.4	27.7	38.3	28.0	26.8	28.5	32.1	43.1	42.0	29.9	34.4	**34.0**
	Recall@100	77.3	82.9	70.5	83.5	67.9	61.8	68.6	69.9	83.5	84.9	73.6	75.1	**74.9**
Sep Doc	MRR@100	35.5	38.2	26.2	38.3	24.9	27.9	28.3	32.6	41.3	42.6	28.1	33.6	33.1
	Recall@100	74.7	82.4	68.0	81.7	65.2	59.8	66.5	66.9	87.2	83.6	73.0	73.6	73.5
Sep Doc + Head	MRR@100	35.8	39.7	28.8	36.5	24.7	25.1	26.9	32.0	20.8	38.8	28.0	30.9	30.6
	Recall@100	75.4	76.1	70.2	81.7	63.5	59.5	65.6	69.1	68.2	82.2	72.4	71.2	71.3

Through the detailed results, we demonstrate that our proposed MSM has consistent improvements over others in average results and most languages. Interestingly though only fine-tuning on English data, MSM also achieves more gains in other languages. For example, MSM improves more than 4% on recall@100 on BN, FI, TE, and TH compared to XLMR, which means it leads to better cross-lingual transfer compared to others. We dig deeper with more analysis in Sec.5.4 on the emergence of cross-lingual transfer ability. Another observation is that learning from two views of the same document (i.e. ICT and CROP) can achieve competitive results. Yet compared to them, MSM achieves more gains especially in low-resource languages, which indicates modeling sequential sentence relation across languages is indeed beneficial for cross-lingual retrieval. More detailed results across different languages on other tasks including Mewsli-X and LAReQA can be seen in Appendix A.2.

5.4 ANALYSIS OF CROSS-LINGUAL ABILITY

To investigate why MSM can advantage cross-lingual retrieval and how the cross-lingual ability emerges, we design some analytical experiments. Recall that in the zero-shot transfer setting, the pre-trained model is first fine-tuned on English data and then evaluated on all languages, which relies on the cross-lingual transfer ability from *en* to others. So in this experiment, we set individual the document encoder for *en* language and other languages to break the sentence relation shared between *en* and others, to see how it impacts the retrieval performance.

In Table.4, we report the results of different settings: Share All mean the original MSM where the document encoder is shared for all languages, Sep Doc sets two separate document encoder for *EN* and others, and Sep Doc + Head separates both encoder and projection head. The results clearly show that if *EN* and others don't share the same document encoder or projection head, the cross-lingual transfer ability drops rapidly. The previous works on multi-lingual BERTology (Conneau et al., 2020; Artetxe et al., 2020; Rogers et al., 2020) found the shared model can learn the universal word embeddings across languages. Similar to it, our experiments indicate that the shared document encoder benefits universal sentence embedding. This experiment further demonstrates that the sequential sentence relation is universal across languages, and modeling this relation is helpful for cross-lingual retrieval.

5.5 ABLATION STUDY

In this section, we conduct the ablation study on several components in our model. Considering computation efficiency and for a fair comparison, we fine-tune all the pre-trained models on NQ dataset and evaluate them on the target data, which is a default setting in their original papers (Zhang et al., 2021b; Asai et al., 2021a).

Ablation of Loss Function. We first study the effectiveness of the hierarchical contrastive loss proposed in Eq.1. As shown in Table.5, $Cross\text{-}doc$ means only using cross-doc negatives without the intra-doc negatives. It results in poor performance due to the lack of utilization of intra-doc samples' information. When w/o bias, it leads to a significant decrease for it regards intra-doc sentences as negatives, which would harm the representation space as we stated in Sec.3.2. We can change the hyper μ to tune the impact of intra-doc negatives, and it gets the best results when setting μ at an appropriate value, which indicates ours can contribute to better representation learning.

Table 5: Comparison of different settings for the hierarchical contrastive loss.

Setting	Mr. TyDi		XOR Retrieve	
	MRR@100	R@100	R@2k	R@5k
Cross-doc	32.9	73.9	33.2	41.6
w/o bias α	31.1	73.1	29.8	39.9
$\mu = 0.3$	31.7	73.3	31.0	41.5
$\mu = 0.5$	**34.0**	**74.9**	**34.9**	**44.7**
$\mu = 0.7$	32.5	74.2	34.7	44.2

Table 6: Impact of contrastive negatives number. Best are marked bold.

Size	Mr. TyDi		XOR Retrieve	
	MRR@100	R@100	R@2k	R@5k
256	31.4	73.6	33.2	42.9
512	**34.0**	**74.9**	**34.9**	**44.7**
1024	32.0	73.9	32.1	42.4
4096	31.8	72.8	32.3	43.2

Table 7: Impact of the projector settings. Best are marked bold.

Setting	Mr. TyDi		XOR Retrieve	
	MRR@100	R@100	R@2k	R@5k
w/o PL	27.0	66.1	30.3	39.1
Shared PL	32.1	71.0	34.5	43.8
Asymmetric PL	**34.0**	**74.9**	**34.9**	**44.7**

Table 8: Comparison of different document encoder layers. Best are marked bold.

Layers	Mr. TyDi		XOR Retrieve	
	MRR@100	R@100	R@2k	R@5k
1	29.7	71.4	33.1	42.2
2	**34.0**	**74.9**	**34.9**	**44.7**
4	33.3	74.4	34.3	44.9
6	30.9	71.4	34.2	43.9

Impact of Contrastive Negative Size. We analyze how the number of negatives influences performance and range the negative size from 256 to 4096 in our experiments. As shown in Table.6, the performance increase as the size of the negatives become larger and it has diminishing gain if the batch is sufficiently large. Interestingly the model performance does not improve with continually increasing batch size, which has been also observed in some work (Cao et al., 2022) on contrastive learning for text representations. In our work, it may be due to that the number of intra-document negatives is limited and when the total size of negatives increased, the impact of intra-document negatives would be diminished.

Impact of Projector Setting. Existing work has shown the projection layers (Dong et al., 2022; Cao et al., 2022) between the representation and the contrastive loss in contrastive learning affect the quality of learned representations. We explore the impact of projection layer under different configurations in Tab.7. Referring to Fig.1, Shared PL means the two projection layers for contrastive learning share the same parameters, and Asymmetric PL means not sharing the layers. We adopt the nonlinear projector network during pre-training and discard it in the fine-tuning stage. The results show that using an asymmetric projection head performs better than others and the removal of projection layers badly degrades the performance. One possible reason is that the projection layer can bridge the semantic gap between the representation of different samples in the embedding spaces.

Impact of Decoder Layers. We explore the impact of the size of document encoder layers in Table.8 and find a two-layer document encoder can achieve the best results. When the document encoder only has one layer, its capability is not enough to model sequential sentence relation, resulting in inefficient utilization of information. When the layer increase to larger, the masked sentence prediction task may depend more on the document encoder's ability and causes degradation of sentence representations, which is also in line with the findings of (Wu et al., 2022b; Lu et al., 2021).

6 CONCLUSION

In this paper, we propose a novel masked sentence model which leverages sequential sentence relation for pre-training to improve cross-lingual retrieval. It contains a two-level encoder in which the document encoder applied to the sentence vectors generated by the sentence encoder from a sequence of sentences. Then we propose a masked sentence prediction task to train the model, which masks and predicts the selected sentence vector via a hierarchical contrastive loss with sampled negatives. Through comprehensive experiments on 4 cross-lingual retrieval benchmark datasets, we demonstrate that MSM significantly outperforms existing advanced pre-training methods. Our further analysis and detailed ablation study clearly show the effectiveness and stronger cross-lingual retrieval capabilities of our approach. Code and model will be made publicly available.

REFERENCES

Mikel Artetxe, Sebastian Ruder, and Dani Yogatama. On the cross-lingual transferability of mono-lingual representations. In *ACL*, 2020.

Akari Asai, Jungo Kasai, Jonathan Clark, Kenton Lee, Eunsol Choi, and Hannaneh Hajishirzi. XOR QA: Cross-lingual open-retrieval question answering. In *NAACL*, 2021a.

Akari Asai, Xinyan Yu, Jungo Kasai, and Hanna Hajishirzi. One question answering model for many languages with cross-lingual dense passage retrieval. *Advances in Neural Information Processing Systems*, 34:7547–7560, 2021b.

Jan A. Botha, Zifei Shan, and Daniel Gillick. Entity Linking in 100 Languages. In *EMNLP*, 2020.

Rui Cao, Yihao Wang, Yuxin Liang, Ling Gao, Jie Zheng, Jie Ren, and Zheng Wang. Exploring the impact of negative samples of contrastive learning: A case study of sentence embedding. In *Findings of ACL*, 2022.

Wei-Cheng Chang, Felix X. Yu, Yin-Wen Chang, Yiming Yang, and Sanjiv Kumar. Pre-training tasks for embedding-based large-scale retrieval. In *ICLR*, 2020.

Zewen Chi, Li Dong, Furu Wei, Nan Yang, Saksham Singhal, Wenhui Wang, Xia Song, Xian-Ling Mao, Heyan Huang, and Ming Zhou. InfoXLM: An information-theoretic framework for cross-lingual language model pre-training. In *NAACL*, 2021.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Un-supervised cross-lingual representation learning at scale. *arXiv preprint arXiv:1911.02116*, 2019.

Alexis Conneau, Shijie Wu, Haoran Li, Luke Zettlemoyer, and Veselin Stoyanov. Emerging cross-lingual structure in pretrained language models. In *ACL*, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *NAACL*, 2019.

Zhe Dong, Jianmo Ni, Dan Bikel, Enrique Alfonseca, Yuan Wang, Chen Qu, and Imed Zitouni. Exploring dual encoder architectures for question answering. *arXiv preprint arXiv:2204.07120*, 2022.

Fangxiaoyu Feng, Yinfei Yang, Daniel Cer, Naveen Arivazhagan, and Wei Wang. Language-agnostic BERT sentence embedding. In *ACL*, 2022.

Nicola Ferro and Gianmaria Silvello. Clef 2000-2014: Lessons learnt from ad hoc retrieval. In *IIR*, 2015.

Luyu Gao and Jamie Callan. Unsupervised corpus aware language model pre-training for dense passage retrieval. *arXiv preprint arXiv:2108.05540*, 2021.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. SimCSE: Simple contrastive learning of sentence embeddings. In *EMNLP*, 2021.

John Giorgi, Osvald Nitski, Bo Wang, and Gary Bader. DeCLUTR: Deep contrastive learning for unsupervised textual representations. In *ACL*, 2021.

Junjie Hu, Sebastian Ruder, Aditya Siddhant, Graham Neubig, Orhan Firat, and Melvin Johnson. Xtreme: A massively multilingual multi-task benchmark for evaluating cross-lingual generalisa-tion. In *ICML*, pp. 4411–4421. PMLR, 2020.

Haoyang Huang, Yaobo Liang, Nan Duan, Ming Gong, Linjun Shou, Daxin Jiang, and Ming Zhou. Unicoder: A universal language encoder by pre-training with multiple cross-lingual tasks. *arXiv preprint arXiv:1909.00964*, 2019.

Kung-Hsiang Huang, ChengXiang Zhai, and Heng Ji. Concrete: Improving cross-lingual fact-checking with cross-lingual retrieval. *arXiv preprint arXiv:2209.02071*, 2022.

Dan Iter, Kelvin Guu, Larry Lansing, and Dan Jurafsky. Pretraining with contrastive sentence objectives improves discourse performance of language models. In *ACL*, 2020.

Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. Towards unsupervised dense information retrieval with contrastive learning. *arXiv preprint arXiv:2112.09118*, 2021.

Xiaoze Jiang, Yaobo Liang, Weizhu Chen, and Nan Duan. Xlm-k: Improving cross-lingual language model pre-training with multilingual knowledge. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 10840–10848, 2022.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick S. H. Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *EMNLP*, 2020.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: A benchmark for question answering research. *TACL*, 2019.

Guillaume Lample and Alexis Conneau. Cross-lingual language model pretraining. *arXiv preprint arXiv:1901.07291*, 2019.

Kenton Lee, Ming-Wei Chang, and Kristina Toutanova. Latent retrieval for weakly supervised open domain question answering. In *ACL*, 2019.

Chunyuan Li, Xiang Gao, Yuan Li, Baolin Peng, Xiujun Li, Yizhe Zhang, and Jianfeng Gao. Optimus: Organizing sentences via pre-trained modeling of a latent space. In *EMNLP*, November 2020.

Yulong Li, Martin Franz, Md Arafat Sultan, Bhavani Iyer, Young-Suk Lee, and Avirup Sil. Learning cross-lingual ir from an english retriever. *arXiv preprint arXiv:2112.08185*, 2021.

Yaobo Liang, Nan Duan, Yeyun Gong, Ning Wu, Fenfei Guo, Weizhen Qi, Ming Gong, Linjun Shou, Daxin Jiang, Guihong Cao, Xiaodong Fan, Ruofei Zhang, Rahul Agrawal, Edward Cui, Sining Wei, Taroon Bharti, Ying Qiao, Jiun-Hung Chen, Winnie Wu, Shuguang Liu, Fan Yang, Daniel Campos, Rangan Majumder, and Ming Zhou. XGLUE: A new benchmark datasetfor cross-lingual pre-training, understanding and generation. In *EMNLP*, 2020.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692, 2019.

Shuqi Lu, Di He, Chenyan Xiong, Guolin Ke, Waleed Malik, Zhicheng Dou, Paul Bennett, Tie-Yan Liu, and Arnold Overwijk. Less is more: Pretrain a strong Siamese encoder for dense text retrieval using a weak decoder. In *EMNLP*, 2021.

Xinyu Ma, Jiafeng Guo, Ruqing Zhang, Yixing Fan, and Xueqi Cheng. Pre-train a discriminative text encoder for dense retrieval via contrastive span prediction. *arXiv preprint arXiv:2204.10641*, 2022.

Zhengyi Ma, Zhicheng Dou, Wei Xu, Xinyu Zhang, Hao Jiang, Zhao Cao, and Ji-Rong Wen. Pre-training for ad-hoc retrieval: hyperlink is also you need. In *CIKM*, pp. 1212–1221, 2021.

Jian-Yun Nie. Cross-language information retrieval. *Synthesis Lectures on Human Language Technologies*, 3(1):1–125, 2010.

Barlas Oğuz, Kushal Lakhotia, Anchit Gupta, Patrick Lewis, Vladimir Karpukhin, Aleksandra Piktus, Xilun Chen, Sebastian Riedel, Wen-tau Yih, Sonal Gupta, et al. Domain-matched pre-training tasks for dense retrieval. *arXiv preprint arXiv:2107.13602*, 2021.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Xuan Ouyang, Shuohuan Wang, Chao Pang, Yu Sun, Hao Tian, Hua Wu, and Haifeng Wang. ERNIE-M: Enhanced multilingual representation by aligning cross-lingual semantics with monolingual corpora. In *EMNLP*, 2021.

Yingqi Qu, Yuchen Ding, Jing Liu, Kai Liu, Ruiyang Ren, Wayne Xin Zhao, Daxiang Dong, Hua Wu, and Haifeng Wang. RocketQA: An optimized training approach to dense passage retrieval for open-domain question answering. In *NAACL*, 2021.

Revanth Gangi Reddy, Vikas Yadav, Md Arafat Sultan, Martin Franz, Vittorio Castelli, Heng Ji, and Avirup Sil. Towards robust neural retrieval models with synthetic pre-training. *arXiv preprint arXiv:2104.07800*, 2021.

Philip Resnik. Parallel strands: a preliminary investigation into mining the web for bilingual text. In *Proceedings of the Third Conference of the Association for Machine Translation in the Americas: Technical Papers*, 1998.

Anna Rogers, Olga Kovaleva, and Anna Rumshisky. A primer in bertology: What we know about how bert works. *Transactions of the Association for Computational Linguistics*, 2020.

Uma Roy, Noah Constant, Rami Al-Rfou, Aditya Barua, Aaron Phillips, and Yinfei Yang. LAReQA: Language-agnostic answer retrieval from a multilingual pool. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

Sebastian Ruder, Noah Constant, Jan Botha, Aditya Siddhant, Orhan Firat, Jinlan Fu, Pengfei Liu, Junjie Hu, Dan Garrette, Graham Neubig, and Melvin Johnson. XTREME-R: Towards more challenging and nuanced multilingual evaluation. In *EMNLP*, 2021.

Bishal Santra, Potnuru Anusha, and Pawan Goyal. Hierarchical transformer for task oriented dialog systems. In *NAACL*, June 2021.

Peng Shi, Rui Zhang, He Bai, and Jimmy Lin. Cross-lingual training of dense retrievers for document retrieval. In *Proceedings of the 1st Workshop on Multilingual Representation Learning*, 2021.

Shuo Sun and Kevin Duh. CLIRMatrix: A massively large collection of bilingual and multilingual datasets for cross-lingual information retrieval. In *EMNLP*, 2020.

Yu Sun, Shuohuan Wang, Yukun Li, Shikun Feng, Hao Tian, Hua Wu, and Haifeng Wang. Ernie 2.0: A continual pre-training framework for language understanding. In *AAAI*, pp. 8968–8975, 2020.

Brian Thompson and Philipp Koehn. Exploiting sentence order in document alignment. In *EMNLP*, 2020.

Xiangpeng Wei, Rongxiang Weng, Yue Hu, Luxi Xing, Heng Yu, and Weihua Luo. On learning universal representations across languages. *arXiv preprint arXiv:2007.15960*, 2020.

Guillaume Wenzek, Marie-Anne Lachaux, Alexis Conneau, Vishrav Chaudhary, Francisco Guzmán, Armand Joulin, and Edouard Grave. Ccnet: Extracting high quality monolingual datasets from web crawl data. *arXiv preprint arXiv:1911.00359*, 2019.

Ning Wu, Yaobo Liang, Houxing Ren, Linjun Shou, Nan Duan, Ming Gong, and Daxin Jiang. Unsupervised context aware sentence representation pretraining for multi-lingual dense retrieval. *arXiv preprint arXiv:2206.03281*, 2022a.

Xing Wu, Guangyuan Ma, Meng Lin, Zijia Lin, Zhongyuan Wang, and Songlin Hu. Contextual mask auto-encoder for dense passage retrieval. *arXiv preprint arXiv:2208.07670*, 2022b.

Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul Bennett, Junaid Ahmed, and Arnold Overwijk. Approximate nearest neighbor negative contrastive learning for dense text retrieval. *CoRR*, abs/2007.00808, 2020.

Xiaohui Yan, Jiafeng Guo, Yanyan Lan, and Xueqi Cheng. A biterm topic model for short texts. In *Proceedings of the 22nd international conference on World Wide Web*, pp. 1445–1456, 2013.

Peilin Yang, Hui Fang, and Jimmy Lin. Anserini: Enabling the use of lucene for information retrieval research. In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pp. 1253–1256, 2017.

Hang Zhang, Yeyun Gong, Yelong Shen, Weisheng Li, Jiancheng Lv, Nan Duan, and Weizhu Chen. Poolingformer: Long document modeling with pooling attention. In *International Conference on Machine Learning*, pp. 12437–12446. PMLR, 2021a.

Xingxing Zhang, Furu Wei, and Ming Zhou. HIBERT: Document level pre-training of hierarchical bidirectional transformers for document summarization. In *ACL*, 2019.

Xinyu Zhang, Xueguang Ma, Peng Shi, and Jimmy Lin. Mr. TyDi: A multi-lingual benchmark for dense retrieval. In *Proceedings of the 1st Workshop on Multilingual Representation Learning*, 2021b.

Xinyu Zhang, Kelechi Ogueji, Xueguang Ma, and Jimmy Lin. Towards best practices for training multilingual dense retrieval models. *arXiv preprint arXiv:2204.02363*, 2022.

Jiawei Zhou, Xiaoguang Li, Lifeng Shang, Lan Luo, Ke Zhan, Enrui Hu, Xinyu Zhang, Hao Jiang, Zhao Cao, Fan Yu, Xin Jiang, Qun Liu, and Lei Chen. Hyperlink-induced pre-training for passage retrieval in open-domain question answering. In *ACL*, 2022.

A   APPENDIX

A.1   HYPER-PARAMETERS OF FINE-TUNING

Mr. TyDi. We mainly follow the open-source codebase DPR (Karpukhin et al., 2020) with minor modifications for multi-lingual models. When fine-tuned on MS MARCO in the zero-shot setting, we use AdamW optimizer with a learning rate of 2e-5. The model is trained for up to 3 epochs with a mini-batch size of 64. When fine-tuning on the NQ dataset, it is up to 40 epochs with a mini-batch size of 128. When further fine-tuning on Mr. TyDi's in-language data, it is 40 epochs, mini-batch size 128, and 1e-5 learning rate. Note all of them mainly follow what the original papers (Zhang et al., 2021b; 2022) suggest. All these experiments are conducted on 8 NVIDIA Tesla A100 GPUs.

XOR Retrieve. Similar to the settings of the previous one, we use AdamW Optimizer with a learning rate of 2e-5. The model is trained up to 40 epochs with a mini-batch size of 128 when fine-tuning on NQ dataset. And when further tuning on XOR's data, the hyper-parameter remains the same. We evaluate all the compared pre-trained models in the same pipelines on 8 NVIDIA Tesla A100 GPUs.

Mewsli-X. We mainly follow the setting of XTREME-R (Hu et al., 2020). It adopts a 2e-5 learning rate, and it is trained for up to 2 epochs with batch size of 16. As the original paper suggests, all the evaluations are conducted on NVIDIA Tesla V100 GPU for a fair comparison.

LAReQA. It also follows the setting proposed by XTREME-R (Hu et al., 2020). It adopts a 2e-5 learning rate and it is trained up to 3 epochs with batch size of 4. All the evaluations are conducted on NVIDIA Tesla V100 GPU.

A.2   DETAILED RESULTS ACROSS LANGUAGES

We show the detailed results for each task across different languages corresponding to Table.1. Specifically, the results of Mr. TyDi are as shown in Table.9, XOR Retrieve in Table.10, Mewsli-X in Table.11, and LAReQA in Table.12.

A.3   MONOLINGUAL EXPERIMENT

We adapt our MSM pre-training method to the monolingual domain, in which we narrow the train corpus and model to English only. We initialize the sentence encoder with ERNIE-2.0-Large and others adopt the same setting to our multi-lingual experiment. In Table.13, we report the performance on the Natural Question (Kwiatkowski et al., 2019) test set after fine-tuning. It shows that our

Table 9: Mr. TyDi results across languages. We report MRR@100 and Recall@100 on the test sets of Mr. TyDi in the two settings.

Method	Metrics	AR	BN	EN	FI	ID	JA	KO	RU	SW	TE	TH	AVG
Cross-lingual zero-shot transfer (models are fine-tuned on English data)													
mBERT	MRR@100	45.3	38.8	29.1	28.7	35.5	29.6	29.8	32.6	27.8	40.8	25.3	33.0
	Recall@100	77.8	84.7	73.8	65.8	72.9	68.4	59.9	71.1	56.4	76.8	59.2	69.7
XLMR	MRR@100	43.8	41.2	29.3	33.2	45.4	27.0	33.4	32.2	35.3	44.5	49.7	37.7
	Recall@100	77.4	81.5	68.5	72.2	81.8	61.2	66.5	66.4	63.9	75.5	85.4	72.8
MSM	MRR@100	51.6	53.0	31.6	39.4	50.5	32.0	36.8	37.2	43.4	62.6	53.5	44.7
	Recall@100	83.0	83.8	73.9	77.9	85.7	67.5	70.3	71.4	73.0	89.8	88.2	78.6
Multi-lingual fine-tune (models are fine-tuned on the multi-lingual data)													
mBERT	MRR@100	66.8	63.3	50.8	55.0	55.7	47.8	43.3	47.3	60.5	85.8	57.7	57.6
	Recall@100	90.3	95.0	89.0	85.8	89.3	81.6	80.2	85.6	86.7	96.3	87.2	87.9
XLMR	MRR@100	66.4	66.0	48.5	53.7	58.3	45.4	44.3	47.4	61.4	86.2	65.7	58.5
	Recall@100	89.4	93.2	84.3	86.6	90.0	82.3	79.3	82.8	86.4	97.4	93.8	87.8
MSM	MRR@100	67.7	69.9	49.6	55.1	61.2	48.2	49.4	47.5	63.9	85.2	67.7	60.5
	Recall@100	90.5	95.9	86.5	88.0	90.1	82.0	81.6	82.5	88.9	97.6	95.0	89.0

Table 10: XOR Retrieve results across languages. We report R@2k and R@5 metrics on the test sets in the two settings.

Method	Metrics	AR	BN	FI	JA	KO	RU	TE	AVG
Cross-lingual zero-shot transfer (models are fine-tuned on English data)									
mBERT	R@2k	31.1	26.6	38.5	32.4	38.6	24.9	29.1	31.6
	R@5k	44.1	36.2	48.1	41.5	48.1	38.4	39.5	42.3
XLMR	R@2k	39.9	25.7	41.1	27.8	31.9	22.4	25.2	30.6
	R@5k	49.6	34.9	50.0	34.9	41.8	30.4	34.0	39.3
MSM	R@2k	47.9	32.6	44.9	24.1	35.8	25.3	34.0	34.9
	R@5k	58.4	41.8	51.9	36.9	44.6	37.6	42.1	44.7
Multi-lingual fine-tune (models are fine-tuned on the multi-lingual data)									
mBERT	R@2k	51.7	52.7	52.2	41.9	51.9	47.5	40.5	48.3
	R@5k	58.4	61.5	58.6	50.6	63.2	54.9	51.8	57.0
XLMR	R@2k	59.2	48.7	46.8	36.1	46.0	35.4	43.4	45.1
	R@5k	67.2	58.6	53.5	45.6	56.1	45.1	51.5	53.9
MSM	R@2k	61.8	55.3	51.3	36.9	50.5	41.4	43.0	48.6
	R@5k	68.9	63.8	59.9	48.1	56.1	52.7	51.5	57.3

proposed unsupervised model achieves better performance than strong baselines including BERT and advanced ERNIE2.0 (Sun et al., 2020). It further proves our MSM is a general pre-training method tailored for dense retrieval including monolingual and multi-lingual domains.

A.4 SCALE TO LARGE-SIZE MODEL

Table 14 shows the results of large-size MSM model initialized with XLMR-Large. All compared models are in large-size except for mBERT for it only has the base-size model. LABSE (Feng et al., 2022) and InfoXLM (Chi et al., 2021) encourage bilingual alignment via a translation ranking loss. They all use additional bi-lingual parallel corpora and also adopt MLM and TLM tasks. CCP (Wu et al., 2022a) proposed a contrastive context prediction task to utilize neighboring sentences for contrastive learning. And InfoXLM and CCP are both initialized with XLMR-Large. Compared with these advanced methods, MSM achieves a significant performance improvement, which further demonstrates the effectiveness of our approach.

Table 11: Mewsli-X results across different input languages. We report the mean average precision@20 (mAP@20) results.

Method	AR	DE	EN	ES	FA	JA	PL	RO	TA	TR	UK	AVG
Cross-lingual zero-shot transfer (models are fine-tuned on English data)												
mBERT	14.2	65.5	57.4	55.7	11.3	44.8	57.2	38.2	5.8	42.7	36.2	39.0
XLMR	15.5	62.7	57.2	53.5	12.5	46.2	59.3	34.1	7.5	51.8	36.0	39.7
MSM	18.6	68.0	58.7	57.3	13.7	46.3	60.2	36.3	7.6	52.8	37.3	**41.5**

Table 12: LAReQA results across different question languages. We report the mean average precision@20 (mAP@20) results.

Method	AR	DE	EL	EN	ES	HI	RU	TH	TR	VI	ZH	AVG
Cross-lingual zero-shot transfer (models are fine-tuned on English data)												
mBERT	20.1	32.2	19.9	34.8	33.5	15.3	29.6	7.2	23.3	27.6	26.2	24.5
XLMR	21.4	31.7	26.7	36.7	34.3	25.2	32.3	27.8	29.0	29.1	28.5	29.3
MSM	28.0	36.1	31.9	40.6	38.3	29.4	36.0	30.2	34.3	33.2	29.7	**33.4**

Table 13: Monolingual Retrieval performance on Natural Question test. The best performing models are marked bold and the results unavailable are left blank.

Method	R@5	R@20	R@100
BM25 (Yang et al., 2017)	-	59.1	73.7
BERT (Karpukhin et al., 2020)	-	78.4	85.3
RoBERTa (Liu et al., 2019)	64.9	76.8	84.7
ERNIE2.0 (Sun et al., 2020)	68.7	79.8	86.1
MSM (ours)	**69.3**	**80.3**	**86.5**

Table 14: Performance of large-size models on Mr. TyDi across languages. mBERT only has the base-size model and the others are all large-size models.

Method	Metrics	AR	BN	EN	FI	ID	JA	KO	RU	SW	TE	TH	AVG
mBERT	MRR@100	45.3	38.8	29.1	28.7	35.5	29.6	29.8	32.6	27.8	40.8	25.3	33.0
	Recall@100	77.8	84.7	73.8	65.8	72.9	68.4	59.9	71.1	56.4	76.8	59.2	69.7
XLMR	MRR@100	36.5	37.4	27.5	31.8	39.5	29.9	30.4	30.6	27.4	34.6	40.1	33.3
	Recall@100	81.3	84.2	77.6	78.2	88.6	78.5	72.7	77.4	63.3	87.5	88.2	79.8
LABSE	MRR@100	37.3	35.4	32.5	30.0	38.0	31.0	29.9	31.3	35.1	31.1	40.0	33.8
	Recall@100	80.6	86.0	80.4	74.9	86.9	78.8	71.7	76.7	72.4	86.7	87.4	80.2
InfoXLM	MRR@100	37.2	50.4	31.4	30.9	37.6	27.1	30.9	32.5	39.4	46.5	37.4	36.5
	Recall@100	76.2	91.0	78.3	76.0	85.2	66.9	64.4	74.4	75.0	88.9	83.4	78.2
CCP	MRR@100	42.6	45.7	35.9	37.2	46.2	37.7	34.6	36.0	39.2	47.0	48.9	41.0
	Recall@100	82.0	88.3	80.1	78.7	87.5	80.0	73.2	77.2	75.1	88.8	88.9	81.8
MSM	MRR@100	53.8	51.2	35.3	42.7	51.8	37.5	39.6	39.1	38.5	65.0	56.9	**46.5**
	Recall@100	88.4	91.9	77.8	84.3	88.6	75.6	74.3	76.8	69.3	94.3	90.7	**82.9**