The future is log-Gaussian: ResNets and their infinite-depth-and-width limit at initialization

Abstract

Theoretical results show that neural networks can be approximated by Gaussian processes in the infinite-width limit. However, for fully connected networks, it has been previously shown that for any fixed network width, n, the Gaussian approximation gets worse as the network depth, d, increases. Given that modern networks are deep, this raises the question of how well modern architectures, like ResNets, are captured by the infinite-width limit. To provide a better approximation, we study ReLU ResNets in the infinite-depth-and-width limit, where *both* depth and width tend to infinity as their ratio, d/n, remains constant. In contrast to the Gaussian infinite-width limit, we show theoretically that the network exhibits log-Gaussian behaviour at initialization in the infinite-depth-and-width limit, with parameters depending on the ratio d/n. Using Monte Carlo simulations, we demonstrate that even basic properties of standard ResNet architectures are poorly captured by the Gaussian limit, but remarkably well captured by our log-Gaussian limit. Moreover, our analysis reveals that ReLU ResNets at initialization are hypoactivated: fewer than half of the ReLUs are activated. Additionally, we calculate the interlayer correlations, which have the effect of exponentially increasing the variance of the network output. Based on our analysis, we introduce *Balanced ResNets*, a simple architecture modification, which eliminates hypoactivation and interlayer correlations and is more amenable to theoretical analysis.

1 Introduction

The characterization of infinite-width dynamics of gradient descent (GD) in terms of the so-called Neural Tangent Kernel (NTK) [1–8] represented a major breakthrough in our understanding of deep learning in the large-width regime. Before the identification of infinite-width limits, the theoretical study of deep learning had long been hindered by the apparent analytical intractability of gradient descent and variants acting on the nonconvex objectives used to train neural networks. Despite this progress, evidence suggests that deep neural networks can outperform their infinite-width limits in practice [9], particularly when the depth of the network is large. These observations motivate the study of other approximations that may close the gap.

Several alternative limits have been proposed. Around the time of the discovery of the NTK limit, mean-field limits were also characterized [10–13], and more recently have been linked with the NTK limit [14]. Yang and Hu [15] describe a family of infinite-width limits indexed by the scaling limits of initial weight variance, weight rescaling, and learning rates. This family includes both the NTK and mean field limits. One motivation for studying these alternative limits is that they yield a notion of feature learning, which provably does not occur in the NTK limit [15].

Despite the variety of these limits, one common feature is that the *depth* of the network (i.e., the number of its layers) is treated as a constant as the width of the network is allowed to grow. Indeed,

Figure 1: **Probability density function of** $\ln \|z^{\text{out}}\|^2$ for six network configurations on initialization. All networks have $n = 100, n_{\text{in}} = n_{\text{out}} = 10, \alpha = \lambda = 1/\sqrt{2}$. Depth d varies by column. Top row: Vanilla ReLU ResNets. Bottom Row: Balanced ResNets (Section 2.2), which randomize the non-linearities used at each neuron thereby exponentially reducing the variance. The theoretical curves shown are the result of Theorem 1 and Theorem 4. These predictions converge to the infinite-width prediction when $d/n \to 0$. The details of the simulations and plot here is in Appendix C.

for fixed width, n, the Gaussian approximations at initialization [16–21] worsen as the depth, d, increases. While real-world networks are fairly wide, their relative depth is not trivial. Hanin and Nica [22] were the first to compute an infinite-depth-and-width limit for fully connected networks. While the training dynamics of this limit are still not completely understood, we now know that, in the infinite-depth-and-width limit, the neural tangent kernel is random, and the derivative of the kernel is nonzero at initialization. This means training does not correspond to that of a linear model, like it does in the NTK limit [23, 24].

In addition to these theoretical corrections to the Gaussian limit, practitioners have begun to notice that even basic properties of standard neural networks do not line up with those predicted by the infinite-width limit. Perhaps the most basic is that the gradients of the network early in training are not Gaussian, but instead are approximately log-Gaussian [25]. In fact, one should see log-Gaussian behaviour agrees with the theoretical predictions of Hanin and Nica [22], although there has yet to be a careful empirical comparison made between the precise predictions coming from infinite-depth-and-width models and real world networks.

In practice, however, fully connected networks are not often used without architectural modifications. Instead, variations such as the ResNet [26] seem to be much more practically useful, especially for very deep networks.That being said, the theoretical analysis of ResNets is more complicated than for fully connected networks due to the skip connections. These connections introduce interlayer correlations that have a non-negligible effect in the infinite-depth-and-width limit. We also observe a counterintuitave phenomenon whereby these skip connection cause the network to be hypoactivated, meaning that less than half of the neurons are activated on initialization.

In this work, we find a simple approximation that captures the effect of interlayer correlation and hypoactivation. Using this, we prove a limit theorem characterizing the marginal distribution of the output at initialization in the infinite-depth-and-width limit up to order $O(dn^{-2})$.

Our result shows that ResNets have *log-Gaussian behaviour* on initialization, and like fully connected networks [22], the behaviour is determined by the depth-to-width aspect ratio. This corroborates recent empirical observations about deep ResNets [25]. Since real world networks are finite, the question of how well this approximates finite behaviour is of paramount importance. Based on

Monte Carlo simulations, we find excellent agreement between our predictions and finite networks (see Figure 1). Moreover, for very deep networks (e.g. $d/n = 1$) the infinite-depth-and-width prediction is extremely different than the infinite-width prediction. More surprisingly, however, is that even at comparatively small depth-to-width ratio (e.g. $d/n = 0.1$) the two limits are already significantly different. Furthermore, we also observe that the effects due to hypoactivation and interlayer correlation are non-negligible; these effects are precisely the difference between Balanced ResNets and Vanilla ResNets in Figure 1. Perhaps most importantly, we observe that real network outputs exhibit exponentially larger variance than predicted by the infinite-width limits. This type of variance at initialization is known to cause exploding and vanishing gradients and other types of training failures [27, 28]. Our result also implies that the output neurons of the network are not independent as predicted by the Gaussian infinite-width limit. See Figure 3.

We introduce the Balanced ResNet architecture, which maintains the same skip connections from layer to layer, but makes the activation patterns completely independent from layer to layer on initialization. This is achieved by randomizing the activation function used at each neuron. We demonstrate that this exponentially decreases the variance of the network output on initialization. Moreover, this independence between neurons also makes the model more amenable to theoretical analysis and opens the door to future understanding of network behaviour. Although it is beyond the scope of this paper, a small preliminary empirical study (Appendix C) suggests that standard training regimes are not negatively affected by replacing ResNet architectures with Balanced ResNets ones.

1.1 Contributions

- We show that ResNets have **interlayer activation dependencies** that persist in the **infinite-depth-and-width limit**. These dependencies cause the network to be **hypoactivated**: less than half the ReLU neurons are activated. We construct an approximation for these interlayer correlations and hypoactivation which is verified by Monte Carlo simulations.

- We prove a limit theorem which shows that the output of ResNets on initialization exhibits **log-Gaussian** behaviour with parameterization depending on the depth-to-width ratio d/n.

- We provide **empirical evidence** from Monte Carlo simulations showing our theory provides more accurate predictions for simple properties of finite networks compared to the predictions made by the Gaussian infinite-width limit.

- We introduce the *Balanced ResNet* **architecture**, which corrects the hypoactivation and variance due to layerwise correlation from Vanilla ResNets. We also prove that the output for this architecture is log-Gaussian on initialization with exponentially lower variance. This simple modification can be applied to *any* neural network that uses ReLU activations.

2 Main Results

2.1 Log-Gaussian Behaviour of Vanilla ResNets

In terms of the notation in Table 1, a **Vanilla ResNet** with fully connected first/last layers and d hidden layers of width n is defined by

$$z^0 := \frac{1}{\sqrt{n_{\text{in}}}} W^0 x, \quad z^\ell := \alpha z^{\ell-1} + \lambda \sqrt{\frac{2}{n}} W^\ell \varphi_+ \left(z^{\ell-1} \right) \text{ for } 1 \le \ell \le d, \quad z^{\text{out}} := \frac{1}{\sqrt{n}} W^{\text{out}} z^d . \quad (1)$$

Note that factors of $\sqrt{2n^{-1}}$ in the hidden layer are equivalent to intializing according to the so-called He initialization [29]. Other intializations correspond to changing the coefficient λ. This setup is similar to that of "Stable ResNets" [30], where the infinite-width limit is studied.

In the infinite-depth-and-width limit, the intuition that half of the ReLU units are active (i.e. nonzero) because of symmetry is surprisingly not correct. We find that the following quantities play an important role. We define the **average hypoactivation (of layer ℓ)** and the **total hypoactivation of the network** by

$$h_\ell := \mathbf{E}\left[\left\| \varphi_+ \left(\hat{z}^\ell \right) \right\|^2 \right] - \frac{1}{2}, \qquad h_{\text{total}} := \sum_{\ell=1}^{d} h_\ell, \quad (2)$$

where $\hat{z}^\ell := z^\ell / \left\| z^\ell \right\|$ and $\mathbf{E}$ means expectation over the choice of random network weights on initialization. The average hypoactivation is a measure of how many ReLU neurons are activated in

Notation	Description	Notation	Description	Table 1: Notation
$n_{\text{in}} \in \mathbb{N}$	Input dimension	$n_{\text{out}} \in \mathbb{N}$	Output dimension	
$n \in \mathbb{N}$	Hidden layer width	$d \in \mathbb{N}$	Number of hidden layers (depth)	
$\varphi_+(\cdot)$	ReLU function $\varphi_+(x) = \max\{x, 0\}$	$\varphi_-(\cdot)$	"Domain Flipped" ReLU $\varphi_-(x) = \max\{-x, 0\}$	
$\alpha \in \mathbb{R}$	Skip connection coefficient	$\lambda \in \mathbb{R}^+$	Feed-forward coefficient	
$x \in \mathbb{R}^{n_{\text{in}}}$	Input	$W^0 \in \mathbb{R}^{n_{\text{in}} \times n}$	Weight matrix at layer 0	
$z^{\text{out}} \in \mathbb{R}^{n_{\text{out}}}$	Network output	$W^{\text{out}} \in \mathbb{R}^{n \times n_{\text{out}}}$	Weight matrix at final layer.	
$z^\ell \in \mathbb{R}^n$	Neurons (pre-activation) for layer $1 \leq \ell \leq d$	$W^\ell \in \mathbb{R}^{n \times n}$	Weight matrix at layer $1 \leq \ell \leq d$ all weights initialized i.i.d. $\sim \mathcal{N}(0,1)$	

layer ℓ; $h_\ell = 0$ indicates roughly half of the neurons are active. Counter-intuitively, we observe that in a vanilla ResNet, h_ℓ is *negative* and $|h_\ell| = O(1/n)$, indicating slightly less than half the neurons are active.[1] After compounding over d layers, the total hypoactivation is of order $h_{\text{total}} = O(d/n) = O(1)$ in the infinite-depth-and-width limit. As we will see, this effect has a non-trivial contribution.

At the same time, we also find the covariance between the activations of various layers does not vanish in the infinite-depth-and-width limit. This motivates the definition of the **total interlayer covariance correction**

$$I_{\text{total}} := \sum_{1 \leq \ell \neq \ell' \leq d} \mathbf{Cov}\left(2\left\|\varphi_+\left(\hat{z}^\ell\right)\right\|^2, 2\|\varphi_+(\hat{z}^{\ell'})\|^2\right). \tag{3}$$

As with the hypoactivation, skip connections cause this term to be non-trivial. We formulate Conjecture 5, which contains a precise encapsulation of the behaviour of $\hat{z}^\ell$ we observe.

Conjecture 5 (Informal). In expectation, the layers $\hat{z}^\ell$ can be approximated by uniform random variables from the sphere up to a relative error of $O(1/n)$.

The conjecture is well supported by Monte-Carlo simulations (see Figure 4). We provide a more detailed discussion and a precise statement of Conjecture 5 in Section 4. Assuming the conjecture holds, we prove a limit theorem about the distribution of z^{out}. Informally, this says that z^{out} is **approximately a log-Gaussian scalar** times an independent Gaussian vector

$$z^{\text{out}} \approx \frac{\|x\|}{\sqrt{n_{\text{in}}}} \left(\alpha^2 + \lambda^2\right)^{\frac{d}{2}} \exp\left(\frac{1}{2}\mathcal{N}\left(-\frac{\beta}{2} + 2ch_{\text{total}}, \beta + c^2 I_{\text{total}}\right)\right) \vec{Z}, \tag{4}$$

where $\vec{Z}$ has iid $\mathcal{N}(0,1)$ entries, and β and c are defined by

$$\beta := \frac{2}{n} + \frac{d}{n} \cdot \frac{5\lambda^4 + 4\alpha^2\lambda^2}{(\alpha^2 + \lambda^2)^2}, \quad c := \frac{\lambda^2}{\alpha^2 + \lambda^2}. \tag{5}$$

The precise statement, including asymptotic error bounds, is as follows.

Theorem 1. *For any choice of hyperparameters $n_{in}, n_{out}, n, d, \alpha, \lambda$, and every input x, the output z^{out} at initialization has a marginal distribution which can be written in the form*

$$z^{out} \overset{d}{=} \frac{\|x\|}{\sqrt{n_{in}}} \left(\alpha^2 + \lambda^2\right)^{\frac{d}{2}} \exp\left(\frac{1}{2}G\right) \vec{Z}, \tag{6}$$

where $\vec{Z} \in \mathbb{R}^{n_{out}}$ is a Gaussian random vector with iid $\mathcal{N}(0,1)$ entries, $G = G(n, d, \alpha, \lambda)$ is a random variable which is independent of $\vec{Z}$ and whose distribution does not depend on n_{in}, n_{out} or x.

Consider the limit where both *the network depth $d \to \infty$ and hidden layer width $n \to \infty$ in such a way that the ratio d/n converges to a non-zero constant. In this limit, assuming that Conjecture 5 holds, then the random variable $G \in \mathbb{R}$ has the following asymptotic behaviour:*

$$\mathbf{E}[G] = -\frac{\beta}{2} + 2ch_{total} + O\left(\frac{d}{n^2}\right), \quad \mathbf{Var}[G] = \beta + c^2 I_{total} + O\left(\frac{d}{n^2}\right), \tag{7}$$

where β and c are as in (5), and moreover G converges in distribution to a Gaussian random variable with mean and variance given by (7) in this limit.

---

[1] For a quantity $f = f(n, d)$ whose dependence on width and depth may be implicit, we use the notation $f = O(d^a/n^b)$ to mean that, for all choice of constants $\alpha, \lambda, r_-, r_+ > 0$, there exists a constant $C > 0$ such that $|f(n, d)| \leq Cd^a/n^b$ for all d, n where $r_- < d/n < r_+$. This notation will allow us to state precise limit theorems when $d, n \to \infty$ with the ratio d/n converging to a constant.

(a) **E** and **Var** of G from (6) and prediction. (b) Prediction error for **E** and **Var** of G from (6).

Figure 2: Empirical mean and variance and infinite-depth-and-width prediction for the random variable $G(n, d, \alpha, \lambda)$ from (6) compared to the results of Theorems 1 & 4 . For these simulations, $\alpha = \lambda = 1/\sqrt{2}, d/n = 1$ are fixed and width n is varied on the x-axis. The error bars indicate 95% confidence interval (CI) of the Monte-Carlo simulation, with truncation at $1e{-}3$ for plotting on log-scale. The balanced ResNet predictions fall within the Monte-Carlo CI and so are not plotted on log scale. Since d/n is fixed, Figure 2b indicates the error in the asymptotic prediction of variance (7) is $O(n^{-1}) = O(dn^{-2})$ as claimed. On the other hand, the error in mean (7) is $O(n^{-2}) = O(dn^{-3})$; this is one order smaller than the statement proven in Theorem 1. A possible explanation is that the sub-leading error term in our approximation for G is mean zero.

The main ideas of the proof of Theorem 1 is given in Section 5 and the detailed proof is given in Appendix B. We also provide more explicit formulas for h_{total}, I_{total} below.

Proposition 2. *Assume Conjecture 5 is true. Then in the same infinite-depth-and-width limit as Theorem 1, the total hypoactivation h_{total} and total interlayer covariance I_{total} obey*

$$h_{total} = C_{\alpha, \lambda} \frac{d}{n} + O\left(\frac{d}{n^2}\right), \quad I_{total} = \sum_{1 \le \ell \neq \ell' \le d} \frac{\bar{J}_2(\theta_{|\ell'-\ell|}) - \bar{J}_2(\pi - \theta_{|\ell'-\ell|})}{n} + O\left(\frac{d}{n^2}\right). \quad (8)$$

Here $C_{\alpha, \lambda}$ is a constant depending on α, λ and

$$\bar{J}_2(\theta) := J_2(\theta)/\pi = 3\sin(\theta)\cos(\theta)/\pi + (1 - \theta/\pi)\left(1 + 2\cos^2\theta\right),$$

where $J_2(\theta)$ first appeared in [31], and θ_k is such that $\cos(\theta_k) = \alpha^k/(\alpha^2 + \lambda^2)^{k/2}$.

Remark 3. The Gaussian infinite-width limit predicts that the marginals of z^{out} should have the form of (6) with G being identically zero. As z^{out} depends exponentially on G, the infinite-depth-and-width limit predicts the variance is exponentially larger than the infinite-width limit. See Section 3.1 for a detailed discussion and Figure 3 for verification against finite networks.

Using Monte Carlo simulations, we estimate the constant $C_{\alpha, \lambda}$. The result of Theorem 1 is then compared against finite networks in Figure 2. Full proof can be found Appendix B.

The idea of using a scaling parameter $\alpha = 1/\sqrt{2}$ in the skip connections has been previously discovered in empirical papers but without a theoretical explanation of why this would be useful. See, e.g., [32]. Our result shows that by choosing $\alpha^2 + \lambda^2 = 1$, the prefactor in (6) does not grow with depth thereby enabling deeper networks to be trained.

In the case that $\alpha = 0$, $\lambda = 1$, the architecture reduces to a fully connected network. In this case, log-Gaussian behaviour of the network was discovered in Hanin and Nica [22]. The fully connected case is simpler because the direction vectors $\hat{z}^\ell$ are always uniformly distributed on the unit sphere and are independent from layer to layer. This means $h_\ell = 0$ and $\theta_n = 0$ which greatly simplifies the result of Theorem 1.

Furthermore, the proof easily extends to the case where the coefficients $\alpha_\ell, \lambda_\ell$ vary from layer to layer; see Appendix A.1 for the general statement. Hayou et al. [30] and Hanin and Rolnick [27] have studied ResNets where $\alpha_\ell = 1$ in every layer, but λ_ℓ is allowed to vary. The prefactor of our result in this case becomes $\prod_{\ell=1}^{d}(1^2 + \lambda_\ell^2) \approx \exp\left(\sum_{\ell=1}^{d}\lambda_\ell^2\right)$, which is akin to the behaviour found in those papers. Additionally, our result precisely quantifies the log-Gaussian behaviour and its dependence on the sequence λ_i through the parameters β and c in the infinite-depth-and-width limit.

2.2 Log-Gaussian Behaviour of Balanced ResNets

Given a collection of *iid fair random signs*, $s_i^\ell \in \{+, -\}, 1 \leq \ell \leq d, 1 \leq i \leq n$, a **balanced ResNet** is defined similarly to the Vanilla ResNet with the following modification in the hidden layers

$$z^\ell := \alpha z^{\ell-1} + \lambda\sqrt{\frac{2}{n}}W^\ell\varphi_{s^\ell}\left(z^{\ell-1}\right) \text{ for } 1 \leq \ell \leq d,$$

where at each layer the vector function $\varphi_{s^\ell} : \mathbb{R}^n \to \mathbb{R}^n$ applies either φ_+ or φ_- to the entries according to the random signs s^ℓ. More precisely, the i-th component is

$$\varphi_{s^\ell}(z)_i := \begin{cases} \varphi_+(z_i) = \max(z_i, 0), & \text{if } s_i^\ell = +, \\ \varphi_-(z_i) = \max(-z_i, 0), & \text{if } s_i^\ell = -. \end{cases}$$

An equivalent definition is the entrywise multiplication $\varphi_{s^\ell}(z) = \varphi_+(s^\ell \odot z)$. Note that the random signs s_i^ℓ are *not* trainable parameters; they are frozen on initialization. We now present a corresponding limiting theorem for Balanced ResNets.

Theorem 4. *For a balanced ResNet, the same result as Theorem 1 given in* (6) *still holds, but with the mean and variance of G given simply by*

$$\mathbf{E}[G] = -\frac{\beta}{2} + O\left(\frac{d}{n^2}\right), \quad \mathbf{Var}[G] = \beta + O\left(\frac{d}{n^2}\right). \tag{9}$$

Balanced ResNets are constructed so that the activation of each neuron is independent of all others due to the random signs s^ℓ. This eliminates the hypoactivation and variance terms which complicated the analysis of the Vanilla ResNet and necessitated Conjecture 5. Instead, for Balanced ResNets it is straightforward to compute that for any fixed $z, w \in \mathbb{R}^n$ we have

$$\mathbf{E}\left[\|\varphi_{s^\ell}(z)\|^2\right] = \frac{\|z\|^2}{2}, \mathbf{Var}\left[\|\varphi_{s^\ell}(z)\|^2\right] = \sum_{i=1}^n \frac{z_i^4}{4}, \mathbf{Cov}\left[\|\varphi_{s^\ell}(z)\|^2, \|\varphi_{s^{\ell'}}(w)\|^2\right] = 0. \tag{10}$$

Even though the layers $\hat{z}^\ell, \hat{z}^{\ell'}$ are correlated, because the activation functions φ_{s^ℓ} and $\varphi_{s^{\ell'}}$ are set to be independent on initialization, the correlation between layers does not induce a correlation on which neurons are activated from layer to layer. This explains why there is no hypoactivation and interlayer correlation correction in Theorem 4 as there is in Theorem 1.

3 Consequences of Theorems 1 & 4 and Comparison to Infinite-Width Limit

3.1 Vanishing and Exploding Norms

By the basic fact $\mathbf{E}[\exp(\mathcal{N}(\mu, \sigma^2))] = \exp(\mu + \frac{1}{2}\sigma^2)$ it follows from Theorems 1 & 4 that, when the inputs x has $\|x\| = \sqrt{n_{\text{in}}}$, the mean size scale of any neuron z_i^{out} is approximately

$$\mathbf{E}\left[(z_i^{\text{out}})^2\right] \approx \begin{cases} (\alpha^2 + \lambda^2)^d \exp\left(2ch_{\text{total}} + \frac{1}{2}c^2 I_{\text{total}}\right), & \text{for Vanilla ResNets,} \\ (\alpha^2 + \lambda^2)^d, & \text{for Balanced ResNets.} \end{cases}$$

(Note that the terms with β cancel out!) When $\alpha^2 + \lambda^2 = 1$, this is constant for Balanced ResNets. In contrast, Vanilla ResNets have a complicated dependence on the network depth d and width n due to the *hypoactivation* and *correlations* terms. This means the behaviour is $\exp(Cd/n)$, which is somewhat surprising. A more serious issue is the variance which Theorems 1 & 4 predict to be

$$\mathbf{Var}\left[(z_i^{\text{out}})^2\right] \approx \begin{cases} (\alpha^2 + \lambda^2)^{4d}\left(3\exp\left(\beta + c^2 I_{\text{total}}\right) - 1\right)\exp\left(4ch_{\text{total}} + c^2 I_{\text{total}}\right), & \text{for Vanilla,} \\ (\alpha^2 + \lambda^2)^{4d}\left(3\exp\left(\beta\right) - 1\right), & \text{for Balanced.} \end{cases}$$

Since $\beta \approx Cd/n$, the term $\exp(\beta)$ represents exponentially larger variance for deep nets compared to shallow ones of the same width. In contrast, the variance predicted by the infinite width limit does not grow with depth for this model when $\alpha^2 + \lambda^2 = 1$. This effect means the relative sizes of different network outputs can be widely disparate. Unlike problems with the mean, this issue is harder to resolve. For example, normalization methods that divide all neurons by a constant does nothing to address the large relative disparity between two points. Techniques like batch normalization will be

Figure 3: Behaviour of the mean and variance of the typical output $(z_i^{\text{out}})^2$ and the correlation between $(z_i^{\text{out}})^2, (z_j^{\text{out}})^2$ for two different output neurons. Here $n = 200$, $\alpha = \lambda = 1/\sqrt{2}$ and d/n varies on the x-axis. The infinite width prediction for correlation is zero, but due to plotting on log-scale, we replace zero by 0.01 for display.

skewed by large outliers. This kind of variance is known to obstruct training [27]. The input-output derivative $\partial_{x_i} z^{\text{out}}$ has the same type of behaviour as z^{out} itself; a simple proof is given in Appendix B. It is expected that the gradient with respect to the weights $\partial_{W_{ij}^\ell} z^{\text{out}}$ will also have the same qualitative behaviour [25] although more investigation is needed to understand this theoretically. Exponentially large variance for gradients is a manifestation of the vanishing-and-exploding gradient problem [28].

Balanced ResNets suffer from this variance problem less because the interlayer correlation term is zero. Since this variance reduction happens at the exponential scale in, the difference can be significant; for networks with $d/n = 1$, the contribution is a factor of $\approx e^{5.5} \approx 250$ for Vanilla ResNets vs. $\approx e^{2.5} \approx 10$ for Balanced ResNets. See Figure 3 for a comparison of these theoretically predicted properties vs experiments with finite networks.

3.2 Correlated Output Neurons

Since the same random variable G multiplies the entire vector z^{out}, the individual neurons in the output layer are *not* independent. For example, Theorem 1 and 4 predict that the squared entries have strictly positive correlation given by $\mathbf{Corr}\left((z_i^{\text{out}})^2, (z_j^{\text{out}})^2\right) = (\exp(\sigma^2) - 1)/(3\exp(\sigma^2) - 1)$ for any two neurons $i \neq j$ where $\sigma^2 = \mathbf{Var}(G)$. This tends to $1/3$ as d/n grows. The effect of correlated output neurons persists for Balanced ResNet but is reduced again due to the lower variance. This is very different from the infinite-width limit, which predicts that individual neurons should be independent Gaussians. This prediction of the theorem matches finite networks closely; see Figure 3.

4 Conjecture 5: Hypoactivation and Layerwise Correlations

Vanilla ResNets have a subtle asymmetry in the architecture due to the skip connections. Unlike fully connected networks, the distribution of $\hat{z}^\ell := z^\ell / \|z^\ell\|$ for $\ell \geq 1$ is *not* exactly uniformly distributed on the unit sphere. Informally speaking, $\hat{z}^\ell$ can be thought of as a random walk whose variance at each step is proportional to $\|\varphi_+(\hat{z}^\ell)\|$. *More* randomness is injected when $\|\varphi_+(\hat{z}^\ell)\|$ is *large* and less when it is small. The net effect is that the walk moves slower when $\|\varphi_+(\hat{z}^\ell)\|$ is small, thereby spending more time in those locations. Consequently, $\|\varphi_+(\hat{z}^\ell)\|$ is biased toward smaller values.

The size of this effect is limited by entropy; most of the unit sphere $\mathbb{S}^{n-1}$ has $\|\varphi_+(u)\|^2 \approx 1/2$ in the sense that for any $\epsilon > 0$, the measure of the set $\left\{u : |\|\varphi_+(u)\|^2 - \frac{1}{2}| > 1/n^{\frac{1}{2}-\epsilon}\right\}$ vanishes as $n \to \infty$. Based on Monte Carlo simulations we conjecture that the expected size of the hypoactivation effect is only $O(1/n)$ in expectation; Conjecture 5 contains a precise statement.

Even if each layer $\hat{z}^\ell$ is marginally close to the uniform distribution on the unit sphere, the directions $\hat{z}^\ell$ and $\hat{z}^{\ell+1}$ are not independent because of the skip connections in the network. As above, the exact behaviour is complicated due to fluctuations in the exact number of neurons which are activated

| (a) | (b) | (c) | (d) |

Figure 4: Monte Carlo evidence for Conjecture 5. $d = 200$, $\alpha = \lambda = 1/\sqrt{2}$, and n varies on the x-axis. The plots show the quantities (a) $\left| \mathbf{E}\|\varphi_+(\hat{z}^\ell)\|^2 - \mathbf{E}\|\varphi_+(u)\|^2 \right|$, (b) $\left| \mathbf{Var}\|\varphi_+(\hat{z}^\ell)\|^2 - \mathbf{Var}\|\varphi_+(u)\|^2 \right|$, (c) $\left| \mathbf{Cov}\left(\|\varphi_+(\hat{z}^\ell)\|^2, \varphi_+(\hat{z}^{\ell-1})\|^2 \right) - C(\theta_1) \right|$, (d) $\left| \mathbf{Cov}\left(\|\varphi_+(\hat{z}^\ell)\|^2, \varphi_+(\hat{z}^{\ell-2})\|^2 \right) - C(\theta_2) \right|$. $C(\theta_k)$ is the theoretical covariance formula from the term where $\ell' - \ell = k$ in (8). Note also that the absolute error is expected to be $O(n^{-2})$ when the theoretical quantity is $O(n^{-1})$. Figures (a) and (b) verify the conjecture in (11) and (12), and Figures (c) and (d) verify (13) when $k = 1$ and $k = 2$ respectively. For display, we clip the bottom edge of the CI to 2e-5 on log scale; otherwise the error bar would go down to $-\infty$ on the log scale.

in each layer. However, using the idea that $\left\|\varphi_+(\hat{z}^\ell)\right\|^2 = \frac{1}{2}(1 + o(1))$, we construct the following approximation. From (16), we have the approximation $z^{\ell+1}/\|z^\ell\| = \alpha\hat{z}^\ell + \lambda g^{\ell+1}/\sqrt{n}\,(1 + o(1))$ We observe that the norm of RHS is concentrated around $\sqrt{\alpha^2 + \lambda^2}$ as $n \to \infty$, so normalizing this to get $\hat{z}^{\ell+1}$ we have

$$\hat{z}^{\ell+1} = \left(\frac{\alpha}{\sqrt{\alpha^2 + \lambda^2}} \hat{z}^\ell + \frac{\lambda}{\sqrt{\alpha^2 + \lambda^2}} \frac{g^{\ell+1}}{\sqrt{n}} \right) (1 + o(1)).$$

Iterating this gives the same relationship for $\hat{z}^{\ell+k}$ where the first coefficient becomes $\alpha^k/\sqrt{\alpha^2 + \lambda^2}^k$. As before, based on Monte Carlo simulations, we conjecture that the size of the error is $O(1/n)$ in expectation. We formalize this as a precise statement in Conjecture 5 below.

Conjecture 5. *The distribution of the unit vector $\hat{z}^\ell = z^\ell/\left\|z^\ell\right\|$ is approximately uniformly distributed from the unit sphere $u \in \mathbb{S}^{n-1}$ in the precise sense that the following asymptotics hold*

$$\mathbf{E}\left[\left\|\varphi_+(\hat{z}^\ell)\right\|^2 \right] = \mathbf{E}\left[\left\|\varphi_+(u)\right\|^2 \right] \left(1 + O\left(\frac{1}{n} \right) \right), \tag{11}$$

$$\mathbf{Var}\left[\left\|\varphi_+(\hat{z}^\ell)\right\|^2 \right] = \mathbf{Var}\left[\left\|\varphi_+(u)\right\|^2 \right] \left(1 + O\left(\frac{1}{n} \right) \right). \tag{12}$$

Moreover, for two layers ℓ, ℓ', which are $k \geq 1$ layers apart $|\ell' - \ell| = k$, the joint *distribution of $\hat{z}^\ell, \hat{z}^{\ell'}$ is approximately equal to the joint distribution of $u, \cos(\theta_k)u + \sin(\theta_k)g/\sqrt{n}$ where g is a Gaussian vector with iid $\mathcal{N}(0, 1)$ entries which is independent of u and θ is such that $\cos(\theta_k) = \alpha^k/(\alpha^2 + \lambda^2)^{k/2}$ in the sense that the following asymptotics hold*

$$\mathbf{Cov}\left[\left\|\varphi_+(\hat{z}^\ell)\right\|^2, \left\|\varphi_+(\hat{z}^{\ell'})\right\|^2 \right] = \mathbf{Cov}\left[\|\varphi_+(u)\|^2, \left\|\varphi_+(\cos(\theta_k)u + \frac{\sin(\theta_k)}{\sqrt{n}}g)\right\|^2 \right] \left(1 + O\left(\frac{1}{n} \right) \right). \tag{13}$$

5 Proof Ideas for Theorems 1 & 4

A key element of the proof is the following property of Gaussian random matrices. If W which has iid $\mathcal{N}(0, 1)$ entries, then for any vector x, we have

$$Wx \stackrel{d}{=} \|x\| g, \tag{14}$$

where g is a vector whose entries are iid $\mathcal{N}(0, 1)$ random variables. Because of the fully connected first and last layer of the network, (14) implies that

$$z^0 \stackrel{d}{=} \frac{\|x\|}{\sqrt{n_{\text{in}}}} g, \quad z^{\text{out}} \stackrel{d}{=} \frac{\|z^d\|}{\sqrt{n}} g'. \tag{15}$$

Hence $G := \ln\left((\|z^d\|^2/n)\cdot(\|x\|^2/n_{\mathrm{in}})^{-1}\cdot(\alpha^2+\lambda^2)^{-d}\right)$ only depends on n, d, α, λ. (Equivalently, G has the distribution of $\ln(\|z^d\|^2/n\cdot(\alpha^2+\lambda^2)^{-d})$ when $z^0 = g$.) With this definition, (15) also shows z^{out} is proportional to $\exp(G/2)$, establishing the first part of Theorem 1.

From this construction, the essence of the proof is to understand the distribution of $\|z^d\|$ when $z^0 = g$. To understand $\|z^d\|$, we look at the ratios $\|z^{\ell+1}\|/\|z^\ell\|$ layer by layer. By using the homogeneity property of ReLU $\varphi_+(|c|\,x) = |c|\,\varphi_+(x)$, we can divide $z^{\ell+1}$ from (1) by $\|z^\ell\|$ to obtain

$$\frac{z^{\ell+1}}{\|z^\ell\|} = \alpha\hat{z}^\ell + \lambda\sqrt{\frac{2}{n}}W^{\ell+1}\varphi_+(\hat{z}^\ell) \overset{d}{=} \alpha\hat{z}^\ell + \lambda\sqrt{\frac{2}{n}}\|\varphi_+(\hat{z}^\ell)\|\,g^{\ell+1}, \tag{16}$$

where g^ℓ are iid Gaussian vectors with iid $\mathcal{N}(0,1)$ entries by application of (14). Hence

$$\frac{\|z^{\ell+1}\|}{\|z^\ell\|} \overset{d}{=} \left\|\alpha\hat{z}^\ell + \lambda\sqrt{\frac{2}{n}}\|\varphi_+(\hat{z}^\ell)\|\,g^{\ell+1}\right\| \overset{d}{=} \left\|\alpha\vec{e}_1 + \lambda\sqrt{\frac{2}{n}}\|\varphi_+(\hat{z}^\ell)\|\,g^{\ell+1}\right\|.$$

The last equality follows by applying an orthogonal transformation O such that $O\hat{z}^\ell = \vec{e}_1 = (1,0,0\ldots,0)^T$ inside the norm, and observing that Gaussian random vectors are invariant under orthogonal transformations $Og^\ell \overset{d}{=} g^\ell$. Hence we have the telescoping product for $\|z^d\|$:

$$\|z^d\| = \|z^0\|\prod_{\ell=0}^{d-1}\frac{\|z^{\ell+1}\|^2}{\|z^\ell\|} \overset{d}{=} \|z^0\|\prod_{\ell=0}^{d-1}\left\|\alpha\vec{e}_1 + \lambda\sqrt{\frac{2}{n}}\|\varphi_+(\hat{z}^\ell)\|\,g^{\ell+1}\right\|. \tag{17}$$

This shows that $\|z^d\|$ is a product of d random variables which are dependent on each other only through the terms $\|\varphi_+(\hat{z}^\ell)\|$. (Note that $\|z^0\|$ is independent of $\hat{z}^0$ since z^0 is Gaussian.) Since $\|\varphi_+(\hat{z}^\ell)\|^2 \approx 1/2$ with typical fluctuations on the scale $1/\sqrt{n}$, therefore the dependence between terms of (17) is small. Taking the ln of (17) exhibits $\ln(\|z^d\|^2/n)$ as a sum of these weakly correlated random variables. A Central Limit Theorem (CLT) for weakly correlated sums [33] can be used to prove convergence to a Gaussian. The proof of Theorem 1 is completed by computing the mean, variance and covariance of terms using Conjecture 5. For Theorem 4, the final calculation is simplified by (10) which shows the terms are uncorrelated. The detailed proof is given in Appendix B.

6 Conclusion and Next Steps

Our work demonstrates that for simple statistics, such as the norm of the output and correlations between individual neurons, the infinite-depth-and-width limit more accurately captures finite network behaviour than the infinite-width limit. Clearly, log-Gaussian behaviour plays an important role in understanding deep but finite ResNets in practice. However, our work is only a first step toward understanding the complete log-Gaussian picture. For instance, finding the joint distribution of z^{out} for multiple inputs x, x' in the infinite-depth-and-width limit would provide a depth dependent analogue of the neural network Gaussian process (NNGP) model. For Vanilla ResNets, this endeavour is complicated by hypoactivation and correlation issues we investigate here. For Balanced ResNets, the independence between neuron activations for a single input gives hope that this might be possible.

Another direction is to understand the gradients, and therefore training dynamics, of ResNets in the infinite-depth-and-width limit. In Balanced ResNets, because of the independence of the activations, it is easily shown that the derivative of the output with respect to the input has the same behaviour as z^{out} itself. This is essentially because the function z^{out} is locally linear for every input x; a simple argument is provided in Appendix B. For Vanilla ResNets, this is more difficult once again because of the hypoactivation and interlayer correlation issue. A much more difficult question still is to study the gradient with respect to the weights. For fully connected networks, the gradient with respect to weights is closely related to this input-output derivative, but for ResNets the issue is more complicated. Nevertheless, it would be expected that log-Gaussian behaviour is present there too [25]. A complete description of these gradients and how they depend on the input x would enable an analogue of the NTK theory of training dynamics that applies to ResNets and captures their log-Gaussian behaviour. For fully connected networks, it is already known that the NTK has non-trivial behaviour in the infinite-depth-and-width limit [23]. A theoretical understanding of how training dynamics evolve that incorporates depth could be the key to understanding why depth seems to play such an important role in modern neural networks.

References

[1] A. Jacot, F. Gabriel, and C. Hongler. "Neural tangent kernel: Convergence and generalization in neural networks." *Advances in Information Processing Systems (NeurIPS)*. 2018. arXiv: `1806.07572`.

[2] S. Du, J. Lee, H. Li, L. Wang, and X. Zhai. "Gradient descent finds global minima of deep neural networks." *Int. Conf. Machine Learning (ICML)*. PMLR. 2019, pp. 1675–1685.

[3] Z. Allen-Zhu, Y. Li, and Z. Song. "A convergence theory for deep learning via over-parameterization." *Int. Conf. Machine Learning (ICML)*. PMLR. 2019, pp. 242–252.

[4] D. Zou, Y. Cao, D. Zhou, and Q. Gu. "Gradient descent optimizes over-parameterized deep ReLU networks." In: *Machine Learning* 109.3 (2020), pp. 467–492.

[5] L. Chizat, E. Oyallon, and F. Bach. "On Lazy Training in Differentiable Programming." In: *Advances in Neural Information Processing Systems* 32 (2019), pp. 2937–2947.

[6] J. Lee, L. Xiao, S. S. Schoenholz, Y. Bahri, R. Novak, J. Sohl-Dickstein, and J. Pennington. *Wide neural networks of any depth evolve as linear models under gradient descent*. 2019. arXiv: `1902.06720`.

[7] G. Yang. *Scaling limits of wide neural networks with weight sharing: Gaussian process behavior, gradient independence, and neural tangent kernel derivation*. 2019. arXiv: `1902.04760`.

[8] G. Yang. *Tensor programs ii: Neural tangent kernel for any architecture*. 2020. arXiv: `2006.14548`.

[9] S. Arora, S. S. Du, Z. Li, R. Salakhutdinov, R. Wang, and D. Yu. *Harnessing the power of infinitely wide deep nets on small-data tasks*. 2019. arXiv: `1910.01663`.

[10] G. M. Rotskoff and E. Vanden-Eijnden. *Trainability and Accuracy of Neural Networks: An Interacting Particle System Approach*. 2018. arXiv: `1805.00915`.

[11] L. Chizat and F. Bach. *On the Global Convergence of Gradient Descent for Over-parameterized Models using Optimal Transport*. 2018. arXiv: `1805.09545`.

[12] J. Sirignano and K. Spiliopoulos. *Mean Field Analysis of Neural Networks: A Law of Large Numbers*. 2018. arXiv: `1805.01053`.

[13] S. Mei, A. Montanari, and P.-M. Nguyen. "A mean field view of the landscape of two-layer neural networks." In: *Proceedings of the National Academy of Sciences* 115.33 (2018), E7665–E7671. ISSN: 0027-8424. DOI: `10.1073/pnas.1806579115`. eprint: `https://www.pnas.org/content/115/33/E7665.full.pdf`.

[14] S. Mei, T. Misiakiewicz, and A. Montanari. *Mean-field theory of two-layers neural networks: dimension-free bounds and kernel limit*. arXiv: `1902.06015`.

[15] G. Yang and E. J. Hu. "Feature Learning in Infinite-Width Neural Networks." *Int. Conf. Machine Learning (ICML)*. 2021. arXiv: `2011.14522`.

[16] R. M. Neal. *Bayesian learning for neural networks*. Vol. 118. Springer Science & Business Media, 1995.

[17] G. Yang and S. S. Schoenholz. "Mean field residual networks: on the edge of chaos." *Advances in Neural Information Processing Systems*. 2017, pp. 2865–2873.

[18] J. Lee, Y. Bahri, R. Novak, S. S. Schoenholz, J. Pennington, and J. Sohl-Dickstein. "Deep Neural Networks as Gaussian Processes." *Int. Conf. Learning Representations (ICLR)*. 2018.

[19] A. De Matthews, J. Hron, M. Rowland, R. Turner, and Z. Ghahramani. "Gaussian process behaviour in wide deep neural networks." *Int. Conf. Learning Representations (ICLR)*. 2018.

[20] R. Novak, L. Xiao, Y. Bahri, J. Lee, G. Yang, J. Hron, D. A. Abolafia, J. Pennington, and J. Sohl-dickstein. "Bayesian Deep Convolutional Networks with Many Channels are Gaussian Processes." *Int. Conf. Learning Representations (ICLR)*. 2018.

[21] G. Yang. *Tensor programs i: Wide feedforward or recurrent neural networks of any architecture are gaussian processes*. 2019. arXiv: `1910.12478`.

[22] B. Hanin and M. Nica. "Products of many large random matrices and gradients in deep neural networks." In: *Communications in Mathematical Physics* (2019), pp. 1–36.

[23] B. Hanin and M. Nica. "Finite Depth and Width Corrections to the Neural Tangent Kernel." *Int. Conf. Learning Representations (ICLR)*. 2019.

[24] M. Seleznova and G. Kutyniok. *Analyzing Finite Neural Networks: Can We Trust Neural Tangent Kernel Theory?* 2020. arXiv: `2012.04477`.

[25] B. Chmiel, L. Ben-Uri, M. Shkolnik, E. Hoffer, R. Banner, and D. Soudry. "Neural gradients are near-lognormal: improved quantized and sparse training." *Int. Conf. Learning Representations (ICLR)*. arXiv: 2006.08173. URL: https://openreview.net/forum?id=EoFNy62JGd.

[26] K. He, X. Zhang, S. Ren, and J. Sun. "Deep residual learning for image recognition." *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2016, pp. 770–778.

[27] B. Hanin and D. Rolnick. "How to Start Training: The Effect of Initialization and Architecture." In: *Advances in Neural Information Processing Systems* 31 (2018).

[28] B. Hanin. "Which neural net architectures give rise to exploding and vanishing gradients?" Vol. 31. 2018.

[29] K. He, X. Zhang, S. Ren, and J. Sun. "Delving deep into rectifiers: Surpassing human-level performance on imagenet classification." *Proc. IEEE Int. Conf. Computer Vision*. 2015, pp. 1026–1034.

[30] S. Hayou, E. Clerico, B. He, G. Deligiannidis, A. Doucet, and J. Rousseau. "Stable ResNet." *Int. Conf. Artificial Intelligence and Statistics (AISTATS)*. PMLR. 2021, pp. 1324–1332.

[31] Y. Cho and L. K. Saul. "Kernel methods for deep learning." *Advances in Neural Information Processing Systems (NeurIPS)*. 2009, pp. 342–350.

[32] P. Dhariwal and A. Nichol. *Diffusion Models Beat GANs on Image Synthesis*. 2021. arXiv: 2105.05233.

[33] M. H. Neumann. "A central limit theorem for triangular arrays of weakly dependent random variables, with applications in statistics." In: *ESAIM: PS* 17 (2013), pp. 120–134. DOI: 10.1051/ps/2011144.

[34] J. Bradbury, R. Frostig, P. Hawkins, M. J. Johnson, C. Leary, D. Maclaurin, G. Necula, A. Paszke, J. VanderPlas, S. Wanderman-Milne, and Q. Zhang. *JAX: composable transformations of Python+NumPy programs*. Version 0.2.5. 2018. URL: http://github.com/google/jax.

[35] C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, R. Kern, M. Picus, S. Hoyer, M. H. van Kerkwijk, M. Brett, A. Haldane, J. F. del Río, M. Wiebe, P. Peterson, P. Gérard-Marchant, K. Sheppard, T. Reddy, W. Weckesser, H. Abbasi, C. Gohlke, and T. E. Oliphant. "Array programming with NumPy." In: *Nature* 585.7825 (Sept. 2020), pp. 357–362. DOI: 10.1038/s41586-020-2649-2. URL: https://doi.org/10.1038/s41586-020-2649-2.

[36] Plotnine Contributors. *has2k1/plotnine: v0.8.0*. Version v0.8.0. Mar. 2021. DOI: 10.5281/zenodo.4636791. URL: https://doi.org/10.5281/zenodo.4636791.

[37] H. Wickham. *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York, 2016. ISBN: 978-3-319-24277-4. URL: https://ggplot2.tidyverse.org.

[38] Pandas Contributors. *pandas-dev/pandas: Pandas 1.0.3*. Version v1.0.3. Mar. 2020. DOI: 10.5281/zenodo.3715232. URL: https://doi.org/10.5281/zenodo.3715232.

[39] *Anaconda Software Distribution*. Version Vers. 2-2.4.0. 2020. URL: https://docs.anaconda.com/.

[40] T. Kluyver, B. Ragan-Kelley, F. Pérez, B. Granger, M. Bussonnier, J. Frederic, K. Kelley, J. Hamrick, J. Grout, S. Corlay, P. Ivanov, D. Avila, S. Abdalla, and C. Willing. "Jupyter Notebooks – a publishing format for reproducible computational workflows." *Positioning and Power in Academic Publishing: Players, Agents and Agendas*. Ed. by F. Loizides and B. Schmidt. IOS Press. 2016, pp. 87–90.