Fairness in Representation for Multilingual NLP: Insights from Controlled Experiments on Conditional Language Modeling

Abstract

We perform systematically and fairly controlled experiments with the 6-layer Transformer to investigate whether languages which have been traditionally considered morphologically rich (AR and RU) and poor (ZH) are equally hard to conditional-language-model. We evaluate through statistical comparisons across 30 possible language directions from the 6 languages of the United Nations Parallel Corpus on 3 representation levels — character, byte, and word. Results show that performance is relative to the representation granularity of each of the languages, not to the language as a whole. By eliminating statistically significant performance disparity on the character and byte levels, we show that performance disparity is not a necessary condition. The disparity that mirrors the morphological complexity hierarchy is a byproduct of word segmentation. Evidence from data statistics, along with the fact that word segmentation is qualitatively indeterminate, renders a decades-long debate on morphological complexity (unless it is being intentionally modeled in a word-based, meaning-driven context) irrelevant in the context of computing. The intent of our work is to help effect more objectivity and adequacy in evaluation as well as fairness and inclusivity in experimental setup in the area of language and computing so to uphold diversity in ML and AI research. Multilinguality is real and relevant in computing not due to canonical, structural linguistic concepts such as morphology or "words" in our minds, but rather standards related to internationalization and localization, such as character encoding — something which has thus far been sorely overlooked in our discourse and curricula.

1 Introduction

1.1 Background and motivation

Most current work on fairness in Natural Language Processing (NLP) focuses on the societal biases encoded in natural language data that are propagated and amplified when they are used at scale for/as Artifical Intelligence (AI) solutions[1]. But little has been said or questioned about the bias, as in, the favoring of certain outcomes, implicit in our theoretical/scientific assumptions that results in the varying performance of different languages in computing.

Disparity in machine translation results For instance, results reported in Junczys-Dowmunt et al. (2016) for Phrase-Based Statistical Machine Translation (PBSMT) (Koehn et al., 2003) and Neural MT (Bahdanau et al., 2014) on the 6 official languages[2] of the United Nations (UN) Parallel Corpus (Ziemski et al., 2016) indicate a disparity between EN/ES/FR and AR/RU/ZH in BLEU (Papineni et al., 2002) — translation performance in the latter group is generally worse, regardless of the MT algorithm used. AR and RU are traditionally considered morphologically complex (see e.g. Minkov et al. (2007), Seddah et al. (2010) and proceedings of related workshops in subsequent years for *Statistical Parsing of Morphologically Rich Languages*), and ZH morphologically frugal (for its lacking determiners and plural or tense markers) (Koehn, 2005). While Koehn (2005) found

---

[1] see e.g. work from conference (https://facctconference.org) and workshops in previous years on "Fairness, Accountability, and Transparency" (FAccT)

[2] Arabic (AR), English (EN), Spanish (ES), French (FR), Russian (RU), and Chinese (ZH)

translating into EN to be easier than into morphologically rich languages based on BLEU scores of word tokens from PBSMT systems of 110 language directions from the 11 Europarl languages then, Bugliarello et al. (2020) found it is easier to translate out of EN than into it based on 21 Europarl languages in BPEs (Byte Pair Encodings) (Sennrich et al., 2016) with the Transformer (Vaswani et al., 2017) in a new metric, cross-mutual information.

Disparity in language modeling results Disparate performances across different languages seem to have been implicitly accepted in that it is often believed that some languages are harder to model than others. Bender (2009) advocated the relevance of linguistic typology for the design of language-universal NLP systems due to differences based on crosslinguistic structural notions, such as parts of speech and morphological complexity. Cotterell et al. (2018) studied (monolingual) language models (LMs) on the 21 Europarl languages using a word-level 7-gram standard Kneser & Ney (1995) model and LSTM-LMs (Sundermeyer et al., 2012) with characters and lemmatized forms in information-theoretic terms, and found morphological complexity to be the primary culprit for the differences in performance. Mielke et al. (2019) supplemented with the multilingual Bible corpus (Mayer & Cysouw, 2014) to extend the coverage to 69 languages, tested on RNN-LMs (an implementation of LSTM (Hochreiter & Schmidhuber, 1997)) with characters and BPEs, but concluded that basic data statistics in vocabulary size ($|V|$) and sequence length were the most predictive features of performance.

Since: i) different input representations have been tested with different architectures with divergent results in different metrics; ii) we noticed a discrepancy in the results from Mielke et al. (2019) for ZH — it came out as the least difficult for the character model, but it is the 6[th] most difficult language for the BPE model; and iii) each of the previous studies only tested with one data size, without statistical comparisons of score distributions between languages; we decided to investigate the matter more systematically once again.

1.2 RESEARCH QUESTIONS AND CONTRIBUTIONS

Research questions Are languages which have been traditionally considered morphologically rich (AR and RU) and poor (ZH) equally hard to Conditional-Language-Model (CLM) with the 6-layer Transformer? To which extent is morphological complexity necessary in computing?

Summary of findings and insights

1. In a bilingual (one-to-one) CLMing setup, there is neutralization of source language instances, i.e. there are no statistically significant differences between source language pairs. Only pairs of target languages differ significantly (see Table 1).
2. Hardness in modeling is relative to and bounded by its representation level (*representation relativity*).
3. On the character and byte levels, hardness is correlated with statistical properties concerning sequence length and $|V|$ of a language, regardless of its morphological profile. As it is possible to eliminate performance disparity through data transformation on the character and byte levels, we show that, unless word-based methods are used, there is no morphological complexity applicable or necessary in computing.
4. On the word level, hardness is correlated with $|V|$, and a complexity hierarchy arises through the manual preprocessing step of word tokenization. This complexity/disparity effected by word segmentation can be improved by subword tokenization but cannot be eliminated due to the fundamental qualitative differences in the definition of a "word" being one that neither holds universally nor is suitable/consistent for fair crosslinguistic comparisons.
5. Representational units of finer granularity can help close the gap in performance disparity.

Orthogonal to our main research questions, we also observed 2 types of sample-wise non-monotonicity — Double Descent (Belkin et al., 2019; Nakkiran et al., 2020) and *erraticity*. For reasons due to length and scope for this paper, we will defer discussions and analyses of these beyond what is addressed in § 5 to future work.

Outline of the paper In § 2, we define our method and experimental setup. We present our results and analysis on the primary representations in § 3 and those from secondary set of controls in § 4

in a progressive manner to ease understanding. Meta analysis on performance disparity and other discussions are in § 5.

2 METHOD AND DEFINITIONS

Conditional language modeling CLMing is the modeling of the probability of the next token, given the history of the preceding tokens and conditioning context. In our case, such conditioning context is a line from the source language. To explicitly focus on modeling the complexities that may or may not be *intrinsic* to the languages, we study the more fundamental process of CLMing without performing any downstream translation. This allows us to eliminate confounds associated with generation[3] and other evaluation metrics. One could think of our setup as estimating conditional probabilities with the Transformer, with a bilingual setup where perplexity (PP) of one target language (l_{trg}) is estimated given the parallel data in one source language (l_{src}), where $l_{\text{src}} \neq l_{\text{trg}}$. We focus on the very basics and examine the first step in our pipeline — input representations, holding everything else constant. Instead of measuring absolute cross-entropy scores at one data size, we evaluate the relative differences between development (dev) set score distributions between languages.

Controlled experiments as basic research for scientific understanding Using the United Nations Parallel Corpus (Ziemski et al., 2016), the data from which the MT results in Junczys-Dowmunt et al. (2016) stem, we perform a series of controlled experiments on the Transformer, holding the hyperparameter settings for all 30 one-to-one language directions from the 6 languages constant. We control for size (from 10^2 to 10^6 lines) and language with respect to representational granularity. We examine 3 primary representation types/levels — character, byte (UTF-8), and word, and upon encountering some unusual phenomena, we perform a secondary set of controls with 5 alternate representations — on the character level: Pinyin and Wubi (ASCII representations for ZH phones and character strokes, respectively), on the byte level: code page 1256 (for AR) and code page 1251 (for RU), and on the word level: BPE. These symbolic variants allow us to manipulate the statistical properties of the representations, while staying as "faithful" to the language as possible. We adopt this symbolic data-centric[4] approach because we would like to more directly interpret the confounds, if any, that make language data different from other data types. We operate on a smaller data size range as this is more common in traditional language sciences and one of our higher goals is to bridge an understanding between language sciences and engineering (the latter being the dominant focus in NLP), and between traditional symbolic science and Machine Learning (ML). We run statistical tests to identify the strongest correlates of performance and to assess whether the differences between the mean performance of different groups are indeed significant. We are concerned *not* with the absolute scores, but with the *differences* between score distributions from different languages.

Fair evaluation with multitexts Multitexts are multiway parallel corpora. We use the UN Parallel Corpus because it covers languages conventionally regarded as morphologically rich and poor, has quality and size sufficient for evaluation, and more importantly, it comes as raw texts (untokenized), unlike both of the corpora that Mielke et al. (2019) used. Detokenization (esp. the evaluation thereof) is not a trivial task.

Fair information-theoretic evaluation metric Most sequence-to-sequence models are optimized using a cross-entropy loss, defined as:

$$H(\boldsymbol{t}, \boldsymbol{s}) = -\sum_{i=1}^{N} \log_2 p(t_i \mid \boldsymbol{t}_{<i}, \boldsymbol{s}) \tag{1}$$

where $\boldsymbol{t}$ is the sequence of tokens to be predicted, t_i refers to the i^{th} token in that sequence, $\boldsymbol{s}$ is the sequence of tokens conditioned on, and $N = |\boldsymbol{t}|$. It is customary to report scores as PP, which is $2^{\frac{1}{N}H(\boldsymbol{t}, \boldsymbol{s})}$, i.e. 2 to the power of the cross-entropy averaged by the number of tokens in the dev data. Cotterell et al. (2018) proposed to use "renormalized" PP to evaluate LMs tokenwise fairly

---

[3]"Exact MAP (maximum a posteriori) decoding is intractable in NMT, and the beam search algorithm (Sutskever et al., 2014) is employed as a viable approximation." (Eikema & Aziz, 2020)

[4]Two testing/evaluation approaches — data-centric: hold the algorithm constant and tweak data, vs. algorithm-centric: hold data constant and tweak the algorithm.

by dividing the overall bits per utterance/sequence by one constant token count in any one arbitrary language (e.g. so to arrive at "bits per character" in one language to evaluate all languages). But we find that it is not necessary to assign a perspective that is centered on any one particular language, when we can evaluate simply by the total number of bits for a larger portion of texts/sequences. This can be a fairer, more general and flexible way of evaluating data that has not been or cannot be perfectly segmented or aligned line by line. We hence used instead "unnormalized" PP, i.e. the total number of bits needed to encode the dev set (3,077 lines per language, after length filtering, in our case). As the implementation we used only reports PP, we transformed it back to entropy as defined above via $H(\boldsymbol{t}, \boldsymbol{s}) = \log_2 PP(\boldsymbol{t}|\boldsymbol{s}) \times N$.

Disparity/Inequality In the context of our CLMing experiments, we consider there to be "disparity" or "inequality" between languages l_1 and l_2 if there are significant differences between the performance distributions of these two languages with respect to each representation. Here, by performance we mean the number of bits required to encode the held-out data using a trained CLM. With 30 directions, there are 15 pairs of source languages $(l_{\mathrm{src}1}, l_{\mathrm{src}2})$ and 15 pairs of target languages $(l_{\mathrm{trg}1}, l_{\mathrm{trg}2})$ possible. We compare the source languages among each other, and the target languages among each other. Each l_{src} or each l_{trg} consists of scores from all models trained across various sizes and directions. To assess whether the differences are significant, we perform unpaired two-sided significance tests with the null hypothesis that the score distributions for the two languages are not different. Upon testing for normality with the Shapiro-Wilk test (Shapiro & Wilk, 1965; Royston, 1995), we use the parametric unpaired two-sample Welch's t-test (Welch, 1947) (when normal) or the non-parametric unpaired Wilcoxon test (Wilcoxon, 1945) (when not normal) for the comparisons. We use the implementation in R (R Core Team, 2014) for these 3 tests. To account for the multiple comparisons we are performing, we correct all p-values using Bonferroni's correction (Benjamini & Heller, 2008; Dror et al., 2017) and follow Holm's procedure[5] (Holm, 1979; Dror et al., 2017) to identify the pairs of l_1 and l_2 with significant differences after correction. We report all 3 levels of significance ($\alpha \leq 0.05, 0.01, 0.001$) for a more comprehensive overview. In contrast to Dror et al. (2017), which aimed to compare the performance of different algorithms, we compare languages (in the context of computing).

Experimental setup The systematic, identical treatment we give to our data is described as follows with further preprocessing and hyperparameter details in Appendices A and B, respectively.

After filtering length to 300 characters maximum per line in parallel for the 6 languages, we made 3 subsets of the data with 1 million lines each — one having lines in the order of the original corpus (dataset A) and two other randomly sampled (without replacement) from the full corpus (datasets B & C). Lines in all datasets are extracted in parallel and remain fully aligned for the 6 languages. For each run and each representation, there are 30 pairwise directions (i.e. one l_{src} to one l_{trg}) that result from the 6 languages. We trained all 150 (for 5 sizes) 6-layer Transformer models for each run using the SOCKEYE Toolkit (Hieber et al., 2018). We optimize using PP and use early stopping if no PP improvement occurs after 3 checkpoints up to 50 epochs maximum, taking the best checkpoint. Characters and bytes are supposed to mitigate the out-of-vocabulary (OOV) problem on the word level. In order to assess the effect of modeling with finer granularity more precisely, all vocabulary items appearing once in the train set are accounted for (i.e. full vocabulary on train, as in Gerz et al. (2018a;b)). But we allow our system to categorize all unknown items in the dev set to be unknown (UNK) so to measure OOVs (open vocabulary on dev (Jurafsky & Martin, 2009)). To identify correlates of performance, we perform Spearman's correlation (Spearman, 1904) with some basic statistical properties of the data (e.g. length, $|V|$, type-token-ratio, OOV rate) as metrics — a complete list thereof is provided in App. C. For each of the 3 primary representations — character, byte, and word, we performed 5 runs total in 5 sizes (10^2-10^6 lines) (runs A0, B0, C0, A1, & A2) and 7 more runs in 4 sizes (10^2-10^5 lines) (A3-7, B1, & C1), also controlling for seeds. For the alternate/secondary representations, we ran 3 runs each in 5 sizes (10^2-10^6 lines) (A0, B0, & C0).

3 EXPERIMENTAL RESULTS OF PRIMARY REPRESENTATIONS

Subfigures 1a, 1b, and 1c present the mean results across 12 runs of the 3 primary representations — character, byte, and word, respectively. The x-axis represents data size in number of lines and

---

[5]using implementation from `https://github.com/rtmdrr/replicability-analysis-NLP`

(a) CHAR   (b) BYTE   (c) WORD

(d) CHAR by target   (e) BYTE by target   (f) WORD by target

Figure 1: Number of bits (the lower the better) across data size from 10^2 to 10^6 lines plotted for all 30 directions. Subfigures 1a, 1b, and 1c show mean scores across 12 runs. Subfigures 1d, 1e, and 1f depict the corresponding information respectively sorted in 6 facets by target language and with error bars. Legend in Subfigure 1g shows the correspondence between colors and source languages, in Subfigure 1h between line types and target languages. (These figures are also shown enlarged in Appendix E. Please note that results are summarized in Table 1, figures are a visual aid only. We are not concerned with the absolute scores or the non-monotonic development past 10^4 as they'd be accounted for in our statistical comparisons. The point of the graphs here is to show the difference in Transformer's learning behavior relative to the representational granularity.)

y-axis the total conditional cross-entropy, measured in bits (Eq. 1). Each line connects 5 data points corresponding to the number of bits the CLMs (trained with training data of 10^2, 10^3, 10^4, 10^5, and 10^6 lines) needed to encode the target language dev set given the corresponding text in the source language. These are the same data in the same 30 language directions and 5 sizes with the same training regime, just preprocessed/segmented differently. This confirms **representation relativity** — languages (or any objects being modeled) need to be evaluated relative to their representation. "One size does not fit all" (Durrani et al., 2019). Our conventional way of referring to "language" (as a socio-cultural product or with traditional word-based approaches, or even for most multilingual tasks and competitions) is too coarse-grained (see also Fisch et al. (2019) and Ponti et al. (2020)).

Subfigures 1d, 1e, and 1f display the corresponding information sorted into facets by target language, source languages represented as line types. Through these we see more clearly that results can be grouped rather neatly by target language — as implicit in the Transformer's architecture, the decoder is unaware of the source language in the encoder. As shown in Table 1 in § 5 summarizing the number of source and target language pairs with significant differences, there are **no significant differences across any source language pairs**. The Transformer neutralizes source language instances. This could explain why transfer learning or multilingual/zero-shot translation (Johnson et al., 2017) is possible at all on a conceptual level.

In general, for character and byte models, most language directions do seem to converge at 10^4 lines to similar values across all target languages, with few notable exceptions. There are some fluctuations past 10^4, indicating further tuning of hyperparameters would be beneficial due to our present setting possibly working most favorably at 10^4. On the character level, target language ZH (ZH_{trg}) shows a different learning pattern throughout. And on the byte level, AR_{trg} and RU_{trg} display non-monotonic and unstable behavior, which we refer to as *erratic*. Word models exhibit Double Descent across the board (note the spike at 10^3), but overall, difficult/easy languages stay consistent, with AR and RU being the hardest, followed by ES and FR, then EN and ZH. A practical takeaway from this set of experiments: in order to obtain more robust training results, use bytes for ZH (as suggested in Li et al. (2019a)) and characters for AR and RU (e.g. Lee et al. (2017)) — also if one wanted to avoid any "class" problems in performance disparity with words. Performance disparity for these representations is reported in Table 1 under "CHAR", "BYTE", and "WORD". Do note, however, that the intrinsic performance of ZH with word segmentation is not particularly subpar. But this often does not correlate with its poorer downstream tasks results (recall results from Junczys-Dowmunt et al. (2016)). Since the notion of word in ZH is highly contested and ambiguous — i) it is often aimed to align with that in other languages so to accommodate manual feature engineering[6] and academic theories, ii) there is great variation among different conventions, iii) native ZH speakers identify characters as words — there are reasons to rethink this procedure now that fairer and language-independent processing in finer granularity is possible. Li et al. (2019b) questioned the necessity of CWS in DL-based ZH NLP and presented evidence in favor of character-based processing, including results from downstream NLP tasks. In Linguistics, Duanmu (2017) presented a summary on the contested nature of wordhood in ZH. A more native analysis of ZH, despite a couple of dialects/varieties of it being considered a high-resource language, has not yet been fully recognized and accepted in NLP.

4 UNDERSTANDING THE PHENOMENA WITH ALTERNATE REPRESENTATIONS

To understand why some languages show different results than others, we carried out a secondary set of control experiments with representations targeting the problematic statistical properties of the corresponding target languages.

| (a) Wubi | (b) Wubi by target | (c) Pinyin | (d) Pinyin by target |

Figure 2: Character-level remedies for ZH: Wubi vs. Pinyin.

Character level We reduced the high $|V|$ in ZH with representations in ASCII characters — Pinyin and Wubi. The former is a romanization of ZH characters based on their pronunciations and the latter an input algorithm that decomposes character-internal information into stroke shape and ordering and matches these to 5 classes of radicals (Lunde, 2008). We replaced the ZH data in these formats *only on the target side* and reran the experiments involving ZH_{trg} on the character level. Results in Figure 2

---

[6]It is a (legacy) convention from the early days in ZH NLP when the goal was to align with EN words for MT. Chinese word segmentation (CWS) has been a decades-long issue in text processing. But even in EN, there are no clear or stable standards (for humans or for computing) for the definition of "words". The definition of "words" (even for an academic account, external of CWS) is indeterminate (see Haspelmath (2011) and references therein from the past century). Kilgarriff (1997; 2014) pointed out that "words" and "word senses" and the number thereof, in terms of lexical entries for dictionaries, are contextual and arbitrary.

(a) Code page 1256 & 1251   (b) Code page by target   (c) BPE   (d) BPE by target

Figure 3: Byte-level (Subfigures 3a & 3b) remedies with code page 1256 for target AR and 1251 for target RU, and word-level (Subfigures 3c & 3d) remedy with BPE for all languages.

and Table 1 show that the elimination of disparity on character level is possible if ZH is represented through Pinyin (transliteration), as in Subfigure 2c. But models with ZH logographic scripts display a behaviorial tendency unlike those with other (phonetic) alphabetic scripts (Subfigure 2a). Work published thus far using Wubi with the Transformer seems to have needed some form of architectural modification (Gao et al., 2020) or a different architecture altogether (Nikolov et al., 2018; Zhang et al., 2019), suggesting that this script pattern may be one that is problematic for the Transformer.

Byte level   Length is the most salient statistical attribute that makes AR and RU outliers. To shorten their sequence lengths, we tested with alternate encodings on AR_{trg} and RU_{trg} — code page 1256 and 1251, which provide 1-byte encodings specific to AR and RU, respectively. Results are shown in Subfigures 3a and 3b. Not only is erraticity resolved, the number of 15 possible target language pairs with significant differences reduces from 8 with the UTF-8 byte representation to **0** (Table 1 under "$ARRU_t$"), indicating that we eliminated disparity with this optimization heuristic. Since our heuristic is a lossless and reversible transform, it shows that **a complexity that is intrinsic and necessary in language**[7] **does not exist** in computing, however diverse they may be, as our 6 are, from the conventional linguistic typological, phylogenetic, historical, or geographical perspectives.

Word level   The main difference between word and character/byte models is length not being a top contributing factor correlating with performance, but instead $|V|$ is. This is understandable as word segmentation neutralizes sequence lengths. To remedy the OOV problem, we use BPE, which learns a fixed vocabulary of variable-length character sequences (on word level, as it presupposes word segmentation) from the training data. It is more fine-grained than word segmentation and is known for its capability to model subword units for morphologically complex languages. We use the same vocabulary of 30,000 as specified in Junczys-Dowmunt et al. (2016). This reduced our averaged OOV token rate by 89-100% across the 5 sizes. The number of language pairs with significant differences reduced to 7 from 8 for word models, showing how **finer-grained modeling has a positive effect on closing the disparity gap**.

5   META-RESULTS, ANALYSIS, AND DISCUSSION

Performance disparity   Table 1 lists the number of language pairs with significant differences under the representations studied. Considering how it is **possible** for our character and byte models to effect no performance disparity for the same languages on the same data, this indicates that disparity is not a necessary condition. In fact, the customary expectation that languages ought to perform differently stems from our word segmentation practice. Furthermore, the order of AR/RU > ES/FR > EN/ZH (Figure 1c) resembles the idea of morphological complexity. Considering there are character-internal meaningful units in languages with logographic script such as ZH (cf. Zhang

---

[7]aside from its statistical properties related to length and vocabulary. To show something is not necessarily true, only 1 counter observation is needed.

Table 1: Number of language pairs out of 15 with significant differences, with respective p-values. $ARRU_t$ refers to AR & RU being optimized only on the target side; whereas $ARRU_{s,t}$ denotes optimization on both source and target sides (relevant for directions AR-RU and RU-AR).

p-value	CHAR		Pinyin		Wubi		BYTE		$ARRU_t$		$ARRU_{s,t}$		WORD		BPE	
	src	trg	src	trg	src	trg	src	trg	src	trg	src	trg	src	trg	src	trg
0.05	0	7	0	4	0	8	0	9	0	4	0	4	0	11	0	10
0.01	0	5	0	2	0	6	0	8	0	3	0	4	0	8	0	8
☞ 0.001	0	3	**0**	**0**	0	5	0	8	**0**	**0**	0	2	0	8	0	7

Table 2: Language pairs with significant differences indicate that the 2 languages are *not* equally/similarly good or equally/similarly bad. 15 (non-directional) language pairs total possible from 30 language directions, p=0.001.

LANG PAIR	CHAR	Pinyin	Wubi	BYTE	$ARRU_t$	$ARRU_{s,t}$	WORD	BPE
AR-EN				X			X	X
AR-ES								
EN-ES							X	
AR-FR				X				
EN-FR							X	X
ES-FR								
AR-RU				X				
EN-RU				X		X	X	X
ES-RU				X				
FR-RU				X				
AR-ZH	X		X	X			X	X
EN-ZH	X		X					
ES-ZH			X				X	X
FR-ZH	X		X				X	X
RU-ZH			X	X		X	X	X

& Komachi (2018)) that are rarely captured, studied, or referred to as "morphemes", this goes to show that linguistic morphology, along with its complexity, as is practiced today[8] and that which has occurred in the NLP discourse thus far, has only been relevant on and is bounded to the "word" level. The definition of word, however, has been recognized as problematic for a very long time in the language sciences (cf. Footnote 6).

While the lack of significant differences between pairs of source languages would signify neutralization of source language instances, it does not mean that source languages have no effect on target. For our byte solutions with code pages, we experimented also with source side optimization in the directions that involve AR/RU as source. This affected the distribution of the disparity results for that representation — with 2 pairs being significantly different (see Table 1 under "$ARRU_{s,t}$"). We defer further investigation on the nature of source language neutralization to future work.

Language pairs with significant differences are summarized in Table 2. Do note, however, that these are based on a one-setting-for-all configuration, with no hyperparameter tuning, in a 6-layer network, where differences may be magnified. We show that even in this setting, the pattern of morphological complexity can be empirically eliminated. A more analytical solution can be obtained through data statistics (see App. D). A conceptual solution lies in the definition of "words" and morphology.

Sample-wise Double Descent (DD) Sample-wise non-monotonicity/DD (Nakkiran et al., 2020) denotes a degradation followed by an improvement in performance with increasing data size. We

---

[8]But there are no reasons we cannot adopt a statistical science of language beyond/without "words", or with continuous representations of characters and bytes. In fact, that could complement the needs of language engineering and the NN/DL/ML communities better.

notice word models and character models with ZH_{trg}, i.e. models with high target $|V|$, are prone to exhibit a spike at 10^3. A common pattern for these is the ratio of target training token count to number of parameters falls into $O(10^{-4})$ for 10^2 lines, $O(10^{-3})$ at 10^3, $O(10^{-2})$ at 10^4, and $O(10^{-1})$ for 10^5 lines and so on. But for more atomic units such as alphabetic (not logographic) characters (may it be Latin, Cyrillic, or Abjad) and for bytes, this progression instead begins at $O(10^{-3})$ at 10^2 lines. Instead of thinking this spike of 10^3 as irregular, we may instead want to think of this learning curve as shifted by 1 order of magnitude to the right for characters and bytes and/or the performance at 10^2 lines for words and ZH-characters due to being overparameterized and hence abnormal. This would also fit in with the findings by Belkin et al. (2019) and Nakkiran et al. (2020) attributing DD to overparameterization. While almost all work attribute DD to algorithmic reasons, findings from Chen et al. (2020) corroborate our observation and confirms that DD arises due to "the interaction between the properties of the data and the inductive biases of learning algorithms". Other related work on the DD phenomenon and its development can also be found in their work.

Erraticity We observe another type of sample-wise non-monotonicity, one that signals irregular and unstable performance across data sizes and runs. Within one run, erraticity can be observed directly as changes in direction on the y-axis. Across runs, large variance can be observed, even with the same dataset. Erraticity can also be observed indirectly through a negative correlation between data size and performance. Many work on length bias in NMT have focused on solutions related to search, e.g. Murray & Chiang (2018). Our experiments show that a kind of length bias can surface already with CLMing, without generation taking place.

Additional related work That basic data statistics are the driver of success in performance in multilingual modeling has so far only been explicitly argued for in Mielke et al. (2019). We go beyond their work in monolingual LMs to study CLMs and evaluate also in relation to data size, representational granularity, and quantitative and qualitative fairness. To the best of our knowledge, there has been no prior work on demonstrating the neutralization of source language instances through statistical comparisons, a numerical analysis on DD for sequence-to-sequence models, the meta phenomenon of a sample-wise non-monotonicity (erraticity) being related to length.

6 CONCLUSION

Summary We investigate whether the performance disparity between languages which have been traditionally considered morphologically rich (AR and RU) and poor (ZH) in the 6-layer Transformer CLM is justified due to morphological complexity and find that it is not. Performance disparity can be explained by data statistics and in the context of computing, it can be eliminated by optimization on length and $|V|$ through character/byte representations. In fact, morphological complexity is not a necessarily concept in computing because "word" is not a necessary concept in computing, unless we make it so through word segmentation. A morphological complexity hierarchy can result simply through word segmentation. Furthermore, there are many possible interpretations to "words" for humans and since morphology is defined with the concept of "word", there is no stable ground for assessing this complexity. Representational units of finer granularity were shown to help eliminate performance disparity though at the cost of longer sequence length, which can have a negative impact on robustness. In addition, we found all word models and character models with ZH_{trg} to behave similarly in their being prone to exhibit a peak (as sample-wise DD) around 10^3 lines in our setting.

Outlook Machine learning has enabled greater diversity in NLP (Joshi et al., 2020). Fairness, in the elimination of disparity, does not require big data. This paper made a pioneering attempt to bridge research in DL/NNs, language sciences, and language engineering through a data-centric perspective. Multilinguality is real and relevant in computing not due to canonical, structural linguistic concepts such as morphology or "words" in our minds, but rather standards related to internationalization and localization, such as character encoding — something which has thus far been sorely overlooked in our discourse and curricula. We also believe that a statistical science for NLP as a data science can well complement algorithmic analyses with an empirical view contributing to a more generalizable pool of knowledge for NNs/DL/ML. A more comprehensive study not only can lead us to new scientific frontiers, but also better design and evaluation, benefitting the development of a more general, diverse and inclusive AI.

REFERENCES

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv e-prints*, abs/1409.0473, September 2014. URL https://arxiv.org/abs/1409.0473.

Mikhail Belkin, Daniel Hsu, Siyuan Ma, and Soumik Mandal. Reconciling modern machine-learning practice and the classical bias–variance trade-off. *Proceedings of the National Academy of Sciences*, 116(32):15849–15854, 2019. ISSN 0027-8424. doi: 10.1073/pnas.1903070116. URL https://www.pnas.org/content/116/32/15849.

Emily M. Bender. Linguistically naïve != language independent: Why NLP needs linguistic typology. In *Proceedings of the EACL 2009 Workshop on the Interaction between Linguistics and Computational Linguistics: Virtuous, Vicious or Vacuous?*, pp. 26–32, Athens, Greece, March 2009. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W09-0106.

Yoav Benjamini and Ruth Heller. Screening for partial conjunction hypotheses. *Biometrics*, 64(4): 1215–1222, 2008. ISSN 0006341X, 15410420. URL http://www.jstor.org/stable/25502204.

Emanuele Bugliarello, Sabrina J. Mielke, Antonios Anastasopoulos, Ryan Cotterell, and Naoaki Okazaki. It's easier to translate out of English than into it: Measuring neural translation difficulty by cross-mutual information. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 1640–1649, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.149. URL https://www.aclweb.org/anthology/2020.acl-main.149.

Lin Chen, Yifei Min, Mikhail Belkin, and Amin Karbasi. Multiple descent: Design your own generalization curve, 2020.

Tianqi Chen, Mu Li, Yutian Li, Min Lin, Naiyan Wang, Minjie Wang, Tianjun Xiao, Bing Xu, Chiyuan Zhang, and Zheng Zhang. Mxnet: A flexible and efficient machine learning library for heterogeneous distributed systems. *arXiv preprint arXiv:1512.01274*, 2015.

Colin Cherry, George Foster, Ankur Bapna, Orhan Firat, and Wolfgang Macherey. Revisiting character-based neural machine translation with capacity and compression. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 4295–4305. Association for Computational Linguistics, 2018. URL http://aclweb.org/anthology/D18-1461.

Ryan Cotterell, Sabrina J. Mielke, Jason Eisner, and Brian Roark. Are all languages equally hard to language-model? In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, pp. 536–541, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-2085. URL https://www.aclweb.org/anthology/N18-2085.

Rotem Dror, Gili Baumer, Marina Bogomolov, and Roi Reichart. Replicability analysis for natural language processing: Testing significance with multiple datasets. *Transactions of the Association for Computational Linguistics*, 5:471–486, 2017. URL http://aclweb.org/anthology/Q17-1033.

San Duanmu. Word and wordhood, modern. In Rint Sybesma (ed.), *Encyclopedia of Chinese Language and Linguistics*, pp. 543–549. Brill, 2017.

Nadir Durrani, Fahim Dalvi, Hassan Sajjad, Yonatan Belinkov, and Preslav Nakov. One size does not fit all: Comparing NMT representations of different granularities. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1504–1516, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1154. URL https://www.aclweb.org/anthology/N19-1154.

Bryan Eikema and Wilker Aziz. Is MAP decoding all you need? the inadequacy of the mode in neural machine translation. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 4506–4520, Barcelona, Spain (Online), December 2020. International Committee on Computational Linguistics. doi: 10.18653/v1/2020.coling-main.398. URL `https://aclanthology.org/2020.coling-main.398`.

Adam Fisch, Jiang Guo, and Regina Barzilay. Working hard or hardly working: Challenges of integrating typology into neural dependency parsers. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5713–5719, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1574. URL `https://www.aclweb.org/anthology/D19-1574`.

Yingqiang Gao, Nikola I. Nikolov, Yuhuang Hu, and Richard H.R. Hahnloser. Character-level translation with self-attention. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 1591–1604, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.145. URL `https://www.aclweb.org/anthology/2020.acl-main.145`.

Daniela Gerz, Ivan Vulić, Edoardo Ponti, Jason Naradowsky, Roi Reichart, and Anna Korhonen. Language modeling for morphologically rich languages: Character-aware modeling for word-level prediction. *Transactions of the Association for Computational Linguistics*, 6:451–465, 2018a. doi: 10.1162/tacl_a_00032. URL `https://www.aclweb.org/anthology/Q18-1032`.

Daniela Gerz, Ivan Vulić, Edoardo Maria Ponti, Roi Reichart, and Anna Korhonen. On the relation between linguistic typology and (limitations of) multilingual language modeling. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 316–327, Brussels, Belgium, October-November 2018b. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/D18-1029`.

Martin Haspelmath. The indeterminacy of word segmentation and the nature of morphology and syntax. *Folia Linguistica*, 2011.

Felix Hieber, Tobias Domhan, Michael Denkowski, David Vilar, Artem Sokolov, Ann Clifton, and Matt Post. The Sockeye neural machine translation toolkit at AMTA 2018. In *Proceedings of the 13th Conference of the Association for Machine Translation in the Americas (Volume 1: Research Papers)*, pp. 200–207. Association for Machine Translation in the Americas, 2018. URL `http://aclweb.org/anthology/W18-1820`.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8):1735–1780, November 1997. ISSN 0899-7667. doi: 10.1162/neco.1997.9.8.1735. URL `http://dx.doi.org/10.1162/neco.1997.9.8.1735`.

Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979. ISSN 03036898, 14679469. URL `http://www.jstor.org/stable/4615733`.

Melvin Johnson, Mike Schuster, Quoc V. Le, Maxim Krikun, Yonghui Wu, Zhifeng Chen, Nikhil Thorat, Fernanda Viégas, Martin Wattenberg, Greg Corrado, Macduff Hughes, and Jeffrey Dean. Google's multilingual neural machine translation system: Enabling zero-shot translation. *Transactions of the Association for Computational Linguistics*, 5:339–351, 2017. doi: 10.1162/tacl_a_00065. URL `https://www.aclweb.org/anthology/Q17-1024`.

Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. The state and fate of linguistic diversity and inclusion in the NLP world. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 6282–6293, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.560. URL `https://www.aclweb.org/anthology/2020.acl-main.560`.

Marcin Junczys-Dowmunt, Tomasz Dwojak, and Hieu Hoang. Is neural machine translation ready for deployment? A case study on 30 translation directions. In *IWSLT 2016, Seattle*, October 2016. URL `https://www.microsoft.com/en-us/research/publication/`

```
neural-machine-translation-ready-deployment-case-study-30-\
translation-directions/.
```

Daniel Jurafsky and James H. Martin. *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition.* Pearson Prentice Hall, second edition, 2009.

Adam Kilgarriff. "i don't believe in word senses". *CoRR*, cmp-lg/9712006, 1997. URL `http://arxiv.org/abs/cmp-lg/9712006`.

Adam Kilgarriff. "how many words are there?". 2014. URL `https://www.sketchengine.eu/wp-content/uploads/How_Many_Words_2014.pdf`.

Reinhard Kneser and Hermann Ney. Improved backing-off for m-gram language modeling. In *1995 International Conference on Acoustics, Speech, and Signal Processing*, volume 1, pp. 181–184. IEEE, 1995.

Philipp Koehn. Europarl: A parallel corpus for statistical machine translation. In *Proceedings of Machine Translation Summit X: Papers*, pp. 79–86, Phuket, Thailand, September 13-15 2005. URL `https://aclanthology.org/2005.mtsummit-papers.11`.

Philipp Koehn, Franz J. Och, and Daniel Marcu. Statistical phrase-based translation. In *Proceedings of the 2003 Human Language Technology Conference of the North American Chapter of the Association for Computational Linguistics*, pp. 127–133, 2003. URL `https://www.aclweb.org/anthology/N03-1017`.

Philipp Koehn, Hieu Hoang, Alexandra Birch, Chris Callison-Burch, Marcello Federico, Nicola Bertoldi, Brooke Cowan, Wade Shen, Christine Moran, Richard Zens, Chris Dyer, Ondrej Bojar, Alexandra Constantin, and Evan Herbst. Moses: Open source toolkit for statistical machine translation. In *Proceedings of the 45th Annual Meeting of the Association for Computational Linguistics Companion Volume Proceedings of the Demo and Poster Sessions*, pp. 177–180. Association for Computational Linguistics, 2007. URL `http://aclweb.org/anthology/P07-2045`.

Jason Lee, Kyunghyun Cho, and Thomas Hofmann. Fully character-level neural machine translation without explicit segmentation. *Transactions of the Association for Computational Linguistics*, 5: 365–378, December 2017. doi: 10.1162/tacl_a_00067. URL `https://www.aclweb.org/anthology/Q17-1026`.

Bo Li, Yu Zhang, Tara Sainath, Yonghui Wu, and William Chan. Bytes are all you need: End-to-end multilingual speech recognition and synthesis with bytes. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 5621–5625. IEEE, 2019a.

Xiaoya Li, Yuxian Meng, Xiaofei Sun, Qinghong Han, Arianna Yuan, and Jiwei Li. Is word segmentation necessary for deep learning of Chinese representations? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3242–3252, Florence, Italy, July 2019b. Association for Computational Linguistics. doi: 10.18653/v1/P19-1314. URL `https://www.aclweb.org/anthology/P19-1314`.

Ken Lunde. *CJKV Information Processing*. O'Reilly Media, Inc., 2nd edition, 2008. ISBN 0596514476, 9780596514471.

Thomas Mayer and Michael Cysouw. Creating a massively parallel Bible corpus. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC-2014)*, pp. 3158–3163, Reykjavik, Iceland, May 2014. European Languages Resources Association (ELRA).

Sabrina J. Mielke, Ryan Cotterell, Kyle Gorman, Brian Roark, and Jason Eisner. What kind of language is hard to language-model? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4975–4989, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1491. URL `https://www.aclweb.org/anthology/P19-1491`.

Einat Minkov, Kristina Toutanova, and Hisami Suzuki. Generating complex morphology for machine translation. In *Proceedings of the 45th Annual Meeting of the Association of Computational Linguistics*, pp. 128–135, Prague, Czech Republic, June 2007. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P07-1017.

Kenton Murray and David Chiang. Correcting length bias in neural machine translation. In *Proceedings of the Third Conference on Machine Translation: Research Papers*, pp. 212–223, Belgium, Brussels, October 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-6322. URL https://www.aclweb.org/anthology/W18-6322.

Preetum Nakkiran, Gal Kaplun, Yamini Bansal, Tristan Yang, Boaz Barak, and Ilya Sutskever. Deep double descent: Where bigger models and more data hurt. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=B1g5sA4twr.

Nikola Nikolov, Yuhuang Hu, Mi Xue Tan, and Richard H.R. Hahnloser. Character-level Chinese-English translation through ASCII encoding. In *Proceedings of the Third Conference on Machine Translation: Research Papers*, pp. 10–16, Belgium, Brussels, October 2018. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W18-6302.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL https://www.aclweb.org/anthology/P02-1040.

Edoardo Maria Ponti, Helen O'Horan, Yevgeni Berzak, Ivan Vulić, Roi Reichart, Thierry Poibeau, Ekaterina Shutova, and Anna Korhonen. Modeling language variation and universals: A survey on typological linguistics for natural language processing, 2020.

R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2014. URL http://www.R-project.org/.

Patrick Royston. Remark as r94: A remark on algorithm as 181: The w-test for normality. *Journal of the Royal Statistical Society. Series C (Applied Statistics)*, 44(4):547–551, 1995. ISSN 00359254, 14679876. URL http://www.jstor.org/stable/2986146.

Djame Seddah, Sandra Koebler, and Reut Tsarfaty (eds.). *Proceedings of the NAACL HLT 2010 First Workshop on Statistical Parsing of Morphologically-Rich Languages*, Los Angeles, CA, USA, June 2010. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W10-1400.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1715–1725, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1162. URL https://www.aclweb.org/anthology/P16-1162.

S. S. Shapiro and M. B. Wilk. An analysis of variance test for normality (complete samples)†. *Biometrika*, 52(3-4):591–611, 12 1965. ISSN 0006-3444. doi: 10.1093/biomet/52.3-4.591. URL https://doi.org/10.1093/biomet/52.3-4.591.

C. Spearman. The proof and measurement of association between two things. *The American Journal of Psychology*, 15(1):72–101, 1904. ISSN 00029556. URL http://www.jstor.org/stable/1412159.

Martin Sundermeyer, Ralf Schlüter, and Hermann Ney. Lstm neural networks for language modeling. In *INTERSPEECH*, 2012.

Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 3104–3112. Curran Associates, Inc., 2014. URL http://papers.nips.cc/paper/5346-sequence-to-sequence-learning-with-neural-networks.pdf.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5998–6008. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7181-attention-is-all-you-need.pdf`.

B. L. Welch. The Generalization of 'Student's' Problem when Several Different Population Variances are Involved. *Biometrika*, 34(1-2):28–35, 01 1947. ISSN 0006-3444. doi: 10.1093/biomet/34.1-2.28. URL `https://doi.org/10.1093/biomet/34.1-2.28`.

Frank Wilcoxon. Individual comparisons by ranking methods. *Biometrics Bulletin*, 1(6):80–83, 1945. ISSN 00994987. URL `http://www.jstor.org/stable/3001968`.

Longtu Zhang and Mamoru Komachi. Neural machine translation of logographic language using sub-character level information. In *Proceedings of the Third Conference on Machine Translation: Research Papers*, pp. 17–25, Belgium, Brussels, October 2018. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/W18-6303`.

Wei Zhang, Feifei Lin, Xiaodong Wang, Zhenshuang Liang, and Zhen Huang. Subcharacter Chinese-English neural machine translation with Wubi encoding, 2019.

Michał Ziemski, Marcin Junczys-Dowmunt, and Bruno Pouliquen. The United Nations Parallel Corpus v1.0. In Nicoletta Calzolari (Conference Chair), Khalid Choukri, Thierry Declerck, Sara Goggi, Marko Grobelnik, Bente Maegaard, Joseph Mariani, Helene Mazo, Asuncion Moreno, Jan Odijk, and Stelios Piperidis (eds.), *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC 2016)*, Paris, France, may 2016. European Language Resources Association (ELRA). ISBN 978-2-9517408-9-1.

APPENDICES

A   DATA SELECTION AND PREPROCESSING DETAILS

The UN Parallel Corpus v1.0 (Ziemski et al., 2016) consists of manually translated UN documents from 1990 to 2014 in the 6 official UN languages. Therein is a subcorpus that is fully aligned by line, comprising the 6-way parallel corpus we use. We tried to have as little preprocessing or filtering as necessary to eliminate possible confounds. But as the initial runs of our experiment failed due to insufficient memory on a single GPU with 12 GB VRAM[9], we filtered out lines with more than 300 characters in any language in lockstep with one another for all the 6 languages such that the subcorpora would remain parallel, thereby keeping the material of each language semantically equivalent to one another. 8,944,859 lines for each language were retained as our training data which cover up to the 75th percentile in line length for all 6 languages. In order to monitor the effect of data size, we made subcorpora of each language in 5 sizes by heading the first $10^2, 10^3, 10^4, 10^5, 10^6$ lines[10]. We refer to this as dataset A. In addition, to better understand and verify the consistency of the phenomena observed, we made 2 supplemental datasets by shuffling the 8,944,859 lines two different times randomly and heading the number of lines in our 5 sizes for each language, again in lockstep with one another (datasets B and C).

For character modeling, we used a dummy symbol to denote each whitespace. For byte, we turned each UTF-8-encoded character into a byte string in decimal value, such that each token is a number between 0 and 255, inclusive. For word, we followed (Junczys-Dowmunt et al., 2016) and used the Moses tokenizer (Koehn et al., 2007) as is standard in NMT practice when word tokenization is applied and Jieba[11] for segmentation in ZH.

For Pinyin, we used the implementation from `https://github.com/lxyu/pinyin` in the numerical format such that each character/syllable is followed by a single digit indicating its lexical tone in Mandarin. For Wubi, we used the dictionary from the implementation from `https://github.com/arcsecw/wubi`.

We have implemented all representations such that they would be reversible even when the sequence contains code-mixing.

We used the official dev set as provided in (Ziemski et al., 2016), 3,077 lines per language remained from 4,000 after filtering line length to 300 characters. Data statistics is provided in Appendix D for reference.

The systematic training regime that we give to our language directions are identical for all. For each primary representation type (character, byte, and word), we performed:

- 5 runs in 5 sizes ($10^2 - 10^6$): A0 (seed=13), B0 (13), C0 (9948), A1 (9948), A2 (265), and
- 7 more runs in 4 sizes ($10^2 - 10^5$): A3 (777), A4 (42), A5 (340589), A6 (1000), A7 (83146), B1 (9948), & C1 (13).

For each run and each size, there are 30 pairwise directions (i.e. 1 source language to 1 target language, e.g. AR-EN for Arabic to English) that result from the 6 languages. We trained all 150 jobs for each run and representation using the Transformer model (Vaswani et al., 2017) as supported by the SOCKEYE Toolkit (Hieber et al., 2018) (version 1.18.85), based on MXNet (Chen et al., 2015). A detailed description of the architecture of the Transformer can be found in (Vaswani et al., 2017). The same set of hyperparameters applies to all and its values are listed in Appendix B.

Notes on training time   Each run of 30 directions in 5 sizes took approximately 8-12 days for character and byte models. Byte models generally took longer — hence training time is positively

---

[9]GPUs used for experiments in this paper range from a NVIDIA TITAN RTX (24 GB), NVIDIA GeForce RTX 2080 Ti (11 GB), a GTX Titan X (12 GB), to a GTX 1080 (8 GB). All jobs were run on a single GPU setting. Some word-level experiments involving AR_{trg} or RU_{trg} at 10^6 had to be run on a CPU as 24 GB VRAM were not sufficient. Models with higher maximum sequence lengths (e.g. byte models) were trained with 24 GB VRAM. Difference in equipment does not necessarily lead to degradation/improvement in scores.

[10]The terms "line" and "sentence" have been used interchangeably in the NLP literature. We use "line" to denote a sequence that ends with a newline character and "sentence" as one with an ending punctuation. Most parallel corpora, such as ours, are aligned by line, as a line may be part of a sentence or without an ending punctuation (e.g. a header/title). Using a standardized unit such as "line" would also be a fairer measure to linguae/scriptiones continuae (languages/scripts with no explicit punctuation).

[11]`https://github.com/fxsjy/jieba`

correlated with length (concurring with observations by Cherry et al. (2018) as they compared character with BPE models). A maximum length of 300 characters entails a maximum length of *at least* 300 bytes in UTF-8. Each run of word models (30 directions, 5 sizes) took about 6 days (excluding the training of some 7-9 directions out of 30 per run involving AR_{trg} or RU_{trg} at 10^6 on word level which took about 12-18 hours *each direction* to train on a CPU as these required more space and would run out of memory (OOM) on our GPUs otherwise). These figures do not include the additional probing experiments described in § 4.

B HYPERPARAMETER SETTING

- encoder transformer;
- decoder transformer;
- num-layers 6:6;
- num-embed 512:512;
- transformer-model-size 512;
- transformer-attention-heads 8;
- transformer-feed-forward-num-hidden 2048;
- transformer-activation-type relu;
- transformer-positional-embedding-type fixed;
- transformer-preprocess d; transformer-postprocess drn;
- transformer-dropout-attention 0.1;
- transformer-dropout-act 0.1;
- transformer-dropout-prepost 0.1;
- batch-size 15;
- batch-type sentence;
- max-num-checkpoint-not-improved 3;
- max-num-epochs 50;
- optimizer adam;
- optimized-metric perplexity;
- optimizer-params epsilon: 0.000000001, beta1: 0.9, beta2: 0.98;
- label-smoothing 0.0;
- learning-rate-reduce-num-not-improved 4;
- learning-rate-reduce-factor 0.001;
- loss-normalization-type valid;
- max-seq-len 300 for character, word, and BPE, 672 for all bytes, 688 for Wubi, 680 for Pinyin;
- checkpoint-frequency/interval 4000.
  (For smaller datasets, the end of 50 epochs is often reached before the first checkpoint. Since SOCKEYE only outputs scores at checkpoints, we adjusted the checkpoint frequency as follows to get a score outputted by the end of 50 epochs: 1000 for 100 lines for all character & byte instances, 400 for 100 lines for word and 500 for 100 lines BPE, 3450 for 1000 lines for word & BPE. For the very few cases that this default does not suffice due to bucketing of similar length sequences, we manually set the checkpoint frequency to the last batch.)

C CORRELATION STATISTICS

Best correlating metrics, i.e. the union of top 3 metrics for all representations.
For each representation, the **top 3 metrics** are boldfaced.
All correlations are **highly significant** ($p < 10^{-30}$), except for min source length for WORD ($p \approx 0.0001$) and min target length for WORD ($p \approx 0.3861$).

Metric	CHAR	Pinyin	Wubi	BYTE	$ARRU_t$	$ARRU_{s,t}$	WORD	BPE
minimum length (target)	**0.84**	**0.85**	**0.86**	**0.60**	**0.84**	**0.84**	-0.02	0.65
minimum length (source)	**0.82**	**0.84**	**0.85**	0.57	**0.84**	**0.84**	0.10	0.64
number of tokens (source)	-0.78	-0.81	-0.82	$\mathbf{-0.60}$	-0.81	-0.81	-0.59	$\mathbf{-0.83}$
TTR (target)	**0.83**	**0.83**	**0.84**	0.48	0.81	0.81	0.61	0.83
$|V|$ (source)	-0.54	-0.51	-0.51	-0.50	-0.67	-0.68	$\mathbf{-0.63}$	$\mathbf{-0.86}$
data size in lines	-0.80	-0.83	-0.83	-0.59	-0.81	-0.81	-0.62	$\mathbf{-0.86}$
OOV token rate (target)	0.69	0.66	0.66	0.47	0.67	0.68	**0.66**	0.62
OOV type rate (target)	0.70	0.71	0.72	0.47	0.69	0.70	**0.65**	0.62
TTR (source)	0.67	0.71	0.71	**0.60**	0.81	0.81	0.56	0.82

The full list of metrics used for the correlation analysis is:

1. minimum length (source),
2. minimum length (target),
3. maximum length (source),
4. maximum length (target),
5. median length (source),
6. median length (target),
7. mean length (source),
8. mean length (target),
9. length std (source),
10. length std (target),
11. data size in lines,
12. number of parameters,
13. number of types ($|V|$) (source),
14. number of types ($|V|$) (target),
15. number of tokens (source),
16. number of tokens (target),
17. type-token-ratio (TTR) (source),
18. type-token-ratio (TTR) (target),
19. OOV type rate (source),
20. OOV type rate (target),
21. OOV token rate (source),
22. OOV token rate (target),
23. token ratio,
24. target type-to-parameter ratio,
25. target token-to-parameter ratio,
26. distance between the TTRs of source and target = $(1 - TTR_{src}/TTR_{trg})^2$,
27. token-to-parameter ratio (i) = (median length source * median length target * num_lines) / num_parameters,
28. token-to-parameter ratio (ii) = (num_source_tokens * num_target_tokens) / num_parameters.

D DATA STATISTICS

- Number of types, i.e. vocabulary size ($|V|$). Note that Sockeye adds for its calculation 4 additional types: <pad>, , , <unk>.
- Number of tokens.
- Out-of-vocabulary (OOV) type rate (in %). This excludes the 1 EOS/BOS (end-/beginning-of-sentence) marker added by Sockeye to each line.
- OOV token rate (in %), i.e. the fraction of types in the dev data that is not covered by the types in the training data.
- OOV token rate (in %), i.e. the fraction of tokens in the dev data that is not covered by the types in the training data. Tokens in the dev data that is treated as UNKnowns.
- Type-token-ratio (in %), i.e. the ratio between the number of types and tokens in the data. This is a rough proxy for lexical diversity in that a value of 1 would indicate that no type is ever seen twice, and a value very close to 0 would indicate that very few distinct types account for almost all of the data.
- Line length (excl. EOS/BOS marker): mean±standard deviation, and the 0/25/50/75/100-th percentile.

Statistics for dataset A

The table reports statistics for four representations (CHAR, BYTE, WORD, BPE), each across vocabulary/merge settings 100, 1,000, 10,000, 100,000, 1,000,000. Rows are grouped by metric (Number of TYPES, Number of TOKENS, OOV type rate (%), OOV token rate (%), TTR (%), Mean line length ±std 0/25/50/75/100-th), with sub-rows for languages AR, EN, ES, FR, RU, ZH, and variants ZH.pinyin, ZH_wubi, AR_cp1256, RU_cp1251.

Statistics for dataset B

Representation Number of lines	CHAR					BYTE					WORD					BPE				
	100	1,000	10,000	100,000	1,000,000	100	1,000	10,000	100,000	1,000,000	100	1,000	10,000	100,000	1,000,000	100	1,000	10,000	100,000	1,000,000
Number of TYPES																				
AR	87	134	168	251	431	88	124	147	159	181	1,129	6,719	28,222	97,467	311,355	810	4,408	18,800	29,680	29,959
EN	76	99	131	189	343	89	103	135	163	181	876	4,148	42,844	51,366	140,912	784	3,408	10,756	26,830	29,178
ES	86	104	134	189	366	89	108	133	161	185	970	4,775	16,735	51,366	154,482	814	3,705	12,529	26,068	29,471
FR	89	112	147	202	352	91	141	159	162	185	955	4,636	15,639	45,548	182,881	812	3,670	12,258	27,744	29,370
RU	89	142	173	204	520	112	153	165	175	180	1,142	6,520	25,959	83,937	251,335	993	4,829	18,837	29,261	29,811
ZH	761	1,575	2,402	3,465	4,705	123				188	897	4,162	14,714	46,788	140,188	1,068	3,717	11,069	27,409	29,107
ZH_pinyin	71	104	140			87	134	168	251	431										
ZH_wubi	87	124	154			109	142	173	246	321										
AR_cp1256	11,391	115,377	1,166,227	11,732,204	117,267,349															
RU_cp1251	10,085	101,049	1,015,113	10,242,540	102,460,573															
Number of TOKENS																				
AR	9,798	100,599	1,019,696	10,248,976	102,481,816	17,656	181,866	1,842,138	18,517,669	185,172,618	1,825	18,760	190,465	1,915,746	19,138,724	3,387	25,234	210,622	2,090,403	20,986,116
EN	11,816	119,796	1,301,839	12,687,922	120,993,163	11,820	119,839	1,302,217	12,691,602	121,006,803	2,047	21,058	211,029	2,122,365	21,234,437	3,262	24,634	220,391	2,159,566	21,693,709
ES	13,543	135,106	1,363,454	13,709,493	137,194,542	13,790	137,613	1,368,283	13,722,013	137,184,362	2,390	23,858	241,789	2,431,729	24,328,055	3,702	28,179	253,075	2,485,292	24,933,987
FR	13,173	134,702	1,358,567	13,682,024	136,811,870	13,617	139,250	1,404,001	14,121,629	141,403,257	2,362	24,442	247,027	2,485,203	24,874,355	3,664	28,541	257,305	2,527,889	25,374,629
RU	13,106	130,289	1,325,793	13,356,717	133,699,473	24,059	239,145	2,433,154	24,532,949	245,396,332	2,360	19,642	200,188	2,014,889	20,153,124	3,750	26,136	228,325	2,370,410	21,792,216
ZH	3,329	33,768	380,692	3,419,883	34,506,196	9,122	92,689	935,172	9,402,743	94,064,353	1,866	18,697	189,773	1,906,704	19,073,133	2,563	21,650	199,028	1,946,543	19,574,572
ZH_pinyin	11,391	115,377	1,166,227	11,732,204	117,267,349															
ZH_wubi	10,085	101,049	1,015,113	10,242,540	102,460,573	9,798	100,599	1,019,696	10,248,976	102,481,816										
AR_cp1256						13,106	130,289	1,325,793	13,356,717	133,699,473										
RU_cp1251																				
OOV type rate (%)																				
AR	35.58	5.38	0.77	0.00	0.00	29.46	4.88	0.81	0.00	0.00	93.61	72.07	35.51	13.07	4.82	7.86	0.30	0.00	0.00	0.00
EN	35.77	11.24	8.25	2.06	0.00	28.47	11.76	5.88	0.91	0.00	89.58	61.04	26.28	10.25	4.18	4.00	0.44	0.15	0.04	0.00
ES	26.13	12.61	11.71	3.60	0.00	24.55	10.91	8.18	0.91	0.00	90.09	64.27	27.73	9.61	3.95	4.08	0.44	0.17	0.05	0.00
FR	23.01	11.50	7.96	2.65	0.00	24.58	7.63	5.08	0.85	0.00	90.23	62.61	25.79	8.71	3.36	3.87	0.47	0.12	0.03	0.01
RU	26.71	6.16	2.74	0.00	0.00	23.61	4.86	2.08	0.00	0.00	90.20	69.75	32.20	11.10	3.91	4.39	0.23	0.03	0.01	0.00
ZH	61.84	26.97	6.68	1.01	0.15	20.26	2.61	0.65	0.00	0.00	89.73	64.10	29.54	10.44	3.84	67.89	27.00	5.27	0.67	0.04
ZH_pinyin	27.55	8.16	2.04	0.00	0.00	35.38	5.38	0.77	0.00	0.00										
ZH_wubi	28.33	4.17	0.83	0.00	0.00	26.71	6.16	2.74	0.00	0.00										
OOV token rate (%)																				
AR	0.31	0.01	0.00	0.00	0.00	0.11	0.00	0.00	0.00	0.00	53.94	25.89	9.36	3.14	1.15	0.82	0.08	0.00	0.00	0.00
EN	0.05	0.01	0.00	0.00	0.00	0.05	0.00	0.00	0.00	0.00	34.11	12.18	3.50	1.22	0.50	0.30	0.02	0.01	0.01	0.00
ES	0.04	0.01	0.00	0.02	0.00	0.04	0.01	0.00	0.00	0.00	31.52	12.57	3.72	1.15	0.46	0.19	0.03	0.04	0.02	0.00
FR	0.07	0.01	0.00	0.00	0.01	0.04	0.01	0.00	0.00	0.00	30.96	11.91	3.38	0.99	0.39	0.22	0.02	0.01	0.00	0.00
RU	0.22	0.08	0.16	0.10	0.00	0.11	0.00	0.00	0.00	0.00	49.05	22.75	7.55	2.36	0.81	0.71	0.02	0.00	0.00	0.00
ZH	10.44	1.21	0.00	0.02	0.01	0.10	0.00	0.00	0.00	0.00	37.81	13.74	4.42	1.42	0.53	22.02	4.99	0.79	0.00	0.00
ZH_pinyin	0.03	0.00	0.00	0.00	0.00	0.31	0.01	0.00	0.00	0.00										
ZH_wubi	0.09	0.00	0.00	0.00	0.00	0.22	0.01	0.00	0.00	0.00										
TTR (%)																				
AR	0.89	0.13	0.02	0.02	0.00	0.50	0.07	0.01	0.00	0.00	61.86	35.82	14.82	5.09	1.63	23.91	17.47	8.93	1.42	0.14
EN	0.64	0.08	0.01	0.01	0.00	0.67	0.09	0.01	0.00	0.00	42.79	19.70	6.47	2.02	0.66	24.03	13.83	4.88	1.24	0.13
ES	0.64	0.08	0.01	0.00	0.00	0.65	0.08	0.01	0.00	0.00	40.59	18.57	6.92	2.11	0.64	23.16	13.15	4.76	1.10	0.12
FR	0.64	0.08	0.01	0.00	0.00	0.65	0.08	0.01	0.00	0.00	40.43	18.97	6.33	1.82	0.53	22.16	12.86	4.05	1.10	0.12
RU	0.83	0.11	0.01	0.00	0.01	0.47	0.06	0.01	0.00	0.00	58.27	33.19	12.97	4.17	1.25	26.41	18.48	8.63	1.35	0.14
ZH	22.86	4.66	0.71	0.10	0.01	1.35	0.17	0.02	0.00	0.00	48.07	22.26	7.75	2.45	0.74	41.67	17.18	5.56	1.41	0.15
ZH_pinyin	0.62	0.09	0.01	0.00	0.00	0.89	0.13	0.02	0.00	0.00										
ZH_wubi	0.87	0.12	0.01	0.00	0.00	0.83	0.11	0.02	0.01	0.00										
Mean line length±std																				
0/25/50/75/100-th																				
AR	97.98 ± 55.47	100.60 ± 59.60	101.97 ± 59.10	102.49 ± 58.39	102.48 ± 58.39	176.56 ± 101.97	185.87 ± 108.08	184.21 ± 107.40	185.17 ± 108.29	185.17 ± 108.29	18.25 ± 10.12	18.75 ± 11.10	19.05 ± 10.05	19.16 ± 10.08	19.14 ± 10.82	33.87 ± 18.38	25.23 ± 15.36	21.06 ± 12.27	20.08 ± 12.02	20.09 ± 12.08
EN	118.16 ± 68.05	119.80 ± 71.15	120.88 ± 69.43	120.97 ± 69.54	120.07 ± 69.54	138.20 ± 68.05	119.86 ± 71.17	120.22 ± 70.02	120.02 ± 69.44	121.01 ± 69.55	20.47 ± 11.02	21.06 ± 12.60	21.10 ± 12.25	21.23 ± 12.15	21.23 ± 12.15	32.62 ± 17.93	24.63 ± 14.90	22.04 ± 12.78	21.60 ± 12.34	21.67 ± 12.40
ES	135.43 ± 77.54	135.11 ± 79.66	136.35 ± 79.00	137.09 ± 78.22	137.18 ± 78.45	137.90 ± 78.93	137.01 ± 81.03	138.93 ± 80.43	139.67 ± 79.61	139.75 ± 79.84	23.00 ± 13.29	23.86 ± 14.12	24.18 ± 13.94	24.32 ± 13.81	24.33 ± 13.86	37.02 ± 20.68	28.18 ± 16.96	25.31 ± 14.60	24.85 ± 14.13	24.93 ± 14.21
FR	131.73 ± 75.95	134.70 ± 80.48	135.86 ± 79.51	136.02 ± 79.71	138.61 ± 78.80	138.12 ± 78.50	139.25 ± 83.69	140.40 ± 82.18	141.22 ± 83.35	141.40 ± 81.55	23.62 ± 13.40	24.44 ± 14.69	24.70 ± 14.41	24.85 ± 14.27	24.87 ± 14.30	36.64 ± 21.18	25.73 ± 14.96	25.26 ± 14.49	25.37 ± 14.57	25.37 ± 14.57
RU	131.06 ± 76.80	139.29 ± 77.80	132.58 ± 77.80	133.57 ± 77.09	133.70 ± 77.19	340.35 ± 144.25	280.15 ± 144.35	245.33 ± 142.89	245.40 ± 143.08	245.80 ± 144.11	24.62 ± 14.08	19.64 ± 11.58	20.02 ± 11.63	20.15 ± 11.51	20.15 ± 11.50	37.60 ± 21.50	30.14 ± 15.06	21.83 ± 12.79	21.70 ± 12.75	21.79 ± 12.63
ZH	33.29 ± 17.41	33.77 ± 19.77	34.07 ± 19.50	34.21 ± 19.26	34.21 ± 19.26	91.22 ± 50.88	92.69 ± 55.28	93.92 ± 54.29	94.03 ± 53.67	94.06 ± 53.73	18.66 ± 10.28	18.70 ± 11.18	18.98 ± 11.05	19.07 ± 10.90	19.07 ± 10.90	25.63 ± 13.65	21.63 ± 13.59	19.90 ± 11.61	19.47 ± 11.13	19.57 ± 11.24
ZH_pinyin	113.01 ± 64.46	115.58 ± 68.18	106.62 ± 68.33	117.22 ± 67.41	34.21 ± 19.26		100.00 ± 59.60	97.98 ± 55.47	102.49 ± 58.39	102.48 ± 58.35										
ZH_wubi	100.35 ± 55.70	101.03 ± 60.13	101.91 ± 58.94	102.43 ± 58.21	102.46 ± 58.35	97.98 ± 55.47	100.60 ± 59.60	101.97 ± 59.10	102.49 ± 58.39	102.48 ± 58.39										
AR_cp1256																				
RU_cp1251																				

Statistics for dataset C

Representation	CHAR					BYTE					WORD					BPE				
Number of lines	100	1,000	10,000	100,000	1,000,000	100	1,000	10,000	100,000	1,000,000	100	1,000	10,000	100,000	1,000,000	100	1,000	10,000	100,000	1,000,000
Number of TYPES																				
Number of TOKENS																				
OOV type rate (%)																				
OOV token rate (%)																				
TTR (%)																				
Mean line length ±std 025/50/75/100-th																				

Statistics for development (dev) set

As a different set of vocabulary is learned from each training dataset and data size, BPE has a distinct dev set for each.

Representation / Number of lines in train set	CHAR	BYTE	WORD	BPE_A 100	1,000	100,000	1,000,000	BPE_B 100	1,000	100,000	1,000,000	BPE_C 100	1,000	100,000	1,000,000
Number of TYPES															
AR	130	123	13,836	708	3,232	8,994	12,430	865	3,991	11,473	12,954	13,000	908	4,119	12,934
EN	97	102	7,199	656	2,567	5,998	7,556	801	3,149	7,461	7,507	7,528	823	3,245	7,524
ES	111	110	8,551	680	2,832	6,919	8,871	833	3,436	8,752	8,869	8,906	834	3,424	8,871
FR	113	118	8,212	744	2,821	6,925	8,466	827	3,407	8,326	8,705	8,705	883	3,463	8,679
RU	146	144	12,819	878	3,769	10,065	12,788	1,024	4,438	12,505	11,602	12,054	1,038	4,509	12,882
ZH	1,976	153	7,413	3,224	4,215	6,386	7,654	3,261	4,481	7,541	6,735	7,702	3,260	4,524	7,654
ZH_pinyin ZH_wubi	98	130													
	120	146													
AR_cp1256 RU_cp1251															
Number of TOKENS															
AR	334,358	605,516	61,371	167,574	115,693	83,001	70,527	149,689	97,843	73,314	68,270	149,623	97,231	73,541
EN	301,222	391,260	67,629	150,826	101,782	77,089	70,339	140,256	90,871	73,531	69,348	140,377	90,360	73,468
ES	443,458	452,810	78,087	170,433	113,083	88,634	81,341	155,687	103,788	84,914	80,337	154,746	103,172	84,670
FR	438,083	452,556	78,745	166,289	114,694	88,726	81,559	156,256	104,067	85,115	80,844	153,745	104,091	85,125
RU	431,538	703,214	64,180	177,818	113,628	79,763	71,081	163,319	100,294	75,051	80,991	163,806	70,196	75,086
ZH	107,990	301,085	60,013	96,745	80,231	68,129	62,810	93,775	75,636	65,212	61,882	94,127	61,916	65,203
ZH_pinyin ZH_wubi	376,679 330,734	334,358 431,538													
AR_cp1256 RU_cp1251															
TTR (%)															
AR	0.04	0.02	22.54	0.42	2.79	10.84	17.62	0.58	4.08	14.64	19.17	0.61	4.24	14.52
EN	0.03	0.03	10.64	0.42	2.52	7.78	10.74	0.57	3.47	8.86	10.93	0.59	3.59	8.92
ES	0.03	0.03	10.95	0.40	2.48	7.81	10.91	0.54	3.30	8.80	11.15	0.54	3.32	8.87
FR	0.03	0.03	10.56	0.45	2.46	7.80	10.63	0.53	3.27	8.80	10.79	0.57	3.33	8.73
RU	0.03	0.02	19.97	0.49	3.32	12.64	17.99	0.63	4.42	14.73	18.51	0.63	4.51	14.66
ZH	1.83	0.05	12.35	3.33	5.25	9.37	12.19	3.48	5.92	10.33	12.46	3.46	5.07	10.41
ZH_pinyin ZH_wubi	0.03 0.04	0.04 0.03													
AR_cp1256 RU_cp1251															
Mean line length @25/50/75/100ch.															
AR	108.66 ± 58.01 3/60/110/153/277	196.70 ± 105.85 6/107/199/277/303	19.95 ± 10.58 1/12/20/27/58	54.46 ± 29.51 1/30/54/76/152	37.60 ± 20.51 1/22/37/52/125	26.07 ± 14.80 1/16/27/37/95	22.02 ± 12.56 1/14/22/32/75	48.65 ± 26.35 1/27/49/68/156	31.80 ± 17.76 1/18/32/44/110	23.83 ± 13.15 1/14/24/33/80	22.19 ± 12.07 1/13/22/31/71	48.63 ± 26.21 1/28/49/67/145	31.60 ± 17.53 1/18/31/44/110	23.00 ± 13.20 1/14/24/33/87	22.29 ± 12.14 1/13/22/31/73
EN	127.14 ± 68.64 6/81/330/181/289	127.16 ± 68.65 6/68/130/181/299	21.98 ± 11.81 1/13/22/31/61	50.64 ± 27.44 1/27/51/72/136	33.08 ± 18.07 1/19/33/46/110	25.10 ± 13.56 1/15/25/35/78	22.96 ± 12.27 1/14/23/32/71	45.58 ± 24.86 1/26/46/65/129	29.53 ± 16.30 1/17/29/41/94	23.90 ± 12.95 1/14/24/33/74	22.54 ± 12.05 1/13/23/31/65	45.62 ± 24.67 1/26/46/66/122	29.37 ± 16.13 1/17/29/41/92	23.88 ± 12.91 1/14/24/33/73	22.63 ± 12.12 1/13/23/31/65
ES	114.28 ± 77.78 5/77/145/207/300	140.96 ± 79.21 5/78/148/211/307	25.26 ± 13.56 1/15/25/36/63	55.39 ± 30.13 1/30/56/79/141	37.24 ± 20.13 1/21/37/52/111	28.51 ± 15.53 1/17/29/41/85	26.44 ± 14.14 1/15/26/37/73	50.08 ± 27.66 1/27/51/72/133	33.72 ± 18.48 1/19/34/47/103	27.00 ± 14.88 1/15/28/39/75	26.11 ± 13.94 1/15/26/37/71	50.28 ± 27.27 1/28/51/71/131	33.53 ± 18.38 1/19/34/47/95	27.38 ± 14.86 1/15/28/39/75	26.19 ± 13.99 1/15/26/37/71
FR	142.37 ± 77.81 4/74/145/205/300	147.08 ± 80.30 4/77/150/212/310	25.59 ± 13.86 1/14/26/36/66	54.04 ± 29.55 1/29/55/76/139	37.27 ± 20.65 1/20/38/52/119	28.84 ± 15.76 1/16/29/40/89	26.51 ± 14.35 1/16/27/37/70	50.78 ± 27.79 1/27/52/72/135	33.82 ± 18.74 1/18/34/47/108	27.66 ± 15.11 1/15/28/39/80	26.22 ± 14.16 1/14/27/37/69	49.97 ± 27.25 1/27/51/70/131	33.88 ± 18.80 1/18/34/47/107	27.66 ± 15.09 1/15/28/39/84	26.31 ± 14.16 1/14/27/37/69
RU	140.25 ± 76.21 5/75/141/200/300	207.79 ± 141.53 7/136/359/370/369	20.86 ± 11.25 1/12/21/29/89	57.79 ± 32.12 1/31/58/82/185	36.93 ± 20.73 1/21/36/52/185	25.02 ± 14.48 1/15/26/36/128	23.10 ± 12.71 1/13/23/32/106	53.08 ± 29.00 1/29/53/75/185	32.99 ± 18.42 1/18/32/46/106	24.39 ± 13.59 1/14/24/34/112	22.75 ± 12.46 1/13/23/32/93	53.24 ± 29.18 2/30/53/76/185	32.49 ± 18.49 1/18/32/45/161	24.41 ± 13.57 1/14/24/34/116	22.74 ± 12.45 1/13/23/32/92
ZH	35.10 ± 18.48 2/21/35/49/125	97.85 ± 52.10 4/50/99/138/288	19.50 ± 10.42 1/11/20/27/64	31.44 ± 16.86 1/18/31/44/100	26.07 ± 14.19 1/16/26/36/93	22.14 ± 12.02 1/13/22/31/80	20.41 ± 11.05 1/12/20/29/74	30.88 ± 16.47 1/17/30/43/104	24.58 ± 13.42 1/14/24/34/92	21.19 ± 11.49 1/12/21/29/71	20.09 ± 10.79 1/12/20/28/65	30.39 ± 16.45 1/18/30/43/101	24.01 ± 13.49 1/14/24/34/93	20.12 ± 10.81 1/12/20/28/64	20.09 ± 10.79 1/12/20/28/65
ZH_pinyin	122.22 ± 65.59 6/67/123/173/353	109.66 ± 58.01 3/60/110/133/277													
ZH_wubi	107.49 ± 56.73 4/60/108/151/294														
AR_cp1256		109.66 ± 58.01 3/60/110/133/277													
RU_cp1251		140.25 ± 76.21 5/75/141/200/300													

E ENLARGED FIGURES FOR ALL 30 LANGUAGE DIRECTIONS (AGGREGATE RESULTS FROM ALL RUNS)

Figure 4: CHAR: character models

Figure 4: CHAR: character models (target language as facet)

Figure 5: CHAR with Pinyin for ZH_{trg}

Figure 5: CHAR with Pinyin for ZH_{trg} (target language as facet)

Figure 6: CHAR with Wubi for ZH_{trg}

Figure 6: CHAR with Wubi for ZH_{trg} (target language as facet)

Figure 7: BYTE models with UTF-8 encoding

Figure 7: BYTE models with UTF-8 encoding (target language as facet)

Figure 8: BYTE with AR_{trg} & RU_{trg} optimized with code pages 1256 & 1251 ($ARRU_{trg}$)

Figure 8: BYTE with AR_{trg} & RU_{trg} optimized with code pages 1256 & 1251 (target language as facet)

Figure 9: BYTE with directions AR-RU & RU-AR optimized on both source and target sides ($\mathrm{ARRU}_{src,trg}$)

Figure 9: BYTE with directions AR-RU & RU-AR optimized on both source and target sides (target language as facet)

Figure 10: WORD models

Figure 10: WORD models (target language as facet)

Figure 11: BPE models

Figure 11: BPE models (target language as facet)

Fairness in Representation for Multilingual NLP: Insights from Controlled Experiments on Conditional Language Modeling

Version 0.1