SeaFormer: Squeeze-enhanced Axial Transformer for Mobile Semantic Segmentation

Abstract

Since the introduction of Vision Transformers, the landscape of many computer vision tasks (*e.g.*, semantic segmentation), which has been overwhelmingly dominated by CNNs, recently has significantly revolutionized. However, the computational cost and memory requirement render these methods unsuitable on the mobile device, especially for the high resolution per-pixel semantic segmentation task. In this paper, we introduce a new method *squeeze-enhanced Axial Transformer* (***SeaFormer***) for mobile semantic segmentation. Specifically, we design a generic attention block characterized by the formulation of squeeze Axial and detail enhancement. It can be further used to create a family of backbone architectures with superior cost-effectiveness. Coupled with a light segmentation head, we demonstrate state-of-the-art results on the ADE20K, Pascal Context and COCO-stuff datasets. Critically, we beat both the mobile-friendly rivals and Transformer-based counterparts with better performance and lower latency without bells and whistles. Beyond semantic segmentation, we further apply the proposed SeaFormer architecture to image classification problem, demonstrating the potentials of serving as a versatile mobile-friendly backbone. Our anonymous repository is at `https://anonymous.4open.science/r/SeaFormer_anonymous-5C8C`.

1 Introduction

As a fundamental problem in computer vision, semantic segmentation aims to assign a semantic class label to each pixel in an image. Conventional methods rely on stacking local convolution kernel Long et al. (2015) to perceive the long-range structure information of the image.

Since the introduction of Vision Transformers Dosovitskiy et al. (2020), the landscape of semantic segmentation has significantly revolutionized. Transformer-based approaches Zheng et al. (2021); Xie et al. (2021) have remarkably demonstrated the capability of global context modelling. However, the computational cost and memory requirement of Transformer render these methods unsuitable on mobile devices, especially for the high resolution imagery inputs.

Following the conventional wisdom of efficient operation, local/window-based attention Luong et al. (2015); Liu et al. (2021); Huang et al. (2021a); Yuan et al. (2021), efficient attention Shen et al. (2021); Xu et al. (2021), Axial attention Huang et al. (2019); Ho et al. (2019); Wang et al. (2020a) and some other lightweight attention mechanisms Liu et al. (2018); Cao et al. (2019); Woo et al. (2018); Wang et al. (2020b); Choromanski et al. (2020); Chen et al. (2017); Mehta & Rastegari (2021) are introduced.

However, these advances are still insufficient to satisfy the design requirements and constraints for mobile device due to the high latency on the high-resolution inputs (see Figure 1). Recently there is a surge of interest in building a Transformer-based mobile semantic segmentation.

In order to reduce the computation cost at high resolution, TopFormer Zhang et al. (2022b) dedicates to apply the global self-attention at 1/64 scale of the original input, which definitely harms the segmentation performance.

To solve the dilemma of high-resolutional computation for pixel-wise segmentation task and low latency requirement on the mobile device in a performance harmless way, we propose a family

Figure 1: **Left**: Latency comparison with Transformer Vaswani et al. (2017), MixFormer Chen et al. (2022), ACmix Pan et al. (2021), Axial attention Ho et al. (2019) and local attention Luong et al. (2015). It is measured with a single module of channel dimension 64 on a Qualcomm Snapdragon 865 processor. **Right**: The mIoU versus latency on the ADE20K *val* set. MV2 means MobileNetV2 Sandler et al. (2018). MV3-L means MobileNetV3-Large Howard et al. (2019). MV3-Lr denotes MobileNetV3-Large-reduce Howard et al. (2019). The latency is measured on a single Qualcomm Snapdragon 865, and only an ARM CPU core is used for speed testing. No other means of acceleration, e.g., GPU or quantification, is used. For figure *Right*, the input size is 512×512. SeaFormer achieves superior trade-off between mIoU and latency.

of mobile-friendly Transformer-based semantic segmentation model, dubbed as *squeeze-enhanced Axial Transformer* (SeaFormer), which reduces the computational complexity of axial attention from $\mathcal{O}((H+W)HW)$ to $\mathcal{O}(HW)$, to achieve superior accuracy-efficiency trade-off on mobile devices and fill the vacancy of mobile-friendly efficient Transformer.

The core building block *squeeze-enhanced Axial attention* (SEA attention) seeks to squeeze (pool) the input feature maps along horizontal/vertical axis into a compact column/row and computes self-attention. We concatenate query, keys and values to compensate the detail information sacrificed during squeeze and then feed it into a depth-wise convolution layer to enhance local details.

Coupled with a light segmentation head, our design (see Figure 2) with the proposed SeaFormer layer in the small-scale feature is capable of conducting high resolution image semantic segmentation with low latency on the mobile device. As shown in Figure 1, the proposed SeaFormer outperforms other efficient neural networks on the ADE20K dataset with lower latency. In particular, SeaFormer-Base is superior to the lightweight CNN conterpart MobileNetV3 (41.0 *vs.*33.1 mIoU) with lower latency (106ms *vs.*126ms) on an ARM-based mobile device.

We make the following **contributions**: **(i)** We introduce a novel *squeeze-enhanced Axial Transformer* (SeaFormer) framework for mobile semantic segmentation; **(ii)** Critically, we design a generic attention block characterized by the formulation of squeeze Axial and detail enhancement; It can be used to create a family of backbone architectures with superior cost-effectiveness; **(iii)** We show top performance on the ADE20K, Pascal Context and COCO-stuff dataset, beating both the mobile-friendly rival and Transformer-based segmentation model with clear margins; **(iv)** Beyond semantic segmentation, we further apply the proposed SeaFormer architecture to image classification problem, demonstrating the potentials of serving as a versatile mobile-friendly backbone.

2 RELATED WORK

Combination of Transformers and convolution Convolution is relatively efficient but not suitable to capture long-range dependencies and vision Transformer has powerful capability with global receptive field but lacks efficiency due to the computation of self-attention. In order to make full use of both of their advantages, MobileViT Mehta & Rastegari (2021), TopFormer Zhang et al. (2022b), LVT Yang et al. (2022), Mobile-Former Chen et al. (2021), EdgeViTs Pan et al. (2022), MobileViTv2 Mehta & Rastegari (2022) and EdgeFormer Zhang et al. (2022a) are constructed as efficient ViTs by combining convolution with Transformers. For MobileViT, Mobile-Former and TopFormer,

they are restricted by Transformer blocks and have to trade off between efficiency and performance in model design. As for LVT, MobileViTv2 and EdgeViTs, they keep the model size small at the cost of relatively high computation, which also means high latency.

Axial attention and variants Axial attention Huang et al. (2019); Ho et al. (2019); Wang et al. (2020a) is designed to reduce the computational complexity of original global self-attention Vaswani et al. (2017). It computes self-attention over a single axis at a time and stacks a horizontal and a vertical axial attention module to obtain the global receptive field. Strip pooling Hou et al. (2020) and Coordinate attention Hou et al. (2021) uses a band shape pooling window to pool along either the horizontal or the vertical dimension to gather long-range context. Kronecker Attention Networks Gao et al. (2020) uses the juxtaposition of horizontal and lateral average matrices to average the input matrices and performs attention operation after that. These methods and other similar implementations provide performance gains partly at considerably low computational cost compared with Axial attention. However, they ignore the lack of local details brought by the pooling/average operation.

Mobile semantic segmentation The mainstream of efficient segmentation methods are based on lightweight CNNs. DFANet Li et al. (2019) adopts a lightweight backbone to reduce computation cost and adds a feature aggregation module to refine high-level and low-level features. ICNet Zhao et al. (2018) designs an image cascade network to speed up the algorithm, while BiSeNet Yu et al. (2018; 2021) proposes two-stream paths for low-level details and high-level context information, separately. Fast-SCNN Poudel et al. (2019) shares the computational cost of the multi-branch network to yield a run-time fast segmentation CNN. TopFormer Zhang et al. (2022b) presents a new architecture with a combination of CNNs and ViT and achieves a good trade-off between accuracy and computational cost for mobile semantic segmentation. However, it is still restricted by the heavy computation load of global self-attention.

3 METHOD

3.1 OVERALL ARCHITECTURE

Inspired by the two-branch architectures Yu et al. (2021); Poudel et al. (2019); Hong et al. (2021); Huang et al. (2021b); Chen et al. (2021), we design a **s**queeze-**e**nhanced **A**xial Trans**former** (**SeaFormer**) framework. As is shown in Figure 2, SeaFormer consists of these parts: *shared STEM*, *context branch*, *spatial branch*, *fusion block* and *light segmentation head*.

Shared STEM For a fair comparison, we follow TopFormer to design STEM. It consists of one regular convolution with stride of 2 followed by four MobileNet blocks where stride of the first and third block is 2, so feature map at 1/8 spatial resolution is provided; *i.e.*, given an image $\mathbf{x}_i \in \mathbb{R}^{H_i \times W_i \times 3}$, the shared STEM outputs the feature map $\mathbf{x}_s \in \mathbb{R}^{H_s \times W_s \times C_s}$, where $H_s = \frac{H_i}{8}, W_s = \frac{W_i}{8}$. The context branch and the spatial branch share the produced feature map, which allows us to build a fast semantic segmentation model.

Context branch The context branch is designed to capture context-rich information from the feature map $\mathbf{x}_s$. As illustrated in the red branch of Figure 2, the context branch is divided into three stages. To obtain larger receptive field, we stack SeaFormer layers after applying a MobileNet block to down-sampling and expanding feature dimension. Compared with the standard convolution as the down-sampling module, MobileNet block increases the representation capacity of the model while maintaining a lower amount of computation and latency. For variants except SeaFormer-Large, SeaFormer layers are applied in the last two stages for superior trade-off between accuracy and efficiency. For SeaFormer-Large, we insert SeaFormer layers in each stage of context branch. To achieve a good trade-off between segmentation accuracy and inference speed, we design a squeeze-enhanced Axial attention block (SEA attention) illustrated in the next subsection.

Spatial branch The spatial branch is designed to obtain spatial information in high resolution. Identical to the context branch, the spatial branch reuses feature maps $\mathbf{x}_s$. However, the feature from the early convolution layers contains rich spatial details but lacks high-level semantic information.

Figure 2: The overall architecture of our Seaformer. The architecture contains shared stem, context branch (**red**), spatial brach (**blue**), fusion block and light segmentation head. `MV2` block means MobileNet-V2 block and `MV2 ↓2` means MobileNet-V2 block with downsampling. SeaFormer layers and fusion blocks with dash box only exist in SeaFormer-Large model.

Consequently, we design a fusion block to fuse the features in the context branch into the spatial branch, bringing high-level semantic information into the low-level spatial information.

Fusion block As depicted in Figure 2, high resolution feature maps in the spatial branch are followed by a 1 × 1 convolution and a batch normalization layer to produce a feature to fuse. Low resolution feature maps in the context branch are fed into a 1 × 1 convolution layer, a batch normalization layer, a sigmoid layer and up-sampled to high resolution to produce semantics weights by bilinear interpolation. Then, the semantics weights from context branch are element-wisely multiplied to the high resolution feature from spatial branch. The fusion block enables low-level spatial features to obtain high-level semantic information.

Light segmentation head The feature after the last fusion block is fed into the proposed segmentation head directly, as demonstrated in Figure 2. For fast inference purpose, our light segmentation head consists of two convolution layers, which are followed by a batch normalization layer separately and the feature from the first batch normalization layer is fed into an activation layer.

3.2 SQUEEZE-ENHANCED AXIAL ATTENTION

The global attention can be expressed as

$$\mathbf{y}_o = \sum_{p \in \mathcal{G}(o)} \text{softmax}_p \left(\mathbf{q}_o^\top \mathbf{k}_p \right) \mathbf{v}_p \tag{1}$$

where $\mathbf{x} \in \mathbb{R}^{H \times W \times C}$. $\mathbf{q}, \mathbf{k}, \mathbf{v}$ are linear projection of $\mathbf{x}$, *i.e.* $\mathbf{q} = \mathbf{W}_q \mathbf{x}, \mathbf{k} = \mathbf{W}_k \mathbf{x}, \mathbf{v} = \mathbf{W}_v \mathbf{x}$, where $\mathbf{W}_q, \mathbf{W}_k \in \mathbb{R}^{C_{qk} \times C}, \mathbf{W}_v \in \mathbb{R}^{C_v \times C}$ are learnable weights. $\mathcal{G}(o)$ means all positions on the feature map of location $o = (i, j)$. When traditional attention module is applied on a feature map of $H \times W \times C$, the time complexity can be $\mathcal{O}(H^2 W^2 (C_{qk} + C_v))$, leading to low efficiency and high latency.

$$\mathbf{y}_o = \sum_{p \in \mathcal{N}_{m \times m}(o)} \text{softmax}_p \left(\mathbf{q}_o^\top \mathbf{k}_p \right) \mathbf{v}_p \tag{2}$$

$$\mathbf{y}_o = \sum_{p \in \mathcal{N}_{1 \times W}(o)} \text{softmax}_p \left(\mathbf{q}_o^\top \mathbf{k}_p \right) \mathbf{v}_p + \sum_{p \in \mathcal{N}_{H \times 1}(o)} \text{softmax}_p \left(\mathbf{q}_o^\top \mathbf{k}_p \right) \mathbf{v}_p \tag{3}$$

To improve the efficiency, there are some works Liu et al. (2021); Huang et al. (2019); Ho et al. (2019) computing self-attention within the local region. We show two most representative efficient Transformer in Equation 2, 3. Equation 2 is represented by window-based attention Luong et al. (2015) successfully reducing the time complexity to $\mathcal{O}(m^2 H W (C_{qk} + C_v)) = \mathcal{O}(HW)$, where $\mathcal{N}_{m \times m}(o)$ means the neighbour $m \times m$ positions of o, but loosing global receptiveness. The Equation 3 is represented by Axial attention Ho et al. (2019), which only reduces the time complexity to $\mathcal{O}((H + W) H W (C_{qk} + C_v)) = \mathcal{O}((HW)^{1.5})$, where $\mathcal{N}_{H \times 1}(o)$ means all the positions of the column of o; $\mathcal{N}_{1 \times W}(o)$ means all the positions of the row of o.

According to their drawbacks, we propose the mobile-friendly squeeze-enhanced Axial attention, with a succinct squeeze Axial attention for global semantics extraction and an efficient convolution-based detail enhancement kernel for local details supplement.

Figure 3: **Right**: the schematic illustration of the proposed squeeze-enhanced Axial Transformer layer including a squeeze-enhanced Axial attention and a Feed-Forward Network (FFN). **Left** is the squeeze-enhanced Axial Transformer layer, including detail enhancement kernel and squeeze Axial attention.

$$\mathbf{q}_{(h)} = \frac{1}{W}\left(\mathbf{q}^{\to(C_{qk},H,W)}\mathbb{1}_W\right)^{\to(H,C_{qk})}, \quad \mathbf{q}_{(v)} = \frac{1}{H}\left(\mathbf{q}^{\to(C_{qk},W,H)}\mathbb{1}_H\right)^{\to(W,C_{qk})} \qquad (4)$$

Squeeze Axial attention To achieve a more efficient computation and aggregate global information at the same time, we resort to a more radical strategy. In the same way, $\mathbf{q}, \mathbf{k}, \mathbf{v}$ are first get from $\mathbf{x}$ with $\mathbf{W}_q^{(s)}, \mathbf{W}_k^{(s)} \in \mathbb{R}^{C_{qk} \times C}, \mathbf{W}_v^{(s)} \in \mathbb{R}^{C_v \times C}$. According to Equation 4, we first implement *horizontal squeeze* by taking average of query feature map on the horizontal direction. In the same way, the right shows the *vertical squeeze* on the vertical direction. $\mathbf{z}^{\to(\cdot)}$ means permuting the dimension of tensor $\mathbf{z}$ as given, and $\mathbb{1}_m \in \mathbb{R}^m$ is a vector with all the elements equal to 1. The squeeze operation on $\mathbf{q}$ also repeats on $\mathbf{k}$ and $\mathbf{v}$, so we finally get $\mathbf{q}_{(h)}, \mathbf{k}_{(h)}, \mathbf{v}_{(h)} \in \mathbb{R}^{H \times C_{qk}}$, $\mathbf{q}_{(v)}, \mathbf{k}_{(v)}, \mathbf{v}_{(v)} \in \mathbb{R}^{W \times C_{qk}}$. The squeeze operation reserves the global information to a single axis, thus greatly alleviating the following global semantic extraction showing by Equation 5.

$$\mathbf{y}_{(i,j)} = \sum_{p=1}^{H} \text{softmax}_p\left(\mathbf{q}_{(h)i}^{\top}\mathbf{k}_{(h)p}\right)\mathbf{v}_{(h)p} + \sum_{p=1}^{W} \text{softmax}_p\left(\mathbf{q}_{(v)j}^{\top}\mathbf{k}_{(v)p}\right)\mathbf{v}_{(v)p} \qquad (5)$$

Each position of feature map propagates information only on two squeezed axial features. Although it shows no distinct computation reduction comparing to Equation 3, repeat of Equation 5 can be simply implemented by the most efficient `broadcast` operation. The detail is shown in Figure 3. Time complexity for squeezing $\mathbf{q}, \mathbf{k}, \mathbf{v}$ is $\mathcal{O}((H + W)(2C_{qk} + C_v))$ and the attention operation takes $\mathcal{O}((H^2 + W^2)(C_{qk} + C_v))$ time. Thus, our squeeze Axial attention successfully reduces time complexity to $\mathcal{O}(HW)$.

Squeeze Axial position embedding Equation 4 are, however, not positional-aware, including no positional information of feature map. Hence, we propose squeeze Axial position embedding to squeeze Axial attention. For squeeze Axial attention, we render both $\mathbf{q}_{(h)}$ and $\mathbf{k}_{(h)}$ to be aware of their position in squeezed axial feature by introducing positional embedding $\mathbf{r}_{(h)}^q, \mathbf{r}_{(h)}^k \in \mathbb{R}^{H \times C_{qk}}$, which are linearly interpolated from learnable parameters $\mathbf{B}_{(h)}^q, \mathbf{B}_{(h)}^k \in \mathbb{R}^{L \times C_{qk}}$. L is a constant. In the same way, $\mathbf{r}_{(v)}^q, \mathbf{r}_{(v)}^k \in \mathbb{R}^{W \times C_{qk}}$ are applied to $\mathbf{q}_{(v)}, \mathbf{k}_{(v)}$. Thus, the positional-aware squeeze Axial attention can be expressed as Equation 6.

$$\begin{aligned}\mathbf{y}_{(i,j)} = &\sum_{p=1}^{H} \text{softmax}_p\left((\mathbf{q}_{(h)i} + \mathbf{r}_{(h)i}^q)^{\top}(\mathbf{k}_{(h)p} + \mathbf{r}_{(h)p}^k)\right)\mathbf{v}_{(h)p} \\ &+ \sum_{p=1}^{W} \text{softmax}_p\left((\mathbf{q}_{(v)j} + \mathbf{r}_{(v)i}^q)^{\top}(\mathbf{k}_{(v)p} + \mathbf{r}_{(v)p}^k)\right)\mathbf{v}_{(v)p}\end{aligned} \qquad (6)$$

Detail enhancement kernel The squeeze operation, though extracting global semantic information efficiently, sacrifices the local details. Hence an auxiliary convolution-based kernel is applied to enhance the spatial details. As is shown in the upper path of Figure 3, $\mathbf{q}, \mathbf{k}, \mathbf{v}$ are first get from $\mathbf{x}$ with another $\mathbf{W}_q^{(e)}, \mathbf{W}_k^{(e)} \in \mathbb{R}^{C_{qk} \times C}, \mathbf{W}_v^{(e)} \in \mathbb{R}^{C_v \times C}$ and are concatenated on the channel dimension and then passed to a block made up of 3×3 depth-wise convolution and batch normalization. By using a 3×3 convolution, auxiliary local details can be aggregated from $\mathbf{q}, \mathbf{k}, \mathbf{v}$. And then a linear projection with activation function and batch normalization are used to squeeze $(2C_{qk} + C_v)$ dimension to C and generate detail enhancement weights. Finally, the enhancement feature will be fused with the feature given by squeeze Axial attention. Different enhancement mode including element-wise addition and multiplication will be compared in experiment section. Time complexity for the 3×3 depth-wise convolution is $\mathcal{O}(3^2 HW(2C_{qk} + C_v))$ and the time complexity for the 1×1 convolution is $\mathcal{O}(HWC(2C_{qk} + C_v))$. Time for the other operations like activation can be omitted.

Complexity analysis In our application, we set $C_{qk} = 0.5C_v$ to further reduce computation cost. The total time complexity of squeeze-enhanced Axial attention is

$$\mathcal{O}((H^2 + W^2)(C_{qk} + C_v)) + \mathcal{O}((H + W)(2C_{qk} + C_v)) + \mathcal{O}((HWC + 9HW)(2C_{qk} + C_v))$$
$$= \mathcal{O}((1.5H^2 + 1.5W^2 + 2HWC + 18HW + 2H + 2W)C_v) = \mathcal{O}(HW), \tag{7}$$

if we assume $H = W$ and take channel as constant. SEA attention is linear to the feature map size theoretically. Moreover, SEA Attention only includes mobile-friendly operation like convolution, pooling, matrix multiplication and so on.

Architecture and Variants SeaFormer backbone contains 6 stages, corresponding to the shared STEM and context branch in figure 2. When conducting the image classification experiments, a pooling layer and a linear layer are added at the end of the context branch. we introduce four variants, SeaFormer-Tiny, Small, Base and Large (T, S, B and L). More configuration details are listed in supplementary material.

4 EXPERIMENTS

We evaluate our method on semantic segmentation and image classification tasks. We first describe implementation details and compare results with state of the art. We then conduct a series of ablation studies to validate the design of SeaFormer. Each proposed component and important hyper-parameters are examined thoroughly.

4.1 EXPERIMENTAL SETUP

4.1.1 DATASET

We perform segmentation experiments over ADE20K Zhou et al. (2017), Pascal-Context Mottaghi et al. (2014) and COCO-Stuff Caesar et al. (2018). The mean of intersection over union (mIoU) is set as evaluation metric. We convert full-precision models to TNN Contributors (2019) and measure latency on an ARM-based device with a single Qualcomm Snapdragon 865 processor. **ADE20K** dataset covers 150 categories ,containing 25K images that are split into 20K/2K/3K for *Train/val/test*. **PASCAL Context** dataset has 4998/5105 images for *train* and *test*, covering 59 semantic labels and 1 background. **COCO-Stuff** dataset augments COCO dataset with pixel-level stuff annotations. 10K complex images are selected from COCO. The *train* and *test* set contain 9K/1K images.

4.1.2 IMPLEMENTATION DETAILS

We set ImageNet-1K Deng et al. (2009) pretrained network as the backbone, and training details of ImageNet-1K are illustrated in the last subsection. For semantic segmentation, standard Batch-Norm Ioffe & Szegedy (2015) layer is replaced by synchronize BatchNorm.

Training Our implementation is based on public codebase `mmsegmentation` Contributors (2020). Following TopFormer Zhang et al. (2022b), we train the models for 160,000 iterations

Backbone	Decoder	Params	FLOPs	mIoU	Latency
MobileNetV2	LR-ASPP	2.2M	2.8G	32.0	177ms
MobileNetV3-Large-reduce	LR-ASPP	1.6M	1.3G	32.3	81ms
MobileNetV3-Large	LR-ASPP	3.2M	2.0G	33.1	126ms
HRNet-W18-Small	HRNet-W18-Small	4.0M	10.2G	33.4	639ms
TopFormer-T	Simple Head	1.4M	0.6G	33.6	43ms
TopFormer-T*	Simple Head	1.4M	0.6G	34.6	43ms
SeaFormer-T	Light Head	1.7M	0.6G	**35.0**	**40ms**
SeaFormer-T*	Light Head	1.7M	0.6G	**35.8±0.35**	**40ms**
ConvMLP-S	Semantic FPN	12.8M	33.8G	35.8	777ms
EfficientNet	DeepLabV3+	17.1M	26.9G	36.2	970ms
MobileNetV2	Lite-ASPP	2.9M	4.4G	36.6	235ms
TopFormer-S	Simple Head	3.1M	1.2G	36.5	74ms
TopFormer-S*	Simple Head	3.1M	1.2G	37.0	74ms
SeaFormer-S	Light Head	4.0M	1.1G	**38.1**	**67ms**
SeaFormer-S*	Light Head	4.0M	1.1G	**39.4±0.25**	**67ms**
MiT-B0	SegFormer	3.8M	8.4G	37.4	770ms
ResNet18	Lite-ASPP	12.5M	19.2G	37.5	648ms
ShuffleNetV2-1.5x	DeepLabV3+	16.9M	15.3G	37.6	960ms
MobileNetV2	DeepLabV3+	15.4M	25.8G	38.1	1035ms
TopFormer-B	Simple Head	5.1M	1.8G	38.3	110ms
TopFormer-B*	Simple Head	5.1M	1.8G	39.2	110ms
SeaFormer-B	Light Head	8.6M	1.8G	**40.2**	**106ms**
SeaFormer-B*	Light Head	8.6M	1.8G	**41.0±0.45**	**106ms**
MiT-B1	SegFormer	13.7M	15.9G	41.6	1300ms
SeaFormer-L	Light Head	14.0M	6.5G	**42.7**	**367ms**
SeaFormer-L*	Light Head	14.0M	6.5G	**43.7±0.36**	**367ms**

Table 1: Results of semantic segmentation on ADE20K *val* set, * indicates training batch size is 32. The latency is measured on a single Qualcomm Snapdragon 865 with input size 512×512, and only an ARM CPU core is used for speed testing. References: MobileNetV2 Sandler et al. (2018), MobileNetV3 Howard et al. (2019), HRNet Yuan et al. (2020), TopFormer Zhang et al. (2022b), ConvMLP Li et al. (2021), Semantic FPN Kirillov et al. (2019), EfficientNet Tan & Le (2019), DeepLabV3+ and Lite-ASPP Chen et al. (2018), SegFormer Xie et al. (2021), ResNet He et al. (2016), ShuffleNetV2-1.5x Ma et al. (2018).

on the ADE20K dataset and 80,000 iterations on COCO-Stuff and PASCAL Context datasets with 8 NVIDIA V100. Besides, we adopt the same data augmentation strategy for fair comparison. The initial learning rate is 0.0005 and weight decay is 0.01. A "poly" learning rate scheduled with factor 1.0 is adopted. On COCO-Stuff and PASCAL Context datasets, we use the default augmentation strategy of Contributors (2020). During inference, we set the same resize and crop rules as Top-Former to ensure the fairness.

4.2 Comparison with state of the art

ADE20K Table 1 shows the results of SeaFormer and previous efficient backbones on ADE20K *val* set. The comparison covers Params, FLOPs, Latency and mIoU. As shown in Table 1, SeaFormer outperforms these efficient approaches with comparable or less FLOPs and lower latency. Compared with specially designed mobile backbone, TopFormer, which sets global self-attention as its semantics extractor, SeaFormer achieves higher segmentation accuracy with lower latency. And the performance of SeaFormer-B surpasses MobileNetV3 by a large margin of +7.9% mIoU with lower latency (-16%). The results demonstrate that our SeaFormer layers improve the representation capability significantly.

Pascal Context We evaluate performance on Pascal Context *val* set over 59 categories and 60 categories (including background). Table 2a reveals that SeaFormer-S is +1.4% mIoU higher (45.08 *vs.*43.68) than TopFormer-S with lower latency.

COCO Stuff We compare SeaFormer with the previous approaches on COCO-Stuff *val* set. Table 2b demonstrates that SeaFormer-S is +2.0% mIoU higher (32.82 *vs.*30.83) than TopFormer-S with less computation cost and lower latency.

Backbone	Decoder	F(G)	mIoU(60/59)	Backbone	Decoder	F(G)	mIoU
MBV2-s16	DeepLabV3+	22.24	38.59/42.34	MBV2-s8	PSPNet	52.94	30.14
ENet-s16	DeepLabV3+	23.00	39.19/43.07	ENet-s16	DeepLabV3+	27.10	31.45
MBV3-s16	LR-ASPP	2.04	35.05/38.02	MBV3-s16	LR-ASPP	2.37	25.16
TopFormer-T	Simple Head	0.53	36.41/40.39	TopFormer-T	Simple Head	0.64	28.34
SeaFormer-T	Light Head	0.51	**37.27/41.49**	**SeaFormer-T**	Light Head	0.62	**29.24**
TopFormer-S	Simple Head	0.98	39.06/43.68	TopFormer-S	Simple Head	1.18	30.83
SeaFormer-S	Light Head	0.98	**40.20/45.08**	**SeaFormer-S**	Light Head	1.15	**32.82**
TopFormer-B	Simple Head	1.54	41.01/45.28	TopFormer-B	Simple Head	1.83	33.43
SeaFormer-B	Light Head	1.57	**41.77/45.92**	**SeaFormer-B**	Light Head	1.81	**34.07**

Table 2: (a) Results on Pascal Context *val* set. (b) Results on COCO-Stuff *test* set. F means `Flops`. We omit the latency in table 2 as the input resolution in table 1 and table 2 are almost the same.

4.3 ABLATION STUDIES

In this section, we ablate different self-attention implementations and some important design elements in the proposed model, including our squeeze-enhanced Axial attention module (SEA attention) and fusion block on ADE20K dataset.

Enhance Attn kernel	branch	Enhance input	Enhance mode	Params	FLOPs	Latency	Top1	mIoU
✔		-	-	1.3M	0.58G	38ms	65.9	32.5
	✔	-	-	1.4M	0.57G	38ms	66.3	33.5
✔	✔	conv(x)	Mul	1.6M	0.60G	40ms	67.2	34.9
✔	✔	upconv(x)	Mul	1.8M	0.62G	41ms	68.1	35.9
✔	✔	concat[qkv]	Mul	1.7M	0.60G	40ms	67.9	35.8
✔	✔	concat[qkv]	Add	1.7M	0.60G	40ms	67.3	35.4

Table 3: Ablation studies on components in SEA attention. Enhancement input means the input of detail enhancement kernel. conv(x) means x followed by a point-wise conv. upconv(x) has the same operations as conv(x) except different channels as upconv(x) is from C_{in} to $C_q + C_k + C_v$ and conv(x) is from C_{in} to C_{in}. concat[qkv] stands for concatenation of Q,K and V.

Different self-attention module   To verify the effectiveness of SEA attention, we experiment with convolution, Global attention, Local attention, Axial attention and three convolution enhanced attention methods including our SEA attention, ACmix and MixFormer. The ablation experiments are organized in seven groups based on our pipeline. Since the resolution of computing attention is relatively small, the window size in Local attention, ACmix, and MixFormer is set to 4. We adjust the channels when applying different attention modules to keep the FLOPs aligned and compare their performance and latency. The results are illustrated in Table 4a. As demonstrated in table, SEA attention outperforms the counterpart built on other efficient attentions. Compared with global attention, SEA attention outperforms it by +1.2% Top1 accuracy on ImageNet-1K and +1.6 mIoU on ADE20K with less FLOPs and lower latency. Compared with similar convolution enhanced attention works, ACmix and MixFormer, our SEA attention obtains better results on ImageNet-1K and ADE20K with similar FLOPs but lower latency. The results indicate the effectiveness and efficiency of SEA attention module.

The influence of components in SEA attention   To explore the influence of components in SEA attention, we conduct experiments with several configurations, including the detail enhancement kernel only, the squeeze Axial attention only and fusion of both. As is shown in Table 3, only detail enhancement or squeeze Axial attention achieves a relatively poor performance and enhancing squeeze Axial attention with detail enhancement kernel brings a performance boost with gain of 2.3% mIoU on ADE20K. The results indicate that enhancing global semantic features from squeeze Axial attention with local details from convolution optimizes the feature extraction capability of Transformer. For enhancement input, there is a apparent performance gap between upconv(x) and conv(x). And we can conclude that increasing the channel dimension will boost performance significantly. Comparing concat[qkv] and upconv(x), which also corresponding to w/ or w/o convolution weight sharing between detail enhancement kernel and squeeze Axial attention, we can find that

Method	P	F	L	Top1	mIoU
Conv	1.6M	0.59G	38ms	66.3	32.8
Local	1.3M	0.60G	48ms	65.9	32.8
Axial	1.6M	0.63G	44ms	66.9	33.7
Global	1.3M	0.61G	43ms	66.7	34.2
ACmix	1.3M	0.60G	54ms	66.0	33.1
MixFormer	1.3M	0.60G	50ms	66.8	33.8
SeaFormer	1.7M	0.60G	**40ms**	**67.9**	**35.8**

M	Params	FLOPs	Latency	mIoU
64,96	8.5M	1.7G	102ms	40.3
128,160	8.6M	1.8G	106ms	41.0
192,256	8.7M	2.0G	121ms	41.2

Posbias	Params	FLOPs	Latency	mIoU
✗	1.65M	0.60G	40ms	35.6
✔	1.67M	0.60G	40ms	35.8

Table 4: (a) Ablation studies on different self-attention module. `P` means `Parameters`, `F` means `Flops`, `L` means latency. (b) Ablation studies on embedding dimensions and position bias. M = [128, 160] is an optimal embedding dimensions in fusion blocks.

sharing weights makes our model improve the inference efficiency with minimal performance loss (35.8 *vs.*35.9). As for enhancement modes, multiplying squeeze Axial attention output features by output from detail enhancement kernel, outperforms add enhancement by +0.4% mIoU.

The influence of the width in fusion block To study the influence of the width in fusion block, we perform experiments with different embedding dimensions in fusion blocks on SeaFormer-Base, M denotes the channel dimensions that spatial branch and context branch features mapping to in two fusion blocks, respectively. Results are shown in Table 4b.

4.4 IMAGE CLASSIFICATION

We conduct experiments on ImageNet-1K Deng et al. (2009), which contains 1.28M training images and 50K validation images from 1,000 classes. We employ an AdamW Kingma & Ba (2014) optimizer for 600 epochs using a cosine decay learning rate scheduler. A batch size of 1024, an initial learning rate of 0.064, and a weight decay of 2e-5 are used. The results are illustrated in Table 5. Compared with other efficient approaches, SeaFormer achieves a relatively better trade-off between latency and accuracy.

5 CONCLUSION

In this paper, we propose *squeeze-enhanced Axial Transformer* (***SeaFormer***) for mobile semantic segmentation, filling the vacancy of mobile-friendly efficient Transformer. Moreover, we create a family of

Method	P	F	Top1	L
MobileNetV3-Small	2.9M	0.1G	67.4	**5ms**
SeaFormer-T	1.8M	0.1G	**67.9**	7ms
MobileViT-XXS	1.3M	0.4G	69.0	24ms
MobileViTv2-0.50	1.4M	0.5G	70.2	32ms
MobileOne-S0*	2.1M	0.3G	71.4	14ms
MobileNetV2	3.4M	0.3G	72.0	17ms
Mobile-Former96	4.8M	0.1G	72.8	31ms
SeaFormer-S	4.1M	0.2G	**73.1**	**12ms**
EdgeViT-XXS	4.1M	0.6G	74.4	71ms
LVT	5.5M	0.9G	74.8	97ms
MobileViT-XS	2.3M	0.9G	74.8	54ms
MobileNetV3-Large	5.4M	0.2G	75.2	**16ms**
Mobile-Former151	7.7M	0.2G	75.2	42ms
MobileViTv2-0.75	2.9M	1.0G	75.6	68ms
MobileOne-S1*	4.8M	0.8G	75.9	40ms
SeaFormer-B	8.7M	0.3G	**76.0**	20ms
MobileOne-S2*	7.8M	1.3G	77.4	63ms
EdgeViT-XS	6.8M	1.1G	77.5	124ms
MobileViTv2-1.00	4.9M	1.8G	78.1	115ms
MobileOne-S3*	10.1M	1.9G	78.1	91ms
MobileViT-S	5.6M	1.8G	78.4	88ms
EfficientNet-B1	7.8M	0.7G	79.1	61ms
Mobile-Former508	14.8M	0.5G	79.3	102ms
MobileOne-S4*	14.8M	3.0G	79.4	143ms
SeaFormer-L	14.0M	1.2G	**79.4**	**61**ms

Table 5: Image classification results on ImageNet-1K *val* set. The FLOPs and latency are measured with input size 256×256 for MobileViT and MobileViTv2 according to its original implementation and 224×224 for other models. `P`, `F` and `L` mean `Parameters`, `FLOPs` and `latency`. * indicates re-parameterized variants Vasu et al. (2022). The latency is measured on a single Qualcomm Snapdragon 865, and only an ARM CPU core is used for speed testing. No other means of acceleration, e.g., GPU or quantification, is used.

backbone architectures of SeaFormer and achieve superior cost-effectiveness. The state-of-the-art performance on the ADE20K, Pascal Context and COCO-stuff and lowest latency demonstrate its effectiveness on the ARM-based mobile device. Beyond semantic segmentation, we further apply the proposed SeaFormer architecture to image classification problem, demonstrating the potentials of serving as a versatile mobile-friendly backbone.

REFERENCES

Holger Caesar, Jasper Uijlings, and Vittorio Ferrari. Coco-stuff: Thing and stuff classes in context. In *CVPR*, 2018.

Yue Cao, Jiarui Xu, Stephen Lin, Fangyun Wei, and Han Hu. Gcnet: Non-local networks meet squeeze-excitation networks and beyond. In *ICCV workshops*, 2019.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv preprint*, 2017.

Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. In *ECCV*, 2018.

Qiang Chen, Qiman Wu, Jian Wang, Qinghao Hu, Tao Hu, Errui Ding, Jian Cheng, and Jingdong Wang. Mixformer: Mixing features across windows and dimensions. *arXiv preprint*, 2022.

Yinpeng Chen, Xiyang Dai, Dongdong Chen, Mengchen Liu, Xiaoyi Dong, Lu Yuan, and Zicheng Liu. Mobile-former: Bridging mobilenet and transformer. *arXiv preprint*, 2021.

Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. *arXiv preprint*, 2020.

MMSegmentation Contributors. Mmsegmentation: Openmmlab semantic segmentation toolbox and benchmark, 2020.

TNN Contributors. Tnn: A high-performance, lightweight neural network inference framework., 2019.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*. Ieee, 2009.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint*, 2020.

Hongyang Gao, Zhengyang Wang, and Shuiwang Ji. Kronecker attention networks. In *ACM SIGKDD*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Jonathan Ho, Nal Kalchbrenner, Dirk Weissenborn, and Tim Salimans. Axial attention in multidimensional transformers. *arXiv preprint*, 2019.

Yuanduo Hong, Huihui Pan, Weichao Sun, and Yisong Jia. Deep dual-resolution networks for real-time and accurate semantic segmentation of road scenes. *arXiv preprint*, 2021.

Qibin Hou, Li Zhang, Ming-Ming Cheng, and Jiashi Feng. Strip pooling: Rethinking spatial pooling for scene parsing. In *CVPR*, 2020.

Qibin Hou, Daquan Zhou, and Jiashi Feng. Coordinate attention for efficient mobile network design. In *CVPR*, 2021.

Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *ICCV*, 2019.

Zilong Huang, Xinggang Wang, Lichao Huang, Chang Huang, Yunchao Wei, and Wenyu Liu. Ccnet: Criss-cross attention for semantic segmentation. In *ICCV*, 2019.

Zilong Huang, Youcheng Ben, Guozhong Luo, Pei Cheng, Gang Yu, and Bin Fu. Shuffle transformer: Rethinking spatial shuffle for vision transformer. *arXiv preprint*, 2021a.

Zilong Huang, Yunchao Wei, Xinggang Wang, Wenyu Liu, Thomas S Huang, and Humphrey Shi. Alignseg: Feature-aligned segmentation networks. *TPAMI*, 2021b.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint*, 2014.

Alexander Kirillov, Ross Girshick, Kaiming He, and Piotr Dollár. Panoptic feature pyramid networks. In *CVPR*, 2019.

Hanchao Li, Pengfei Xiong, Haoqiang Fan, and Jian Sun. Dfanet: Deep feature aggregation for real-time semantic segmentation. In *CVPR*, 2019.

Jiachen Li, Ali Hassani, Steven Walton, and Humphrey Shi. Convmlp: Hierarchical convolutional mlps for vision. *arXiv preprint*, 2021.

Peter J Liu, Mohammad Saleh, Etienne Pot, Ben Goodrich, Ryan Sepassi, Lukasz Kaiser, and Noam Shazeer. Generating wikipedia by summarizing long sequences. *arXiv preprint*, 2018.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *ICCV*, 2021.

Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *CVPR*, 2015.

Minh-Thang Luong, Hieu Pham, and Christopher D Manning. Effective approaches to attention-based neural machine translation. *arXiv preprint*, 2015.

Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet v2: Practical guidelines for efficient cnn architecture design. In *ECCV*, 2018.

Sachin Mehta and Mohammad Rastegari. Mobilevit: light-weight, general-purpose, and mobile-friendly vision transformer. *arXiv preprint*, 2021.

Sachin Mehta and Mohammad Rastegari. Separable self-attention for mobile vision transformers. *arXiv preprint*, 2022.

Roozbeh Mottaghi, Xianjie Chen, Xiaobai Liu, Nam-Gyu Cho, Seong-Whan Lee, Sanja Fidler, Raquel Urtasun, and Alan Yuille. The role of context for object detection and semantic segmentation in the wild. In *CVPR*, 2014.

Junting Pan, Adrian Bulat, Fuwen Tan, Xiatian Zhu, Lukasz Dudziak, Hongsheng Li, Georgios Tzimiropoulos, and Brais Martinez. Edgevits: Competing light-weight cnns on mobile devices with vision transformers. *arXiv preprint*, 2022.

Xuran Pan, Chunjiang Ge, Rui Lu, Shiji Song, Guanfu Chen, Zeyi Huang, and Gao Huang. On the integration of self-attention and convolution. *arXiv preprint*, 2021.

Rudra PK Poudel, Stephan Liwicki, and Roberto Cipolla. Fast-scnn: Fast semantic segmentation network. *arXiv preprint*, 2019.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *CVPR*, 2018.

Zhuoran Shen, Mingyuan Zhang, Haiyu Zhao, Shuai Yi, and Hongsheng Li. Efficient attention: Attention with linear complexities. In *WACV*, 2021.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *ICML*. PMLR, 2019.

Pavan Kumar Anasosalu Vasu, James Gabriel, Jeff Zhu, Oncel Tuzel, and Anurag Ranjan. An improved one millisecond mobile backbone. *arXiv preprint*, 2022.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NeurIPS*, 2017.

Huiyu Wang, Yukun Zhu, Bradley Green, Hartwig Adam, Alan Yuille, and Liang-Chieh Chen. Axial-deeplab: Stand-alone axial-attention for panoptic segmentation. In *ECCV*, 2020a.

Sinong Wang, Belinda Z Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv preprint*, 2020b.

Sanghyun Woo, Jongchan Park, Joon-Young Lee, and In So Kweon. Cbam: Convolutional block attention module. In *ECCV*, 2018.

Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M Alvarez, and Ping Luo. Segformer: Simple and efficient design for semantic segmentation with transformers. In *NeurIPS*, 2021.

Weijian Xu, Yifan Xu, Tyler Chang, and Zhuowen Tu. Co-scale conv-attentional image transformers. In *ICCV*, 2021.

Chenglin Yang, Yilin Wang, Jianming Zhang, He Zhang, Zijun Wei, Zhe Lin, and Alan Yuille. Lite vision transformer with enhanced self-attention. In *cvpr*, 2022.

Changqian Yu, Jingbo Wang, Chao Peng, Changxin Gao, Gang Yu, and Nong Sang. Bisenet: Bilateral segmentation network for real-time semantic segmentation. In *ECCV*, 2018.

Changqian Yu, Changxin Gao, Jingbo Wang, Gang Yu, Chunhua Shen, and Nong Sang. Bisenet v2: Bilateral network with guided aggregation for real-time semantic segmentation. *IJCV*, 2021.

Yuhui Yuan, Xilin Chen, and Jingdong Wang. Object-contextual representations for semantic segmentation. In *ECCV*, 2020.

Yuhui Yuan, Rao Fu, Lang Huang, Weihong Lin, Chao Zhang, Xilin Chen, and Jingdong Wang. Hrformer: High-resolution transformer for dense prediction. *arXiv preprint*, 2021.

Haokui Zhang, Wenze Hu, and Xiaoyu Wang. Edgeformer: Improving light-weight convnets by learning from vision transformers. *arXiv preprint*, 2022a.

Wenqiang Zhang, Zilong Huang, Guozhong Luo, Tao Chen, Xinggang Wang, Wenyu Liu, Gang Yu, and Chunhua. Shen. Topformer: Token pyramid transformer for mobile semantic segmentation. In *CVPR*, 2022b.

Hengshuang Zhao, Xiaojuan Qi, Xiaoyong Shen, Jianping Shi, and Jiaya Jia. Icnet for real-time semantic segmentation on high-resolution images. In *ECCV*, 2018.

Sixiao Zheng, Jiachen Lu, Hengshuang Zhao, Xiatian Zhu, Zekun Luo, Yabiao Wang, Yanwei Fu, Jianfeng Feng, Tao Xiang, Philip HS Torr, et al. Rethinking semantic segmentation from a sequence-to-sequence perspective with transformers. In *CVPR*, 2021.

Bolei Zhou, Hang Zhao, Xavier Puig, Sanja Fidler, Adela Barriuso, and Antonio Torralba. Scene parsing through ade20k dataset. In *CVPR*, 2017.