A Gradient Method for Multilevel Optimization

Abstract

Although application examples of multilevel optimization have already been discussed since the '90s, the development of solution methods was almost limited to bilevel cases due to the difficulty of the problem. In recent years, in machine learning, Franceschi et al. have proposed a method for solving bilevel optimization problems by replacing their lower-level problems with the T steepest descent update equations with some prechosen iteration number T. In this paper, we have developed a gradient-based algorithm for multilevel optimization with n levels based on their idea and proved that our reformulation with nT variables asymptotically converges to the original multilevel problem. As far as we know, this is one of the first algorithms with some theoretical guarantee for multilevel optimization. Numerical experiments show that a trilevel hyperparameter learning model considering data poisoning produces more stable prediction results than an existing bilevel hyperparameter learning model in noisy data settings.

1 Introduction

Multilevel optimization When modeling real-world problems, there is often a hierarchy of decision-makers, and decisions are taken at different levels in the hierarchy. In this work, we consider multilevel optimization problems whose simplest form[1] is the following:

$$
\min_{x_1 \in S_1 \subseteq \mathbb{R}^{d_1}, x_2^*, \ldots, x_n^*} f_1(x_1, x_2^*, \ldots, x_n^*) \text{ s.t.}
$$
$$
x_2^* = \operatorname*{argmin}_{x_2 \in \mathbb{R}^{d_2}, x_3^*, \ldots, x_n^*} f_2(x_1, x_2, x_3^*, \ldots, x_n^*) \text{ s.t.}
$$
$$
\ddots \tag{1}
$$
$$
x_n^* = \operatorname*{argmin}_{x_n \in \mathbb{R}^{d_n}} f_n(x_1, x_2, \ldots, x_n),
$$

where d_i is positive integers, $x_i \in \mathbb{R}^{d_i}$ is the decision variable at the ith level, and $f_i \colon \mathbb{R}^{d_i} \to \mathbb{R}$ is the objective function of the ith level for $i = 1, \ldots, n$. In the formulation, an optimization problem contains another optimization problem as a constraint. The framework can be used to formulate problems in which decisions are made in sequence and earlier decisions influence later decisions. An optimization problem in which this structure is n-fold is called an n-level optimization problem or a multilevel optimization problem especially when $n \geq 3$.

Existing study on bilevel optimization Especially, when $n = 2$ in (1), it is called a bilevel optimization problem. Bilevel optimization or multilevel optimization has been a well-known problem in the field of optimization since the '80s or '90s respectively (see the survey paper [22] for the research at that time), and their solution methods have been studied mainly on bilevel

---

[1]This assumes that lower-level problems have unique optimal solutions $x_2^*, \ldots, x_n^*$ for the simplicity.

optimization until now. Recently, studies on bilevel optimization have received significant attention from the machine learning community due to practical applications and the development of efficient algorithms. For example, bilevel optimization was used to formulate decision-making problems for players in conflict [23, 20], and to formulate hyperparameter learning problems in machine learning [5, 11, 12]. Franceschi et al. [11] constructed a single-level problem that approximates a bilevel problem by replacing the lower-level problem with T steepest descent update equations using a prechosen iteration number T. It is shown that the optimization problem with T steepest descent update equations asymptotically converges to the original bilevel problem as $T \to \infty$. It is quite different from the ordinary approach (e.g., [1]) that transforms bilevel optimization problems into single-level problems using the optimality condition of the lower-level problem. The application of the steepest descent method to bilevel optimization problems has recently attracted attention, resulting in a stream of papers; e.g., [13, 18, 17].

Existing study on multilevel optimization Little research has been done on decision-making models (1) that assume the multilevel hierarchy, though various applications of multilevel optimization have been already discussed in the '90s [22]. As far as we know, few solution methods with a theoretical guarantee have been proposed. A metaheuristic algorithm based on a perturbation, i.e., a solution method in which the neighborhood is randomly searched for a better solution in the order of x_1 to x_n has been proposed in [21] for general n-level optimization problems. The effect of updating x_i on the decision variables $x_{i+1}, \ldots, x_n$ of the lower-level problems is not considered, and hence, the hierarchical structure of the multilevel optimization problem cannot be fully utilized in updating the solution. Because of this, the algorithm does not have a theoretical guarantee for the obtained solution. Very recently (two days before the NeurIPS 2021 abstract deadline), a proximal gradient method based on the fixed-point theory for trilevel optimization problem [19] has been proposed. This paper has proved convergence to an optimal solution assuming the convexity of the objective functions. However, it does not include numerical results and hence its practical efficiency is unclear.

Contribution of this paper In this paper, by extending the gradient method for bilevel optimization problems [11] to multilevel optimization problems, we propose an algorithm with a convergence guarantee for multilevel optimization other than one by [19]. Increasing the problem hierarchy from two to three drastically makes developing algorithms and showing theoretical guarantees difficult. In fact, as discussed above, in the case of bilevel, replacing the second-level optimization problem with its optimality condition or replacing it with T steepest-descent sequential updates immediately results in a one-level optimization problem. However, when it comes to $n \geq 3$ levels, it may be necessary to perform this replacement n times, and it seems not easy to construct a solution method with a convergence guarantee. It is not straightforward at all to give our method a theoretical guarantee similar to the one [11] developed for bilevel optimization. There are multiple ways to extend from the bilevel to the trilevel. For example, if it is extended recursively using T steepest-descent sequential updates at each level, the problem size can be increased with T^n variables. On the other hand, our formulation has polynomial-size nT variables. We have confirmed the effectiveness of the proposed method by applying it to hyperparameter learning with real data. Experimental verifications of the effectiveness of trilevel optimization using real-world problems are the first ones as far as we know.

2 Related existing methods

2.1 Two-stage robust optimization problems

When making long-term decisions, it is also necessary to make many decisions according to the situation. If the same objective function is acceptable throughout the period, i.e., $f_1 = \cdots = f_n$, and there are hostile players, such a problem is often formulated as a multistage robust optimization problem. Especially, the concept of two-stage robust optimization (so-called adjustable robust optimization) $\min_{x_1 \in S_1} \max_{x_2 \in S_2} \min_{x_3 \in S_3} f_1(x_1, x_2, x_3)$ was introduced with feasible sets $S_i \subseteq \mathbb{R}^{d_i}$ for $i = 1, 2, 3$, and methodology based on affine decision rules was developed by [4]. Researches based on affine policies are still being actively conducted; see, e.g., [6, 16]. The two-stage robust optimization can be considered as a special case of (1) with $n = 3$ when constraints $x_2 \in S_2 \subseteq \mathbb{R}^{d_2}$ and $x_3 \in S_3 \subseteq \mathbb{R}^{d_3}$ are added. This approach is unlikely to be applicable to our problem (1) without strong assumptions such as affine decision rules.

There is another research stream on min-max-min problems including integer constraints (see e.g., [7, 23]). They transform the problem into the min-max problem by taking the dual for the inner

82 "min" and apply cut-generating approaches or Benders decomposition techniques with the property of
83 integer variables. While the approach is popular in the application studies of electric grid planning, it
84 is restricted to the specific min-max-min problems and no more applicable to multilevel optimization
85 problems (1).

2.2 Existing methods for bilevel optimization problems

87 Various applications are known for bilevel optimization problems, i.e., the case of $n = 2$ in (1):

$$\min_{x_1 \in S_1} f_1(x_1, x_2) \text{ s.t. } x_2 = \operatorname*{argmin}_{x_2'} f_2(x_1, x_2'). \tag{2}$$

88 One of the most well-known applications in machine learning is hyperparameter learning. For
89 example, the problem that finds the best hyperparameter value in the ridge regression is formulated as

$$\min_{\lambda \geq 0} \|y_{\text{valid}} - X_{\text{valid}}\theta\|_2^2 \text{ s.t. } \theta = \operatorname*{argmin}_{\theta'} \|y_{\text{train}} - X_{\text{train}}\theta'\|_2^2 + \lambda\|\theta'\|_2^2,$$

90 where $(X_{\text{train}}, y_{\text{train}})$ are training samples, $(X_{\text{valid}}, y_{\text{valid}})$ are validation samples, and λ is a hyperpa-
91 rameter that is optimized in this problem. Under Assumption 1 restricted to $n = 2$ shown later, the
92 existence of an optimal solution to the bilevel problem (2) is ensured by [12, Theorem 3.1].

93 There are mainly two approaches to solve bilevel optimization problems. The old practice is to
94 replace the lower-level problem with its optimality condition and to solve the resulting single-level
95 problem. It seems difficult to use this approach to multilevel problems because we need to apply the
96 replacement n-times. The other one is to use gradient-based methods developed by Franceschi et al.
97 [11, 12] for bilevel optimization problems. Their approach reduces (2) to a single-level problem by
98 replacing the lower-level problem with T equations using a prechosen number T.

99 Hereinafter, we briefly summarize the results of Franceschi et al. [11, 12] for bilevel opti-
100 mization. Under the continuous differentiability assumption for f_2, x_2 is iteratively updated by
101 $x_2^{(t)} = \Phi^{(t)}(x_1, x_2^{(t-1)})$ at the tth iteration using an iterative method, e.g., the gradient descent
102 method:

$$\Phi^{(t)}(x_1, x_2^{(t-1)}) = x_2^{(t-1)} - \alpha^{(t)}\nabla_{x_2}f_2(x_1, x_2^{(t-1)}).$$

103 Then, the bilevel optimization problem is approximated by the single-optimization problem with T
104 equality constraints and new variables $\{x_2^{(t)}\}_{t=1}^T$ instead of x_2:

$$\min_{x_1 \in S_1, \{x_2^{(t)}\}} f_1(x_1, x_2^{(T)}) \text{ s.t. } x_2^{(t)} = \Phi^{(t)}(x_1, x_2^{(t-1)}) \ (t = 1, \ldots, T), \tag{3}$$

105 where $x_2^{(0)}$ is a given constant. Eliminating $x_2^{(1)}, \ldots, x_2^{(T)}$ using constraints, we can equivalently
106 recast the problem above into the unconstrained problem $\min_{x_1 \in S_1} \tilde{F}_1(x_1)$.

107 Under assumption on differentiability, the gradient of $\tilde{F}_1(x_1)$ is given in [11, Section 3] by

$$\nabla_{x_1}\tilde{F}_1(x_1) = \nabla_{x_1}f_1(x_1, x_2^{(T)}) + \sum_{t=1}^T B^{(t)}\left(\prod_{s=t+1}^T A^{(s)}\right)\nabla_{x_2}f_1(x_1, x_2^{(T)}),$$

$$A^{(t)} = \nabla_{x_2}\Phi^{(t)}(x_1, x_2^{(t-1)}) \ (t = 1, \ldots, T),$$

$$B^{(t)} = \nabla_{x_1}\Phi^{(t)}(x_1, x_2^{(t-1)}) \ (t = 1, \ldots, T).$$

108 Roughly speaking, [12, Theorem 3.2] proved the optimal value and the solution set of (3) converges
109 to those of (2) as $T \to \infty$ under Assumptions 1 and 3 restricted to $n = 2$.

3 Multilevel optimization problems and their approximation

111 We will develop an algorithm for multilevel optimization problems (1) under some assumptions by
112 extending the studies [11, 12] on bilevel problems. Our algorithm and its theoretical guarantee look
113 similar to those in [11, 12], but they are not straightforwardly obtained. As emphasized in Section
114 1, unlike the bilevel problem, even if the lower-level problem is replaced with T steepest-descent
115 sequential updates, the resulting problem is still a multilevel problem. In this section, we show how
116 to resolve these difficulties that come from the multilevel hierarchy.

3.1 Existence of optima of multilevel optimization problems

First, we discuss the existence of an optimal solution of the multilevel optimization problem (1). To do so, we introduce the following assumption, which is a natural extension of that in [11].

Assumption 1.

    (i) S_1 is compact.

    (ii) For $i = 1, \ldots, n$, f_i is jointly continuous.

    (iii) For $i = 2, \ldots, n$, the set of optimal solutions of the ith level problem with arbitrarily fixed $(x_1, \ldots, x_{i-1})$ is a singleton.

    (iv) For $i = 2, \ldots, n$, the optimal solution of the ith level problem remains bounded as x_1 varies in S_1.

Assumption 1-(iii) means that the ith level problem with parameter $(x_1, \ldots, x_{i-1})$ has a unique optimizer, that is described as x_i^* in (1) though it should be formally written as $x_i^*(x_1, \ldots, x_{i-1})$ since it is determined by $x_1, \ldots, x_{i-1}$. We define $F_i(x_1, \ldots, x_i) \coloneqq f_i(x_1, \ldots, x_i, x_{i+1}^*, \ldots, x_n^*)$ by eliminating $x_{i+1}^*, \ldots, x_n^*$ since it depends only on $(x_1, \ldots, x_i)$. Then, the ith level problem with parameter $(x_1, \ldots, x_{i-1})$ can be written as $\min_{x_i} F_i(x_1, \ldots, x_i)$. Similarly, in the 1st level problem, for fixed x_1, the remaining variables $x_2, x_3, \ldots, x_n$ can be represented as $x_2^*(x_1), x_3^*(x_1, x_2^*(x_1))$ and so on. In what follows, we denote them by $x_2^*(x_1), x_3^*(x_1), \ldots, x_n^*(x_1)$ since they are determined by x_1. Eliminating them, we can rewrite the 1st level problem, equivalently (1), as

$$\min_{x_1 \in S_1} F_1(x_1). \tag{4}$$

Theorem 2. *Under Assumption 1, Problem (4) admits optimal solutions.*

Theorem 2 is a generalization of [12, Theorem 3.1], which is valid only for $n = 2$, to general n. It is difficult to extend the original proof to general n because, to derive the continuity of x_i^* extending the original proof, a sequence $(x_1, \ldots, x_{i-1})$ approaches to its accumulation point only from a specific direction. Instead, in the multilevel case, we employ the theory of point-to-set mapping. A proof of Theorem 2 is shown in Supplementary material A.1.

3.2 Approximation by iterative methods

We extend the gradient method for bilevel optimization problems proposed by Franceschi et al. [11] to multilevel optimization problems (1). Based on an argument similar to one in Subsection 2.2, we approximate lower level problems in (1) by applying an iterative method with T_i iterations to the ith level problem for $i = 2, \ldots, n$. Then, we obtain the following approximated problem:

$$\min_{x_1 \in S_1, \{x_2^{(t_2)}\}, \ldots, \{x_n^{(t_n)}\}} f_1(x_1, x_2^{(T_2)}, \ldots, x_n^{(T_n)})$$
$$\text{s.t. } x_i^{(t_i)} = \Phi_i^{(t_i)}(x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})}, x_i^{(t_i-1)}) \ (i = 2, \ldots, n; t_i = 1, \ldots, T_i), \tag{5}$$

where $\Phi_i^{(t_i)}(x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})}, x_i^{(t_i)})$ is the t_ith iteration formula of an iterative method for the ith level approximated problem with parameters $(x_1, \ldots, x_{i-1}) = (x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})})$, i.e.,

$$\min_{x_i, \{x_{i+1}^{(t_{i+1})}\}, \ldots, \{x_n^{(t_n)}\}} f_i(x_1, \ldots, x_i, x_{i+1}^{(T_{i+1})}, \ldots, x_n^{(T_n)})$$
$$\text{s.t. } x_j^{(t_i)} = \Phi_i^{(t_i)}(x_1, \ldots, x_i, x_{i+1}^{(T_{i+1})}, \ldots, x_{j-1}^{(T_{j-1})}, x_j^{(t_i-1)}) \ (j = i+1, \ldots, n; t_i = 1, \ldots, T_i),$$

and its initial point $x_i^{(0)}$ for each i are regarded as a given constant. For $i = 1, \ldots, n$, if we fix $x_1, \ldots, x_i$, each remaining variable $x_j^{(t)}$ is determined by constraints and thus, we denote it by $x_j^{(t_j)}(x_1, \ldots, x_i)$ for $j = i+1, \ldots, n$. Using this notation, the ith level objective function can be written as

$$\tilde{F}_i(x_1, \ldots, x_i) \coloneqq f_i(x_1, \ldots, x_{i-1}, x_i, x_{i+1}^{(T_{i+1})}(x_1, \ldots, x_i), \ldots, x_n^{(T_n)}(x_1, \ldots, x_{n-1}^{(T_{n-1})}(\cdots (x_{i+1}^{(T_{i+1})}(x_1, \ldots, x_i))\cdots))),$$

where $(x_1, \ldots, x_{i-1})$ acts as a fixed parameter in the ith level problem. When we approximate the ith level problem with the steepest descent method for example, we use $\Phi_i^{(t_i)}(x_1, \ldots, x_{i-1}, x_i^{(t_i)}) = x_i^{(t_i-1)} - \alpha_i^{(t_i-1)} \nabla_{x_i} \tilde{F}_i(x_1, \ldots, x_{i-1}, x_i^{(t_i-1)})$.

Especially, all variables other than x_1 in (5) can be expressed as $\{x_2^{(t_2)}(x_1)\}, \ldots, \{x_n^{(t_n)}(x_1)\}$ since it is determined by x_1. By plugging the constraints into the objective function and eliminating them, we can reformulate (5) as

$$\min_{x_1 \in S_1} \tilde{F}_1(x_1). \tag{6}$$

In the remainder of this subsection, we assume $T_2 = \cdots = T_n = T$ for simplicity. Then, the optimal value and solutions of Problem (6) converge to those of Problem (4) as $T \to \infty$ in some sense. To derive it, we introduce the following assumption, which is also a natural extension of that in [11].

Assumption 3.

(i) $f_1(x_1, \cdot, \ldots, \cdot)$ is uniformly Lipschitz continuous on S_1.

(ii) For all $i = 2, \ldots, n$, sequence $\{x_i^{(T)}(x_1)\}$ converges uniformly to $x_i^*(x_1)$ on S_1 as $T \to \infty$.

Theorem 4. *Under Assumptions 1 and 3, the followings hold:*

(a) The optimal value of Problem (6) converges to that of Problem (4) as $T \to \infty$.

(b) The set of the optimal solutions of Problem (6) converges to that of Problem (4); more precisely, denoting an optimal solution of Problem (6) by $x_{1,T}^*$, we have

- *$\{x_{1,T}^*\}_{T=1}^\infty$ admits a convergent subsequence;*
- *for every subsequence $\{x_{1,T_k}^*\}_{k=1}^\infty$ such that $x_{1,T_k}^* \to x_1^*$ as $k \to \infty$, the accumulation point x_1^* is an optimal solution of Problem (4).*

See Supplementary material A.2 for a proof of this theorem.

4 Proposed method: Gradient computation in the approximated problem

Now we propose to apply a projected gradient method to the approximated problem (6) for multilevel optimization problems (1) because (6) asymptotically converges to (1) as shown in Theorem 4. In this section, we derive the formula of $\nabla_{x_1} \tilde{F}_1(x_1)$ and confirm the global convergence of the resulting projected gradient method.

4.1 Gradient of the objective function in the approximated problem

The following theorem provides a computation formula of $\nabla_{x_1} \tilde{F}_1(x_1)$.

Theorem 5 (Gradient formula for the n-level optimization problems). *The gradient $\nabla_{x_1} \tilde{F}_1(x_1)$ can be expressed as follows:*

$$\nabla_{x_1} \tilde{F}_1(x_1) = \nabla_{x_1} f_1(x_1, x_2^{(T_2)}, \ldots, x_n^{(T_n)}) + \sum_{i=2}^n Z_i \nabla_{x_i} f_1(x_1, x_2^{(T_2)}, \ldots, x_n^{(T_n)}),$$

$$Z_i = \sum_{t=1}^{T_i} \left(\sum_{j=2}^{i-1} Z_j C_{ij}^{(t)} + B_i^{(t)} \right) \prod_{s=t+1}^{T_i} A_i^{(s)},$$

$$A_i^{(t)} = \nabla_{x_i} \Phi_i^{(t)}(x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})}, x_i^{(t-1)}),$$

$$B_i^{(t)} = \nabla_{x_1} \Phi_i^{(t)}(x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})}, x_i^{(t-1)}),$$

$$C_{ij}^{(t)} = \nabla_{x_j} \Phi_i^{(t)}(x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})}, x_i^{(t-1)})$$

for any $i = 2, \ldots, n$; $t = 1, \ldots, T_i$; and $j = 2, \ldots, i - 1$, where we define $\prod_{s=t+1}^{T_i} A_i^{(s)} := A_i^{(t+1)} A_i^{(t+2)} \ldots A_i^{(T_i)}$ for $t < T_i$ and $\prod_{s=T_i+1}^{T_i} A_i^{(s)} = I$.

See supplementary material A.3 for a proof of this theorem.

We consider computing $\nabla_{x_1}\tilde{F}_1(x_1)$ using Theorem 5. Notice that we can easily compute $Z_2 = \sum_{t=1}^{T_2} B_2^{(t)} \prod_{s=t+1}^{T_2} A_2^{(s)}$. For $i = 3, \ldots, n$, when we have $Z_2, \ldots, Z_{i-1}$, we can compute Z_i. We show an algorithm that computes $\nabla_{x_1}\tilde{F}_1(x_1)$ by computing $Z_2, \ldots, Z_n$ in this order in Algorithm 1.

Algorithm 1 Computation of $\nabla_{x_1}\tilde{F}_1(x_1)$

Input: x_1: current value of the 1st level variable. $\{x_i^{(0)}\}_{i=2}^n$: initial values of the lower level iteration.
Output: The exact value of $\nabla_{x_1}\tilde{F}_1(x_1)$.
1: $g := (0, \ldots, 0)^\top$.
2: **for** $k := 2, \ldots, n$ **do**
3:      $Z_i := O$.
4:      **for** $t := 1, \ldots, T_i$ **do**
5:          $x_i^{(t)} := \Phi_i^{(t)}(x_1, x_2^{(T_2)}, \ldots, x_{i-1}^{(T_{i-1})}, x_i^{(t-1)})$.
6:          $\bar{B}_i^{(t)} := \sum_{l=2}^{k-1} Z_l C_{kl}^{(t)} + B_i^{(t)}$.
7:          $Z_i := Z_i A_i^{(t)} + \bar{B}_i^{(t)}$.
8: **for** $i = 2, \ldots, n$ **do**
9:      $g := g + Z_i \nabla_{x_i} f_1$.
10: $g := g + \nabla_{x_1} f_1$.
11: **return** g

For $i = 2, \ldots, n$ and $t = 1, \ldots, T_i$, $\Phi_i^{(t)}$, which appears in the 5th line of Algorithm 1, is the update formula based on the gradient $\nabla_{x_i}\tilde{F}_i(x_1, \ldots, x_i)$ of the ith level objective function. It can be computed as the gradient of the 1st level objective function of $(n - i + 1)$-level optimization problem with objective functions $\tilde{F}_i, \ldots, \tilde{F}_n$. Therefore, recursively calling Algorithm 1 in the computation of $\Phi_i^{(t)}$, we can compute $\nabla_{x_1}\tilde{F}_1(x_1)$. Figure 5 in Supplementary material B shows the procedure of the gradient computation.

4.2 Complexity of the gradient computation

We analyze the complexity for computing $\nabla_{x_1}\tilde{F}_1(x_1)$ by recursively calling Algorithm 1. In the following theorem, the asymptotic big O notation is denoted by $O(\cdot)$.

Theorem 6. *Let the time and space complexity for computing $\nabla_{x_i}\tilde{F}_i(x_i)$ be c_i and s_i, respectively. We use $\Phi_i^{(t_i)}$ based on $\nabla_{x_i}\tilde{F}_i(x_i)$ and recursively call Algorithm 1 for computing $\nabla_{x_i}\tilde{F}_i(x_1, \ldots, x_i)$. We assume that those for evaluating $\Phi_i^{(t_i)}$ are $O(c_i)$ and $O(s_i)$. In addition, we assume that the time and space complexity of $\nabla_{x_1} f_1$ and $\nabla_{x_i} f_1$ for $i = 1, \ldots, n$ are smaller in the sense of the order than those of $\mathtt{for}$ loops in lines 2–9 in Algorithm 1. Then, the overall time complexity c_1 and space complexity s_1 for computing $\nabla_{x_i}\tilde{F}_i(x_1, \ldots, x_i)$ can be written as*

$$c_1 = O\left(p^n n! c_n \prod_{i=1}^{n-1}(T_{i+1}d_i) \right), \quad s_1 = O(q^n s_n), \tag{7}$$

respectively, for some constant $p, q > 0$.

For the proof, see Supplementary material A.4. Note that, if n is a fixed parameter, those complexity reduces to a polynomial of T_i's, d_i's, c_n, and s_n. Hence, Algorithm 1 can be regarded as a fixed-parameter tractable algorithm.

4.3 Global convergence of projected gradient method

Here, we consider solving Problem (6) by the projected gradient method, which calculates the gradient vector by Algorithm 1 and projects the updated point on S_1 in each iteration. When all lower-level updates are based on the steepest descent method, we can derive the Lipschitz continuity of the gradient of the objective function of (6). Hence, we can guarantee the global convergence of the projected gradient method for (6) by taking a sufficiently small step size.

Theorem 7. *Suppose* $\Phi_i^{(t)}(x_1, \ldots, x_{i-1}, x_i^{(t-1)}) = x_i^{(t-1)} - \alpha_i^{(t-1)} \nabla_{x_i} \tilde{F}_i(x_1, \ldots, x_{i-1}, x_i^{(t-1)})$
for all $i = 2, \ldots, n$ *and* $t_i = 1, \ldots, T_i$, *where* $\alpha_i^{(t-1)}$ *and* $x_i^{(0)}$ *are given parameters for all* i *and*
t. *Assume that* $\nabla_{x_j} f_i$ *is Lipschitz continuous and bounded for all* $i = 1, \ldots, n$ *and* $j = 1, \ldots, n$
and also $\nabla_{x_i} \Phi_i^{(t)}$, $\nabla_{x_1} \Phi_i^{(t)}$, *and* $\nabla_{x_j} \Phi_i^{(t)}$ *are Lipschitz continuous and bounded for all* $i = 2, \ldots, n$;
$j = 2, \ldots, i-1$; $t = 1, \ldots, T_i$. *Then,* $\nabla_{x_1} \tilde{F}_1$ *is Lipschitz continuous.*

See Supplementary material A.5 for a proof of this theorem.

Corollary 8. *Suppose the same assumption as Theorem 7. Let* L *be the Lipschitz constant of* $\nabla_{x_1} \tilde{F}_1$.
Then, a sequence generated by the projected gradient method with sufficiently small constant step
size, e.g., smaller than $2/L$, *for Problem* (6) *from any initial point converges to a stationary point.*

Proof. From Theorem 7, the gradient of the objective function of Problem (6) is L-Lipschitz continu-
ous. Then, from [3, Theorem 10.15], by setting the step size parameter $\alpha_1^{(t)}$ of the projected gradient
method satisfying $0 < \alpha_1^{(t)} < 2/L$ for all t, we can guarantee its global convergence. $\qquad\square$

5   Numerical experiments

To validate the effectiveness of our proposed method, we conducted numerical experiments on an arti-
ficial problem and a hyperparameter optimization problem arising from real data (see Supplementary
material C for more results). In our numerical experiments, we implemented all codes with Python
3.9.2 and JAX 0.2.10 for automatic differentiation and executed them on a computer with 12 cores of
Intel Core i7-7800X CPU 3.50 GHz, 64 GB RAM, Ubuntu OS 20.04.2 LTS.

5.1   Convergence to the optimal solution

We solved the following trilevel optimization problem with Algorithm 1 to evaluate the performance:

$$
\begin{aligned}
\min_{x_1 \in \mathbb{R}^2} f_1(x_1, x_2^*, x_3^*) &= \|x_3^* - x_1\|_2^2 + \|x_1\|_2^2 \text{ s.t.} \\
x_2^* \in \operatorname*{argmin}_{x_2 \in \mathbb{R}^2} f_2(x_1, x_2, x_3^*) &= \|x_2 - x_1\|_2^2 \text{ s.t.} \\
x_3^* \in \operatorname*{argmin}_{x_3 \in \mathbb{R}^2} f_3(x_1, x_2, x_3) &= \|x_3 - x_2\|_2^2.
\end{aligned}
\tag{8}
$$

Clearly, the optimal solution for this problem is $x_1 = x_2 = x_3 = (0,0)^\top$.

We solved (8) with different (T_2, T_3) and the same constant step size and initialization. For the
iterative method in Algorithm 1, we employed the steepest descent method at all levels. We show
the transition of the value of the objective functions in Figure 1 and the trajectories of each decision
variable in Figure 2. We can confirm that the objective values f_1, f_2, and f_3 converge to the optimal
value 0 at all levels and the gradient method outputs the optimal solution $(0,0)^\top$ even if we use small
iteration numbers $T_2 = 1$ and $T_3 = 1$ for the approximation problem (5).

5.2   Application to hyperparameter optimization

For deriving a machine learning model robust to noise in input data, we formulate a trilevel model by
assuming two players: a model learner and an attacker. The model learner decides the hyperparameter
λ to minimize the validation error, while the attacker tries to poison training data so as to make the
model less accurate. This model is formulated as follows:

$$
\begin{aligned}
\min_{\lambda} \frac{1}{m} \|y_{\text{valid}} - X_{\text{valid}}\theta\|_2^2 \text{ s.t.} \\
P \in \operatorname*{argmax}_{P'} \frac{1}{n} \|y_{\text{train}} - (X_{\text{train}} + P')\theta\|_2^2 - \frac{c}{nd} \|P'\|_2^2 \text{ s.t.} \\
\theta \in \operatorname*{argmin}_{\theta'} \frac{1}{n} \|y_{\text{train}} - (X_{\text{train}} + P')\theta'\|_2^2 + \exp(\lambda)\frac{\|\theta'\|_{1^*}}{d},
\end{aligned}
$$

where θ denotes the parameter of the model and d denotes the dimension of θ, n denotes the number
of the training data X_{train}, m denotes the number of the validation data X_{val}, c denotes the penalty

(a) $T_2 = 10, T_3 = 10$

(b) $T_2 = 1, T_3 = 1$

Figure 1: Performance of Algorithm 1 for Problem (8). Objective values linearly decreased.

(a) $T_2 = 10, T_3 = 10$

(b) $T_2 = 1, T_3 = 1$

Figure 2: Trajectories of each variable. $(0, 0)$ is the optimal solution of each level. Our algorithm with few iterations for lower-level problems $T_2 = T_3 = 1$ performed well.

for the noise P, and $\| \cdot \|_{1*}$ is a smoothed ℓ_1-norm, which is a differentiable approximation of the ℓ_1-norm. Here, we use $\exp(\lambda)$ to express a nonnegative penalty parameter instead of the constraint $\lambda \geq 0$.

To validate the effectiveness of our proposed method, we compared the results by the trilevel model with those of the following bilevel model:

$$\min_{\lambda} \frac{1}{m} \|y_{\text{valid}} - X_{\text{valid}}\theta\|_2^2 \text{ s.t. } \theta \in \operatorname*{argmin}_{\theta'} \frac{1}{n} \|y_{\text{train}} - X_{\text{train}}\theta'\|_2^2 + \exp(\lambda) \frac{\|\theta'\|_{1*}}{d}.$$

This model is equivalent to the trilevel model without the attacker's level.

We used Algorithm 1 to compute the gradient of the objective function in the trilevel and bilevel models with real datasets. For the iterative method in Algorithm 1, we employed the steepest descent method at all levels. We set $T_2 = 30$ and $T_3 = 3$ for the trilevel model and $T_2 = 30$ for the bilevel model. In each dataset, we used the same initialization and step sizes in the updates of λ and θ in trilevel and bilevel models. We compared these methods on the regression tasks with the following datasets: the diabetes dataset [10], the (red and white) wine quality datasets [8], the Boston dataset [14]. For each dataset, we standardized each feature and the objective variable; randomly chose 40 rows for training data $(X_{\text{train}}, y_{\text{train}})$, chose other 100 rows for validation data $(X_{\text{valid}}, y_{\text{valid}})$, and used the rest of the rows for test data.

We show the transition of the mean squared error (MSE) by test data with Gaussian noise in Figure 3. The solid line and colored belt respectively indicate the mean and the standard deviation over 500 times of generation of Gaussian noise. The dashed line indicates the MSE without noise as a baseline. In the results of the diabetes dataset (Figure 3), the trilevel model provided a more robust parameter than the bilevel model, because the MSE of the trilevel model rises less in the large noise setting for test data.

(a) $\sigma = 0.01$ (b) $\sigma = 0.08$

Figure 3: MSE by test data with Gaussian noise with the standard deviation of σ on diabetes dataset.

(a) Diabetes dataset   (b) Red wine quality dataset

Figure 4: MSE by test data with Gaussian noise, using early-stopped parameters for prediction.

Table 1: MSE by test data with Gaussian noise with the standard deviation of 0.08, using early-stopped parameters for prediction. The better values are shown in boldface.

	diabetes	Boston	wine (red)	wine (white)
Trilevel	**0.8601 ± 0.0479**	**0.4333 ± 0.0032**	**0.7223 ± 0.0019**	**0.8659 ± 0.0013**
Bilevel	1.0573 ± 0.0720	0.4899 ± 0.0033	0.7277 ± 0.0019	0.8750 ± 0.0014

Next, we compared the quality of the resulting model parameters by the trilevel and bilevel models. We set an early-stopping condition on learning parameters: after 1000 times of updates on the model parameter, if one time of update on hyperparameter λ did not improve test error, terminate the iteration and return the parameters at that time. By using the early-stopped parameters, we show the relationship of test error and standard deviation of the noise on the test data in Figure 4 and Table 1. For the diabetes dataset, the growth of MSE by the trilevel model was slower than that of the bilevel model. For wine quality and Boston house-prices datasets, the MSE of the trilevel model was consistently lower than that of the bilevel model. Therefore, the trilevel model provides more robust parameters than the bilevel model in these settings of problems.

6   Conclusion

In this paper, we have provided an approximated formulation for a multilevel optimization problem by iterative methods and discussed its asymptotical properties of it. In addition, we have proposed an algorithm for computing the gradient of the objective function of the approximated problem. Using the gradient information, we can solve the approximated problem by the projected gradient method. We have also established the global convergence of the projected gradient method.

Limitation and future work   Our proposed gradient computation algorithm is fixed-parameter tractable and hence it works efficiently for small n. For large n, however, the exact computation of the gradient is expensive. Development of heuristics for approximately computing the gradient is left for future research. Weakening assumptions in the theoretical contribution is also left for future work.

References

[1] G. B. Allende and G. Still. Solving bilevel programs with the KKT-approach. *Mathematical Programming*, 138(1):309–332, 2013.

[2] A. G. Baydin, B. A. Pearlmutter, A. A. Radul, and J. M. Siskind. Automatic differentiation in machine learning: A survey. *Journal of Machine Learning Research*, 18(153):1–43, 2017.

[3] A. Beck. *First-Order Methods in Optimization*. SIAM, 2017.

[4] A. Ben-Tal, A. Goryashko, E. Guslitzer, and A. Nemirovski. Adjustable robust solutions of uncertain linear programs. *Mathematical Programming*, 99(2):351–376, 2004.

[5] K. P. Bennett, J. Hu, X. Ji, G. Kunapuli, and J.-S. Pang. Model selection via bilevel optimization. In *The 2006 IEEE International Joint Conference on Neural Network Proceedings*, pages 1922–1929, 2006.

[6] D. Bertsimas and F. J. C. T. de Ruiter. Duality in two-stage adaptive linear optimization: Faster computation and stronger bounds. *INFORMS Journal on Computing*, 28(3):500–511, 2016.

[7] A. Billionnet, M.-C. Costa, and P.-L. Poirion. 2-stage robust MILP with continuous recourse variables. *Discrete Applied Mathematics*, 170:21–32, 2014.

[8] P. Cortez, A. Cerdeira, F. Almeida, T. Matos, and J. Reis. Modeling wine preferences by data mining from physicochemical properties. *Decision Support Systems*, 47:547–553, 2009.

[9] A. L. Dontchev and T. Zolezzi. *Well-Posed Optimization Problems*. Springer-Verlag Berlin Heidelberg, 1993.

[10] D. Dua and C. Graff. UCI machine learning repository, 2017. http://archive.ics.uci.edu/ml.

[11] L. Franceschi, M. Donini, P. Frasconi, and M. Pontil. Forward and reverse gradient-based hyperparameter optimization. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1165–1173, 2017.

[12] L. Franceschi, P. Frasconi, S. Salzo, R. Grazzi, and M. Pontil. Bilevel programming for hyperparameter optimization and meta-learning. In J. Dy and A. Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 1568–1577, 2018.

[13] L. Franceschi, M. Niepert, M. Pontil, and X. He. Learning discrete structures for graph neural networks. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 1972–1982, 2019.

[14] D. Harrison and D. L. Rubinfeld. Hedonic prices and the demand for clean air. *Journal of Environmental Economics and Management*, 5:81–102, 1978.

[15] W. W. Hogan. Point-to-set maps in mathematical programming. *SIAM Review*, 15:591–603, 1973.

[16] D. d. H. İhsan Yanikoğlu, Bram L. Gorissen. A survey of adjustable robust optimization. *European Journal of Operational Research*, 277(3):799–813, 2019.

[17] J. Lorraine, P. Vicol, and D. Duvenaud. Optimizing millions of hyperparameters by implicit differentiation. In S. Chiappa and R. Calandra, editors, *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pages 1540–1552, 2020.

[18] A. Shaban, C.-A. Cheng, N. Hatch, and B. Boots. Truncated back-propagation for bilevel optimization. In K. Chaudhuri and M. Sugiyama, editors, *Proceedings of the Twenty-Second International Conference on Artificial Intelligence and Statistics*, volume 89 of *Proceedings of Machine Learning Research*, pages 1723–1732, 2019.

[19] A. Shafiei, V. Kungurtsev, and J. Marecek. Trilevel and multilevel optimization using monotone operator theory, 2021. arXiv:2105.09407v1.

[20] A. Sinha, P. Malo, and K. Deb. A review on bilevel optimization: From classical to evolutionary approaches and applications. *IEEE Transactions on Evolutionary Computation*, 22(2):276–295, 2018.

[21] S. L. Tilahun, S. M. Kassa, and H. C. Ong. A new algorithm for multilevel optimization problems using evolutionary strategy, inspired by natural adaptation. In *PRICAI 2012: Trends in Artificial Intelligence*, pages 577–588, 2012.

[22] L. N. Vicente and P. H. Calamai. Bilevel and multilevel programming: A bibliography review. *Journal of Global Optimization*, 5:291–306, 1994.

[23] X. Wu and A. J. Conejo. An efficient tri-level optimization model for electric grid defense planning. *IEEE Transactions on Power Systems*, 32(4):2984–2994, 2017.