Dynamic Bottleneck for Robust Self-Supervised Exploration

Abstract

Exploration methods based on pseudo-count of transitions or curiosity of dynamics
have achieved promising results in solving reinforcement learning with sparse
rewards. However, such methods are usually sensitive to environmental dynamics-
irrelevant information, e.g., white-noise. To handle such dynamics-irrelevant
information, we propose a Dynamic Bottleneck (DB) model, which attains a
dynamics-relevant representation based on the information-bottleneck principle.
Based on the DB model, we further propose DB-bonus, which encourages the agent
to explore state-action pairs with high information gain. We establish theoretical
connections between the proposed DB-bonus, the upper confidence bound (UCB)
for linear case, and the visiting count for tabular case. We evaluate the proposed
method on Atari suits with dynamics-irrelevant noises. Our experiments show
that exploration with DB bonus outperforms several state-of-the-art exploration
methods in noisy environments.

1 Introduction

The tradeoff between exploration and exploitation has long been a major challenge in reinforcement learning (RL) [31, 44]. Generally, excessive exploitation of the experience suffers from the potential risk of being suboptimal, whereas excessive exploration of novel states hinders the improvement of the policy. A straightforward way to tackle the exploration-exploitation dilemma is to enhance exploration efficiency while keeping exploitation in pace. When the extrinsic rewards are dense, reward shaping is commonly adopted for efficient exploration. However, in many real-world applications such as autonomous driving [30], the extrinsic rewards are sparse, making efficient exploration a challenging task in developing practical RL algorithms. The situations become even worse when the extrinsic rewards are entirely unavailable. In such a scenario, the task of collecting informative trajectories from exploration is known as the self-supervised exploration [10].

An effective approach to self-supervised exploration is to design a dense intrinsic reward that motivates the agent to explore novel transitions. Previous attempts include count-based [8] and curiosity-driven [34] explorations. The count-based exploration builds a density model to measure the pseudo-count of state visitation and assign high intrinsic rewards to less frequently visited states. In contrast, the curiosity-driven methods maintain a predictive model of the transitions and encourage the agent to visit transitions with high prediction errors. However, all these methods becomes unstable when the states are noisy, e.g., containing dynamics-irrelevant information. For example, in autonomous driving tasks, the states captured by the camera may contain irrelevant objects, such as clouds, birds, and aircraft. Hence, if we measure the novelty of states or the curiosity of transitions through raw observed pixels, exploration are likely to be affected by the dynamics of these irrelevant objects.

To encourage the agent to explore the most informative transitions of dynamics, we propose a Dynamic Bottleneck (DB) model, which generates a dynamics-relevant representation Z_t of the

current state-action pair (S_t, A_t) through the Information-Bottleneck (IB) principle [49]. The goal of training DB model is to acquire dynamics-relevant information and discards dynamics-irrelevant features simultaneously. To this end, we maximize the mutual-information $I(Z_t; S_{t+1})$ between a latent representation Z_t and the next state S_{t+1} through maximizing its lower bound and using contrastive learning. Meanwhile, we minimize the mutual-information $I([S_t, A_t]; Z_t)$ between the state-action pair and the corresponding representation to compress dynamics-irrelevant information. Based on our proposed DB model, we further construct a DB-bonus for exploration. DB-bonus measures the novelty of state-action pairs by their information gain with respect to the representation computed from the DB model. We show that the DB-bonus are closely related to the provably efficient UCB-bonus in linear Markov Decision Processes (MDPs) [1] and the visiting count in tabular MDPs [3, 20]. We further estimate the DB-bonus by the learned dynamics-relevant representation from the DB model. We highlight that exploration based on DB-bonus directly utilize the information gain of the transitions, which filters out dynamics-irrelevant noise. We conduct experiments on the Atari suit with dynamics-irrelevant noise injected. Results demonstrate that our proposed self-supervised exploration with DB-bonus is robust to dynamics-irrelevant noise and outperforms several state-of-the-art exploration methods.

2   Related Work

Our work is closely related to previous exploration algorithms that construct intrinsic rewards to quantify the novelty of states and transitions. Several early approaches directly define the pseudo-count by certain statistics to measure the novelty of states [36, 26]; more recent methods utilize density model [8, 33] or hash map [46, 37] for state statistics. Nevertheless, these approaches are easily affected by dynamics-irrelevant information such as white-noise. The contingency awareness method [15] addresses such an issue by using an attentive model to locate the agent and computes the pseudo-count based on regions around the agent. However, such an approach could ignore features that are distant from the agent but relevant to the transition dynamics. Another line of research measures the novelty through learning a dynamics model and then use the prediction error to generate an intrinsic reward. These methods are known as the curiosity-driven exploration algorithms. Similar to the pseudo-count based methods, curiosity-driven methods become unstable in the presence of noises, because the prediction model is likely to yield high error for stochastic inputs or targets. Some recent attempts improve the curiosity-driven approach by learning the inverse dynamics [34] and variational dynamics [7] to define curiosity, or utilizes the prediction error of a random network to construct intrinsic rewards [11]. However, without explicitly removing dynamics-irrelevant information, these methods are still vulnerable to noises in practice [10]. Previous approaches also quantify the epistemic uncertainty of dynamics through Bayesian neural network [19], ensembles [35], and Stein variational inference [38] to tackle noisy environments. However, they typically require either complicated optimization methods or large networks. In contrast, DB learns a dynamics-relevant representation of the state-action pair and encourage exploration by directly accessing the information gain of new transitions via DB-bonus.

Another closely related line of studies uses the IB principle to promote exploration in RL. Novelty Search (NS) [47] proposes to learn a representation through IB. Curiosity Bottleneck (CB) [23] also performs exploration based on IB by measuring the task-relevant novelty. However, both NS and CB require extrinsic rewards to learn a value function and are not applicable for self-supervised exploration. Moreover, NS contains additional k-nearest-neighbor to generate intrinsic reward and representation loss to constrain the distance of consecutive states, which are costly for computation. In contrast, our DB model handles self-supervised exploration without accessing extrinsic rewards.

Our work is also related to representation learning in RL. DrQ [24], RAD [25] and CURL [43] learn the state representation by data augmentation and contrastive learning [13, 18, 32] to improve the data-efficiency of DRL. Deep InfoMax [29] and Self-Predictive Representation (SPR) [41] learn the contrastive and predictive representations of dynamics, respectively, and utilize such representations as auxiliary losses for policy optimization. However, none of these existing approaches extracts information that benefits exploration. In contrast, we show that the dynamics-relevant representation learned by DB can be utilized for efficient exploration.

3   The Dynamic Bottleneck

In this section, we introduce the objective function and architecture of the DB model. We consider an MDP that can be described by a tuple $(\mathcal{O}, \mathcal{A}, \mathbb{P}, r, \gamma)$, which consists of the observation space $\mathcal{O}$, the

Figure 1: Illustration of DB objective. DB minimizes the mutual information $I([S_t, A_t]; Z_t)$ to obtain a compressive representation, and maximize $I(Z_t; S_{t+1})$ to preserve the information.

action space $\mathcal{A}$, the transition dynamics $\mathbb{P}$, the reward function r, and the discount factor $\gamma \in (0, 1)$. At each time step, an agent decides to perform an action $a_t \in \mathcal{A}$ after observing $o_t \in \mathcal{O}$, and then the observation transits to o_{t+1} with a reward r_t received. In this paper, we use upper letters, such as O_t, to denote random variables and the corresponding lower case letter, such as o_t, to represent their corresponding realizations.

DB follows the IB principle [49] to learn dynamics-relevant representation. The input variable of the DB model is a tuple (O_t, A_t) that contains the current observation and action, and the target is the next observation O_{t+1}. We denote by S_t and S_{t+1} the encoding of observations O_t and O_{t+1}. The goal of the DB model is to obtain a compressed latent representation Z_t of (S_t, A_t), that preserves the information that is relevant to S_{t+1} only. Specifically, we use f_o^S and f_m^S as the encoders of two consecutive observations o_t and o_{t+1}, respectively. We parameterize the dynamics-relevant representation z_t by a Gaussian distribution with parameter ϕ, and it takes (s_t, a_t) as input. We summarize the DB model as follows,

$$s_t = f_o^S(o_t; \theta_o), \quad s_{t+1} = f_m^S(o_{t+1}; \theta_m), \quad z_t \sim g^Z(s_t, a_t; \phi). \tag{1}$$

Following the IB principle, the objective of the DB model seeks to maximize the mutual information $I(Z_t; S_{t+1})$ while minimizing the mutual information $I([S_t, A_t]; Z_t)$. To this end, we propose the DB objective by following the IB Lagrangian [49], which takes the form of

$$\min -I(Z_t; S_{t+1}) + \alpha_1 I([S_t, A_t]; Z_t). \tag{2}$$

Here α_1 is a Lagrange multiplier that quantifies the amount of information about the next state preserved in Z_t. Fig. 1 illustrates the DB objective. In what follows, we propose a lower bound of (2), which we optimize to train the DB model.

3.1 Maximizing the lower bound of $I(Z_t; S_{t+1})$

As directly maximizing $I(Z_t; S_{t+1})$ is intractable, we propose to optimize a predictive objective, which is a lower bound of $I(Z_t; S_{t+1})$ [2]. It holds that

$$I(Z_t; S_{t+1}) = \mathbb{E}_{p(z_t, s_{t+1})}\left[\log \frac{p(s_{t+1}|z_t)}{p(s_{t+1})}\right] = \mathbb{E}\left[\log \frac{q(s_{t+1}|z_t; \psi)}{p(s_{t+1})}\right] + D_{\mathrm{KL}}[p(s_{t+1}|z_t) \| q(s_{t+1}|z_t; \psi)], \tag{3}$$

where $p(s_{t+1}|z_t)$ is an intractable conditional distribution and $q(s_{t+1}|z_t; \psi)$ is a tractable variational decoder with parameter ψ. By the non-negativity of the KL-divergence, we obtain the following lower bound,

$$I(Z_t; S_{t+1}) \geq \mathbb{E}_{p(z_t, s_{t+1})}[\log q(s_{t+1}|z_t; \psi)] + \mathcal{H}(S_{t+1}),$$

where $\mathcal{H}(\cdot)$ is the entropy. Since $\mathcal{H}(S_{t+1})$ is irrelevant to the parameter ψ, maximizing $I(Z_t; S_{t+1})$ is equivalent to maximizing the following lower bound,

$$I_{\mathrm{pred}} \triangleq \mathbb{E}_{p(z_t, s_{t+1})}[\log q(s_{t+1}|z_t; \psi)]. \tag{4}$$

I_{pred} can be interpreted as the log-likelihood of the next-state encoding s_{t+1} given the dynamics-relevant representation z_t. In practice, we parameterize the prediction head $q(s_{t+1}|z_t; \psi)$ by a neural network that outputs a diagonal Gaussian random variable. Since s_t, s_{t+1} and z_t are all low-dimensional vectors instead of raw image pixels, optimizing I_{pred} is computationally efficient.

Momentum Encoder To encode the consecutive observations o_t and o_{t+1}, we adopt the Siamese architecture [9] that uses the same neural network structures for the two encoders. Nevertheless, we

observe that if we train both the encoders by directly maximizing I_{pred}, the Siamese architecture tends to converge to a collapsed solution. That is, the generated encodings appears to be uninformative constants. A simple fact is that if both the encoders generate zero vectors, predicting zeros conditioning on z_t (or any variables) is a trivial solution. To address such issue, we update the parameter θ_o of f_o^S in (1) by directly optimizing I_{pred}. Meanwhile, we update the parameter θ_m of f_m^S by an momentum moving average of θ_o, which takes the form of $\theta_m \leftarrow \tau\theta_m + (1-\tau)\theta_o$. In the sequel, we call f_o^S the online encoder and f_m^S the *momentum* encoder, respectively. Similar techniques is also adopted in previous study [17, 41] to avoid the mode collapse.

3.2 Contrastive Objective for Maximizing $I(Z_t; S_{t+1})$

In addition to the lower bound of $I(Z_t; S_{t+1})$ in §3.1, we also investigate the approach of maximizing the mutual information by contrastive learning (CL) [32]. CL classifies positive samples and negative samples in the learned representation space. An advantage of adopting CL is that training with negative samples playes the role of regularizer, which avoids collapsed solutions. Moreover, the contrastive objective yields a variational lower bound of the mutual information $I(Z; S_{t+1})$. To see such a fact, note that by the Bayes rule, we have

$$I(Z_t; S_{t+1}) \geq \mathbb{E}_{p(z_t, s_{t+1})}\mathbb{E}_{S^-}\left[\log \frac{\exp(h(z_t, s_{t+1}))}{\sum_{s_j \in S^- \cup s_{t+1}} \exp(h(z_t, s_j))}\right] \triangleq I_{\text{nce}}. \tag{5}$$

Here h is a score function which assigns high scores to positive pairs and low score to negative pairs. We refer to Appendix A for a detailed proof of (5). The right-hand side of (5) is known as the InfoNCE objective [32]. In practice, we collect the negative sample by sampling observation encodings randomly from the batch. We remark that comparing with methods that require data augmentation to construct negative samples [18, 43], DB utilizes a simple scheme to obtain positive and negative samples from on-policy experiences.

In (5), we adopt the standard bilinear function as the score function h, which is defined as follows,

$$h(z_t, s_{t+1}) = f_o^P(\bar{q}(z_t; \psi))^\top \mathcal{W} f_m^P(s_{t+1}), \tag{6}$$

where $f_o^P(\cdot; \varphi_o)$ and $f_m^P(\cdot; \varphi_m)$ project s_{t+1} and the mean value of next-state prediction $q(s_{t+1}|z_t; \varphi)$, i.e., $\bar{q}(\cdot; \psi)$, to a latent space to apply the contrastive loss I_{nce} in (5), and $\mathcal{W}$ is the parameter of the score function. Similar to the observation encoder and MoCo-based architectures [43, 18, 14], we also adopt an online projector f_o^P and a momentum projector f_m^P for z_t and s_{t+1}, respectively. The momentum projector is updated by $\varphi_m \leftarrow \tau\varphi_m + (1-\tau)\varphi_o$.

3.3 Minimizing the Upper Bound of $I([S_t, A_t]; Z_t)$

We minimize the mutual information $I([S_t, A_t]; Z_t)$ through minimizing a tractable upper bound of the mutual information. To this end, we introduce a variational approximation $r(z_t)$ to the intractable marginal $p(z_t) = \int p(s_t, a_t)p(z_t|s_t, a_t)ds_t a_t$. Specifically, the following upper-bound of $I([S_t, A_t]; Z_t)$ holds,

$$I([S_t, A_t]; Z_t) = \mathbb{E}_{p(s_t, a_t)}\left[\frac{p(z_t|s_t, a_t)}{p(z_t)}\right] = \mathbb{E}_{p(s_t, a_t)}\left[\frac{p(z_t|s_t, a_t)}{r(z_t)}\right] - D_{\text{KL}}\left[p(z_t)\|r(z_t)\right]$$
$$\leq \mathbb{E}_{p(s_t, a_t)}\left[D_{\text{KL}}[p(z_t|s_t, a_t)\|r(z_t)]\right] \triangleq I_{\text{upper}}, \tag{7}$$

where the inequality follows from the non-negativity of the KL divergence, and $r(z_t)$ is an approximation of the marginal distribution of Z_t. We follow Alemi et al. [2] and use a standard spherical Gaussian distribution $r(z_t) = \mathcal{N}(0, \mathbf{I})$ as the approximation. The expectation of I_{upper} is estimated by sampling from on-policy experiences.

3.4 The Loss Function and Architecture

The final loss for training the DB model is a combination of the upper and lower bounds established in previous sections,

$$\min_{\theta_o, \phi, \psi, \varphi_o, \mathcal{W}} \mathcal{L}_{\text{DB}} = \alpha_1 I_{\text{upper}} - \alpha_2 I_{\text{pred}} - \alpha_3 I_{\text{nce}}, \tag{8}$$

Figure 2: The network architecture of DB. The architecture contains several convolution neural networks (CNNs) and fully-connected networks (FCNs). It consists of four components, including (i) the observation encoder (f_o^S, f_m^S), which consists of an online network f_o^S and a momentum network f_m^S; (ii) the representation posterior $g^Z(s_t, a_t; \phi)$, which generates a Gaussian distribution for the input state action pair (s_t, a_t); (iii) the prediction head $q_\psi(s_{t+1}|z_t)$, which predicts the next state s_{t+1} based on sampling representation z_t from the representation posterior; and (iv) the projection heads (f_o^P, f_m^P), which maps the next observation encoding s_{t+1} and its prediction from the prediction head to low-dimensional space to perform contrastive estimation.

where α_1, α_2 and α_3 are hyper-parameters. As we show in the ablation study (§5), all of the three components in the loss plays an important role in learning dynamics-relevant representations. We illustrate the architecture of the DB model in Fig. 2. In practice, we minimize $\mathcal{L}_{\mathrm{DB}}$ in (8) by gradient descent, which iteratively updates the parameters of $f_o^S, g^Z, q_\psi, \mathcal{W}$ and f_o^P. Meanwhile, we adopt exponential moving average to update the parameters of f_m^S and f_m^P to avoid collapsed solutions. We refer to Appendix B for the pseudocode of training DB model.

4 Exploration with DB-Bonus

We are now ready to introduce the DB-bonus r^{db} for exploration. In this section, we first present the DB-bonus for self-supervised exploration. We establish the theoretical connections between the DB-bonus and provably efficient bonus functions. We further present the empirical estimation of DB-bonus and the policy optimization algorithm that utilizes the DB-bonus.

In the sequel, we assume that the learned parameter Θ of the DB model follows a Bayesian posterior distribution given the training dataset $\mathcal{D}_m = \{(s_t^i, a_t^i, s_{t+1}^i)\}_{i \in [0,m]}$, which is a collection of past experiences from m episodes performed by the agent to train the DB model. We aim to estimate the following conceptual reward, which is defined by the mutual information between the parameter of the DB model and the transition dynamics given the training dataset,

$$
\begin{aligned}
r^{\mathrm{db}}(s_t, a_t) &\triangleq I\big(\Theta; (s_t, a_t, S_{t+1})|\mathcal{D}_m\big)^{1/2} \\
&= \Big[\mathcal{H}\big((s_t, a_t, S_{t+1})|\mathcal{D}_m\big) - \mathcal{H}\big((s_t, a_t, S_{t+1})|\Theta, \mathcal{D}_m\big)\Big]^{1/2}.
\end{aligned}
\tag{9}
$$

Intuitively, DB-bonus defined in (9) encourages the agent to explore transitions that are maximally informative to the improvement of the DB model.

4.1 Theoretical Analysis

We show that the DB-bonus defined in (9) enjoys well theoretical properties, and establish theoretical connections between r^{db} and bonuses based on the optimism in the face of uncertainty [4, 21], which incorporates UCB into value functions in both tabular [5, 20, 16] and linear MDPs [22, 12].

Connection to UCB-bonus in linear MDPs In linear MDPs, the transition kernel and reward function are assumed to be linear. In such a setting, LSVI-UCB [22] provably attains a near-optimal worst-case regret, and we refer to Appendix C.1 for the details. The idea of LSVI-UCB is using an optimistic Q-value, which is obtained by adding an UCB-bonus r^{ucb} [1] to the estimation of the Q-value. The UCB-bonus is defined as $r_t^{\mathrm{ucb}} = \beta \cdot \big[\eta(s_t, a_t)^\top \Lambda_t^{-1} \eta(s_t, a_t)\big]^{1/2}$, where β is a constant, $\Lambda_t = \sum_{i=0}^m \eta(x_t^i, a_t^i)\eta(x_t^i, a_t^i)^\top + \lambda \cdot \mathbf{I}$ is the Gram matrix, and m is the index of the current episode. The UCB-bonus measures the epistemic uncertainty of the state-action and is provably efficient [22].

For linear MDPs, we consider representation $z \in \mathbb{R}^c$ as the mean of the posterior g^Z from the DB model, and set z_t to be a linear function of the state-action encoding, i.e., $z_t = W_t \eta(s_t, a_t)$

parameterized by $W_t \in \mathbb{R}^{c \times d}$. Then, the following theorem establishes a connection between the DB-bonus r^{db} and the UCB-bonus r^{ucb}.

Theorem 1. *In linear MDPs, for tuning parameter $\beta_0 > 0$, it holds that*

$$\beta_0/\sqrt{2} \cdot r_t^{\text{ucb}} \le I(W_t; (s_t, a_t, S_{t+1})|\mathcal{D}_m)^{1/2} \le \beta_0 \cdot r_t^{\text{ucb}}, \tag{10}$$

where $I(W_t; (s_t, a_t, S_{t+1})|\mathcal{D}_m)^{1/2}$ is the DB-bonus $r^{\text{db}}(s_t, a_t)$ under the linear MDP setting.

In addition, using r^{db} as bonus leads to the same regret as LSVI-UCB by following a similar proof to Jin et al. [22]. We refer to Appendix C.2 for the problem setup and the detailed proofs. We remark that Theorem 1 is an approximate derivation because we only consider the predictive objective I_{pred} in (8) in Theorem 1. Nevertheless, introducing the contrastive objective I_{nce} is important in the training of the DB model as it prevents the mode collapse issue. Theorem 1 shows that the DB-bonus provides an instantiation of the UCB-bonus in DRL, which enables us to measure the epistemic uncertainty of high-dimensional states and actions without the linear MDP assumption.

Connection to visiting count in tabular MDP The following theorem establishes connections between DB-bonus and the count-based bonus $r^{\text{count}}(s_t, a_t) = \frac{\beta}{\sqrt{N_{s_t, a_t} + \lambda}}$ in tabular MDPs.

Theorem 2. *In tabular MDPs, it holds for the DB-bonus $r^{\text{db}}(s_t, a_t)$ and the count-based intrinsic reward $r^{\text{count}}(s_t, a_t)$ that,*

$$r^{\text{db}}(s_t, a_t) \approx \frac{\sqrt{|\mathcal{S}|/2}}{\sqrt{N_{s_t, a_t} + \lambda}} \;\; = \;\; \beta_0 \cdot r^{\text{count}}(s_t, a_t), \tag{11}$$

when N_{s_t, a_t} is large, where $\lambda > 0$ is a tuning parameter, $|\mathcal{S}|$ is the number of states in tabular setting.

We refer to Appendix C.3 for a detailed proofs. As a result, DB-bonus can also be considered as a count-based intrinsic reward in the space of dynamics-relevant representations.

4.2 Empirical Estimation

To estimate such a bonus under our DB model, we face several challenges. (i) Firstly, estimating the bonus defined in (9) requires us to parameterize representation under a Bayesian learning framework, whereas our DB model is parameterized by non-Bayesian neural networks. (ii) Secondly, estimating the DB-bonus defined in (9) requires us to compute the mutual information between the unknown transitions and the estimated model, which is in general hard as we do not have access to such transitions in general. To address such challenges, we estimate a lower bound of the DB-bonus, which is easily implementable and achieves reasonable performance empirically. Specifically, we consider to use $r_l^{\text{db}}(s_t, a_t)$ as the lower bound of the information gain in (9),

$$r^{\text{db}}(s_t, a_t) \ge \left[\mathcal{H}\big(g(s_t, a_t, S_{t+1})|\mathcal{D}_m\big) - \mathcal{H}\big(g(s_t, a_t, S_{t+1})|\Theta, \mathcal{D}_m\big) \right]^{1/2} \triangleq r_l^{\text{db}}(s_t, a_t), \tag{12}$$

which holds for any mapping g according to data processing inequality. In our model, we adopt the following mapping,

$$g(s_t, a_t, S_{t+1})|\Theta, \mathcal{D}_m = g^Z(s_t, a_t; \phi), \tag{13}$$

where g^Z is the representation distribution of DB, and ϕ constitutes a part of parameters of the total parameters Θ. Intuitively, since g^Z is trained by IB principle to capture information of transitions, adopting the mapping g^Z to (12) yields a reasonable approximation of the DB-bonus. It further holds

$$r_l^{\text{db}}(s_t, a_t) = \left[\mathcal{H}\big(g^{\text{margin}}\big) - \mathcal{H}\big(g^Z(s_t, a_t; \phi)\big) \right]^{1/2} = \mathbb{E}_\Theta D_{\text{KL}}\big[g^Z(z_t|s_t, a_t; \phi)\|g^{\text{margin}}\big]^{1/2}, \tag{14}$$

where we define $g^{\text{margin}} = g(s_t, a_t, S_{t+1})|\mathcal{D}_m$ as the marginal of the encodings over the posterior of the parameters Θ of the DB model. In practice, since g^{margin} is intractable, we approximate g^{margin} with standard Gaussian distribution. We remark that such approximation is motived by the training of DB model, which drives the marginal of representation g^Z toward $\mathcal{N}(0, \mathbf{I})$ through minimizing I_{upper} in (7). Such approximation leads to a tractable estimation and stable empirical performances.

In addition, since we do not train the DB model with Bayesian approach, we replace the expectation over posterior Θ in (14) by the corresponding point estimation, namely the parameter Θ of the

Algorithm 1 SSE-DB

1: **Initialize:** The DB model and the actor-critic network
2: **for** episode $i = 1$ to M **do**
3:     **for** timestep $i = 0$ to $T - 1$ **do**
4:         Obtain action from the actor $a_t = \pi(s_t)$, then execute a_t and observe the state s_{t+1};
5:         Add (s_t, a_t, s_{t+1}) into the on-policy experiences;
6:         Obtain the DB-bonus $\hat{r}_l^{\mathrm{db}}$ of (s_t, a_t) by (15);
7:     **end for**
8:     Update the actor and critic by PPO with the collected on-policy experiences as the input;
9:     Update DB by gradient descent based on (8) with the collected on-policy experiences;
10: **end for**
---

neural networks trained with DB model on the dataset $\mathcal{D}_m$. To summarize, we utilize the following approximation of the DB-bonus r^{db} proposed in (9),

$$\hat{r}_l^{\mathrm{db}}(s_t, a_t) = D_{\mathrm{KL}}\left[g^Z(\cdot | s_t, a_t; \phi) \, \| \, \mathcal{N}(0, \mathbf{I}) \right]^{1/2} \approx r_l^{\mathrm{db}}(s_t, a_t). \tag{15}$$

Since DB is trained by IB principle, which filters out the dynamics-irrelevant information, utilizing the bonus defined in (15) allows the agent to conduct robust exploration in noisy environments.

We summarize the the overall RL algorithm with self-supervised exploration induced by the DB-bonus in Algorithm 1, which we refer to as Self-Supervised Exploration with DB-bonus (SSE-DB). For the RL implementation, we adopt Proximal Policy Optimization (PPO) [40] with generalized advantage estimation [39] and the normalization schemes from Burda et al. [10]. We refer to Appendix D for the implementation details. The codes are available at `https://github.com/review-anon/DB`.

5 Experiments

We evaluate SSE-DB on Atari games. We conduct experiments to compare the following methods. (i) **SSE-DB**. The proposed method in Alg. 1. (ii) **Intrinsic Curiosity Model (ICM)** [34]. ICM uses an inverse dynamics model to extract features related to the actions. ICM further adopts the prediction error of dynamics as the intrinsic reward for exploration. (iii) **Disagreement** [35]. This method captures epistemic uncertainty by the disagreement among predictions from an ensemble of dynamics models. Disagreement performs competitive to ICM and RND [11]. Also, this method is robust to white-noise. (iv) **Curiosity Bottleneck (CB)** [23]. CB quantifies the compressiveness of observation with respect to the representation as the bonus. CB is originally proposed for exploration with extrinsic rewards. We adapt CB for self-supervised exploration by setting the extrinsic reward zero. We compare the model complexity of all the methods in Appendix D. Other methods including Novelty Search [47] and Contingency-aware exploration [15] are also deserve to compare. However, we find Novelty Search ineffective in our implementation since the detailed hyper-parameters and empirical results in Atari are not available. Contingency-aware exploration is related to DB while the attention module is relatively complicated and the code is not achievable.

5.1 The Main Results

We evaluate all methods on Atari games with high-dimensional observations. The selected 18 games are frequently used in previous approaches for efficient exploration. The overall results are provided in Fig. 3. We highlight that in our experiments, the agents are trained without accessing the extrinsic rewards. The extrinsic rewards are ONLY utilized to evaluate the performance of the policies obtained from self-supervised exploration. Our experiments show that SSE-DB performs the best in 15 of 18 tasks, suggesting that dynamics-relevant feature together with DB-bonus helps the exploration of states with high extrinsic rewards.

Nevertheless, we observe that SSE-DB is suboptimal in one of the games, namely, Tennis. A possible explanation is that for Tennis, the prediction error based methods, such as ICM, could capture additional information in the intrinsic rewards. For example, in Tennis, the prediction error becomes higher when the ball moves faster or when the agent hits the ball towards a tricky direction. The prediction-error based methods can naturally benefit from such nature of the game. In contrast,

Figure 3: The evaluation curve in Atari games. The different methods are trained with different intrinsic rewards. Each method was run with three random seeds.

SSE-DB encourages exploration based on the information gain from learning the dynamics-relevant representation, which may not capture such critical events in Tennis.

5.2 Robustness in the Presence of Noises

Observation Noises. To analyze the robustness of SSE-DB to observation noises, an important evaluation metric is the performance of SSE-DB in the presence of dynamics-irrelevant information. A particularly challenging distractor is the white-noise [10, 23], which incorporates random task-irrelevant patterns to the observations. In such a scenario, a frequently visited state by injecting an unseen noise pattern may be mistakenly assigned with a high intrinsic reward by curiosity or pseudo-count based methods.

We use two types of distractors for the observations of Atari games, namely, (1) the random-box noise distractor, which places boxes filled with random Gaussian noise over the raw pixels, and (2) the pixel-level noise distractor, which adds pixel-wise Gaussian noise to the observations. Fig. 4 shows examples of the two types of distractors. In the sequel, we discuss results for the random-box noise distractor on selected Atari games, which we find sufficiently representative, and defer the complete report to Appendix E.1 and E.2.

Normal Observation   **Random-Box Noise**   **Pixel Noise**

Figure 4: Observation of Breakout with no distractor (left), random-box noise distractor (middle), and pixel noise distractor (right).

Fig. 5(a) shows the performance of the compared methods on Alien, Breakout and TimePilot with and without noises. We observer that SSE-DB outperforms ICM on Alien and TimePilot with random-box noises. Nevertheless, in Breakout, we observe that both the methods fail to learn informative policies. A possible explanation is that, in Breakout, the ball is easily masked by the box-shaped noise (i.e., middle of Fig. 4). The random-box noise therefore buries critical transition information of the ball, which hinders all the baselines to extract dynamics-relevant information and leads to failures on Breakout with random-box noise as shown in Fig. 5(a).

Action Noise. In addition to observation noises, noises in actions also raise challenges for learning the transition dynamics. To further study the robustness of SSE-DB, we conduct experiments on Atari games with sticky actions [28, 35]. At each time step, the agent may execute the previous action instead of the output action of current policy with a probability of 0.25. We illustrate results on three selected Atari games, i.e., Boxing, Gravitar and MsPacman, in Fig. 5(b) and defer the complete

| (a) Atari with random-box noise | (b) Atari with sticky actions |

Figure 5: A comparison on selected Atari games with and without noises. (a) Random-box noise. In Alien and TimePilot, SSE-DB is barely affected by random-box noise. Both methods fail in Breakout. (b) Sticky actions. Illustration shows SSE-DB is barely affected by the sticky actions.

results to Appendix E.3. Our experiments show that SSE-DB is robust to action noises, whereas ICM suffers significant performance drop from the action noise.

5.3 Visualization and Ablation Study

Visualization of the Learned Representations. To understand the latent representation learned by the DB model, we visualize the learned Z with t-SNE [27] plots, which projects a 128d z-vector to a 2d one through dimensionality reduction. We compare the representations learned by SSE-DB and ICM with random-box noise. We illustrate the learned representations of MsPacman in Fig. 6. According to the visualization, representations learned by DB tends to align temporally-consecutive movements on the same curve. Moreover, each segment of a curve corresponds to a semantic component of the trajectory, such as eating pellets aligned together or avoiding ghosts. The segments of a curve end up with critical states, including death and reborn of the agent and ghosts. The visualization indicates that DB well captures the dynamics-relevant information in the learned representations. In contrast, such temporally-consecutive patterns are missing in the learned representation of ICM.

(a) DB representations with Random-Box   (b) ICM representations with Random-Box

Figure 6: Visualization of latent representations of MsPacman with random-box noise. The figures plot the representation of the same trajectory by DB (left) and ICM (right). Consecutive states are connected by the shaded lines. Numbers on the representations are the corresponding number of time steps. Representation learned by DB tends to align consecutive states on the same curve.

Visualization of the DB bonus. We provide visualization of the DB-bonus in Appendix E.5. The results show the DB-bonus effectively encourages the agent to explore the informative transitions.

Ablation Study. The training of DB loss consists of multiple components, including I_{pred}, I_{nce}, I_{upper}, and the momentum observation encoder. To analyze the importance of the components, we conduct an ablation study by removing each of them respectively and evaluate the DB model correspondingly. The ablation study suggests that the all the components are crucial for learning effective dynamics-relevant representations. In addition, we observe that I_{upper} is particularly important in the environment with dynamics-irrelevant noise. Please refer to Appendix E.4 for details.

6 Conclusion

In this paper, we introduce Dynamic Bottleneck model that learns dynamics-relevant representations based on the IB principle. We further propose DB-bonus based on the DB model for efficient exploration. We establish theoretical connections between the proposed DB-bonus and provably efficient bonuses. Our experiments show that SSE-DB outperforms several strong baselines in stochastic environments for self-supervised exploration. Moreover, we observe that DB learns well-structured representations and the DB-bonus characterizes informative transitions for exploration. For our future work, we wish to combine the DB representation to effective exploration methods including BeBold [52] and NGU [6] to enhance their robustness in stochastic environments.

References

[1] Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in neural information processing systems*, volume 24, pages 2312–2320, 2011.

[2] Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. In *International Conference on Learning Representations*, 2017.

[3] Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

[4] Peter Auer and Ronald Ortner. Logarithmic online regret bounds for undiscounted reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 49–56, 2007.

[5] Mohammad Gheshlaghi Azar, Ian Osband, and Rémi Munos. Minimax regret bounds for reinforcement learning. In *International Conference on Machine Learning*, pages 263–272, 2017.

[6] Adrià Puigdomènech Badia, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, Bilal Piot, Steven Kapturowski, Olivier Tieleman, Martin Arjovsky, Alexander Pritzel, Andrew Bolt, and Charles Blundell. Never give up: Learning directed exploration strategies. In *International Conference on Learning Representations*, 2020.

[7] Chenjia Bai, Peng Liu, Zhaoran Wang, Kaiyu Liu, Lingxiao Wang, and Yingnan Zhao. Variational dynamic for self-supervised exploration in deep reinforcement learning. *arXiv preprint arXiv:2010.08755*, 2020.

[8] Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, pages 1471–1479, 2016.

[9] Jane Bromley, James W Bentz, Léon Bottou, Isabelle Guyon, Yann LeCun, Cliff Moore, Eduard Säckinger, and Roopak Shah. Signature verification using a "siamese" time delay neural network. *International Journal of Pattern Recognition and Artificial Intelligence*, 7(04):669–688, 1993.

[10] Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. In *International Conference on Learning Representations*, 2019.

[11] Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. In *International Conference on Learning Representations*, 2019.

[12] Qi Cai, Zhuoran Yang, Chi Jin, and Zhaoran Wang. Provably efficient exploration in policy optimization. In *International Conference on Machine Learning*, pages 1283–1294. PMLR, 2020.

[13] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, 2020.

[14] Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020.

[15] Jongwook Choi, Yijie Guo, Marcin Moczulski, Junhyuk Oh, Neal Wu, Mohammad Norouzi, and Honglak Lee. Contingency-aware exploration in reinforcement learning. In *International Conference on Learning Representations*, 2019.

[16] Christoph Dann and Emma Brunskill. Sample complexity of episodic fixed-horizon reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 2818–2826, 2015.

[17] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[18] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

[19] Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Vime: Variational information maximizing exploration. In *Advances in Neural Information Processing Systems*, pages 1109–1117, 2016.

[20] Thomas Jaksch, Ronald Ortner, and Peter Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 11(Apr):1563–1600, 2010.

[21] Chi Jin, Zeyuan Allen-Zhu, Sebastien Bubeck, and Michael I Jordan. Is q-learning provably efficient? In *Advances in Neural Information Processing Systems*, pages 4863–4873, 2018.

[22] Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pages 2137–2143, 2020.

[23] Youngjin Kim, Wontae Nam, Hyunwoo Kim, Ji-Hoon Kim, and Gunhee Kim. Curiosity-bottleneck: Exploration by distilling task-specific novelty. In *International Conference on Machine Learning*, pages 3379–3388, 2019.

[24] Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

[25] Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. In *Advances in Neural Information Processing Systems*, 2020.

[26] Manuel Lopes, Tobias Lang, Marc Toussaint, and Pierre-Yves Oudeyer. Exploration in model-based reinforcement learning by empirically estimating learning progress. In *Advances in Neural Information Processing Systems*, pages 206–214, 2012.

[27] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.

[28] Marlos C Machado, Marc G Bellemare, Erik Talvitie, Joel Veness, Matthew Hausknecht, and Michael Bowling. Revisiting the arcade learning environment: Evaluation protocols and open problems for general agents. *Journal of Artificial Intelligence Research*, 61:523–562, 2018.

[29] Bogdan Mazoure, Remi Tachet des Combes, Thang Long DOAN, Philip Bachman, and R Devon Hjelm. Deep reinforcement and infomax learning. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[30] Rhiannon Michelmore, Marta Kwiatkowska, and Yarin Gal. Evaluating uncertainty quantification in end-to-end autonomous driving control. *arXiv preprint arXiv:1811.06817*, 2018.

[31] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.

[32] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[33] Georg Ostrovski, Marc G Bellemare, Aäron van den Oord, and Rémi Munos. Count-based exploration with neural density models. In *International Conference on Machine Learning*, pages 2721–2730, 2017.

[34] Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pages 2778–2787, 2017.

[35] Deepak Pathak, Dhiraj Gandhi, and Abhinav Gupta. Self-supervised exploration via disagreement. In *International Conference on Machine Learning*, pages 5062–5071, 2019.

[36] Pascal Poupart, Nikos Vlassis, Jesse Hoey, and Kevin Regan. An analytic solution to discrete bayesian reinforcement learning. In *International conference on Machine learning*, pages 697–704, 2006.

[37] Tabish Rashid, Bei Peng, Wendelin Boehmer, and Shimon Whiteson. Optimistic exploration even with a pessimistic initialisation. In *International Conference on Learning Representations*, 2020.

[38] Neale Ratzlaff, Qinxun Bai, Li Fuxin, and Wei Xu. Implicit generative modeling for efficient exploration. In *International Conference on Machine Learning*, pages 7985–7995. PMLR, 2020.

[39] John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

[40] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[41] Max Schwarzer, Ankesh Anand, Rishab Goel, R Devon Hjelm, Aaron Courville, and Philip Bachman. Data-efficient reinforcement learning with self-predictive representations. In *International Conference on Learning Representations*, 2021.

[42] Ravid Shwartz-Ziv and Naftali Tishby. Opening the black box of deep neural networks via information. *arXiv preprint arXiv:1703.00810*, 2017.

[43] Aravind Srinivas, Michael Laskin, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, 2020.

[44] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[45] Adrien Ali Taiga, William Fedus, Marlos C Machado, Aaron Courville, and Marc G Bellemare. On bonus based exploration methods in the arcade learning environment. In *International Conference on Learning Representations*, 2020.

[46] Haoran Tang, Rein Houthooft, Davis Foote, Adam Stooke, OpenAI Xi Chen, Yan Duan, John Schulman, Filip DeTurck, and Pieter Abbeel. # exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 2753–2762, 2017.

[47] Ruo Yu Tao, Vincent François-Lavet, and Joelle Pineau. Novelty search in representational space for sample efficient exploration. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[48] Naftali Tishby and Noga Zaslavsky. Deep learning and the information bottleneck principle. In *2015 IEEE Information Theory Workshop (ITW)*, pages 1–5. IEEE, 2015.

[49] Naftali Tishby, Fernando C Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

[50] Lingxiao Wang, Zhuoran Yang, and Zhaoran Wang. Provably efficient causal reinforcement learning with confounded observational data. *arXiv preprint arXiv:2006.12311*, 2020.

[51] Mike West. Outlier models and prior distributions in bayesian linear regression. *Journal of the Royal Statistical Society: Series B (Methodological)*, 46(3):431–439, 1984.

[52] Tianjun Zhang, Huazhe Xu, Xiaolong Wang, Yi Wu, Kurt Keutzer, Joseph E Gonzalez, and Yuandong Tian. Bebold: Exploration beyond the boundary of explored regions. *arXiv preprint arXiv:2012.08621*, 2020.