Tensor Normal Training for Deep Learning Models

Abstract

Despite the predominant use of first-order methods for training deep learning
models, second-order methods, and in particular, natural gradient methods, remain
of interest because of their potential for accelerating training through the use
of curvature information. Several methods with non-diagonal preconditioning
matrices, including KFAC [32] and Shampoo [18], have been proposed and shown
to be effective. Based on the so-called *tensor normal* (TN) distribution, we propose
and analyze a brand new approximate natural gradient method, *Tensor Normal
Training* (TNT), which like Shampoo, only requires knowledge on the shape
of the training parameters. By approximating the probabilistically based Fisher
matrix, as opposed to the empirical Fisher matrix, our method uses the layer-
wise covariance of the sampling based gradient as the pre-conditioning matrix.
Moreover, the assumption that the sampling-based (tensor) gradient follows a TN
distribution, ensures that its covariance has a Kronecker separable structure, which
leads to a tractable approximation to the Fisher matrix. Consequently, TNT's
memory requirements and per-iteration computational costs are only slightly higher
than those for first-order methods. In our experiments, TNT exhibited superior
optimization performance to KFAC and Shampoo, and to state-of-the-art first-order
methods. Moreover, TNT demonstrated its ability to generalize as well as these
first-order methods, using fewer epochs.

1 Introduction

First-order methods are currently by far the most popular and successful optimization methods for
training deep learning models. Stochastic gradient descent (SGD) [37] uses the (stochastic) gradient
direction to guide its update at every iteration. Adaptive learning rate methods, including AdaGrad
[11], RMSprop [20], and Adam [22], scale each element of the gradient direction (possibly modified
to incorporate momentum) by the square root of the second moment of each element of the gradient.
These first-order methods use little curvature information to "pre-condition" the gradient direction;
SGD uses an identity matrix as its pre-conditioning matrix, whereas the others use a diagonal matrix.

On the other hand, second-order methods have the potential to greatly accelerate the optimization
process by exploring the rich curvature information of the problem. Traditional second-order methods
such as Newton's method, BFGS [6, 13, 14, 38], and limited-memory BFGS (L-BFGS) [26], without
modification, are not practical in a deep learning setting, because these methods require enormous
amounts of memory and computational effort per iteration due to the huge number of parameters
such models have. Some second-order methods have been proposed to deal with the non-convexity
and stochasiticity of objective functions arising in machine learning (see e.g. [34, 7, 16, 41]), but
directly using these methods to train deep learning models still requires large amounts of memory
and computing resources.

Recently, there has been considerable advancement in the development of second-order methods that
are suitable for deep learning models with huge numbers of parameters. These methods usually ap-

proach pre-conditioning of the gradient in a modular way, resulting in block-diagonal pre-conditioning matrices, where each block corresponds to a layer or a set of trainable parameters in the model. Inspired by the idea of the natural gradient method [2], KFAC [32] proposed a Kronecker-factored approximation to the Fisher matrix as its pre-conditioning matrix that can be applied to multilayer perceptrons, which was subsequently extended to other architectures, such as convolutional neural networks [17] and recurrent neural networks [33]. Kronecker-factored preconditioners based on the structure of the Hessian and quasi-Newton methods have also been developed [15, 36]. Despite the great success of these efficient and effective second-order methods, developing such methods requires careful examination of the structure of the preconditioning matrix to design appropriate approximations for each type of layer in a model.

Another well-recognized second-order method, Shampoo [18, 3], extends the adaptive learning rate method AdaGrad, so that the gradient is pre-conditioned along every dimension of the underlying tensor of parameters in the model, essentially replacing the diagonal pre-conditioning matrix of adaptive learning rate methods by a block diagonal Kronecker-factored matrix which can be viewed as an approximation to a fractional power of the empirical Fisher (EF) matrix. However, while estimating the Fisher matrix, in a deep learning setting, by the EF matrix saves some computational effort, it does not capture as much valuable curvature information as the Fisher matrix [24].

Variants of the normal distribution, i.e. the matrix-normal distribution [9] and the tensor-normal distribution [29], have been proposed to estimate the covariance of matrix and higher-order tensor observations, respectively. By imposing a Kronecker structure on the covariance matrix, the resulting covariance estimate requires a vastly reduced amount of memory, while still capturing the interactions between the various dimensions of the respective matrix or tensor. Iterative MLE methods for estimating the parameters of matrix-normal and tensor-normal distributions have been examined in e.g. [12, 29], and various ways to identify the unique representation of the distribution parameters have been proposed in [40, 10]. However, to the best of our knowledge, this advanced statistical methodology has not been used to develop optimization methods for deep learning. In this paper, we describe a first attempt to do this and demonstrate its great potential.

Our Contributions. In this paper, we propose a brand new approximate natural gradient (NG) method, Tensor-Normal Training (TNT), that makes use of the tensor normal distribution to approximate the Fisher matrix. Significantly, the TNT method can be applied to any model whose training parameters are a collection of tensors without knowing the exact structure of the model.

To achieve this, we first propose a new way, that is suitable for optimization, to identify the covariance parameters of tensor normal (TN) distributions, in which the average eigenvalues of the covariance matrices corresponding to each of the tensor dimensions are required to be the same (see Section 3).

By using the Kronecker product structure of the TN covariance, TNT only introduces mild memory and per-iteration computational overhead compared with first-order methods. Also, TNT's memory usage is the same as Shampoo's and no greater than KFAC's, while its per-iteration computational needs are no greater than Shampoo's and KFAC's (see Section 5).

The effectiveness of TNT is demonstrated on deep learning models. Specifically, on standard autoencoder problems, when optimization performance is compared, TNT converges faster than benchmark first- and second-order methods. Moreover, on standard CNN models, when generalization is concerned, TNT is able to achieve roughly the same level of validation accuracy as the first-order methods, but using far fewer epochs (see Section 6).

We also prove that, if the statistics used in TNT can be estimated ideally, it converges to a stationary point under mild assumptions (see Section 4).

2 Preliminaries

Supervised Learning. Throughout this paper, we consider the classic supervised learning setting where we learn the parameters θ of a model, by minimizing $\mathcal{L}(\theta) = \frac{1}{N} \sum_{i=1}^{N} l(y_i, f_\theta(x_i))$, where $\{(x_i, y_i)\}_{i=1}^{N}$ denotes a given dataset (x_i being the input to the model and y_i being the target), $f_\theta(x_i)$ denotes the output of the model when x_i is provided as the input, and l denotes a loss function (e.g. least-squares loss for regression and cross entropy loss for classification) that measures the discrepancy between the model output $f_\theta(x_i)$ and the target y_i.

Natural Gradient Method and the Fisher Matrix. In a first-order method, say SGD, the updating direction is always derived from an estimate to the gradient direction $\nabla_\theta \mathcal{L}(\theta)$. In a natural gradient (NG) method [2], however, the Fisher matrix is used as a pre-conditioning matrix that is applied to the gradient direction. As shown in [32], the Fisher matrix is defined as

$$F = \mathbb{E}_{x \sim Q_x, y \sim p(\cdot|x,\theta)} \left[\nabla_\theta \log p(y|x,\theta) \left(\nabla_\theta \log p(y|x,\theta) \right)^\top \right], \tag{1}$$

where Q_x is the data distribution of x and $p(\cdot|x,\theta)$ is the density function of the conditional distribution defined by the model with a given input x.

In many cases, such as when p is associated with a Gaussian distribution and the loss function l measures least-squares loss, or when p is associated with a multinomial distribution and l is cross-entropy loss, $\log p$ is equivalent to l (see e.g. [31, 32]). Hence, if $\mathcal{D}\theta$ denotes the gradient of l w.r.t. θ for a given x and y, we have that $F = \mathbb{E}_{x \sim Q_x, y \sim p}[\mathcal{D}\theta \mathcal{D}\theta^\top]$. Consequently, one can sample x from Q_x and perform a forward pass of the model, then sample y from $p(\cdot|x,\theta)$, and perform a backward pass to compute $\mathcal{D}\theta$, and then use $\mathcal{D}\theta \mathcal{D}\theta^\top$ to estimate F. We call $\mathcal{D}\theta$ a *sampling-based gradient*, as opposed to the *empirical gradient* $\nabla_\theta l(y_i, f_\theta(x_i))$ where (x_i, y_i) is one instance from the dataset.

It is worth noting that the first moment of $\mathcal{D}\theta$ is zero. To see this, note that, with given x,

$$\mathbb{E}_{y \sim p}[\nabla_\theta \log p(y|x,\theta)] = \int \nabla_\theta \log p(y|x,\theta) p(y|x,\theta) dy = \int \nabla_\theta p(y|x,\theta) dy$$

$$= \nabla_\theta \left(\int p(y|x,\theta) dy \right) = \nabla_\theta 1 = 0.$$

Hence, $\mathbb{E}_{x \sim Q_x, y \sim p}[\mathcal{D}\theta] = \mathbb{E}_{x \sim Q_x} \{\mathbb{E}_{y \sim p}[\nabla_\theta \log p(y|x,\theta)] \mid x\} = 0$. Thus, the Fisher matrix F can be viewed as the covariance matrix of $\mathcal{D}\theta$. Note that the empirical Fisher CANNOT be viewed as the covariance of the empirical gradient, because the first moment of the latter is, in general, NOT zero.

Tensor-Normal Distribution. The development of our new method makes use the so-called *tensor-normal* distribution [29, 10]:

Definition 1. *An arbitrary tensor $G \in \mathbb{R}^{d_1 \times \cdots \times d_k}$ is said to follow a tensor normal (TN) distribution with mean parameter $M \in \mathbb{R}^{d_1 \times \cdots \times d_k}$ and covariance parameters $U_1 \in \mathbb{R}^{d_1 \times d_1}, ..., U_k \in \mathbb{R}^{d_k \times d_k}$ if and only if $\overline{vec}(G) \sim Normal(\overline{vec}(M), U_1 \otimes \cdots \otimes U_k)$.*

In the above definition, the $\overline{vec}$ operation refers to the *vectorization* of a tensor, whose formal definition can be found in Sec A in the Appendix. Note that *matrix-normal* distribution can be viewed as a special case of TN distribution where $k = 2$. Compared with a regular normal distribution, whose covariance matrix has $\prod_{i=1}^k d_i^2$ elements, the covariance of a k-way tensor-normal distribution is stored in k smaller matrices with a total number of elements equal to $\sum_{i=1}^k d_i^2$.

To estimate the covariance submatrices $U_1, \ldots, U_k$, the following property (e.g., see [10]) is used:

$$\mathbb{E}[G^{(i)}] = U_i \cdot \prod_{j \neq i} \text{tr}(U_j), \tag{2}$$

where $G^{(i)} := \text{mat}_i(G)\text{mat}_i(G)^\top \in \mathbb{R}^{d_i \times d_i}$ denotes the *contraction* of G with itself along all but the ith dimension and mat_i refers to *matricization* of a tensor (see Section A for the formal definitions). By (2), we can sample G to obtain estimates of the $G^{(i)}$'s, and hence, estimates of the U_i's. The complexity of computing $G^{(i)}$ is $d_i \prod_{j=1}^k d_j$, which is also far less than the complexity of computing $\overline{vec}(G)\overline{vec}(G)^\top$ needed to estimate the covariance of a regular normal distribution.

3 Tensor-Normal Training

In this section, we propose Tensor-Normal Training (TNT), a brand new variant of the natural gradient (NG) method that makes use of the tensor-normal distribution.

3.1 Block Diagonal Approximation

In this paper, we consider the case where the parameters of the model θ consists of multiple tensor variables $W_1, ..., W_L$, i.e. $\theta = \left(\overline{vec}(W_1)^\top, ..., \overline{vec}(W_L)^\top \right)^\top$. This setting is applicable to most

common models in deep learning such as multi-layer perceptrons, convolutional neural networks, recurrent neural networks, etc. In these models, the trainable parameter W_l $(l = 1, \ldots, L)$ come from the weights or biases of a layer, whether it be a feed-forward, convolutional, recurrent, or batch normalization layer, etc. Note that the index l of W_l refers to the index of a tensor variable, as opposed to a layer.

To obtain a practical NG method, we assume, as in KFAC and Shampoo, that the pre-conditioning Fisher matrix is block diagonal. To be more specific, we assume that each block corresponds to the covariance of a tensor variable in the model. Hence, the approximate Fisher matrix is:

$$F \approx \operatorname{diag}_{l=1}^{L} \left\{ \mathbb{E}_{x \sim Q_x, y \sim p} \left[\overline{\operatorname{vec}}(\mathcal{D}W_l)(\overline{\operatorname{vec}}(\mathcal{D}W_l))^{\top} \right] \right\} = \operatorname{diag}_{l=1}^{L} \left\{ \operatorname{Var}(\overline{\operatorname{vec}}(\mathcal{D}W_l)) \right\}.$$

The remaining question is how should one approximate $\operatorname{Var}(\overline{\operatorname{vec}}(\mathcal{D}W_l))$ for $l = 1, ..., L$.

3.2 Computing the Approximate Natural Gradient Direction by TNT

We consider a tensor variable $W \in \mathbb{R}^{d_1 \times \cdots \times d_k}$ in the model and assume that $G := \mathcal{D}W \in \mathbb{R}^{d_1 \times \cdots \times d_k}$ follows a TN distribution with zero mean and covariance parameters $U_1, ..., U_k$ where $U_i \in \mathbb{R}^{d_i \times d_i}$. Thus, the Fisher matrix corresponding to W is $F_W = \mathbb{E}_{x \sim Q_x, y \sim p}[\operatorname{Var}(\overline{\operatorname{vec}}(G))] = U_1 \otimes \cdots \otimes U_k$. Let $\nabla_W \mathcal{L} \in \mathbb{R}^{d_1 \times \cdots \times d_k}$ denote the gradient of $\mathcal{L}$ w.r.t. W. The approximate NG updating direction for W is computed as

$$F_W^{-1} \overline{\operatorname{vec}}(\nabla_W \mathcal{L}) = (U_1^{-1} \otimes \cdots \otimes U_k^{-1}) \overline{\operatorname{vec}}(\nabla_W \mathcal{L}) = \overline{\operatorname{vec}} \left(\nabla_W \mathcal{L} \times_1 U_1^{-1} \times_2 \cdots \times_k U_k^{-1} \right), \quad (3)$$

where $\times_i$ $(i = 1, ..., k)$ denotes a mode-i product (see Section A in the Appendix). Note that the last equality of (3) makes use of the following proposition, which also appears in [18] (see Sec A in the Appendix for a proof):

Proposition 1. *Let $G \in \mathbb{R}^{d_1 \times \cdots \times d_k}$ and $U_i \in \mathbb{R}^{d_i \times d_i}$ for $i = 1, ..., k$. Then, we have*

$$\left(\otimes_{i=1}^{k} U_i \right) \overline{vec}(G) = \overline{vec}(G \times_1 U_1 \times_2 U_2 \cdots \times_k U_k). \quad (4)$$

To summarize, the generic Tensor-Normal Training algorithm is:

Algorithm 1 Generic Tensor-Normal Training (TNT)

Require: Given batch size m, and learning rate α
 1: **for** $t = 1, 2, \ldots$ **do**
 2:    Sample mini-batch M_t of size m
 3:    Perform a forward-backward pass over M_t to compute the mini-batch gradient
 4:    Perform another backward pass over M_t with y sampled from the predictive distribution to compute $G_l = \mathcal{D}W_l$ $(l = 1, ..., L)$ averaged across M_t
 5:    **for** $l = 1, ... L$ **do**
 6:      Estimate $\mathbb{E}[G_l^{(i)}]$ $(i = 1, ..., k_l)$ from G_l
 7:      Determine $U_1^{(l)}, ..., U_{k_l}^{(l)}$ from $\mathbb{E}[G_l^{(1)}], ..., \mathbb{E}[G_l^{(k_l)}]$
 8:      Compute the inverses of $U_1^{(l)}, ..., U_{k_l}^{(l)}$
 9:      Compute the updating direction p_l by (3)
10:      $W_l = W_l - \alpha \cdot p_l$.
11:    **end for**
12: **end for**

3.3 Identifying the Covariance Parameters of the Tensor Normal Distribution

By (2), U_i can be inferred from $\mathbb{E}[G^{(i)}]$ up to a constant multiplier. However, different sets of multipliers can generate the same F, i.e. the same distribution. This is less of a problem if one only cares about F. However, we need F^{-1} to compute the approximate natural gradient. That is, we first must choose a representation of $F = c(\tilde{U}_1 \otimes \cdots \otimes \tilde{U}_k)$ (see below), and then compute $F^{-1} = c^{-1}((\tilde{U}_1 + \epsilon I)^{-1} \otimes \cdots \otimes (\tilde{U}_k + \epsilon I)^{-1})$ with a proper choice of $\epsilon > 0$ where ϵI plays a damping role in the preconditioning matrix. In this case, different representations of F will lead to different F^{-1}.

The statistics community has proposed various representations for $\tilde{U}_i$'s. For example, [40] imposed that $c = 1$ and the first element of $\tilde{U}_i$ to be one for $i = 1, ..., k - 1$, whereas [10] imposed that $\text{tr}(\tilde{U}_i) = 1$ for $i = 1, ..., k$. Although these representations have nice statistical properties, they are not ideal from the perspective of inverting the covariance for use in a NG method in optimization.

We now describe one way to determine $\tilde{U}_1, ..., \tilde{U}_k$, and c from $\mathbb{E}[G^{(1)}], ..., \mathbb{E}[G^{(k)}]$. In particular, we first set $c = 1$, so that F^{-1} has a constant upper bound $\epsilon^{-k}I$. We then require that $\frac{\text{tr}(\tilde{U}_i)}{d_i}$ is constant w.r.t i. In other words, the average of the eigenvalues of each of the $\tilde{U}_i$'s is the same. This helps the $\tilde{U}_i$'s have similar overall "magnitude" so that a suitable ϵ can be found that works for all dimensions. Moreover, this shares some similarity with how KFAC splits the overall damping term between KFAC matrices, although KFAC adjusts the damping values whereas TNT adjusts the matrices. A bit of algebra gives the formula of

$$\tilde{U}_i = \frac{\mathbb{E}[G^{(i)}]}{c_0^{k-1} \prod_{j \neq i} d_j} \tag{5}$$

where $c_0 = \left(\frac{\text{tr}(\mathbb{E}[G^{(i)}])}{\prod_j d_j} \right)^{1/k}$.

3.4 Comparison with Shampoo and KFAC

Shampoo, proposed in [18], and later modified and extended in [3], is closely related to TNT. Both methods use a block-diagonal Kronecker-factored preconditioner based on second-order statistics of the gradient and are able to handle all sorts of tensors, and hence, can be applied to all sorts of deep neural network models, easily and seamlessly. The major differences between them are:

(i) The TN distribution cannot be directly applied to EF, which is used in Shampoo, because the empirical gradient does not have a zero mean; hence its covariance and second moment are different. It is also believed that EF does not capture as much valuable curvature information as Fisher [24].
(ii) Using the statistics $\mathbb{E}[G^{(i)}]$'s, TNT approximates the Fisher matrix as the covariance of the layer-wise sampling-based gradients assuming that they are TN distributed. On the other hand, Shampoo computes $1/2k$-th power of the statistics of each direction of the tensor-structured empirical gradient and forms a preconditioning matrix from the Kronecker product of them. It is unclear to us how to interpret statistically such a matrix other than by its connection to EF. We further note that Shampoo was developed as a Kronecker-factored approximation to the full-matrix version of AdaGrad [11], whereas TNT was developed as a NG method using a TN-distributed approximation to the Fisher matrix.
(iii) TNT computes the updating direction using the inverse (i.e. power of -1) of the Kronecker factors of the approximate Fisher matrix, whereas Shampoo uses the $-1/2k$-th power[1] of the Kronecker factors of the EF matrix.

Another method related to TNT is KFAC [32, 17], which, like TNT, uses Fisher as its preconditioning matrix. Their major differences are:

(i) KFAC develops its approximation based on the structure of the gradient and Fisher matrix for each type of layer. Admittedly, this could lead to better approximations. But it is relatively hard to implement (e.g. one need to store some intermediate variables to construct the KFAC matrices). Similarly, it is not easy to implement KFAC for batch normalization layers. Also, if new types of layers with different structures are considered, one needs to develop suitable Kronecker factorizations, i.e., KFAC matrices. On the contrary, TNT is a model-agnostic method, in the sense that, TNT can be directly applied as long as the shape of the tensor variables are specified.
(ii) Each block of TNT corresponds to a tensor variable whose shape needs to be specified, whereas each block of KFAC corresponds to all variables in a layer. For example, for a linear or convolutional layer, the KFAC block would correspond to the Fisher of both its weights and bias (and their correlation), whereas TNT would produce two blocks corresponding to the weights and bias, respectively.

In order to gain more insight into how well TNT approximates the Fisher matrix compared with other methods, we computed the cosine similarity between the direction produced by each method and that

---

[1]In [3], for autoencoder problems involving tensors of order 2, the power was set to $-\frac{\alpha}{2}$, where $\alpha \in [0, 1]$ was treated as a hyper-parameter which required tuning, and was set to $\alpha = 1$ after tuning.

Figure 1: Cosine similarity between the directions produced by the methods shown in the legend and that of a block Fisher method. The algorithms were run on a 16×16 down-scaled MNIST [25] dataset and a small feed-forward NN with layer widths 256-20-20-20-20-20-10 described in [32]. As in [32], we only show the middle four layers. For all methods, we always follow the trajectory produced by the block Fisher method.

by a block Fisher method, where each block corresponded to one layer's full Fisher matrix in the model. In our experiment, depicted in Figure 1, the cosine similarity for TNT is always around 0.7 to 0.8, which is similar to (and sometimes higher) than the structure-aware method KFAC, and always better than Shampoo. To provide more information, we also include SGD with momentum and Adam, whose similarity to the block Fisher direction is usually lower that of the second-order methods.

4   Convergence

In this section, we present results on the convergence of an idealized version of TNT that uses the actual covariance of $\mathcal{D}\theta$, rather than a statistical estimate of it (see Algorithm 2 in the Appendix). In particular, our results show that Algorithm 2, with constant batch size and decreasing step size, converges to a stationary point under some mild assumptions. For simplicity, we assume that the model only contains one tensor variable W. However, our results can be easily extended to the case of multiple tensor variables. To start with, our proofs, which are delayed to Section B in the Appendix, require the following assumptions:

Assumption 1. $\mathcal{L} : \mathbb{R}^n \to \mathbb{R}$ is continuously differentiable. $\mathcal{L}(\theta)$ is lower bounded by a real number $\mathcal{L}^{low}$ for any $\theta \in \mathbb{R}^n$. $\nabla \mathcal{L}$ is globally Lipschitz continuous with Lipschitz constant L; namely for any $\theta, \theta' \in \mathbb{R}^n$, $\|\nabla \mathcal{L}(\theta) - \nabla \mathcal{L}(\theta')\| \leqslant L\|\theta - \theta'\|$.

Assumption 2. For any iteration t, we have

$$a)\ \mathbb{E}_{\xi_t} \left[\nabla l(\theta_t, \xi_t) \right] = \nabla \mathcal{L}(\theta_t) \qquad b)\ \mathbb{E}_{\xi_t} \left[\|\nabla l(\theta_t, \xi_t) - \nabla \mathcal{L}(\theta_t)\|^2 \right] \leqslant \sigma^2$$

where $\sigma > 0$ is the noise level of the gradient estimation, and $\xi_t, t = 1, 2, \ldots$, are independent samples, and for a given t the random variable ξ_t is independent of $\{\theta_j\}_{j=1}^t$

Assumption 3. Let $G := \mathcal{D}\theta$. For any $\theta \in \mathbb{R}^n$, the norm of the Fisher matrix $F = \mathbb{E}_{x \sim Q_x, y \sim p}[\overline{vec}(G)\overline{vec}(G)^\top]$ is bounded above.

Since F represents the curvature of the KL divergence of the model's predictive distribution, Assumption 3 controls the change of predictive distribution when the model's parameters change; hence, it is a mild assumption for reasonable deep learning models. Essentially, we would like to prove that, if the Fisher matrix is upper bounded, our approximated Fisher (by TNT) is also upper bounded.

We now present two lemmas and our main theorem; see Section B in the Appendix for proofs.

Lemma 1. $\|\mathbb{E}_{x \sim Q_x, y \sim p}[G^{(i)}]\| \leqslant \left(\frac{1}{d_i} \prod_{i'=1}^k d_{i'} \right) \|\mathbb{E}_{x \sim Q_x, y \sim p}[\overline{vec}(G)\overline{vec}(G)^\top]\|, \ \forall \ i = 1, \ldots, k.$

Lemma 2. Suppose Assumption 3 holds. Let $F_{TNT} := (\tilde{U}_1 + \epsilon I) \otimes \cdots \otimes (\tilde{U}_k + \epsilon I)$ where $\tilde{U}_i$'s are defined in (5). Then, the norm of F_{TNT} is bounded both above and below.

Theorem 1. Suppose that Assumptions 1, 2, and 3 hold for $\{\theta_t\}$ generated by Algorithm 2 with batch size $m_t = m$ for all t. If we choose $\alpha_t = \frac{\kappa}{L\bar{\kappa}^2}t^{-\beta}$, with $\beta \in (0.5, 1)$, then

$$\frac{1}{N}\sum_{t=1}^N \mathbb{E}_{\{\xi_j\}_{j=1}^\infty} \left[\|\nabla \mathcal{L}(\theta_t)\|^2 \right] \leqslant \frac{2L\left(M_\mathcal{L} - \mathcal{L}^{low}\right)\bar{\kappa}^2}{\underline{\kappa}^2}N^{\beta-1} + \frac{\sigma^2}{(1-\beta)m}\left(N^{-\beta} - N^{-1}\right),$$

Table 1: Memory and per-iteration time complexity beyond that required by SGD

Name	Memory	Time (per-iteration)
TNT	$O(\sum_{i=1}^{k} d_i^2)$	$O((\frac{1}{T_1}m + \sum_{i=1}^{k} d_i)\prod_{i=1}^{k} d_i + \frac{1}{T_2}\sum_{i=1}^{k} d_i^3)$
Shampoo	$O(\sum_{i=1}^{k} d_i^2)$	$O((\sum_{i=1}^{k} d_i)\prod_{i=1}^{k} d_i + \frac{1}{T_2}\sum_{i=1}^{k} d_i^3)$
Adam-like	$O(\prod_{i=1}^{k} d_i)$	$O(\prod_{i=1}^{k} d_i)$
Newton-like	$O(\prod_{i=1}^{k} d_i^2)$	depends on specific algorithm

where N denotes the iteration number and the constant $M_{\mathcal{L}} > 0$ depends only on $\mathcal{L}$. Moreover, for a given $\delta \in (0,1)$, to guarantee that $\frac{1}{N}\sum_{t=1}^{N} \mathbb{E}_{\{\xi_j\}_{j=1}^{\infty}}\left[\|\nabla\mathcal{L}(\theta_t)\|^2\right] < \delta$, N needs to be at most $O\left(\delta^{-\frac{1}{1-\beta}}\right)$.

5   Implementation Details of TNT and Comparison on Complexity

Implementation Details of TNT. In practice, we compute $\overline{G} = \overline{\mathcal{DW}}$ averaged over a minibatch of data at every iteration, and use the value of $\overline{G}^{(i)}$ to update a moving average estimate $\widehat{G^{(i)}}$ of $\mathbb{E}[G^{(i)}]$. The extra work for these computations (as well as for updating the inverses of $\tilde{U}_i$) compared with a stochastic gradient descent method is amortized by only performing them every T_1 (and T_2) iterations, which is also the approach used in KFAC and Shampoo, and does not seems to degrade the overall performance of the TNT algorithm. Moreover, we compute $\mathbb{E}[G^{(i)}]$ using the whole dataset at the initialization point as a warm start, which is also done in our implementations of Shampoo and KFAC. See Algorithm 3 in the Appendix for the detailed implementation of TNT.

A Comparison on Memory and Per-iteration Time Complexity. To compare the memory requirements and per-iteration time complexities of different methods, we consider the case where we optimize one tensor variable of size $d_1 \times \cdots \times d_k$ using minibatches of size m at every iteration. A plain SGD method requires $O(\prod_{i=1}^{k} d_i)$ to store the model parameters and the gradient, whereas its per-iteration time complexity is $O(m\prod_{i=1}^{k} d_i)$. Table 1 lists the memory requirements and per-iteration time complexities in excess of that required by SGD for different methods.

Compared with a classic Newton-like method (e.g. BFGS), TNT (as well as Shampoo) reduces the memory requirement from $O(\prod_{i=1}^{k} d_i^2)$ to $O(\sum_{i=1}^{k} d_i^2)$, which is comparable to that of Adam-like adaptive gradient methods. In fact, if the d_i's are all equal to d and $3 \leqslant k << d$, the Kronecker-factored TNT pre-conditioning matrix requires kd^2 storage, which is less than that required by the diagonal pre-conditioners used by Adam-like methods. On the other hand, in terms of per-iteration time complexity, TNT (as well as Shampoo) only introduces a mild overhead for estimating the statistics $\mathbb{E}[G^{(i)}]$'s, inverting the pre-conditioning matrices, and computing the updating direction. Also, the first two of these operations can be amortized by only performing them every T_1 and T_2 iterations. Lastly, the extra work of $O(\frac{1}{T_1}m\prod_{i=1}^{k} d_i)$ required by TNT relative to Shampoo is due to the extra backward pass needed to estimate the true Fisher, as opposed to the EF.

Moreover, although TNT and Shampoo both incur $\frac{1}{T_2}\sum_{i=1}^{k} d_i^3$ amortized time to invert the pre-conditioning matrices, the SVD operation in Shampoo can take much more time than the matrix inverse operation in TNT, especially when the matrix size is large[2].

The per-iteration computational complexity of KFAC is more complicated because it depends on the type of the layer/variable. For linear layers, TNT and KFAC both uses two matrices, whose sizes are the number of input nodes and output nodes, respectively. For convolutional layers, TNT uses three matrices, whose sizes are the size of filter, number of input channels, and number of output channels, whereas KFAC uses two matrices whose sizes are the size of filter times number of input channels, and number of output channels. As a result, the first KFAC matrix requires much more memory. In general, the per-iteration complexity of KFAC is no less than that of TNT.

---

[2]In [3] it is shown that replacing the SVD operation by a coupled Schur-Newton method saves time for matrices of size greater than 1000×1000.

6 Experiments

In this section, we compare TNT with some SOTA second-order (KFAC, Shampoo) and first-order (SGD with momentum, Adam) methods (see Section D.1 in the Appendix on how the other methods were implemented). Our experiments were run on a machine with one V100 GPU and eight Xeon Gold 6248 CPUs using PyTorch [35]. After appropriate grid search (specified below), the algorithms were run with the best hyper-parameters and 5 different random seeds, whose mean values were plotted as the solid curves, and $\pm$std were plotted as the shaded area in Figure 2 and Figure 3. Code can be found in the supplemental material.

6.1 Optimization: Autoencoder Problems

a) MNIST autoencoder

b) FACES autoencoder

Figure 2: Optimization performance of different algorithms on two autoencoder problems

We first compared the optimization performance of each algorithm on two autoencoder problems [21] with datasets MNIST [25] and FACES[3], which were also used in [30, 32, 5, 15] as benchmarks to compare different algorithms. For each algorithm, we conducted a grid search on the learning rate and damping value based on the criteria of minimal training loss. We set the statistics update frequency $T_1 = 1$ and inverse update frequency $T_2 = 20$ for all of the second-order methods. Details of our experiment settings are listed in Section D.2 in the Appendix. From Figure 2, it is clear that TNT outperformed all other methods in terms of per-epoch progress. In terms of process time, TNT and KFAC performed the best on MNIST, whereas TNT alone preformed the best on FACES.

6.2 Generalization: Convolutional Neural Networks

a) CIFAR-10, ResNet-32

b) CIFAR-100, VGG16

Figure 3: Generalization ability of different algorithms on two CNN models. Upper row depicts the training loss whereas lower row depicts the validation classification error.

We then compared the generalization ability of each algorithm on two CNN models, namely, ResNet32 [19] (with CIFAR10 dataset [23]) and VGG16 [39] (with CIFAR100 dataset [23]). The first-order

---

[3]https://cs.nyu.edu/~roweis/data.html

methods were run for 200 epochs during which the learning rate was decayed by 0.1 every 60 epochs, whereas the second-order methods were run for 100 epochs during which the learning rate was decayed by 0.1 every 40 epochs (these settings are the same as in [43]). Moreover, as indicated in [27, 43], weight decay, different from the L_2 regularization added to the loss function, helps improve generalization across different optimizers. Thus, for each algorithm, we conducted a grid search on the initial learning rate and the weight decay factor based on the criteria of maximal validation classification accuracy. The damping parameter was set to 1e-8 for Adam (following common practice), and 0.03 for KFAC[4]. For TNT and Shampoo, we set $\epsilon = 0.01$. We set $T_1 = 10$ and $T_2 = 100$ for the three second-order methods (same as in [43]). Details of our experiment settings and a further discussion of the choice of damping hyper-parameters can be found in Section D.3 in the Appendix.

The results in Figure 3 indicate that, with a proper learning rate and weight decay factor, second-order methods and Adam have roughly the same generalization capacity as SGD with momentum, which corroborate the results in [27, 43]. In particular, TNT has a similar (and sometimes better) generalization capacity than the other methods. For example, comparing TNT with SGD-m, TNT (SGD-m) achieves 93.08% (93.06%) validation accuracy with ResNet32 on CIFAR10 and 73.33% (73.43%) validation accuracy with VGG16 on CIFAR-100, after 100 (200) epochs (see Table 3 in the Appendix for other algorithm's accuracy). Moreover, in terms of process time, TNT is roughly twice (equally) as fast as SGD-m on ResNet32/CIFAR10 in Figure 3a (on VGG16 on CIFAR-100 in Figure 3b). This illustrates the fact that TNT requires only mildly more computational efforts per-iteration than first-order methods. Also, as shown on the VGG16 model, TNT can be much faster than Shampoo and KFAC, especially on larger models. This is because Shampoo and the most recent version of KFAC, which we implemented, both use SVD (i.e. eigenvalue decomposition) to compute inverse matrices (see Section D.1.2 in the Appendix for a discussion on this), which, as discussed in Section 5, can be much slower than a direct inverse operation for large matrices.

7 Conclusion and Further Discussions

In this paper, we proposed a new second-order method, in particular, an approximate natural gradient method TNT, for training deep learning models. By approximating the Fisher matrix with the help of the tensor normal distribution, TNT only requires mild memory and computational overhead compared with first-order methods. Our experiments on various deep learning models and datasets, demonstrate that TNT provides comparable and sometimes better results than the state-of-the-art (SOTA) methods, both from the optimization and generalization perspective.

Due to space and computational resource constraints, we did not run experiments on even larger models such as ImageNet and advanced models for NLP tasks. However, the results in this paper already show very strong evidence of the potential of the TNT method. We also did not explore extending our method to a distributed setting, which has been shown to be a promising direction for second-order methods such as KFAC and Shampoo [4, 3]. Since TNT already outperforms these methods on a single machine, we expect that it will continue to do so in a distributed setting. These issues will be addressed in future research. We did not compare TNT with the SOTA Kronecker-based quasi-Newton methods [15, 36], since they are not as closely related to TNT as are Shampoo and KFAC. Their performance relative to TNT can be inferred from the comparisons here combined with those reported in [15, 36, 3]

The method proposed in this paper can be applied to any deep learning or machine learning model. If the model and/or data has a flawed designed or contains bias, this could potentially have negative societal impacts. However, this possibility is beyond the control of our work presented in this paper.

---

[4]The value of 0.03 is suggested in https://github.com/alecwangcq/KFAC-Pytorch, a github repo by the authors of [43].

References

[1] N. Agarwal, B. Bullins, X. Chen, E. Hazan, K. Singh, C. Zhang, and Y. Zhang. The case for full-matrix adaptive regularization. *arXiv preprint arXiv:1806.02958*, 2018.

[2] S.-I. Amari, H. Park, and K. Fukumizu. Adaptive method of realizing natural gradient learning for multilayer perceptrons. *Neural computation*, 12(6):1399–1409, 2000.

[3] R. Anil, V. Gupta, T. Koren, K. Regan, and Y. Singer. Scalable second order optimization for deep learning. *arXiv preprint arXiv:2002.09018*, 2021.

[4] J. Ba, R. Grosse, and J. Martens. Distributed second-order optimization using kronecker-factored approximations. 2016.

[5] A. Botev, H. Ritter, and D. Barber. Practical gauss-newton optimisation for deep learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 557–565. JMLR. org, 2017.

[6] C. G. Broyden. The convergence of a class of double-rank minimization algorithms 1. general considerations. *IMA Journal of Applied Mathematics*, 6(1):76–90, 1970.

[7] R. H. Byrd, S. L. Hansen, J. Nocedal, and Y. Singer. A stochastic quasi-newton method for large-scale optimization. *SIAM Journal on Optimization*, 26(2):1008–1031, 2016.

[8] D. Choi, C. J. Shallue, Z. Nado, J. Lee, C. J. Maddison, and G. E. Dahl. On empirical comparisons of optimizers for deep learning. *arXiv preprint arXiv:1910.05446*, 2019.

[9] A. P. Dawid. Some matrix-variate distribution theory: notational considerations and a bayesian application. *Biometrika*, 68(1):265–274, 1981.

[10] B. S. Dees and D. P. Mandic. A statistically identifiable model for tensor-valued gaussian random variables. *arXiv preprint arXiv:1911.02915*, 2019.

[11] J. Duchi, E. Hazan, and Y. Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research*, 12(Jul):2121–2159, 2011.

[12] P. Dutilleul. The mle algorithm for the matrix normal distribution. *Journal of statistical computation and simulation*, 64(2):105–123, 1999.

[13] R. Fletcher. A new approach to variable metric algorithms. *The computer journal*, 13(3):317–322, 1970.

[14] D. Goldfarb. A family of variable-metric methods derived by variational means. *Mathematics of computation*, 24(109):23–26, 1970.

[15] D. Goldfarb, Y. Ren, and A. Bahamou. Practical quasi-newton methods for training deep neural networks. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 2386–2396. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/192fc044e74dffea144f9ac5dc9f3395-Paper.pdf.

[16] R. Gower, D. Goldfarb, and P. Richtárik. Stochastic block bfgs: Squeezing more curvature out of data. In *International Conference on Machine Learning*, pages 1869–1878, 2016.

[17] R. Grosse and J. Martens. A kronecker-factored approximate fisher matrix for convolution layers. In *International Conference on Machine Learning*, pages 573–582, 2016.

[18] V. Gupta, T. Koren, and Y. Singer. Shampoo: Preconditioned stochastic tensor optimization. *arXiv preprint arXiv:1802.09568*, 2018.

[19] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[20] G. Hinton, N. Srivastava, and K. Swersky. Neural networks for machine learning lecture 6a overview of mini-batch gradient descent. *Cited on*, 14(8), 2012.

[21] G. E. Hinton and R. R. Salakhutdinov. Reducing the dimensionality of data with neural networks. *science*, 313(5786):504–507, 2006.

[22] D. Kingma and J. Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 2014.

[23] A. Krizhevsky, G. Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[24] F. Kunstner, P. Hennig, and L. Balles. Limitations of the empirical fisher approximation for natural gradient descent. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/46a558d97954d0692411c861cf78ef79-Paper.pdf.

[25] Y. LeCun, C. Cortes, and C. Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

[26] D. C. Liu and J. Nocedal. On the limited memory bfgs method for large scale optimization. *Mathematical programming*, 45(1-3):503–528, 1989.

[27] I. Loshchilov and F. Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

[28] H. Lu, K. N. Plataniotis, and A. Venetsanopoulos. *Multilinear subspace learning: dimensionality reduction of multidimensional data*. CRC press, 2013.

[29] A. M. Manceur and P. Dutilleul. Maximum likelihood estimation for the tensor normal distribution: Algorithm, minimum sample size, and empirical bias and dispersion. *Journal of Computational and Applied Mathematics*, 239:37–49, 2013.

[30] J. Martens. Deep learning via hessian-free optimization. In *ICML*, volume 27, pages 735–742, 2010.

[31] J. Martens. New insights and perspectives on the natural gradient method. *arXiv preprint arXiv:1412.1193*, 2014.

[32] J. Martens and R. Grosse. Optimizing neural networks with kronecker-factored approximate curvature. In *International conference on machine learning*, pages 2408–2417, 2015.

[33] J. Martens, J. Ba, and M. Johnson. Kronecker-factored curvature approximations for recurrent neural networks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=HyMTkQZAb.

[34] A. Mokhtari and A. Ribeiro. Res: Regularized stochastic bfgs algorithm. *IEEE Transactions on Signal Processing*, 62(23):6089–6104, 2014.

[35] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Kopf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[36] Y. Ren and D. Goldfarb. Kronecker-factored quasi-newton methods for convolutional neural networks. *arXiv preprint arXiv:2102.06737*, 2021.

[37] H. Robbins and S. Monro. A stochastic approximation method. *The annals of mathematical statistics*, pages 400–407, 1951.

[38] D. F. Shanno. Conditioning of quasi-newton methods for function minimization. *Mathematics of computation*, 24(111):647–656, 1970.

[39] K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[40] M. Singull, M. R. Ahmad, and D. von Rosen. More on the kronecker structured covariance matrix. *Communications in Statistics-Theory and Methods*, 41(13-14):2512–2523, 2012.

[41] X. Wang, S. Ma, D. Goldfarb, and W. Liu. Stochastic quasi-newton methods for nonconvex stochastic optimization. *SIAM Journal on Optimization*, 27(2):927–956, 2017.

[42] G. Zhang, J. Martens, and R. B. Grosse. Fast convergence of natural gradient descent for over-parameterized neural networks. In *Advances in Neural Information Processing Systems*, pages 8082–8093, 2019.

[43] G. Zhang, C. Wang, B. Xu, and R. Grosse. Three mechanisms of weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1lz-3Rct7.