Dance of SNN and ANN: Solving binding problem by combining spike timing and reconstructive attention

Abstract

The binding problem is one of the fundamental challenges that prevent the artificial neural network (ANNs) from a compositional understanding of the world like human perception, because disentangled and distributed representations of generative factors can interfere and lead to ambiguity when complex data with multiple objects are presented. In this paper, we propose a brain-inspired unsupervised hybrid neural network (HNN) that introduces temporal binding theory originated from neuroscience into ANNs by integrating spike timing dynamics (via spiking neural networks, SNNs) with reconstructive attention (by ANNs). Spike timing provides an additional dimension for grouping, while reconstructive feedback coordinates the spikes into temporal coherent states. Through iterative interaction of ANN and SNN, the model continuously binds multiple objects at alternative synchronous firing times in the SNN coding space. The effectiveness of the model is evaluated on five artificially generated datasets of binary images. By visualization and analysis, we demonstrate that the binding is explainable, soft, flexible, and hierarchical. Notably, the model is trained on single object datasets without explicit supervision on grouping, but can successfully bind multiple objects on test datasets, showing its compositional generalization capability. Further results show its binding ability in dynamic situations.

1 Introduction

Learning disentangled and distributed representation of generative factors of the world is believed to benefit compositional generalization, because those invariant features can be reused as symbols to build exponentially larger amounts of objects with higher complexity [1, 2, 3, 4]. However, disentangled representation can suffer from a fundamental difficulty when the inputs are composed of multiple objects. Since the features are disentangled and invariant to specific objects, multiple coexist feature representations interfere and lead to superposition catastrophe (Fig.1a). This is conceptualized as the binding problem by von der Malsburg (1981)[5, 6] and extensively debated in neuroscience and psychology literature [7]. Recently, the binding problem is also documented as a fundamental reason behind various inabilities of artificial neural networks (ANNs) like data inefficiency and limited transfer capability [3].

Segregating and representing symbol-like entities from raw data is challenging and often requires supervision [8, 9, 10, 11, 12, 13] or task-specific design[14, 15, 16, 17]. Thus, the problem is usually ignored by assuming there is only a single object of interest or mediated by using static localized binding [18, 19] at the cost of expensive computational demand. All the above methods in ANNs cannot fundamentally solve the binding problem. In contrast, slot models[3, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32] in ANNs seems to provide a promising approach, which uses various types of computational slots to inform the object label. However, current slot models are not so flexible and

dynamic as human perception partly because they require pre-defined, fixed, discrete number of slots to place a hard label to each object. Besides, the slot is usually entangled with certain dimension of features[33] and the set of features often need to be duplicated for each slot[25].

To overcome this challenge, we brought ideas from neuroscience. In neuroscience, temporal coordination is an alternative solution to support the binding in a human brain. The solution is based on spike timing correlation in a network of spiking neurons (SNNs), referred to as temporal binding theory[5] or correlation brain theory[34]. The theory assumes a hybrid code. Each neuron has its receptive field of firing rate tuned to certain features. Its spike timing can additionally be modulated to express grouping information, so that assemblies encoding features belonging to the same object fire coherently in time (Fig.1b). Grouping in time dimension has five important advantages. First, object representation based on additional dimension of time will naturally be in a common format[3], essential for systematic generalization to unseen situations or more objects. Second, unlike slot models, a single set of features are shared among all object representations. Third, the grouping information is usually continuous thus may naturally encode uncertainty about the grouping. Fourth, unlike supervised method, temporal binding is an unsupervised process, thus can support multi-stability of the grouping. Fifth, the number of groups is not needed to be explicitly pre-defined, but self-organized dynamically according to temporal coherence. Despite the virtue of temporal binding, however, how to realize spike timing correlation in various computational demanding situation remains an open and challenging problem. As far as we know, the temporal binding ability of pure-SNN models is only tested on very simple stimulus patterns[35, 36, 37, 38, 39, 40], not as complex as datasets in the field of ANNs. Besides, since the concept of spike and spike timing is incompatible with the pure-ANN framework, very few studies have incorporated the promising SNN solution into ANNs[3].

In this work, we introduce a hybrid neural network architecture (HNN), combining spike timing code within the SNN module with delayed reconstructive feedback from the ANN module (Fig.1c). First, the augmented spike coding space exploits time dimension to softly group multiple objects with a natural common format and a single set of features. Second, the denoising autoencoder (DAE)[41, 42] feedback important modulatory signals to coordinate the spike timing into coherent states. Third, the spiking dynamics induces temporal competition among multiple objects to group them at separate timings. Taken together, SNNs expand the representation space of ANNs, and ANNs provide the complex computations necessary for flexible binding. Two parts interact iteratively. Thus, we name the resulting architecture as **DASBE** (short for " **D**ance of **A**NN and **S**NN " **B**inding n**E**twork). We also provide an informal proof of the convergence of the model.

Evaluating binding is intrinsically challenging due to multi-stability [3]: scenes can be ambiguous and afford multiple groupings states, some of which are even unknown. Thus, we combine quantitative and qualitative analysis for evaluation. The former is mainly to provide a partial measure of the effectiveness based on pre-defined ground truth while the latter provide important additional proof of the binding. Specifically, (1) We quantitatively evaluate the binding in **DASBE** by the mean adjusted mutual information (AMI) score [43] between clustering result of spiking patterns and ground truth segmentation. The **DASBE** achieves more than 0.50 on all dataset and 0.80 on 3 out of 5 datasets, demonstrating its grouping capability on different types of stimuli. (2) We further visualize the spike representation and analyze the properties of the representation on the Shape dataset, showing that the grouping is continuous and based on spike synchrony, which is measured based on Victor-Purpura metric [44] of spiking patterns. Interestingly, the bound assemblies are seated on the peak of emerged gamma-like oscillations, analogous to the brain[45]. (3) Besides binding in pixel-level features, we also show that features of hierarchical levels can be bound in **DASBE**. (4) Lastly, it is demonstrated that **DASBE** can even track multiple moving objects and detect pop-up objects in the dynamic situation without explicit supervision. Taken together, we hope integrating ANNs and SNNs properly can provide new possibilities to solve binding problem in a brain-inspired manner.

2 Contribution

(1) We introduce the spiking dynamics into ANNs to solve the binding problem, so that the binding is unsupervised, soft, in a common format and keep a single set of features. (2) We introduce reconstructive attention from trainable DAE into SNNs so that the capability of temporal binding is enlarged beyond that of traditional fixed connection models (3) We develop neuroscience-inspired analysis method to evaluate and visualize the property of spiking representation in a single level or hierarchical levels, in static or dynamic situations. Gamma-like oscillation is observed.

Figure 1: (a) The binding problem. (b) Temporal binding theory. (c) Overview of **DASBE** architecture. (d) Biological relevance. (e) Single neuron model in **DASBE**. (f) Detailed information flow of **DASBE**. (i) input image (ii) SNN coding space (iii) coincidence detector (iv) Encoder (v) latent space (vi) attention map given by decoder. Feedback flow is not shown for clarity

3   Model

How can temporal binding be incorporated in ANNs to enhance the compositional representation ability of ANNs? We provide an answer by augmenting an ANN with a spike coding space (by SNNs), so that the time dimension can possibly be used to group different objects. On the contrary, how can each spiking neuron "know" its grouping companions to fire with? We provide an answer by a top-down modulation from a denoising autoencoder (DAE). Lastly, how can different object be grouped at separate timings? We provide a minimal answer with neural refractory dynamics to induce a mandatory temporal competition.

The model is composed of four parts: a spike coding space (SCS) of low-level features, an ANN encoder, a latent space of higher-level features, and an ANN decoder (Fig.1c). Four parts are connected end to end, so that the ANNs and SNNs interact dynamically in an iterative way (with delay). The biological interpretation of each part is shown in Fig.1d.

3.1   Encode binary stimulus by topographical mapping

Inspired by topographical mapping in primary cortical layers [46], the dimension of spike coding space (SCS) is set to be of the same as the input image so that pixels in the image have one-to-one correspondence to neurons in the SCS (Fig.1f(i)). The encoding is binary. $x \in \{0,1\}^N$ and $s \in \{0,1\}^N$ where x is the image stimulus and s is the spiking response of neurons in SCS.

3.2   Spike coding space (SCS)

The single neuron model in SCS (Fig.1f(ii)) is the two-compartment model of pyramidal cells [47](Fig.1e). The proximal dendrite [48] of neuron i receives binary driving signals from external

stimuli $x_i(t)$. The distal dendrite [49] of neuron i receives smooth modulatory signals $\gamma_i(t)$ from delayed top-down feedback.

Since the distal and proximal current usually interact in a non-linear manner in vivo [50, 47], the product of two terms determines the firing rate of the active neurons (not in refractory peroid).

$$\rho_i(t) = x_i \cdot \gamma_i(t), \tag{1}$$

where i is the neuron index; $\rho_i(t)$ is the firing rate. If the neuron generates a spike, $s_i = 1$, otherwise $s_i = 0$. After firing a spike, the neuron undergoes a period of refraction $\tau_{rfr} \in \mathbb{N}$. In total,

$$s_i(t) = \mathtt{Ber}(\rho_i(t)), i \in A. \tag{2}$$

where A is the set of active neurons that are not in refractory periods τ_{rfr}, and $\mathtt{Ber}()$ is a sampling step according to Bernoulli distribution with mean $\rho_i(t)$. Thus, the firing event $s_i = 1$ reflects the integrative effect of external stimuli, top-down modulation from ANNs and spiking dynamics in SNNs.

3.3   Bottom-up processing by the encoder of DAE with coincidence detectors

The spiking events in SCS are readout by coincidence detectors (CD, Fig.1f(iii)) [51], which only response to a very limited temporal window $\tau_w < 3$ with stochastic decay $\alpha_{(i,p)}^\tau \in \{0, 1\}$. The CD result is further fed to the autoencoder.

$$\tilde{x}_i(t) = \Theta(\sum_{\tau=0}^{\tau_w} \alpha_{i,p}^\tau \cdot s_i(t - \tau) - V_{th}). \tag{3}$$

Θ is a step function with threshold V_{th}, standing for the activation function of the CD; stochastic decay $\alpha_{i,p}^T \sim \mathtt{Ber}(p^\tau), p < 1$. Then the DAE encoder extracts out higher-level features of the objects in the images as the latent representation $\theta(t) = \mathrm{T}(f(\tilde{x}(t)))$. Here, f is the encoder and θ is the latent vector (Fig.1f(iv,v)). T is an additional spike sampling operation if latent representation is binary, otherwise it is just an identity map.

3.4   Delayed modulation of attention map given by the decoder of DAE

The output of DAE decoder is fed back to the pyramidal neuron in SCS through distal dendrite as top-down modulation, but with a delay period.

$$\gamma(t) = g(\theta(t - \tau_{delay})) = \hat{\gamma}(t - \tau_{delay})). \tag{4}$$

g is the decoder of DAE. $\hat{\gamma}$ refers to the attention map given by the DAE (Fig.1f(vi)) and $\tau_{delay} \in \mathbb{N}$ refers to the delay period.

For clarity, the overall binding process is shown in Algorithm 1. We identify three key properties of the **DASBE** binding process: First, the positive feed-back structure of DAE, which is termed as the "folded" DAE here, embeds each single object as its attractive fixed points.Those fixed points act as associative memories of symbol-like entities. Second, The superposed state of multiple objects is not such a fixed point. Thus, superposition is not a stable representation of "folded DAE". However, "folded" DAE may focus on one object and ignore others. Third, if augmenting "folded" DAE with refractory dynamcs of SNN, and delayed feedback, then each object becomes only transient states due to temporal competition. However, alternations of objects in turn is a possible stable trajectory. More formally,

Proposition 1. Assume the mapping $f_{DAE}: R^d \to R^d$ has learned to reconstruct vectors of single objects $\{x_n\}, x_n \in \{0, 1\}^d$ perfectly. Then, (1) (Fixed point) $\forall x_n \in \{x_n\}, x_n = f_{DAE}(x_n)$ and (2) (Attractive) Under dynamics $x(t + 1) = f_{DAE}(x(t)): \exists \delta > 0, \alpha \in (0, 1)$, s.t., $\forall \epsilon \in \{0, 1\}^d$, s.t. $\|\epsilon\| \le \delta$, then, $\|f_{DAE}(x_n - \epsilon) - x_n\| < \alpha \cdot \|(x_n - \epsilon) - x_n\|$, "$-$" is constraint in binary space of x_n

Algorithm 1 Temporal binding process in **DASBE**. The input x is a binary vector of dimension D_{image}. The attention map (attn) is a real-valued vector of dimension $(T + \tau_{delay}) \times D_{image}$. T is the length of binding process. We initialize $\text{attn}[t], t \in [-\tau_{delay}, 0]$ as independent positive samples (attn > 0) from standard Gaussian distribution $\mathcal{N}(0, I)$. Refractory variable rfr is initialized as 0. $\tau_{delay}, \tau_w, \tau_{rfr}$ are time-scale parameters. In our experiments, we set $\tau_{delay} \in [20, 60], \tau_w = 3$, $\tau_{rfr} \in [0, 15], T \approx 1000$.

1: **Input:** $\text{inputs} \in \{0, 1\}^{D_{image}}, \text{attn}[-\tau_{delay} : 0] \sim |\mathcal{N}(0, I)| \in \mathbb{R}^{\tau_{delay} \times D_{image}}$
2: **Layer params:** Norm; CD; Ber, Softmax; MLP_f, MLP_g: encoder and decoder of DAE; T: Bernuli sampling operation for binary latent space or identity map for real-valued latent space.
3:    $\text{attn}[-\tau_{delay} : 0] = \text{Norm}(\text{attn}[-\tau_{delay} : 0]);$ # normalization of initial attention map
4:    **for** $t = 0 \ldots T$
5:       $\text{context} = \text{attn}[t - \tau_{delay}];$
6:       $\text{firing\_rate} = \text{inputs} \odot \text{context} \odot (\text{rfr} == 0);$ # $\odot$: element_wise product
7:       $\text{spike}[t] \sim \text{Ber}(\text{firing\_rate});$ # Ber: sampling according to Bernoulli distribution
8:       $\text{rfr}+ = \text{spike}[t] \cdot \tau_{rfr};$ # set spiking neuron into refractory period
9:       $\text{rfr} = \max(\text{rfr} - 1, 0);$ # update refractory variable
10:      $\text{input2dae} = \text{CD}(\text{spike}[t - \tau_w : t]);$ # CD: coincidence detector
11:      $\text{encode} = \text{Softmax}(\text{MLP}_f(\text{input2dae}));$
12:      $\text{latent} = \text{T}(\text{encode});$ # latent space can be real-valued or binary
13:      $\text{attn}[t] = \text{Softmax}(\text{MLP}_g(\text{latent}));$
14:    **return** spike

Proposition 2. $\exists x' = \sum_{i=1}^{K} x_{n_i}$, $\|f_{DAE}(x') - x'\| > 0$ (superposed state is not a fixed point)

Proposition 3. Under delayed dynamics: $x(t + 1) = f_{DAE}(x(t - \tau_{delay}))$, "$x(t) \equiv x_n, t \in [0, T]$" is a possible attractive solution.

Proposition 4. Taking refractory dynamics and delayed feedback together: $x(t + 1) = f_{DAE}(\text{Ber}(x(t - \tau_{delay}) \odot I(rfr = 0))$, then "$x(t) \equiv x_n, t \in [0, T]$" is not a solution. Given $x' = \sum_{i=1}^{K} x_{n_i}$, $\exists x_{tra} : [0, T] \rightarrow \{0, 1\}^d$, $x_{tra}(t) \in \{x_{n_i}\} \cup \{\mathbf{0}\}$ is a possible stable trajectory. ($I(x)$ is an indicator function)

The proof is in the Appendix. Note that the propositions are idealized so that they cannot guarantee the convergence of the **DASBE** in practice. But the above properties are still important to heuristically support the feasibility that the **DASBE** may bind objects at alternative spike timings by incorporating ANN attention and SNN dynamics as demonstrated in experiments.

4 Experiment and results

4.1 Experiment setup

We test the binding performance on benchmark datasets[2], including Bars, Shapes, Corners, Multi-MNIST and MNIST+Shape. All these datasets are synthetic for convenience of evaluation and analysis. Further visualization are only analyzed in Shapes dataset for clarity, while results on other datasets can be found in Appendix.

4.2 Results

4.2.1 Quantitative evaluation of binding

We evaluate the **DASBE** binding performance on a list of benchmarked artificially generated datasets consisting of binary images of different complexity. For each dataset, a DAE is trained to remove salt&pepper noise on images of single objects. The best trained DAE is used for binding on images containing multiple objects. The binding quality is evaluated based on ground truth object identity.

After the simulation, we use the K-means clustering to cluster spiking neurons into different groups according to their spike train pattern. Since the ground-truth segmentation is available for generated

Table 1: AMI score

Dataset	DASBE	pure-ANN	pure-SNN
Bars	**96.5** ± 0.03	9.6±0.04	9.3±0.04
Shapes	**90.2** ± 0.07	47.5±0.04	44.7±0.15
Corners	**80.6** ± 0.08	54.2±0.15	28.5±0.08
Multi-MNIST	55.5 ± 0.06	43.0± 0.08	23.0 ± 0.11
MNIST+Shape	53.3 ± 0.26	38.3±0.03	12.9±0.08

Figure 2: Temporal binding process in SCS. (a) Evolution of averaged synchrony score and rate score in five random initial condition.(b) Relationship between clustering score (shared x-axis) and synchrony score(top y-axis), rate score(bottom y-axis) during (a). (c) firing phase of each feature neuron during simulation, indicated by color. (d) Zoomed in firing pattern of initial phase (red box) and bound phase(green box) in (c), respectively.(e) Input image . (f) Ground truth label. (g) spike recording (color dots) of each neuronal group in bound phase (green box). Shallow shadow is the firing rate of each group. Black line is the total population activity, implying gamma-like oscillation. (h) auto-correlation of spike trains(in bound phase) in each assembly. x-axis from -20 to +20, y-axis from 0 to 1 (h) correlation matrix based on Euclidean-metric of smoothed spike trains in bound phase.

datasets, we compare the clustering result and ground-truth by adjusted mutual information (AMI) [43] as a measure for temporal feature binding performance. The grouping is perfect when AMI score is 1, and around 0 when they bind feature neurons by chance. Although K-means uses Euclidean distance to compare each spike train with an averaged firing density, thus, in principle, do not explicitly evaluate timing difference, it will be shown that the clustering is actually based on spike timing code instead of firing rate difference (See Sec4.2.3 or Fig.3). The model achieves more than **0.50** on all datasets and **0.80** on 3 out of 5 datasets (5 random seeds, 6000 samples), implying their successful binding ability (Table 1).

To show the synergistic effect of combing ANN and SNN part, we reduce the hybrid **DASBE** into pure-SNN (PCNN) and pure-ANN ("folded" DAE) version as baseline. Pulse-coupled neural network (PCNN) is a traditional temporal binding model in neuroscience [52, 53, 54], and can be considered as replacing the trainable ANN(DAE) part by the fixed recurrent connections. Since original PCNN binds objects based on connectivity only, it gets into trouble when objects overlap (Bars, MNIST+Shape) or when unconnected parts compose a whole (Corners). The "folded" DAE (as defined in Proposition 3 and Appendix) can be considered as removing the spiking dynamics or

Figure 3: Synchrony score, rate score and clustering score of K-means. (a) Temporal evolution of synchrony score (b) Rate score (c) Synchrony score vs clustering score. (d) Rate score vs clustering score.

replacing the SNN coding space by a non-spiking layer. As shown in Proposition 3, such model may focus too much on one object and ignore others. As a result, both control models perform much worse than the **DASBE** (Table 1).

4.2.2 Qualitative analysis

Visualization of spike timing pattern in SCS on Shapes dataset is shown in Fig.2 c.d.g. The randomly selected image consists of a square and two triangles located at different positions (Fig.2e). Starting from random scattered firings, feature neurons responsive to the same object gradually synchronize themselves and keep out of phase to that of other objects. Object-related assemblies are seated on the peak of emergent gamma-like oscillatory population activities[45] (Fig.2 g.h).

4.2.3 Evaluating synchrony, coding scheme and convergence

To get more insights of spiking code, we develop a method to evaluate synchrony level. Here, we define synchrony as a measure of temporal coherence of spike firing in each group. Such measure requires two things. (1) a coherence measure of clusters and (2) a metric explicitly dependent on spike timing difference. In this spirit, we define synchrony score as the silhouette score [55] of clusters based on Victor-Purpura metric [44] of spike trains. The non Euclidean metric has a time-scale parameter q. At its extreme, the metric explicitly measures the spiking rate when $q \rightarrow 0$ and spiking synchrony when $q \rightarrow +\infty$ (see Appendix). Similarly, We define the rate score. It can be observed that, along the temporal binding process on Shapes, synchrony score is increased from 0.2 to 0.9, indicating the neurons converge to an object-dependent synchronous state from random guess (Fig.2a). On the contrast, rate score remains around zeros. Due to consistency between synchrony score and clustering score during the binding (Fig.2b), spike timing is indeed used by both binding process and clustering evaluation. These properties are roughly consistent across all datasets (Fig.3).

It is interesting to note that the grouping information is continuous (Fig.2 d.g). Since simulation step is much larger than the number of groups, each features is not hard-paired to a discrete slot, but "softly" bound to one or multiple limited contingent region in time dimension (2 ∼ 3 time step in our simulation and around 10 millisecond in the brain). Thus, firing dispersion can continuously encode the uncertainty of the binding in a natural way, acting like a coherence measure of grouping. The number of coherent states is not fixed by a pre-defined number K, but an emergent phenomenon during the dance of ANN and SNN parts. These are special features of temporal binding both in **DASBE** and in the brain.

4.2.4 Hierarchical binding in DASBE

Features in both the brain and ANNs has a hierarchical organization. Thus, we further study whether **DASBE** can bind hierarchical features in time. To verify it in shape dataset, we realized a spiking latent coding space (Fig.4c) in the DAE by making T a Bernoulli sampling process (Sec3.3; Alg1). To get disentangled and distributed higher-level features as studied in the original binding problem (Fig.1b), we train the DAE using an additional contrastive loss [56]. Feature neurons are identified if they invariantly response to certain generative factors (shape and position in this simple case, Fig.4a)

The results show that the shape and position, two generative factors of the shape dataset, is represented in an approximately distributed and disentangled manner in the latent spike coding space of DAE

Figure 4: Hierarchical temporal binding in **DASBE**. (a) Feature neurons whose receptive field is related to certain features and independent of opposite type of features (b) Firing activity in hidden layer, firing time indicated by grouping color. Exemplar of found feature neurons are circled. (c) **DASBE** with hierarchical spike coding space (d) Spiking recording of low-level (bottom) and high-level (top) feature neurons (e) Decoding of synchronous firing neurons in the hidden layer

Figure 5: Binding in moving situation. Black-white image is the input and color image is the clustering result of latest spikes (1 delay period). Time evolves left-to-right and up-to-bottom.

(Fig.4 a.b). After the binding converges, both the low-level features(object-related pixels neurons) and high-level features (shape and position neurons) synchronize together (Fig.4 d.e). It is interesting to note that a hierarchy tree of features of different levels can be readout by following such spiking synchrony.

4.2.5 Binding in moving situation

We further study whether the simple **DASBE** can bind in dynamic situation. To verify, we generate the moving shape dataset (Fig.5), where each object can move along a fixed direction during the experiment with a constant speed (1 pixel per delay period) . Besides, a new DAE with a recurrent hidden layer is trained to predict next step of single object. Surprisingly, the **DASBE** can not only track multiple moving objects robustly even in overlap situation but also detect pop-up objects. The result shows that temporal binding in **DASBE** is flexible since the number of groups is not fixed, and dynamic since the model can re-correct itself based on on-going situation.

5 Related work

The concept of synchrony was first illustrated in the ANNs by a complex-valued network [57]. However, this work uses simplified phase code, which was interpreted to be the phase of firing time. The dynamics of the phase is very different from spiking dynamics, which is more challenging to be realized and be integrated in ANNs. Thus, the **DASBE** opens up a more general and direct way to incorporate various temporal binding mechanisms into the deep learning framework.

Using the autoencoder to cluster objects is modelled in [2], followed by a line of recent work on compositional generative models[21, 22, 23, 24, 25, 27]. However, the binding in these works is based on discrete slots instead of continuous grouping in temporal binding. The same difference exists

for most pure-ANN models including the recurrent neural networks (RNNs) that can in principle learn sequential slots [58, 26, 22].

Some earlier works solve temporal binding problem by attractor dynamics [36, 40] that memorizes the single objects. Here, the **DASBE** is also an dynamical system as a whole. The interesting point is that the pre-trained DAE seems to parameterize the attractor dynamics and explicitly plant the fixed point of this system (Proposition1) in an equivariant and structured way. Equivarince refers to that retrieved memories can adapt itself in feature space along with the change of stimulus, instead of a discrete converged prototype. Besides, the structure of the attractor is encoded in latent layers of the DAE, like shape and position. Thus, the capacity of SNN binding model get expanded so that they can be tested beyond toy patterns.

The top-down modulation may remind us of the attention mechanisms in solving the binding problem [59, 20, 26]. It also has been argued that temporal binding and attentional binding may be the two sides of the same coin and it seems the brain uses both methods [60]. Thus, this model can be considered as bridging the temporal binding and the attention mechanism together.

6 Discussion

Can the **DASBE** provides insights to the temporal binding process in the brain? In a point of view of modeling, the model can be imagined as a kind of simplified cortical circuits (Fig.1d): The SCS composed of refractory pyramidal neurons with proximal and distal dendritic sites [47, 48, 49] mimics the layer I/II. The delayed loop of bottom-up/top-down processing[61, 62] in higher cortical layers (III, IV, V, VI) is formulated as a folded denoising autoencoder[63]. In this way, **DASBE** suggests a theory of temporal binding, which highlights the role of top-down modulation from pre-wired cortical circuits: the pre-wired cortical pathway, from thousands of years of evolution, encodes priors of prototypes of plenty of single objects. This prior is the essential cue for actively sampling the input and providing preparing signals for grouping. This prior is encoded in the decoder of DAE in **DASBE** during training. The preparing modulatory signals and driving signals act on pyramidal neurons at different dendritic locations in a non-linear manner [50]. The driving signals at the proximal sites dominate as gating signals while modulatory signals select which neuron to finally be activated [49]. The refractory period provides important competition in temporal dimension, thus firing alternates among different groups. Coincidence detectors [51] readout the synchrony events and feed to the higher cortical areas, where higher-level features are extracted. The feedback, carrying the prior cue, is delayed due to signal transmission along the pathway, of tens of milliseconds [64]. This delay period provides a window where grouping can alternate on gamma waves. Thus, the model highlights the role of the priors in pre-wired cortical circuits, and the interaction between refractory dynamics and the delay of feedback. In our model, it is the dance between SNNs and ANNs.

Note that we do not claim that the current, simple approach would compete with a dedicated segmentation algorithm or state of art ANNs models at this point. Instead, the aim in this paper is to demonstrate the spike timing binding concept, how it could be bridged into ANNs, and what is the synergistic function of HNNs in this situation. With these insights, we hope that the temporal binding concept can inspire increasingly powerful models in the future.

Lastly, we are aware that the model is so simplified that it misses some other important ingredients in the binding theory of the brain, like spike-timing dependent plasticity [65, 34]. Besides, how can a novel, unknown object be learned online[66]? How the attention in the binding relates to the predictive coding framework[67, 68]? Moreover, can **DASBE** be realized as a single mini-column in GLOM [69] to represent part-whole hierarchy? We hope that the **DASBE** variants can act as a framework to give answers to these questions in future works.

7 Conclusion

We propose **DASBE**, a hybrid model to bridge SNN binding mechanism into ANNs framework. The model flexibly binds object in alternative spike timing by dynamic interplay between DAE modulation and SNN dynamics. We evaluate the binding performance by AMI score, visualization, correlation matrix, and synchrony measure. We further explored the binding of hierarchical features and in moving situation. The results show that augmented with spiking dynamics, the model trained by single object datasets can perceive the compositional world of multiple or even moving objects.

References

[1] Irina Higgins, David Amos, David Pfau, Sebastien Racaniere, Loic Matthey, Danilo Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *arXiv preprint arXiv:1812.02230*, 2018.

[2] Klaus Greff, Rupesh Kumar Srivastava, and Jürgen Schmidhuber. Binding via reconstruction clustering. *arXiv preprint arXiv:1511.06418*, 2015.

[3] Klaus Greff, Sjoerd Van Steenkiste, and Jürgen Schmidhuber. On the binding problem in artificial neural networks. *arXiv preprint arXiv:2012.05208*, 2020.

[4] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

[5] Christoph Von der Malsburg. The what and why of binding: the modeler's perspective. *Neuron*, 24(1):95–104, 1999.

[6] Geoffrey E Hinton. Distributed representations. 1984.

[7] Jerome Feldman. The neural binding problem (s). *Cognitive neurodynamics*, 7(1):1–11, 2013.

[8] Kexin Yi, Chuang Gan, Yunzhu Li, Pushmeet Kohli, Jiajun Wu, Antonio Torralba, and Joshua B Tenenbaum. Clevrer: Collision events for video representation and reasoning. *arXiv preprint arXiv:1910.01442*, 2019.

[9] Chen Sun, Per Karlsson, Jiajun Wu, Joshua B Tenenbaum, and Kevin Murphy. Stochastic prediction of multi-agent interactions from partial observations. *arXiv preprint arXiv:1902.09641*, 2019.

[10] Nicholas Watters, Daniel Zoran, Theophane Weber, Peter Battaglia, Razvan Pascanu, and Andrea Tacchetti. Visual interaction networks: Learning a physics simulator from video. *Advances in neural information processing systems*, 30, 2017.

[11] Boris Knyazev, Harm de Vries, Cătălina Cangea, Graham W Taylor, Aaron Courville, and Eugene Belilovsky. Graph density-aware losses for novel compositions in scene graph generation. *arXiv preprint arXiv:2005.08230*, 2020.

[12] Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 580–587, 2014.

[13] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pages 2961–2969, 2017.

[14] Tejas D Kulkarni, Pushmeet Kohli, Joshua B Tenenbaum, and Vikash Mansinghka. Picture: A probabilistic programming language for scene perception. In *Proceedings of the ieee conference on computer vision and pattern recognition*, pages 4390–4399, 2015.

[15] Matthias Minderer, Chen Sun, Ruben Villegas, Forrester Cole, Kevin P Murphy, and Honglak Lee. Unsupervised learning of object structure and dynamics from videos. *Advances in Neural Information Processing Systems*, 32, 2019.

[16] Anand Gopalakrishnan, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Unsupervised object keypoint learning using local spatial predictability. *arXiv preprint arXiv:2011.12930*, 2020.

[17] Coline Devin, Pieter Abbeel, Trevor Darrell, and Sergey Levine. Deep object-centric representations for generalizable robot learning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7111–7118. IEEE, 2018.

[18] Maximilian Riesenhuber and Tomaso Poggio. Hierarchical models of object recognition in cortex. *Nature neuroscience*, 2(11):1019–1025, 1999.

[19] Yann LeCun, Bernhard Boser, John Denker, Donnie Henderson, Richard Howard, Wayne Hubbard, and Lawrence Jackel. Handwritten digit recognition with a back-propagation network. *Advances in neural information processing systems*, 2, 1989.

[20] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. *Advances in Neural Information Processing Systems*, 33:11525–11538, 2020.

[21] Klaus Greff, Raphaël Lopez Kaufman, Rishabh Kabra, Nick Watters, Christopher Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-object representation learning with iterative variational inference. In *International Conference on Machine Learning*, pages 2424–2433. PMLR, 2019.

[22] Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. Monet: Unsupervised scene decomposition and representation. *arXiv preprint arXiv:1901.11390*, 2019.

[23] Martin Engelcke, Adam R Kosiorek, Oiwi Parker Jones, and Ingmar Posner. Genesis: Generative scene inference and sampling with object-centric latent representations. *arXiv preprint arXiv:1907.13052*, 2019.

[24] Klaus Greff, Antti Rasmus, Mathias Berglund, Tele Hao, Harri Valpola, and Jürgen Schmidhuber. Tagger: Deep unsupervised perceptual grouping. *Advances in Neural Information Processing Systems*, 29, 2016.

[25] Klaus Greff, Sjoerd Van Steenkiste, and Jürgen Schmidhuber. Neural expectation maximization. *Advances in Neural Information Processing Systems*, 30, 2017.

[26] SM Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, David Szepesvari, Geoffrey E Hinton, et al. Attend, infer, repeat: Fast scene understanding with generative models. *Advances in Neural Information Processing Systems*, 29, 2016.

[27] Sjoerd Van Steenkiste, Michael Chang, Klaus Greff, and Jürgen Schmidhuber. Relational neural expectation maximization: Unsupervised discovery of objects and their interactions. *arXiv preprint arXiv:1802.10353*, 2018.

[28] Adam Kosiorek, Hyunjik Kim, Yee Whye Teh, and Ingmar Posner. Sequential attend, infer, repeat: Generative modelling of moving objects. *Advances in Neural Information Processing Systems*, 31, 2018.

[29] Karl Stelzner, Robert Peharz, and Kristian Kersting. Faster attend-infer-repeat with tractable probabilistic models. In *International Conference on Machine Learning*, pages 5966–5975. PMLR, 2019.

[30] Eric Crawford and Joelle Pineau. Spatially invariant unsupervised object detection with convolutional neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3412–3420, 2019.

[31] Jindong Jiang, Sepehr Janghorbani, Gerard De Melo, and Sungjin Ahn. Scalor: Generative world models with scalable object representations. *arXiv preprint arXiv:1910.02384*, 2019.

[32] Zhixuan Lin, Yi-Fu Wu, Skand Vishwanath Peri, Weihao Sun, Gautam Singh, Fei Deng, Jindong Jiang, and Sungjin Ahn. Space: Unsupervised object-oriented scene representation via spatial attention and decomposition. *arXiv preprint arXiv:2001.02407*, 2020.

[33] Geoffrey E Hinton, Sara Sabour, and Nicholas Frosst. Matrix capsules with em routing. In *International conference on learning representations*, 2018.

[34] Christoph von der Malsburg. The correlation theory of brain function. In *Models of neural networks*, pages 95–119. Springer, 1994.

[35] DeLiang Wang. The time dimension for scene analysis. *IEEE Transactions on Neural Networks*, 16(6):1401–1426, 2005.

[36] DeLiang Wang and Xiuwen Liu. Scene analysis by integrating primitive segmentation and associative memory. *IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics)*, 32(3):254–268, 2002.

[37] David Horn and Irit Opher. Collective excitation phenomena and their applications. *Pulsed neural networks*, pages 297–320, 1999.

[38] DeLiang Wang and David Terman. Image segmentation based on oscillatory correlation. *Neural Computation*, 9(4):805–836, 1997.

[39] G Kuntimad and Heggere S Ranganath. Perfect image segmentation using pulse coupled neural networks. *IEEE Transactions on Neural networks*, 10(3):591–598, 1999.

[40] DeLiang Wang, Joachim Buhmann, and Christoph von der Malsburg. Pattern segmentation in associative memory. *Neural Computation*, 2(1):94–106, 1990.

[41] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th international conference on Machine learning*, pages 1096–1103, 2008.

[42] Sven Behnke. Learning iterative image reconstruction in the neural abstraction pyramid. *International Journal of Computational Intelligence and Applications*, 1(04):427–438, 2001.

[43] Nguyen Xuan Vinh, Julien Epps, and James Bailey. Information theoretic measures for clusterings comparison: Variants, properties, normalization and correction for chance. *The Journal of Machine Learning Research*, 11:2837–2854, 2010.

[44] Jonathan D Victor and Keith P Purpura. Nature and precision of temporal coding in visual cortex: a metric-space analysis. *Journal of neurophysiology*, 76(2):1310–1326, 1996.

[45] Andreas K Engel and Wolf Singer. Temporal binding and the neural correlates of sensory awareness. *Trends in cognitive sciences*, 5(1):16–25, 2001.

[46] Jon H Kaas. Topographic maps are fundamental to sensory processing. *Brain research bulletin*, 44(2):107–112, 1997.

[47] Nelson Spruston. Pyramidal neurons: dendritic structure and synaptic integration. *Nature Reviews Neuroscience*, 9(3):206–221, 2008.

[48] Charles C Lee and S Murray Sherman. On the classification of pathways in the auditory midbrain, thalamus, and cortex. *Hearing research*, 276(1-2):79–87, 2011.

[49] Charles C Lee and S Murray Sherman. Drivers and modulators in the central auditory pathways. *Frontiers in neuroscience*, 4:14, 2010.

[50] S Murray Sherman and RW Guillery. On the actions that one nerve cell can have on another: distinguishing "drivers" from "modulators". *Proceedings of the National Academy of Sciences*, 95(12):7121–7126, 1998.

[51] Peter König, Andreas K Engel, and Wolf Singer. Integrator or coincidence detector? the role of the cortical neuron revisited. *Trends in neurosciences*, 19(4):130–137, 1996.

[52] Reinhard Eckhorn, Herbert J Reitboeck, MT Arndt, and P Dicke. Feature linking via synchronization among distributed assemblies: Simulations of results from cat visual cortex. *Neural computation*, 2(3):293–307, 1990.

[53] Reinhard Eckhorn, Roman Bauer, Wolfgang Jordan, Michael Brosch, Wolfgang Kruse, Matthias Munk, and HJ Reitboeck. Coherent oscillations: A mechanism of feature linking in the visual cortex? *Biological cybernetics*, 60(2):121–130, 1988.

[54] Kun Zhan, Jinhui Shi, Haibo Wang, Yuange Xie, and Qiaoqiao Li. Computational mechanisms of pulse-coupled neural networks: a comprehensive review. *Archives of Computational Methods in Engineering*, 24(3):573–588, 2017.

[55] Peter J Rousseeuw. Silhouettes: a graphical aid to the interpretation and validation of cluster analysis. *Journal of computational and applied mathematics*, 20:53–65, 1987.

[56] Phuc H Le-Khac, Graham Healy, and Alan F Smeaton. Contrastive representation learning: A framework and review. *IEEE Access*, 8:193907–193934, 2020.

[57] David P Reichert and Thomas Serre. Neuronal synchrony in complex-valued deep networks. *arXiv preprint arXiv:1312.6115*, 2013.

[58] Luming Tang, Yexiang Xue, Di Chen, and Carla Gomes. Multi-entity dependence learning with rich context via conditional variational auto-encoder. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[59] Jeremy M Wolfe. Forty years after feature integration theory: An introduction to the special issue in honor of the contributions of anne treisman. *Attention, Perception, & Psychophysics*, 82(1):1–6, 2020.

[60] Shifei Ding, Lingheng Meng, Youzhen Han, and Yu Xue. A review on feature binding theory and its functions observed in perceptual process. *Cognitive Computation*, 9(2):194–206, 2017.

[61] Sayak Bhattacharya, Matthieu BL Cauchois, Pablo A Iglesias, and Zhe Sage Chen. The impact of a closed-loop thalamocortical model on the spatiotemporal dynamics of cortical and thalamic traveling waves. *Scientific reports*, 11(1):1–19, 2021.

[62] Andreas J Keller, Morgane M Roth, and Massimo Scanziani. Feedback generates a second receptive field in neurons of the visual cortex. *Nature*, 582(7813):545–549, 2020.

[63] Rajesh PN Rao and Dana H Ballard. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. *Nature neuroscience*, 2(1):79–87, 1999.

[64] Lionel G Nowak and Jean Bullier. The timing of information transfer in the visual system. In *Extrastriate cortex in primates*, pages 205–241. Springer, 1997.

[65] Sen Song, Kenneth D Miller, and Larry F Abbott. Competitive hebbian learning through spike-timing-dependent synaptic plasticity. *Nature neuroscience*, 3(9):919–926, 2000.

[66] Amira Chalbi, Jacob Ritchie, Deokgun Park, Jungu Choi, Nicolas Roussel, Niklas Elmqvist, and Fanny Chevalier. Common fate for animated transitions in visualization. *IEEE transactions on visualization and computer graphics*, 26(1):386–396, 2019.

[67] Karl Friston. Does predictive coding have a future? *Nature neuroscience*, 21(8):1019–1021, 2018.

[68] William Lotter, Gabriel Kreiman, and David Cox. A neural network trained for prediction mimics diverse features of biological neurons and perception. *Nature Machine Intelligence*, 2(4):210–219, 2020.

[69] Geoffrey Hinton. How to represent part-whole hierarchies in a neural network. *arXiv preprint arXiv:2102.12627*, 2021.