Mask-based Latent Reconstruction for Reinforcement Learning

Abstract

For deep reinforcement learning (RL) from pixels, learning effective state representations is crucial for achieving high performance. However, in practice, limited experience and high-dimensional input prevent effective representation learning. To address this, motivated by the success of masked modeling in other research fields, we introduce mask-based reconstruction to promote state representation learning in RL. Specifically, we propose a simple yet effective self-supervised method, Mask-based Latent Reconstruction (MLR), to predict the complete state representations in the latent space from the observations with spatially and temporally masked pixels. MLR enables the better use of context information when learning state representations to make them more informative, which facilitates RL agent training. Extensive experiments show that our MLR significantly improves the sample efficiency in RL and outperforms the state-of-the-art sample-efficient RL methods on multiple continuous and discrete control benchmarks.

1 Introduction

Learning effective state representations is crucial for reinforcement learning (RL) from visual signals (where a sequence of images is usually the input to an RL network), such as in DeepMind Control Suite [43], Atari games [5], *etc*. Inspired by the success of masked pretraining in the fields of natural language processing (NLP) [11, 37, 38, 7] and computer vision (CV) [4, 21, 47], we make the first endeavor to explore the idea of mask-based reconstruction in RL.

Masked pretraining exploits the reconstruction of masked word embeddings or pixels to promote feature learning in NLP or CV. This is, in fact, not straightforwardly applicable for RL due to the following two reasons. First, RL agents learn from interactions with environments, where the experienced states vary as the policy network is updated. Intuitively, collecting additional rollouts for pretraining is often costly in real-world applications. Besides, it is challenging to learn effective state representations without the awareness of the learned policy. Second, visual signals usually have high information density, which may contain distractions and redundancies for policy learning. Thus, for RL, performing reconstruction in the original (pixel) space is not as necessary as it is in the CV or NLP domain.

Based on the analysis above, we study the masked modeling tailored to vision-based RL. We present Mask-based Latent Reconstruction (MLR), a simple yet effective self-supervised method, to better learn state representations in RL. Contrary to treating masked modeling as a pretraining task in the fields of CV and NLP, our proposed MLR is an auxiliary objective optimized together with the policy learning objectives. In this way, the coordination between representation learning and policy learning is considered within a joint training framework. Apart from this, another key difference compared to vision/language research is that we reconstruct masked pixels in the latent space instead of the input space. We take the state representations (*i.e.*, features) inferred from original unmasked frames

as the reconstruction targets. This effectively reduces unnecessary reconstruction relative to the pixel-level one and further facilitates the coordination between representation learning and policy learning because the state representations are directly optimized.

Consecutive frames are highly correlated. In MLR, we exploit this property to enable the learned state representations to be more informative, predictive and consistent over both spatial and temporal dimensions. Specifically, we randomly mask a portion of space-time cubes in the input observation (*i.e.*, video clip) sequence and reconstruct the information in the missing contents in the latent space. In this way, similar to the spatial reconstruction for images in [21, 47], MLR enhances the awareness of the agents of the global context information of the entire input observations and promotes the state representations to be predictive in both spatial and temporal dimensions. The global predictive information is encouraged to be encoded into each frame-level state representation, achieving better representation learning and further facilitating policy learning.

Not only is an effective masked modeling method proposed, but we also conduct a systematical empirical study for the practices of masking and reconstruction that are as applicable to RL as possible. First, we study the influence of masking strategies by comparing spatial masking, temporal masking and spatial-temporal masking. Second, we investigate the differences between masking and reconstructing in the pixel space and in the latent space. Finally, we study how to effectively add reconstruction supervisions in the latent space.

Our contributions are summarized below:

- We introduce the idea of enhancing representation learning by mask-based reconstruction to RL to improve the sample efficiency. We integrate the mask-based reconstruction into RL training with an auxiliary objective, obviating the need for collecting additional rollouts for pretraining and helping the coordination between representation learning and policy learning in RL.
- We propose Mask-based Latent Reconstruction (MLR), a self-supervised masked modeling method to improve the state representations for RL. Tailored to RL, we propose to randomly mask space-time cubes in the pixel space and reconstruct the information in the missing content *in the latent space*. This is shown to be effective for improving the sample efficiency on multiple continuous and discrete control benchmarks (*e.g.*, DeepMind Control Suite [43] and Atari games [5]).
- A systematical empirical study is conducted to investigate the good practices of masking and reconstructing operations in MLR for RL. This demonstrates the effectiveness of our proposed designs in MLR.

2 Related Work

2.1 Representation Learning for RL

Reinforcement learning from visual signals is of high practical value in real-world applications such as robotics, video game AI, *etc*. However, such high-dimensional observations may contain distractions or redundant information, imposing considerable challenges for RL agents to learn effective representations [41]. Many prior works address this challenge by taking advantage of self-supervised learning to promote the representation learning of the states in RL. A popular approach is to jointly learn policy learning objectives and auxiliary objectives such as pixel reconstruction [41, 50], reward prediction [23, 41], bisimulation [53], dynamics prediction [41, 13, 28, 29, 39, 52], and contrastive learning of instance discrimination [27] or (spatial -) temporal discrimination [35, 2, 42, 54, 33]. In this line, BYOL [12] style auxiliary objectives, which often cooperate with data augmentation, show promising performance [39, 52, 48, 19, 14]. Extended introduction to BYOL and the BYOL-style objectives can be found in Appendix A.3. Another feasible way of acquiring good representations is to pretrain the state encoder to learn effective representations for the original observations before policy learning. It requires additional offline sample collection or early access to the environments [20, 42, 32, 31, 40], which is not fully consistent with the principle of sample efficiency in practice. This work aims to design a more effective auxiliary task to improve the learned representations toward sample-efficient RL.

2.2 Sample-Efficient Reinforcement Learning

Collecting rollouts from the interaction with the environment is commonly costly, especially in the real world, leaving the sample efficiency of RL algorithms concerned. To improve the sample

Figure 1: The framework of the proposed MLR. We perform a random spatial-temporal masking (*i.e.*, *cube* masking) on the sequence of consecutive observations in the pixel space. The masked observations are encoded to be the latent states through an online encoder. We further introduce a predictive latent decoder to decode/predict the latent states conditioned on the corresponding action sequence and temporal positional embeddings. Our method trains the networks to reconstruct the information available in the missing contents in an appropriate *latent* space using a cosine similarity based distance metric applied between the predicted features of the reconstructed states and the target features inferred from original observations by momentum networks.

efficiency of vision-based RL (*i.e.*, RL from pixel observations), recent works design auxiliary tasks to explicitly improve the learned representations [50, 27–29, 54, 30, 39, 51, 52] or adopt data augmentation techniques, such as random crop/shift, to improve the diversity of data used for training based on collected samples [49, 26]. Besides, there are some model-based methods that learn (world) models in the pixel [55] or latent space [16–18, 51], and perform planning, imagination or policy learning based on the learned models. We focus on the auxiliary task line in this work.

2.3 Masked Language/Image Modeling

Masked language modeling (MLM) [11] and its autoregressive variants [37, 38, 7] achieve significant success in the NLP field and produce impacts in other domains. MLM masks a portion of word tokens from the input sentence and trains the model to predict the masked tokens, which has been demonstrated to be generally effective in learning language representations for various downstream tasks. For computer vision (CV) tasks, similar to MLM, masked image modeling (MIM) learns representations for images/videos by pretraining the neural networks to reconstruct masked pixels from visible ones. As an early exploration, Context Encoder [36] apply this idea to Convolutional Neural Network (CNN) model to train a CNN model with a masked region inpainting task. With the recent popularity of the Transfomer-based architectures, a series of works [9, 4, 21, 47, 46] dust off the idea of MIM and show impressive performance on learning representations for vision tasks. Inspired by MLM and MIM, we explore the masked modeling for RL to exploit the high correlation in vision data to improve agents' awareness of global-scope dynamics in learning state representations. Most importantly, *we propose to predict the masked information in the latent space*, instead of the pixel space like the aforementioned MIM works, which better coordinates the representation learning and the policy learning in RL.

3 Approach

3.1 Background

Vision-based RL aims to learn policies from pixel observations by interacting with the environment. The learning process corresponds to a partially observable Markov decision process (POMDP) [6, 24], formulated as $(\mathcal{O}, \mathcal{A}, p, r, \gamma)$, where $\mathcal{O}$, $\mathcal{A}$, p, r and γ are the observation space (*e.g.*, pixels), the action space, the transition dynamics $p = Pr(\mathbf{o}_{t+1}|\mathbf{o}_{\leq t}, \mathbf{a}_t)$, the reward function $\mathcal{O} \times \mathcal{A} \to \mathbb{R}$ and the discount factor, respectively. Following common practice [34], several consecutive observations are stacked to construct a state $\mathbf{s}_t = \{\mathbf{o}_t, \mathbf{o}_{t-1}, \cdots\}$ to convert the POMDP to an MDP [6]. And the transition dynamics and the reward function can be written as $p_t = Pr(\mathbf{s}_{t+1}|\mathbf{s}_t, \mathbf{a}_t)$ and $r_t = r(\mathbf{s}_t, \mathbf{a}_t)$, respectively. The objective of RL is to learn a policy $\pi(\mathbf{a}_t|\mathbf{s}_t)$ that maximizes the cumulative discounted return $\mathbb{E}_\pi \sum_{t=0}^{\infty} \gamma^t r_t$, where $\gamma \in [0, 1]$.

3.2 Mask-based Latent Reconstruction

Mask-based Latent Reconstruction (MLR) is an auxiliary objective to promote representation learning in vision-based RL and is generally applicable to different RL algorithms, *e.g.*, Soft Actor-Critic (SAC) and Rainbow [22]. The core idea of MLR is to facilitate state representation learning by reconstructing spatially and temporally masked pixels in the latent space. This mechanism enables the better use of context information when learning state representations, further enhancing the understanding of RL agents for visual signals. We illustrate the overall framework of MLR in Figure 1 and elaborate on it below.

Framework. In MLR, as shown in Figure 1, we mask a portion of pixels in the input observation sequence along its spatial and temporal dimensions. We encode the masked sequence and the original sequence from observations to latent states with an encoder and a momentum encoder, respectively. We perform predictive reconstruction from the states corresponding to the masked sequence by taking the states encoded from the original sequence as the target. We add reconstruction supervisions between the prediction results and the targets in the decoded latent space. The processes of *masking*, *encoding*, *decoding* and *reconstruction* are introduced in detail below.

(i) Masking. Given an observation sequence of K timesteps $\tau_K^o = \{\mathbf{o}_t, \mathbf{o}_{t+1}, \cdots, \mathbf{o}_{t+K-1}\}$ (with a slight abuse of notation, for simplicity we define the input to the deep RL networks at each timestep as $\mathbf{o}_t$) and each observation containing d RGB frames, all the observations in the sequence are stacked to be a cuboid with the shape of $K \times H \times W$ where $H \times W$ is the spatial size. Note that the actual shape is $K \times H \times W \times D$ where $D = 3d$ is the number of channels in each observation. We omit the channel dimension for simplicity. As illustrated in Figure 2, we divide the cuboid into regular non-overlapping *cubes* with the shape of $k \times h \times w$. We then randomly mask a portion of the cubes following a uniform distribution and obtain a masked observation sequence $\tilde{\tau}_K^o =$

Figure 2: Illustration of our cube masking. We divide the input observation sequence to non-overlapping cubes ($k \times h \times w$). In this example, we have $k = \frac{1}{2}K$, $h = \frac{1}{3}H$ and $w = \frac{1}{3}W$ where the observation sequence has $K = 4$ timesteps and a spatial size of $H \times W$.

$\{\tilde{\mathbf{o}}_t, \tilde{\mathbf{o}}_{t+1}, \cdots, \tilde{\mathbf{o}}_{t+K-1}\}$. Following [52], we perform stochastic image augmentation $Aug(\cdot)$ (*e.g.*, random crop and intensity) on each masked observation in $\tilde{\tau}_K^o$. The objective of MLR is to predict the state representations of the unmasked observation sequence from the masked one in the latent space.

(ii) Encoding. We adopt two encoders to learn state representations from masked observations and original observations respectively. A CNN-based encoder f is used to encode each masked observation $\tilde{\mathbf{o}}_{t+i}$ into its corresponding latent state $\tilde{\mathbf{s}}_{t+i} \in \mathbb{R}^d$. After the encoding, we obtain a sequence of the masked latent states $\tilde{\tau}_K^s = \{\tilde{\mathbf{s}}_t, \tilde{\mathbf{s}}_{t+1}, \cdots, \tilde{\mathbf{s}}_{t+K-1}\}$ for masked observations. The parameters of this encoder are updated based on gradient back-propagation in an end-to-end way. We thus call it "online" encoder. The state representations inferred from original observations are taken as the targets of subsequently described reconstruction. To make them more robust, inspired

164 by [27, 39, 52], we exploit another encoder for the encoding of original observations. This encoder,
165 called "momentum" encoder as in Figure 1, has the same architecture as the online encoder, and its
166 parameters are updated by an exponential moving average (EMA) of the online encoder weights θ_f
167 with the momentum coefficient $m \in [0, 1)$, as formulated below:

$$\bar{\theta}_f \leftarrow m\bar{\theta}_f + (1 - m)\theta_f. \tag{1}$$

168 **(iii) Decoding.** Similar to the masked modeling in the CV field, *e.g.*, [21, 47], the online encoder in
169 our MLR predicts the information of the masked contents from the unmasked contents. As opposed
170 to pixel-space reconstruction in [21, 47], MLR performs the reconstruction in the latent space since
171 pixels usually have high information density [21] which may contain distractions and redundancies
172 for the policy learning in RL. Further, we consider the fact in RL that the next state is determined
173 by the current state as well as the action and propose to utilize the actions to reduce the possible
174 ambiguity during prediction as an RL-tailored masked modeling design. To this end, we adopt a
175 transformer-based latent decoder to further infer the reconstruction results via a global message
176 passing where the actions and temporal information are exploited. Through this process, the predicted
177 information is "passed" to its corresponding state representations.

178 As shown in Figure 3, the input tokens of the latent decoder consist of both the masked state sequence
179 $\tilde{\tau}_K^s$ (*i.e.*, state tokens) and the corresponding action sequence $\tau_K^a = \{\mathbf{a}_t, \mathbf{a}_{t+1}, \cdots, \mathbf{a}_{t+K-1}\}$ (*i.e.*,
180 action tokens). Each action token is embedded as a feature vector with the same dimension as the
181 stated token using an embedding layer, through an embedding layer $Emb(\cdot)$. Following the common
182 practices in transformer-based models [45], we adopt the relative positional embeddings to encode
183 relative temporal positional information into both state and action tokens via an element-wise addition
184 denoted by "+" in the following equation (see Appendix B.1 for more details). Notably, the state and
185 action token at the same timestep $t + i$ share the same positional embedding $\mathbf{p}_{t+i} \in \mathbb{R}^d$. Thus, the
186 inputs of latent decoder can be mathematically represented as follows:

$$\mathbf{x} = [\tilde{\mathbf{s}}_t, \mathbf{a}_t, \tilde{\mathbf{s}}_{t+1}, \mathbf{a}_{t+1}, \cdots, \tilde{\mathbf{s}}_{t+K-1}, \mathbf{a}_{t+K-1}] + [\mathbf{p}_t, \mathbf{p}_t, \mathbf{p}_{t+1}, \mathbf{p}_{t+1}, \cdots, \mathbf{p}_{t+K-1}, \mathbf{p}_{t+K-1}]. \tag{2}$$

187 The input token sequence is passed through a Transformer encoder [45] consisting of L attention
188 layers. Each layer is composed of a Multi-Headed Self-Attention (MSA) layer [45], a layer normali-
189 sation (LN) [3], and multilayer perceptron (MLP) blocks. The process can be described as follows:

$$\mathbf{z}^l = \text{MSA}(\text{LN}(\mathbf{x}^l)) + \mathbf{x}^l, \tag{3}$$

$$\mathbf{x}^{l+1} = \text{MLP}(\text{LN}(\mathbf{z}^l)) + \mathbf{z}^l. \tag{4}$$

192 The output tokens of the latent decoder, *i.e.*, $\hat{\tau}_K^s = \{\hat{\mathbf{s}}_t, \hat{\mathbf{s}}_{t+1}, \cdots, \hat{\mathbf{s}}_{t+K-1}\}$, are the predictive
193 reconstruction results for the latent representations inferred from the original observations. We
194 elaborate on the reconstruction loss between the prediction results and the corresponding targets in
195 the following.

(iv) Reconstruction. Motivated by the success
196 of BYOL [12] in self-supervised learning, we
197 use an asymmetric architecture for calculating
198 the distance between the predicted/reconstructed
199 latent states and the target states, similar to
200 [39, 52]. For the outputs of the latent de-
201 coder, we use a projection head g and a pre-
202 diction head q to get the final prediction re-
203 sult $\hat{\mathbf{y}}_{t+i} = q(g(\hat{\mathbf{s}}_{t+i}))$ corresponding to $\mathbf{s}_{t+i}$.
204 For the encoded results of original observations,
205 we use a momentum-updated projection head
206 $\bar{g}$ whose weights are updated with an EMA of
207 the weights of the online projection head. These
208 two projection heads have the same architectures. The outputs of the momentum projection head $\bar{g}$,
209 *i.e.*, $\bar{\mathbf{y}}_{t+i} = \bar{g}(\bar{\mathbf{s}}_{t+i})$, are the final reconstruction targets. Here, we apply a stop-gradient operation as
210 illustrated in Figure 1 to avoid model collapse, following [12].

Figure 3: Illustration of predictive latent decoder.

212 The objective of MLR is to enforce the final prediction result $\hat{\mathbf{y}}_{t+i}$ to be as close as possible to its
213 corresponding target $\bar{\mathbf{y}}_{t+i}$. To achieve this, we design the reconstruction loss in our proposed MLR
214 by calculating the cosine similarity between $\hat{\mathbf{y}}_{t+i}$ and $\bar{\mathbf{y}}_{t+i}$, which can be formulated below:

$$\mathcal{L}_{mlr} = 1 - \frac{1}{K} \sum_{i=0}^{K-1} \frac{\hat{\mathbf{y}}_{t+i}}{\|\hat{\mathbf{y}}_{t+i}\|_2} \frac{\bar{\mathbf{y}}_{t+i}}{\|\bar{\mathbf{y}}_{t+i}\|_2}. \tag{5}$$

215 The loss $\mathcal{L}_{mlr}$ is used to update the parameters of the online networks, including encoder f, predictive
216 latent decoder ϕ, projection head g and prediction head q. Through our proposed self-supervised
217 auxiliary objective MLR, the learned state representations by the encoder will be more informative
218 and thus can further facilitate policy learning.

219 **Objective.** The proposed MLR is an auxiliary task, which is optimized together with the policy
220 learning. Thus, the overall loss function $\mathcal{L}_{total}$ for RL agent training is:

$$\mathcal{L}_{total} = \mathcal{L}_{rl} + \lambda \mathcal{L}_{mlr}, \tag{6}$$

221 where $\mathcal{L}_{rl}$ and $\mathcal{L}_{mlr}$ are the loss functions of the base RL agent (*e.g.*, SAC [15] and Rainbow [22])
222 and the proposed mask-based latent reconstruction, respectively. λ is a hyperparameter for balancing
223 the two terms. Notably, the agent of vision-based RL commonly consists of two parts, *i.e.*, the (state)
224 representation network (*i.e.*, encoder) and the policy learning network. The encoder of MLR is taken
225 as the representation network to encode observations into the state representations for RL training.
226 The latent decoder is not adopted because the unmasked observations are taken as the inputs. More
227 details can be found in Appendix B.

4 Experiment

4.1 Setup

230 **Environments and Evaluation.** We evaluate the sample efficiency of our MLR on both the con-
231 tinuous control benchmark DeepMind Control Suite (DMControl) [43] and the discrete control
232 benchmark Atari [5]. On DMControl, following the previous works [27, 49, 26, 52], we choose six
233 commonly used environments from DMControl, *i.e.*, *Finger, spin*; *Cartpole, swingup*; *Reacher, easy*;
234 *Cheetah, run*; *Walker, walk* and *Ball in cup, catch* for the evaluation. We test the performance of
235 RL agents with the mean and median scores over 10 episodes at 100k and 500k environment steps,
236 referred to as **DMControl-100k** and **DMControl-500k** benchmarks, respectively. The score of each
237 environment ranges from 0 to 1000 [43]. For discrete control, we test agents on the **Atari-100k** bench-
238 mark [55, 44, 25, 27] which contains 26 Atari games and allows the agents 100k interaction steps
239 (*i.e.*, 400k environment steps with action repeat of 4) for training. Human-normalized score (HNS) [1]
240 is used to measure the performance on each game. Considering the high variance of the scores on
241 this benchmark, we test each run over 100 episodes [39]. To achieve a more rigorous evaluation on
242 high-variance benchmarks such as Atari-100k with a few runs, recent work Rliable [1] systematically
243 studies the evaluation bias issue in deep RL and recommends robust and efficient aggregate metrics
244 to evaluate the overall performance (across all tasks and runs), *e.g.*, interquartile-mean (IQM) and
245 optimality gap (OG) [2], with percentile confidence intervals (CIs, estimated by the percentile bootstrap
246 with stratified sampling). We follow the recommendation and report the aggregate metrics on the
247 Atari-100k benchmark with 95% CIs.

248 **Implementation.** SAC [15] and Rainbow [22] are taken as the base continuous-control agent and
249 discrete-control agent, respectively (see Appendix A for the details of the two algorithms). In our
250 experiments, we denote the base agents trained only by RL loss $\mathcal{L}_{rl}$ (as in Equation 6) as *Baseline*,
251 while denoting the models of applying our proposed MLR to the base agents as *MLR* for the brevity.
252 Note that compared to naive SAC or Rainbow on pixels, our *Baseline* additionally adopts data
253 augmentation (random crop and random intensity). This practice follows prior works [26, 49] which
254 uncovers that applying proper data augmentation can significantly improve the sample efficiency of
255 SAC or Rainbow. As shown in Equation 6, we set a weight λ to balance $\mathcal{L}_{rl}$ and $\mathcal{L}_{mlr}$ so that the
256 gradients of these two loss items lie in a similar range and empirically find $\lambda = 1$ works well in most
257 environments. In MLR, by default, we set the length of a sampled trajectory K to 16 and mask ratio
258 η to 50%. We set the size of the masked cube ($k \times h \times w$) to $8 \times 10 \times 10$ on most DMControl tasks
259 and $8 \times 12 \times 12$ on the Atari games. More implementation details can be found in Appendix B.

4.2 Comparison with State-of-the-Arts

261 **DMControl.** We compare our proposed MLR with the state-of-the-art (SOTA) sample-efficient RL
262 methods proposed for continuous control, including PlaNet [16], Dreamer [17], SAC+AE [50], SLAC

---

[1]HNS is calculated by $\frac{S_A - S_R}{S_H - S_R}$, where S_A, S_R and S_H are the scores of the agent, random play and the expert human, respectively.

[2]IQM discards the top and bottom 25% of the runs and calculates the mean score of the remaining 50% runs. OG is the amount by which the agent fails to meet a minimum score of the default human-level performance.

Table 1: Comparison results (mean ± std) on the DMControl-100k and DMControl-500k benchmarks. Our method augments *Baseline* with the proposed MLR objective (denoted as *MLR*).

100k Step Scores	PlaNet	Dreamer	SAC+AE	SLAC	CURL	DrQ	PlayVirtual	Baseline	MLR
Finger, spin	136 ± 216	341 ± 70	740 ± 64	693 ± 141	767 ± 56	901 ± 104	**915 ± 49**	853 ± 112	907 ± 58
Cartpole, swingup	297 ± 39	326 ± 27	311 ± 11	-	582 ± 146	759 ± 92	**816 ± 36**	784 ± 63	806 ± 48
Reacher, easy	20 ± 50	314 ± 155	274 ± 14	-	538 ± 233	601 ± 213	785 ± 142	593 ± 118	**866 ± 103**
Cheetah, run	138 ± 88	235 ± 137	267 ± 24	319 ± 56	299 ± 48	344 ± 67	474 ± 50	399 ± 80	**482 ± 38**
Walker, walk	224 ± 48	277 ± 12	394 ± 22	361 ± 73	403 ± 24	612 ± 164	460 ± 173	424 ± 281	**643 ± 114**
Ball in cup, catch	0 ± 0	246 ± 174	391 ± 82	512 ± 110	769 ± 43	913 ± 53	926 ± 31	648 ± 287	**933 ± 16**
Mean	135.8	289.8	396.2	471.3	559.7	688.3	729.3	616.8	**772.8**
Median	137.0	295.5	351.0	436.5	560.0	685.5	800.5	620.5	**836.0**
500k Step Scores									
Finger, spin	561 ± 284	796 ± 183	884 ± 128	673 ± 92	926 ± 45	938 ± 103	963 ± 40	944 ± 97	**973 ± 31**
Cartpole, swingup	475 ± 71	762 ± 27	735 ± 63	-	841 ± 45	868 ± 10	865 ± 11	871 ± 4	**872 ± 5**
Reacher, easy	210 ± 390	793 ± 164	627 ± 58	-	929 ± 44	942 ± 71	942 ± 66	943 ± 52	**957 ± 41**
Cheetah, run	305 ± 131	570 ± 253	550 ± 34	640 ± 19	518 ± 28	660 ± 96	**719 ± 51**	602 ± 67	674 ± 37
Walker, walk	351 ± 58	897 ± 49	847 ± 48	842 ± 51	902 ± 43	921 ± 4575	928 ± 30	818 ± 263	**939 ± 10**
Ball in cup, catch	460 ± 380	879 ± 87	794 ± 58	852 ± 71	959 ± 27	963 ± 9	**967 ± 5**	960 ± 10	964 ± 14
Mean	393.7	782.8	739.5	751.8	845.8	882.0	**897.3**	856.3	896.5
Median	405.5	794.5	764.5	757.5	914.0	929.5	935.0	907.0	**948.0**

Figure 4: Comparison results on Atari-100k. Aggregate metrics (IQM and optimality gap (OG)) [1] with 95% confidence intervals (CIs) are used for the evaluation. Higher IQM and lower OG are better.

[28], CURL [27], DrQ [49] and PlayVirtual [52]. The comparison results are shown in Table 1, and all results are averaged over 10 random seeds. We can observe that: (i) MLR significantly improves *Baseline* in both DMControl-100k and DMControl-500k, and achieves consistent gains relative to *Baseline* across all environments. It is worthy to mention that, for the DMControl-100k, our proposed method outperforms *Baseline* by **25.3%** and **34.7%** in mean and median scores, respectively. This demonstrates the superiority of MLR in improving the sample efficiency of RL algorithms. (ii) The RL agent equipped with MLR outperforms most state-of-the-art methods on DMControl-100k and DMControl-500k. Specifically, our method surpasses the best previous method (*i.e.*, PlayVirtual) by 43.5 and 35.5 respectively on mean and median scores on DMControl-100k. Our method also delivers the best median score and reaches a comparable mean score with the strongest SOTA method on DMControl-500k.

Atari-100k. We further compare MLR with the SOTA model-free methods for discrete control, including DER [44], OTR [25], CURL [27], DrQ [49], DrQ(ϵ) (DrQ using the ϵ-greedy parameters in [8]) , SPR [39] and PlayVirtual [52]. These methods and our MLR for Atari are all based on Rainbow [22]. The Atari-100k results are shown in Figure 4. MLR achieves an interquartile-mean (IQM) score of 0.432, which is **28.2%** higher than SPR (IQM: 0.337) and **15.5%** higher than PlayVirtual (IQM: 0.374). This indicates that MLR has the highest sample efficiency overall. For the optimality gap (OG) metric, MLR reaches an OG of 0.522 better than SPR (OG: 0.577) and PlayVirtual (OG: 0.558), showing that our method performs closer to the desired target, *i.e.*, human-level performance. The full scores of MLR (over 3 random seeds) across the 26 Atari games and more comparisons and analysis can be found in Appendix C.

4.3 Ablation Study

In this section, we investigate the effectiveness of our MLR auxiliary objective, the impact of masking methods and the model/architecture design. Unless otherwise specified, we conduct the ablation studies on the DMControl-100k benchmark and run each model for 5 random seeds.

Table 2: Ablation study of masking strategy and reconstruction target. We compare three masking strategies: spatial masking (*MLR-S*), temporal masking (*MLR-T*) and spatial-temporal masking (*MLR*), and two reconstruction targets: original pixels (denoted as *MLR-Pixel*) and momentum projections in the latent space (*i.e.*, *MLR*).

Environment	Baseline	MLR-S	MLR-T	MLR-Pixel	MLR
Finger, spin	822 ± 146	$\mathbf{919 \pm 55}$	787 ± 139	782 ± 95	907 ± 69
Cartpole, swingup	782 ± 74	665 ± 118	$\mathbf{829 \pm 33}$	803 ± 91	791 ± 50
Reacher, easy	557 ± 137	848 ± 82	745 ± 84	787 ± 136	$\mathbf{875 \pm 92}$
Cheetah, run	438 ± 33	449 ± 46	443 ± 43	346 ± 84	$\mathbf{495 \pm 13}$
Walker, walk	414 ± 310	556 ± 189	393 ± 202	490 ± 216	$\mathbf{597 \pm 102}$
Ball in cup, catch	669 ± 310	927 ± 6	934 ± 29	675 ± 292	$\mathbf{939 \pm 9}$
Mean	613.7	727.3	688.5	647.2	**767.3**
Median	613.0	756.5	766.0	728.5	**833.0**

Effectiveness evaluation. Besides the comparison with SOTA methods, we demonstrate the effectiveness of our proposed MLR by studying its improvements compared to our *Baseline*. The numerical results are presented in Table 1, while the curves of test performance during the training process are given in Appendix C. Both numerical results and test performance curves can demonstrate that our method obviously outperforms *Baseline* across different environments thanks to more informative representations learned by MLR.

Masking strategy. We compare three design choices of the masking operation: (i) *Spatial masking* (denoted as *MLR-S*): we randomly mask *patches* for each frame independently. (ii) *Temporal masking* (denoted as *MLR-T*): we divide the input observation sequence into multiple segments along the temporal dimension and mask out a portion of segments randomly. (Here, the segment length is set to be equal to the temporal length of cube, *i.e.*, k.) And (iii) *Spatial-temporal masking* (also referred to as "cube masking"): as aforementioned and illustrated in Figure 2, we rasterize the observation sequence into non-overlapping cubes and randomly mask a portion of them. Except for the differences described above, other configurations for masking remain the same as our proposed spatial-temporal (*i.e.*, cube) masking. From the results in Table 2, we have the following observations: (i) All three masking strategies (*i.e.*, *MLR-S*, *MLR-T* and *MLR*) achieve mean score improvements compared to *Baseline* by **18.5%**, **12.2%** and **25.0%**, respectively, and achieve median score improvements by **23.4%**, **25.0%** and **35.9%**, respectively. This demonstrates the effectiveness of the core idea of introducing mask-based reconstruction to improve the representation learning of RL. (ii) Spatial-temporal masking is the most effective strategy over these three design choices. This strategy matches better with the nature of video data due to its spatial-temporal continuity in masking. It encourages the state representations to be more predictive and consistent along the spatial and temporal dimensions, thus facilitating the policy learning in RL.

Reconstruction target. In masked language/image modeling, reconstruction/prediction is commonly performed in the original signal space, such as word embeddings or RGB pixels. To study the influence of the reconstruction targets for the task of RL, we compare two different reconstruction spaces: (i) *Pixel space reconstruction* (denoted as *MLR-Pixel*): we predict the masked contents directly by reconstructing original pixels, like the practices in CV and NLP domains; (ii) *Latent space reconstruction* (*i.e.*, *MLR*): we reconstruct the state representations (*i.e.*, features) of original observations from masked observations, as we proposed in MLR. Table 2 shows the comparison results. The reconstruction in the latent space is superior to that in the pixel space in improving sample efficiency. As discussed in the preceding sections, vision data might contain distractions and redundancies for policy learning, making the pixel-level reconstruction unnecessary. Besides, latent space reconstruction is more conducive to the coordination between the representation learning and the policy learning in RL, because the state representations are directly optimized.

Mask ratio. In recent works of masked image modeling [21, 47], the mask ratio is found to be crucial for the final performance. We study the influences of different masking ratios on sample efficiency in Figure 5 (with 3 random seeds) and find that the ratio of 50% is an appropriate choice for our proposed MLR. An over-small value of this ratio could not eliminate redundancy, making the objective easy to reach by extrapolation from neighboring contents that are

Figure 5: Ablation study of mask ratio.

free of capturing and understanding semantics from visual signals. An over-large value leaves too few contexts for achieving the reconstruction goal. As discussed in [21, 47], the choice of this ratio varies for different modalities and depends on the information density of the input signals.

Action token. We study the contributions of action tokens used for the latent decoder in Figure 1 by discarding it from our proposed framework. The results are given in Table 3. Intuitively, prediction only from visual signals is of more or less ambiguity. Exploiting action tokens benefits by reducing such ambiguity so that the gradients of less uncertainty can be obtained for updating the encoder.

Table 3: Ablation studies on action token, masking features and momentum decoder. *MLR w.o. ActTok* denotes removing the action tokens in the input tokens of the predictive latent decoder. *MLR-F* indicates performing masking on convolutuional feature maps. And *MLR-MoDec* indicates adding a momentum predictive latent decoder in the target networks.

Environment	Baseline	MLR w.o. ActTok	MLR-F	MLR-MoDec	MLR
Finger, spin	822 ± 146	832 ± 46	828 ± 143	843 ± 135	$\mathbf{907 \pm 69}$
Cartpole, swingup	782 ± 74	$\mathbf{816 \pm 27}$	789 ± 55	766 ± 88	791 ± 50
Reacher, easy	557 ± 137	835 ± 51	753 ± 159	800 ± 49	$\mathbf{875 \pm 92}$
Cheetah, run	438 ± 33	433 ± 72	477 ± 38	470 ± 12	$\mathbf{495 \pm 13}$
Walker, walk	414 ± 310	412 ± 210	$\mathbf{673 \pm 33}$	571 ± 152	597 ± 102
Ball in cup, catch	669 ± 310	837 ± 114	843 ± 119	788 ± 155	$\mathbf{939 \pm 9}$
Mean	613.7	694.2	727.2	706.4	**767.3**
Median	613.0	824.2	771.0	777.0	**833.0**

Masking features. We compare "masking pixels" and "masking features" in Table 3. Masking features (denoted by *MLR-F*) does not perform equally well compared with masking pixels as proposed in MLR, but it still achieves significant improvements to *Baseline*.

Why not use a latent decoder for targets? We have tried to add a momentum-updated latent decoder for obtaining the target states $\bar{s}_{t+i}$ as illustrated in Figure 1. The results in Table 3 show that adding the momentum decoder leads to performance drops. Since there is no information prediction for the state representation learning from the original observation sequence without masking, we do not need to refine the implicitly predicted information like that in the outputs $\hat{s}_{t+i}$ of the online encoder.

Decoder depth. We analyze the influence of using Transformer-based latent decoders of different depths. The experimental result is shown in Appendix C. Generally, deeper latent decoders lead to worse sample efficiency with lower mean and median scores.

Similarity loss. We compare models using two kinds of similarity metrics to measure the distance in the latent space and observe that using cosine similarity loss is better than using mean squared error (MSE) loss. The results and analysis can be found in Appendix C.

Projection and prediction heads. Previous works [12, 39, 10] have shown that in self-supervised learning, supervising the feature representations in the projected space via the projection/prediction heads is often better than in the original feature space. We investigate the effect of the two heads and find that both improve agent performance (see Appendix C).

Sequence length and cube size. These two factors can be viewed as hyperparameters. Their corresponding experimental analysis and results are in Appendix C.

5 Conclusion

In this work, we make the first effort to introduce the mask-based reconstruction to RL for facilitating policy learning by improving the learned state representations. We propose MLR, a simple yet effective self-supervised auxiliary objective to reconstruct the masked information in the latent space. In this way, the learned state representations are encouraged to include richer and more informative features. Extensive experiments demonstrate the effectiveness of MLR and show that MLR achieves the state-of-the-art performance on both DeepMind Control and Atari benchmarks. We conduct a detailed ablation study for the proposed designs in MLR and analyze their differences from that in NLP and CV domains. We hope our proposed method can inspire further research for vision-based RL from the perspective of improving representation learning. Moreover, the masked latent reconstruction concept is also worthy of being explored and extended in computer vision and natural language processing. We are looking forward to seeing more mutual promotion between different research fields.

References

[1] Agarwal, R., Schwarzer, M., Castro, P. S., Courville, A. C., and Bellemare, M. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems*, 34, 2021.

[2] Anand, A., Racah, E., Ozair, S., Bengio, Y., Côté, M.-A., and Hjelm, R. D. Unsupervised state representation learning in atari. In *Advances in Neural Information Processing Systems*, 2019.

[3] Ba, J. L., Kiros, J. R., and Hinton, G. E. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[4] Bao, H., Dong, L., Piao, S., and Wei, F. Beit: Bert pre-training of image transformers. In *International Conference on Learning Representations*, 2021.

[5] Bellemare, M. G., Naddaf, Y., Veness, J., and Bowling, M. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013.

[6] Bellman, R. A markovian decision process. *Journal of mathematics and mechanics*, 6(5): 679–684, 1957.

[7] Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

[8] Castro, P. S., Moitra, S., Gelada, C., Kumar, S., and Bellemare, M. G. Dopamine: A research framework for deep reinforcement learning. *arXiv preprint arXiv:1812.06110*, 2018.

[9] Chen, M., Radford, A., Child, R., Wu, J., Jun, H., Luan, D., and Sutskever, I. Generative pretraining from pixels. In *International Conference on Machine Learning*, pp. 1691–1703. PMLR, 2020.

[10] Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pp. 1597–1607. PMLR, 2020.

[11] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[12] Grill, J.-B., Strub, F., Altché, F., Tallec, C., Richemond, P., Buchatskaya, E., Doersch, C., Avila Pires, B., Guo, Z., Gheshlaghi Azar, M., Piot, B., kavukcuoglu, k., Munos, R., and Valko, M. Bootstrap your own latent - a new approach to self-supervised learning. In *Advances in Neural Information Processing Systems*, 2020.

[13] Guo, Z. D., Pires, B. A., Piot, B., Grill, J.-B., Altché, F., Munos, R., and Azar, M. G. Bootstrap latent-predictive representations for multitask reinforcement learning. In *International Conference on Machine Learning*, pp. 3875–3886. PMLR, 2020.

[14] Guo, Z. D., Thakoor, S., Pîslar, M., Pires, B. A., Altché, F., Tallec, C., Saade, A., Calandriello, D., Grill, J.-B., Tang, Y., et al. Byol-explore: Exploration by bootstrapped prediction. *arXiv preprint arXiv:2206.08332*, 2022.

[15] Haarnoja, T., Zhou, A., Hartikainen, K., Tucker, G., Ha, S., Tan, J., Kumar, V., Zhu, H., Gupta, A., Abbeel, P., et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[16] Hafner, D., Lillicrap, T., Fischer, I., Villegas, R., Ha, D., Lee, H., and Davidson, J. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, pp. 2555–2565. PMLR, 2019.

[17] Hafner, D., Lillicrap, T., Ba, J., and Norouzi, M. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020.

[18] Hafner, D., Lillicrap, T., Norouzi, M., and Ba, J. Mastering atari with discrete world models. *arXiv preprint arXiv:2010.02193*, 2020.

[19] Hansen, N. and Wang, X. Generalization in reinforcement learning by soft data augmentation. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 13611–13617. IEEE, 2021.

[20] Hansen, S., Dabney, W., Barreto, A., Van de Wiele, T., Warde-Farley, D., and Mnih, V. Fast task inference with variational intrinsic successor features. *arXiv preprint arXiv:1906.05030*, 2019.

[21] He, K., Chen, X., Xie, S., Li, Y., Dollár, P., and Girshick, R. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

[22] Hessel, M., Modayil, J., Van Hasselt, H., Schaul, T., Ostrovski, G., Dabney, W., Horgan, D., Piot, B., Azar, M., and Silver, D. Rainbow: Combining improvements in deep reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[23] Jaderberg, M., Mnih, V., Czarnecki, W. M., Schaul, T., Leibo, J. Z., Silver, D., and Kavukcuoglu, K. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

[24] Kaelbling, L. P., Littman, M. L., and Cassandra, A. R. Planning and acting in partially observable stochastic domains. *Artificial intelligence*, 101(1-2):99–134, 1998.

[25] Kielak, K. Do recent advancements in model-based deep reinforcement learning really improve data efficiency? *arXiv preprint arXiv:2003.10181*, 2020.

[26] Laskin, M., Lee, K., Stooke, A., Pinto, L., Abbeel, P., and Srinivas, A. Reinforcement learning with augmented data. In *Advances in Neural Information Processing Systems*, 2020.

[27] Laskin, M., Srinivas, A., and Abbeel, P. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, pp. 5639–5650. PMLR, 2020.

[28] Lee, A. X., Nagabandi, A., Abbeel, P., and Levine, S. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. In *Advances in Neural Information Processing Systems*, 2020.

[29] Lee, K.-H., Fischer, I., Liu, A., Guo, Y., Lee, H., Canny, J., and Guadarrama, S. Predictive information accelerates learning in RL. *arXiv preprint arXiv:2007.12401*, 2020.

[30] Liu, G., Zhang, C., Zhao, L., Qin, T., Zhu, J., Jian, L., Yu, N., and Liu, T.-Y. Return-based contrastive representation learning for reinforcement learning. In *International Conference on Learning Representations*, 2021.

[31] Liu, H. and Abbeel, P. Aps: Active pretraining with successor features. In *International Conference on Machine Learning*, pp. 6736–6747. PMLR, 2021.

[32] Liu, H. and Abbeel, P. Behavior from the void: Unsupervised active pre-training. *Advances in Neural Information Processing Systems*, 34:18459–18473, 2021.

[33] Mazoure, B., Tachet des Combes, R., DOAN, T. L., Bachman, P., and Hjelm, R. D. Deep reinforcement and infomax learning. In *Advances in Neural Information Processing Systems*, 2020.

[34] Mnih, V., Kavukcuoglu, K., Silver, D., Graves, A., Antonoglou, I., Wierstra, D., and Riedmiller, M. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

[35] Oord, A. v. d., Li, Y., and Vinyals, O. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[36] Pathak, D., Krahenbuhl, P., Donahue, J., Darrell, T., and Efros, A. A. Context encoders: Feature learning by inpainting. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2536–2544, 2016.

[37] Radford, A., Narasimhan, K., Salimans, T., and Sutskever, I. Improving language understanding by generative pre-training. 2018.

[38] Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., Sutskever, I., et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

[39] Schwarzer, M., Anand, A., Goel, R., Hjelm, R. D., Courville, A., and Bachman, P. Data-efficient reinforcement learning with self-predictive representations. In *International Conference on Learning Representations*, 2021.

[40] Schwarzer, M., Rajkumar, N., Noukhovitch, M., Anand, A., Charlin, L., Hjelm, R. D., Bachman, P., and Courville, A. C. Pretraining representations for data-efficient reinforcement learning. *Advances in Neural Information Processing Systems*, 34:12686–12699, 2021.

[41] Shelhamer, E., Mahmoudieh, P., Argus, M., and Darrell, T. Loss is its own reward: Self-supervision for reinforcement learning. *ArXiv*, abs/1612.07307, 2017.

[42] Stooke, A., Lee, K., Abbeel, P., and Laskin, M. Decoupling representation learning from reinforcement learning. *arXiv preprint arXiv:2009.08319*, 2020.

[43] Tassa, Y., Doron, Y., Muldal, A., Erez, T., Li, Y., Casas, D. d. L., Budden, D., Abdolmaleki, A., Merel, J., Lefrancq, A., et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

[44] van Hasselt, H. P., Hessel, M., and Aslanides, J. When to use parametric models in reinforcement learning? In *Advances in Neural Information Processing Systems*, 2019.

[45] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

[46] Wei, C., Fan, H., Xie, S., Wu, C.-Y., Yuille, A., and Feichtenhofer, C. Masked feature prediction for self-supervised visual pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14668–14678, 2022.

[47] Xie, Z., Zhang, Z., Cao, Y., Lin, Y., Bao, J., Yao, Z., Dai, Q., and Hu, H. Simmim: A simple framework for masked image modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9653–9663, 2022.

[48] Yarats, D., Fergus, R., Lazaric, A., and Pinto, L. Reinforcement learning with prototypical representations. In *International Conference on Machine Learning*, pp. 11920–11931. PMLR, 2021.

[49] Yarats, D., Kostrikov, I., and Fergus, R. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*, 2021.

[50] Yarats, D., Zhang, A., Kostrikov, I., Amos, B., Pineau, J., and Fergus, R. Improving sample efficiency in model-free reinforcement learning from images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 10674–10681, 2021.

[51] Ye, W., Liu, S., Kurutach, T., Abbeel, P., and Gao, Y. Mastering atari games with limited data. *Advances in Neural Information Processing Systems*, 34, 2021.

[52] Yu, T., Lan, C., Zeng, W., Feng, M., Zhang, Z., and Chen, Z. Playvirtual: Augmenting cycle-consistent virtual trajectories for reinforcement learning. In *Advances in Neural Information Processing Systems*, 2021.

[53] Zhang, A., McAllister, R. T., Calandra, R., Gal, Y., and Levine, S. Learning invariant representations for reinforcement learning without reconstruction. In *International Conference on Learning Representations*, 2021.

[54] Zhu, J., Xia, Y., Wu, L., Deng, J., Zhou, W., Qin, T., and Li, H. Masked contrastive representation learning for reinforcement learning. *arXiv preprint arXiv:2010.07470*, 2020.

[55] Łukasz Kaiser, Babaeizadeh, M., Miłos, P., Osiński, B., Campbell, R. H., Czechowski, K., Erhan, D., Finn, C., Kozakowski, P., Levine, S., Mohiuddin, A., Sepassi, R., Tucker, G., and Michalewski, H. Model based reinforcement learning for atari. In *International Conference on Learning Representations*, 2020.