Multilingual evaluation of image captioning: How far can we get with CLIP models?

Abstract

The evaluation of image captions, looking at both linguistic fluency and semantic correspondence to visual contents, has witnessed a significant effort. Still, despite advancements such as the CLIPScore metric, multilingual captioning evaluation has remained relatively unexplored. This work evaluates CLIPScore in multilingual captioning, demonstrating the benefits of finetuning models with diverse data. To address the lack of multilingual test data, we consider two different strategies: (1) using machine-translated datasets with human judgements, and (2) re-purposing multilingual datasets that target semantic inference and reasoning. Our results highlight the potential of finetuned multilingual models to generalize across languages and to improve their ability to handle complex cases. Tests with machine-translated data show that multilingual CLIPScore can maintain a high correlation with human judgements across different languages, and additional tests with natively multilingual and multicultural data further attest to the high-quality assessments.

1 Introduction

Computer-generated image captions are nowadays commonly used as descriptive annotations. The Image Captioning (IC) task has been extensively studied, including in multilingual settings, with many recent approaches combining established vision encoders with large language model decoders (Ramos et al., 2023b,a; Yang et al., 2023; Geigle et al., 2023; Ramos et al., 2024). The automatic evaluation of captions, accounting for linguistic fluency and alignment with visual contents, has also witnessed a significant effort. Approaches like CLIPScore (Hessel et al., 2021) have been proposed to evaluate captions through cosine similarity between image and text embeddings, leveraging large-scale pre-trained vision and language models and achieving high correlations with human judgments. Still, despite the many recent advancements, most approaches are English-centric, while multilingual image captioning evaluation has remained relatively unexplored, and lacking in resources.

This work explores the use of CLIPScore in multilingual captioning, evaluating different CLIP models under various settings. Given the lack of available benchmarks for the evaluation of multilingual captioning metrics, we propose two different evaluation strategies: (1) using a combination of Machine Translation (MT) and Quality Estimation (QE) models to obtain high-quality multilingual data from English-centric benchmarks, and (2) re-purposing multilingual benchmarks originally designed for evaluation of the semantic inference and reasoning capabilities of vision-language models.

Through extensive experiments, we show that multilingual CLIP models achieve comparable or even better performance on English benchmarks, while allowing for multilingual assessments. We also propose a multilingual fine-tuning strategy for CLIPScore, that allows to account for linguistic and cultural diversity while learning from human judgements, resulting in further performance improvements. Performance generally increases according to model size, and larger models, trained on more data, attained similar or even better performance to methods that extended the original CLIPScore (Sarto et al., 2023; Kim et al., 2022; Hu et al., 2023; Kim et al., 2023; Narins et al., 2024; Wada et al., 2024). Tests with machine-translated data show that multilingual CLIPScore can also maintain a high correlation with human judgements across different languages, and additional tests with natively multilingual and multicultural data further attest to high-quality assessments across languages.

Our study highlights the importance of multilingual and multicultural research in the evaluation of image captions, aiming to inspire the development of multilingual frameworks in this domain. We show that multilingual models, trained on equally sized datasets, perform just as well as English-

only models on English assessments, while also excelling across various evaluation tasks that involve multilingual and multicultural data, making them far more versatile and valuable assets than English-centric models.

Our contributions include (i) a finetuning strategy that accounts for linguistic and diversity as well as alignment with human judgements (Section 3); (ii) an extension of English-centric benchmarks to multiple languages, incorporating human evaluations and diverse linguistic phenomena, while preserving the original benchmarks' quality (Sections 4.3.2 and 4.3.3) ; and (iii) an adaptation of existing multilingual and multicultural datasets for captioning evaluation (Section 4.3.3) [1].

2 Related Work

Conventional image captioning evaluation has relied on reference-based assessments, where machine-generated captions are compared against human-generated ones (i.e., the references). Frequently used metrics such as BLEU or CIDEr (Vedantam et al., 2015a) rely on lexical matches, and hence may fail to capture finer nuances and semantic overlaps in rich captions. A recent shift in the evaluation paradigm involves the use of learned vision-and-language models to enable evaluation through reference-free metrics.

The CLIPScore metric (Hessel et al., 2021) was one of the first proposals for evaluating image captions that departed from traditional metrics. Grounded in a vision-and-language encoder, specifically the Contrastive Language-Image Pretraining (CLIP) model (Radford et al., 2021), this strategy employs a modified cosine similarity between representations for the input image and the caption under evaluation. CLIPScore exhibits a high correlation with human judgments across various datasets, and despite being a reference-free metric, it even surpasses established reference-based metrics like BLEU and CIDEr. Today, CLIPScore-based metrics are widely used for evaluating image captions and have inspired the development of numerous new evaluation metrics that build on CLIP (Sarto et al., 2023; Hu et al., 2023; Kim et al., 2022), including reference-based variants.

Despite the advancements, recent studies have noted that CLIPScore can lack rating granularity, emphasising the need for better benchmark datasets

to evaluate image captioning metrics (Ahmadi and Agrawal, 2023). Datasets like VICR (Narins et al., 2024) or Polaris (Wada et al., 2024), have employed more rigorous methods for collecting human ratings, but remain limited to English. Alongside these datasets, researchers have shown that models specifically trained for image captioning evaluation can slightly outperform CLIPScore. We corroborate these findings by proposing a fine-tuned version of CLIPScore that surpasses previous variants.

Recent work also highlights the need for multilingual and multicultural benchmarks. Kim et al. (2023) proposed a multilingual image captioning evaluation method. The authors finetuned the CLIP text encoder with a language-agnostic approach to differentiate between original and perturbed text. They also introduced a new dataset for evaluating multilingual captioning metrics, though it has yet to be made publicly available.

The lack of linguistic and cultural diversity in datasets has been further criticized by Liu et al. (2021), who argue that relying on English-based lexical databases and image queries introduces a North American and Western European bias, since existing visio-linguistic datasets often fail to capture concepts relevant to non-English languages and cultures outside of Europe and North America. To mitigate this limitation, the authors built MaRVL, which proposes a new protocol for constructing an ImageNet-style hierarchy that better reflects diverse languages and cultures. They benchmark multilingual, multimodal models, but these often perform just above chance, underscoring the challenges of handling out-of-distribution concepts and images. This calls for a reassessment of model robustness and accuracy and the development of more inclusive systems.

Similarly, Bugliarello et al. (2022) highlighted the importance of multilingual benchmarks, noting that vision-and-language research has primarily focused on English tasks. To address this, the authors proposed a multilingual dataset for evaluating vision-language inference, where models predict entailment relationships between a textual hypothesis and an image premise, expanding the scope of evaluation to include diverse languages.

3 Multilingual CLIPScore

The CLIPScore metric uses an adjusted cosine similarity to compare representations for the input image and the caption being assessed, as originally

---

[1] The code and adapted datasets supporting our evaluation experiments will be made publicly available upon acceptance.

described by Hessel et al. (2021). In our work, we adopted the original formulation. A more detailed explanation of the CLIPScore and RefCLIPScore metrics can be found in Appendix A.

To boost performance across languages, we propose a strategy to finetune multilingual CLIP models in a setting that considers both linguistic and cultural diversity while accounting for human preference alignment.

Two distinct datasets were used for finetuning. The first, CrossModal-3600, focuses on multilingual captions and multicultural imagery (Thapliyal et al., 2022), whereas the second, named VICR, comprises English image-caption pairs that are evaluated by humans (Narins et al., 2024), which we machine translated to different languages following a strict quality-aware translation scheme to help maintain quality. We also propose the combination of different training objectives tailored to the specific characteristics of each dataset.

In more detail, to enhance the model's ability to process multilingual and multicultural instances, we finetuned it on both datasets using the original CLIP contrastive loss, which can be formally described as follows:

$$\mathcal{L}_C = -\frac{1}{2N} \sum_{i=1}^{N} \left[\log \frac{e^{s_{i,i}/\tau}}{\sum_{j=1}^{N} e^{s_{i,j}/\tau}} + \log \frac{e^{s_{i,i}/\tau}}{\sum_{j=1}^{N} e^{s_{j,i}/\tau}} \right],$$

(1)

where N is the number of image-text pairs in a batch, $s_{i,j}$ is the similarity score between the i-th image and the j-th text description, and τ is a temperature parameter that scales the similarity scores and helps in controlling the concentration level for the distribution of scores.

For the second dataset, to improve the alignment of CLIPScore with human ratings, we also considered a Pearson correlation loss:

$$\mathcal{L}_P = 1 - \frac{(x-\overline{x})^T(y-\overline{y})}{||(x-\overline{x})|| \cdot ||(y-\overline{y})||},$$

(2)

where x is the vector of CLIPScore values, y is a vector with the human rating scores, and $\overline{x}$ and $\overline{y}$ are the respective average values.

Considering that both loss functions can benefit from larger batch sizes, we sample instances for training alternating between each task, without mixing instances with respect to different losses in the same batch. We accumulate gradients for two steps before updating the network, effectively combining both loss effects while leveraging the benefits of larger batches, i.e., $\mathcal{L} \sim \mathcal{L}_C + \mathcal{L}_P$.

4 Experimental Evaluation

This section presents the datasets, the experimental setup, and the results for different CLIP models, considering English, multilingual, and multicultural scenarios for image captioning evaluation.

4.1 Datasets

To ensure a fair and comprehensive evaluation of our multilingual models, we extended several well-established English-centric datasets to a multilingual scenario. These datasets, originally developed for assessing human judgments in image-captioning tasks, contain one or more human quality assessments for each image-caption pair.

- **Expert** (Flickr8K-Expert), consisting of $5,664$ pairs (Hodosh et al., 2013).
- **Crowdflower** (Flickr8K-CF), with $47,830$ pairs (Hodosh et al., 2013).
- **Composite**, containing $13,146$ pairs (Aditya et al., 2015).
- **VICR**, with $10,175$ training, $2,310$ validation, and $3,161$ test pairs (Narins et al., 2024).

In addition to these datasets, we evaluated the robustness of our models to various linguistic phenomena using the **VALSE** dataset (Parcalabescu et al., 2021), which comprises $6,704$ correct image-caption pairs alongside their foil caption versions.

While the comparison between multilingual and monolingual models on English data offers some insights, it provides a limited perspective on multilingual performance. Unfortunately, high-quality multilingual resources featuring curated human assessments of caption quality are scarce or nonexistent, restricting the scope of multilingual evaluation. To overcome this, we developed a translation scheme that leverages large machine translation models (Fan et al., 2021; Alves et al., 2024; Liu et al., 2020), paired with language and translation quality estimation models (Rei et al., 2022), to translate English captions with pre-existing human assessments into multiple languages. This approach targets the highest possible translation quality, filtering out low-quality translations and thus ensuring the validity of human judgments across target languages. Further details of our translation scheme can be found in Appendix C.

Our language selection is in line with recent machine translation studies (Alves et al., 2024), covering high-resource languages (i.e., English, French, German, Spanish, and Chinese) and also mid- (i.e.,

Portuguese, Italian, and Russian) to low-resource languages (i.e., Dutch and Korean). We translated both the **VICR** and **VALSE** datasets into the nine aforementioned languages using our MT scheme.

In addition, to further expand our multilingual evaluation, we used natively multilingual and multicultural datasets, i.e., **XVNLI** (Bugliarello et al., 2022) and **MaRVL** (Liu et al., 2021), re-purposing them for the evaluation of image captioning metrics. We also expanded both native multilingual datasets by translating them into English, allowing us to compare a multilingual model with its English-only counterpart, assessing the impact of our translation scheme in inference time.

4.2 Evaluation Metrics

We evaluate the different models using correlation with human judgements, and also through classification tasks. Regarding the correlation experiments, we measure performance using three different correlation coefficients, namely Spearman ρ and Kendall τ with variations b and c. The correlation metrics are formally defined in Appendix B.

For the classification experiments, we measure performance under the assumption that a caption entailed by an image should reflect a higher CLIP-Score than a contradiction/foil caption. Based on this assumption, we use accuracy to measure performance.

4.3 Experiments and Results

This section presents experimental results for the different models and evaluation datasets, establishing a comparison with previously reported results and contributing to the multi-linguistic exploration of existing models and datasets. We also performed a qualitative study focusing on image-caption pairs that feature concepts that could be associated with cultural bias, which is reported in Appendix G.

4.3.1 Model Selection

To select the specific CLIP model to be in our multilingual experiments, following the CLIPScore methodology described by Hessel et al. (2021), we first analysed correlation results between CLIP-Score values and human ratings across four English datasets and considering publicly available CLIP models (see Table 5 in Appendix E). The results indicate that CLIPScore estimates improve significantly with larger CLIP models trained on more data, even if the data is multilingual and tested in an English-centric environment.

We selected the laion/CLIP-ViT-B-32-xlm-roberta-base-laion5B-s13B-b90k variant for further experiments, as it demonstrated the best performance. From this point forward, we will refer to this multilingual model as MLaion (ML), and our finetuned version as MLaion-F (MLF).

Apart from selecting the best model, we used these experiments to assess the impact of including multilingual data versus data size and model parameters. When comparing the ML model to Apple's ViT-H/14, both models have similar sizes and were trained on 5 billion instances. However, Apple's model was trained entirely with English data, while the ML model used multilingual data. Despite having less English training data, the multilingual model performed similarly on English benchmarks, surpassing Apple's model in several correlation metrics. This suggests that the information from the different languages was effectively generalized, enhancing the model performance in English-focused tasks as if the training data were entirely English-centric. Additional results about the correlation on English data are provided in Appendix E.

4.3.2 Correlation on Multilingual Data

Table 1 displays the correlation between multilingual CLIPScore values and human ratings across the different languages. Our fine-tuned version achieves significantly better correlations with human judgments in reference and reference-free settings across all evaluated languages and for all correlation metrics. The finetuned CLIPScore strongly correlates with human preferences in high-resource languages (i.e., English, French, German, Spanish, and Chinese), and it also exhibits equally strong performance in medium- and low-resource languages. Importantly, our finetuned CLIPScore outperformed the pre-finetuned one even when the latter was using references, achieving a higher average correlation across all metrics, even without using references. This observation is particularly useful as it would allow for the application of the model to new instances, without requiring additional human input. Appendix H provides additional results regarding different model sizes and loss variants for model finetuning. The findings in the appendix support the idea that smaller models can obtain higher gains in correlation with human judgements when using our finetuning strategy, compared to the original models.

In an ideal scenario, i.e. assuming perfect ma-

| | CIDEr | | | Without Finetuning | | | | | | With Finetuning | | | | | |
| | | | | ML CLIPScore | | | ML RefCLIPScore | | | MLF CLIPScore | | | MLF RefCLIPScore | | |
	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ
English	63.1	69.8	79.3	67.6	73.0	82.4	69.1	74.6	83.6	68.7	75.4	84.1	**69.7**	**76.5**	**84.8**
German	58.3	64.4	74.4	66.1	72.3	81.5	68.0	74.4	83.2	68.0	74.8	83.6	**69.1**	**75.9**	**84.4**
French	60.0	66.4	76.3	65.9	71.8	81.3	67.6	73.6	82.7	68.0	74.7	83.6	**69.1**	**75.9**	**84.4**
Spanish	61.3	67.8	77.6	66.3	72.7	81.8	67.9	74.4	83.2	67.8	74.5	83.5	**68.9**	**75.7**	**84.3**
Chinese	58.5	64.6	74.6	65.0	71.4	80.8	66.7	73.2	82.3	67.4	74.0	83.1	**68.5**	**75.2**	**83.9**
Portuguese	61.3	67.8	77.6	66.1	72.2	81.6	67.8	74.1	83.0	67.9	74.6	83.5	**69.0**	**75.8**	**84.3**
Italian	60.7	67.1	77.0	65.8	72.1	81.4	67.5	74.0	82.9	67.9	74.6	83.5	**68.9**	**75.7**	**84.3**
Russian	54.0	59.6	69.4	65.0	71.4	80.7	66.7	73.3	82.2	67.6	74.2	83.2	**68.8**	**75.6**	**84.2**
Korean	58.1	64.3	74.1	64.3	70.5	80.0	66.3	72.7	81.8	67.4	74.1	83.1	**68.3**	**75.0**	**83.8**
Dutch	58.1	64.2	74.2	65.8	72.0	81.4	67.7	74.1	83.0	68.2	74.9	83.8	**69.0**	**75.8**	**84.3**
Average	59.3	65.6	75.5	65.8	71.9	81.3	67.4	73.7	82.7	67.9	74.6	83.5	**68.9**	**75.7**	**84.3**

Table 1: Correlation between M-CLIPScore values and human rankings, considering machine-translated versions of the VICR dataset into 9 different languages besides the original English. The last row presents macro-averaged correlation results across all the languages (inc. English). **Bold** values signify the best score per language. All observed score differences are statistically significant using the Williams test ($p < 0.01$).

chine translation results and balanced CLIP performance across languages, the correlations between CLIPScore values across the different languages would equal one, signifying a perfect alignment. To explore deviations from this behaviour, we use heatmaps to visually represent the interrelationships between CLIPScore values across languages.

Figure 1 presents Pearson correlation scores between languages for the best multilingual CLIPScore model (presented in squared cells) and our fine-tuned version (presented in circular cells). The image contains three heatmaps:

- The first, on the left, shows CLIPScore correlations for the full VICR test dataset, comparing the fine-tuned model (upper triangle with circular cells) and the pre-finetuned model (lower triangle with squared cells).
- The second and third heatmaps display correlations based on translation quality. Specifically, they focus on translations with COMETKiwi scores in the bottom 25% (lower triangle) and top 25% percentile (upper triangle). The second heatmap with squared cells represents the pre-finetuned model, and the third heatmap with circular cells shows the fine-tuned version.

In the left heatmap of Figure 1, which includes the entire VICR test set, we observe consistently high correlation values across all languages. As expected, the results indicate that CLIPScore correlations are influenced by the quality of the translated captions, with the most notable differences occurring in non-Latin script languages.

The second and third heatmaps show slightly higher correlations for high-quality translations (up-per triangles) compared to the poorest translations (lower triangles). However, even the poorest translations still demonstrate relatively high correlations, suggesting that the overall quality of the translations remains strong across different languages.

It is worth noting that, as expected, the most impacted languages are those that use a different script, particularly in the non-finetuned case. We also see a significant improvement in correlations between languages when using our fine-tuned CLIPScore model. Although this improvement is expected, given that the fine-tuned model was trained on *in-distribution* data, it also reflects the high quality of our multilingual training data, further validating our translation strategy.

4.3.3 Multilingual Classification

This section explores the robustness of the multilingual CLIPScore assessments through different types of classification tasks. Inspired by previous work (Hessel et al., 2021; Sarto et al., 2023) which assessed accuracy in English-only benchmarks, our goal is to delve deeper into the nuanced realm of multilingual and multicultural understanding.

Robustness to linguistic phenomena: These experiments used our machine translated versions of the VALSE dataset, designed to evaluate the robustness to phenomena such as inconsistencies in numeric quantities or spatial relations (Parcalabescu et al., 2021). VALSE comprises seven tests that encompass a range of linguistic structures. In each test, a model is presented with a visual input and is tasked with distinguishing true captions from altered versions (i.e, foils), modified to exhibit a specific feature. Additional information about the

Figure 1: Pearson correlation scores between different languages, for the original multilingual CLIPScore model (squared cells) and our finetuned version (circular cells). The first heatmap considers the complete set of instances from the VICR dataset, reporting results for both the original and finetuned model versions (lower/upper diagonal values). The second and third heatmaps consider the subset of instances with COMETKiwi scores below/above the 25th/75th percentile value for each language (lower/upper diagonal values), for the original multilingual CLIPScore model and our finetuned model version, respectively.

	Proposed Models										VALSE Models	
Finetuning method	English	German	French	Spanish	Chinese	Portuguese	Italian	Russian	Korean	Dutch	Model	English
MLF Both Losses	69.7	**67.3**	**67.5**	**67.9**	66.9	**69.0**	**66.0**	**67.1**	**60.6**	**66.2**	CLIP	64.0
MLF Pearson Loss	69.2	67.2	66.8	67.4	**67.3**	67.2	66.0	65.0	59.4	65.8	LXMERT	59.6
MLF Contrastive Loss	68.4	65.0	65.5	65.7	65.6	66.4	64.6	64.8	59.2	63.7	ViLBERT	46.4
ML	67.6	64.8	64.2	65.6	64.0	65.4	64.4	63.4	58.4	62.5	12-in-1	**75.1**

Table 2: Average accuracy scores for the different classification tasks present in the VALSE dataset and its multilingual variants, considering different CLIP models. **Bold** values signify the best score per language.

446 dataset is provided in Appendix D.

447 Table 2 displays the average performance across
448 different language variants, considering that the
449 CLIPScore values regarding the true captions
450 should be higher than the ones related to the corre-
451 sponding foils. The results show that our finetuned
452 model delivers the highest average performance
453 across nearly all languages. Compared to the mod-
454 els reported in the original VALSE dataset paper,
455 the MLF model was only surpassed by the multi-
456 task ViLBERT 12-in-1 model (Lu et al., 2020).

457 Table 9 in Appendix H contains a more detailed
458 breakdown of the performance across the differ-
459 ent tests within VALSE. We observe a significant
460 improvement of 6% to 10%, on average, in the
461 existence *quantifier*, *plurality*, and *counting* adver-
462 sarial tests with the fine-tuned model. For the re-
463 maining tests, we saw a more modest performance
464 increase, ranging from 1% to 5% compared to the
465 non-finetuned model, with the exception of the *ac-*
466 *tion replacement* and *coreference* tests where per-
467 formance did not improve. The lower performance
468 for the coreference tests likely stems from the na-
469 ture of the task and the limitations of our evaluated
470 method. CLIPScore, which was designed to eval-
471 uate declarative captions, struggles to effectively
472 score a caption that combines both a question and
473 a yes/no answer. This mismatch may explain the
474 lower results for coreference handling, and can be a

	Accuracy 1			Accuracy 2			Accuracy 3		
	ML	MLF	EN	ML	MLF	EN	ML	MLF	EN
Arabic	84.6	**85.4**	82,2	**76.3**	**76.3**	73,4	**44.7**	41.8	38,82
French	86.7	**90.5**	86,2	77.9	**79,9**	76,9	45.4	**47.7**	43,75
Spanish	86.2	**87.8**	87,3	77.7	**78,4**	77,3	**46.7**	45.1	44,41
Russian	87.5	**88.9**	88,6	78.0	**79,2**	78,2	44.4	**46.7**	44,08
Overall	86.3	**88,4**	86,1	77.8	**78,8**	76,5	45.1	**45.9**	42,8

Table 3: Accuracy for different classification tasks defined over the datasets derived from XVNLI. **EN:** English-only laion-H-14 model. **Bold** values signify the best value per language/task.

475 key factor for the higher performance of ViLBERT
476 12-in-1 in the overall average score present in ta-
477 ble 2 when compared to CLIPScore-type strategies.

478 Additionally, we observed that different loss
479 functions contributed distinct benefits to various
480 test scenarios. For example, the Pearson loss
481 proved particularly effective in the existence quanti-
482 fier and action actant swap tests, when compared to
483 the contrastive loss. In contrast, the contrastive loss
484 delivered superior performance in the foil-it and the
485 counting adversarial tests. This demonstrates the
486 advantages of our proposed training strategy, which
487 combines both losses to maximize performance.

Classification of multicultural instances: We
489 also used natively multilingual datasets (i.e.,
490 XVNLI and MaRVL) to assess the multilingual and
491 multicultural capabilities of CLIPScore models.

492 These datasets originally aimed at assessing se-
493 mantic inference between the contents of images

	Accuracy 1			Accuracy 2		
	ML	MLF	EN	ML	MLF	EN
Indonesian	92.4	**93.4**	91,4	82.3	**83.3**	81,2
Mandarin	89.4	**91.5**	91,1	80.1	**81.3**	79,9
Swahili	**85.0**	**85.0**	84,3	65.3	65.3	**70,1**
Tamil	85.7	88.0	**92,8**	74.7	77.5	**85,3**
Turkish	**93.5**	92.9	87,7	**87.0**	86.0	79,1
Overall	89.4	**91.5**	91,1	80.1	**81.3**	79,9

Table 4: Accuracy for different classification tasks defined over the datasets derived from MaRVL. **EN:** English-only laion-H-14 model. **Bold** values signify the best value per language/task.

| Caption A (Entailment) | Caption C (Contradition) |

ACC1: CLIPS(I,A) > CLIPS(I,C)

| Caption A (Entailment) | Caption B (Neutral) | Caption C (Contradition) |

CLIPS(I,A) > CLIPS(I,B)
ACC2: CLIPS(I,B) > CLIPS(I,C)
CLIPS(I,A) > CLIPS(I,C)

ACC3: CLIPS(I,A) > CLIPS(I,B) > CLIPS(I,C)

Figure 2: The three different XVNLI multilingual classification tasks, where accuracy is defined with basis on comparisons between CLIPSCore values.

and texts, featuring positive and negative instances whose challenges for interpretation are more likely to lie on fine-grained semantic understanding and compositional reasoning instead of object detection, and with captions featuring slight variations in how the contents of an image are expressed.

Each instance in the XVNLI dataset contains an image-caption pair and a categorical label associated with the relationship between the pair. This label can be either (a) contradiction, (b) neutral, or (c) entailment. Based on these labels, **we defined three multilingual classification tasks** under this scenario, **leveraging concordant/discordant instances** as illustrated in Figure 2:

Task 1: This setting only considers contradiction and entailment instances, under the assumption that the order of the CLIPScore values should match the order of the labels.
Task 2: In a more challenging scenario, we can consider a larger set of duplets and the ordering between the three possible labels.
Task 3: In this case, we also consider the three possible labels, but we now assess triples of instances A, B, and C from the dataset, sharing the same image. We only assume a correct classification when we achieve a perfect match between the order of the labels and the CLIPScore values.

In the case of the MaRVL dataset, each instance consists of a caption, a pair of images, and a Boolean label with the value *true* when the caption accurately matches the images and *false* when the caption is incorrect (e.g. because its contents only describe at maximum one of the images instead of both). The data can be analyzed considering four instances simultaneously, sharing the same caption but featuring distinct pairs of images. In turn we devise two evaluation tasks based on MaRVL.

Task 1: We consider the scenario where the CLIPScore for the image that best aligns with the caption should be higher than the CLIPScore for the image that least aligns with the caption.
Task 2: In a more challenging scenario, we consider sets of four instances sharing the same caption and decide on a correct classification only if all best-aligning captions have a CLIPScore higher than all least aligning captions.

Our objective in rearranging both datasets into the aforementioned classification tasks (several tests with increasing difficulty) was to allow for the evaluation of the ability of CLIPScore models to reason with fine-grained semantic distinctions in natively multilingual and multicultural contexts.

In this set of multilingual experiments, we assessed three distinct models: the original multilingual Laion/ViT-H-14 (ML), our fine-tuned variant (MLF), and the English-only Laion/ViT-H-14 (EN). Apart from the multilingual setup, we employed our translation scheme to convert the native non-English data into English to evaluate English models within these native multilingual scenarios. This approach allows us to explore two key aspects: the comparative benefits of leveraging machine translation during training versus inference and an indirect assessment of the quality of our MT process.

Table 3 summarizes the results for the classification tasks from the XVNLI. As expected, accuracy declined from Task 1 to Task 3 for all model variants, indicating that model performance tends to decrease as task complexity increases. Additionally, the English-only model performs worse than the MLF model across all languages and tasks, with particularly noticeable gaps in Arabic and French (for which languages it is also outperformed by the ML variant). This suggests that while machine translation can make non-English data accessible to English-only models, it leads to performance degradation, potentially forgoing some cultural nuances, especially in more complex tasks.

Table 4, shows a similar overall trend, i.e. the MLF model performs on par or even better than other variants for most languages but displays different patterns for extremely low-resource languages like Tamil and Swahili. For both, the English-only model performs better in the more difficult accuracy task (Accuracy 2). This behaviour might reflect the challenges faced by multilingual models in extremely low-resource languages where their occurrence is scarce to nonexistent in the pre-training data. Additionally, it may relate to the imbalanced quality of out-of-English versus into-English MT, with the latter being better for low-resource languages.

Overall, our findings indicate that the finetuned version of the multilingual model achieved superior results compared to the original model, emphasizing the effectiveness of our training strategy. In addition, using the translation pipeline with the English-only model, the latter performed worse than simply using the multilingual model. It should also be noted that including the translation scheme during inference significantly increases computational costs and response times. With this in mind, **despite the high quality of the translations, we conclude that translating original captions into English offers no advantages during inference**. Instead, leveraging machine translation for a cost-effective dataset expansion for finetuning or evaluation is far more beneficial.

A more detailed explanation for both the XVNLI and MaRVL experiments is given in Appendix F.

While the experiments with the XVNLI and MaRVL datasets provide interesting insights into the effectiveness of multilingual CLIPScore models, they also involve several important limitations. Considering the XVNLI experiments, previous studies have reported good results in multimodal inference leveraging CLIP (Song et al., 2022). However, the authors of SNLI-VE (Xie et al., 2019), from which XVNLI is derived, noted that good performance (i.e., accuracy up to 67%) can be achieved when looking only at the information in the textual hypothesis, without the visual premise, pointing to significant biases in the XVNLI data. In the case of the MaRVL experiments, given that the captions refer to a pair instead of individual images, the CLIPScore values can be unreliable when attempting to match images to textual sentences. Previous studies have noted that CLIP models can treat inputs as a bag-of-words and suffer from a concept association bias (Yamada et al., 2022), e.g.

ignoring the missing information when two concepts are present in one of the inputs while the other only contains a single concept. Hence, there is room for future work that pushes even further the analysis of the robustness of caption evaluation metrics. We note that the process to device accuracy tasks which we presented, is easily transferrable to newer datasets that address these limitations.

5 Conclusions

This study highlights the importance of expanding image captioning evaluation to include multilingual and multicultural research, encouraging more inclusive frameworks in this field. Using a quality filtering machine translation scheme, we can cost-effectively extend well-established English-centric benchmarks to multiple languages without compromising benchmark quality and validity, which can be very beneficial for the fine-tuning and evaluation of new, multilingual evaluation models.

We propose a finetuning strategy to better leverage and learn from both multi-cultural data and human preferences and test our models on a set of different datasets and tasks. Our findings show that multilingual models trained with the same amount but with less English-specific data perform equally well on English tasks while excelling in multilingual and multicultural ones. This reveals the potential of multilingual models to generalize across languages, making them more versatile assets. Additionally, our finetuning approach significantly boosted the model's ability to handle complex linguistic challenges, such as quantifiers, plurality, and numeric inconsistencies, highlighting its adaptability to more intricate language patterns.

Further to machine translation of English data, we propose a strategy to adapt multilingual datasets from other tasks to IC evaluation benchmarks. The integration of natively multilingual and multicultural datasets into both training and evaluation processes mitigates cultural information loss, reinforcing the reliability of our proposed pipeline for training and evaluating multilingual models, and making them effective tools for real-world multilingual and multicultural evaluation.

Overall, our work contributes to multilingual IC evaluation both in terms of modelling and benchmarking approaches and we hope it will inspire and support further work in this under-researched field.

Limitations and Ethical Considerations

Although our work does not raise new ethical issues within the domain of vision-language models (e.g., we conducted our experiments on public datasets, carefully designed for academic research and extensively used in previous studies), there are some general important concerns.

Models like CLIP are, for instance, notorious for their internal biases, e.g. inherited from the training data itself. We therefore recommend caution in the use of the approach proposed in this paper, and anticipate further research into the specific issue of model biases, before relying on our work beyond research environments. Another important limitation in the work reported in this paper concerns the use of machine translated data in some of the evaluation experiments, which, despite our best efforts to avoid translation errors, can still lead to different types of biases and to the reliance on artificially impoverished language. The development of manually curated benchmarks, specifically designed for the assessment of multilingual metrics for image captioning evaluation, is left as an important challenge for future work.

We also note that we used Github Copilot[2] during the development of our research work, and we used ChatGPT[3] for minor verifications during the preparation of this manuscript.

References

Somak Aditya, Yezhou Yang, Chitta Baral, Cornelia Fermuller, and Yiannis Aloimonos. 2015. From images to sentences through scene description graphs using commonsense reasoning and knowledge. *arXiv preprint arXiv:1511.03292*.

Saba Ahmadi and Aishwarya Agrawal. 2023. An examination of the robustness of reference-free image captioning evaluation metrics. *arXiv preprint arXiv:2305.14998*.

Duarte M Alves, José Pombal, Nuno M Guerreiro, Pedro H Martins, João Alves, Amin Farajian, Ben Peters, Ricardo Rei, Patrick Fernandes, Sweta Agrawal, et al. 2024. Tower: An open multilingual large language model for translation-related tasks. *arXiv preprint arXiv:2402.17733*.

Emanuele Bugliarello, Fangyu Liu, Jonas Pfeiffer, Siva Reddy, Desmond Elliott, Edoardo Maria Ponti, and Ivan Vulić. 2022. IGLUE: A benchmark for transfer learning across modalities, tasks, and languages. In *Proceedings of the International Conference on Machine Learning*.

Angela Fan, Shruti Bhosale, Holger Schwenk, Zhiyi Ma, Ahmed El-Kishky, Siddharth Goyal, Mandeep Baines, Onur Celebi, Guillaume Wenzek, Vishrav Chaudhary, Naman Goyal, Tom Birch, Vitaliy Liptchinsky, Sergey Edunov, Michael Auli, and Armand Joulin. 2021. Beyond english-centric multilingual machine translation. *Journal of Machine Learning Research*, 22(107).

Gregor Geigle, Abhay Jain, Radu Timofte, and Goran Glavaš. 2023. mblip: Efficient bootstrapping of multilingual vision-llms. *arXiv preprint arXiv:2307.06930*.

Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. 2021. Clipscore: A reference-free evaluation metric for image captioning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 7514–7528.

Micah Hodosh, Peter Young, and Julia Hockenmaier. 2013. Framing image description as a ranking task: Data, models and evaluation metrics. *Journal of Artificial Intelligence Research*, 47:853–899.

Anwen Hu, Shizhe Chen, Liang Zhang, and Qin Jin. 2023. InfoMetIC: An informative metric for reference-free image caption evaluation. *arXiv preprint arXiv:2305.06002*.

Maxime Kayser, Oana-Maria Camburu, Leonard Salewski, Cornelius Emde, Virginie Do, Zeynep Akata, and Thomas Lukasiewicz. 2021. e-vil: A dataset and benchmark for natural language explanations in vision-language tasks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*.

Jin-Hwa Kim, Yunji Kim, Jiyoung Lee, Kang Min Yoo, and Sang-Woo Lee. 2022. Mutual information divergence: A unified metric for multimodal generative models. In *Proceedings of the Annual Meeting on Neural Information Processing Systems*.

Yongil Kim, Yerin Hwang, Hyeongu Yun, Seunghyun Yoon, Trung Bui, and Kyomin Jung. 2023. PR-MCS: Perturbation robust metric for multilingual image captioning. *arXiv preprint arXiv:2303.08389*.

Fangyu Liu, Emanuele Bugliarello, Edoardo Maria Ponti, Siva Reddy, Nigel Collier, and Desmond Elliott. 2021. Visually grounded reasoning across languages and cultures. *arXiv preprint arXiv:2109.13238*.

Yinhan Liu, Jiatao Gu, Naman Goyal, Xian Li, Sergey Edunov, Marjan Ghazvininejad, Mike Lewis, and Luke Zettlemoyer. 2020. Multilingual denoising pre-training for neural machine translation. *Transactions of the Association for Computational Linguistics*, 8.

---

[2] https://github.com/features/copilot
[3] https://openai.com/chatgpt/

Jiasen Lu, Vedanuj Goswami, Marcus Rohrbach, Devi Parikh, and Stefan Lee. 2020. 12-in-1: Multi-task vision and language representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10437–10446.

Lothar D Narins, Andrew Scott, Aakash Gautam, Anagha Kulkarni, Mar Castanon, Benjamin Kao, Shasta Ihorn, Yue-Ting Siu, James M Mason, Alexander Blum, et al. 2024. Validated image caption rating dataset. In *Proceedings of the Annual Meeting on Neural Information Processing Systems*.

Letitia Parcalabescu, Michele Cafagna, Lilitta Muradjan, Anette Frank, Iacer Calixto, and Albert Gatt. 2021. Valse: A task-independent benchmark for vision and language models centered on linguistic phenomena. *arXiv preprint arXiv:2112.07566*.

Haoyi Qiu, Zi-Yi Dou, Tianlu Wang, Asli Celikyilmaz, and Nanyun Peng. 2023. Gender biases in automatic evaluation metrics for image captioning. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. 2021. Learning transferable visual models from natural language supervision. In *Proceedings of the International conference on machine learning*.

Rita Ramos, Emanuele Bugliarello, Bruno Martins, and Desmond Elliott. 2024. PAELLA: Parameter-efficient lightweight language-agnostic captioning model. In *Findings of the Annual Conference of the North American Chapter of the Association for Computational Linguistics*.

Rita Ramos, Bruno Martins, and Desmond Elliott. 2023a. LMCap: Few-shot multilingual image captioning by retrieval augmented language model prompting. In *Findings of the Association for Computational Linguistics*.

Rita Ramos, Bruno Martins, Desmond Elliott, and Yova Kementchedjhieva. 2023b. SmallCap: Lightweight image captioning prompted with retrieval augmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*.

Ricardo Rei, Nuno M Guerreiro, José Pombal, Daan van Stigt, Marcos Treviso, Luisa Coheur, José GC de Souza, and André FT Martins. 2023. Scaling up COMETKiwi: Unbabel-IST 2023 submission for the quality estimation shared task. *arXiv preprint arXiv:2309.11925*.

Ricardo Rei, Marcos Treviso, Nuno M Guerreiro, Chrysoula Zerva, Ana C Farinha, Christine Maroti, José GC De Souza, Taisiya Glushkova, Duarte M Alves, Alon Lavie, et al. 2022. Cometkiwi: Ist-unbabel 2022 submission for the quality estimation shared task. *arXiv preprint arXiv:2209.06243*.

Sara Sarto, Manuele Barraco, Marcella Cornia, Lorenzo Baraldi, and Rita Cucchiara. 2023. Positive-augmented contrastive learning for image and video captioning evaluation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*.

Haoyu Song, Li Dong, Wei-Nan Zhang, Ting Liu, and Furu Wei. 2022. CLIP models are few-shot learners: Empirical studies on vqa and visual entailment. *arXiv preprint arXiv:2203.07190*.

Alane Suhr, Stephanie Zhou, Ally Zhang, Iris Zhang, Huajun Bai, and Yoav Artzi. 2018. A corpus for reasoning about natural language grounded in photographs. *arXiv preprint arXiv:1811.00491*.

Ashish V Thapliyal, Jordi Pont-Tuset, Xi Chen, and Radu Soricut. 2022. Crossmodal-3600: A massively multilingual multimodal evaluation dataset. *arXiv preprint arXiv:2205.12522*.

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. 2015a. CIDEr: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*.

Ramakrishna Vedantam, C. Lawrence Zitnick, and Devi Parikh. 2015b. Cider: Consensus-based image description evaluation. In *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4566–4575.

Yuiga Wada, Kanta Kaneda, Daichi Saito, and Komei Sugiura. 2024. Polos: Multimodal metric learning from human feedback for image captioning. *arXiv preprint arXiv:2402.18091*.

Ning Xie, Farley Lai, Derek Doran, and Asim Kadav. 2019. Visual entailment: A novel task for fine-grained image understanding. *arXiv preprint arXiv:1901.06706*.

Yutaro Yamada, Yingtian Tang, and Ilker Yildirim. 2022. When are lemons purple? the concept association bias of CLIP. *arXiv preprint arXiv:2212.12043*.

Bang Yang, Fenglin Liu, Xian Wu, Yaowei Wang, Xu Sun, and Yuexian Zou. 2023. MultiCapCLIP: Auto-encoding prompts for zero-shot multilingual visual captioning. *arXiv preprint arXiv:2308.13218*.

A The CLIPScore Metric

We now formally describe the CLIPScore and RefCLIPScore metrics (Hessel et al., 2021), which in our study are assessed in multilingual image captioning scenarios. In brief, we have that CLIPScore is based on a modified cosine similarity between representations for the input image and the caption under evaluation. The image and the caption are both passed through the respective feature extractors from a given CLIP model. Then, we compute the cosine similarity of the resultant embeddings, adjusting the resulting value through a re-scaling operation. For an image with visual CLIP embedding $\mathbf{v}$ and a candidate caption with textual CLIP embedding $\mathbf{c}$, a re-scaling parameter is set as $w = 2.5$ and we compute the corresponding CLIPScore as follows:

$$\text{CLIPScore}(\mathbf{c}, \mathbf{v}) = w \times \max(\cos(\mathbf{c}, \mathbf{v}), 0). \quad (3)$$

To compute a corpus-level CLIPScore, e.g. for evaluating the overall quality of a captioning method over a given dataset of images, we can simply average over all the image-candidate pairs.

Note that CLIPScore does not depend on the availability of underlying references for each of the images in an evaluation dataset. However, an extension named RefCLIPScore was also proposed, which additionally extracts the vector representations $\mathbf{R}$ of each available reference with the CLIP text encoder, and computes the harmonic mean of the CLIPScore value from Equation 3, and the maximal reference cosine similarity:

$$\begin{aligned}
\text{RefCLIPScore}(\mathbf{c}, \mathbf{R}, \mathbf{v}) = \\
\text{H-Mean}(\text{CLIPScore}(\mathbf{c}, \mathbf{v}), \quad (4) \\
\max(\max_{\mathbf{r} \in \mathbf{R}} \cos(\mathbf{c}, \mathbf{r}), 0)).
\end{aligned}$$

B The Correlation Metrics

This appendix presents a formal definition of the metrics used in the correlation experiments.

Seeing each of our evaluation datasets as sets of n observations with the form $(\hat{y}_1, y_1), \ldots, (\hat{y}_n, y_n)$, for CLIPScore values $\hat{y}_i$ and reference ratings y_i, the Spearman correlation coefficient ρ is defined as the Pearson correlation between the results of converting the scores $\hat{y}_i$ and y_i to ranks.

Instead of using ranks, we can also define any pair of observations $(\hat{y}_i, y_i)$ and $(\hat{y}_j, y_j)$, where $i < j$, as concordant (or otherwise discordant) if the sort order of the instances agrees (i.e. if either both $\hat{y}_i > \hat{y}_j$ and $y_i > y_j$ holds, or both $\hat{y}_i < \hat{y}_j$ and $y_i < y_j$). Based on pairs, the Kendall τ correlation coefficient assesses the strength of association between the CLIPScore values and the reference ratings, with the τ_b variant accounting for ties and being defined as:

$$\tau_B = \frac{n_c - n_d}{\sqrt{(n_0 - n_1)(n_0 - n_2)}}, \quad (5)$$

where n_c is the number of concordant pairs, n_d the number of discordant pairs, $n_0 = n(n-1)/2$, $n_1 = \sum_i t_i(t_i - 1)/2$, $n_2 = \sum_j u_j(u_j - 1)/2$, t_i is the number of tied values in the i^{th} group of ties for the CLIPScore, and u_j is the number of tied values in the j^{th} group of ties for the reference ratings.

In turn, τ_c accounts with the fact that the underlying scales of the scores are different for CLIPScore and the reference ratings, being defined as:

$$\tau_c = \frac{n_c - n_d}{n_0} \times \frac{n-1}{n} \times \frac{m}{m-1}, \quad (6)$$

where m is the number of values in the ranking scale for the reference ratings.

C The Machine Translation Scheme

This appendix describes the translation scheme that was used to machine translate the datasets used in our experiments. This scheme is design to mitigate low-quality translations, or hallucinations generated by the machine translation model, thus providing a reliable dataset at the end. We specifically used a large (i.e., 1.2 billion parameters) open-access multilingual machine translation model named M2M100 (Fan et al., 2021), available on the HuggingFace[4] model hub. M2M100 was trained on a range of high and low-resource languages from different families and using different scripts, achieving state-of-the-art performance across a diverse set of 100 languages.

While machine translated data allows us to assess multilingual captioning metrics, the results will depend not only on the performance of the metrics but also on the quality of the translations. Low-quality translations, or hallucinations generated by the translation model, will impact the caption and break our assumption that human ratings for the English data can be transferred across languages. To address this issue, we propose to use the COMETKiwi (Rei et al., 2023) machine translation quality estimation metric to control for translation

---
[4]https://huggingface.co/facebook/m2m100_1.2B

quality, assessing the impact of low quality translations on the observed results.

We specifically began by translating the VICR dataset, featuring English captions with human ratings and also reference captions originally from the MSCOCO and Flickr8K datasets. For each caption, whether a candidate or a reference, we return 25 translations using a beam search technique with 100 beams. Subsequently, we filtered the candidates with a language checker, to ensure proper translation into the intended language. After the language check, we selected for each instance the translation that scored higher based on a large COMETKiwi model[5].

D   Description of the Datasets

The following datasets were used in the tests that assessed correlation with human judgment.

- **Flickr8K-Expert (Hodosh et al., 2013):** This dataset comprises $16,992$ expert human judgments for $5,664$ image-caption pairs from Flickr8K. Human assessors graded captions on a scale of 1 to 4, where 4 indicates a caption that accurately describes the image without errors, and 1 signifies a caption unrelated to the image.

- **Flickr8K-CF (Hodosh et al., 2013):** This dataset consists of $145,000$ binary quality judgments collected with CrowdFlower, involving $47,830$ image-caption pairs with $1,000$ unique Flickr8K images. Each pair received at least three binary judgments, and we use the proportion of *yes* annotations as the score for each pair.

- **Composite (Aditya et al., 2015):** This dataset contains $13,146$ image-caption pairs taken from MSCOCO (2007 images), Flickr8K (997 images), and Flickr30K (991 images). Each image originally had five reference captions. One of these references was chosen for human rating and subsequently removed from the reference set that is to be used when assessing evaluation metrics.

- **VICR (Narins et al., 2024):** The Validated Image Caption Rating (VICR) dataset features 68,217 ratings, collected through a gamified approach, for 15,646 image-caption pairs involving 9,990 distinct images. The authors of

the dataset demonstrated that it exhibits a superior inter-rater agreement compared to other alternatives (e.g., an improvement of 19% in Fleiss' κ when compared to the agreement for the Flickr8K-Expert dataset), and it features a more balanced distribution across various levels of caption quality. In our tests, we used the test split of the VICR dataset, which includes 3,161 image-caption pairs, with 2,000 images from the MSCOCO 2014 validation dataset and 1,161 images from the Flickr8K dataset. When using VICR to finetune CLIP models with a contrastive loss, we used the original image captions from MSCOCO or Flickr8K.

All the previous datasets are originally available only for English, but we translated them to nine other different languages using the approach described in Appendix C.

For the experiments that assessed accuracy in terms of distinguishing correct vs incorrect captions, we used the following datasets.

- **VALSE (Parcalabescu et al., 2021):** VALSE is designed to test visio-linguistic grounding capabilities on specific linguistic phenomena. It is composed by seven tasks, each with the same structure: given a visual input, a model is asked to distinguish real captions from foils, where a foil is constructed from a caption by altering a word or phrase that realizes a specific linguistic phenomenon. The tests include: (a) existential quantifiers, where models need to differentiate between examples (i) where there is no entity of a certain type or (ii) where one or more of these entities are visible in an image; (b) plurality, where models need to distinguish between noun phrases denoting a single entity in an image (*exactly one flower*), versus multiple entities (*some flowers*); (c) counting, where models needs to differentiate between examples where the specific number of entities in the associated image is correct or incorrect, given the statement; (d) spatial relations, where Models need to distinguish between different spatial relations, with foils differing from the original caption only by the replacement of a spatial preposition; (e) actions, particularly (i) action replacement and (ii) actant swaping, where models need to (i) identify whether an action mentioned in the text matches the action seen in the image (e.g., *a man shouts* versus *smiles*

---

[5] https://huggingface.co/Unbabel/wmt23-cometkiwi-da-xxl

at a woman), and (ii) correctly identify the participants of an action and the roles they play (e.g., is it the man who is shouting or is it the woman); (f) coreference, where models need to perform pronominal coreference resolution, encompassing cases where (i) the pronoun has a noun (phrase) antecedent and pronoun and (noun) phrase are both grounded in the visual modality (e.g., in *a woman is driving a motorcycle*, is she wearing a helmet?), and cases where (ii) the pronoun refers to a region in the image or even to the entire image (e.g., *is this outside?*); (g) foil-it cases, in which the foil minimally differs from the original caption, only by swapping a important noun.

- **XVNLI (Bugliarello et al., 2022):** XVNLI is a multilingual dataset for evaluating vision-language inference, challenging models to predict entailment relationships between a textual hypothesis and an image premise. XVNLI includes high/mid-resource languages like Arabic, French, Spanish, Russian, and English. This dataset includes 1,164 instances per language, each featuring an image and two captions in different languages. There are 357 unique images in total.

- **MaRVL (Liu et al., 2021):** MaRVL follows a format similar to the English NLVR2 dataset (Suhr et al., 2018) and is designed as a multicultural vision-language reasoning dataset, where the goal is to determine the correctness of a sentence about a pair of images. MaRVL predominantly comprises very low-resource languages: Indonesian, Chinese, Swahili, Tamil, and Turkish. This dataset includes around one thousand instances per language, each featuring two image and one caption. There are 1,411 unique captions in total. The English content is composed by collecting the reverse translations from the low-resource languages into English, as provided by the authors on the original GitHub[6].

For model training, besides instances in the training split from the aforementioned VICR dataset, we also used data from the natively multilingual CrossModal-3600 dataset (i.e., XM3600, in short).

- **XM3600 (Thapliyal et al., 2022):** This is a geographically-diverse set of 3600 images annotated with human-generated reference captions in 36 languages. The images were selected from all across the world, covering regions where the 36 languages are spoken, and consistently annotating captions in terms of style across all languages, while avoiding annotation artifacts due to direct translation.

E Correlation Assessment on English Data

Table 5 displays the correlation results between CLIPScore values and human ratings, across the four English datasets and considering existing and publicly available English-only and multilingual CLIP models. The results show that the CLIPScore estimates can improve significantly with larger CLIP models trained with more data.

Comparing results against the performance of the original CLIPScore computed with a ViT-B/32 vision encoder, we can observe substantial improvements. Apple's ViT-H/14 model with 378px resolution achieves the highest correlation results among the English models, although the multilingual model of the same size and trained with less english specific data from LAION is the second best-performing alternative (even outperforming the English-only model on the Composite dataset).

When comparing the top-performing multilingual model to Apple's ViT-H/14, both models have similar sizes and were trained on 5 billion instances. However, Apple's model was trained entirely with English data, while the multilingual model used a mix of English and multilingual data. Despite having less English-specific training data, the multilingual model performed similarly on English benchmarks, surpassing Apple's model in several correlation metrics. This suggests that the information from the different languages was effectively generalized, enhancing the model performance in English-focused tasks as if the training data were entirely English-centric.

In turn, Table 6 compares recent studies proposing other metrics against the best performing English-only and multilingual CLIPScore models[7]. We considered different evaluation settings, assessing results (a) without references, (b) using references, and (c) combining CIDER with RefCLIP-Score when using references (Qiu et al., 2023).

---

[6]https://github.com/marvl-challenge/
marvl-code/tree/master/data

[7]Note that we computed all the correlation scores for the CLIPScore variants and traditional image caption metrics based on lexical matches, whereas the results for other more recent metrics are taken from the corresponding publications.

		Size (B)		VICR			Expert			CrowdFlower			Composite		
		Model	Data	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ
English	openai/clip-vit-base-patch32	0.1	0.4	60.7	67.1	76.9	51.1	51.5	63.1	34.4	17.8	42.4	50.6	51.4	67.9
	apple/DFN5B-CLIP-ViT-H-14-378	0.9	5.0	67.4	**74.4**	**83.1**	56.3	**56.6**	**68.4**	**38.5**	19.9	**47.1**	55.0	55.9	72.8
	apple/DFN5B-CLIP-ViT-H-14	0.9	5.0	66.5	73.5	82.4	55.6	56.0	67.7	38.2	19.7	46.8	54.5	55.3	72.3
	apple/DFN2B-CLIP-ViT-L-14	0.4	2.0	65.8	72.6	81.6	55.5	55.6	67.5	37.1	19.2	45.6	53.6	54.3	71.3
	laion/CLIP-ViT-g-14-laion2B-s12B-b42K	1.3	2.0	66.4	73.0	82.0	55.3	55.1	66.9	37.1	19.1	45.5	54.9	55.7	72.7
	laion/CLIP-ViT-H-14-laion2B-s32B-b79K	0.9	2.0	66.4	73.1	82.1	54.9	54.9	66.7	37.2	19.2	45.6	53.6	54.4	71.2
	laion/CLIP-ViT-L-14-laion2B-s32B-b82K	0.4	2.0	65.9	72.6	81.7	54.4	54.5	66.3	36.7	18.9	45.1	53.6	54.4	71.3
	BAAI/AltCLIP	0.8	-	65.1	71.9	81.1	54.1	54.4	66.2	36.2	18.7	44.6	53.8	54.6	71.6
	openai/clip-vit-large-patch14-336	0.4	0.4	62.0	68.5	78.1	52.6	53.0	64.6	35.4	18.3	43.7	52.8	53.6	70.3
	openai/clip-vit-large-patch14	0.4	0.4	62.3	68.9	78.5	52.6	53.0	64.6	35.2	18.2	43.4	52.5	53.3	70.0
Multilingual	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	1.1	5.0	**67.6**	73.0	82.4	**57.4**	54.3	67.3	38.2	19.4	46.2	**55.5**	**56.2**	**73.2**
	BAAI/AltCLIP-m18	1.1	-	66.6	73.4	82.3	54.8	55.0	66.8	37.1	19.2	45.6	55.2	56.0	73.0
	M-CLIP/XLM-Roberta-Large-Vit-B-16Plus	0.7	0.4	64.6	71.3	80.6	54.6	54.8	66.7	36.0	18.6	44.3	52.1	52.9	69.6
	BAAI/AltCLIP-m9	0.8	-	64.2	70.9	80.3	54.1	54.4	66.2	36.4	18.8	44.8	53.9	54.6	71.6
	laion/CLIP-ViT-B-32-xlm-roberta-base-laion5B-s13B-b90k	0.3	5.0	63.3	69.8	79.3	52.7	52.8	64.5	35.2	18.2	43.3	49.9	50.6	67.1
	M-CLIP/XLM-Roberta-Large-Vit-L-14	0.9	0.4	62.2	68.7	78.4	53.0	53.4	65.0	35.4	18.3	43.7	52.9	53.6	70.4
	M-CLIP/XLM-Roberta-Large-Vit-B-32	0.7	0.4	60.5	66.9	76.7	51.8	52.2	63.9	34.4	17.8	42.4	50.7	51.4	67.9
	sentence-transformers/clip-ViT-B-32-multilingual-v1	0.3	1.1	60.3	66.7	76.6	51.5	51.8	63.6	33.3	17.2	41.1	48.9	49.6	65.9

Table 5: Correlation between CLIPScore values and human rankings, considering a set of different English (top rows) and multilingual (bottom rows) CLIP models. "Size (B)" column contains the size of the model in billions of parameters, and the amount of training data in billions of image-caption instances.

		VICR			Expert			CrowdFlower			Composite		
		τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ
Related Work	BLEU1	57.9	63.7	74.0	32.2	32.3	40.4	17.9	9.3	22.3	45.8	46.2	63.0
	BLEU4	54.8	60.4	70.5	30.6	30.8	38.7	16.9	8.7	21.0	46.4	46.9	63.7
	CIDEr	63.1	69.8	79.3	43.6	43.9	54.3	24.6	12.0	29.3	48.1	48.8	65.0
	CLIPScore	60.7	67.1	76.9	51.1	51.5	63.1	34.4	17.8	42.4	50.6	51.3	67.9
	RefCLIPScore	66.3	73.3	82.2	52.0	52.4	63.7	36.4	18.8	44.7	56.8	57.6	74.7
	CLIP+CIDEr	66.8	73.8	82.6	53.1	53.4	65.3	33.9	17.5	41.8	54.3	55.1	72.2
	MID (Kim et al., 2022)	–	–	–	–	54.9	–	37.3	–	–	–	–	–
	InfoMetIC (Hu et al., 2023)	–	–	–	–	54.2	–	36.3	–	–	–	59.2	–
	InfoMetIC$^+$ (Hu et al., 2023)	–	–	–	–	55.5	–	36.6	–	–	–	**59.3**	–
	PR-MCS (Kim et al., 2023)	–	–	–	–	50.6	65.6	–	–	–	–	–	–
	VICR (Narins et al., 2024)	–	75.8	–	–	53.1	–	–	–	–	–	–	–
	PACScore (Sarto et al., 2023)	–	–	–	53.9	54.3	–	36.0	18.6	–	51.5	55.7	–
	RefPACScore (Sarto et al., 2023)	–	–	–	55.5	55.9	–	37.6	19.5	–	53.0	57.3	–
CLIPScore variants	English CLIPScore	67.4	74.4	83.1	56.3	56.6	68.4	38.5	19.9	47.1	55.1	55.9	72.8
	English RefCLIPScore	68.3	75.4	83.8	56.8	57.1	68.9	38.6	**19.9**	**47.3**	56.4	57.2	74.0
	English CLIP+CIDEr	67.6	74.8	83.3	56.0	56.4	68.5	35.6	18.4	43.8	53.9	54.7	71.7
	Mlaion CLIPScore	67.6	73.0	82.4	57.4	54.3	67.3	38.2	19.4	46.2	55.5	56.2	73.2
	Mlaion RefCLIPScore	69.1	74.6	83.6	58.1	55.0	67.9	**38.8**	19.7	46.9	**57.3**	58.1	**75.0**
	Mlaion CLIP+CIDEr	67.6	74.7	83.4	55.5	55.9	67.8	36.3	18.8	44.7	55.6	56.4	73.5
	Mlaion-F CLIPScore	68.7	75.4	84.1	59.8	57.1	70.2	37.8	19.3	45.9	47.4	48.0	64.7
	Mlaion-F RefCLIPScore	**69.7**	**76.5**	**84.8**	**60.2**	57.5	**70.6**	37.6	19.1	45.6	53.3	54.0	70.8
	Mlaion-F CLIP+CIDEr	68.5	75.8	84.2	57.3	**57.7**	70.0	35.8	18.5	44.0	52.5	53.2	70.0

Table 6: Comparison between published results and our best English, multilingual and finetuned (also multilingual) CLIPScore models, considering settings (a) without human references, (b) using human references, and (c) combining CIDEr with CLIPScore when using human references.

Results confirm that the original CLIPScore outperforms standard captioning metrics in all evaluated datasets, such as BLEU or CIDEr. The correlations consistently improve with RefCLIPScore, but the combination of RefCLIPScore with CIDEr only improved the smaller CLIP model (by previously published results from Qiu et al. (2023)), instead decreasing the performance in the cases involving the other CLIPScore variants.

The multilingual model competes head-to-head with the best English-only models, outperforming the previously published results for almost all the metrics, whether human references are considered or not. This competitive performance in both reference-free and reference-aided settings further solidifies the potential of multilingual CLIPScore.

Lastly, it is also interesting to note that our finetuned model outperformed the original multilingual LAION ViT-H model, and also Apple's best model across all CLIPScore variants, on both the VICR and Expert datasets, even without using references. The version of our model that uses ref-

erences achieved the best performance for these datasets, surpassing even specialized architectures such as VICR, InfoMetIC, and RefPACScore.

CLIPSCORE RESULTS	HC	HI	HM	MM
CLIP-32-B	56.4	99.1	96.9	73.8
Best English model	57.0	99.7	96.3	74.9
MLaion	57.8	99.7	96.2	73.6
MLaion-F	66.2	99.6	96.0	78.8
MLaion-F$_C$	65.8	99.6	97.0	76.7
MLaion-F$_P$	65.7	99.6	99.3	75.1

Table 7: Correlation between CLIPScore values and human rankings, considering a set of different English (top rows) and multilingual (bottom rows) CLIP models.

REFCLIPSCORE RESULTS	HC	HI	HM	MM
CLIP-32-B	64.8	99.7	96.4	73.9
Best English model	68.1	99.8	97.6	78
Mlaion	64.9	99.8	97.6	75.2
Mlaion-F	72.6	99.7	97.6	80.6
Mlaion-F$_C$	71.7	99.7	98.0	78.9
Mlaion-F$_P$	70.5	99.7	97.0	78.5

Table 8: Correlation between CLIPScore values and human rankings, considering a set of different English (top rows) and multilingual (bottom rows) CLIP models.

In Pascal-50S (Vedantam et al., 2015b), raters made pairwise preference judgments between pairs of sentences. There are 4K sentence pairs total, split evenly across four categories:

- HC: Two correct captions written by a human;
- HI: Two captions are human written, but one is wrong;
- HM: Two correct captions one caption is written by a human, one by an algorithm;
- MM: Two correct captions written by an algorithm.

For each pair, 48 human pairwise judgments of preferred captions were gathered. Following prior work, instead of computing correlation coefficients, we compute accuracy.

Tables 7 and 8 compare the top-performing English and multilingual models, including our fine-tuned version of the best multilingual model, on the Pascal-50S benchmark using CLIPScore and RefCLIPScore respectfully. The results show significant improvement after applying our fine-tuning strategy, particularly in the most challenging tasks (i.e., HC and MM, where both captions

are correct and written by a similar entity). Ablation experiments using model checkpoints trained solely with contrastive loss or Pearson loss (i.e., Fine-tuned model$_C$ and Fine-tuned model$_P$, respectively) demonstrated improvements over the original model, suggesting that both loss functions contribute to enhanced performance.

F   Multicultural Experiments

This appendix details the datasets and experimental settings that were considered for the tests including natively multilingual and multicultural data.

F.1   Settings for the XVNLI Experiments

Each instance in the XVNLI dataset contains an image-caption pair and a categorical label associated with the relationship between the pair. This label can be either (a) contradiction, (b) neutral, or (c) entailment. With basis on the labels, we defined three multilingual classification experiments under this scenario, leveraging concordant/discordant instances as illustrated in Figure 2:

Experiment 1: This setting only considers instances with the extreme label classes (i.e., contradiction and entailment), noting that some previous studies have pointed to the fact that SNLI-VE, from which XVNLI is derived, has some problems in the annotations for the neutral class (Kayser et al., 2021). We compare pairs of instances A and B with the same image, in which the label associated with A differs from the label associated with B. When computing CLIPScore values individually for the instances A and B, the order of the CLIPScore values should match the order of the labels (i.e., contradiction $<$ entailment).

Experiment 2: In a more challenging scenario, we can consider a larger set of instances and the ordering between the three possible labels (i.e. entailment $>$ neutral $>$ contradiction), i.e. including also the neutral class. Similarly to the previous case, by fixing an image and comparing pairs of captions associated with that image with different labels, we assess the matching of the order between the labels against the CLIPScore values.

Experiment 3: In this case, we also consider the three possible labels, but we now assess triples of instances A, B, and C from the dataset, sharing the same image. We only assume a correct classification when we achieve a perfect match between the order of the labels and the CLIPScore values.

Figure 3: Multilingual CLIPScore values for image-caption pairs featuring concepts biased to particular languages.

F.2 Settings for the MaRVL Experiments

In the case of the MaRVL dataset, each instance consists of a caption, a pair of images, and a Boolean label with the value *true* when the caption accurately matches the images, and *false* when the caption is incorrect (e.g., because its contents only describe at maximum one of the images instead of both). The data can be analyzed considering four instances at a time, sharing the same caption but featuring distinct pairs of images. MaRVL was designed in such a way that, within these four instances, two of them are labeled as *true* while the remaining two are labeled as *false*. We consider two multilingual classification experiments under this scenario, defined as follows:

Experiment 1: We draw comparisons between pairs of instances with distinct labels. For the instance labeled as *true*, we compute the CLIPScore values for both images associated with the caption and select the maximum, obtaining the score for the image that best aligns with the caption. Conversely, we perform a similar computation for the instance labeled as *false*, this time choosing the minimum CLIPScore value, which results in the score for the image that least aligns with the caption, presumably the incorrect image. The maximum CLIPScore value in an instance labeled as *true* should be higher than the minimum CLIPScore value of an instance labeled as *false*.

Experiment 2: In a more challenging scenario, we consider sets of four instances sharing the same caption, and decide on a correct classification only if all maximum CLIPScore values of the *true* instances are higher than all the minimum CLIPScore values of the *false* instances.

G A Qualitative Study with Captions Featuring Cluturally Related Concepts

We performed a small qualitative study on image-caption pairs that feature concepts where some languages should exhibit a particular bias (e.g., *codfish* in the case of Portugal, *paella* for Spain, *beer* for Germany, *croissant* for France, *ushanka* for Russia, and *cheongsam* for China). We attempted to see if the multilingual CLIPScore could distinguish between two plausible captions, where one mentions a specific concept that should better match the image. Figure 3 shows that the multilingual CLIPScore is indeed capable of distinguishing nuanced multicultural concepts and favouring culturally specific captions over generic ones.

H Additional Classification Results

Table 9 presents classification results on the different tasks from the VALSE dataset, separately for each of the considered languages and comparing CLIP models of different sizes under different finetuning strategies (i.e., without model finetuning, considering only the contrastive loss, only the Pearson correlation loss, or the combined loss function). The results show that the smaller CLIP model can achieve significantly higher gains from finetuning, approaching the performance of the larger CLIP model. Better results are, in general, obtained when considering the combined loss function.

In turn, Table 10 presents correlation results on the VICR dataset, separately for each language and comparing the same two CLIP models under the different finetuning strategies. Results again show that the smaller CLIP model approach the performance of the larger model, with better results consistently obtained when considering the combined loss function.

Table 9 header: Model | Finetuning | **Existence** quantifiers | **Plurality** number | **Counting** balanced sns. adv. | **Sp.Rel** relations | **Action** repl. actant swap | **Coreference** standard clean | **Foil-it!** | **Avg.**

Lang	Model	Finetuning	Existence quantifiers	Plurality number	Counting balanced	Counting sns.	Counting adv.	Sp.Rel relations	Action repl.	Action actant swap	Coref. standard	Coref. clean	Foil-it!	Avg.
English	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	**81.6**	**76.3**	**68.3**	**75.8**	66.1	**66.5**	86.0	**62.1**	46.9	42.3	95.0	**69.7**
		Pearson	80.8	75.9	67.1	74.7	65.8	64.7	**87.5**	62.0	46.9	41.3	94.8	69.2
		Contrastive	75.4	75.3	66.7	74.4	**66.9**	61.5	87.0	58.5	47.6	44.2	**95.2**	68.4
		None	74.7	69.6	66.9	72.4	65.3	61.7	86.7	56.1	51.3	45.2	94.2	67.6
German	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	78.8	**71.7**	68.4	**74.6**	58.5	**57.2**	77.6	62.1	53.0	43.3	**94.9**	**67.3**
		Pearson	**79.8**	71.1	**68.9**	73.7	55.3	56.8	77.2	**62.5**	**54.7**	45.2	94.2	66.8
		Contrastive	64.8	71.0	66.2	72.7	61.9	54.6	76.1	59.2	48.9	45.2	94.3	65.0
		None	69.3	69.2	68.8	72.6	56.6	53.3	75.9	57.4	53.4	44.2	91.9	64.8
French	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	80.2	**75.1**	**69.7**	72.4	61.4	**56.1**	75.5	**61.4**	48.6	48.1	**94.5**	**67.5**
		Pearson	**82.2**	73.4	69.0	**72.8**	56.9	55.9	75.8	61.3	47.1	47.1	94.0	66.8
		Contrastive	69.9	73.1	66.6	70.7	**63.5**	55.5	73.6	57.3	49.6	46.2	**94.5**	65.5
		None	70.7	65.7	66.0	69.4	53.8	53.3	75.9	53.6	53.8	50.0	93.4	64.2
Spanish	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	84.2	**73.0**	69.2	**75.1**	64.4	58.9	**80.2**	**64.6**	44.8	40.4	91.9	**67.9**
		Pearson	**85.1**	72.3	**69.6**	73.2	61.2	58.3	78.9	63.6	**47.0**	40.4	91.2	67.4
		Contrastive	74.7	66.5	66.8	73.2	**65.4**	58.7	78.7	61.7	41.9	38.5	**92.9**	65.7
		None	75.8	66.5	68.2	67.2	61.8	**61.3**	79.0	61.5	42.9	**46.2**	91.1	65.6
Chinese	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	78.0	69.3	**69.0**	72.2	65.4	**55.7**	74.1	63.8	48.0	49.0	91.6	66.9
		Pearson	**82.0**	68.5	68.3	72.2	63.4	52.7	**75.2**	**64.7**	49.2	**53.8**	90.8	**67.3**
		Contrastive	69.1	**69.3**	68.4	70.2	**66.4**	53.8	73.6	59.5	48.4	50.0	**92.2**	65.6
		None	69.1	66.4	66.8	69.3	63.0	55.1	75.9	62.2	46.3	41.3	88.3	64.0
Portuguese	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	78.8	**74.3**	70.2	74.2	63.1	54.4	**79.0**	64.1	50.7	56.7	**93.7**	**69.0**
		Pearson	**80.4**	71.0	68.0	72.1	55.9	51.8	78.5	**64.5**	47.2	**57.7**	92.7	67.2
		Contrastive	68.3	72.6	65.7	71.7	62.5	53.3	76.2	60.5	50.8	54.8	93.6	66.4
		None	68.5	67.6	68.3	71.2	62.1	56.1	77.2	58.3	50.6	48.1	91.9	65.4
Italian	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	77.2	72.3	**68.5**	**75.0**	57.9	56.6	77.5	64.0	43.5	39.4	93.5	66.0
		Pearson	**77.8**	71.2	68.2	73.1	52.7	56.4	77.8	**64.8**	45.5	45.2	93.1	**66.0**
		Contrastive	61.4	**72.6**	64.5	71.7	60.1	56.8	77.5	61.2	46.9	44.2	**94.2**	64.6
		None	67.3	67.5	65.9	68.2	52.1	**58.7**	**78.4**	62.7	46.5	50.0	91.3	64.4
Russian	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	**79.2**	**74.4**	**67.6**	**73.3**	**62.4**	**57.0**	**74.8**	62.7	47.9	**47.1**	91.3	**67.1**
		Pearson	78.6	72.3	65.4	71.3	57.5	55.0	74.4	**63.4**	45.8	40.4	91.2	65.0
		Contrastive	65.5	74.1	65.6	70.3	61.8	55.3	74.1	59.6	**50.4**	42.3	**93.1**	64.0
		None	70.5	65.8	66.0	68.0	56.2	53.6	72.2	58.3	49.9	49.0	88.3	63.4
Korean	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	61.0	69.4	64.9	70.9	59.9	54.4	69.0	57.5	36.4	32.7	90.9	**60.6**
		Pearson	63.2	67.1	**65.3**	70.9	54.4	52.9	67.9	58.4	37.4	26.0	91.5	59.2
		Contrastive	48.5	**69.4**	63.8	68.2	**61.9**	52.1	69.1	55.5	35.6	35.6	**91.5**	59.2
		None	56.4	61.1	63.9	66.8	54.4	**57.4**	69.1	49.2	**39.3**	38.5	86.3	58.4
Dutch	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	78.2	**72.3**	68.5	74.6	61.2	53.3	75.5	60.4	48.3	42.3	93.6	66.2
		Pearson	**79.0**	70.3	66.6	72.7	56.0	53.3	75.9	**61.7**	49.3	46.2	93.1	65.8
		Contrastive	63.8	72.2	67.6	72.8	**61.9**	52.9	75.0	58.3	44.6	38.5	93.6	63.7
		None	64.4	66.5	62.8	67.2	49.2	55.1	75.9	59.2	46.6	47.1	92.9	62.5
Average	laion/CLIP-ViT-H-14-frozen-xlm-roberta-large-laion5B-s13B-b90k	Both	78,8	73	68,5	74,2	62,4	56,1	75,5	62,1	48	43,3	93,6	-
		Pearson	80,4	71,1	68	72,7	56,9	55	75,9	62,5	47	45,2	92,7	-
		Contrastive	68,3	72,6	66,6	71,7	62,5	54,6	75	59,2	48,4	44,2	93,6	-
		None	69,3	66,5	66,8	69,3	56,6	55,1	75,9	58,3	49,9	46,2	91,9	-

Table 9: Performance of multimodal models on the multilingual VALSE benchmark according to different metrics. **sns.** Counting small numbers. **adv.** Counting adversarial. **repl.** Action replacement. **Sp.rel.** Spatial relations.

| | Multilingual CLIP ViT-B | | | | | | | | | Multilingual CLIP ViT-H | | | | | | | | |
| | Contrastive | | | Pearson | | | Combined | | | Contrastive | | | Pearson | | | Combined | | |
	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ	τ_b	τ_c	ρ
ENG	65.8	72.2	81.5	66.7	73.2	82.3	67.2	73.5	82.6	68.6	75.0	83.8	64.5	70.6	80.6	68.7	75.4	84.1
GER	65.1	71.4	80.8	65.6	72.1	81.4	66.5	72.6	81.9	**68.0**	74.3	83.2	62.9	69.1	79.3	**68.0**	74.8	83.6
FRE	65.4	71.7	81.1	66.0	72.4	81.7	66.7	72.9	82.1	**68.0**	74.4	83.3	62.8	69.0	79.3	**68.0**	74.7	83.6
SPA	65.1	71.3	80.8	65.9	72.6	81.7	66.4	72.7	81.9	67.8	74.3	83.2	62.4	68.6	78.9	67.8	74.5	83.5
CHI	64.4	70.6	80.2	64.7	71.3	80.7	65.7	71.9	81.3	67.4	73.8	82.8	62.1	68.3	78.6	67.4	74.0	83.1
POR	65.2	71.5	80.9	65.7	72.1	81.4	66.5	72.7	81.9	67.9	74.3	83.2	62.7	68.9	79.2	67.9	74.6	83.5
ITA	65.0	71.3	80.7	65.6	72.2	81.4	66.3	72.6	81.8	**67.9**	74.3	83.2	62.5	68.7	79.0	67.9	74.6	83.5
RUS	64.6	70.8	80.3	65.1	71.6	80.9	65.9	71.9	81.4	67.4	73.8	82.8	62.7	68.9	79.2	67.6	74.2	83.2
KOR	63.8	70.0	79.6	64.3	70.8	80.2	65.1	71.2	80.7	67.3	73.7	82.7	62.1	68.3	78.6	67.4	74.1	83.1
DUT	65.2	71.4	80.8	65.8	72.4	81.6	66.6	72.8	82.0	**68.1**	74.5	83.4	62.9	69.1	79.3	**68.2**	74.9	83.8
AVG	65.0	71.2	80.7	65.5	72.1	81.3	66.2	72.5	81.8	67.8	74.2	83.2	62.8	68.9	79.2	67.9	74.6	83.5

Table 10: Correlation between CLIPScore values and human rankings, using multimodal models finetuned with different loss functions. The last row presents macro-averaged correlation results across all the languages (including English). Non-English results above the English baseline are shown in bold.