DanmuCloak: A Script-Based Benchmark for Moderation-Relevant Cloaked Expressions in Chinese Danmu

Abstract

Online moderation increasingly struggles with evasive language, yet existing benchmarks focus primarily on overt toxicity or synthetic perturbations rather than hidden meaning recovery. We present DanmuCloak[1], a benchmark for moderation-relevant cloaked expressions in Chinese danmu with a GTVH-inspired script framework for computational moderation. Sourced from real-world Bilibili comments that were visible on the platform at collection time, DanmuCloak contains 1,054 items spanning phonological, orthographic, semantic, and mixed cloaking strategies that are likely challenging for standard moderation pipelines. It supports binary MRC expression detection and positive-only cloaked type classification, evaluating both the presence and encoding of hidden meanings. Experiments with frontier LLMs reveal a clear performance gap: binary detection is tractable, whereas mechanism classification remains substantially harder. GTVH-informed prompts often help but remain non-monotonic, and a script-informed ablation shows that explicit adjudicated script fields improve type macro-F_1 by +0.15 to +0.23 across three models. These results identify script-level recovery as the central bottleneck in hidden-meaning interpretation, making DanmuCloak a foundation for future benchmarks utilizing richer semantic, phonological, and visual scripts.

1 Introduction

Online content moderation increasingly struggles with evasive language, where users preserve toxic intent while altering the visible form of an expression to appear benign. Such cases bypass keyword filters and toxicity detectors because the sensitive meaning is not always encoded in explicit lexical tokens. This problem becomes even more salient in Chinese digital discourse: dense homophony, character variation, alphanumeric substitution, code-mixing, and rapidly evolving Internet slang empower users to create surface forms that remain intelligible to the "insider" audience but opaque to standard detection pipelines (Davidson et al., 2017; Zampieri et al., 2019; Lu et al., 2023; Xiao et al., 2024; Guo et al., 2025). We formalize these instances as **moderation-relevant cloaked (MRC) expressions**—indirect surface forms that appear benign or ambiguous but activate a concealed target reading under pragmatic context.

Recent work has begun to examine Chinese cloaking through homophonic perturbation, emoji replacement, phonetic cloaking replacement, and multimodal toxic variation (Xiao et al., 2024; Wu et al., 2025; Guo et al., 2025; Yang et al., 2025). While these works show that disguised hostility compromises NLP system robustness, existing resources still tend to treat cloaking as localized character perturbations or input noise. Consequently, they overlook the *relational structure* of linguistic evasion: how an innocuous surface reading cues a hidden sensitive target, and what specific pathways link the two. This distinction matters because cloaked language is not merely corrupted text; its decoding hinges on a structured relation between the visible signifier and the implicit, targeted signified.

We study this problem in the communicative ecology of Chinese *danmu* (time-synchronized bullet-screen comments). Danmu is not merely another social-media text format; it represents a fragmented, interactional stream of user discourse heavily dependent on video timing, subtitles, and platform-specific norms (He et al., 2017; Chen et al., 2017; Zhang and Cassany, 2019). These properties complicate automated moderation. In stand-up comedy clips—where punchlines, audience reactions, and socio-cultural parodies already invite layered interpretations—users frequently com-

---

[1] Anonymous code repository: https://anonymous.4open.science/r/anonymous_code-57CD/README.md.

bine multiple cloaking mechanisms (e.g., phonetic drifting, graphic manipulation, and semantic allusions) to negotiate content boundaries. This turns danmu into an ideal testbed for evaluating whether language models can recover hidden moderation-relevant meanings from minimal textual evidence.

To model these surface–hidden alignments, we adapt script opposition from the General Theory of Verbal Humor (GTVH) as a cognitive scaffold for content moderation (Raskin, 1985; Attardo and Raskin, 1991; Attardo, 1994, 2017). While MRC expressions are not inherently humorous, linguistic evasion and humor share a useful structural similarity: both rely on the coexistence of two overlapping yet incompatible semantic schemas. We leverage GTVH scripts to formalize the contrast between the overt benign reading and the concealed target, using the theory's *Logical Mechanism* (LM) to categorize the linguistic pathways connecting them. Grounding our benchmark in this framework enables us to transcend binary detection and evaluate whether models can characterize the cloaking mechanism and trace the mapping from surface to hidden meanings.

Based on this paradigm, we introduce `DanmuCloak`, a benchmark comprising 1,054 authentic Chinese danmu comments (536 MRC-positive items and 518 negatives) from Bilibili stand-up comedy videos. The benchmark evaluates two tasks: detecting whether a comment contains an `MRC expression` and classifying its `cloaked type` among five mechanisms: Homophonic Hanzi Replacement (HHR), Alphanumeric Replacement (AR), Glyph/Delimiter Manipulation (GDM), Mixed Replacement (MR), and Semantic Indirection (SI). We evaluate six frontier model variants from five LLM families under four prompt conditions and conduct a script-informed ablation using adjudicated script fields. Our results show that while models can perform competitively on MRC detection, mechanism classification remains substantially harder. The script-informed ablation yields substantial macro-F_1 gains (+0.15 to +0.23), indicating that script recovery is a key bottleneck in hidden-meaning interpretation.

Our main contributions are threefold:

- We introduce `DanmuCloak`, a benchmark for MRC expressions in Chinese danmu, built from authentic platform comments. The benchmark targets naturally occurring phonological, orthographic, alphanumeric, semantic, and mixed cloaking strategies while distinguishing MRC from benign slang, metaphor, and playful masking.

- We operationalize a GTVH-inspired script framework for computational moderation, using script opposition and related abstractions to represent the relation between surface form, hidden target, and cloaking mechanism within a unified annotation and evaluation setup.

- We benchmark six frontier model variants from five LLM families under four prompt conditions and show that script-aware prompting can improve detection, while explicit script information yields substantial gains in cloaked-type classification. These findings identify script-level recovery as a central bottleneck for moderation-oriented hidden-meaning interpretation.

2 Related Work

2.1 GTVH and Humor Studies

The General Theory of Verbal Humor (GTVH) explains verbal humor through a hierarchy of Knowledge Resources, including script opposition (SO), logical mechanism (LM), situation (SI), target, narrative strategy, and language (Attardo and Raskin, 1991; Attardo, 1994, 2017). In script-based humor theory, a script refers to structured knowledge associated with a word, situation, event, or cultural frame (Raskin, 1985; Attardo, 1994). For DanmuCloak, SO, LM, and SI are most relevant: SO captures the contrast between two scripts, LM describes the mechanism linking them, and SI specifies the contextual assumptions needed for interpretation. These concepts are highly effective for deconstructing cloaked expressions that share a parallel surface–hidden structure, wherein an innocuous visible reading coexists with a recoverable target reading.

Subsequent work extends GTVH to audiovisual and multimodal humor (Tsakona, 2009; Balirano and Corduas, 2008; Chen and Wang, 2022), demonstrating that incongruity can span multiple modalities. For our benchmark, however, we focus on textual danmu, where cloaking is organized primarily through semantic and phonetic scripts and their interplay. This adaptation proves that script-based analysis extends beyond canonical jokes, a capability that `DanmuCloak` operationalizes within a text-based moderation setting. Relevance-theoretic

accounts, another influential approach to humor, effectively explain the contextual inference of implicit meanings (Sperber and Wilson, 1995; Wilson and Sperber, 2004; Yus, 2016) and have informed NLP research on metaphor and implicit toxicity (Zeng and Li, 2022; Sato et al., 2025; Chen and Wang, 2025). For benchmark construction, however, GTVH is more practically viable because its Knowledge Resources decompose layered meaning into discrete, annotatable components that align well with our annotation and prompt design. Although some computational work has examined claims associated with script theories (Skalicky and Attardo, 2025), GTVH has not yet been widely formalized as an NLP scaffold; therefore, we adapt it as a compact structural framework.

2.2 Humor, Cloaking, and Moderation in NLP

Computational humor research demonstrates that non-literal language remains a key challenge for natural language understanding, requiring pragmatic inference and context resolution (Yang et al., 2015; Gupta et al., 2021). Recent work explores tasks such as humor generation (Loakman et al., 2025), pun detection (Zangari et al., 2025), stand-up routine identification (Romanowski et al., 2025), multimodal humor (Baluja, 2025), and pun translation (Ma et al., 2025). These studies indicate that frontier LLMs often process layered meaning shallowly, struggling when interpretation relies on deliberate ambiguity or implicit cultural scripts.

Within content moderation, a parallel challenge manifests as linguistic evasion. Prior literature primarily formalizes this problem as an issue of text perturbation or adversarial robustness. For instance, Wu et al. (2025) and Guo et al. (2025) evaluate model vulnerabilities against character-level phonetic and homophonic mutations in offensive posts, while Yang et al. (2025) map multimodal variations across glyphs and emojis. Although these studies reveal how disguised toxic inputs challenge current systems, they mainly characterize surface variants rather than the relation between surface reading and hidden target, leaving semantic indirection less systematically modeled. This gap is especially relevant because robustness-oriented adaptation can lead to the overcorrection of normal Chinese expressions as toxic, rendering our benign-but-opaque negatives crucial for evaluating moderation-sensitive interpretation.

DanmuCloak occupies a distinct position at the intersection of these domains. Unlike humor benchmarks focused on funniness (Zangari et al., 2025; Xu et al., 2025), our framework is strictly moderation-centered, shifting the objective toward safety-relevant intent recovery. Concurrently, unlike existing moderation datasets that treat cloaking purely as input noise to be resisted (Wu et al., 2025; Guo et al., 2025), DanmuCloak frames linguistic evasion as a structured cognitive mapping between an overt benign script and a covert sensitive target. Sourced from the synchronized ecology of danmu rather than synthetic augmentations, our benchmark introduces a diagnostic challenge: separating authentic cloaking from benign slang, metaphors, or playful masking.

3 Data

3.1 Data Selection and Preprocessing

Rather than relying on pre-existing or synthetic perturbation datasets, we build DanmuCloak from real-world Chinese danmu collected from Bilibili, a major Chinese video-sharing platform. As these comments were naturally displayed on the platform at the time of collection, they represent authentic platform-visible cases rather than synthetic perturbations. We curated two video pools and converted their associated danmu files into a CSV-formatted master pool for subsequent selection.

For video selection, we prioritize stand-up comedy content, including fan-translated clips, local Chinese performances, punchline compilations, and commentary videos. This domain is selected because it inherently fosters the creative use of fandom jargon, contextual references, and punchline reinterpretation. These linguistic practices make danmu likely to contain more intricate forms of disguise, yielding hard cases in which offensive or sensitive intent may remain recoverable to insiders while avoiding more direct forms of detection.

Our master pool comprises two primary sources (Table 1). The first is a larger stand-up danmu collection derived from a single high-exposure Bilibili fansub source specializing in English stand-up comedy translation. Since *danmu* interactions reflect the secondary reception of translated content, this source is instrumental in capturing AR and MR cloaking—mechanisms that frequently emerge in response to cultural disparities and sensitive themes (e.g., political and sexual humor) that complement the thematic scope of Chinese stand-up. For this source, we included all videos within the May 2024 to January 2026 collection window.

Source	Role in master pool	Videos	Danmu
Stand-up collection	Fansub stand-up; broad coverage	126	45,327
Keyword supplement	Targeted sensitive-humor search	42	37,310
Total	Master pool total	168	82,637

Table 1: Raw-data sources underlying the 82,637-comment master pool used to construct DanmuCloak.

The second source is a *keyword supplement*, designed to enrich harder cases that may be underrepresented in the first source. Using an LLM-assisted keyword planning sheet, we conducted topic-oriented searches targeting politically charged, gender-related, racial, and taboo-humor contexts, and retained top candidate videos using popularity-based signals of view counts and danmu volume. This supplement increases the likelihood of observing HHR and toxic cloaked expressions within danmu interactions. The keyword list used for supplement collection was drafted with LLM assistance and then manually filtered by the authors; it should be understood as a heuristic expansion step rather than a neutral sampling procedure.

Collectively, these two sources were curated to prioritize mechanism coverage over mere data volume. From a resulting master pool of 82,637 comments, the first author manually extracted 1,054 candidate cases following the selection criteria detailed in Appendix B. The candidate set was designed to select difficult MRC cases as many as possible while retaining hard negatives and potentially confusable non-positive items. Item labels were not pre-determined at selection time, but assigned only through the subsequent annotation and adjudication process. The resulting benchmark is therefore designed as a curated diagnostic set for interpretive moderation rather than as a naturally distributed sample of platform traffic. The 1,054-item candidate set was then passed to the annotation procedure described below.

3.2 Annotation Procedure

The candidate set was annotated through a two-stage process involving three annotators. All annotators hold Master's degrees, have training in linguistics or translation studies, and are familiar with Bilibili danmu discourse.

Label schema. Stage 1 is a binary detection task. A danmu is labeled positive if it contains an MRC expression: a manipulated surface form that avoids a sensitive or filterable target, intensifies offensiveness through a safer-looking variant,

or combines both functions. These correspond to three annotation rationales—evasive avoidance, offensive intensification, and hybrid evasion—but all require a recoverable surface-to-hidden mapping rather than mere offensiveness, topic sensitivity, or use of informal slang. This criterion prevents ordinary toxicity from being treated as cloaking unless the surface form itself masks or redirects the target reading. Negative items include ordinary metaphors, standard slang, benign joking or abbreviation, direct insults without clear cloaking, and non-toxic playful masking; these serve as hard negatives for distinguishing cloaking from broader non-literal or offensive language.

Stage 2 adds `cloaked type`, `extra knowledge`, and auxiliary script-based fields. `Cloaked type` captures the dominant surface–hidden mechanism using five labels adapted from prior taxonomies of Chinese phonetic cloaking (Guo et al., 2025): homophonic Hanzi replacement (HHR), pinyin-, alphabetic-, or digit-based alphanumeric replacement (AR), glyph or delimiter manipulation (GDM) through splitting, spacing, punctuation, or symbols, meaning-based semantic indirection (SI) through coded reference or indirect target activation, and mixed replacement (MR) for cases without a single dominant mechanism. The `extra knowledge` label records whether stable interpretation requires background knowledge, while script fields record the visible surface reading and intended hidden reading. The two prediction targets are MRC expression and `cloaked type`; `extra knowledge` supports post-hoc analysis, and script annotations are used only in the supplementary ablation. Fuller label details are provided in Appendix C.

Workflow and adjudication. In Stage 1, three annotators independently labeled MRC expression after a calibration round based on the written guidelines, using a standardized Excel annotation sheet. Inter-annotator agreement was computed before discussion, yielding a Fleiss' kappa of 0.697 (Fleiss, 1971). Provisional labels were derived using a 2-of-3 majority rule, and 239 non-unanimous cases were then reviewed through discussion and adjudication. The final Stage 1 output contains 1,054 items, including 536 positive and 518 negative cases.

In Stage 2, the 536 Stage 1 positive items were further annotated for `cloaked type` and `extra knowledge` by the first author and two Stage 1 an-

Figure 1: Annotation workflow. Stage 1 uses three-way binary annotation to identify MRC expressions and construct the binary benchmark. Stage 2 labels positive items for cloaked type, extra knowledge, and reviewed script fields.

notators. Fleiss' kappa (Fleiss, 1971) on the raw pre-discussion labels was 0.783 for `cloaked type` and 0.530 for `extra knowledge`. Provisional labels were again derived using a 2-of-3 majority rule. In total, 243 cases were non-unanimous on at least one Stage 2 dimension and were resolved through discussion and adjudication.

For the script-based fields, we used a prefill-and-review workflow: the first author prefilled the proposed surface–hidden script pairs, and two annotators reviewed them before final adjudication. Further methodological rationale for the two-stage design, disagreement patterns, and the script-field workflow is provided in Appendix C.

3.3 Dataset Characteristics

The final DanmuCloak benchmark contains 1,054 annotated danmu items, including 536 positive and 518 negative cases, yielding a near-balanced binary benchmark. Within the positive subset, `cloaked type` is unevenly distributed: HHR is the largest category, followed by AR, while SI, MR, and GDM are less frequent. We retain this skew to preserve the natural distribution of cloaking mechanisms in authentic danmu rather than impose an artificially balanced subtype inventory; it likely also reflects non-uniform user preferences among available cloaking strategies in platform discourse.

The `extra knowledge` label further indicates that benchmark difficulty is not reducible to surface masking alone: 204 positive items require background knowledge for stable interpretation. Table 2 summarises the final label distribution.

4 Experiments

4.1 Experiment Setup

Our experimental study has three components: a main benchmark on `MRC expression` detection and `cloaked type` classification, a supplementary script-informed ablation, and post-hoc error analysis of prompt effects and model failures.

Dimension	Label	Count
MRC expression	Positive	536
	Negative	518
cloaked type	HHR	254
	AR	121
	SI	80
	MR	42
	GDM	39
extra knowledge	0	332
	1	204

Table 2: Final label distribution in DanmuCloak after adjudication. `cloaked type` and `extra knowledge` are defined only for the 536 gold-positive items.

Prompt Design and Progression We evaluate models under a unified single-item prompting framework. Each input consists of one `danmu_text`, and each model is required to return exactly one structured JSON object with two fields: `MRC expression` and `cloaked type`. Video titles, which were used during human annotation only as minimal auxiliary context for disambiguation, were excluded from model input to keep the benchmark focused on recovering cloaked meaning from the danmu itself rather than from potentially confounding topic-level cues.

We test four prompts that preserve the same task, label space, input unit, and output schema, while varying the degree of interpretive structure provided: (1) *Std* defines the task and label inventory only; (2) *Script-Std* adds explicit instructions to distinguish the surface reading from the concealed target; (3) *Script-CoT* structures the decision process around the surface-hidden script relation before the final JSON decision; and finally, (4) *GTVH* provides the strongest theory-informed scaffold for script relation and offers the most granular guidance on mechanism selection. This progression aims to test whether increasingly explicit guidance on dual readings and cloaking-type distinctions improves model performance. Full prompt templates are included in the anonymous supplementary repository.

In addition to the main no-script setting, we

Model	MRC expression detection				cloaked type classification		
	Best Prompt	Acc.	BAcc.	F1	Best Prompt	Type Acc.	Type F1
GPT-5.4	*GTVH*	0.673	0.673	0.663	*Script-CoT*	0.422	0.424
GPT-5.5	*Script-CoT*	0.738	0.739	0.734	*Script-CoT*	0.562	0.550
Claude Sonnet 4.6	*Std*	0.666	0.669	0.610	*Std*	0.373	0.416
DeepSeek-V4-Flash	*GTVH*	0.600	0.594	0.699	*Std*	0.347	0.339
Gemini-3-Flash-Preview	*GTVH*	**0.732**	**0.730**	**0.766**	*Std*	**0.638**	**0.592**
Qwen3.6-Plus	*Script-CoT*	0.735	0.736	0.729	*Script-CoT*	0.534	0.445

Table 3: Main non-thinking results on DanmuCloak. For each model, we report the best-performing prompt variant selected post hoc for diagnostic comparison on the primary binary task (`MRC expression`) and positive-only `cloaked type` classification.

Model	Condition	Type Acc.	Type Macro-F1
Gemini-3-Flash-Preview	No-script	0.632	0.589
Gemini-3-Flash-Preview	With-script	**0.819**	**0.740**
Qwen3.6-Plus	No-script	0.392	0.381
Qwen3.6-Plus	With-script	**0.692**	**0.588**
GPT-5.5	No-script	0.394	0.407
GPT-5.5	With-script	**0.700**	**0.635**

Table 4: Script-informed ablation on the 536 gold-positive items, comparing no-script and with-script conditions for `cloaked type` classification.

include a supplementary script-informed ablation that assesses whether making script information explicit for each item improves *cloaked type* identification. Since script fields are annotated only for Stage 2 positive items, this condition is restricted to the positive subset. We use *Script-Std* as the base prompt because it already operationalizes the surface–hidden distinction central to the script fields without adding the heavier theoretical framing of *GTVH* or the staged-reasoning effects of *Script-CoT*. To keep the setup comparable to the main experiment, the ablation uses the same non-thinking model setting and JSON output schema, with adjudicated script fields appended after the danmu text as the only input change. Although models still output both `MRC expression` and `cloaked type`, evaluation is conducted primarily on `cloaked type`, while the `MRC expression` output is retained only for diagnostic purposes. The script-informed ablation should therefore be interpreted as a gold-script diagnostic upper bound rather than as a deployable moderation setting.

Tested Models and Evaluation. We benchmark six non-thinking model variants drawn from five prominent LLM families: GPT, Gemini, Claude, Qwen, and DeepSeek. Here, "non-thinking" refers to direct response generation without enabling any explicit reasoning, thinking, or extended deliberation mode exposed by the corresponding API. The evaluated models are GPT-5.4, GPT-5.5, Gemini-3-Flash-Preview, Claude Sonnet 4.6, Qwen3.6-Plus, and DeepSeek-V4-Flash. This selection spans multiple widely used commercial and multilingual model families, reducing dependence on any single provider or model lineage. Across all models, we keep the input unit, prompt variants, label space, and JSON output schema fixed. To control decoding variation, we use temperature-0 settings across the retained non-thinking runs, while keeping top-p at the provider default for all six models.[2]

Primary evaluation is conducted on the full 1,054-instance benchmark in the core no-script setting. For each model and prompt configuration, we extract the two required JSON fields for evaluation. `MRC expression` is assessed using accuracy, balanced accuracy,[3] precision, recall, and F1-score. `cloaked type` is evaluated only on the 536 gold-positive instances, using type accuracy and macro-F1. When transient API-level failures occurred, we reran only the affected items under identical model and decoding settings while retaining successful predictions unchanged; all such cases are documented in the run log.

The script-informed ablation is conducted on a representative subset of models—Gemini-3-Flash-Preview, GPT-5.5, and Qwen3.6-Plus. These models were selected because they are the top three systems on the main task by F1-score (Table 3), while also covering both English- and Chinese-dominant model families and the most recent retained GPT model. The ablation compares each model's existing no-script *Script-Std* predictions against a matched with-script condition on the same gold-positive subset, and is evaluated primarily on

---

[2]We retain provider-default top-p settings because provider APIs differ in whether such parameters are exposed for manual control. Exact API-facing model identifiers, access dates, decoding settings, and prompt templates are reported in the anonymous supplementary repository.

[3]Balanced accuracy is reported as a complementary metric under the near-balanced binary label distribution.

`cloaked type` identification.

4.2 Results and Analysis

Main results. Across non-thinking models, Gemini-3-Flash-Preview delivered the strongest overall performance on the main benchmark (Table 3). For `MRC expression` detection, its best result was obtained under *GTVH*, reaching an F1 of 0.766. For `cloaked type` classification on the 536 gold-positive items, its best result came from the *Std* prompt, with a type macro-F1 of 0.592 and a type accuracy of 0.638. This difference is important: prompts that are strongest for binary detection are not always the strongest for fine-grained mechanism classification.

Within the GPT family, GPT-5.5 clearly outperformed GPT-5.4 on the binary main task. Its best `MRC expression` result was obtained under *Script-CoT* (F1 = 0.734), compared with 0.663 for GPT-5.4. The same prompt also gave GPT-5.5 its best `cloaked type` result, with a type macro-F1 of 0.550. This suggests that for newer GPT models, moderate interpretive structuring around opposition and hidden reading is more effective than either the plain baseline or the heaviest theory-loaded prompt.

Prompt effects were not uniform across providers. Gemini remained strong under all four prompt variants, with only limited variation across them. By contrast, Qwen3.6-Plus and GPT-5.5 both benefited most from *Script-CoT*. DeepSeek-V4-Flash showed a different profile again: *GTVH* gave it the highest recall on the binary task, but also produced much weaker mechanism classification, indicating that aggressive positive prediction does not translate into stronger type discrimination. Claude Sonnet 4.6, meanwhile, performed best under the simplest *Std* prompt, suggesting that heavier interpretive structuring does not uniformly help across model families.

More broadly, `cloaked type` classification remained consistently harder than binary detection. Even the strongest non-thinking result on the positive subset stayed below 0.60 macro-F1. This gap supports the benchmark design: determining whether a danmu contains a moderation-relevant cloaked expression is easier than identifying the dominant mechanism by which the expression is cloaked. Prompt effects are helpful but non-monotonic: *Script-CoT* is the most consistently helpful prompt for `cloaked type` classification, whereas *GTVH* more often yields the strongest bi-

nary `MRC expression` results. Full prompt-level results and discussion are reported in Appendix E.

Script-informed ablation. Table 4 shows that explicit script fields substantially improve `cloaked type` identification across all tested models under a gold-script diagnostic upper-bound setting. For Gemini-3-Flash-Preview, type macro-F_1 and accuracy increase by +0.151 and +0.187, respectively. Qwen3.6-Plus yields gains of +0.207 in macro-F_1 and +0.300 in accuracy. GPT-5.5 exhibits the largest absolute improvements, with macro-F_1 rising by +0.228 and accuracy by +0.306. These results reveal that script annotations materially enhance the models' capacity to recover the underlying cloaking mechanism under idealized access to adjudicated script information. The ablation also highlights why the benchmark remains formidable in the no-script setting. We select *Script-Std* over the empirically superior *Script-CoT* to isolate the direct impact of explicit script data under a lighter, controlled prompt scaffold. This ensures that observed improvements stem from the appended script fields rather than multi-step procedural reasoning. Without these fields, models—especially GPT-5.5 and Qwen3.6-Plus—struggle to generate stable mechanism labels, a failure mode sharply mitigated by introducing script information. This divergence reveals that the definitive bottleneck lies not in navigating our type taxonomy, but in recovering the script opposition from sparse danmu text. For practical moderation, this underscores that script-level interpretive evidence is highly valuable for automated explanation, failure analysis, and human-in-the-loop review workflows.

Post-hoc error analysis We leverage `extra knowledge` (EK) to diagnose model failures across varying prompting and input conditions. For the `MRC expression` detection task, false negative errors are dominated by two recurrent categories: HHR with EK=0 ($n = 274$ model-instance misses) and SI with EK=1 ($n = 150$). This shows that task difficulty stems both from compact internet slang or neologisms that require implicit cultural decoding and from expressions whose hidden meaning depends on source-video understanding, such as stand-up comedy punchlines. False negatives frequently occur in short English acronyms and Chinese homophonic abuse—such as English *omfg* or the near-homophone 糙 [*cao1*, 'rough'] for 操 [*cao4*, 'fuck']—as well as SI cases whose surface forms are everyday language but whose offensive

Figure 2: Post-hoc error profiles of the retained non-thinking models in their best-prompt main-task runs. Left: false-negative (FN) and false-positive (FP) counts for `MRC expression` detection. Right: recurrent type-error buckets, grouped by gold `cloaked type` and whether stable interpretation requires extra knowledge (EK).

meanings emerge only through contextual interpretation. Conversely, false positives repeatedly over-flag benign code-mixed expressions and direct, non-cloaked insults that fall outside the benchmark definition of MRC. This binary asymmetry is also reflected across models in Figure 2A: Claude Sonnet 4.6 is strongly FN-heavy, whereas DeepSeek-V4-Flash is more FP-heavy.

A related but not identical pattern recurs in `cloaked type` classification. The dominant error bucket is again HHR with EK=0 ($n = 520$ aggregated type errors), but the distribution is broader than in binary detection: AR with EK=0 is the second-largest bucket ($n = 231$), followed by HHR with EK=1 ($n = 203$), SI with EK=1 ($n = 186$), and MR with EK=1 ($n = 170$). In the binary task, failure to recover hidden meaning often leads models to dismiss compact expressions as routine internet language and predict a negative label. In `cloaked type` classification, by contrast, the same failure more often leads to mechanism confusion: models may recognize that a positive hidden meaning is present, but still fail to recover the correct surface–hidden relation strongly enough to distinguish lightweight substitution from indirectness or mixed mechanisms. Figure 2B shows that these concentrations recur across the retained non-thinking models, with HHR+EK0 as the clearest shared bottleneck and SI/MR+EK1 as the most persistent higher-inference error regions.

The script-informed ablation sharpens this di-

agnosis. Appending adjudicated script fields reduces recurrent HHR and AR errors across Gemini, GPT-5.5, and Qwen, with the largest gains concentrated in HHR with EK=0. Once script information is made explicit, the remaining hard cases shift toward MR, SI, and other inference-heavy items. Crucially, SI and MR remain the most persistent error regions, showing that explicit scripts cannot fully resolve implicature-like indirectness or complex interacting mechanisms, even when surface–hidden relations are partially scaffolded. A fuller script-conditioned comparison is reported in Appendix F, and representative qualitative examples are reported in Appendix G.

5 Conclusion

This work frames moderation-relevant cloaked language as a script-recovery problem rather than a surface perturbation problem alone. `DanmuCloak` exposes a consistent gap between binary `MRC expression` detection and fine-grained `cloaked type` classification, especially when hidden meanings involve indirectness, mixed mechanisms, or background knowledge. GTVH-informed prompting can improve performance, and adjudicated script information yields macro-F_1 gains of +0.15 to +0.23, identifying script-level recovery as a central bottleneck. Future work can extend this direction through richer GTVH-based, multimodal, and retrieval-augmented approaches to recovering latent surface–hidden relations.

Limitations

First, DanmuCloak is a diagnostic benchmark rather than a prevalence-estimating sample of platform traffic. Candidate construction begins from a much larger pool of real danmu comments, but the final benchmark prioritizes informative, confusable, and mechanism-revealing cases rather than random sampling from the full distribution. The benchmark is therefore intended to stress-test interpretive moderation on hard, moderation-relevant cloaked (MRC) expressions, not to estimate how frequently such expressions occur on Bilibili or on other platforms.

Second, the benchmark is platform- and genre-specific. The data come from Bilibili danmu in stand-up and humor-adjacent settings, where comments are short, fragmented, temporally synchronized with video, and often dependent on audio-visual cues. Our current evaluation is deliberately text-only: models do not receive full video, audio, subtitles, surrounding danmu streams, or performer cues. Some model errors may therefore reflect missing multimodal context rather than purely linguistic failure, and performance should not be interpreted as a direct estimate of full-pipeline moderation quality.

Third, the dataset and script fields involve structured human judgment. Candidate screening, later-stage adjudication, and script-field construction include substantial first-author involvement, and the script annotations used in the supplementary ablation remain partly interpretive, especially for borderline cases with more than one plausible surface–hidden decomposition. Relatedly, some labels, such as extra knowledge, are less stable than the core task labels. We mitigate this with multi-annotator adjudication and explicit guidelines, but the benchmark still reflects a curated interpretive analysis rather than a fully objective inventory of cloaking strategies.

Fourth, cloaking practices are dynamic. Homophonic variants, alphanumeric replacements, memes, intertextual references, and platform-specific references may shift over time. In addition, cloaking is shaped not only by lexical drift but also by anticipated moderation: the degree of self-censorship and the specific form of evasive expression may change with platform norms and perceived enforcement pressure. DanmuCloak should therefore be read as a time-bounded snapshot of a moving moderation problem rather than a closed taxonomy of all future cloaking behavior.

Fifth, the model evaluation is intentionally narrow. We study prompt-based inference with frontier general-purpose LLMs, and do not compare against rule-based homophone/keyword baselines, smaller encoder classifiers, platform-specialized toxicity systems, fine-tuned models, retrieval-augmented systems, or multimodal moderation pipelines. Prompt selection is performed on the same benchmark used for reporting results, so the best-prompt numbers should be interpreted as diagnostic upper-bound comparisons rather than fully held-out estimates. We therefore do not claim that the reported prompt/model combinations constitute an optimized deployment recipe.

Sixth, the script-informed ablation is a gold-script diagnostic upper bound, not a deployable moderation setting. The ablation uses human-adjudicated script fields that are not automatically available in realistic pipelines, and it shows the value of structured interpretive information under idealized access conditions. It should therefore be read as evidence about what kinds of hidden structure current models fail to recover unaided, not as evidence that the same gains are already achievable at scale in production systems.

Finally, the benchmark simplifies both moderation policy and data release conditions. Detecting an MRC expression is not equivalent to making an enforcement decision, which in practice also depends on policy scope, severity, target status, user intent, false-positive risk, and downstream human review. The benchmark also contains politically charged, gender-related, racial, and sexual content drawn from real user comments. For that reason, released materials should be treated as research data rather than as a moderation lexicon, and any public release should minimize user-identifying metadata, avoid unnecessary reproduction of harmful content, and respect platform-specific legal, copyright, and policy constraints.

Ethics and Data Statement

Content warning. This paper discusses offensive and discriminatory language that may be disturbing to some readers. This work studies moderation-relevant cloaked expressions in publicly visible Bilibili danmu. The source comments were accessible at the time of collection, but public visibility should not be interpreted as user consent for unrestricted redistribution. The released bench-

mark does not include usernames, profile information, user IDs, or other direct user identifiers; where possible, release materials should also avoid unnecessary video-level metadata or exact timestamps that could facilitate re-identification. Because the material includes politically charged, gender-related, racial, sexual, and otherwise offensive content, examples and glosses are presented only when necessary for task definition, annotation, or error analysis, following a minimization principle. Annotators were familiar with danmu discourse and worked with content that may contain offensive language. The benchmark is intended as a research resource for studying evasive language and moderation-relevant interpretation, not as a ready-to-deploy moderation lexicon, a tool for censorship or harassment, or a direct audit of platform enforcement decisions. Any public release should be used for research purposes only and should respect platform-specific legal, copyright, and policy constraints.

References

Salvatore Attardo. 1994. *Linguistic Theories of Humor*. Mouton de Gruyter, Berlin and New York.

Salvatore Attardo. 2017. The general theory of verbal humor. In Salvatore Attardo, editor, *The Routledge Handbook of Language and Humor*, pages 126–142. Routledge, London and New York.

Salvatore Attardo and Victor Raskin. 1991. Script theory revis(it)ed: Joke similarity and joke representation model. *Humor: International Journal of Humor Research*, 4(3-4):293–347.

Giuseppe Balirano and Marcella Corduas. 2008. Detecting semiotically-expressed humor in diasporic TV productions. *Humor: International Journal of Humor Research*, 21(3):227–251.

Ashwin Baluja. 2025. Text is not all you need: Multimodal prompting helps LLMs understand humor. In *Proceedings of the 1st Workshop on Computational Humor (CHum)*, pages 9–17, Online. Association for Computational Linguistics.

Xi Chen and Shuo Wang. 2025. Pragmatic inference chain (PIC) improving LLMs' reasoning of authentic implicit toxic language. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 5826–5841, Suzhou, China. Association for Computational Linguistics.

Yue Chen, Qin Gao, and Pei-Luen Patrick Rau. 2017. Watching a movie alone yet together: Understanding reasons for watching danmaku videos. *International Journal of Human–Computer Interaction*, 33(9):731–743.

Yuping Chen and Wei Wang. 2022. Translating English humor into Chinese subtitles: A semiotic perspective. *Perspectives: Studies in Translation Theory and Practice*, 30(3):454–470.

Thomas Davidson, Dana Warmsley, Michael Macy, and Ingmar Weber. 2017. Automated hate speech detection and the problem of offensive language. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 11, pages 512–515.

Dmitriy Dligach, Rodney Nielsen, and Martha Palmer. 2010. To annotate more accurately or to annotate more. In *Proceedings of the Fourth Linguistic Annotation Workshop*, pages 64–72, Uppsala, Sweden. Association for Computational Linguistics.

Joseph L. Fleiss. 1971. Measuring nominal scale agreement among many raters. *Psychological Bulletin*, 76(5):378–382.

Haotan Guo, Jianfei He, Jiayuan Ma, Hongbin Na, Zimu Wang, Haiyang Zhang, Qi Chen, Wei Wang, Zijing Shi, Tao Shen, and Ling Chen. 2025. Lost in pronunciation: Detecting Chinese offensive language disguised by phonetic cloaking replacement. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 2538–2550, Suzhou, China. Association for Computational Linguistics.

Aishwarya Gupta, Avik Pal, Bholeshwar Khurana, Lakshay Tyagi, and Ashutosh Modi. 2021. Humor@IITK at SemEval-2021 task 7: Large language models for quantifying humor and offensiveness. In *Proceedings of the 15th International Workshop on Semantic Evaluation (SemEval-2021)*, pages 290–296, Online. Association for Computational Linguistics.

Ming He, Yong Ge, Enhong Chen, Qi Liu, and Xuesong Wang. 2017. Exploring the emerging type of comment for online videos: DanMu. *ACM Transactions on the Web*, 12(1):1–33.

Jan-Christoph Klie, Richard Eckart de Castilho, and Iryna Gurevych. 2024. Analyzing dataset annotation quality management in the wild. *Computational Linguistics*, 50(3):817–866.

Tyler Loakman, William Thorne, and Chenghua Lin. 2025. Comparing apples to oranges: A dataset & analysis of LLM humour understanding from traditional puns to topical jokes. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 9502–9518, Suzhou, China. Association for Computational Linguistics.

Junyu Lu, Bo Xu, Xiaokun Zhang, Changrong Min, Liang Yang, and Hongfei Lin. 2023. Facilitating fine-grained detection of Chinese toxic language: Hierarchical taxonomy, resources, and benchmarks. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16235–16250, Toronto, Canada. Association for Computational Linguistics.

Yiran Rex Ma, Shan Huang, Yuting Xu, Ziyu Zhou, and Yuanxi Wei. 2025. Pun2Pun: Benchmarking LLMs on textual-visual Chinese-English pun translation via pragmatics model and linguistic reasoning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 4: Student Research Workshop)*, pages 331–354, Vienna, Austria. Association for Computational Linguistics.

Jonas Pfeiffer, Christian M. Meyer, Claudia Schulz, Jan Kiesewetter, Jan Zottmann, Michael Sailer, Elisabeth Bauer, Frank Fischer, Martin R. Fischer, and Iryna Gurevych. 2019. FAMULUS: Interactive annotation and feedback generation for teaching diagnostic reasoning. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP): System Demonstrations*, pages 73–78, Hong Kong, China. Association for Computational Linguistics.

Victor Raskin. 1985. *Semantic Mechanisms of Humor*. D. Reidel Publishing Company, Dordrecht.

Adrianna Romanowski, Pedro H. V. Valois, and Kazuhiro Fukui. 2025. From punchlines to predictions: A metric to assess LLM performance in identifying humor in stand-up comedy. In *Proceedings of the Workshop on Cognitive Modeling and Computational Linguistics*, pages 36–46, Albuquerque, New Mexico, USA. Association for Computational Linguistics.

Takuma Sato, Seiya Kawano, and Koichiro Yoshino. 2025. Pragmatic theories enhance understanding of implied meanings in LLMs. In *Proceedings of the 14th International Joint Conference on Natural Language Processing and the 4th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics*, pages 2458–2477, Mumbai, India. The Asian Federation of Natural Language Processing and The Association for Computational Linguistics.

Claudia Schulz, Christian M. Meyer, Jan Kiesewetter, Michael Sailer, Elisabeth Bauer, Martin R. Fischer, Frank Fischer, and Iryna Gurevych. 2019. Analysis of automatic annotation suggestions for hard discourse-level tasks in expert domains. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 2761–2772, Florence, Italy. Association for Computational Linguistics.

Stephen Skalicky and Salvatore Attardo. 2025. Testing humor theory using word and sentence embeddings. In *Proceedings of the 1st Workshop on Computational Humor (CHum)*, pages 58–62, Online. Association for Computational Linguistics.

Dan Sperber and Deirdre Wilson. 1995. *Relevance: Communication and Cognition*, 2 edition. Blackwell, Oxford.

Villy Tsakona. 2009. Language and image interaction in cartoons: Towards a multimodal theory of humor. *Journal of Pragmatics*, 41(6):1171–1188.

Deirdre Wilson and Dan Sperber. 2004. Relevance theory. In Laurence R. Horn and Gregory Ward, editors, *The Handbook of Pragmatics*, pages 607–632. Blackwell, Oxford.

Junqi Wu, Shujie Ji, Kang Zhong, Huiling Peng, Zhendong Xiao, Xiongding Liu, and Wu Wei. 2025. Enhancing Chinese offensive language detection with homophonic perturbation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 22660–22675, Suzhou, China. Association for Computational Linguistics.

Yunze Xiao, Yujia Hu, Kenny Tsu Wei Choo, and Roy Ka-Wei Lee. 2024. ToxiCloakCN: Evaluating robustness of offensive language detection in Chinese with cloaking perturbations. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 6012–6025, Miami, Florida, USA. Association for Computational Linguistics.

Zhijun Xu, Siyu Yuan, Yiqiao Zhang, Jingyu Sun, Tong Zheng, and Deqing Yang. 2025. PunMemeCN: A benchmark to explore vision-language models' understanding of Chinese pun memes. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 18694–18710, Suzhou, China. Association for Computational Linguistics.

Diyi Yang, Alon Lavie, Chris Dyer, and Eduard Hovy. 2015. Humor recognition and humor anchor extraction. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 2367–2376, Lisbon, Portugal. Association for Computational Linguistics.

Shujian Yang, Shiyao Cui, Chuanrui Hu, Haicheng Wang, Tianwei Zhang, Minlie Huang, Jialiang Lu, and Han Qiu. 2025. Exploring multimodal challenges in toxic Chinese detection: Taxonomy, benchmark, and findings. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 14382–14396, Vienna, Austria. Association for Computational Linguistics.

Francisco Yus. 2016. *Humour and Relevance*. John Benjamins, Amsterdam.

Marcos Zampieri, Shervin Malmasi, Preslav Nakov, Sara Rosenthal, Noura Farra, and Ritesh Kumar. 2019. SemEval-2019 task 6: Identifying and categorizing offensive language in social media (OffensEval). In *Proceedings of the 13th International Workshop on Semantic Evaluation*, pages 75–86, Minneapolis, Minnesota, USA. Association for Computational Linguistics.

Alessandro Zangari, Matteo Marcuzzo, Andrea Albarelli, Mohammad Taher Pilehvar, and Jose Camacho-Collados. 2025. Pun unintended: LLMs and the illusion of humor understanding. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 27936–27971, Suzhou, China. Association for Computational Linguistics.

Qingcheng Zeng and An-Ran Li. 2022. A survey in automatic irony processing: Linguistic, cognitive, and multi-X perspectives. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 824–836, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.

Leticia-Tian Zhang and Daniel Cassany. 2019. The "danmu" phenomenon and media participation: Intercultural understanding and language learning through "the ministry of time". *Comunicar*, 27(58):19–29.

A Keyword List for the Target Keyword Search Supplement

Search scope. These keywords were designed to target politically charged, gender-related, racial, and taboo-humor stand-up contexts.

Keyword generation. The target keyword search supplement was constructed using the following Bilibili search keywords, generated with GPT-5.4 with thinking mode enabled and then manually filtered by the authors. For each keyword, we retained the top 3–5 videos under Bilibili's default comprehensive ranking and danmu-count sorting; duplicate videos were counted only once.

- 特朗普脱口秀
- 杨笠脱口秀
- 女权脱口秀
- 男女对立脱口秀
- Ali Wong 脱口秀
- Trevor Noah 脱口秀
- 鸟鸟脱口秀
- 小帕脱口秀
- 地狱笑话standup 译制
- 黄段子脱口秀

B Candidate Selection from the Master Pool

From the 82,637-comment master pool, the researcher manually constructed the candidate subset using the following rules. The final adjudicated benchmark contains 1,054 items, including 536 positive and 518 negative cases.

Definition-driven selection. Positive candidates were retained if a manipulated surface form served to avoid direct mention of a more sensitive target, intensify hostility or offensiveness through a safer-looking form, or combine both functions.

Default exclusions and hard negatives. Ordinary metaphor, ordinary slang, ordinary joking, direct insult without manipulation, and non-toxic playful masking were not treated as positive candidates by default; such cases served as the main source of negative items. We also retained a subset of hard or potentially confusing items labeled 0 in order to preserve challenging decision boundaries.

Preference for informative cases. Selection prioritized cases useful for later mechanism annotation, including phonological substitution, alphabetic or alphanumeric disguise, semantic indirection, mixed-mechanism cases, and items requiring contextual or world knowledge.

Redundancy control. We did not retain all near-duplicate danmu. When many items shared the same or nearly identical canonicalized form, we kept only a limited number of representative instances.

C Annotation Design Rationale

This appendix provides additional methodological justification for the two-stage annotation design and the script-field workflow.

Label-schema details. For Stage 1, positive MRC cases cover evasive avoidance, offensive intensification, and hybrid evasion. Evasive avoidance includes cases such as near-homophones used to avoid directly writing a taboo term, while offensive intensification includes safer-looking variants that recast an expression into a derogatory or non-standard form. Negative cases include ordinary metaphor, ordinary slang, ordinary joking, direct insult without manipulation, and non-toxic playful masking.

Mechanism labels. The Stage 2 `cloaked type` inventory broadens prior phonetic-cloaking taxonomies to include both form-based and semantic cloaking. HHR covers homophonic Hanzi replacement; AR covers pinyin-, alphabetic-, or digit-based disguise; GDM covers character splitting, spacing, punctuation insertion, and symbol masking; SI covers coded reference, unusual renaming, and indirect target activation through meaning association; and MR is used when multiple mechanisms are strongly active and no single mechanism is dominant.

Two-stage annotation design. Our annotation procedure is organized in two stages to align with task complexity while controlling annotation cost. Stage 1 focuses on binary `MRC expression` detection, allowing annotators to identify plausible positive cases before committing to finer-grained mechanism labels. This ordering reduces the risk that borderline but potentially informative MRC cases are discarded too early. Stage 2 is then restricted to the Stage 1 positive subset, where annotators assign `cloaked type` and `extra knowledge`.

Constraining fine-grained annotation to plausible positives reduces noise and lowers overall annotation overhead (Dligach et al., 2010).

Stage 1 workflow and adjudication. In Stage 1, each annotator labeled all samples independently in a standardized Excel annotation sheet after an initial calibration round based on the written guidelines. The final Stage 1 output contains 1,054 items, including 536 positive and 518 negative items; 239 non-unanimous cases were resolved through adjudication. At this stage, we derive provisional labels using a 2-of-3 majority rule rather than strict unanimity. This choice is especially important for context-sensitive cases, where a unanimity requirement would disproportionately exclude difficult but analytically valuable examples. The majority-based procedure therefore improves recall at the candidate-selection stage while retaining a principled basis for subsequent adjudication (Klie et al., 2024).

Stage 2 disagreement patterns. In Stage 2, disagreement is not evenly distributed across the two annotation dimensions. Among the 536 positive items, 111 cases were non-unanimous for `cloaked type`, 171 were non-unanimous for `extra knowledge`, and 39 were non-unanimous on both dimensions, yielding a combined disagreement pool of 243 cases requiring adjudication on at least one variable. The lower agreement on `extra knowledge` relative to `cloaked type` is expected. Unlike `cloaked type`, which asks annotators to identify the dominant surface–hidden mechanism, `extra knowledge` requires a judgment about whether stable interpretation is recoverable from the danmu text alone or depends on background knowledge beyond the local text. Borderline cases often involve cross-lingual expressions, internet abbreviations, intertextual references, and culture-specific slang, for which annotators may differ in prior familiarity. For this reason, `extra knowledge` is used in the current benchmark primarily as a post-hoc analytical dimension rather than as a prediction target.

Script-field workflow. For the script-based fields, including `Script A–Script F`, we use a prefill-and-review workflow rather than full independent annotation. The first author prefilled these fields using the danmu text together with publicly accessible contextual information and, when necessary, the original time-stamped video to verify the intended surface–hidden relation. Two annotators then reviewed each proposed script pair. If a pair was judged inaccurate, incomplete, or misleading, it was flagged for later discussion and revision. Final gold script fields were therefore produced through adjudication after review, rather than being taken directly from any single annotator's first-pass judgment.

Why prefill-and-review was preferred. This workflow was selected because script interpretation is explanation-heavy and often requires integrating local wording, source-video context, and background knowledge. A full independent annotation protocol for all script fields would have imposed substantially higher cost without guaranteeing more reliable surface–hidden reconstructions. The prefill-and-review design instead balances interpretive depth with methodological transparency. In addition, the reviewers for the script stage also participated in Stage 1, allowing them to draw on prior familiarity with the data while checking the consistency of the proposed script pairs (Schulz et al., 2019; Pfeiffer et al., 2019).

D Experimental Framework

Figure 3 summarizes how the main benchmark, the script-informed ablation, and post-hoc analyses connect to the reported results.

Figure 3: Experimental framework: main benchmark, script-informed ablation, and post-hoc analysis.

Figure 4: Distributional shift in type-classification errors under the script-informed ablation. The no-script error pool ($n = 848$) is partitioned into errors resolved by script fields ($n = 482$) and those still wrong with script fields ($n = 366$).

E Prompt-Level Results

This appendix reports the full prompt-level results for the six retained non-thinking models and summarizes the main prompt-structure pattern.

Model	Prompt	MRC F1	Type F1
GPT-5.4	*Std*	0.533	0.326
	Script-Std	0.539	0.332
	Script-CoT	0.626	**0.424**
	GTVH	**0.663**	0.373
GPT-5.5	*Std*	0.667	0.464
	Script-Std	0.610	0.407
	Script-CoT	**0.734**	**0.550**
	GTVH	0.730	0.521
Gemini	*Std*	0.758	**0.592**
	Script-Std	0.757	0.589
	Script-CoT	0.760	0.584
	GTVH	**0.766**	0.533
Claude	*Std*	**0.610**	**0.416**
	Script-Std	0.568	0.356
	Script-CoT	0.596	0.397
	GTVH	0.536	0.327
Qwen	*Std*	0.621	0.356
	Script-Std	0.619	0.381
	Script-CoT	**0.729**	**0.445**
	GTVH	0.708	0.432
DeepSeek	*Std*	0.576	**0.339**
	Script-Std	0.571	0.278
	Script-CoT	0.675	0.285
	GTVH	**0.699**	0.239

Table 5: Full prompt-level non-thinking results. Prompt variants use the abbreviations *Std*, *Script-Std*, *Script-CoT*, and *GTVH*.

Prompt-structure analysis

The prompt progression yields non-monotonic effects on the main task. Moving from *Std* to *Script-Std* brings only limited gains, suggesting that simply making the surface–hidden distinction explicit is not sufficient on its own. Clearer improvements emerge when moving to *Script-CoT* and *GTVH*, indicating that stronger interpretive structure is generally helpful. However, the best prompt remains both model- and task-dependent. *Script-CoT* is the most consistently helpful prompt for cloaked type classification, yielding the strongest Type F1 for GPT-5.4, GPT-5.5, and Qwen, whereas *GTVH* more often gives the strongest binary MRC expression results, especially for GPT-5.4, Gemini, and DeepSeek.

At the same time, these gains do not transfer uniformly across evaluation targets: for example, Gemini achieves its best binary result under *GTVH* but its best type result under *Std*, while Claude performs best under the simplest *Std* prompt for both tasks. Overall, added interpretive structure can help, but its benefits are not monotonic and the most theory-loaded prompt is not uniformly optimal across models.

F Post-hoc Error Analyses

This appendix reports two post-hoc analyses: script-conditioned error redistribution (Figure 4) and the extra-knowledge contrast (Figure 5).

Figure 5: Effect of extra knowledge on detection recall and type accuracy.

G Representative Error Cases

Task	Gold / Type	EK	Fail count	Danmu Text
No-script binary `MRC` expression hard cases				
MRC	1 / HHR	0	6/6	太糙了hhh
				"so crude, haha"
				糙 (cao1, 'rough') → 操 (cao4, 'fuck')
MRC	1 / AR	0	6/6	omfg†
				"oh my fucking god"
				acronym → expletive
MRC	1 / SI	1	6/6	好活†
				"nice one"
				活 (huo2, 'move') → 活 (huo2, sexually suggestive 'skill')
MRC	1 / SI	1	6/6	中外都一样，平板是终极武器†
				"same in China and abroad; flat chests are the ultimate weapon"
				平板 (pingban, 'flat board') → 平板 (pingban, 'flat chest')
MRC	1 / MR	1	6/6	赤 壁 之 战†
				"Battle of Red Cliffs"
				赤壁 (chibi, 'Red Cliffs') → 吃逼 (chibi, vulgar sexual target)
MRC	0 / –	–	6/6	说说得一般的都是Y吗？
				"are the ones saying it was mediocre all Y-chromosome types?"
				Y → male-coded reference
MRC	0 / –	–	6/6	易女而奴
				"woman-to-slave wordplay"
				女 ('woman') → 奴 ('slave')
MRC	0 / –	–	6/6	脑吸氨了
				"your brain inhaled ammonia"
				ammonia inhalation → stupidity
No-script `cloaked` type hard cases				
Type	HHR	0	6/6	分手吧，剑刃†
				"let's break up, jianren"
				剑刃 (jianren, 'sword blade') → 贱人 (jianren, 'bitch')
Type	AR	0	6/6	dior癌是骂人用的†
				"dior-cancer is used as an insult"
				dior / 迪奥 → diao3 ('dick')
Type	SI	1	6/6	海豚喜欢乱搞†
				"dolphins like to sleep around"
				海豚 ('dolphin') → sexualized label for a hairless man
Type	GDM	1	6/6	slav†
				slav → 'slave'
Type	MR	0	6/6	非得是男的开头是吧，长的跟个78似的，一嘴大份味†
				"so it has to start with a man, right? looks like a 78, reeks of shit"
				78 → 鸡吧; 大份 → 大粪 ('shit')
Type	SI	1	6/6	什么时候轮到这种虫豸来评价男性了？†
				"since when did this kind of vermin get to judge men?"
				虫豸 ('vermin') → contemptible people

Table 6: Representative no-script hard cases from the binary `MRC` expression task and the positive-only `cloaked` type task. Each example is shown with the original danmu, an approximate English gloss, and a compact meaning-shift annotation. Rows marked with † also appear in the script-conditioned comparison.

Type	EK	Group	Danmu Text	No-script	With-script
Resolved by script					
HHR	0	Resolved	分手吧，剑刃[†] *"let's break up, jianren"* 剑刃 (jianren, 'sword blade') → 贱人 (jianren, 'bitch')	wrong (3/3)	correct
HHR	1	Resolved	干洗 *"dry cleaning"* 干洗 (ganxi, 'dry clean') → 干死 (gansi, 'fuck to death')	wrong (3/3)	correct
AR	0	Resolved	dior癌是骂人用的[†] *"dior-cancer is used as an insult"* dior / 迪奥 → *diao3* ('dick')	wrong (3/3)	correct
AR	0	Resolved	是呢，连开玩笑的ai都不敢说，觉得非常冒犯生病的人。 *"right, they do not even dare say ai as a joke, because it feels offensive to sick people"* ai → 癌 (ai, 'cancer')	wrong (3/3)	correct
SI	1	Resolved	海豚喜欢乱搞[†] *"dolphins like to sleep around"* 海豚 ('dolphin') → sexualized label for a hairless man	wrong (3/3)	correct
MR	0	Resolved	非得是男的开头是吧，长的跟个78似的，一嘴大份味[†] *"so it has to start with a man, right? looks like a 78, reeks of shit"* 78 → 鸡吧; 大份 → 大粪 ('shit')	wrong (3/3)	correct
Still hard with script					
GDM	1	Still hard	slav[†] slav → 'slave'	wrong (3/3)	wrong (3/3)
AR	0	Still hard	omfg[†] *"oh my fucking god"* acronym → expletive	wrong (3/3)	wrong (3/3)
SI	1	Still hard	好活[†] *"nice one"* 活 (huo2, 'move') → 活 (huo2, sexually suggestive 'skill')	wrong (3/3)	wrong (3/3)
SI	1	Still hard	中外都一样，平板是终极武器[†] *"same in China and abroad; flat chests are the ultimate weapon"* 平板 (pingban, 'flat board') → 平板 (pingban, 'flat chest')	wrong (3/3)	wrong (3/3)
MR	1	Still hard	赤 壁 之 战[†] *"Battle of Red Cliffs"* 赤壁 (chibi, 'Red Cliffs') → 吃逼 (chibi, vulgar sexual target)	wrong (3/3)	wrong (3/3)
SI	1	Still hard	什么时候轮到这种虫豸来评价男性了？[†] *"since when did this kind of vermin get to judge men?"* 虫豸 ('vermin') → contemptible people	wrong (3/3)	wrong (3/3)

Table 7: Script-conditioned outcomes for representative no-script `cloaked type` failures. Each example is shown with the original danmu, an approximate English gloss, and a compact meaning-shift annotation. Rows marked with [†] also appear in the no-script hard-case table.