Evaluating Gradient Inversion Attacks and Defenses in Federated Learning

Abstract

Gradient inversion attack (or input recovery from gradient) is an emerging threat to the security and privacy preservation of Federated learning, whereby malicious eavesdroppers on the protocol can recover (partially) the clients' private data. This paper evaluates existing attacks and defenses. We find that current attacks make strong assumptions about the setup. Relaxing those assumptions in the setup substantially weakens these attacks. We then evaluate the benefits of three proposed defense mechanisms against gradient inversion attacks. We show the trade-offs of privacy leakage and data utility of these defense methods, and find that combining them in an appropriate manner essentially makes the attack less effective, *even under the original strong assumptions*. We also estimate the computation cost of end-to-end recovery of a single image under each evaluated defense. Our findings suggest that the state-of-the-art attacks can currently be defended against with minor data utility loss, as summarized in a list of best practices.

1 Introduction

Federated learning [McMahan et al., 2016, Kairouz et al., 2019] is a framework that allows multiple clients in a distributed environment to collaboratively train a neural network model at a central server, without moving their data to the central server. At every training step, each client computes a model update —i.e., gradient— on its local data using the latest copy of the global model, and then sends the gradient to the central server. The server aggregates these updates (typically by averaging) to construct a global model, and then sends the new model parameters to all clients. By allowing clients to participate in training without directly sharing their data, such protocols align better with data privacy regulations such as Health Insurance Portability and Accountability Act (HIPPA) [Act, 1996] and California Consumer Privacy Act (CCPA) [Legislature, 2018].

While sharing gradients was thought to leak little information about the client's private data, recent papers [Zhu et al., 2019, Geiping et al., 2020, Yin et al., 2021] developed a "gradient inversion attack" by which an attacker eavesdropping on a client's communications with the server can begin to reconstruct the client's private data. These attacks have been shown to work with batch sizes only up to 100 but even so they have created doubts about the level of privacy ensured in Federated Learning. The current paper seeks to evaluate the risks and suggest ways to minimize them, including a set of recommended best practices.

Several defenses against gradient inversion attacks have been proposed. These include gradient pruning [Zhu et al., 2019, Wei et al., 2020] and using transformation for training data that clients can apply on the fly [Zhang et al., 2018a, Huang et al., 2020]. (More traditional cryptographic ideas including secure aggregation [Bonawitz et al., 2016] or homomorphic encryption [Phong et al., 2018] for the gradients can also be used and presumably stop the attacks completely. They will not be studied here due to their special setups and overhead.)

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

We are not aware of a prior systematic evaluation of the level of risk arising from current attacks and the level of security provided by various defenses, as well as the trade-off (if any) between test accuracy, computation overhead, and privacy risks.

Our main contributions are as follows:

1. We draw attention to two unrealistic assumptions that current gradient inversion attacks implicitly make. We show that in more realistic settings, the performance of such attacks drop significantly. The trade-offs are explored in Section 3 and already yield some simple good practices.

2. We summarize various defenses (Section 4) and systematically evaluate (Section 5) some of their performance of defending against a state-of-the-art gradient inversion attack, and present their data utility and privacy leakage trade-offs. We estimate the computation cost of end-to-end recovery of a single image under each evaluated defense. We also experimentally demonstrate the feasibility and effectiveness of combined defenses.

3. We summarize the results with a list of best practices based on our findings for federated learning participants, on how to improve their schemes' security against gradient inversion attacks (Section 6).

In Appendix B, we provide theoretical insights for mechanism of each evaluated defense.

2   Gradient Inversion Attacks

Previous works have shown the feasibility of recovering input from gradient (i.e. gradient inversion) for image classification tasks, by formulating it as an optimization problem: given a neural network with parameters θ, and the gradient $\nabla_\theta \mathcal{L}_\theta(x^*, y^*)$ computed with a private data batch $(x^*, y^*) \in \mathbb{R}^{b \times d} \times \mathbb{R}^b$ (b, d being the batch size, image size), the attacker tries to recover $x \in \mathbb{R}^{b \times d}$, an approximation of x^*:

$$\arg\min_x \mathcal{L}_{\text{grad}}(x; \theta, \nabla_\theta \mathcal{L}_\theta(x^*, y^*)) + \alpha \mathcal{R}_{\text{aux}}(x) \tag{1}$$

The optimization goal consists of two parts: $\mathcal{L}_{\text{grad}}(x; \theta, \nabla_\theta \mathcal{L}_\theta(x^*, y^*))$ enforces matching of the gradient of recovered batch x with the provided gradients $\mathcal{L}_\theta(x^*, y^*)$, and $\mathcal{R}_{\text{aux}}(x)$ regularizes the recovered image based on image prior(s).

[Phong et al., 2017] brings theoretical insights on this task by proving that such reconstruction is possible with a single-layer neural network. [Zhu et al., 2019] is the first to show that accurate pixel-level reconstruction is practical for a maximum batch size of 8. Their formulation uses ℓ_2-distance as $\mathcal{L}_{\text{grad}}(\cdot, \cdot)$ but no regularization term $\mathcal{R}_{\text{aux}}(x)$. The approach works for low-resolution CIFAR datasets [Krizhevsky et al., 2009], with simple neural networks with sigmoid activations, but cannot scale up to high-resolution images, or larger models with ReLU activations. A follow-up [Zhao et al., 2020] proposes a simple approach to extract the ground-truth labels from the gradient, which improves the attack but still cannot overcome its limitations.

With a careful choice of $\mathcal{L}_{\text{grad}}$ and $\mathcal{R}_{\text{aux}}(x)$, [Geiping et al., 2020] substantially improves the attack and succeeds in recovering a single ImageNet [Deng et al., 2009] image from gradient: their approach uses cosine distance as $\mathcal{L}_{\text{grad}}$, and the total variation as $\mathcal{R}_{\text{aux}}(x)$. Their approach is able to reconstruct low-resolution images with a maximum batch size of 100. Based on [Geiping et al., 2020], [Wei et al., 2020] analyzes how different configurations in the training may affect attack effectiveness. A more recent work [Yin et al., 2021] further enhances the attack on high-resolution images, by introducing to $\mathcal{R}_{\text{aux}}(x)$ a new image prior term based on batch normalization [Ioffe and Szegedy, 2015] statistics, and a regularization term which enforces consistency across multiple attack trials.

Recently, [Zhu and Blaschko, 2021] proposes to formulate the gradient inversion attack as a closed-form recursive procedure, instead of an optimization problem. However, their implementation can recover only low-resolution images under the setting where batch size = 1.

3   Strong Assumptions Made by SOTA Attacks

3.1   The state-of-the-art attacks

Two recent attacks [Geiping et al., 2020, Yin et al., 2021] achieve best recovery results. Our analysis focuses on the former as the implementation of the latter is not available at the time of writing this paper. We plan to include the analysis for the latter attack in the final version of this paper if its implementation becomes available.

Attack Methods	[Zhu et al., 2019]	[Zhao et al., 2020]	[Geiping et al., 2020]	[Yin et al., 2021]
Knowing BN statistics	N/A[†]	N/A[†]	Yes	Yes[*]
Knowing private label(s)	No	No[‡]	Yes	No[‡]

Table 1: Assumptions of gradient inversion attacks.

[†]Its evaluation uses a simple model without a BatchNorm layer; [‡]It proposes a method to infer private labels, which works when images in a batch have unique labels (see Section 3.3); [*]Although the paper discusses a setting where BatchNorm statistics are unknown, its main results assume knowing BatchNorm statistics.

geiping2020inverting's attack optimizes the following objective function:

$$\arg\min_x 1 - \frac{\langle \nabla_\theta \mathcal{L}_\theta(x,y), \nabla_\theta \mathcal{L}_\theta(x^*, y^*) \rangle}{\| \nabla_\theta \mathcal{L}_\theta(x,y) \| \| \nabla_\theta \mathcal{L}_\theta(x^*, y^*) \|} + \alpha_{\mathrm{TV}} \mathcal{R}_{\mathrm{TV}}(x) \tag{2}$$

where $\langle \cdot, \cdot \rangle$ is the inner-product between vectors, and $\mathcal{R}_{\mathrm{TV}}(x)$ is the total variation of image.

We notice that Geiping et al. has made two strong assumptions (Section 3.2). Changing setups to invalidate those assumptions will substantially weaken the attacks (Section 3.3). We also summarize whether other attacks have made similar assumptions in Table 1.

3.2 Strong assumptions

We find that previous gradient inversion attacks have made different assumptions about whether the attacker knows Batch normalization statistics or private labels, as shown in Table 3.2. Note that [Geiping et al., 2020]'s attack assumes both strong assumptions.

Assumption 1: Knowing BatchNorm statistics. Batch normalization (BatchNorm) [Ioffe and Szegedy, 2015] is a technique for training neural networks that normalizes the inputs to a layer for every mini-batch. It behaves differently during training and evaluation. Assume the model has L batch normalization layers. Given x^*, a batch of input images, we use x_l^* to denote the input features to the l-th BatchNorm layer, where $l \in [L]$. During training, the l-th BatchNorm layer normalizes x_l^* based on the batch's mean $\mathrm{mean}(x_l^*)$ and variance $\mathrm{var}(x_l^*)$, and keeps a running estimate of mean and variance of all training data points, denoted by μ_l and σ_l^2. During inference, $\{\mu_l\}_{l=1}^L$ and $\{\sigma_l^2\}_{l=1}^L$ are used to normalize test images. In the following descriptions, we leave out $\{\cdot\}_{l=1}^L$ for simplicity (i.e. use μ, σ^2 to denote $\{\mu_l\}_{l=1}^L, \{\sigma_l^2\}_{l=1}^L$, and $\mathrm{mean}(x^*), \mathrm{var}(x^*)$ to denote $\{\mathrm{mean}(x_l^*)\}_{l=1}^L, \{\mathrm{var}(x_l^*)\}_{l=1}^L$).

We notice that [Geiping et al., 2020]'s implementation[1] assumes that BatchNorm statistics of the private batch, i.e., $\mathrm{mean}(x^*), \mathrm{var}(x^*)$, are jointly provided with the gradient. Knowing BatchNorm statistics would enable the attacker to apply the same batch normalization used by the private batch on his recovered batch, to achieve a better reconstruction. This implicitly increases the power of the attacker, as sharing BatchNorm statistics are not necessary in Federated learning [Li et al., 2021].

Note that this assumption may be *realistic* in some settings: 1) the neural network is shallow, thus does not require using BatchNorm layers, or 2) the neural network is deep, but adapts approaches that normalize batch inputs with a fixed mean and variance (as alternative to BatchNorm), e.g. Fixup initialization [Zhang et al., 2019].

Assumption 2: Knowing or able to infer private labels. Private labels are not intended to be shared in Federated learning, but knowing them would improve the attack. [Zhao et al., 2020] finds that label information of a *single* private image can be inferred from the gradient (see Section 3.3 for details). Based on this, [Geiping et al., 2020] assumes the attacker knows private labels (see remark at the end of their Section 4). However, this assumption may not hold true when multiple images in a batch share the same label, as we will show in the next section.

3.3 Re-evaluation under relaxed assumptions

We re-evaluate the performance of the gradient inversion attack in settings where two assumptions above are relaxed. For each relaxation, we re-design the attack (if needed) based on the knowledge that the attacker has.

Relaxation 1: Not knowing BatchNorm statistics. We refer to the previous threat model as $\mathrm{BN}_{\mathrm{exact}}$, where the attacker knows exact BatchNorm statistics of the private batch. We consider a more realistic threat model where these statistics are not exposed, and re-design the attack based on it.

---

[1]The official implementation of [Geiping et al., 2020]: https://github.com/JonasGeiping/invertinggradients.

131 *Threat model.* In each training step, the client normalizes its private batch x^* using the batch's mean
132 $\text{mean}(x^*)$ and variance $\text{var}(x^*)$, keeps the running estimate of mean and variance *locally* as in [Li
133 et al., 2021], and shares the gradient. The client releases the final aggregated mean μ, and aggregated
134 variance σ^2 of all training data points at the end of training. Same as before, the attacker has access
135 to the model and the gradient during training.

136 *Re-design A:* BN_{proxy}, *attacker naively uses μ and σ^2.* A simple idea is that the attacker uses (μ, σ^2)
137 as the proxy for $(\text{mean}(x^*), \text{var}(x^*))$, and uses them to normalize x, his guesses of the private batch.
138 Other operations of the gradient inversion attack remain the same as before. However, Figure 1.d
139 and 1.h show poor-quality reconstruction with this re-design.

140 *Re-design B:* BN_{infer}, *attacker infers $(\text{mean}(x^*), \text{var}(x^*))$ based on (μ, σ^2).* A more reasonable
141 attacker will try to infer $(\text{mean}(x^*), \text{var}(x^*))$ while updating x, his guesses of the private batch,
142 and uses $(\text{mean}(x), \text{var}(x))$ to normalize the batch. In this case, (μ, σ^2) could be used as a prior of
143 BatchNorm statistics to regularize the recovery, as suggested in [Yin et al., 2021]:

$$\arg \min_x 1 - \frac{\langle \nabla_\theta \mathcal{L}_\theta(x, y), \nabla_\theta \mathcal{L}_\theta(x^*, y^*) \rangle}{\|\nabla_\theta \mathcal{L}_\theta(x, y)\| \|\nabla_\theta \mathcal{L}_\theta(x^*, y^*)\|} + \alpha_{\text{TV}} \mathcal{R}_{\text{TV}}(x) + \alpha_{\text{BN}} \mathcal{R}_{\text{BN}}(x) \tag{3}$$

144 where $\mathcal{R}_{\text{BN}}(x) = \sum_l \|\text{mean}(x_l) - \mu_l\|_2 + \sum_l \|\text{var}(x_l) - \sigma_l^2\|_2$.

145 We tune α_{BN} and present the best result in Figure 1.c and 1.g (see results of different α_{BN}'s
146 in Appendix A). As shown, for a batch of low-resolution images, BN_{infer} gives a much better
147 reconstruction result than BN_{proxy}, but still cannot recover some details of the private batch when
148 compared with BN_{exact}. The result for a single high-resolution image is worse: the attacker fails to
149 return a recognizable reconstruction with BN_{infer}. This suggests not having access to BatchNorm
150 statistics of the private batch already weakens the state-of-the-art gradient inversion attack.

(a) Original   (b) BN_{exact} (c) BN_{infer} (d) BN_{proxy} (e) Original   (f) BN_{exact} (g) BN_{infer} (h) BN_{proxy}

Figure 1: Attacking a batch of 16 low-resolution images from CIFAR-10 (a-d) and a single high-resolution image from ImageNet (e-h) with different knowledge of BatchNorm statistics. Attack is weakened when BatchNorm statistics are not available (c, d versus b, and g, h versus f).

151 **Relaxation 2: Not knowing private labels.** [Zhao et al., 2020] notes that label information of a
152 *single* private image can be computed analytically from the gradients of the layer immediately before
153 the output layer. [Yin et al., 2021] further extends this method to support recovery of labels for a
154 batch of images. However, if multiple images in the private batch belong to a same label, neither
155 approach can tell how many images belong to that label, let alone which subset of images belong to
156 that label. Figure 2a demonstrates that with CIFAR-10, for batches of various sizes it is possible for
157 many of the training samples to be have the same label - and hence, inferring labels becomes harder
158 and the attack would be weakened. In Figure 2b we evaluate the worst-case for an attacker in this
159 setting by comparing recoveries where the batch labels are simultaneously reconstructed alongside
160 the training samples.

(a) Distribution of labels in a batch   (b) Reconstructions with and without private labels

Figure 2: Attack is weakened when private labels are not available. (a) shows that for CIFAR-10, when the batch size is large, many images in the batch belong to the same class, which essentially disables label restoration [Zhao et al., 2020, Yin et al., 2021]. (b) visualizes a reconstructed batch with and without private labels known. The quality of the reconstruction drops without knowledge of private labels (see Appendix A for more examples and quantitative results).

4 Defenses Against the Gradient Inversion Attack

Several defense ideas have been proposed to mitigate the risks of gradient inversion.

4.1 Encrypt gradients

Cryptography-based approaches encrypt gradient to prevent gradient inversion. [Bonawitz et al., 2016] presents a secure aggregation protocol for Federated learning by computing sum of gradient vectors based on secret sharing [Shamir, 1979]. [Phong et al., 2018] proposes using homomorphic encryption to encrypt the gradients before sending. These approaches require special setup and can be costly to implement. As alternatives, two other types of defensive mechanisms have been proposed to mitigate the risks of attacks on *plain-text* gradient.

4.2 Perturbing gradient

Gradient pruning. When proposing the first practical gradient inversion attack, [Zhu et al., 2019] also suggests a defense by setting gradients of small magnitudes to zero (i.e. gradient pruning). Based on their attack, they demonstrate that pruning more than 70% of the gradients would make the recovered images no longer visually recognizable. However, the suggested prune ratio is determined based on weaker attacks, and may not remain safe against the state-of-the-art attack.

Adding noise to gradient. Motivated by DPSGD [Abadi et al., 2016] which adds noise to gradients to achieve differential privacy [Dwork, 2009, Dwork and Roth, 2014], [Zhu et al., 2019, Wei et al., 2020] also suggests defending by adding Gaussian or Laplacian noise to gradient. They show that a successful defense requires adding high noise level such that its accuracy drops by more than 30% with CIFAR-10 tasks. Recent works [Papernot et al., 2020, Tramèr and Boneh, 2021] suggest using better pre-training techniques and a large batch size (e.g. $4,096$) to achieve a better accuracy for DPSGD training.

This paper does not compare DPSGD for two reasons: first, it uses a pre-training and fine tuning pipeline; second, the SOTA attack methods currently handle smaller batch sizes (up to 100). Therefore, it is harder to fairly compare DPSGD with other defense method against a SOTA attack. We leave such a comparison to future work.

4.3 Encoding inputs

MixUp. MixUp data augmentation [Zhang et al., 2018a] trains neural networks on composite images created via linear combination of image pairs. It has been shown to improve the generalization of the neural network and stabilizes the training. Recent work also suggests that MixUp increases the model's robustness to adversarial examples [Pang et al., 2020, Lamb et al., 2019].

InstaHide. Inspired by MixUp, [Huang et al., 2020] proposes InstaHide as a light-weight instance-encoding scheme for private distributed learning. To encode an image $x \in \mathbb{R}^d$ from a private dataset, InstaHide first picks $k-1$ other images $s_2, s_3, \ldots, s_k$ from that private dataset, or a large public dataset, and k random nonnegative coefficients $\{\lambda_i\}_{i=1}^k$ that sum to 1, and creates a composite image $\lambda_1 x + \sum_{i=2}^k \lambda_i s_i$ (k is typically small, e.g., 4). A composite label is also created using the same set of coefficients.[2] Then it adds another layer of security: pick a random sign-flipping pattern $\sigma \in \{-1, 1\}^d$ and output the encryption $\tilde{x} = \sigma \circ (\lambda_1 x + \sum_{i=2}^k \lambda_i s_i)$, where $\circ$ is coordinate-wise multiplication of vectors. The neural network is then trained on encoded images, which look like random pixel vectors to the human eye and yet lead to good classification accuracy ($< 6\%$ accuracy loss on CIFAR-10, CIFAR-100, and ImageNet).

Recently, [Carlini et al., 2020] gives an attack to recover private images of a small dataset, when the InstaHide encodings are revealed to the attacker (not in a Federated learning setting). Their first step is to train a neural network on a public dataset for similarity annotation, to infer whether a pair of InstaHide encodings contain the same private image. With the inferred similarities of all pairs of encodings, the attacker then runs a combinatorial algorithm (cubic time in size of private dataset) to cluster all encodings based on their original private images, and finally uses a regression algorithm (with the help of composite labels) to recover the private images.

Neither [Huang et al., 2020] or [Carlini et al., 2020] has evaluated their defense or attack in the Federated learning setting, where the attacker observes gradients of the encoded images instead of original encoded images. This necessitates the systematic evaluation in our next section.

---

[2]Only the labels of examples from the private dataset will get combined. See [Huang et al., 2020] for details.

5 Evaluation of defenses

The main goal of our experiments is to understand the trade-offs between data utility (accuracy) and securely defending the state-of-the-art gradient inversion attack even in its strongest setting, *without* any relaxation of its implicit assumptions. Specifically, we grant the attacker the knowledge of 1) BatchNorm statistics of the private batch, and 2) labels of the private batch.

We vary key parameters for each defense, and evaluate their performance in terms of the test accuracy, computation overhead, and privacy risks (Section 5.2). We then investigate the feasibility of combining defenses (Section 5.3). We also estimate the computation cost of end-to-end recovery of a single image under evaluated defenses (Section 5.4).

We focus on the evaluation with low-resolution images, as the feasibility of the state-of-the-art attack [Geiping et al., 2020] on a batch of high-resolution images remain elusive when its implicit assumptions no longer hold (see Figure 1).

5.1 Experimental setup

Key parameters of defenses. We evaluate following defenses on CIFAR-10 dataset [Krizhevsky et al., 2009] with ResNet-18 architecture [He et al., 2016]:

- **GradPrune** (gradient pruning): gradient pruning set gradients of small magnitudes to zero. We vary the pruning ratio p in $\{0.5, 0.7, 0.9, 0.95, 0.99, 0.999\}$.
- **MixUp**: MixUp encodes a private image by linearly combining it with $k-1$ other images from the training set. Following [Huang et al., 2020], we vary k in $\{4, 6\}$, and set the upper bound of a single coefficient to 0.65 (coefficients sum to 1).
- **Weak-InstaHide (W-InstaHide)**: InstaHide further encodes a MixUp image by randomly flipping its pixel signs. We are only mixing private images in our experiments, which is a *weaker* version of InstaHide. Similar to the evaluation of MixUp, we vary k in $\{4, 6\}$, and set the upper bound of a single coefficient to 0.65. Note that InstaHide flips signs of pixels in the image, which destroys the total variation prior. However, the absolute value of adjacent pixels should still be close. Therefore, for the InstaHide defense, we apply the total variation regularizer on $|x|$, i.e. taking absolute value of each pixel in the reconstruction.

We train the ResNet-18 architecture on CIFAR-10 using different defenses, and launch the attack. We provide the hyper-parameters used for training in Appendix A.

The attack. We use a subset of 50 CIFAR-10 images to evaluate the attack performance. Note that attacking MixUp and InstaHide involves another step to decode private images from the encoded images. We apply [Carlini et al., 2020]'s attack here as the decode step, where the attacker needs to eavesdrop T epochs of training, instead of a single training step. We set $T = 20$ in our evaluation. We also grant the attacker the strongest power for the decode step to evaluate the upper bound of privacy leakage. Given a MixUp or Weak-InstaHide image which encodes k private images, we assume the attacker knows:

1. The indices of k images in the private dataset. In a realistic scenario, the attacker of [Carlini et al., 2020] would need to train a neural network to detect similarity of encodings, and run a combinatorial algorithm to solve *an approximation of* this mapping.
2. The mixing coefficients for each of the k private image. In real Federated learning, this information is *not available*.

Hyper-parameters of the attack. The attack minimize the objective function given in Eq.3. We search α_{TV} in $\{0, 0.001, 0.005, 0.01, 0.05, 0.1, 0.5\}$ for all defenses, and apply the best choice for each defense: 0.05 for GradPrune, 0.1 for MixUp, and 0.01 for Weak-InstaHide. We apply $\alpha_{\mathrm{BN}} = 0.001$ for all defenses after searching it in $\{0, 0.0005, 0.001, 0.01, 0.05, 0.01\}$. We optimize the attack for $10,000$ iterations using Adam [Kingma and Ba, 2015], with initial learning rate 0.1. We decay the learning rate by a factor of 0.1 at $3/8, 5/8, 7/8$ of the optimization.

Batch size of the attack. [Zhu et al., 2019, Geiping et al., 2020] have shown that a small batch size is important for the success of the attack. We intentionally evaluate the attack with three small batch sizes to test the upper bound of privacy leakage, including the minimum (and unrealistic) batch size 1, and two small but realistic batch sizes, 16 and 32.

Metrics for reconstruction quality. We visualize reconstructions obtained under different defenses. Following [Yin et al., 2021], we also use the learned perceptual image patch similarity (LPIPS) score [Zhang et al., 2018b] to measure mismatch between reconstruction and original images: higher values suggest more mismatch (less privacy leakage).

| | None | GradPrune (p) | | | | | | MixUp (k) | | Weak-InstaHide (k) | | GradPrune ($p=0.9$) | |
												+ MixUp	+ Weak-InstaHide
Parameter	-	0.5	0.7	0.9	0.95	0.99	0.999	4	6	4	6	$k=4$	$k=4$
Test Acc.	94.21	93.59	93.22	90.91	90.99	88.92	84.58	92.98	90.73	91.21	88.93	92.07	87.20
Time (train)	$1\times$			$1.04\times$				$1.06\times$		$1.06\times$		$1.10\times$	
Attack batch size $= 1$													
Avg. LPIPS ↓	0.17	0.18	0.20	0.28	0.34	0.46	0.52	0.34	0.46	0.57	**0.61**	0.41	0.60
Best LPIPS ↓	0.08	0.08	0.11	0.16	0.23	0.32	0.36	0.12	0.25	0.40	0.42	0.21	**0.43**
(LPIPS std.)	0.05	0.06	0.07	0.07	0.06	0.06	0.06	0.08	0.07	0.09	0.09	0.07	0.09
Attack batch size $= 16$													
Avg. LPIPS ↓	0.44	0.44	0.44	0.45	0.49	0.52	0.56	0.34	0.31	0.62	0.63	0.46	**0.68**
Best LPIPS ↓	0.25	0.24	0.29	0.28	0.31	0.32	0.44	0.11	0.13	0.41	0.44	0.22	**0.54**
(LPIPS std.)	0.10	0.10	0.09	0.09	0.09	0.06	0.05	0.09	0.09	0.08	0.08	0.10	0.07
Attack batch size $= 32$													
Avg. LPIPS ↓	0.41	0.41	0.42	0.46	0.48	0.50	0.55	0.50	0.49	0.69	0.69	0.62	**0.73**
Best LPIPS ↓	0.21	0.22	0.27	0.29	0.30	0.29	0.48	0.31	0.28	0.56	0.56	0.37	**0.65**
(LPIPS std.)	0.09	0.08	0.07	0.06	0.06	0.06	0.04	0.10	0.10	0.06	0.07	0.10	0.05

Table 2: Utility-security trade-off of different defenses. We train the ResNet-18 model on the whole CIFAR-10 dataset, and report the averaged test accuracy and running time of 5 independent runs. We evaluate the attack on a subset of 50 CIFAR-10 images, and report the attack's relative running time and a metric for privacy leakage (↓: lower values suggest more leakage). We mark the least-leakage defense measured by the metric in **green**.

5.2 Performance of defense methods

We summarize the performance of each defense in Table 2, and visualize reconstructed images in Figure 3. We report the averaged and the best results for the metric of reconstruction quality, as a proxy for average-case and worst-case privacy leakage.

No defense. Without any defense, when batch size is 1, the attack can recover images well from the gradient. Increasing the batch size makes it difficult to recover well, but the recovered images are visually similar to the originals (see Figure 3).

Gradient pruning (GradPrune). Figure 3 shows that as the pruning ratio p increases, there are more artifacts in the reconstructions. However, the reconstructions are still recognizable even when the pruning ratio $p = 0.9$, thus the previous suggestion of using $p = 0.7$ by [Zhu et al., 2019] is no longer safe against the state-of-the-art attack. Our results suggest that, for CIFAR-10, defending the strongest attack with gradient pruning may require the pruning ratio $p \geq 0.999$. As a trade-off, such a high pruning ratio would introduce an accuracy loss of around 10% (see Table 2).

MixUp. MixUp introduces a small computational overhead to training. MixUp with $k = 4$ only has a minor impact (~1.5%) on test accuracy, but it is not sufficient to defend the gradient inversion attack (see Figure 3). Increasing k from 4 to 6 slightly reduces the leakage, however, the reconstruction is still highly recognizable. This suggests that MixUp alone may not be a practical defense against the state-of-the-art gradient inversion attack.

W-InstaHide. W-InstaHide with $k = 4$ incurs an extra ~2% accuracy loss compared with MixUp, but it achieves better defense performance: when batch size is 32, there are obvious artifacts and color shift in the reconstruction (see Figure 3). However, with batch size 32, W-InstaHide alone also cannot defend the state-of-the-art gradient inversion, as structures of private images are still vaguely identifiable in reconstructions.

Appendix A provides the whole reconstructed dataset under MixUp and W-InstaHide.

5.3 Performance of combined defenses

We notice that two types of defenses (i.e perturbing gradient and encoding inputs) are complementary to each other, which motivates an evaluation of combining gradient pruning with MixUp or W-InstaHide.

(a) Batch size $= 1$

(b) Batch size $= 16$

(c) Batch size $= 32$

Figure 3: Reconstruction results under different defenses with batch size 1 (a), 16 (b) and 32 (c). When batch size is 32, combining gradient pruning and Weak-InstaHide makes the reconstruction almost unrecognizable (the last column).

As shown in Figure 3, when the batch size is 32, combining W-InstaHide ($k = 4$) with gradient pruning ($p = 0.9$) makes the reconstruction almost unrecognizable. The combined defense yields a higher LPIPS score than using gradient pruning with $p = 0.999$, but introduces a smaller accuracy loss (~7% compared with a no-defense pipeline).

Note that our evaluation uses *the strongest attack* and *relatively small batch sizes*. As shown in Appendix A, invalidating assumptions in Section 3 or increasing the batch size may hinder the attack with an even weaker defense (e.g. with a lower p, or smaller k), which gives a better accuracy.

5.4 Time estimate for end-to-end recovery of a single image

Table 3 shows time estimates for the end-to-end recovery of a single image in a Federated learning setting with GradPrune or InstaHide defense. We do not estimate for MixUp since it has been shown to be a weak defense (see Section 5.2).

Our time estimates consider three fairly small dataset sizes. The largest size in our estimate is a small fraction of a dataset of ImageNet scale. We consider a client holds a dataset of N private images and participates in Federated learning, which trains a ResNet-18 model with batch size $b = 128$. Assumes that the resolution of the client's data is $32 \times 32 \times 3$. If the attacker uses a single NVIDIA GeForce RTX 2080 Ti GPU as his computation resource, and runs gradient inversion with 10,000 iterations of optimization, then t, the running time for attacking a single batch is ~0.25 GPU hours (batch size b has little impact on the attack's running time, but a larger b makes the attack less effective).

Non-defended and gradient pruning. Recovering a single image in a non-defended pipeline (or a pipeline that applies gradient pruning alone as the defense) only requires the attacker to invert gradient of a single step of training, which takes time t.

InstaHide. When InstaHide is applied, the current attack [Carlini et al., 2020] suggests that recovering a single image would involve recovering the whole dataset first. As discussed in Section 4, Carlini et al.'s attack consists of two steps: 1) recover InstaHide images from gradient of T epochs.

Size of client's dataset (N)	No defense	GradPrune	InstaHide
5,000			934.48
50,000	0.25	0.25	46,579.01 ($\approx$ 5.5 GPU years)
500,000			4,215,524.32 ($\approx$493.4 GPU years)

Table 3: Time estimates (NVIDIA GeForce RTX 2080 Ti GPU hours) of recovering *a single image* from the client's dataset using the state-of-the-art gradient inversion attack [Geiping et al., 2020] under different defenses. We assume image resolution of the client's data is $32 \times 32 \times 3$.

This would take $(NT/b) \times t$ GPU hours. 2) Run the decode attack [Carlini et al., 2020] on InstaHide images to recover the private dataset, which involves:

    2a Train a neural network to detect similarity in recovered InstaHide images. Assume that training the network requires at least n recovered InstaHide images, then collecting these images by running gradient inversion would take $(n/b) \times t$ GPU hours. The training takes 10 GPU hours according to [Carlini et al., 2020], so training the similarity network would take $(n/b) \times t + 10$ GPU hours in total.

    2b Run the combinotorial algorithm to recover original images. Running time of this step has been shown to be at least quadratic in m, the number of InstaHide encodings [Chen et al., 2020]. This step takes $1/6$ GPU hours with $m = 5 \times 10^3$. Therefore for $m = NT$, the running time is at least $1/6 \times (\frac{NT}{5 \times 10^3})^2$ GPU hours.

In total, an attack on InstaHide in this real-world setting would take $(NT/b) \times t + (n/b) \times t + 10 + 1/6 \times (\frac{NT}{5 \times 10^3})^2$ GPU hours. We use $T = 50$ (used by [Carlini et al., 2020]), $n = 10,000$ and give estimate in Table 3. As shown, when InstaHide is applied on a small dataset ($N = 5,000$), the end-to-end recovery of a single image takes $> 3,000\times$ longer than in a no-defense pipeline or GradPrune pipeline; when InstaHide is applied on a larger dataset ($N = 500,000$), the computation cost for end-to-end recovery is enormous.

6 Conclusions

This paper first points out that the state-of-the-art gradient inversion attacks have made strong assumptions about knowing BatchNorm statistics and private labels. Relaxing such assumptions can significantly weaken these attacks.

The paper then reports the performance of a set of proposed defenses against gradient inversion attacks, and estimates the computation cost of an end-to-end recovery of a single image in different dataset sizes. Our evaluation shows that a weaker version of InstaHide combined with gradient pruning can defend the state-of-the-art attack, and the estimated time to recover a single image in a medium-size client dataset (e.g. of 500,000 images) is enormous.

As discussed in Section 4, the most secure practice for Federated learning is using cryptographic approaches [Bonawitz et al., 2016, Phong et al., 2018] to encrypt gradient. However, encryption-based approaches can be costly to deploy. Based on our evaluation, we recommend the following **best practices in Federated learning to mitigate gradient inversion risk:**

1. *Use BatchNorm layers in your deep net but don't share BatchNorm statistics of the private batch during Federated learning*. We have demonstrated in Section 3 that exposing Batch-Norm statistics to the attacker significantly improves the quality of gradient inversion. So a simple good practice would be to use BatchNorm layers, but do not share BatchNorm statistics in training, which has been shown feasible in [Li et al., 2021].

2. *Use a large batch size; do not use a batch size smaller than 32*. We have shown that a larger batch size hinders the attack by making it harder to guess the private labels (Section 3) and to recover the private images even with correct private labels (Section 5). Our experiments suggest that even with some weak defenses applied, a batch size smaller than 32 is not safe against the strongest gradient inversion attack.

3. *Try to combine multiple defenses to achieve better utility-privacy trade-off.* In our experiment, for a batch size of 32, combining InstaHide ($k = 4$) with gradient pruning ($p = 0.9$) achieves the best utility-privacy trade-off, by making the reconstruction almost unrecognizable at a cost of ~7% accuracy loss (using InstaHide also makes the end-to-end recovery of a single image more computationally expensive). Best parameters would vary for different deep learning tasks, but we strongly encourage Federated learning participants to explore the possibility of combining multiple defensive mechanisms, instead of only using one of them.

We hope to extend our work with a systematic evaluation of defenses for high-resolution images, once [Yin et al., 2021]'s implementation becomes available. We also hope to evaluate defense mechanisms that rely on adding noise to gradient, when new attacks can scale up to its batch size.

References

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pages 308–318, 2016.

Accountability Act. Health insurance portability and accountability act of 1996. *Public law*, 104:191, 1996.

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. In *ICML*, 2019.

K. A. Bonawitz, Vladimir Ivanov, Ben Kreuter, Antonio Marcedone, H. Brendan McMahan, Sarvar Patel, Daniel Ramage, Aaron Segal, and Karn Seth. Practical secure aggregation for federated learning on user-held data. In *NIPS Workshop on Private Multi-Party Machine Learning*, 2016.

Nicholas Carlini, Samuel Deng, Sanjam Garg, Somesh Jha, Saeed Mahloujifar, Mohammad Mahmoody, Shuang Song, Abhradeep Thakurta, and Florian Tramer. An attack on instahide: Is private learning possible with instance encoding? In *IEEE Symposium on Security and Privacy*, 2020.

Sitan Chen, Xiaoxiao Li, Zhao Song, and Danyang Zhuo. On instahide, phase retrieval, and sparse matrix factorization. *arXiv preprint arXiv:2011.11181*, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

Cynthia Dwork. The differential privacy frontier. In *Theory of Cryptography Conference (TCC)*, pages 496–502, 2009.

Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Foundations and Trends in Theoretical Computer Science*, 9(3–4):211–407, 2014.

Jonas Geiping, Hartmut Bauermeister, Hannah Dröge, and Michael Moeller. Inverting gradients–how easy is it to break privacy in federated learning? In *NeurIPS*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Yangsibo Huang, Zhao Song, Kai Li, and Sanjeev Arora. Instahide: Instance-hiding schemes for private distributed learning. In *ICML*, 2020.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015.

Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Keith Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *arXiv preprint arXiv:1912.04977*, 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

Alex Lamb, Vikas Verma, Juho Kannala, and Yoshua Bengio. Interpolated adversarial training: Achieving robust neural networks without sacrificing too much accuracy. In *Proceedings of the 12th ACM Workshop on Artificial Intelligence and Security*, pages 95–103, 2019.

California State Legislature. California consumer privacy act. https://oag.ca.gov/privacy/ccpa, 2018.

Xiaoxiao Li, Meirui Jiang, Xiaofei Zhang, Michael Kamp, and Qi Dou. Fedbn: Federated learning on non-iid features via local batch normalization. In *ICLR*, 2021.

H Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, et al. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics (AISTATS)*, pages 1273–1282, 2016.

414 Tianyu Pang, Kun Xu, and Jun Zhu. Mixup inference: Better exploiting mixup to defend adversarial
415   attacks. In *ICLR*, 2020.

416 Nicolas Papernot, Steve Chien, Shuang Song, Abhradeep Thakurta, and Ulfar Erlingsson. Making
417   the shoe fit: Architectures, initializations, and tuning for learning with privacy, 2020. URL
418   `https://openreview.net/forum?id=rJg851rYwH`.

419 Le Trieu Phong, Yoshinori Aono, Takuya Hayashi, Lihua Wang, and Shiho Moriai. Privacy-preserving
420   deep learning: Revisited and enhanced. In *ICATIS*, pages 100–110, 2017.

421 Le Trieu Phong, Yoshinori Aono, Takuya Hayashi, Lihua Wang, and Shiho Moriai. Privacy-preserving
422   deep learning via additively homomorphic encryption. *IEEE Transactions on Information Forensics*
423   *and Security*, 2018.

424 Adi Shamir. How to share a secret. *Communications of the ACM*, 22(11):612–613, 1979.

425 Florian Tramèr and Dan Boneh. Differentially private learning needs better features (or much more
426   data). In *ICLR*, 2021.

427 Wenqi Wei, Ling Liu, Margaret Loper, Ka-Ho Chow, Mehmet Emre Gursoy, Stacey Truex, and
428   Yanzhao Wu. A framework for evaluating gradient leakage attacks in federated learning. *arXiv*
429   *preprint arXiv:2004.10397*, 2020.

430 Hongxu Yin, Arun Mallya, Arash Vahdat, Jose M Alvarez, Jan Kautz, and Pavlo Molchanov. See
431   through gradients: Image batch recovery via gradinversion. *arXiv preprint arXiv:2104.07586*,
432   2021.

433 Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. Mixup: Beyond empirical
434   risk minimization. In *ICLR*, 2018a.

435 Hongyi Zhang, Yann N Dauphin, and Tengyu Ma. Fixup initialization: Residual learning without
436   normalization. In *ICLR*, 2019.

437 Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable
438   effectiveness of deep features as a perceptual metric. In *CVPR*, 2018b.

439 Bo Zhao, Konda Reddy Mopuri, and Hakan Bilen. idlg: Improved deep leakage from gradients.
440   *arXiv preprint arXiv:2001.02610*, 2020.

441 Junyi Zhu and Matthew Blaschko. R-gap: Recursive gradient attack on privacy. In *ICLR*, 2021.

442 Ligeng Zhu, Zhijian Liu, and Song Han. Deep leakage from gradients. In *NeurIPS*, 2019.