REST: Stress Testing Large Reasoning Models by Asking Multiple Problems at Once

Abstract

Recent Large Reasoning Models (LRMs) have achieved remarkable progress, yet their evaluation still relies on a narrow paradigm: evaluating one question at a time. This single-question setup suffers from two major limitations: (1) vulnerability to data contamination and less challenging (e.g., DeepSeek-R1 achieves 97.0% on MATH500), forcing costly and perpetual creation of new questions with large human efforts, (2) failure to evaluate models under multi-context pressure, a key requirement for real-world deployment. To bridge this gap, we present **REST** (Reasoning Evaluation through Simultaneous Testing), a stress-testing framework that exposes LRMs to multiple problems simultaneously. Beyond basic reasoning, REST evaluates several under-tested capabilities: *contextual priority allocation* and *dynamic cognitive load management*. Our evaluation over **30** advanced reasoning models on **9** reasoning benchmarks reveals several striking findings: Even state-of-the-art (SOTA) models such as ***DeepSeek-R1 exhibit substantial performance degradation under stress testing***, challenging the prevailing assumption that "LLMs are multi-problem solvers". Crucially, ***REST demonstrates stronger discriminative power*** than existing benchmarks, revealing clear performance gaps among models that exhibit similar, near-ceiling performance under traditional evaluation. Some key insights emerge from our analysis: (1) the ***"overthinking trap"*** is a critical factor contributing to the performance degradation; (2) the models trained with ***"Long2Short" technique preserve more accuracy*** of their single-problem performance under REST, out-performing their standard-trained counterparts. These results establish REST as a cost-efficient, future-proof evaluation paradigm that better reflects real-world reasoning demands while reducing reliance on continuous human annotation. Code is available at `https://anonymous.4open.science/r/REST_ARR-159C`.

1 Introduction

Recent years have witnessed remarkable progress in LRMs (Yang et al., 2024b; Guo et al., 2025; OpenAI, 2025b; Pei et al., 2025), which exhibit strong performance across numerous reasoning tasks. Many benchmarks (Cobbe et al., 2021a; Hendrycks et al., 2021a; Rein et al., 2024; Li et al., 2025) have been introduced to assess LRMs. However, in most existing benchmarks, questions are presented to LRMs one at a time, requiring the model to answer each independently. While this approach is effective for early model development, it now faces two fundamental challenges:

First, some widely used benchmarks, such as GSM8K (Cobbe et al., 2021a) and MATH (Hendrycks et al., 2021a), are rapidly losing their discriminative power, as many LRMs achieve near-saturated accuracy (e.g., *DeepSeek-R1* achieves 97.0% accuracy on MATH500). As a result, the community is forced into a costly cycle of benchmark obsolescence—continuously developing new, more difficult datasets (e.g., AIME25 (Ye et al., 2025)) while discarding still valuable ones. This raises our first key question: ***Can we extend the utility of existing benchmarks by increasing their difficulty, rather than constantly building new ones?***

Second, single-question evaluation fail to capture how models operate in real-world, multi-context scenarios requiring reasoning across multiple queries. For instance, in some conversation systems, large language models (LLMs) need to address multiple questions within one single run to reduce computational cost (Lin et al., 2023; Zhu et al., 2025). Also, in software development, LLMs must identify and fix multiple subtle bugs of a code snippet within a single structured output (Yang et al., 2025b). Though a few prior studies (Cheng et al., 2023; Lin et al., 2023; Wang et al., 2024; Son et al., 2024) have investigated multi-question prompting,

Figure 1: Illustration of REST evaluation. REST concatenates multiple questions into a single prompt, stress testing LRMs' ability in handling increasing reasoning loads within a single reasoning process.

they only focus on simple tasks such as text classification (Semwal et al., 2018) or commonsense QA (Talmor et al., 2019), which are **insufficient** to assess the capability of current LRMs. This leads to our second question: ***How well can current LRMs handle multiple reasoning-intensive questions simultaneously, and what factors affect their performance in such settings?***

To answer the aforementioned research questions, we propose **REST** (Reasoning Evaluation through Simultaneous Testing), a simple yet powerful method that repurposes existing benchmarks into more challenging variants. Specifically, We transform **9** representative reasoning benchmarks (*e.g.,* MATH500, AIME24 and GPQA) using REST, concatenating multiple questions into a single instruction to evaluate these questions at once (see Fig. 1 for illustration). Through a comprehensive evaluation more than **30** LRMS, we have obtained some valuable findings:

- Even SOTA LRMs like DeepSeek-R1 (Guo et al., 2025) **exhibit significant performance degradation** under REST (e.g., 29.1% accuracy drop on AIME24), revealing a critical limitation in their reasoning robustness and challenging the common assumption that "LLMs are multi-problem solvers" (Cheng et al., 2023; Wang et al., 2024; Son et al., 2024).

- REST offers **greater discriminative power**: models with near-identical accuracy on single-question evaluation settings diverge sharply when evaluated under REST.

- REST effectively **revitalizes existing benchmarks**, making them challenging again for top-tier models.

Through further error analysis, we find that the "*overthinking phenomenon*" (Sui et al., 2025; Chen et al., 2024; Wang et al., 2025)—where LRMs produce unnecessarily long and redundant reasoning—is a primary cause of performance degradation under REST. Besides, LRMs trained with "*Long2Short*" training (Sui et al., 2025; Aggarwal and Welleck, 2025; Arora and Zanette, 2025), which encourages concise reasoning, perform better than their standard-trained counterparts under REST. These findings establish REST offers a cost-effective and scalable alternative to constant benchmark replacement, while providing insights for building more robust reasoning systems capable of handling real-world, multi-query scenarios.

2 REST: Reasoning Evaluation through Simultaneous Testing

REST aims to enhance the utility of existing benchmarks by making them more challenging. In REST, we introduce a simple yet effective evaluation protocol that concatenates multiple questions into a single prompt to increase the reasoning load of LRMs. The simplicity of this evaluation protocol is intentional: by concatenating original questions rather than modifying them, REST avoids (1) the potential errors introduced by altering question content and (2) the costly, expert-intensive process of creating new problems from scratch. The details of benchmark reconstruction and evaluation of REST are presented in Sec. 2.1 and Sec. 2.2, respectively.

2.1 REST Benchmark Reconstruction

Let the original benchmark be denoted as $\mathcal{Q} = \{q_1, q_2, \ldots q_N\}$, where q_i represents an individual question and N is the total number of questions. REST transforms the benchmark into a new prompt set $\mathcal{P}^s$ by concatenating s consecutive questions

into each prompt. We refer to the parameter $s \in \mathbb{Z}^+$ as the stress level, since a larger s imposes a greater reasoning burden on the model. Formally, for each $i \in \{1, 2, \ldots, N\}$, we define the stress-level-s prompt p_i^s as:

$$p_i^s = \texttt{Compose}(q_i, q_{i+1}, \ldots, q_{[(i+s-1) \bmod N]}),$$
$$i \in \{1, 2, \ldots, N\}.$$

The function $\texttt{Compose}()$ formats multiple questions into a single prompt:

$$\texttt{Compose}(q_1, \ldots, q_s) = \text{``}Q_1 : \{q_1\}, \ldots, Q_s : \{q_s\}.$$

Moreover, the subscript $q_{[(i+s-1) \bmod N]}$ indicates cyclic indexing, which allows wrapping around when reaching the last question. By concatenating consecutive questions with cyclic indexing, each original question q_i *appears exactly s times* across all the prompts, and *exactly once in each of the s possible positions* within the concatenated prompts. This construction guarantees **fair question coverage** across different stress levels, ensuring that any observed performance degradation under REST arises from the increased reasoning load of handling multiple questions, rather than from artifacts of uneven question usage or positional bias.

After the transformation, REST produces a new prompt set $\mathcal{P}^s = \{p_1^s, p_2^s, \ldots, p_N^s\}$, where each prompt contains s questions. Crucially, the transformed benchmark preserves the original size ($|\mathcal{P}^s| = N$) while replacing single-question prompts with multi-question ones.

2.2 REST Evaluation

Given an LRM model f, we evaluate it on each prompt p_i^s to obtain an output response $o_i^s = f(p_i^s)$. From this response, we extract the individual predicted answers $\{\hat{a}_i^s, \hat{a}_{i+1}^s, \ldots, \hat{a}_{[(i+s-1) \bmod N]}^s\}$ using a function $\texttt{Extract}()$:

$$\texttt{Extract}(o_i^s) = \{\hat{a}_i^s, \hat{a}_{i+1}^s, \ldots, \hat{a}_{[(i+s-1) \bmod N]}^s\}.$$

To facilitate accurate extraction, we instruct LRMs to format their answers in task-specific ways. For Mathematical and GPQA problems, we instruct the model to put each answer within "\boxed{}", while for code generation tasks, answers must be wrapped in Python code blocks "```python ```". Notably, although a more structured format method like JSON output could offer convenience for output parsing, we deliberately avoid imposing such strict formatting constraints, as prior studies (Tam et al., 2024; Shorten et al., 2024) indicate that such requirements will degrade performance.

We employ both rule-based and LLM-based extraction methods: (a) The rule-based method uses regular expressions to extract answers from predefined markers (e.g., "\boxed{}"); (b) The LLM-based method prompts a model to retrieve the predicted answer from the response for each question. Further implementation details can be found in Appendix E. Finally, we define the model's accuracy at stress level s by comparing the predicted answer $\hat{a}$ and the ground truth answer a:

$$Acc(\mathcal{P}^s) = \frac{1}{N} \sum_{i=1}^{N} Acc(p_i^s) = \frac{1}{N} \sum_{i=1}^{N}$$
$$\frac{1}{s} \sum_{j=1}^{s} \delta(\hat{a}_{[(i+j-1) \bmod N]}^s, a_{[(i+j-1) \bmod N]}^s),$$

where δ is the Kronecker delta function such that $\delta(i, j) = 1$ if and only if $i = j$ and 0 otherwise.

3 Experiment

3.1 Evaluation Setup

We evaluate over **30** LRMs, spanning a parameter size range from 1.5B to 671B. The temperature and top-p parameters are configured according to the corresponding official guidelines for each model. We set a maximum output token length of 32K for reasoning models and 8K for non-reasoning models. In addition, we conduct experiments with an extended 128K token limit, but observe negligible performance differences, as shown in Tab. 8 of Appendix F. Our evaluation is based on OpenCompass[*] toolkit. To ensure consistency, we adopt the official prompt for each task, with a minor format requirement for multi-question responses: "Answer the above questions one by one. Remember to put each answer within \boxed{} (or ```python ``` for code generation)." We further validate our findings with alternative prompt designs (Appendix K), confirming that results are robust and not artifacts of prompting.

We select 9 representative benchmarks for evaluation, and in REST, we set different stress levels s for each benchmark. Specifically, for relatively simple benchmarks like GSM8K, ARC-C and BBH, the stress levels are $s \in \{1, 3, 6, 9, 12\}$; for medium-difficulty benchmarks, including MATH500 and AMC23, they are set

---

[*]https://github.com/open-compass/opencompass

Table 1: Evaluation results on various math benchmarks. The "Stress" column reports the average performance across four stress levels, as described in Sec. 3.1. Models that perform best under "Stress" are highlighted in gray. Results on non-math tasks are in Tab. 2 and Tab. 4 (Appendix); additional models are reported in Tab. 6 (Appendix).

Bench / Model	GSM8K		MATH500		AMC23		AIME24		AIME25		AVG.	
	Single	Stress	Single	Stress	Single	Stress	Single	Stress	Single	Stress	Single	Stress
1.5B LRMs												
DeepSeek-R1-Distill-Qwen-1.5B (Guo et al., 2025)	84.62	70.21	83.40	42.47	62.50	13.98	29.17	4.97	25.00	5.91	56.94	27.51
DeepScaleR-1.5B (Luo et al., 2025)	84.84	66.58	**87.60**	59.77	76.25	32.05	**38.75**	12.82	**31.25**	14.23	**63.74**	37.09
L1-Qwen-1.5B-Max (Aggarwal and Welleck, 2025)	84.17	**78.29**	83.40	**73.23**	**77.50**	**48.37**	20.00	**15.13**	22.92	**14.95**	57.60	**45.99**
Qwen2.5-Math-1.5B-Inst (Yang et al., 2024c)	**85.37**	67.49	73.00	53.94	57.50	22.22	10.83	6.17	10.83	2.83	47.51	30.53
7 ∼ 8B LRMs												
DeepSeek-R1-Distill-Qwen-7B (Guo et al., 2025)	89.49	89.06	93.00	66.75	87.50	36.06	54.17	16.53	35.42	11.37	71.92	43.95
Efficient-R1-7B ($\alpha = 0.2$) (Arora and Zanette, 2025)	87.95	80.38	88.20	76.41	85.00	48.05	50.42	22.12	33.75	17.25	69.06	48.84
Nemotron-Nano-8B (Bercovich et al., 2025)	91.36	70.52	94.40	**86.04**	90.00	**76.24**	63.33	43.55	50.00	**32.28**	77.82	**61.71**
AReaL-boba-RL-7B (Mei et al., 2025)	91.66	77.80	95.00	60.77	91.25	32.94	61.25	21.43	45.83	12.33	77.00	41.05
Light-R1-7B-DS (Wen et al., 2025)	88.05	82.69	93.20	61.73	90.00	34.91	55.83	16.63	45.83	12.96	74.58	41.78
OpenR1-Qwen-7B (Face, 2025)	**95.60**	90.22	92.20	81.64	83.75	54.11	47.50	26.77	32.92	21.19	70.39	54.79
OpenThinker2-7B (Team, 2025a)	94.39	91.99	93.80	83.30	85.00	63.23	54.58	34.50	41.67	23.66	73.89	59.33
Qwen2.5-Math-7B-Inst (Yang et al., 2024b)	95.53	78.53	83.60	56.59	60.00	28.46	14.17	6.40	11.67	5.33	52.99	35.06
Qwen2.5-7B-Inst (Yang et al., 2024a)	92.27	85.12	77.60	65.78	42.50	34.46	10.00	7.02	3.75	3.32	45.22	39.14
Qwen3-8B (Yang et al., 2025a)	95.30	**93.90**	**95.40**	80.28	92.50	53.59	74.58	44.28	63.33	32.06	84.22	60.82
32B LRMs												
DeepSeek-R1-Distill-Qwen-32B (Guo et al., 2025)	95.54	95.50	94.60	88.97	94.75	**86.24**	72.92	52.51	51.67	33.83	81.90	71.41
Qwen-QwQ-32B (Team, 2025b)	95.83	**95.78**	96.20	**92.49**	95.00	82.89	78.75	54.79	69.58	41.53	87.07	**73.49**
AReaL-boba-SFT-32B (Mei et al., 2025)	95.01	94.75	95.00	88.92	**97.50**	78.96	77.50	45.79	60.00	33.55	85.00	68.39
Light-R1-32B-DS (Wen et al., 2025)	95.83	94.79	95.60	83.66	96.25	68.80	77.50	41.26	60.00	33.80	85.04	64.46
Qwen2.5-32B-Inst (Yang et al., 2024a)	95.53	93.77	82.20	73.39	60.00	49.72	20.00	9.61	16.67	6.73	54.88	46.64
Qwen3-32B (Yang et al., 2025a)	**95.91**	93.81	**96.60**	83.64	93.75	80.62	**85.00**	**56.67**	**71.67**	**44.53**	**88.59**	71.85
MoE LRMs												
GPT-OSS-20B (OpenAI, 2025a)	88.02	49.31	88.40	46.96	97.50	56.56	66.25	36.20	63.33	29.87	80.70	43.78
GPT-OSS-120B (OpenAI, 2025a)	84.91	47.65	89.60	60.06	93.75	71.93	67.08	60.28	68.33	52.39	80.73	58.46
Qwen3-30B-A3B (Yang et al., 2025a)	96.13	94.91	96.40	80.36	**98.75**	72.34	79.58	48.38	**68.75**	28.67	87.92	64.93
DeepSeek-R1 (Guo et al., 2025)	**96.20**	96.16	**97.00**	92.09	93.75	**81.80**	81.66	52.49	**68.75**	37.17	87.47	**71.94**
Proprietary LRMs												
O3-mini (OpenAI, 2025b)	**95.83**	93.85	95.00	**86.62**	90.00	59.17	**79.16**	34.07	71.66	20.63	86.25	55.51
O4-mini (OpenAI, 2025b)	93.71	93.07	90.00	82.40	96.25	**82.79**	73.33	49.69	**80.00**	41.42	86.66	**69.87**
Gemini-2.5-Flash-Thinking (Team et al., 2023)	89.23	91.28	**97.20**	69.92	97.50	47.63	76.67	26.60	71.67	16.54	86.45	50.39

as $s \in \{1, 3, 5, 7, 9\}$; and for more challenging benchmarks, such as AIME24, AIME25, GPQA-Diamond, and LiveCodeBench (v5), the stress levels are $s \in \{1, 2, 3, 4, 5\}$. To ensure clarity and consistency in evaluation, we report the performance of REST as the **average accuracy** across stress levels greater than 1. Detailed accuracy statistics for each stress level are provided in Appendix D. For relatively small benchmarks like AIME24, AIME25, and AMC23, we conduct 8 random runs and report the average to reduce variance. Results on ARC-C and BBH are included in Tab. 4 (Appendix).

3.2 Evaluation Result

Tab. 1, Tab. 2 and Tab. 4 (Appendix) present the performance of various LRMs on the original reasoning benchmarks (Single) and their transformed counterparts by REST (Stress). Our key findings can be summarized as follows:

LRMs can handle multiple simple questions at once, but struggle with challenging ones. LRMs can address several relatively simple problems within a single run. As shown in Tab. 1, on GSM8K, the accuracy drops under REST for DeepSeek-R1-Distill-Qwen-7B (R1-7B) is just 0.43%. However, ***this robustness diminishes rapidly on more challenging problems***. As shown in Tab. 1, even DeepSeek-R1 suffers substantial performance degradation (e.g., 31.58% accuracy drop on AIME25) when asked to solve multiple Olympiad-level problems within a single reasoning process. This performance gap is even more pronounced for smaller models, such as R1-7B, whose accuracy on AIME24 drops sharply from 54.17% to 16.53% under REST. This contrast——strong multi-question performance on simple tasks but sharp degradation on hard ones——indicates that the performance drop under REST stems not from format artifacts, but from inherent limitations in the LRMs' reasoning capacity.

(a) GSM8K   (b) MATH500   (c) AMC23

Figure 2: Performance comparison of LRMs of different sizes under various stress levels. REST reveals significant performance disparities among models of different sizes, although they demonstrate comparable, near-ceiling performance in traditional single-question evaluations.

(a) 1.5B Model on GSM8K   (b) 7B Model on MATH500   (c) 32B Model on AMC23

Figure 3: Limitation of downstream post training. Downstream post training exacerbates performance degradation under higher stress levels compared to the original DeepSeek distilled models.

REST enhances the discriminative power of existing benchmarks. By concatenating multiple problems into a single prompt, ***REST amplifies performance gaps among models that exhibit comparable, near-ceiling accuracy*** in traditional single-question evaluations. For example, on MATH500, DeepSeek-R1-Distill-Qwen-7B and DeepSeek-R1-Distill-Qwen-32B achieve single-question accuracies of 93.0% and 94.6%, respectively, with R1-7B trailing by just 1.6%. However, the accuracy of R1-7B plummets to 66.75% under REST, while R1-32B maintains a higher 88.97%, revealing a pronounced 22.22% performance gap. This contrast is similarly evident among models of the same size (e.g., AReaL-boba-RL-7B and OpenThinker2-7B). Similar trends are also observed on AMC23, validating that REST can significantly enhance the discriminative power of existing medium-difficulty benchmarks through problem concatenation.

Limitations of downstream post training. The success of DeepSeek-R1 (Guo et al., 2025) has inspired numerous follow-up studies (Luo et al., 2025; Mei et al., 2025; Wen et al., 2025), which fine-tune DeepSeek distilled models on downstream tasks (e.g., math and code). Although such downstream post training yields improved single-question accuracy, our findings suggest that ***they can not maintain their performance advantage on multi-question scenarios as in REST***. For instance,

models like AReaL-boba-RL-7B and Light-R1-7B-DS, both post trained on DeepSeek-R1-Distill-Qwen-7B, achieve single-question accuracies of 95.00% and 93.20% on MATH500, slightly higher than the 93.00% accuracy of R1-7B. However, under REST, their accuracies drop significantly to 60.77% and 61.73%, respectively, both falling behind the 66.75% achieved by R1-7B. This discrepancy becomes even more pronounced at higher stress levels (e.g., stress level $s = 9$), as detailed in Fig. 3b and Tab. 13 (in Appendix). This performance degradation also extends to larger models, such as Light-R1-32B-DS and R1-32B, and is consistently observed across other benchmarks like AMC23, as shown in Tab. 1. These findings reinforce recent calls (Yue et al., 2025; Shah et al., 2025; Hochlehnert et al., 2025) for a more cautious assessment of the benefits of downstream post RL training in enhancing reasoning capabilities.

Potential of "Long2Short" Training. Despite their impressive performance, LRMs often produce unnecessarily lengthy reasoning traces (Sui et al., 2025; Chen et al., 2024). To mitigate this issue, recent studies (Aggarwal and Welleck, 2025; Arora and Zanette, 2025; Team et al., 2025b) propose the "*Long2Short*" technique, which introduces a length reward in the training objective to promote more concise and efficient reasoning. Our experiments reveal that ***"Long2Short" training also enhances***

| (a) 1.5B Model on MATH500 | (b) 7B Model on MATH500 | (c) 7B Model on AMC23 |

Figure 4: The effect of Long2Short training on REST. Long2Short training mitigates the performance degradation under higher stress levels.

Table 2: Evaluation results on GPQA-Diamond and LiveCodeBench (v5). The "Stress" column reports the average performance across four distinct stress levels, as described in Sec. 3.1. Models perform best under "Stress" are highlighted in gray. Results on additional models are reported in Tab. 5 (Appendix).

Bench Model	GQPA-Diamond		LiveCodeBench (v5)	
	Single	Stress	Single	Stress
1.5B LRMs				
DeepSeek-R1-Distill-Qwen-1.5B	**37.37**	22.11	15.05	0.48
DeepScaleR-1.5B	31.82	27.90	**21.15**	1.83
L1-Qwen-1.5B-Max	36.87	**32.03**	19.35	**2.45**
Qwen2.5-1.5B-Inst	26.26	21.52	1.79	0.37
7 ∼ 8B LRMs				
DeepSeek-R1-Distill-Qwen-7B	51.01	31.67	37.63	2.89
Efficient-R1-7B ($\alpha = 0.2$)	47.97	34.37	38.71	2.50
Nemotron-Nano-8B	51.01	34.06	50.90	8.56
AReaL-boba-RL-7B	48.98	29.13	37.99	4.73
Light-R1-7B-DS	41.91	30.32	39.07	2.85
OpenR1-Qwen-7B	38.38	36.04	4.66	1.27
OpenThinker2-7B	49.49	40.60	39.43	14.51
Qwen2.5-7B-Inst	35.86	35.15	13.98	10.19
Qwen3-8B	**61.11**	**58.60**	**56.99**	**31.13**
32B LRMs				
DeepSeek-R1-Distill-Qwen-32B	60.10	53.73	55.56	26.71
Qwen-QwQ-32B	63.64	**60.03**	62.37	**32.16**
AReaL-boba-SFT-32B	63.13	50.59	60.93	31.74
Light-R1-32B-DS	**65.66**	50.11	60.93	28.22
Qwen2.5-32B-Inst	42.93	40.04	26.88	24.00
Qwen3-32B	63.33	48.13	**62.72**	30.98
MoE LRMs				
GPT-OSS-20B	53.54	59.52	43.37	29.83
GPT-OSS-120B	60.10	**65.93**	63.08	**49.16**
Qwen3-30B-A3B	64.65	50.74	61.65	38.48
DeepSeek-R1	**70.20**	64.63	**63.44**	40.83
Proprietary LRMs				
O3-mini	71.21	67.39	60.21	48.36
O4-mini	76.26	**73.11**	70.61	**63.07**
Gemini-2.5-Flash-Thinking	**78.79**	68.00	61.65	48.34

reasoning robustness under REST. As illustrated in Fig. 4, models trained with "*Long2Short*", such as L1-Qwen-1.5B-Max (Aggarwal and Welleck, 2025), exhibit notable performance advantages at high stress levels. For instance, as shown in Tab. 12 (Appendix), L1-Qwen-1.5B-Max surpasses R1-1.5B by a substantial 44.71% accuracy margin at stress level $s = 9$ on MATH500. A similar trend is also observed among 7B models (e.g., Efficient-R1-7B ($\alpha = 0.2$) v.s., R1-7B). Further

error analysis (Sec. I in Appendix) confirms that "*Long2Short*" mitigates not only length-related failures but also core reasoning degradation patterns, enhancing LRM's resilience in multi-question settings.

4 Further Analysis

Performance drops are NOT primarily due to output length limits. To uncover the underlying reasons for LRMs' failures in REST, we analyze the primary factors contributing to performance degradation under multi-question stress. A natural hypothesis is that models fail because they exceed the maximum output length when solving multiple problems. However, our error analysis reveals that this is not the primary cause—*models often fail even when their responses remain within the maximum output token limit.*

To investigate the cause of errors, we categorize model failures into six types (Tab. 3) and manually analyze the error types across four representative LRMs on AIME24 (Fig. 5). Additional error analysis on more models and benchmarks are in Tab. 9 (Appendix). For DeepSeek-R1 (Fig. 5d), Question Omission (QO) and Reasoning Error (RE) dominate, together accounting for 42.00% of failures. The high frequency of Question Omission (QO) suggests that DeepSeek-R1 suffers from a pronounced **question position bias**, focusing more on the first question in multi-problem prompts, despite explicit instructions to address each question sequentially. In contrast, error causes like Summary Error (SE), Output Truncation (OT), and Endless Repetition (ER) are rare in such large models.

However, for smaller models like Light-R1-7B (in Fig. 5b), the *error profile shifts* significantly, with Endless Repetition (ER) and Output Truncation (OT) becoming more prominent, collectively accounting for 48.90%. This shift underscores smaller models' unique challenges, whose limited capacity significantly exacerbates performance

Table 3: Six common cause of the performance degradation in REST.

Error Cause	Definition
Output Truncation (OT)	The output is trucated due to reaching the maximum output length (32K tokens for LRMs).
Endless Repetition (ER)	The model repeatedly generates the same phrase or sentence in its output.
Format Violation (FV)	The model fails to comply with the required output format (*e.g.,* not putting the answer whtin "\boxed{}").
Question Omission (QO)	The model fails to respond to all the given questions in the thinking process. (*e.g.,* only answers the first question)
Summary Error (SE)	The model fails to summarize all the answers generated in the thinking process.
Reasoning Error (RE)	Error occurs in the reasoning process, such as calculation mistakes or concept misunderstandings.

(a) R1-7B
(Guo et al., 2025)

(b) Light-R1-7B
(Wen et al., 2025)

(c) Nemotron-7B
(Bercovich et al., 2025)

(d) DeepSeek-R1
(Guo et al., 2025)

Figure 5: The error type distribution for various LRMs on AIME24 under REST.

degradation under the stress imposed by REST. Finally, it is important to note that no Format Violation (FV) errors are found for any of the four models, which is why they are not included in Fig. 5. This observation supports the robustness of our prompt design and answer extraction strategy, confirming that *the observed performance degradation arises primarily from the intrinsic limitations of the LRMs themselves*, rather than artifacts introduced by the evaluation process.

LRMs that perform better on REST exhibit concise reasoning for earlier questions. In this paragraph, we investigate why certain models exhibit substantial performance differences under REST, despite achieving similar results on traditional single-question benchmarks. To this end, we analyze responses on AIME24 by manually segmenting each model's output into question-aligned chunks and measuring the number of reasoning tokens allocated to each. As shown in Fig. 6, high-performing models under REST, such as GPT-OSS-120B (60.28% AIME24 accuracy under REST), **allocate tokens more evenly** across positions and use fewer reasoning tokens per question on average, indicating concise and balanced reasoning. In contrast, lower-performing models like R1-7B (16.53% AIME24 accuracy under REST) concentrate the majority of their token budget on the first question, leaving insufficient capacity for subsequent ones. This pattern suggests that strong REST performance correlates with the ability to

adaptively allocate reasoning effort——employing more concise reasoning on early questions under pressure, preserving resources for later ones. We term this capability as "**adaptive reasoning effort allocation**", which we believe is a critical factor to achieve high performance under REST.

Question position affects performance under stress test. Recent studies (Yu et al., 2024; Liu et al., 2024) have identified positional biases of LLMs over long inputs. In this paragraph, we investigate whether the position of questions within the input can influence accuracy. Fig. 7 presents a heatmap illustrating the accuracy for questions placed at different positions, indicating that *questions appearing earlier consistently achieve higher accuracy*, even under the highest stress levels. While the accuracy for later questions tends to decline as the stress level increases. We attribute this position-dependent performance degradation to three primary factors. First, as revealed by our error analysis, Question Omission (QO) is a prevalent failure mode, even for strong LRMs like DeepSeek-R1, leading models to frequently overlook later questions in a prompt. Second, the reasoning trace for earlier questions may act as noise, potentially disrupting the reasoning process of subsequent ones. Finally, as shown in Fig. 6, answering the first questions consume a considerable portion of the output tokens, limiting the model's available reasoning tokens for later questions.

(a) R1-7B (16.53% Acc.)   (b) Qwen3-30B-A3B (48.38% Acc.)   (c) GPT-OSS-120B (60.28% Acc.)

Figure 6: The reasoning token count for questions at different positions on AIME24. The number in parentheses is the accuracy on AIME24 under REST. Results on additional models are reported in Fig. 8 (Appendix).

(a) 7B on AIME24   (b) 7B on AIME25   (c) 32B on AIME24   (d) 32B on AIME25

Figure 7: The effect of question position under stress tests. The performance at each position is calculated by averaging the accuracy of questions appearing at the same position across the full benchmark. LRMs generally achieve higher accuracy for earlier questions, while their performance declines for subsequent ones.

5 Related Work

Compositional Instruction Evaluation Many real-world applications require LLMs to address multiple queries within a single inference pass. For instance, in some conversation systems, models must respond to multiple queries simultaneously to minimize computational overhead (Lin et al., 2023; Zhu et al., 2025). Similarly, in software development, LLMs are often expected to detect and correct multiple subtle bugs in a code snippet through a single output (Yang et al., 2025b). Several benchmarks have been proposed to evaluate LLMs' ability to follow compositional instructions. Batch prompting (Cheng et al., 2023; Lin et al., 2023), multi-problem prompting (Wang et al., 2024), and multi-task inference benchmark (Son et al., 2024) concatenates multiple instructions into a prompt, primarily for improving inference efficiency on simple tasks like text classification. However, these methods do not involve complex reasoning tasks—— a key frontier in contemporary LLM research.

Benchmarks for LRMs The rigorous assessment of the reasoning ability of LLMs relies heavily on specialized benchmarks. In mathematical reasoning, GSM8K (Cobbe et al., 2021b) and MATH (Hendrycks et al., 2021b) are most commonly used. As model capabilities surge, harder benchmarks like AIME (AI-MO, 2024; Lin, 2025) and Omni-Math (Gao et al., 2024) have emerged,

further pushing the boundaries of mathematical evaluation. Beyond mathematics, reasoning in other domains like code generation (Jain et al., 2024; Quan et al., 2025; Jimenez et al., 2024), logic reasoning (Suzgun et al., 2023), cryptographic decryption (Li et al., 2025), and scientific problem-solving (Rein et al., 2024), is also critical. Despite the increasing difficulty of these benchmarks, the rapid improvement of models means that their differentiating power can diminish when evaluated solely through standard single-problem manner. Our REST, however, can systematically increasing the difficulty of existing benchmarks by controlling stress level.

6 Conclusion

In conclusion, we present REST, a stress testing framework to evaluate LRMs in simultaneous multi-problem solving scenarios. REST substantially sharpens the discriminative power of existing benchmarks, exposing pronounced performance gaps among models that appear comparable in traditional single-question evaluations. Futhermore, REST uncovers a few reasoning misbehaviors, such as question omission and summary error, which remain obscure in single-question assessments. Critical findings, such as the identification of question position bias and the demonstrated effectiveness of "*Long2Short*" training, offer valuable insights for the future development of more robust LRMs.

Limitations

While REST provides a powerful and discriminative evaluation framework, several limitations remain. First, it increases evaluation costs, as multi-problem prompts generally require longer reasoning sequences, leading to slightly increased computational overhead. Additionally, given the rapid pace of advancement in reasoning models, there is always a risk that our experiments may not capture the latest SOTA LRMs released after our initial experiments. To address this, we plan to continuously monitor newly released models and maintain an up-to-date leaderboard to reflect the latest progress in the field.

References

Pranjal Aggarwal and Sean Welleck. 2025. L1: Controlling how long a reasoning model thinks with reinforcement learning. *arXiv preprint arXiv:2503.04697*.

AI-MO. 2024. AIMO Validation AIME Dataset. https://huggingface.co/datasets/AI-MO/aimo-validation-aime. Accessed: 2025-03-29.

Daman Arora and Andrea Zanette. 2025. Training language models to reason efficiently. *arXiv preprint arXiv:2502.04463*.

Akhiad Bercovich, Itay Levy, Izik Golan, Mohammad Dabbah, Ran El-Yaniv, Omri Puny, Ido Galil, Zach Moshe, Tomer Ronen, Najeeb Nabwani, Ido Shahaf, Oren Tropp, Ehud Karpas, Ran Zilberstein, Jiaqi Zeng, Soumye Singhal, Alexander Bukharin, Yian Zhang, Tugrul Konuk, and 114 others. 2025. Llama-nemotron: Efficient reasoning models. *Preprint*, arXiv:2505.00949.

Xingyu Chen, Jiahao Xu, Tian Liang, Zhiwei He, Jianhui Pang, Dian Yu, Linfeng Song, Qiuzhi Liu, Mengfei Zhou, Zhuosheng Zhang, and 1 others. 2024. Do not think that much for 2+ 3=? on the overthinking of o1-like llms. *arXiv preprint arXiv:2412.21187*.

Zhoujun Cheng, Jungo Kasai, and Tao Yu. 2023. Batch prompting: Efficient inference with large language model apis. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 792–810.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021a. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021b. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Ganqu Cui, Lifan Yuan, Zefan Wang, Hanbin Wang, Wendi Li, Bingxiang He, Yuchen Fan, Tianyu Yu, Qixin Xu, Weize Chen, and 1 others. 2025. Process reinforcement through implicit rewards. *arXiv preprint arXiv:2502.01456*.

Hugging Face. 2025. Open r1: A fully open reproduction of deepseek-r1.

Bofei Gao, Feifan Song, Zhe Yang, Zefan Cai, Yibo Miao, Qingxiu Dong, Lei Li, Chenghao Ma, Liang Chen, Runxin Xu, and 1 others. 2024. Omni-math: A universal olympiad level mathematic benchmark for large language models. *arXiv preprint arXiv:2410.07985*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021a. Measuring mathematical problem solving with the math dataset. *Preprint*, arXiv:2103.03874.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021b. Measuring mathematical problem solving with the math dataset. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, volume 1.

Andreas Hochlehnert, Hardik Bhatnagar, Vishaal Udandarao, Samuel Albanie, Ameya Prabhu, and Matthias Bethge. 2025. A sober look at progress in language model reasoning: Pitfalls and paths to reproducibility. *arXiv preprint arXiv:2504.07086*.

Jingcheng Hu, Yinmin Zhang, Qi Han, Daxin Jiang, Xiangyu Zhang, and Heung-Yeung Shum. 2025. Open-reasoner-zero: An open source approach to scaling up reinforcement learning on the base model. *arXiv preprint arXiv:2503.24290*.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2024. Live-codebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*.

Carlos E Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R Narasimhan. 2024. Swe-bench: Can language models resolve real-world github issues? In *The Twelfth International Conference on Learning Representations*.

Yu Li, Qizhi Pei, Mengyuan Sun, Honglin Lin, Chenlin Ming, Xin Gao, Jiang Wu, Conghui He, and Lijun Wu. 2025. Cipherbank: Exploring the boundary of llm reasoning capabilities through cryptography challenges. *arXiv preprint arXiv:2504.19093*.

Jianzhe Lin, Maurice Diesendruck, Liang Du, and Robin Abraham. 2023. Batchprompt: Accomplish more with less. In *The Twelfth International Conference on Learning Representations*.

Yen-Ting Lin. 2025. Aime 2025 dataset. Accessed: 2025-03-29.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12.

Michael Luo, Sijun Tan, Justin Wong, Xiaoxiang Shi, William Y. Tang, Manan Roongta, Colin Cai, Jeffrey Luo, Li Erran Li, Raluca Ada Popa, and Ion Stoica. 2025. Deepscaler: Surpassing o1-preview with a 1.5b model by scaling rl. Notion Blog.

Zhiyu Mei, Wei Fu, Kaiwei Li, Guangju Wang, Huanchen Zhang, and Yi Wu. 2025. Real: Efficient rlhf training of large language models with parameter reallocation. In *Proceedings of the Eighth Conference on Machine Learning and Systems, MLSys 2025, Santa Clara, CA, USA, May 12-15, 2025*. mlsys.org.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. 2025. s1: Simple test-time scaling. *Preprint*, arXiv:2501.19393.

OpenAI. 2025a. gpt-oss-120b & gpt-oss-20b model card. *Preprint*, arXiv:2508.10925.

OpenAI. 2025b. Openai o3 and o4-mini system card.

Qizhi Pei, Lijun Wu, Zhuoshi Pan, Yu Li, Honglin Lin, Chenlin Ming, Xin Gao, Conghui He, and Rui Yan. 2025. Mathfusion: Enhancing mathematic problem-solving of llm through instruction fusion. *arXiv preprint arXiv:2503.16212*.

Shanghaoran Quan, Jiaxi Yang, Bowen Yu, Bo Zheng, Dayiheng Liu, An Yang, Xuancheng Ren, Bofei Gao, Yibo Miao, Yunlong Feng, and 1 others. 2025. Codeelo: Benchmarking competition-level code generation of llms with human-comparable elo ratings. *arXiv preprint arXiv:2501.01257*.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2024. Gpqa: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

Tushar Semwal, Promod Yenigalla, Gaurav Mathur, and Shivashankar B Nair. 2018. A practitioners' guide to transfer learning for text classification using convolutional neural networks. In *Proceedings of the 2018 SIAM international conference on data mining*, pages 513–521. SIAM.

Darsh J Shah, Peter Rushton, Somanshu Singla, Mohit Parmar, Kurt Smith, Yash Vanjani, Ashish Vaswani, Adarsh Chaluvaraju, Andrew Hojel, Andrew Ma, and 1 others. 2025. Rethinking reflection in pre-training. *arXiv preprint arXiv:2504.04022*.

Connor Shorten, Charles Pierse, Thomas Benjamin Smith, Erika Cardenas, Akanksha Sharma, John Trengrove, and Bob van Luijt. 2024. Structuredrag: Json response formatting with large language models. *arXiv preprint arXiv:2408.11061*.

Guijin Son, SangWon Baek, Sangdae Nam, Ilgyun Jeong, and Seungone Kim. 2024. Multi-task inference: Can large language models follow multiple instructions at once? In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5606–5627.

Yang Sui, Yu-Neng Chuang, Guanchu Wang, Jiamu Zhang, Tianyi Zhang, Jiayi Yuan, Hongyi Liu, Andrew Wen, Shaochen Zhong, Hanjie Chen, and 1 others. 2025. Stop overthinking: A survey on efficient reasoning for large language models. *arXiv preprint arXiv:2503.16419*.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc Le, Ed Chi, Denny Zhou, and 1 others. 2023. Challenging big-bench tasks and whether chain-of-thought can solve them. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13003–13051.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. 2019. Commonsenseqa: A question answering challenge targeting commonsense knowledge. In *Proceedings of the 2019 Conference of the North*, page 4149. Association for Computational Linguistics.

Zhi Rui Tam, Cheng-Kuang Wu, Yi-Lin Tsai, Chieh-Yen Lin, Hung-yi Lee, and Yun-Nung Chen. 2024. Let me speak freely? a study on the impact of format restrictions on performance of large language models. *arXiv preprint arXiv:2408.02442*.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, and 1 others. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, and 1 others. 2025a. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, and 1 others. 2025b. Kimi k1. 5: Scaling reinforcement learning with llms. *arXiv preprint arXiv:2501.12599*.

Open Thoughts Team. 2025a. Open Thoughts.

Qwen Team. 2025b. Qwq-32b: Embracing the power of reinforcement learning.

Yue Wang, Qiuzhi Liu, Jiahao Xu, Tian Liang, Xingyu Chen, Zhiwei He, Linfeng Song, Dian Yu, Juntao Li, Zhuosheng Zhang, and 1 others. 2025. Thoughts are all over the place: On the underthinking of o1-like llms. *arXiv preprint arXiv:2501.18585*.

Zhengxiang Wang, Jordan Kodner, and Owen Rambow. 2024. Evaluating llms with multiple problems at once: A new paradigm for probing llm capabilities. *arXiv e-prints*, pages arXiv–2406.

Liang Wen, Yunke Cai, Fenrui Xiao, Xin He, Qi An, Zhenyu Duan, Yimin Du, Junchen Liu, Lifu Tang, Xiaowei Lv, Haosheng Zou, Yongchao Deng, Shousheng Jia, and Xiangzheng Zhang. 2025. Light-r1: Curriculum sft, dpo and rl for long cot from scratch and beyond. *arXiv preprint arXiv:2503.10460*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025a. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, and 1 others. 2024a. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024b. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *Preprint*, arXiv:2409.12122.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, and 1 others. 2024c. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*.

Zhiyu Yang, Shuo Wang, Yukun Yan, and Yang Deng. 2025b. Why stop at one error? benchmarking llms as data science code debuggers for multi-hop and multi-bug errors. *arXiv preprint arXiv:2503.22388*.

Yixin Ye, Yang Xiao, Tiantian Mi, and Pengfei Liu. 2025. Aime-preview: A rigorous and immediate evaluation framework for advanced mathematical reasoning. https://github.com/GAIR-NLP/AIME-Preview. GitHub repository.

Yijiong Yu, Huiqiang Jiang, Xufang Luo, Qianhui Wu, Chin-Yew Lin, Dongsheng Li, Yuqing Yang, Yongfeng Huang, and Lili Qiu. 2024. Mitigate position bias in large language models via scaling a single dimension. In *First Workshop on Long-Context Foundation Models@ ICML 2024*.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. 2025. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*.

Weihao Zeng, Yuzhen Huang, Qian Liu, Wei Liu, Keqing He, Zejun Ma, and Junxian He. 2025. Simplerl-zoo: Investigating and taming zero reinforcement learning for open base models in the wild. *Preprint*, arXiv:2503.18892.

Yu Zhao, Huifeng Yin, Bo Zeng, Hao Wang, Tianqi Shi, Chenyang Lyu, Longyue Wang, Weihua Luo, and Kaifu Zhang. 2024. Marco-o1: Towards open reasoning models for open-ended solutions. *Preprint*, arXiv:2411.14405.

Xiliang Zhu, Shi Zong, and David Rossouw. 2025. How accurate are llms at multi-question answering on conversational transcripts? *arXiv preprint arXiv:2509.21732*.

A Evaluation Result on Other Tasks

To further demonstrate broader applicability, we conduct additional experiments on (1) AI2 Reasoning Challenge – Challenge (ARC-C) (Clark et al., 2018), including questions that require reasoning and **commonsense knowledge** to answer. (2) Big Bench Hard (BBH) (Suzgun et al., 2023), which evaluates logic reasoning ability. Due to the computation resource constraints, we select the "logical_deduction_five_objects" subset to represent BBH, as it specifically focuses on **logical reasoning**. The results, presented in Tab. 4, strongly corroborate our findings in the main context:

(1) **Substantial performance degradation**: All models, exhibit perfornhance degradation under the multi-problem stress of REST. While some top-tier models like DeepSeek-R1 largely retain their single-question accuracy, smaller models such as DS-R1-Distill-Qwen-7B suffer severe performance drops, especcially on BBH, where its accuracy declined from 88.40% to 57.40%.

Table 4: Evaluation results on *ARC-C* and *BBH*. The "Stress" column reports the average performance across four distinct stress levels, as described in Sec. 3.1. Models perform best under "Stress" are highlighted in gray.

Bench / Model	ARC-C Single	ARC-C Stress	BBH Single	BBH Stress
1.5B LRMs				
DeepSeek-R1-Distill-Qwen-1.5B	62.37	50.70	59.60	18.58
DeepScaleR-1.5B	66.44	48.39	74.80	26.94
L1-Qwen-1.5B-Max	63.39	53.59	73.60	40.75
Qwen2.5-1.5B-Inst	78.64	68.64	32.80	3.74
Qwen3-1.7B	**87.46**	**79.20**	**86.00**	**62.64**
7 ∼ 8B LRMs				
DeepSeek-R1-Distill-Qwen-7B	83.73	77.83	88.40	57.40
DeepSeek-R1-Distill-LLaMA-8B	86.78	75.04	94.40	60.32
Efficient-R1-7B ($\alpha = 0.2$)	83.39	77.24	89.20	57.24
Nemotron-Nano-8B	78.64	55.79	50.80	43.85
AReaL-boba-RL-7B	88.14	72.57	92.40	49.49
Light-R1-7B-DS	81.69	76.34	81.60	51.07
OpenR1-Qwen-7B	79.66	69.90	85.60	54.25
OpenThinker2-7B	91.53	87.85	95.20	82.55
Qwen2.5-7B-Inst	91.19	88.93	60.40	45.65
Qwen3-8B	**94.58**	**91.25**	**98.00**	**89.41**
32B LRMs				
DeepSeek-R1-Distill-Qwen-32B	94.58	94.66	97.20	96.11
Qwen-QwQ-32B	**94.92**	93.50	96.80	**96.99**
Qwen2.5-32B-Inst	94.58	**94.92**	74.80	65.66
Qwen3-32B	94.58	94.13	**99.20**	88.34
Proprietary LRMs				
DeepSeek-R1	**97.29**	94.79	**99.60**	**97.36**
O3-mini	95.93	**95.14**	95.20	89.59
O4-mini	95.93	94.53	97.20	94.11
Gemini-2.5-Flash-Thinking	96.27	94.44	97.60	86.72

Table 5: Evaluation results on GPQA-Diamond and LiveCodeBench (v5) for additional models. The "Stress" column reports the average performance across four distinct stress levels, as described in Sec. 3.1. Models perform best under "Stress" are highlighted in gray.

Bench / Model	GQPA-Diamond Single	GQPA-Diamond Stress	LiveCodeBench (v5) Single	LiveCodeBench (v5) Stress
1.5B LRMs				
DeepSeek-R1-Distill-Qwen-1.5B	**37.37**	22.11	15.05	0.48
DeepScaleR-1.5B	31.82	27.90	21.15	1.83
L1-Qwen-1.5B-Exact	33.84	31.01	18.28	2.70
L1-Qwen-1.5B-Max	36.87	32.03	19.35	2.45
Qwen2.5-1.5B-Inst	26.26	21.52	1.79	0.37
Qwen3-1.7B	**37.37**	**32.21**	30.82	**6.65**
7 ∼ 8B LRMs				
DeepSeek-R1-Distill-Qwen-7B	51.01	31.67	37.63	2.89
DeepSeek-R1-Distill-LLaMA-8B	50.00	33.99	39.43	11.25
Efficient-R1-7B ($\alpha = 0.2$)	47.97	34.37	38.71	2.50
Nemotron-Nano-8B	51.01	34.06	50.90	8.56
AReaL-boba-RL-7B	48.98	29.13	37.99	4.73
Light-R1-7B-DS	41.91	30.32	39.07	2.85
OpenR1-Qwen-7B	38.38	36.04	4.66	1.27
OpenThinker2-7B	49.49	40.60	39.43	14.51
SimpleRL-Zoo-Qwen-7B	33.84	35.49	5.73	0.16
Open-Reasoner-Zero-7B	37.37	34.25	16.13	0.64
Marco-O1-7B	30.81	28.32	9.32	7.24
Qwen2.5-7B-Inst	35.86	35.15	13.98	10.19
Qwen3-8B	**61.11**	**58.60**	56.99	**31.13**
32B LRMs				
DeepSeek-R1-Distill-Qwen-32B	60.10	53.73	55.56	26.71
Qwen-QwQ-32B	63.64	**60.03**	62.37	32.16
AReaL-boba-SFT-32B	63.13	50.59	60.93	31.74
Light-R1-32B-DS	**65.66**	50.11	60.93	28.22
S1.1-32B	61.62	54.54	25.45	24.46
OpenThinker2-32B	62.12	57.79	56.27	**37.53**
SimpleRL-Zoo-Qwen-32B	46.46	46.21	26.52	23.95
Open-Reasoner-Zero-32B	60.10	49.57	35.13	13.01
OpenThinker2-32B	62.12	57.79	56.27	37.53
Qwen2.5-32B-Inst	42.93	40.04	26.88	24.00
Qwen3-32B	63.33	48.13	**62.72**	30.98
MoE LRMs				
GPT-OSS-20B	53.54	59.52	43.37	29.83
GPT-OSS-120B	60.10	**65.93**	63.08	**49.16**
Qwen3-30B-A3B	64.65	50.74	61.65	38.48
DeepSeek-R1	**70.20**	64.63	**63.44**	40.83
Proprietary LRMs				
O3-mini	71.21	67.39	60.21	48.36
O4-mini	76.26	**73.11**	**70.61**	**63.07**
Gemini-2.5-Flash-Thinking	**78.79**	68.00	61.65	48.34

(2) **Enhanced discriminative power**: REST significantly amplifies performance differences between models, thereby enhancing the discrimrinative power of existing benchmarks. For example, on BBH, the accuracy of AReal-boba-RL-7B plummets ffrom 92.40% to just 49.49% under REST, a decline of 42.91%. In contrast, the larger model DS-R1-Distill-Qwen-32B retains more of its single-question performance, with its accuracy under REST only dropping from 97.20% to 96.11%, a reduction of merely 1.09%

(3) **The benifit of "Long2Short" training**: Models trained with the "Long2Short" technique consistently demonstrat more robust performarhce under stress compared to their standard-trained counterparts, confirming our initial findings. For instaInce, the accuracy of L1-Qwen-1.5B-Max on BBH is 40.75% under REST, which is much higher than the 18.58% and 26.94% achieved by R1-1.5B and DeepScaleR-1.5B, respectively.

B Evaluation Result on Additional Models

Table 6 and Table 5 present the evaluation results on additional models. These results again validate our core findings: REST induces significant performance degradation across diverse model size and architectures. And the performance gap between models is substantially amplified under multi-question stress, with smaller models exhibiting notably sharper declines.

Table 6: Evaluation results on various math benchmarks for additional models. The "Stress" column reports the average performance across four stress levels, as described in Sec. 3.1. Models that perform best under "Stress" are highlighted in gray.

Bench / Model	GSM8K Single	GSM8K Stress	MATH500 Single	MATH500 Stress	AMC23 Single	AMC23 Stress	AIME24 Single	AIME24 Stress	AIME25 Single	AIME25 Stress	AVG. Single	AVG. Stress
1.5B LRMs												
DeepSeek-R1-Distill-Qwen-1.5B (Guo et al., 2025)	84.62	70.21	83.40	42.47	62.50	13.98	29.17	4.97	25.00	5.91	56.94	27.51
DeepScaleR-1.5B (Luo et al., 2025)	84.84	66.58	87.60	59.77	76.25	32.05	38.75	12.82	31.25	14.23	63.74	37.09
L1-Qwen-1.5B-Exact (Aggarwal and Welleck, 2025)	84.87	79.01	84.00	72.07	71.25	47.37	21.25	12.62	18.33	12.96	55.94	44.81
L1-Qwen-1.5B-Max (Aggarwal and Welleck, 2025)	84.17	78.29	83.40	73.23	77.50	**48.37**	20.00	15.13	22.92	14.95	57.60	**45.99**
Qwen2.5-Math-1.5B-Inst (Yang et al., 2024c)	85.37	67.49	73.00	53.94	57.50	22.22	10.83	6.17	10.83	2.83	47.51	30.53
Qwen3-1.7B (Yang et al., 2025a)	**90.22**	**85.26**	**90.20**	62.13	**85.00**	40.43	**46.67**	**23.61**	**35.83**	**17.13**	**69.58**	45.71
7 ∼ 8B LRMs												
DeepSeek-R1-Distill-Qwen-7B (Guo et al., 2025)	89.49	89.06	93.00	66.75	87.50	36.06	54.17	16.53	35.42	11.37	71.92	43.95
DeepSeek-R1-Distill-LLaMA-8B (Guo et al., 2025)	90.45	85.18	89.80	81.34	87.50	70.75	50.42	31.23	28.33	22.66	69.30	58.23
Efficient-R1-7B ($\alpha = 0.1$) (Arora and Zanette, 2025)	88.63	84.76	90.00	74.99	87.50	44.25	54.58	21.45	35.42	15.75	71.23	48.24
Efficient-R1-7B ($\alpha = 0.2$) (Arora and Zanette, 2025)	87.95	80.38	88.20	76.41	85.00	48.05	50.42	22.12	33.75	17.25	69.06	48.84
Nemotron-Nano-8B (Bercovich et al., 2025)	91.36	70.52	94.40	86.04	90.00	76.24	63.33	43.55	50.00	32.28	77.82	**61.71**
AReaL-boba-RL-7B (Mei et al., 2025)	91.66	77.80	95.00	60.77	91.25	32.94	61.25	21.43	45.83	12.33	77.00	41.05
Light-R1-7B-DS (Wen et al., 2025)	88.05	82.69	93.20	61.73	90.00	34.91	55.83	16.63	45.83	12.96	74.58	41.78
OpenR1-Qwen-7B (Face, 2025)	**95.60**	90.22	92.20	81.64	83.75	54.11	47.50	26.77	32.92	21.19	70.39	54.79
OpenThinker2-7B (Team, 2025a)	94.39	91.99	93.80	83.30	85.00	63.23	54.58	34.50	41.67	23.66	73.89	59.33
SimpleRL-Zoo-Qwen-7B (Zeng et al., 2025)	90.52	84.01	77.80	62.41	68.50	16.16	26.67	7.55	10.00	6.47	54.70	35.32
Open-Reasoner-Zero-7B (Hu et al., 2025)	92.87	65.14	83.00	32.51	60.00	31.23	17.92	6.13	16.25	3.89	54.01	27.78
Marco-O1-7B (Zhao et al., 2024)	89.08	79.56	72.40	48.19	47.50	17.23	10.00	4.35	10.83	3.64	45.96	30.59
MathFusion-Qwen-7B (Pei et al., 2025)	89.46	83.78	74.00	68.15	52.50	36.24	9.58	7.89	5.83	2.35	46.27	39.68
Eurus-2-7B-PRIME (Cui et al., 2025)	92.72	88.01	81.40	64.69	62.50	38.58	20.83	10.84	14.58	4.49	54.41	41.32
Qwen2.5-Math-7B-Inst (Yang et al., 2024b)	**95.53**	78.53	83.60	56.59	60.00	28.46	14.17	6.40	11.67	5.33	52.99	35.06
Qwen2.5-7B-Inst (Yang et al., 2024a)	92.27	85.12	77.60	65.78	42.50	34.46	10.00	7.02	3.75	3.32	45.22	39.14
Qwen3-8B (Yang et al., 2025a)	95.30	**93.90**	95.40	80.28	92.50	53.59	**74.58**	**44.28**	**63.33**	32.06	**84.22**	60.82
32B LRMs												
DeepSeek-R1-Distill-Qwen-32B (Guo et al., 2025)	95.54	95.50	94.60	88.97	94.75	86.24	72.92	52.51	51.67	33.83	81.90	71.41
Qwen-QwQ-32B (Team, 2025b)	95.83	**95.78**	96.20	92.49	95.00	82.89	78.75	54.79	69.58	41.53	87.07	**73.49**
AReaL-boba-SFT-32B (Mei et al., 2025)	95.01	94.75	95.00	88.92	97.50	78.96	77.50	45.79	60.00	33.55	85.00	68.39
Light-R1-32B-DS (Wen et al., 2025)	95.83	94.79	95.60	83.66	96.25	68.80	77.50	41.26	60.00	33.80	85.04	64.46
S1.1-32B (Muennighoff et al., 2025)	89.84	61.10	90.40	53.85	90.00	32.26	55.83	24.42	45.42	19.13	74.30	38.15
OpenThinker2-32B (Team, 2025a)	**96.44**	95.17	96.20	90.10	95.00	81.00	68.33	53.01	52.50	38.20	81.69	71.49
SimpleRL-Zoo-Qwen-32B (Zeng et al., 2025)	96.06	93.49	83.20	78.90	67.50	57.02	27.20	16.80	16.67	8.87	58.13	51.01
Open-Reasoner-Zero-32B (Hu et al., 2025)	95.83	91.80	92.00	82.90	83.75	70.04	46.67	31.65	36.67	23.63	70.98	60.00
Qwen2.5-32B-Inst (Yang et al., 2024a)	95.53	93.77	82.20	73.39	60.00	49.72	20.00	9.61	16.67	6.73	54.88	46.64
Qwen3-32B (Yang et al., 2025a)	95.91	93.81	**96.60**	83.64	93.75	80.62	**85.00**	**56.67**	**71.67**	**44.53**	**88.59**	71.85
MoE LRMs												
GPT-OSS-20B (OpenAI, 2025a)	88.02	49.31	88.40	46.96	97.50	56.56	66.25	36.20	63.33	29.87	80.70	43.78
GPT-OSS-120B (OpenAI, 2025a)	84.91	47.65	89.60	60.06	93.75	71.93	67.08	**60.28**	68.33	**52.39**	80.73	58.46
Qwen3-30B-A3B (Yang et al., 2025a)	96.13	94.91	96.40	80.36	**98.75**	72.34	79.58	48.38	**68.75**	28.67	**87.92**	64.93
DeepSeek-R1 (Guo et al., 2025)	**96.20**	**96.16**	97.00	92.09	93.75	**81.80**	81.66	52.49	**68.75**	37.17	87.47	**71.94**
Proprietary LRMs												
O3-mini (OpenAI, 2025b)	95.83	93.85	95.00	86.62	90.00	59.17	79.16	34.07	71.66	20.63	86.25	55.51
O4-mini (OpenAI, 2025b)	93.71	93.07	90.00	82.40	96.25	**82.79**	73.33	49.69	**80.00**	**41.42**	86.66	69.87
Gemini-2.5-Flash-Thinking (Team et al., 2023)	89.23	91.28	**97.20**	69.92	**97.50**	47.63	76.67	26.60	71.67	16.54	86.45	50.39

C Additional Analysis on Per Question Token Allocation

We analyze how models distribute reasoning tokens across question positions under multi-question stress. As shown in Fig. 8, strong models under REST like DeepSeek-R1, tend to *use fewer reasoning tokens on the first question* when the stress level exceeds 1. In contrast, models with lower REST performance, such as Light-R1-7B-DS, often *overthink the first question*, consuming a substantial portion of their reasoning tokens and leaving insufficient space for subsequent questions. This findings on additional models again reinforce our conclusion in the main context: "**adaptive reasoning effort allocation**"—the ability to dynamically distribute reasoning resources across questions—is critical for building strong, multi-question capable LRMs.

| (a) Light-R1-7B-DS (16.63% Acc.) | (b) Nemotron-nano-7B (43.55% Acc.) | (c) DeepSeek-R1 (52.49% Acc.) |

Figure 8: The reasoning token count for questions at different positions on AIME24 for additional models. The number in parentheses indicates the accuracy on AIME24 under REST.

D Detailed Evaluation Result

We present the detailed accuracy statistics for each stress level of various LRMs in Table 12, Table 13 and Table 14. The stress degree $\{I, II, III, IV, V\}$ corresponds to different stress levels in each dataset. For GSM8K, ARC-C and BBH: $\{1, 3, 6, 9, 12\}$; for MATH500 and AMC23: $\{1, 3, 5, 7, 9\}$; for AIME24, AIME25, GPQA and LiveCodeBench: $\{1, 2, 3, 4, 5\}$. We use the official test splits for all benchmarks except ARC-C, for which we follow OpenCompass's standard practice and use the development split (see opencompass[†]).

E Comparison between Rule-based and LLM-based Answer Extraction

Extraction Method	GSM8K	MATH500	AMC23	AIME24	AIME25
DS-R1-Distill-Qwen-7B					
Rule-Based	89.06	66.75	36.06	16.53	11.37
LLM-Based	90.00	70.59	41.05	18.32	14.16
DS-R1-Distill-Qwen-32B					
Rule-Based	95.50	88.97	86.24	52.51	33.83
LLM-Based	95.83	92.18	87.48	53.63	34.39

Table 7: Comparison of rule-based answer extraction and LLM-based answer extraction.

In this section, we compare the performance of several representative LRMs under REST when using rule-based versus LLM-based answer extraction. For rule-based extraction, we search the specific pattern sequentially using code modified from Qwen-Math evaluation tool [‡]. For the LLM-based approach, we employ *gemma-3-27b-it* (Team et al., 2025a) with prompt shown in Figure 12. The results in Table 7 indicate that LLM-based answer extraction can lead to a modest performance improvement. However, this approach significantly increases evaluation costs and may introduce additional instability, making it less practical for large-scale assessments. Therefore, we adopt rule-based

---

[†] https://github.com/open-compass/opencompass
[‡] https://github.com/QwenLM/Qwen2.5-Math

answer extraction as the default approach in our experiments.

F The Impact of the maximum output length

Extending the maximum output length can not provide substantial improvement. As our error analysis identified output truncation as a significant error type, it is questionable whether extending the maximum output length could improve performance under stress tests. To evaluate this, we extended the maximum output length from 32K to 128K tokens for top-tier 7B∼32B reasoning models. As shown in Tab. 8, this extension has a negligible impact on stress test accuracy.

Max Output Token	GSM8K	MATH500	AMC23	AIME24	AIME25
DS-R1-Distill-Qwen-7B					
32K	89.06	66.75	36.06	16.53	11.37
128K	89.37	65.83	36.66	16.17	11.73
DS-R1-Distill-Qwen-32B					
32K	95.50	88.97	86.24	52.51	33.83
128K	95.62	89.71	86.77	52.75	33.87

Table 8: The effect of extending the maximum output length. Extending the maximum output length has almost negligible impact on both 7B and 32B models.

G Prompt

We present the prompt for mathematical tasks, *GPQA Diamond* and *LiveCodeBench* in Figure 9, Figure 10 and Figure 11, respectively.

> **Prompt 1:** *Prompt for Math Tasks*
>
> {Questions}. Answer the above questions one by one.
> Remember to put your final answer within \boxed{}.

Figure 9: Evaluation prompt for math tasks.

Figure 10: Evaluation prompt for GPQA Diamond.

Figure 11: Evaluation prompt for code generation tasks.

H Extended Error Analysis on Other Models and Benchmarks

To broaden the scope of our error analysis, we extend our evaluation to: (1) **Additional models**: the smaller DeepSeek-R1-Distill-Qwen-1.5B and the non-reasoning model Qwen2.5-7B-Instruct; and (2) **Simpler benchmarks**: GSM8K and MATH500. Given the substantial volume of data for error analysis, we employ Qwen3-32B for error cause annotation. We randomly sample 10% of the annotated data for manual human review, achieving 98.25% agreement with human labels, which verifies the reliability of this LLM-based error analysis.

As summarized in Tab. 9, this expansion reveals notable shifts in error distributions. For instance, Qwen2.5-7B-Instruct exhibits substantially fewer length-related errors—such as *Question Omission*, *Output Truncation*, and *Endless Repetition*—but shows a marked increase in *Reasoning Errors*. We attribute this to its non-reasoning nature: by using shorter Chain-of-Thought (CoT), it avoids length-related errors but often fails to perform sufficient deliberation.

Furthermore, on simpler benchmarks like GSM8K and MATH500, reasoning misbehaviors such as *Question Omission*, *Summary Error*, and *Endless Repetition* are significantly reduced. This indicates that these degradation patterns are triggered by the increased reasoning load of more challenging questions (e.g., AIME24). Nevertheless, DeepSeek-distilled models still exhibit non-

negligible rates of such errors, and their prevalence remains substantially higher than in Qwen2.5-7B-Instruct. This contrast underscores a key trade-off: while extended Chain-of-Thought (CoT) reasoning enhances single problem solving capability, it simultaneously compromises robustness under multi-question stress.

I Specific Error Type Reduction via "Long2Short" Training

We conduct experiment to probe the specific failure types mitigated by "Long2Short" training. The results in Tab. 10 confirm that "Long2Short" training reduces actual reasoning failures, not just length-related artifacts. Specifically, we observe a notable decrease in "Question Omission" (QO) and "Reasoning Error" (RE) for models after "Long2Short" training. For example, on MATH500, the Long2Short-trained L1-Qwen-1.5B-Max shows a lower percentage of "Question Omission" and "Reasoning Error" (3.85% and 20.60%, respectively) compared to DS-R1-Distill-Qwen-1.5B (15.10% and 33.85%). A similar pattern is also observed in the 7B models (Efficient-R1-7B ($\alpha = 0.2$) vs. DS-R1-Distill-Qwen-7B). These observation indicates that "Long2Short" training not only prevents output truncation by shortening thinking process but also effectively mitigates degradation patterns in reasoning, thus improving model robustness under multi-question stress.

J Error Type Illustrations

In this section, we provide a detailed case study of each error type under stress tests in figs. 13 to 17. Our findings indicate that *Output Truncation* is not the only reason for the performance degradation under REST, revealing some unexpected misbehaviors like *Question Omission* and *Summary Error* that remain hidden in standard evaluation settings.

K Can Few-Shot Prompting Alleviate Performance Degradation?

In this section, we investigate whether improved prompt design can mitigate performance degradation in multi-question evaluation. Inspired by in-context learning, we enhance the instruction prompt with a few-shot example of the target format: we randomly sample three problems from the MATH training set, generate answers (including reasoning content) using DeepSeek-R1, and concatenate them into a single demonstration of the

Figure 12: Prompt for extracting answers from the response.

| Error Type
Model	Question Omission	Summary Error	Endless Repetition	Output Truncation	Reasoning Error	Format Violation	Correct Answer
GSM8K							
DS-R1-Distill-Qwen-1.5B	4.8	3.1	0.7	0.5	20.6	0.1	70.2
DS-R1-Distill-Qwen-7B	2.2	2.0	0.0	0.2	6.5	0.1	89.0
Qwen2.5-7B-Instruct	0.4	0.8	0.3	0.0	13.4	0.0	85.1
MATH500							
DS-R1-Distill-Qwen-1.5B	15.1	5.6	1.3	1.4	33.9	0.2	42.5
DS-R1-Distill-Qwen-7B	10.4	4.7	0.3	0.7	17.0	0.1	66.8
Qwen2.5-7B-Instruct	4.5	0.6	2.7	1.0	25.2	0.2	65.8
AIME24							
DS-R1-Distill-Qwen-1.5B	38.6	5.9	0.9	3.6	45.8	0.2	5.0
DS-R1-Distill-Qwen-7B	29.6	3.0	8.4	8.0	34.5	0.0	16.5
Qwen2.5-7B-Instruct	18.5	4.2	5.8	3.3	61.2	0.0	7.0

Table 9: Error analysis for other models on more benchmarks.

| Error Type
Model	Question Omission	Reasoning Error	Summary Error	Endless Repetition	Format Violation	Output Truncation	Correct Answer
1.5B models on MATH500							
DS-R1-Distill-Qwen-1.5B	15.10	33.85	5.65	1.35	0.20	1.38	42.47
L1-Qwen-1.5B-Max	3.85	20.60	2.17	0.05	0.10	0.00	73.23
7B models on MATH500							
DS-R1-Distill-Qwen-7B	10.40	17.00	4.75	0.35	0.05	0.70	66.75
Efficient-R1-7B ($\alpha = 0.2$)	5.40	14.20	3.35	0.14	0.10	0.40	76.41
7B models on AMC23							
DS-R1-Distill-Qwen-7B	30.62	25.62	4.37	0.84	0.62	1.87	36.06
Efficient-R1-7B ($\alpha = 0.2$)	21.87	24.00	2.81	0.77	1.25	1.25	48.05

Table 10: Error type distribution comparison between standard-trained and Long2Short-trained models.

Table 11: Evaluation results with the few-shot prompt. The "Few-Shot" column reports the average performance across four stress levels using the few-shot prompt described in Sec. K.

Bench Model	GSM8K		MATH500		AMC23		AIME24		AIME25		AVG.	
	Zero-Shot	Few-Shot	Zero-Shot	Few-Shot	Zero-Shot	Few-Shot	Zero-Shot	Few-Shot	Zero-Shot	Few-Shot	Zero-Shot	Few-Shot
7B LRMs												
DS-R1-Distill-Qwen-7B	89.06	88.48	66.75	70.77	36.06	35.88	16.53	14.16	11.37	12.29	43.95	44.32
OpenThinker2-7B	91.99	91.79	83.30	85.72	63.23	71.32	34.50	33.36	23.66	21.81	59.34	60.80
OpenR1-Qwen-7B	90.22	90.03	81.64	81.80	54.11	64.56	26.77	24.13	21.19	19.67	54.79	56.04
Light-R1-7B-DS	82.69	80.60	61.73	66.29	34.91	35.53	16.63	14.97	12.96	11.60	41.78	41.80
Qwen2.5-Math-7B-Inst	78.53	82.65	56.59	61.46	28.46	28.51	6.40	6.19	5.33	4.72	35.06	36.71

form "Q1 Q2 Q3 A1 A2 A3".

As shown in Tab. 11, this few-shot strategy yields modest gains on medium-difficulty benchmarks (i.e., MATH500 and AMC23), but a substantial performance gap relative to the single-question setting persists. This result strongly suggests that the degradation under REST is not primarily due to instruction following or prompt sensitivity, but rather reflects an intrinsic limitation in the model's reasoning capacity under heightened cognitive load.

L Use of AI Assistance

We used large language models to assist with language polishing and editing of the manuscript. All technical content, analysis, and conclusions were developed and verified by the authors.

Example L.1: *Example of Output Truncation*

Query:

Q1: Let $O(0,0)$, $A(\frac{1}{2}, 0)$, and $B(0, \frac{\sqrt{3}}{2})$ be points in the coordinate plane. Let $\mathcal{F}$ be the family of segments $\overline{PQ}$ of unit length lying in the first quadrant with P on the x-axis and Q on the y-axis. There is a unique point C on $\overline{AB}$, distinct from A and B, that does not belong to any segment from $\mathcal{F}$ other than $\overline{AB}$. Then $OC^2 = \frac{p}{q}$, where p and q are relatively prime positive integers. Find $p + q$.

Q2: Find the number of triples of nonnegative integers (a, b, c) satisfying $a + b + c = 300$ and $a^2b + a^2c + b^2a + b^2c + c^2a + c^2b = 6,000,000$.

Answer the above questions one by one. Remember to put your final answer within \boxed{}.

Response:

Okay, so I have these two problems to solve. Let me start with the first one.

Problem Q1:

We have points O(0,0), A(1/2, 0), and B(0, sqrt(3)/2). The family F consists of segments PQ of unit length in the first quadrant, with P on the x-axis and Q on the y-axis. We need to find a unique point C on AB (other than A and B) that doesn't lie on any other segment from F except AB. Then compute OC² and express it as a reduced fraction p/q, and find p+q. Alright, let's break this down. First, let's visualize the points. O is the origin, A is (1/2, 0), which is halfway between (0,0) and (1,0). B is (0, sqrt(3)/2), which is halfway between (0,0) and (0,1) in some sense, but sqrt(3)/2 is approximately 0.866. So, AB is a line segment connecting (1/2, 0) to (0, sqrt(3)/2). Let me compute the equation of line AB.

... (Reasoning content for Q1) ...

So, to find such a point C, we need to find a point on AB that is not on any other PQ, which are all lines from $(p, 0)$ to $(0, q)$ with $p + q = 1$.

Problem Q2:

Find the number of triples of nonnegative integers (a, b, c) satisfying $a + b + c = 300$ and $ab + ac + ba + bc + ca + cb = 6,000,000$.

Okay, so we have two equations:

... (Reasoning content for Q2) ...

Thus, each non-symmetric set is unique, so 6 such sets, each contributing 6 ordered triples 36. Plus the symmetric solution 1. Total=37. But, in reality, the equation may have more solutions. Wait, let me think. Wait, the equation is:$(a(b + c) + b(c + a) + c(a + b))/2006 = abc$. So, with (Truncated)

Figure 13: Example of **Output Truncation** error on DS-R1-Distill-Qwen-7B.

Example L.2: *Example of Endless Repetition*

Query:
Q1: Let $ABCD$ be a tetrahedron such that $AB = CD = \sqrt{41}$, $AC = BD = \sqrt{80}$, and $BC = AD = \sqrt{89}$. There exists a point I inside the tetrahedron such that the distances from I to each of the faces of the tetrahedron are all equal. This distance can be written in the form $\frac{m\sqrt{n}}{p}$, where m, n, and p are positive integers, m and p are relatively prime, and n is not divisible by the square of any prime. Find $m + n + p$.
Q2: Let p be the least prime number for which there exists a positive integer n such that $n^4 + 1$ is divisible by p^2. Find the least positive integer m such that $m^4 + 1$ is divisible by p^2.
Answer the above questions one by one. Remember to put your final answer within \boxed{}.

Response:
Problem Q1: We have a tetrahedron ABCD with some specific edge lengths. The edges AB and CD are both $\sqrt{41}$, AC and BD are both $\sqrt{80}$, and BC and AD are both $\sqrt{89}$. There's a point I inside this tetrahedron such that the distances from I to each face are equal. We need to find this distance, express it in a specific form, and then compute $m + n + p$ where the distance is $m\sqrt{n}/p$. Hmm, okay. So, first, I remember that in a tetrahedron, the point equidistant from all four faces is called the incenter, similar to the incenter of a triangle. The distance from this point to each face is the inradius.
. . . (Reasoning content for Q1) . . .
Wait, 236? Hmm, that seems a bit high, but maybe it's correct. Wait, let me check the formula for the inradius again. Yes, for a tetrahedron, $r = 3V/A$, where A is the total surface area. So, yes, that's correct. Alternatively, another way to compute the inradius is to note that in a disphenoid, the inradius can be computed using the formula $r = (3V)/A_{total}$, which is what I did. So, I think 236 is the answer for Q1.
Problem Q2: We need to find the least prime number p such that there exists a positive integer n where p^2 divides $n^4 + 1$. Once we find that prime p, we need to find the least positive integer m such that $m^4 + 1$ is divisible by p^2. So, first, we need to find the smallest prime p where $p^2 \mid n^4 + 1$ for some n. To do this, I think we can consider primes p where -1 is a quartic residue modulo p^2. Because $n^4 \equiv -1 \mod p^2$, which implies that $n^4 + 1 \equiv 0 \mod p^2$. Therefore, we need to find the smallest prime p such that the equation $x^4 \equiv -1 \mod p^2$ has a solution. Alternatively, since if $x^4 \equiv -1 \mod p^2$, then $x^4 \equiv -1 \mod p$, so first, we can check for primes p where -1 is a quartic residue modulo p.
. . . (Reasoning content for Q2) . . .
But wait, 110 is quite large, maybe I can find a smaller one. Wait, let me try $n = 55$. $55^2 = 3,025$. $3,025 \mod 289$: $289 \cdot 10 = 2,890$. $3,025 - 2,890 = 135$. $135^2 = 18,225$. $18,225 \mod 289$: $289 \cdot 62 = 17,918$. $18,225 - 17,918 = 307$. $307 - 289 = 18$. So, $55^4 \equiv 18 \mod 289$. $18 + 1 = 19 \neq 0$. $n = 55$ doesn't work. Wait, $n = 68$. $68^2 = 4,624$. $4,624 \mod 289$: $289 \cdot 15 = 4,335$. $4,624 - 4,335 = 289$. $289 \equiv 0 \mod 289$. So, $68^2 \equiv 0 \mod 289$. So, $68^4 \equiv 0 \mod 289$. Doesn't work. $n = 69$. $69^2 = 4,761$. $4,761 \mod 289$: $289 \cdot 16 = 4,624$. $4,761 - 4,624 = 137$. $137^2 = 18,769$. $18,769 \mod 289$: $289 \cdot 64 = 18,496$. $18,769 - 18,496 = 273$. $273 - 289 = -16 \equiv 273 \mod 289$. So, $69^4 \equiv 273 \mod 289$. $273 + 1 = 274 \equiv 274 \neq 0$. $n = 70$. $70^2 = 4,900$. $4,900 \mod 289$: $289 \cdot 16 = 4,624$. $4,900 - 4,624 = 276$. $276^2 = 76,176$. $76,176 \mod 289$: $289 \cdot 263 = 76,107$. $76,176 - 76,107 = 69$. So, $70^4 \equiv 69 \mod 289$. $69 + 1 = 70 \equiv 70 \neq 0$. $n = 71$. $71^2 = 5,041$. $5,041 \mod 289$: $289 \cdot 17 = 4,913$. $5,041 - 4,913 = 128$. $128^2 = 16,384$. $16,384 \mod 289$: $289 \cdot 56 = 16,184$. $16,384 - 16,184 = 200$. $200 + 1 = 201 \neq 0$. $n = 72$. $72^2 = 5,184$. $5,184 \mod 289$: $289 \cdot 17 = 4,913$. $5,184 - 4,913 = 271$. $271^2 = 73,441$. $73,441 \mod 289$: $289 \cdot 253 = 73,197$. $73,441 - 73,197 = 244$. $244 - 289 = -45 \equiv 244 \mod 289$. $244 + 1 = 245 \neq 0$. $n = 73$. $73^2 = 5,329$. $5,329 \mod 289$: $289 \cdot 18 = 5,202$. $5,329 - 5,202 = 127$. $127^2 = 16,129$. $16,129 \mod 289$: $289 \cdot 55 = 15,895 \cdot 55 = 15,895 \cdot 55 = 15,895 \cdot 55 = 15,895 \cdot 55 = 15,895 \cdot 55 = 15,895 \cdot 55 = 15$, (Endless Repeating $289 \cdot 55 = 15,895$).

Figure 14: Example of **Endless Repetition** error on DS-R1-Distill-Qwen-7B.

Example L.3: *Example of Question Omission*

Query:

Q1: Let N be the greatest four-digit positive integer with the property that whenever one of its digits is changed to 1, the resulting number is divisible by 7. Let Q and R be the quotient and remainder, respectively, when N is divided by 1000. Find $Q + R$.

Q2: Alice chooses a set A of positive integers. Then Bob lists all finite nonempty sets B of positive integers with the property that the maximum element of B belongs to A. Bob's list has 2024 sets. Find the sum of the elements of A.

Answer the above questions one by one. Remember to put your final answer within \boxed{}.

Response:

Alright, so I have these two math problems to solve. Let me start with Q1. It says:

"Let N be the greatest four-digit positive integer with the property that whenever one of its digits is changed to 1, the resulting number is divisible by 7. Let Q and R be the quotient and remainder, respectively, when N is divided by 1000. Find Q + R."

Okay, so N is a four-digit number, and if you change any one of its digits to 1, the new number is divisible by 7. We need to find N, then divide it by 1000 to get Q and R, and then add them together.

First, let me think about how to approach this. Since changing any digit to 1 results in a number divisible by 7, that gives us several conditions. Let's denote N as a four-digit number: N = ABCD, where A, B, C, D are its digits. Then, changing each digit one by one to 1 should result in a number divisible by 7.

So, changing A to 1: 1BCD should be divisible by 7.

Changing B to 1: A1CD should be divisible by 7.

... (Reasoning content for Q1) ...

After checking various possibilities, we find that the valid number N is 5694.

When $N = 5694$ is divided by 100, the quotient Q is 56 and the remainder R is 94. Therefore, we compute $Q + 10R$:

$$Q + 10R = 56 + 10 \times 94 = 56 + 940 = 996$$

Thus, the final answer is $\boxed{996}$. (Missing answer for Q2)

Figure 15: Example of **Question Omission** error on DS-R1-Distill-Qwen-7B.

Example L.4: *Example of Summary Error*

Query:
Q1: Consider the paths of length 16 that follow the lines from the lower left corner to the upper right corner on an 8×8 grid. Find the number of such paths that change direction exactly four times, like in the examples shown below.

```
[asy] size(7.5cm); usepackage(\"tikz\");
label(\"\\begin{tikzpicture}[scale=.4] \\draw(0,0)grid(8,8);

\\draw[line width=2,red](0,0)--(2,0)--(2,3)--(5,3)--(5,8)--(8,8);

\\end{tikzpicture}\",origin);

label(\"\\begin{tikzpicture}[scale=.4]\\draw(0,0)grid(8,8);

\\draw[line width=2,red](0,0)--(0,3)--(3,3)--(3,5)--(8,5)--(8,8);

\\end{tikzpicture}\",E); [/asy]
```

Q2: Rectangles $ABCD$ and $EFGH$ are drawn such that D, E, C, F are collinear. Also, A, D, H, G all lie on a circle. If $BC = 16$, $AB = 107$, $FG = 17$, and $EF = 184$, what is the length of CE?

```
[asy] import graph; unitsize(0.1cm);  pair A = (0,0);pair B = (70,0);

pair C = (70,16);pair D = (0,16);pair E = (3,16);pair F = (90,16);pair G = (90,33);

pair H = (3,33); dot(A^^B^^C^^D^^E^^F^^G^^H); label(\"$A$\", A, S);

label(\"$B$\", B, S);label(\"$C$\", C, N);label(\"$D$\", D, N);

label(\"$E$\", E, S);label(\"$F$\", F, S);label(\"$G$\", G, N);

label(\"$H$\", H, N); draw(E--D--A--B--C--E--H--G--F--C); [/asy]
```

Answer the above questions one by one. Remember to put your final answer within \boxed{}.

Response:
Okay, so I have these two questions to solve. Let me start with the first one.
Q1 Paths on an 8x8 Grid
Alright, so the problem is about finding the number of paths of length 16 on an 8x8 grid that ...
... (Reasoning content for Q1) ...
Similarly, the second example alternates more, but I think the reasoning still holds. So, yeah, 294 seems correct. Therefore, the answer is 294.
Q2: Rectangles and Circle Problem
Alright, moving on to the second question. It's a geometry problem involving rectangles and a circle.
... (Reasoning content for Q2) ...
Therefore, regardless of the exact value of e, CE is 201. Wait, that's interesting. Therefore, $CE = 201$. So, the exact value is 201. Therefore, the length of CE is 201. </think>
Final Answer To solve the first problem, we need to find the number of ways to arrange the letters of the rectangle ROOT such that the letters D and E are adjacent. 1. The word ROOT has 4 letters with two O's. The distinct letters are R, O, O, T. 2. We treat the pair DE as a single letter, resulting in three units: DE, R, T. 3. These three units can be arranged in 3! = 6 ways. 4. However, DE can also be treated as ED, so we multiply by 2, giving 12 ways. 5. Considering the two O's, the total number of distinct arrangements is 12. Thus, the number of ways is $\boxed{12}$.
(The answer to Q1 in the final answer is inconsistent with the answer given during the thinking process.)
For the second problem, we need to find the length of CE in a rectangle ABCD with specific conditions. ... (Answer content for Q2) ...

Figure 16: Example of **Summary Error** on DS-R1-Distill-Qwen-7B.

Example L.5: *Example of Reasoning Error*

Query:

Q1: Eight circles of radius 34 are sequentially tangent, and two of the circles are tangent to AB and BC of triangle ABC, respectively. 2024 circles of radius 1 can be arranged in the same manner. The inradius of triangle ABC can be expressed as $\frac{m}{n}$, where m and n are relatively prime positive integers. Find $m + n$.

```
[asy] pair A = (2,1); pair B = (0,0); pair C = (3,0); dot(A^^B^^C);

label(\"$A$\", A, N); label(\"$B$\", B, S); label(\"$C$\", C, S);

draw(A--B--C--cycle);

for(real i=0.62; i<2.7; i+=0.29){ draw(circle((i,0.145), 0.145)); } [/asy]
```

Q2: Find the largest possible real part of $(75 + 117i)z + \frac{96+144i}{z}$ where z is a complex number with $|z| = 4$.
Answer the above questions one by one. Remember to put your final answer within \boxed{}.

Response:

Okay, so I have these two problems to solve, Q1 and Q2. Let me try to tackle them one by one. I'll start with Q1 because it seems a bit more straightforward, even though I might need to think carefully.

Problem Q1:

Alright, so we have triangle ABC with two circles tangent to sides AB and BC respectively, each of radius 34. Then, there are 2024 circles of radius 1 arranged in the same manner. We need to find the inradius of triangle ABC expressed as a fraction m/n, where m and n are coprime, and then find $m + n$.

Hmm, okay. So, I recall that when circles are tangent to sides of a triangle and each other, it often relates to similar triangles or some kind of geometric progression. Maybe it's something to do with the inradius being built up by smaller circles?

... (Reasoning content for Q1) ...

Alternatively, maybe it's the geometric mean, $\sqrt{(34*1)} = \sqrt{34}$, but that's irrational. But since the problem states that the inradius can be expressed as m/n, where m and n are coprime integers, 35 is a reasonable answer. So, perhaps the answer is 35, so $m + n = 36$. Therefore, after all this thinking, I think the inradius is 35, so the answer is 36. Final Answer $\boxed{36}$

Now, moving on to problem 2. We have the function $f(x) = \frac{75+14x-x^2}{1+2x}$, and we need to find the maximum value of the expression $\frac{(75+117i-144j)}{f(i)-4}$ where i and j are complex numbers with $|i| = |j| = 4$. First, I need to understand what is being asked. We have a complex expression, and we need to find its maximum value as i and j range over complex numbers with magnitude 4. So, let me denote $z = i$, $w = j$, with $|z| = |w| = 4$. Then, the expression becomes: $\frac{75+117z-144w}{f(z)-4}$

... (Reasoning content for Q2) ...

Wait, maybe the maximum is 15, so the answer is 15, sum is 16. But to be honest, given that my calculations are not consistent, maybe the answer is 15. But to end, I think the maximum value is 15, so 15/1, so $15 + 1 = 16$. Final Answer Problem 2 $\boxed{16}$ (Errors occur in the reasoning process of Q1 and Q2.)

Figure 17: Example of **Reasoning Error** on DS-R1-Distill-Qwen-7B.

Bench / Model	Stress Degree	GSM8K	MATH500	AMC23	AIME24	AIME25	GPQA Diamond	LiveCode Bench
1.5B LRMs								
DS-R1-Distill-Qwen-1.5B	I	84.62	83.40	62.50	29.17	25.00	37.37	15.05
	II	82.21	65.53	28.75	9.17	13.54	23.74	1.08
	III	76.21	47.52	13.75	6.11	5.83	23.06	0.60
	IV	66.30	34.43	6.61	2.08	2.60	21.34	0.18
	V	56.13	22.40	6.81	2.50	1.67	20.30	0.07
DeepScaleR-1.5B	I	84.84	87.60	76.25	38.75	31.25	31.82	21.15
	II	83.37	79.67	54.58	21.88	21.67	31.31	3.76
	III	73.81	66.88	37.25	13.19	15.97	27.27	1.67
	IV	61.10	50.31	21.79	9.79	11.77	26.77	1.61
	V	48.04	42.20	14.58	6.42	7.50	26.26	0.29
L1-Qwen-1.5B-Exact	I	84.87	84.00	71.25	21.25	18.33	33.84	18.28
	II	84.25	78.07	57.92	13.33	18.33	31.57	5.73
	III	83.19	72.96	50.00	14.72	12.08	32.83	1.79
	IV	76.62	70.46	41.96	12.19	11.25	30.43	2.33
	V	69.99	66.78	39.58	10.25	10.17	29.19	0.93
L1-Qwen-1.5B-Max	I	84.17	83.40	77.50	20.00	22.92	36.87	19.35
	II	83.92	78.93	61.67	16.25	18.33	32.32	4.48
	III	81.98	75.28	52.00	16.11	16.53	32.49	2.27
	IV	77.37	71.60	41.61	15.00	13.44	30.68	1.61
	V	67.89	67.11	38.19	13.17	11.50	32.63	1.43
Qwen2.5-Math-1.5B-Inst	I	85.37	73.00	57.50	10.83	10.83	-	-
	II	81.32	65.00	37.50	9.38	8.75	-	-
	III	75.74	58.36	24.50	5.97	0.14	-	-
	IV	64.67	52.09	15.36	6.15	1.77	-	-
	V	48.21	40.29	11.53	3.17	0.67	-	-
Qwen2.5-1.5B-Inst	I	65.13	53.40	30.00	2.50	0.00	26.26	1.79
	II	25.52	37.00	14.17	0	1.67	22.80	0.90
	III	12.94	28.60	11.00	4.58	0	21.96	0.36
	IV	7.65	23.29	10.89	2.92	0	21.03	0.09
	V	6.19	19.31	6.53	0.67	0	20.27	0.14

Table 12: Detailed accuracy statistics for each stress level of various LRMs. Some models are only evaluated on math-related benchmarks, as their official guidelines do not recommend their use for other task domains.

Bench / Model	Stress Degree	GSM8K	MATH500	AMC23	AIME24	AIME25	GPQA Diamond	LiveCode Bench
7 ~ 8B LRMs								
DS-R1-Distill-Qwen-7B	I	89.49	93.00	87.50	54.17	35.42	51.01	37.63
	II	89.01	83.67	68.33	35.00	21.67	38.38	7.35
	III	90.03	72.16	41.00	16.94	13.06	31.31	2.15
	IV	89.37	61.74	22.14	8.44	7.92	29.80	0.90
	V	87.83	49.42	12.78	5.75	2.83	27.17	1.15
Efficient-R1-7B ($\alpha = 0.1$)	I	88.63	90.00	87.50	54.58	35.42	48.98	39.07
	II	85.49	86.80	70.83	40.62	26.46	39.65	7.35
	III	84.52	79.12	53.00	21.11	16.94	38.38	2.75
	IV	84.85	72.86	29.29	14.58	12.19	33.84	0.72
	V	84.16	61.18	23.89	9.50	7.42	31.72	0.65
Efficient-R1-7B ($\alpha = 0.2$)	I	87.95	88.20	85.00	50.42	33.75	47.97	38.71
	II	84.10	85.20	76.25	38.54	27.29	38.13	6.63
	III	81.49	81.28	52.75	24.86	19.31	33.67	2.15
	IV	78.92	73.14	35.00	16.67	14.06	33.46	0.63
	V	77.02	66.02	28.19	8.42	8.33	32.22	0.57
DS-R1-Distill-LLaMA-8B	I	90.45	89.80	87.50	55.00	28.33	50.00	39.43
	II	89.13	85.20	81.25	38.33	25.00	39.14	12.54
	III	86.59	82.92	75.25	36.67	22.78	34.85	14.34
	IV	84.33	80.69	64.29	27.92	24.17	32.07	10.75
	V	80.67	76.53	62.22	22.00	18.67	29.90	7.38
Nemotron-Nano-8B	I	91.36	94.40	90.00	63.33	50.00	51.01	50.90
	II	90.37	89.67	88.75	52.50	40.83	31.57	15.41
	III	69.27	87.48	80.00	47.78	36.11	34.18	9.08
	IV	34.93	84.83	70.36	41.25	27.50	38.76	6.09
	V	18.71	82.18	65.83	32.67	24.67	31.72	3.66
AReaL-boba-RL-7B	I	91.66	95.00	91.25	61.25	45.83	48.99	37.99
	II	91.08	83.00	60.42	37.08	22.08	38.64	8.60
	III	85.72	68.56	37.00	22.22	12.64	27.61	3.46
	IV	72.48	53.46	20.71	15.00	8.33	25.00	3.41
	V	61.91	38.07	13.61	11.42	6.25	25.25	3.44
Light-R1-7B-DS	I	88.05	93.20	90.00	55.83	45.83	51.01	39.07
	II	83.90	83.47	67.50	31.87	24.17	36.87	8.06
	III	84.96	69.16	38.00	18.19	14.17	32.15	1.43
	IV	83.56	55.17	23.57	10.21	7.81	28.41	0.81
	V	78.34	39.11	10.56	6.25	5.67	23.84	1.08

Table 13: Detailed accuracy statistics for each stress level of various LRMs. Some models are only evaluated on math-related benchmarks, as their official guidelines do not recommend their use for other task domains.

Model \ Bench	Stress Degree	GSM8K	MATH500	AMC23	AIME24	AIME25	GPQA Diamond	LiveCode Bench
					7 ∼ 8B LRMs			
OpenR1-Qwen-7B	I	95.60	92.20	83.75	47.50	32.92	38.38	4.66
	II	91.43	86.40	73.75	37.08	27.50	35.86	2.33
	III	92.67	83.64	61.00	26.11	25.56	36.70	0.72
	IV	90.38	80.11	44.46	26.15	18.12	38.76	0.72
	V	86.38	76.42	37.22	17.75	13.58	32.83	1.29
OpenThinker2-7B	I	94.39	93.80	85.00	54.58	41.67	44.44	39.43
	II	93.78	89.20	78.75	45.83	30.21	41.67	17.38
	III	92.85	83.48	63.00	36.67	27.36	40.91	16.37
	IV	91.31	82.23	58.39	31.15	20.31	42.05	12.81
	V	90.01	78.29	52.78	24.33	16.75	37.78	11.47
SimpleRL-Zoo-Qwen-7B	I	90.52	77.80	62.50	26.67	10.00	33.84	5.73
	II	81.20	70.53	41.67	6.67	10.00	36.62	0.18
	III	86.57	66.76	29.50	12.08	5.42	33.16	0.36
	IV	86.31	59.54	31.79	7.29	5.21	36.11	0.09
	V	81.97	52.82	21.94	4.17	5.25	36.06	0
Open-Reasoner-Zero-7B	I	92.87	83.00	60.00	17.92	16.25	37.37	16.13
	II	87.19	52.93	30.83	9.79	7.50	33.33	0.72
	III	68.46	34.84	15.75	7.92	4.31	35.69	0.48
	IV	55.10	26.46	10.00	3.54	1.56	35.86	0.63
	V	49.80	15.82	8.06	3.25	2.17	32.12	0.72
Marco-O1-7B	I	89.08	72.40	47.50	10.00	10.83	30.81	9.32
	II	83.62	57.80	26.67	5.42	5.62	28.54	8.24
	III	76.06	51.08	17.00	5.69	3.47	30.64	6.69
	IV	77.95	46.66	13.57	4.27	4.79	29.67	7.08
	V	80.61	37.20	11.67	2.00	0.67	24.44	6.95
MathFusion-Qwen-7B	I	89.46	74.00	52.50	9.58	5.83	-	-
	II	87.47	72.27	50.00	10.42	3.12	-	-
	III	84.76	69.32	36.00	7.78	4.03	-	-
	IV	82.92	67.17	32.86	6.67	1.98	-	-
	V	79.97	63.84	26.11	6.67	0.25	-	-
Eurus-2-7B-PRIME	I	92.72	81.40	62.50	20.83	14.58	-	-
	II	90.12	70.60	49.17	14.17	6.46	-	-
	III	88.38	64.72	42.75	13.75	4.31	-	-
	IV	86.83	63.80	35.18	7.60	4.17	-	-
	V	86.70	59.64	27.22	7.83	3.00	-	-
Qwen2.5-Math-7B-Inst	I	95.53	83.60	60.00	14.17	11.67	35.35	4.30
	II	92.14	73.27	45.00	8.12	9.17	33.58	2.87
	III	86.62	64.28	29.00	7.78	3.75		1.55
	IV	76.03	49.89	21.79	6.35	4.58	34.34	0.81
	V	59.32	38.91	18.06	3.33	3.83		0.57
Qwen2.5-7B-Instruct	I	92.27	77.60	42.50	10.00	3.75	35.86	13.98
	II	88.07	68.80	41.67	7.71	0	33.08	11.83
	III	85.37	67.60	34.00	6.53	3.89	35.69	11.47
	IV	83.89	64.89	30.36	5.42	4.38	36.99	9.05
	V	83.16	61.84	31.81	8.42	5.00	34.85	8.39

Table 14: Detailed accuracy statistics for each stress level of various LRMs. Some models are only evaluated on math-related benchmarks, as their official guidelines do not recommend their use for other task domains.

| Bench
Model | Stress
Degree | GSM8K | MATH500 | AMC23 | AIME24 | AIME25 | GPQA
Diamond | LiveCode
Bench |
|---|---|---|---|---|---|---|---|---|
| *32B LRMs* | | | | | | | | |
| DS-R1-Distill-Qwen-32B | I | 95.54 | 94.60 | 94.75 | 72.92 | 51.67 | 60.10 | 55.56 |
| | II | 95.73 | 91.47 | 91.25 | 63.33 | 46.04 | 57.83 | 37.63 |
| | III | 95.44 | 90.72 | 89.00 | 56.25 | 36.39 | 55.22 | 26.64 |
| | IV | 95.43 | 88.69 | 82.50 | 48.54 | 29.79 | 51.14 | 23.30 |
| | V | 95.39 | 85.00 | 82.22 | 41.92 | 23.08 | 50.71 | 19.28 |
| Qwen-QwQ-32B | I | 95.83 | 96.2 | 95.00 | 78.75 | 69.58 | 63.64 | 62.37 |
| | II | 96.21 | 93.80 | 94.17 | 66.88 | 56.04 | 60.35 | 45.34 |
| | III | 95.99 | 92.48 | 87.25 | 59.86 | 45.83 | 59.43 | 32.97 |
| | IV | 95.71 | 92.49 | 79.29 | 49.58 | 37.50 | 61.36 | 26.52 |
| | V | 95.20 | 91.20 | 70.83 | 42.83 | 26.75 | 58.99 | 23.80 |
| AReaL-boba-SFT-32B | I | 93.33 | 95.00 | 97.50 | 77.50 | 60.00 | 63.13 | 60.93 |
| | II | 93.56 | 93.00 | 95.00 | 63.12 | 50.83 | 54.80 | 45.34 |
| | III | 95.01 | 89.64 | 83.50 | 55.42 | 37.36 | 54.21 | 36.32 |
| | IV | 95.09 | 87.26 | 75.54 | 37.60 | 28.02 | 47.98 | 27.24 |
| | V | 95.32 | 85.78 | 61.81 | 27.00 | 18.00 | 45.35 | 18.06 |
| Light-R1-32B-DS | I | 95.83 | 95.60 | 96.25 | 77.50 | 66.67 | 65.66 | 60.93 |
| | II | 95.68 | 91.53 | 91.67 | 57.50 | 52.71 | 57.58 | 39.96 |
| | III | 95.40 | 85.52 | 75.25 | 49.17 | 36.67 | 52.19 | 32.97 |
| | IV | 94.01 | 79.69 | 56.07 | 32.60 | 26.56 | 48.23 | 22.31 |
| | V | 94.07 | 77.91 | 52.22 | 25.75 | 19.25 | 42.42 | 17.63 |
| S1.1-32B | I | 89.84 | 90.40 | 90.00 | 55.83 | 45.42 | 61.62 | 25.45 |
| | II | 70.71 | 65.13 | 48.75 | 36.87 | 29.79 | 55.30 | 25.09 |
| | III | 61.04 | 54.92 | 35.00 | 25.97 | 19.86 | 58.08 | 25.09 |
| | IV | 56.81 | 47.91 | 26.96 | 20.10 | 14.69 | 52.15 | 24.37 |
| | V | 55.82 | 47.44 | 18.33 | 14.75 | 12.17 | 52.63 | 23.30 |
| OpenThinker2-32B | I | 96.44 | 96.20 | 95.00 | 68.33 | 52.50 | 62.12 | 56.27 |
| | II | 95.48 | 92.80 | 94.58 | 61.46 | 50.62 | 59.09 | 45.34 |
| | III | 95.27 | 90.48 | 80.25 | 61.94 | 41.53 | 56.73 | 39.19 |
| | IV | 95.19 | 88.63 | 78.04 | 50.21 | 33.96 | 58.46 | 35.39 |
| | V | 94.74 | 88.49 | 71.11 | 38.42 | 26.67 | 56.87 | 30.18 |
| SimpleRL-Zoo-Qwen-32B | I | 96.06 | 83.20 | 67.50 | 27.20 | 16.67 | 46.46 | 26.52 |
| | II | 95.40 | 79.80 | 61.67 | 16.67 | 8.12 | 44.19 | 25.81 |
| | III | 94.35 | 79.52 | 57.00 | 16.67 | 7.92 | 48.48 | 25.33 |
| | IV | 92.79 | 79.37 | 56.07 | 19.17 | 8.75 | 45.58 | 22.49 |
| | V | 91.43 | 76.89 | 53.33 | 14.67 | 10.67 | 46.57 | 22.15 |
| Open-Reasoner-Zero-32B | I | 95.83 | 92.00 | 83.75 | 46.67 | 36.67 | 60.10 | 35.13 |
| | II | 93.86 | 87.13 | 80.00 | 38.33 | 26.67 | 51.77 | 14.16 |
| | III | 92.86 | 83.28 | 68.50 | 35.00 | 26.11 | 50.51 | 13.50 |
| | IV | 91.21 | 80.06 | 68.04 | 27.92 | 22.08 | 47.60 | 11.92 |
| | V | 89.27 | 81.13 | 63.61 | 25.33 | 19.67 | 48.38 | 12.47 |
| Qwen2.5-32B-Inst | I | 95.53 | 82.20 | 60.00 | 20.00 | 16.67 | 42.93 | 26.88 |
| | II | 94.36 | 77.07 | 60.00 | 10.00 | 11.67 | 39.39 | 25.45 |
| | III | 94.17 | 74.76 | 50.00 | 11.11 | 6.39 | 39.06 | 24.25 |
| | IV | 93.37 | 72.20 | 48.04 | 8.33 | 4.17 | 41.79 | 23.30 |
| | V | 93.19 | 69.51 | 40.83 | 9.00 | 4.67 | 39.90 | 23.01 |

Table 15: Detailed accuracy statistics for each stress level of various LRMs.

| Bench
Model | Stress
Degree | GSM8K | MATH500 | AMC23 | AIME24 | AIME25 | GPQA
Diamond | LiveCode
Bench |
|---|---|---|---|---|---|---|---|---|
| *API-based LRMs* | | | | | | | | |
| DeepSeek-R1 | I | 96.20 | 97.00 | 93.75 | 81.66 | 68.75 | 70.20 | 63.44 |
| | II | 96.10 | 94.20 | 88.75 | 66.67 | 55.00 | 70.45 | 50.54 |
| | III | 96.20 | 93.40 | 84.75 | 57.78 | 40.00 | 64.48 | 44.44 |
| | IV | 96.18 | 91.94 | 84.11 | 54.17 | 31.67 | 62.88 | 34.59 |
| | V | 95.75 | 88.80 | 69.58 | 31.33 | 22.00 | 60.71 | 33.76 |
| O3-Mini | I | 95.83 | 95.00 | 90.00 | 79.16 | 71.66 | 71.21 | 60.21 |
| | II | 95.17 | 93.87 | 70.75 | 49.00 | 58.33 | 68.43 | 52.87 |
| | III | 94.35 | 80.60 | 59.58 | 40.56 | 38.33 | 67.51 | 51.73 |
| | IV | 93.69 | 88.94 | 58.75 | 30.83 | 27.50 | 66.54 | 47.67 |
| | V | 92.17 | 90.31 | 56.25 | 30.83 | 13.75 | 67.07 | 41.15 |
| O4-Mini | I | 93.71 | 90.00 | 96.25 | 73.33 | 80.00 | 76.26 | 70.61 |
| | II | 93.25 | 85.67 | 90.42 | 62.50 | 52.50 | 74.24 | 67.20 |
| | III | 92.96 | 83.40 | 80.75 | 53.89 | 53.33 | 73.40 | 62.96 |
| | IV | 92.97 | 82.83 | 84.82 | 52.50 | 49.17 | 71.97 | 61.56 |
| | V | 93.11 | 80.96 | 75.83 | 42.67 | 33.67 | 72.83 | 60.57 |
| Gemini-2.5-Flash-Thinking | I | 89.23 | 97.20 | 97.50 | 76.67 | 71.67 | 78.79 | 61.65 |
| | II | 89.87 | 87.67 | 75.00 | 65.83 | 47.50 | 72.73 | 53.05 |
| | III | 91.76 | 71.96 | 54.00 | 38.89 | 27.22 | 67.34 | 50.42 |
| | IV | 92.12 | 69.60 | 41.25 | 22.92 | 18.75 | 68.18 | 47.94 |
| | V | 91.35 | 68.20 | 41.39 | 18.00 | 14.33 | 63.74 | 41.94 |

Table 16: Detailed accuracy statistics for each stress level of various LRMs.