Understanding the Effectiveness of Cross-Domain Contrastive Unsupervised Domain Adaptation

Abstract

Unsupervised domain adaptation helps to transfer learned tasks from a source to a target domain in the lack of labeled data. Recently, contrastive learning showed promising results on this setup. However, there are limitations on the performance due to unbalanced objectives between the self-representation and the adaptation tasks. We show that pre-training choices and hard negative mining provide consistent improvements to successfully pair contrastive learning and unsupervised domain adaptation.

1 Introduction

The aim of unsupervised domain adaptation (UDA) is to improve the performance of a machine learning model trained on a source domain and tested on a target domain that has different characteristics than the source. This is done without using any labeled data from the target domain by learning a transferable feature representation that captures the shared information between the two domains, which is especially helpful in low data regimes. Several approaches have been proposed in the past which give theoretical bounds on target error (Ben-David et al., 2006; 2010); suggest aligning probability distributions using carefully designed metrics (Gretton et al., 2006; Long et al., 2015; 2017; Zellinger et al., 2017); and, recently, contrastive learning was used for domain adaptation (Chen et al., 2020; He et al., 2020; Kang et al., 2019; Khosla et al., 2020; Toldo et al., 2021; Wang et al., 2022) (Appendix F). However, improper use of these techniques can lead to suboptimal results. Our work examines the limitations of the contrastive approach for UDA introduced by Wang et al. (2022). We show that their method results in lower performance than a naive model without domain adaptation. We found that this degradation is due to the unbalanced effect of contrastive and classification objectives on model training, where domain adaptation shadows the main task of classification. Finally, through extensive experiments, we found that pre-training choices and explicit hard negative sampling can improve model performance.

2 Background

The formal definition of UDA setting can be found in Appendix A.1.

Wang et al. (2022) employ Cross-Domain Contrastive Loss (*CDCL*) for learning domain-invariant class-aware features. We describe their methodology in detail in Appendix A. This approach has caught our attention since it raised several important questions:

- How will additional objective, domain adaptation expressed in contrastive loss, affect the main task (classification)?

- The pseudo-labeling will inevitably produce incorrect labels, especially at the beginning of training. How will that affect model performance?

Thus, the focus of our study is understanding the impact of contrastive loss on the model training.

Table 1: Target accuracy (%) on Office-31 (ResNet-50) and VisDA2017 (ResNet-101) for unsupervised domain adaptation.

Method	Office-31						VisDA	Avg.
	A→W	A→D	W→A	W→D	D→A	D→W		
No adaptation	66.5	67.7	53.0	79.6	49.8	69.6	58.4	63.5
CDCL	48.2	53.7	51.2	50.4	51.8	59.9	60.1	53.6
Pretraining	70.8	70.2	65.5	81.6	65.1	83.8	63.9	71.6
Explicit Negative Sampling	73.2	74.9	64.3	88.3	64.6	83.5	68.1	73.8
Random Sampling	51.9	41.9	52.5	49.6	44.3	57.6	62.3	51.4
Implicit Negative Sampling	70.5	69.1	64.7	74.4	64.9	82.8	69.8	70.9

Figure 1: The accuracy of the baseline model with no domain adaptation. The gap between source and target accuracies signifies a misalignment between the two domains.

3 METHODOLOGY

Compared to the *Baseline* model with no domain adaptation (details are in Appendix B), see Figure 1, *CDCL* resulted in two well-aligned domains (there is a negligible gap between source and target accuracies). However, the accuracy for both domains dropped significantly, and the convergence rate slowed down. Overall, *CDCL* achieves the reduced domain gap by sacrificing accuracy (Table 1).

We found that this result is due to the overwhelming impact of the contrastive loss, which can be seen by examining gradient norms w.r.t. to each of the two losses. Apart from that, the confidence of predictions of the baseline model stays at low values of approx. 3%. For more details see Appendix C.

Since classification is overshadowed during training, we let the model to *pre-train* on the source domain before activating the contrastive loss (details are in Appendix B). The results in Table 1 and Figure 1 show that this technique provides on average an 18% improvement in performance.

Additionally, we discovered that explicit hard *negative sampling* helps to balance two losses, thus shifting focus on classification while still being able to align two domains. Table 1 indicates on average a 20% improvement over the baseline model (no adap.). To validate the positive impact of explicit hard negative sampling, we quantitatively show that neither random sampling nor implicit negative sampling lead to the same improvement (Table 1). More details are in Appendix D.

At last, we found that CDCL is resistant to noise and is not affected by incorrectly labeled target samples (Appendix E). The details of our experimental setup can be found in Appendix B.

4 CONCLUSION

As the result of our investigation, we found that contrastive loss overshadows the classification loss and therefore techniques for their balancing are required. We showed that pretraining of the model allows the establishment of good performance of the classifier before the start of domain adaptation. However, explicit hard-negative sampling may be a preferable method since it improves the classification accuracy and domain alignment in an easier manner, outperforming other approaches.

URM STATEMENT

The authors acknowledge that at least one key author of this work meets the URM criteria of ICLR 2023 Tiny Papers Track.

REFERENCES

Shai Ben-David, John Blitzer, Koby Crammer, and Fernando Pereira. Analysis of representations for domain adaptation. *Advances in neural information processing systems*, 19, 2006.

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 79(1):151–175, 2010.

Konstantinos Bousmalis, Nathan Silberman, David Dohan, Dumitru Erhan, and Dilip Krishnan. Unsupervised pixel-level domain adaptation with generative adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3722–3731, 2017.

Woong-Gi Chang, Tackgeun You, Seonguk Seo, Suha Kwak, and Bohyung Han. Domain-specific batch normalization for unsupervised domain adaptation. In *Proceedings of the IEEE/CVF conference on Computer Vision and Pattern Recognition*, pp. 7354–7362, 2019.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pp. 1180–1189. PMLR, 2015.

Arthur Gretton, Karsten Borgwardt, Malte Rasch, Bernhard Schölkopf, and Alex Smola. A kernel method for the two-sample-problem. *Advances in neural information processing systems*, 19, 2006.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Guoliang Kang, Lu Jiang, Yi Yang, and Alexander G Hauptmann. Contrastive adaptation network for unsupervised domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4893–4902, 2019.

Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *Advances in Neural Information Processing Systems*, 33:18661–18673, 2020.

Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International Conference on Machine Learning*, pp. 6028–6039. PMLR, 2020.

Mingsheng Long, Yue Cao, Jianmin Wang, and Michael Jordan. Learning transferable features with deep adaptation networks. In *International conference on machine learning*, pp. 97–105. PMLR, 2015.

Mingsheng Long, Han Zhu, Jianmin Wang, and Michael I Jordan. Deep transfer learning with joint adaptation networks. In *International conference on machine learning*, pp. 2208–2217. PMLR, 2017.

Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In *European conference on computer vision*, pp. 213–226. Springer, 2010.

Kuniaki Saito, Kohei Watanabe, Yoshitaka Ushiku, and Tatsuya Harada. Maximum classifier discrepancy for unsupervised domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3723–3732, 2018.

Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *European conference on computer vision*, pp. 443–450. Springer, 2016.

Baochen Sun, Jiashi Feng, and Kate Saenko. Return of frustratingly easy domain adaptation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30, 2016.

Marco Toldo, Umberto Michieli, and Pietro Zanuttigh. Unsupervised domain adaptation in semantic segmentation via orthogonal and clustered embeddings. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1358–1368, 2021.

Feng Wang and Huaping Liu. Understanding the behaviour of contrastive loss. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2495–2504, 2021.

Rui Wang, Zuxuan Wu, Zejia Weng, Jingjing Chen, Guo-Jun Qi, and Yu-Gang Jiang. Cross-domain contrastive learning for unsupervised domain adaptation. *IEEE Transactions on Multimedia*, 2022.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? *Advances in neural information processing systems*, 27, 2014.

Werner Zellinger, Thomas Grubinger, Edwin Lughofer, Thomas Natschläger, and Susanne Saminger-Platz. Central moment discrepancy (cmd) for domain-invariant representation learning. *arXiv preprint arXiv:1702.08811*, 2017.

A CDCL

This section is devoted to description of Cross-Domain Contrastive Loss (CDCL) proposed by Wang et al. (2022).

A.1 SETUP

In UDA, the aim is to adopt a model trained on a labeled source domain to perform well on other unlabeled domains. Formally, the source dataset is defined as a set of N_s tuples $(X_s, Y_s) = \{(x_s^i, y_s^i) : i \in [1; N_s]\}$ and target dataset is defined as a set of N_t samples $X_t = \{x_t^i : i \in [1; N_t]\}$. Samples in X_s and X_t are drawn from the source and target distributions D_s and D_t. Also, x_s and x_t belong to the same fixed set of M categories, i.e., $y_s^i \in \{0, \ldots, (M-1)\}$. Then, the task is to construct a model $f_t : X_t \to Y_t$ trained on $X_s \cup X_t$ which consists of feature encoder $g : X_t \to \mathbb{R}^d$ and classification head $h : \mathbb{R}^d \to Y_t$, where d is the dimensionality of feature space. We define z_s^i and z_t^j to be L2-normalized feature encodings of x_s^i and x_t^j.

A.2 PSEUDO-LABELING

The alignment of feature distributions on the class level is crucial for the high performance of a model. However, class information for the target domain is unavailable and requires approximation. That can be achieved with a technique called pseudo-labeling which uses K-means clustering to infer class information. This approach is based on the assumption that feature encodings of objects from the same class are likely to locate close to each other irrespective of their domain. Cluster centers are initialized to class centroids from the source domain, and the algorithm runs until convergence. Then, samples assigned to a cluster are pseudo-labeled as belonging to the class which was used to initialize this cluster. To reduce the labeling noise, all samples located far from cluster centers are removed; specifically, the samples are removed when the cosine similarity between their features and cluster centers is less than a threshold d.

A.3 CONTRASTIVE LOSS

Contrastive loss is generally utilized to produce feature space in which 'similar' samples (positive pairs) are located closer to each other, and 'dissimilar' samples (negative pairs) are far away. In the context of UDA, the contrastive loss is used to ensure that samples from the same class are mapped to the same location in the feature space irrespective of their domain. Therefore, a positive pair is defined as samples that belong to the same class and are from different domains. Similarly, a negative pair consists of samples from different classes and different domains. In each training step, one batch is sampled from each domain, and each target sample in a batch acts as an anchor. Then, the formulation of Cross-Domain Contrastive Loss is:

$$L_{\text{CDC}}^{t,i} = -\frac{1}{|P_s(\hat{y}_t^i)|} \sum_{p \in P_s(\hat{y}_t^i)} \log \frac{\exp(z_t^i z_s^p / \tau)}{\sum_{j \in I_s} \exp(z_t^{iT} z_s^j / \tau)}, \tag{A.1}$$

where i is the index of the anchor sample, I_s is the set of source samples in a mini-batch, $P_s(\hat{y}_t^i) = \{k \mid y_s^k = \hat{y}_t^i\}$ indicates the set of positive samples from the source domain that share the same label with the target anchor x_t^i, and τ is a temperature parameter.

Similarly, source samples are used as anchors to compute $L_{\text{CDC}}^{s,i}$. Combining $L_{\text{CDC}}^{t,i}$ and $L_{\text{CDC}}^{s,i}$ gives the final definition of the Cross-Domain Contrastive Loss:

$$L_{\text{CDC}} = \sum_i^{N_s} L_{\text{CDC}}^{s,i} + \sum_j^{N_t} L_{\text{CDC}}^{t,j}. \tag{A.2}$$

A.4 CLASSIFICATION

Separately from two batches sampled for contrastive loss, another batch is sampled from the source dataset to train the classifier. The outputs of classification head h are used to evaluate classification performance, and Cross-Entropy loss is used as the optimization objective:

$$L_{\text{CE}} = -\sum_i^M y_i log(p_i), \tag{A.3}$$

where y_i is 1 when a sample x is labeled as class i and 0 otherwise; p_i is a probability of a sample x belonging to class i that comes from model predictions.

A.5 FINAL OPTIMIZATION OBJECTIVE

Classification and contrastive losses are combined with a weighting parameter λ to define the final optimization objective:

$$\min_\theta \quad L_{\text{CE}}(\theta; D_s) + \lambda L_{\text{CDC}}(\theta; D_s, D_t). \tag{A.4}$$

B EXPERIMENTAL SETUP

For a fair comparison, we took the same model architecture and datasets as Wang et al. (2022) for our experiments.

B.1 DATASETS

Office-31 contains 31 classes of objects typically encountered in an office environment and is split into 3 domains—'amazon' with images taken on a good camera and on white background; 'dslr' with images taken in an office on a high-resolution camera with various backgrounds; and 'webcam' with images also collected in an office environment and exhibiting significant noise.

VisDA2017 is a large-scale dataset having 12 classes. In our experiments, we evaluated model performance on the synthesis-to-real adaptation task.

The analysis throughout this paper was conducted on the 'amazon-webcam' pair. Other datasets are used for final evaluation with the results present in Table 1.

B.2 IMPLEMENTATION DETAILS

CDCL. For each dataset a separate backbone is used - ResNet50 for Office-31 and ResNet101 for VisDA, both are pretrained on ImageNet (Deng et al., 2009). In addition, we used Domain-Specific BatchNorm (Chang et al., 2019), an L2-normalization component for outputs, and a single fully-connected layer with a bias component disabled as the classification head.

We used SGD with a momentum of 0.9 for model optimization with the learning rate set to $1e^{-3}$ for the backbone and $1e^{-2}$ for the classification head. Learning rate scheduler: $\eta = \eta_0(1 + 10p)^{-b}$, where p linearly increases from 0 to 1 and b is set to 0.75 (for Office-31) and to 2.25 (for VisDA). All pictures are resized to $(224, 224)$ shape, and pixel values are normalized to have mean 0 and variance 1. The number of epochs is 500.

For contrastive loss: temperature parameter $\tau = 1.0$ and weighting parameter $\lambda = 1.4$.

For a reliable estimate of model performance, we averaged the results over 4 dataset splits produced by StratifiedKFold.

Changes described below are made with respect to the settings of **CDCL**.

No Adaptation (Baseline). This model was trained on the source domain with the target domain used only for evaluation. That was achieved by setting weighting parameter $\lambda = 0$.

Pretraining. The model was trained for 100 epochs on the source dataset after which the contrastive loss was activated.

Explicit Negative Sampling. Expression A.1 was substituted for expression D.1 with threshold parameter $s_\alpha = 0.5$.

Implicit Negative Sampling. Temperature parameter $\tau = 0.05$. For Office-31 weighting parameter $\lambda = 0.1$.

Random Sampling. In each training step, we chose random negative pairs in the same amount as the Explicit Negative Sampling thresholding would give.

Obtaining gradients w.r.t. to each loss. We calculated the gradients w.r.t. to each component in the expression A.4 separately - $L_{\text{CE}}(\theta; D_s)$ and $\lambda L_{\text{CDC}}(\theta; D_s, D_t)$. Then, we treated gradients for all weights as a single vector and calculated its L2-norm.

Contrastive-only model The feature encoder was updated only with gradients w.r.t. to the L_{CDC}. Since classification head h does not participate in calculation of contrastive loss, its weights will not be updated in this way. Therefore, classification loss L_{CE} was calculated, but its impact was limited only to the classification head.

C ANALYSIS OF CDCL

The fact that the model succeeds in aligning two domains well but sacrifices the accuracy can signify that two losses are combined disproportionally. Indeed, Figure C.1 shows that for CDCL the gradients w.r.t. to contrastive loss dominate the gradients w.r.t. classification loss, so the model gets too concentrated on domain alignment, and classification loss effectively does not have an impact on weight update. Figure C.2 shows the model performance with classification loss impacting only task-specific classification head, i.e., gradients w.r.t. classification loss do not affect the weights of feature encoder. The curves produced by *CDCL* (Figure 1) and the contrastive-only model are almost identical, which signifies that contrastive loss indeed greatly overweights the classification loss. The details of these experiments are described in Appendix B.

Also, we found that the model is not confident in its predictions. Figure C.3 shows that though a mean probability of predicted class grows over time, it stays at low values of approx. 3%.

Figure C.1: Ratio between gradient norms w.r.t. contrastive and classification loss. The rapid decrease of the ratio for Explicit Negative Sampling training strategy highlights its ability to balance two losses.

Figure C.2: Performance of the Contrastive-only model. This figure resembles the Figure 1 which means that for default settings the classification loss does not effect on weight update.

D EXPLICIT HARD NEGATIVE SAMPLING

Explicit Hard Negative Sampling is intended to make the model focus only on the hardest examples, thus increasing the efficiency of training. Explicit Hard Negative Sampling is defined as:

$$L_{\text{CDC}}^{t,i} = -\frac{1}{|P_s(\hat{y}_t^i)|} \sum_{p \in P_s(\hat{y}_t^i)} \log \frac{\exp(z_t^i z_s^p / \tau)}{\sum_{j \in I_s, z_t^{iT} z_s^j > s_\alpha} \exp(z_t^{iT} z_s^j / \tau)}, \tag{D.1}$$

where s_α is the threshold parameter for filtering hard negatives.

Since contrastive loss greatly overshadows classification, we decided to decrease its impact on parameters' gradients by limiting the set of samples on which it operates. Figure C.1 shows that with this approach the impact of contrastive loss steadily decreases as the set of hard negatives becomes smaller. Importantly, the best performance is achieved when the model is fed with the hardest examples. Our experiments show that random sampling either has no effect or leads to

Figure C.3: The mean probability of predicted class in each epoch for CDCL. Though overall, the model becomes more confident in its predictions throughout training, it stays at low values.

worse performance (Table 1). Alternatively, Negative Sampling can be performed in an implicit way by lowering the value of temperature parameter τ. Wang & Liu (2021) describe this behavior of contrastive loss and show the superiority of Explicit Negative Sampling. Our experiments also indicate that on average Implicit Negative Sampling gives worse results (Table 1), which is in line with the work of Wang & Liu (2021).

E   REMOVING INCORRECTLY LABELED SAMPLES

Our experiments show that on average approx. 15% of training target samples were mislabeled for the '$A \rightarrow W$' dataset pair. Despite this, the methodology suggested by Wang et al. (2022) is resistant to incorrect pseudo-labels present in the training dataset. To support this conclusion, we conducted the following experiment: we used the original CDCL setup as described in Appendix B, but after each pseudo-labeling procedure, we filtered out samples for which $y_{real} \neq y_{pseudo}$. In this way, the model received only correctly labeled samples throughout training. Figure E.1 shows the performance of this model—the curves almost exactly repeat the ones on Figure 1 (b), showing that the presence of noise in training data does not affect the quality of the model.

F   RELATED WORK

Previous studies (Ben-David et al., 2006; 2010) have provided theoretical bounds on target error in terms of source error, domain divergence, and shared expected loss. Therefore, many UDA works focus on minimizing domain divergence, and can be broadly categorized into two paradigms.

The first paradigm is based on adversarial approach. For instance, Ben-David et al. (2006) propose using a binary classifier to distinguish between two domains as a way of measuring domain divergence. This idea leads to the adversarial model proposed by Ganin & Lempitsky (2015), which extracts domain-invariant features by reversing gradients from the domain discriminator to the feature extractor. Another example is the use of Generative Adversarial Networks (GANs) to transform source images to look like they are drawn from the target distribution (Bousmalis et al., 2017).

The second paradigm is based on aligning probability distributions of features between the source and target domains. This approach is motivated by the study of Yosinski et al. (2014) that show that transferability decreases in higher layers of a neural network, and the idea of minimizing discrepancy. Several studies have proposed metrics for aligning probability distributions, such as Maximum Moment Discrepancy (MMD) (Gretton et al., 2006; Long et al., 2015; 2017), Central Moment

Figure E.1: The performance of CDCL trained with removal of incorrectly pseudo-labeled target samples. This figure resembles Figure 1, which indicates that CDCL is resistant to pseudo-labeling noise.

Discrepancy (CMD) (Zellinger et al., 2017), and aligning covariance matrices of features from the top level of the feature extractor (Sun & Saenko, 2016; Sun et al., 2016).

Some works attempt to address misalignment on the class level. For example, Saito et al. (2018) train two classifiers on labeled source data and minimize disagreement between their predictions for target data. Kang et al. (2019) suggest a Contrastive Domain Discrepancy (CDD) metric for distributions conditioned on class information. Saenko et al. (2010) attempt to find a transform into a latent space where the source and target look similar while preserving class information. However, these approaches require labeled examples for each class in the target data.

In UDA, labels for target data are not available, but can be approximated by pseudo-labeling (Kang et al., 2019; Liang et al., 2020; Toldo et al., 2021). For example, Kang et al. (2019) use K-means algorithm to cluster target data, and initial cluster centers are set to centroids of classes calculated on source data.

Our work is inspired by Wang et al. (2022), which apply contrastive learning to minimize cross-domain distances between samples of the same category.