Q-Transformer: Scalable Offline Reinforcement Learning via Autoregressive Q-Functions

Abstract: In this work, we present a scalable reinforcement learning method for training multi-task policies from large offline datasets that can leverage both human demonstrations and autonomously collected data. Our method uses a Transformer to provide a scalable representation for Q-functions trained via offline temporal difference backups. We therefore refer to the method as Q-Transformer. By discretizing each action dimension and representing the Q-value of each action dimension as separate tokens, we can apply effective high-capacity sequence modeling techniques for Q-learning. We present several design decisions that are crucial to obtain good performance with offline RL training, and show that Q-Transformer outperforms prior offline RL algorithms and imitation learning techniques on a large diverse real-world robotic manipulation task suite.

Keywords: reinforcement learning, offline RL, robotic manipulation

1 Introduction

Robotic learning methods that incorporate large and diverse datasets in combination with high-capacity expressive models, such as Transformers [1, 2, 3, 4, 5, 6], have the potential to acquire generalizable and broadly applicable policies that perform well on a wide variety of tasks [1, 2]. For example, these policies can follow natural language instructions [4, 7], perform multi-stage behaviors [8, 9], and generalize broadly across environments, objects, and even robot morphologies [10, 3]. However, many of the recently proposed high-capacity models in the robotic learning literature are trained with supervised learning methods. As such, the performance of the resulting policy is limited by the degree to which human demonstrators can provide high-quality demonstration data. This is limiting for two reasons. First, we would like robotic systems that are *more* proficient than human teleoperators, exploiting the full potential of the hardware to perform tasks quickly, fluently, and reliably. Second, we would like robotic systems that get better with autonomously gathered experience, rather than relying entirely on high-quality demonstrations.

Figure 1: Q-Transformer enables training high-capacity sequential architectures on mixed quality data. Our policies are able to improve upon human demonstrations and execute a variety of manipulation tasks in the real world.

Reinforcement learning in principle provides both of these capabilities. A number of promising recent advances demonstrate the successes of large-scale robotic RL in varied settings, such as robotic grasping and stacking [11, 12], learning heterogeneous tasks with human-specified rewards [13], learning multi-task policies [14, 15], learn-

ing goal-conditioned policies [16, 17, 18, 19], and robotic navigation [20, 21, 22, 23, 24]. However, training high-capacity models such as Transformers using RL algorithms has proven more difficult to instantiate effectively at large scale. In this paper, we aim to combine large-scale robotic learning from diverse real-world datasets with modern high-capacity Transformer-based policy architectures.

While in principle simply replacing existing architectures (e.g., ResNets [15] or smaller convolutional neural networks [11, 14]) with a Transformer is conceptually straightforward, devising a methodology that effectively makes use of such architectures is considerably more challenging. High-capacity models only make sense when we train on large and diverse datasets – small, narrow datasets simply do not require this much capacity and do not benefit from it. While prior works used simulation to create such datasets [2, 25, 26], the most representative data comes from the real world [12, 11, 14]. Therefore, we focus on reinforcement learning methods that can use Transformers and incorporate large, previously collected datasets via *offline* RL. Offline RL methods train on prior data, aiming to derive the most effective possible policy from a given dataset. Of course, this dataset can be augmented with additionally autonomously gathered data, but the training is separated from data collection, providing an appealing workflow for large-scale robotics applications [27].

Another issue in applying Transformer models to RL is to design RL systems that can effectively train such models. Effective offline RL methods generally employ Q-function estimation via temporal difference updates [28]. Since Transformers model discrete token sequences, we convert the Q-function estimation problem into a discrete token sequence modeling problem, and devise a suitable loss function for each token in the sequence. Naïvely discretizing the action space leads to exponential blowup in action cardinality, so we employ a per-dimension discretization scheme, where each dimension of the action space is treated as a *separate time step* for RL. Different bins in the discretization corresponds to distinct actions. The per-dimension discretization scheme allows us to use simple discrete-action Q-learning methods with a conservative regularizer to handle distributional shift [29, 30]. We propose a specific regularizer that minimizes values of every action that was *not* taken in the dataset and show that our method can learn from both narrow demonstration-like data and broader data with exploration noise. Finally, we utilize a hybrid update that combines Monte Carlo and n-step returns with temporal difference backups [31], and show that doing so improves the performance of our Transformer-based offline RL method on large-scale robotic learning problems.

In summary, our main contribution is the Q-Transformer, a Transformer-based architecture for robotic offline reinforcement learning that makes use of per-dimension tokenization of Q-values and can readily be applied to large and diverse robotic datasets, including real-world data. We summarize the components of Q-Transformer in Figure 1. Our experimental evaluation validates the Q-Transformer by learning large-scale text-conditioned multi-task policies, both in simulation for rigorous comparisons and in large-scale real-world experiments for realistic validation. Our real-world experiments utilize a dataset with 38,000 *successful* demonstrations and 20,000 *failed* autonomously collected episodes on more than 700 tasks, gathered with a fleet of 13 robots. Q-Transformer outperforms previously proposed architectures for large-scale robotic RL [15, 14], as well as previously proposed Transformer-based models such as the Decision Transformer [32, 33].

2   Related Work

Offline RL has been extensively studied in recent works [34, 35, 36, 37, 35, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 39]. Conservative Q-learning (CQL) [29] learns policies constrained to a conservative lower bound of the value function. Our goal is not to develop a new algorithmic principle for offline RL, but to devise an offline RL system that can integrate with high-capacity Transformers, and scale to real-world multi-task robotic learning. We thus develop a version of CQL particularly effective for training large Transformer-based Q-functions on mixed quality data. While some works have noted that imitation learning outperforms offline RL on demonstration data [49], other works showed offline RL techniques to be effective with demonstrations both in theory and in practice [50, 15]. Nonetheless, a setting that combines "narrow" demonstration data with "broad" sub-optimal (e.g., autonomously collected) data is known to be particularly difficult [51, 52, 53], though it is quite natural in many robotic learning settings where we might want to augment a core set of demonstrations with relatively inexpensive low-quality autonomously collected data. We believe that the effectiveness of our method in this setting is of particular interest to practitioners.

Transformer-based architectures [54] have been explored in recent robotics research, both to learn generalizable task spaces [55, 56, 57, 58, 8, 59] and to learn multi-task or even multi-domain se-

Figure 2: **Q-values update for each action dimension at timestep** t. Given a history of states, we update the Q-values of all bins in all action dimensions. The Q-values of the discrete action bins of the *dataset actions* are trained via the Bellman update (the green boxes). The values of action bins not observed in the dataset are minimized towards zero (the red boxes). The Q-targets of all action dimensions except the last are computed using maximization over the next action dimension within the same time step. The Q-target of the last action dimension is computed using the discounted maximization of the first dimension of the next time step plus the reward. We also incorporate Monte Carlo returns by taking the maximum of the computed Q-targets and the return-to-go.

quential policies directly [2, 1, 6, 3]. Although most of these works considered Transformers in a supervised learning setting, e.g. learning from demonstrations [4, 5], there are works on employing Transformers for RL and conditional imitation learning [32, 20, 60, 33]. In our experiments, we compare to Decision Transformer (DT) in particular [32], which extends conditional imitation learning with reward conditioning [61, 62] to use sequence models and structurally resembles imitation learning methods that have been used successfully for robotic control. Although DT incorporates elements of RL (namely, reward functions), it does not provide a mechanism to improve over the demonstrated behavior or recombine parts of the dataset to synthesize more optimal behaviors, and indeed is known to have theoretical limitations [63]. On the other hand, such imitation-based recipes are popular perhaps due to the difficulty of integrating Transformer architectures with more powerful temporal difference methods (e.g., Q-learning). We show that several simple but important design decisions are needed to make this work, and our method significantly outperforms non-TD methods such as DT, as well as imitation learning, on our large-scale multi-task robotic control evaluation.

To develop a Transformer-based Q-learning method, we discretize each action space dimension, with each dimension acting as a distinct time step. Autoregressive generation of discrete actions has been explored by Metz et al. [64], who propose a hierarchical decomposition of an MDP and then utilize LSTM [65] for autoregressive discretization. Our discretization scheme is similar but simpler, in that we do not use any hierarchical decomposition but simply treat each dimension as a time step. However, since our goal is to perform offline RL at scale with real-world image based tasks (vs. the smaller state-space tasks learned via online RL by Metz et al. [64]), we present a number of additional design decisions to impose a conservative regularizer, enabling training our Transformer-based offline Q-learning method at scale, providing a complete robotic learning system.

3 Background

In RL, we learn policies π that maximizes the expected total reward in a Markov decision process (MDP) with states s, actions a, discount factor $\gamma \in (0, 1]$, transition function $T(s'|s, a)$ and a reward function $R(s, a)$. Actions a have dimensionality $d_{\mathcal{A}}$. Value-based RL approaches learn a Q-function $Q(s, a)$ representing the total discounted return $\sum_t \gamma^t R(s_t, a_t)$, with policy $\pi(a|s) = \arg\max_a Q(s, a)$. The Q-function can be learned by iteratively applying the Bellman operator:

$$\mathcal{B}^* Q(s_t, a_t) = R(s_t, a_t) + \gamma \max_{a_{t+1}} Q(s_{t+1}, a_{t+1}),$$

approximated via function approximation and sampling. The offline RL setting assumes access to an offline dataset of transitions or episodes, produced by some unknown behavior policy $\pi_\beta(a|s)$, but does not assume the ability to perform additional online interaction during training. This is appealing

Figure 3: Q-Transformer network architecture. The language instruction is encoded with *Universal Sentence Encoder* [66] and then fed to *Film EfficientNet* [67, 68] network together with the robot camera images. The output is then concatenated with embeddings of predicted action dimensions and processed by Transformer layers. We apply sigmoid to the Transformer output to produce Q-values of all action value bins. Finally, one-hot action vectors are constructed by taking the $\arg\max$ over all bins and are fed back to the network to predict the Q-values of the next action dimensions.

for real-world robotic learning, where on-policy data collection is time-consuming. Learning from offline datasets requires addressing distributional shift, since in general the action that maximizes $Q(s_{t+1}, a_{t+1})$ might lie outside of the data distribution. One approach to mitigate this is to add a conservative penalty [29, 52] that pushes down the Q-values $Q(s, a)$ for any action a outside of the dataset, thus ensuring that the maximum value action is in-distribution.

In this work, we consider tasks with sparse rewards, where a binary reward $R \in \{0, 1\}$ (indicating success or failure) is assigned at the last time step of episodes. Although our method is not specific to this setting, such reward structure is common in robotic manipulation tasks that either succeed or fail on each episode, and can be particularly challenging for RL due to the lack of reward shaping.

4   Q-Transformer

In this section, we introduce Q-Transformer, an architecture for running offline Q-learning with Transformer models, which is based on three main ingredients. First, we describe how we apply discretization and autoregression to enable TD-learning with Transformer architectures. Next, we introduce a particular conservative Q-function regularizer that enables learning from offline datasets. Lastly, we show how Monte Carlo and n-step returns can be used to improve learning efficiency.

4.1   Autoregressive Discrete Q-Learning

Using Transformers with Q-learning presents two challenges: **(1)** we must tokenize the inputs to the Transformer to effectively apply attention mechanisms, which requires discretizing the action space; **(2)** we must perform maximization of Q-values over discretized actions while avoiding the curse of dimensionality. Addressing these issues within the standard Q-learning framework requires new modeling decisions, which we discuss in this section. The intuition behind our autoregressive Q-learning update is to treat each dimension of the action as essentially a separate time step. That way, we can discretize individual dimensions (1D quantities), rather than the entire action space, avoiding the curse of dimensionality. This can be viewed as a simplified version of the scheme proposed by Metz et al. [64], though we apply this to high-capacity transformer models, extend it to the offline RL setting, and scale it up to real-world robotic learning.

Let $\tau = (s_1, a_1, \ldots, s_T, a_T)$ be a trajectory of robotic experience of length T from an offline dataset $\mathcal{D}$. For a given time-step t, and the corresponding action a_t in the trajectory, we define a per-dimension view of the action a_t. Let $a_t^{1:i}$ denote the vector of action dimensions from the first dimension a_t^1 until the i-th dimension a_t^i, where i can range from 1 to the total number of action dimensions, that we denote as $d_{\mathcal{A}}$. Then, for a time window w of state history, we define the Q-value of the action a_t^i in the $i-th$ dimension using an autoregressive Q-function conditioned on states from this time window $s_{t-w:t}$ and previous action dimensions for the current time step $a_t^{1:i-1}$. To train the Q-function, we define a per-dimension Bellman update. For all dimensions $i \in \{1, \ldots, d_{\mathcal{A}}\}$:

$$Q(s_{t-w:t}, a_t^{1:i-1}, a_t^i) \leftarrow \begin{cases} \max_{a_t^{i+1}} Q(s_{t-w:t}, a_t^{1:i}, a_t^{i+1}) & \text{if } i \in \{1, \ldots, d_{\mathcal{A}} - 1\} \\ R(s_t, a_t) + \gamma \max_{a_{t+1}^0} Q(s_{t-w+1:t+1}, a_{t+1}^0) & \text{if } i = d_{\mathcal{A}} \end{cases} \tag{1}$$

The reward is only applied on the last dimension (second line in the equation), as we do not receive any reward before executing the whole action. In addition, we only discount Q-values between the time steps and keep discounting at 1.0 for all but the last dimension within each time step, to ensure the same discounting as in the original MDP. Figure 2 illustrates this process, where each yellow box represents the Q-target computation with additional conservatism and Monte Carlo returns described in the next subsections. It should be noted that by treating each action dimension as a time step for the Bellman update, we do not change the general optimization properties of Q-learning algorithms and the principle of the Bellman optimality still holds for a given MDP as we maximize over an action dimension given the optimality of all action dimensions in the future.

4.2 Conservative Q-Learning with Transformers

Having defined a Bellman backup for running Q-learning with Transformers, we now develop a technique that enables learning from offline data, including human demonstrations and autonomously collected data. This typically requires addressing over-estimation due to distributional shift, when the Q-function for the target value is queried at an action that differs from the one on which it was trained. Conservative Q-learning (CQL) [29] minimizes the Q-function on out-of-distribution actions, which can result in Q-values that are significantly smaller than the minimal possible cumulative reward that can be attained in any trajectory. When dealing with sparse rewards $R \in \{0, 1\}$, results in [27] show that the Q-function regularized with a standard conservative objective can take on negative values, even though instantaneous rewards are all non-negative. This section presents a modified version of conservative Q-learning that addresses this issue in our problem setting.

The key insight behind our design is that, rather than minimizing the Q-values on actions not in the data, we can instead regularize these Q-values to be close to the minimal attainable possible cumulative reward. Concretely, denoting the minimal possible reward on the task as $R_{\min}$, and the time horizon of the task as T, our approach regularizes the Q-values on actions not covered by the dataset towards $R_{\min} \cdot T$, which in our problem setting is equal to 0 (i.e., $R_{\min} = 0$). For simplicity of notation, we omit the action dimension indices in presenting the resulting objective, but remark that the training objective below is applied to Bellman backups on all action dimensions as described in the previous section. Let π_β be the behavioral policy that induced a given dataset $\mathcal{D}$, and let $\tilde{\pi}_\beta(a|s) = \frac{1}{Z(s)} \cdot (1.0 - \pi_\beta(a|s))$ be the distribution over all actions which have a very low density under $\pi_\beta(a|s)$). Our objective to train the Q-function is:

$$J = \frac{1}{2} \underbrace{\mathbb{E}_{s \sim \mathcal{D}, a \sim \pi_\beta(a|s)} \left[\left(Q(s,a) - \mathcal{B}^* Q^k(s,a) \right)^2 \right]}_{(i), \text{ TD error}} + \alpha \cdot \frac{1}{2} \underbrace{\mathbb{E}_{s \sim \mathcal{D}, a \sim \tilde{\pi}_\beta(a|s)} \left[(Q(s,a) - 0)^2 \right]}_{(ii), \text{ conservative regularization } \mathcal{L}_C}, \quad (2)$$

where the first term (i) trains the Q-function by minimizing the temporal difference error objective as defined in Eq. 1, and the second term (ii) regularizes the Q-values to the minimal possible Q-value of 0 in expectation under the distribution of actions induced by $\tilde{\pi}_\beta$, which we denote as a conservative regularization term $\mathcal{L}_C$. Term (ii) is also weighted by a multiplier α, which modulates the strength of this conservative regularization. We discuss the choice of α in our implementation in Appendix B.2 and analyze the behavior of the conservatism term in Appendix A, providing a simple characterization of how this regularizer modifies the learned Q-function in tabular settings.

4.3 Improving Learning Efficiency with Monte Carlo and n-step Returns

When the dataset contains some good trajectories (e.g., demonstrations) and some suboptimal trajectories (e.g., autonomously collected trials), utilizing Monte Carlo return-to-go estimates to accelerate Q-learning can lead to significant performance improvements, as the Monte Carlo estimates along the better trajectories lead to much faster value propagation. This has also been observed in prior work [31]. Based on this observation, we propose a simple improvement to Q-transformer that we found to be quite effective in practice. The Monte Carlo return is defined by the cumulative reward within the offline trajectory τ: $\text{MC}_{t:T} = \sum_{j=t}^{T} \gamma^{j-t} R(s_j, a_j)$. This matches the Q-value of the behavior policy π_β, and since the optimal $Q^*(s,a)$ is larger than the Q-value for any other policy, we have $Q^*(s_t, a_t) \geq \text{MC}_{t:T}$. Since the Monte Carlo return is a lower bound of the optimal Q-function, we can augment the Bellman update to take the maximum between the MC-return and the current Q-value: $\max \left(\text{MC}_{t:T}, Q(s_t, a_t) \right)$, without changing what the Bellman update will converge to.

Task category	# of tasks	Q-T	DT	IQL	RT-1
drawer pick and place	18	64%	49%	11 %	17%
open and close drawer	7	33%	11%	11%	0%
move object near target	47	71%	40%	60%	58%
Average success rate		**56**%	33%	27%	25%

Figure 4: **Left**: Real world manipulation tasks. **Right:** Real world performance comparison. RT-1 [1] is imitation learning on demonstrations. Q-Transformer (Q-T), Decision Transformer (DT) [32], Implicit Q-learning (IQL) [40] learn from both demonstrations and autonomous data.

Although this does not change convergence, including this maximization speeds up learning (see Section 5.3). We present a hypothesis why this occurs. In practice, Q-values for final timesteps (s_T, a_T) are learned first and then propagated backwards in future gradient steps. It can take multiple gradients for the Q-value to propagate all the way to (s_1, a_1). The $\max(\text{MC}, Q)$ allows us to apply useful gradients to $Q(s_1, a_1)$ at the start of training before the Q-values have propagated.

In our experiments, we also notice that additionally employing n-step returns [69, 70] over action dimensions can significantly help with the learning speed. We pick n such that the final Q-value of the last dimension of the next time step is used as the Q-target. This is because we get a new state and reward only after inferring and executing the whole action as opposed to parts of it, meaning that intermediate rewards remain 0 all the way until the last action dimension. While this introduces bias to the Bellman backups, as is always the case with off-policy learning with n-step returns, we find in our ablation study in Section 5.3 that the detrimental effects of this bias are small, while the speedup in training is significant. This is consistent with previously reported results [70].

More details about our Transformer sequence model architecture (depicted in Figure 3) conservative Q-learning implementation, and the robot system can be found in Appendix B.

5 Experiments

In our experiments, we aim to answer the following questions: (1) Can Q-Transformer learn from a combination of demonstrations and sub-optimal data? (2) How does Q-Transformer compare to other methods? (3) How important are design choices made in the method development? (4) Can Q-Transformer be applied to large-scale real world robotic manipulation problems?

5.1 Real-world language-conditioned manipulation evaluation

Training dataset. The offline data used in our experiments was collected with a fleet of 13 robots, and consists of a subset of the demonstration data described by Brohan et al. [1], combined with lower quality autonomously collected data. The demonstrations were collected via human teleoperation for over 700 distinct tasks, each with a separate language description. We use a maximum of 100 demonstrations per task, for a total of about 38,000 demonstrations. All of these demonstrations succeed on their respective tasks and receive a reward of 1.0. The rest of the dataset was collected by running the robots autonomously, executing policies learned via behavioral cloning.

In our experiments, we compare Q-Transformer to imitation learning, and to ensure a fair comparison, we discard all *successful* episodes in the autonomously collected data, to ensure that by including the autonomous data the Q-Transformer does not get to observe more successful trials than the imitation learning baselines. This leaves us with about 20,000 additional autonomously collected *failed* episodes, each with a reward of 0.0, for a total dataset size of about 58,000 episodes. The episodes are on average 35 time steps in length. Examples of the tasks are illustrated in Figure 4.

Performance evaluation. To evaluate how well Q-Transformer can perform when learning from real-world offline datasets while effectively incorporating autonomously collected failed episodes, we evaluate Q-Transformer on three challenging real world robotic manipulation task categories, "drawer pick and place", "open and close drawer", "move object near target", each consisting of 18, 7 and 48 unique tasks instructions respectively to specify different object combinations and drawers. As such, the average success rate in Table 4 is the average over 72 unique manipulation tasks.

Since each task in the training set only has a maximum of 100 demonstrations, we observe from Figure 4 that an imitation learning algorithm like RT-1 [1], which also uses a similar Transformer archi-

texture, struggles to obtain a good performance when learning from only the limited pool of successful robot demonstrations. Existing offline RL methods, such as IQL [40] and a Transformer-based method such as Decision Transformer (DT) [32], can learn from both successful demonstrations and failed episodes, and show better performance compared to RT-1, though by a relatively small margin. Q-Transformer has the highest success rate and outperforms both the behavior cloning baseline (RT-1) and offline RL baselines (Decision Transformer, IQL), exceeding the average performance of the best-performing prior method by about 70%. This demonstrates that Q-Transformer can effectively improve upon human demonstrations using autonomously collected sub-optimal data.

Appendix D also shows that Q-transformer can be successfully applied in combination with a recently proposed language task planner [8] to perform both affordance estimation and robot action execution. Q-transformer outperforms prior methods for planning and executing long-horizon tasks.

5.2 Benchmarking in simulation

In this section, we evaluate Q-Transformer on a challenging simulated offline RL task that require incorporating sub-optimal data in order to solve the task. In particular, we use a visual simulated picking task depicted in Figure 5, where we have a small amount of position controlled human demonstrations (∼8% of the data). The demonstrations are replayed with noise to generate more trajectories (∼92% of the data). Figure 5 shows a comparison to several offline algorithms, such as QT-Opt with CQL [11, 29], IQL [40], AW-Opt [71], and Decision Transformer [32], along with RT-1 using Behavioral Cloning [1] on demonstrations only. As we see, algorithms that can effectively perform TD-learning to combine optimal and sub-optimal data (such as Q-Transformer and QT-Opt) perform better than others. BC with RT-1 is not able to take advantage of sub-optimal

Figure 5: Performance comparison on the simulated picking task.

data. Decision Transformer is trained on both demonstrations and sub-optimal data, but is not able to leverage the noisy data for policy improvement and does not end up performing as well as our method. Although IQL and AW-Opt perform TD-learning, the actor remains too close to the data and can not fully leverage the sub-optimal data. Q-Transformer is able to both bootstrap the policy from demonstrations and also quickly improve through propagating information with TD-learning.

5.3 Ablations

We perform a series of ablations of our method design choices in simulation, with results presented in Figure 6 (left). First, we demonstrate that our choice of conservatism for Q-Transformer performs better than the standard CQL regularizer, which corresponds to a *softmax* layer on top of the Q-function outputs with a cross-entropy loss between the dataset action and the output of this softmax [29]. This regularizer plays a similar role to the one we propose, decreasing the Q-values for out-of-distribution actions and staying closer to the behavior policy.

As we see in Figure 6 (left), performance with softmax conservatism drops to around the fraction of demonstration episodes (∼8%). This suggests collapse conservatism penalty is too good at constraining to the behavior policy distribution. Due to the nature of the softmax, pushing Q-values down for unobserved actions also pushes Q-values up for the observed actions, and we theorize this makes it difficult to keep Q-values low for sub-optimal in-distribution actions that fail to achieve high reward. Next, we show that using conservatism is important. When removing conservatism entirely, we observe that performance collapses. Actions that are rare in the dataset will have overestimated Q-values, since they are not trained by the offline Q-learning procedure. The resulting overestimated values will propagate and collapse the entire Q-function, as described in prior work [38]. Finally, we ablate the Monte-Carlo returns and again observe performance collapse. This demonstrates that adding information about the sampled future returns significantly helps in bootstrapping the training of large architectures such as Transformers.

n-step ablation	n-step	1-step	1-step
# of gradient steps	137480	582960	136920
Training duration (hours)	32	163	40
pick object	94%	97%	92%
move object near target	88%	80%	67%

Large offline dataset	Q-T	DT	RT-1
Average success rate	**88%**	78%	82%

Figure 6: **Left**: Ablations: changing to softmax conservatism decreases performance. Removing MC returns or conservatism completely collapse performance. **Top Right:** The n-step return version of our method reaches similar performance to the standard version with 4 times fewer steps, indicating that the added bias from n-step returns is small compared to the gain in training speed. Using n-step return also leads to better performance on tasks that have longer horizon, e.g. *move object near target* **Bottom Right:** Success rates on real world task categories with larger dataset.

We also ablate the choice of n-step returns from Sec. 4.3 on real robots and observe that using n-step returns lead to significantly faster training speed as measured by number of gradient steps and wall clock time compared to using 1-step returns, with minimal loss in performance (Figure 6 top right).

5.4 Massively scaling up Q-Transformer

The experiments in the previous section used a large dataset that included successful demonstrations and failed autonomous trials, comparable in size to some of the largest prior experiments that utilized demonstration data [72, 15, 58]. We also carry out a preliminary experiment with a much larger dataset to investigate the performance of Q-Transformer as we scale up dataset size.

This experiment includes all of the data collected with 13 robots and comprises of the demonstrations used by RT-1 [1] and successful autonomous episodes, corresponding to about 115,000 successful trials, and an additional 185,000 failed autonomous episodes, for a total dataset size of about 300,000 trials. Model architecture and hyperparameters were kept exactly the same, as the computational cost of the experiment made further hyperparameter tuning prohibitive (in fact, we only train the models once). Note that with this number of successful demonstrations, even standard imitation learning with the RT-1 architecture already performs very well, attaining 82% success rate. However, as shown in Figure 6 (bottom right), Q-Transformer was able to improve even on this very high number. This experiment demonstrates that Q-Transformer can continue to scale to extremely large dataset sizes, and continues to outperform both imitation learning with RT-1 and Decision Transformer.

6 Limitations and Discussion

In this paper, we introduced the Q-Transformer, an architecture for offline reinforcement learning with high-capacity Transformer models that is suitable for large-scale multi-task robotic RL. Our framework does have several limitations. First, we focus on sparse binary reward tasks corresponding to success or failure for each trial. While this setup is reasonable for a broad range of episodic robotic manipulation problems, it is not universal, and we expect that Q-Transformer could be extended to more general settings as well in the future.

Second, the per-dimension action discretization scheme that we employ may become more cumbersome in higher dimensions (e.g., controlling a humanoid robot), as the sequence length and inference time for our model increases with action dimensionality. Although n-step returns mitigate this to a degree, the length of the sequences still increases with action dimensionality. For such higher-dimensional action space, adaptive discretization methods might also be employed, for example by training a discrete autoencoder model and reducing representation dimensionality. Uniform action discretization can also pose problems for manipulation tasks that require a large range of motion granularities, e.g. both coarse and fine movements. In this case, adaptive discretization based on the distribution of actions could be used for representing both types of motions.

Finally, in this work we concentrated on the offline RL setting. Although the Q-Transformer framework should be readily extendable to the online RL setting and fine-tuning with online data collection, it remains a focus of further research.

References

[1] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, J. Dabis, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, J. Hsu, et al. Rt-1: Robotics transformer for real-world control at scale. *arXiv preprint arXiv:2212.06817*, 2022.

[2] Y. Jiang, A. Gupta, Z. Zhang, G. Wang, Y. Dou, Y. Chen, L. Fei-Fei, A. Anandkumar, Y. Zhu, and L. Fan. Vima: General robot manipulation with multimodal prompts. *arXiv preprint arXiv:2210.03094*, 2022.

[3] A. Gupta, L. Fan, S. Ganguli, and L. Fei-Fei. Metamorph: Learning universal controllers with transformers. *arXiv preprint arXiv:2203.11931*, 2022.

[4] M. Shridhar, L. Manuelli, and D. Fox. Perceiver-actor: A multi-task transformer for robotic manipulation. *arXiv preprint arXiv:2209.05451*, 2022.

[5] N. M. M. Shafiullah, Z. J. Cui, A. Altanzaya, and L. Pinto. Behavior transformers: Cloning k modes with one stone. *arXiv preprint arXiv:2206.11251*, 2022.

[6] S. Reed, K. Zolna, E. Parisotto, S. G. Colmenarejo, A. Novikov, G. Barth-Maron, M. Gimenez, Y. Sulsky, J. Kay, J. T. Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

[7] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *Proceedings of the 5th Conference on Robot Learning (CoRL)*, 2021.

[8] M. Ahn, A. Brohan, N. Brown, Y. Chebotar, O. Cortes, B. David, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, et al. Do as I can, not as I say: Grounding language in robotic affordances. *arXiv preprint arXiv:2204.01691*, 2022.

[9] D.-A. Huang, Y.-W. Chao, C. Paxton, X. Deng, L. Fei-Fei, J. C. Niebles, A. Garg, and D. Fox. Motion reasoning for goal-based imitation learning. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 4878–4884. IEEE, 2020.

[10] D. Shah, A. Sridhar, A. Bhorkar, N. Hirose, and S. Levine. Gnm: A general navigation model to drive any robot. *arXiv preprint arXiv:2210.03370*, 2022.

[11] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, et al. Scalable deep reinforcement learning for vision-based robotic manipulation. In *Conference on Robot Learning*, pages 651–673. PMLR, 2018.

[12] A. X. Lee, C. M. Devin, Y. Zhou, T. Lampe, K. Bousmalis, J. T. Springenberg, A. Byravan, A. Abdolmaleki, N. Gileadi, D. Khosid, et al. Beyond pick-and-place: Tackling robotic stacking of diverse shapes. In *5th Annual Conference on Robot Learning*, 2021.

[13] S. Cabi, S. G. Colmenarejo, A. Novikov, K. Konyushkova, S. Reed, R. Jeong, K. Zolna, Y. Aytar, D. Budden, M. Vecerik, et al. Scaling data-driven robotics with reward sketching and batch reinforcement learning. *arXiv preprint arXiv:1909.12200*, 2019.

[14] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. MT-opt: Continuous multi-task robotic reinforcement learning at scale. *arXiv*, 2021.

[15] A. Kumar, A. Singh, F. Ebert, Y. Yang, C. Finn, and S. Levine. Pre-training for robots: Offline rl enables learning new tasks from a handful of trials. *arXiv preprint arXiv:2210.05178*, 2022.

[16] L. P. Kaelbling. Learning to achieve goals. In R. Bajcsy, editor, *IJCAI*, pages 1094–1099. Morgan Kaufmann, 1993. ISBN 1-55860-300-X.

[17] Y. Chebotar, K. Hausman, Y. Lu, T. Xiao, D. Kalashnikov, J. Varley, A. Irpan, B. Eysenbach, R. Julian, C. Finn, et al. Actionable models: Unsupervised offline reinforcement learning of robotic skills. *arXiv preprint arXiv:2104.07749*, 2021.

[18] T. Schaul, D. Horgan, K. Gregor, and D. Silver. Universal value function approximators. In F. Bach and D. Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 1312–1320, Lille, France, 07–09 Jul 2015. PMLR.

[19] M. Andrychowicz, D. Crow, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, pages 5048–5058, 2017.

[20] K. Fang, A. Toshev, L. Fei-Fei, and S. Savarese. Scene memory transformer for embodied agents in long-horizon tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 538–547, 2019.

[21] P. Anderson, A. X. Chang, D. S. Chaplot, A. Dosovitskiy, S. Gupta, V. Koltun, J. Kosecka, J. Malik, R. Mottaghi, M. Savva, and A. R. Zamir. On evaluation of embodied naviga­tion agents. *CoRR*, abs/1807.06757, 2018. URL http://dblp.uni-trier.de/db/journals/corr/corr1807.html#abs-1807-06757.

[22] P. Anderson, Q. Wu, D. Teney, J. Bruce, M. Johnson, N. Sünderhauf, I. D. Reid, S. Gould, and A. van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. *CoRR*, abs/1711.07280, 2017. URL http://arxiv.org/abs/1711.07280.

[23] P. Mirowski, R. Pascanu, F. Viola, H. Soyer, A. J. Ballard, A. Banino, M. Denil, R. Goroshin, L. Sifre, K. Kavukcuoglu, D. Kumaran, and R. Hadsell. Learning to navigate in complex environments. *CoRR*, abs/1611.03673, 2016. URL http://dblp.uni-trier.de/db/journals/corr/corr1611.html#MirowskiPVSBBDG16.

[24] Y. Zhu, R. Mottaghi, E. Kolve, J. J. Lim, A. Gupta, L. Fei-Fei, and A. Farhadi. Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *ICRA*, pages 3357–3364. IEEE, 2017. ISBN 978-1-5090-4633-1. URL http://dblp.uni-trier.de/db/conf/icra/icra2017.html#ZhuMKLGFF17.

[25] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on robot learning*, pages 1094–1100. PMLR, 2020.

[26] J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

[27] A. Kumar, A. Singh, S. Tian, C. Finn, and S. Levine. A workflow for offline model-free robotic reinforcement learning. *arXiv preprint arXiv:2109.10813*, 2021.

[28] R. S. Sutton and A. G. Barto. *Introduction to Reinforcement Learning*. MIT Press, Cambridge, MA, USA, 1st edition, 1998. ISBN 0262193981.

[29] A. Kumar, A. Zhou, G. Tucker, and S. Levine. Conservative q-learning for offline reinforce­ment learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

[30] V. Mnih, K. Kavukcuoglu, D. Silver, A. Graves, I. Antonoglou, D. Wierstra, and M. Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

[31] A. Wilcox, A. Balakrishna, J. Dedieu, W. Benslimane, D. S. Brown, and K. Goldberg. Monte carlo augmented actor-critic for sparse reward deep reinforcement learning from suboptimal demonstrations. In A. H. Oh, A. Agarwal, D. Belgrave, and K. Cho, editors, *Advances in Neu­ral Information Processing Systems*, 2022. URL https://openreview.net/forum?id=FLzTj4ia8BN.

[32] L. Chen, K. Lu, A. Rajeswaran, K. Lee, A. Grover, M. Laskin, P. Abbeel, A. Srinivas, and I. Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

[33] K.-H. Lee, O. Nachum, M. Yang, L. Lee, D. Freeman, W. Xu, S. Guadarrama, I. Fischer, E. Jang, H. Michalewski, et al. Multi-game decision transformers. *arXiv preprint arXiv:2205.15241*, 2022.

[34] N. Jaques, A. Ghandeharioun, J. H. Shen, C. Ferguson, A. Lapedriza, N. Jones, S. Gu, and R. Picard. Way off-policy batch deep reinforcement learning of implicit human preferences in dialog. *arXiv preprint arXiv:1907.00456*, 2019.

[35] Y. Wu, G. Tucker, and O. Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

[36] X. B. Peng, A. Kumar, G. Zhang, and S. Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

[37] N. Y. Siegel, J. T. Springenberg, F. Berkenkamp, A. Abdolmaleki, M. Neunert, T. Lampe, R. Hafner, and M. Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. *arXiv preprint arXiv:2002.08396*, 2020.

[38] A. Kumar, J. Fu, M. Soh, G. Tucker, and S. Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems*, pages 11761–11771, 2019.

[39] I. Kostrikov, J. Tompson, R. Fergus, and O. Nachum. Offline reinforcement learning with fisher divergence critic regularization. *arXiv preprint arXiv:2103.08050*, 2021.

[40] I. Kostrikov, A. Nair, and S. Levine. Offline reinforcement learning with implicit q-learning. *arXiv preprint arXiv:2110.06169*, 2021.

[41] Z. Wang, A. Novikov, K. Żołna, J. T. Springenberg, S. Reed, B. Shahriari, N. Siegel, J. Merel, C. Gulcehre, N. Heess, et al. Critic regularized regression. *arXiv preprint arXiv:2006.15134*, 2020.

[42] S. Fujimoto and S. S. Gu. A minimalist approach to offline reinforcement learning. *arXiv preprint arXiv:2106.06860*, 2021.

[43] X. Chen, Z. Zhou, Z. Wang, C. Wang, Y. Wu, and K. Ross. Bail: Best-action imitation learning for batch deep reinforcement learning, 2019. URL https://arxiv.org/abs/1910.12179.

[44] H. Furuta, Y. Matsuo, and S. S. Gu. Generalized decision transformer for offline hindsight information matching. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=CAjxVodl_v.

[45] Y. Jang, J. Lee, and K.-E. Kim. GPT-critic: Offline reinforcement learning for end-to-end task-oriented dialogue systems. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=qaxhBG1UUaS.

[46] L. Meng, M. Wen, Y. Yang, chenyang le, X. yun Li, H. Zhang, Y. Wen, W. Zhang, J. Wang, and B. XU. Offline pre-trained multi-agent decision transformer, 2022. URL https://openreview.net/forum?id=W08IqLMlMer.

[47] P. Daoudi, M. Barlier, L. D. Santos, and A. Virmaux. Density estimation for conservative q-learning, 2022. URL https://openreview.net/forum?id=liV-Re74fK.

[48] L. Liu, Z. Tang, L. Li, and D. Luo. Robust imitation learning from corrupted demonstrations, 2022. URL https://openreview.net/forum?id=UECzHrGio7i.

[49] A. Mandlekar, D. Xu, J. Wong, S. Nasiriany, C. Wang, R. Kulkarni, F.-F. Li, S. Savarese, Y. Zhu, and R. Martín-Martín. What matters in learning from offline human demonstrations for robot manipulation. In *5th Annual Conference on Robot Learning*, 2021. URL https://openreview.net/forum?id=JrsfBJtDFdI.

[50] A. Kumar, J. Hong, A. Singh, and S. Levine. When should we prefer offline reinforcement learning over behavioral cloning? *arXiv preprint arXiv:2204.05618*, 2022.

[51] A. Singh, A. Kumar, Q. Vuong, Y. Chebotar, and S. Levine. Offline rl with realistic datasets: Heteroskedasticity and support constraints. *arXiv preprint arXiv:2211.01052*, 2022.

[52] Q. Vuong, A. Kumar, S. Levine, and Y. Chebotar. DASCO: Dual-generator adversarial support constrained offline reinforcement learning. In A. H. Oh, A. Agarwal, D. Belgrave, and K. Cho, editors, *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=jBTQGGy9qA-.

[53] J. Li, X. Zhan, H. Xu, X. Zhu, J. Liu, and Y.-Q. Zhang. Distance-sensitive offline reinforcement learning. *arXiv preprint arXiv:2205.11027*, 2022.

[54] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[55] Y. Zhang and J. Chai. Hierarchical task learning from language instructions with unified transformers and self-monitoring. *arXiv preprint arXiv:2106.03427*, 2021.

[56] A. Pashevich, C. Schmid, and C. Sun. Episodic transformer for vision-and-language navigation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 15942–15952, 2021.

[57] A. Silva, N. Moorman, W. Silva, Z. Zaidi, N. Gopalan, and M. Gombolay. Lancon-learn: Learning with language to enable generalization in multi-task manipulation. *IEEE Robotics and Automation Letters*, 7(2):1635–1642, 2021.

[58] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *Conference on Robot Learning*, pages 991–1002. PMLR, 2021.

[59] S. Nair, E. Mitchell, K. Chen, S. Savarese, C. Finn, et al. Learning language-conditioned robot behavior from offline data and crowd-sourced annotation. In *Conference on Robot Learning*, pages 1303–1315. PMLR, 2022.

[60] M. Janner, Q. Li, and S. Levine. Reinforcement learning as one big sequence modeling problem. In *ICML 2021 Workshop on Unsupervised Reinforcement Learning*, 2021.

[61] A. Kumar, X. B. Peng, and S. Levine. Reward-conditioned policies. *arXiv preprint arXiv:1912.13465*, 2019.

[62] R. K. Srivastava, P. Shyam, F. Mutz, W. Jaśkowski, and J. Schmidhuber. Training agents using upside-down reinforcement learning. *arXiv preprint arXiv:1912.02877*, 2019.

[63] D. Brandfonbrener, A. Bietti, J. Buckman, R. Laroche, and J. Bruna. When does return-conditioned supervised learning work for offline reinforcement learning? *arXiv preprint arXiv:2206.01079*, 2022.

[64] L. Metz, J. Ibarz, N. Jaitly, and J. Davidson. Discrete sequential prediction of continuous actions for deep rl. *CoRR*, abs/1705.05035, 2017. URL http://dblp.uni-trier.de/db/journals/corr/corr1705.html#MetzIJD17.

[65] S. Hochreiter and J. Schmidhuber. Long Short-Term Memory. 9(8):1735–1780, 1997.

[66] D. Cer, Y. Yang, S.-y. Kong, N. Hua, N. Limtiaco, R. S. John, N. Constant, M. Guajardo-Cespedes, S. Yuan, C. Tar, et al. Universal sentence encoder. *arXiv preprint arXiv:1803.11175*, 2018.

[67] E. Perez, F. Strub, H. De Vries, V. Dumoulin, and A. Courville. Film: Visual reasoning with a general conditioning layer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[68] M. Tan and Q. Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pages 6105–6114. PMLR, 2019.

[69] R. S. Sutton. Learning to predict by the methods of temporal differences. *Machine learning*, 3 (1):9–44, 1988.

[70] M. Hessel, J. Modayil, H. Van Hasselt, T. Schaul, G. Ostrovski, W. Dabney, D. Horgan, B. Piot, M. Azar, and D. Silver. Rainbow: Combining improvements in deep reinforcement learning. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

[71] Y. Lu, K. Hausman, Y. Chebotar, M. Yan, E. Jang, A. Herzog, T. Xiao, A. Irpan, M. Khansari, D. Kalashnikov, and S. Levine. Aw-opt: Learning robotic skills with imitation andreinforcement at scale. In *5th Annual Conference on Robot Learning*, 2021.

[72] S. Dasari and A. Gupta. Transformers for one-shot visual imitation. In *Conference on Robot Learning*, pages 2071–2084. PMLR, 2021.

[73] T. Xiao, E. Jang, D. Kalashnikov, S. Levine, J. Ibarz, K. Hausman, and A. Herzog. Thinking while moving: Deep reinforcement learning with concurrent control. *arXiv preprint arXiv:2004.06089*, 2020.

[74] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann, P. Schuh, K. Shi, S. Tsvyashchenko, J. Maynez, A. Rao, P. Barnes, Y. Tay, N. Shazeer, V. Prabhakaran, E. Reif, N. Du, B. Hutchinson, R. Pope, J. Bradbury, J. Austin, M. Isard, G. Gur-Ari, P. Yin, T. Duke, A. Levskaya, S. Ghemawat, S. Dev, H. Michalewski, X. Garcia, V. Misra, K. Robinson, L. Fedus, D. Zhou, D. Ippolito, D. Luan, H. Lim, B. Zoph, A. Spiridonov, R. Sepassi, D. Dohan, S. Agrawal, M. Omernick, A. M. Dai, T. S. Pillai, M. Pellat, A. Lewkowycz, E. Moreira, R. Child, O. Polozov, K. Lee, Z. Zhou, X. Wang, B. Saeta, M. Diaz, O. Firat, M. Catasta, J. Wei, K. Meier-Hellstern, D. Eck, J. Dean, S. Petrov, and N. Fiedel. Palm: Scaling language modeling with pathways, 2022. URL https://arxiv.org/abs/2204.02311.