Hallucination-Prone States Beyond Safety Boundaries: Attribution and Mitigation via Attention Information Decoupling

Abstract

Despite their powerful capabilities, *Large Language Models (LLMs)* remain prone to hallucinations deeply rooted in their complex architectures. This work reveals that **hallucinations are closely associated with anomalous distribution patterns in specific attention heads. We observe that hallucination-sensitive heads inherently exhibit a *Safety Boundary* responsible for maintaining stable model outputs during inference, and deviating from these boundaries serves as a precursor to erroneous outputs.** Building on this finding, we propose the *Attention Information Decoupling (AID)* framework, a white-box approach that achieves fine-grained hallucination attribution by decoupling self-attention and mutual attention patterns. Unlike existing hallucination detection methods, AID is training-free, and extensive experiments demonstrate its superior performance across various mainstream attention frameworks. We leverage this attribution framework for further calibration: by calibrating these hallucination-sensitive heads at the token-step level to ensure they consistently remain within their *Safety Boundaries*, our approach effectively mitigates hallucinatory outputs and enhances LLM performance in text generation.

1 Introduction

LLMs have achieved strong performance in knowledge memorization, reasoning, and language generation due to their large parameter scales, leading to success across numerous NLP tasks (Zoph et al., 2022; Brown et al., 2020). However, they still frequently generate hallucinations, including factual errors and logical inconsistencies (Ji et al., 2023). The complex information interactions within Transformers make the underlying causes of hallucinations difficult to interpret and control, limiting the reliability of LLMs.

Code: anonymous.4open.science/r/AID-F700

Recent studies increasingly attempt to interpret hallucinations from the perspective of attention mechanisms. Since attention heads are responsible for contextual dependency modeling and information routing (Olsson et al., 2022; Schlag et al., 2021), many works regard specific attention distribution patterns as hallucination signals and attempt to establish correspondences between certain attention phenomena and hallucination behaviors (Li et al., 2024; Gong et al., 2024).

However, existing studies reveal a contradictory and sometimes confusing perspective on what kinds of attention patterns truly represent hallucinations. For example, some works consider *Attention Sink* as an essential mechanism for maintaining model stability and reasoning capability, while others interpret it as a sign of attention degradation and show that suppressing such patterns can even improve model performance (Darcet et al., 2024; Ran-Milo, 2026; Liu et al., 2026). Similarly, contradictory interpretations also exist regarding the sparsity and dispersion of attention distributions (Qi et al., 2026; Zhang et al., 2025). These contradictions suggest that hallucinations do not correspond to a unified and fixed global attention phenomenon, and relying solely on a single macroscopic metric is insufficient for consistently characterizing complex hallucination mechanisms.

We argue that a key issue lies in the fact that existing studies excessively pursue treating hallucinations as directly tied to single attention phenomena, without considering the nuanced and sometimes contradictory roles that different attention states can play. Moreover, attention matrices encode multiple information dimensions, such as *Self-Information* for token state stability and *Mutual Information* for token dependencies, each of which may affect hallucinations differently. Focusing on only one dimension makes existing conclusions highly model- and architecture-dependent, limiting their generalizability across evolving attention

Figure 1: Overall framework of our method: AID-based hallucination attribution for identifying hallucination-sensitive heads, and token-level dynamic calibration that constrains their attention patterns within safe boundaries to mitigate hallucinations.

mechanisms.

Motivated by these observations, we propose a new perspective on hallucination attribution: **Transformers contain hallucination-sensitive heads that maintain internal attention-distribution *Safety Boundaries* for stable generation behaviors. Deviations from these boundaries make hallucinations significantly more frequent.** Based on this insight, we introduce AID, a framework that analyzes hallucination-sensitive heads from multiple information dimensions. Unlike conventional methods focusing on single attention factors, AID jointly models different attention components to detect hallucination signals more precisely. By constraining sensitive heads within their safe boundaries, AID effectively reduces hallucinations while preserving general language capabilities.

Overall, as shown in Figure 1, this work introduces a unified framework from fine-grained attribution to dynamic intervention, enabling more stable characterization and more interpretable calibration of hallucination mechanisms inside LLMs. Our contributions are summarized as follows:

- We propose a new perspective on hallucinations, suggesting that they are more likely to occur when attention distribution states deviate from *Safety Boundaries*.

- We introduce the AID framework, which jointly models multiple attention information dimensions for fine-grained attribution of hallucination-sensitive heads.

- We verify causal relationships between the hallucination-sensitive heads identified by AID and hallucination behaviors. Constraining these heads within *Safety Boundaries* significantly reduces hallucinations while preserving the general capabilities of LLMs.

2 Preliminary

Attention Information   In autoregressive Transformers, the causal attention is computed as

$$Z^{\ell,h} = Q^{\ell,h}(K^{\ell,h})^\top, \quad A^{\ell,h} = \text{Softmax}\left(\frac{Z^{\ell,h}}{\sqrt{d}}\right),$$

where $A^{\ell,h}$ defines a probability distribution over past tokens under the causal mask constraint.

We adopt a structural view that treats diagonal attention mass as self-information and attention entropy as a proxy for contextual interaction intensity. This formulation is not intended as a strict information-theoretic decomposition, but rather as a functional characterization of different roles within coupled attention distributions.

Task Definition and Safety Boundaries   We define hallucination detection as a binary classification task over attention heads, where a classifier function $f(\cdot)$ indicates hallucination sensitivity:

$$f(A^{\ell,h}) = \begin{cases} 1, & \text{if hallucination is detected} \\ 0, & \text{otherwise} \end{cases}$$

The prediction is determined by comparing the score with a threshold t.

Since different heads may exhibit opposite hallucination tendencies, scores with AUROC below 0.5 are inverted for consistency. We define the *Safety Boundary* as the stable score region determined by threshold t together with its polarity direction. Each attention head therefore possesses a unilateral stable region, and deviations beyond this boundary indicate transitions toward hallucination-prone states. Formally, the safety boundary is defined as:

$$\mathcal{B} = \left\{ f(A^{\ell,h}) \mid \sigma(f(A^{\ell,h}) - t) \le 0 \right\},$$

where t is the classification threshold, and $\sigma \in \{-1, +1\}$ represents the hallucination polarity.

3 Methodology

3.1 Attention Information Decoupling Attribution Framework

To quantify the internal informational uncertainty, we decouple the attention matrix $A^{\ell,h}$ into two projections: *Mutual Information* and *Self-Information*.

Mutual Information The degree of dispersion or sharpness in mutual information reflects the level of focus the model allocates to contextual information. This concept can be quantified through the notion of entropy. For a token i within head $H^{\ell,h}$, the attention matrix $A^{\ell,h}$ records the attention allocation across tokens. We define *Normalized Row Entropy* (RE) to compute the disorder of the attention distribution corresponding to each token:

$$RE_i = -\frac{\sum_{j=1}^{i} A_{i,j}^{\ell,h} \log_2(A_{i,j}^{\ell,h})}{\log_2 i} \quad (1)$$

Where the denominator $\log_2 i$ corresponds to the maximum possible entropy for token i to normalize against sequence length. To isolate the generative portion within a sequence $x = x_p \oplus x_r$ comprising L prompt tokens and T response tokens, we compute the *Attention Entropy* (AE) by averaging the RE over the response index set $R = \{L+1, \ldots, L+T\}$:

$$AE = \frac{1}{T} \sum_{i \in \mathcal{R}} RE_i \quad (2)$$

Self-Information The conceptualization of self-information draws on the definition of *Attention Score* introduced in LLM-Check(Sriramanan et al., 2024). This design is rooted in the spectral analysis of matrices, leveraging eigenvalues and *Singular Value Decomposition* to capture hallucinations by quantifying the information capacity within the feature space:

$$SA = -\sum_{i \in \mathcal{R}} \log_2(A_{i,i}^{\ell,h}) \quad (3)$$

SA reflects the model's degree of reliance on and maintenance of existing generative trends.

The Re-coupled Functional Drawing on contemporary hallucination research, internal model hallucinations can be conceptualized as structural anomalies within the attention graph(Binkowski et al., 2025). By treating the attention matrix as a graph's adjacency matrix, with self-information embedded in node attributes and mutual information mapped to edge weights, we define *Self-Attention Gated Entropy* (SAGE). This metric couples these two information streams to quantify the structural entropy of the attention graph, effectively capturing the structural irregularities induced by hallucinations.

$$SAGE = \frac{1}{T} \sum_{i \in \mathcal{R}} (RE_i \cdot A_{i,i}^{\ell,h}) \quad (4)$$

Within this framework, self-information functions as a gating mechanism that leverages the shifts in hallucination dynamics brought about by the emergence of self-information in sparse attention architectures.

The aforementioned metrics constitute the backbone of our AID framework, maintaining an inherent unity that can be formalized as a coupling function:

$$\mathcal{AID}(A^{\ell,h}) = \mathcal{M}(A^{\ell,h}) \cdot \mathcal{S}(A^{\ell,h}) \quad (5)$$

In this formulation, M and S denote the mutual-information and self-information components within the attention graph. By decoupling and re-coupling these components, AID derives AE, SA, and SAGE as head-level attribution signals for hallucination detection. These metrics are computed for each attention head to evaluate hallucination sensitivity. We then identify hallucination-sensitive heads using a Top-K selection strategy based on attribution performance. Each selected head is further associated with a head-specific *Safety Boundary* determined by its corresponding hallucination classification threshold derived from *Youden Index*.

3.2 Unilateral Safety Boundaries and Dynamic Calibration

To substantiate the causal insights provided by the AID framework, we formalize the stability of hallucination-sensitive heads as a unilateral safety boundary system. Rather than imposing uniform constraints, we identify the functional roles of individual attention heads based on empirical feedback from the preceding AID attribution analysis. To steer the model back to a calibrated state when it deviates, we integrate dynamic calibration parameters τ and Δ into a redefined Softmax operation:

$$\text{Attention}(Z^{\ell,h}) = \text{Softmax}(\frac{Z^{\ell,h} + \Delta \cdot I}{\tau}) \quad (6)$$

Within this formulation, I represents the unit matrix. The scalar τ modulates the degree of dispersion of the mutual information component within the attention distribution, thereby effectively regulating the head entropy. Similarly, the scalar Δ introduces a bias term to the diagonal elements representing self-information.

The dynamic stability of these parameters is governed by their adherence to Unilateral Safety Boundaries, where the relationship between real-time scores and their respective thresholds t defines

the operational Safety Boundary. Specifically, the threshold t acts as a critical frontier: any transgression beyond this boundary triggers compensatory interventions as follows to restore the head to its calibrated state:

$$\tau = 1 - \alpha(s - t) \qquad (7)$$

$$\Delta = \beta \cdot (t - s) \qquad (8)$$

where $s = \mathcal{AID}(A^{\ell,h})$, α and β are scaling coefficients that modulate the intervention strength. By utilizing the AID score as a feedback signal, this protocol achieves fine-grained, step-wise adjustment, thereby suppressing hallucination signals induced by distributional anomalies. We detail the calibration scenarios in Appendix B.6.

4 Probing Attention Phenomena via AID

To verify whether AID can capture internal attention dynamics, we first analyze a classical attention phenomenon known as *Attention Sink*. Low-SAGE reflects both attention concentration and low self-retention, its low-value region is consistent with the attention behaviors observed in Attention Sink. Based on this property, we use AID to conduct a structured analysis of sink-like behaviors.

According to the extension direction of their safety boundaries, SAGE-sensitive heads can be further divided into *positive* and *negative* categories. Negative heads are more likely to induce hallucinations under low-SAGE regimes, while positive heads remain relatively stable under similar patterns. Their layer-wise distributions are shown in Figure 2. We further observe distinct structural patterns across layers. Positive heads are mainly concentrated in the middle layers, while negative heads are more common in early and late layers. This suggests that attention sink may play very different functional roles across layers. In middle layers, attention sink are more related to stable information aggregation and semantic compression, where locally concentrated attention may help maintain semantic consistency rather than directly causing hallucinations. Whereas, similar patterns in early or late layers are more likely to evolve into abnormal routing behaviors.

More importantly, this highlights the flexibility of AID in defining safety boundaries. Unlike traditional methods that assume fixed attention patterns are inherently "safe" or "dangerous," AID does not assign predefined meanings to attention states.

Figure 2: Hallucination-sensitive heads distribution identified by SAGE.

Instead, it captures their relationship with hallucinations through the dynamic extension direction of local safety boundaries. As a result, even under complex, dynamic, or seemingly contradictory attention behaviors, AID can still maintain an objective description of their effects. The function of a given attention pattern may vary across layers, functional regions, and contexts, while AID continuously tracks its correlation with hallucination risk. This local boundary-based formulation makes AID more suitable than global statistical metrics for modeling highly coupled and evolving attention dynamics inside Transformers.

Besides Attention Sink, we further analyze other hallucination-related attention phenomena. Additional results are provided in Appendix A.2.

5 Experimental Results

5.1 Hallucination Attribution

5.1.1 Experimental Setup

Datasets and Detection Task We evaluate the efficacy of the AID through white-box hallucination detection on open-source LLMs. Adopting the experimental setup from LLM-Check, we benchmark our method on FAVA-Annotated (Mishra et al., 2024), RAGTruth (Niu et al., 2024), WikiBio-GPT3-Hallucination (Manakul et al., 2023), and TruthfulQA (Lin et al., 2022).

Evaluation Metrics and Model Selection Using a teacher-forcing paradigm, we formulate hallucination attribution as a white-box detection task to identify hallucination-sensitive heads. We evaluate their diagnostic performance using AUROC, AUPR, and Accuracy. Notably, we include TPR@5%FPR to assess detection robustness under strict false-alarm constraints.

To verify cross-architecture generalization, we benchmark our method on representative open-source LLMs across three attention mechanisms: (i) Multi-Head Attention(Vaswani et al., 2017):

Datasets	FAVA_Annotated				WikiBio-GPT3-Hallucination				RAGTruth			
Methods	AUROC	AUPR	TPR@5%FPR	Acc	AUROC	AUPR	TPR@5%FPR	Acc	AUROC	AUPR	TPR@5%FPR	Acc
Logit-Base												
PPL	53.75 ±2.51	52.40 ±2.17	4.24 ±2.28	58.91 ±1.99	52.14 ±1.46	50.54 ±1.48	4.13 ±1.21	55.29 ±1.13	54.68 ±2.61	54.96 ±2.60	9.54 ±3.05	55.71 ±2.06
WinEnt.	53.12 ±2.32	52.12 ±2.18	5.02 ±2.61	57.49 ±1.93	52.99 ±1.64	50.64 ±1.43	3.77 ±1.09	55.97 ±1.27	52.44 ±1.78	55.32 ±1.72	5.61 ±2.27	54.15 ±1.45
LogitEnt.	54.14 ±2.72	52.79 ±2.46	4.71 ±2.76	57.79 ±2.05	54.18 ±1.73	51.12 ±1.40	4.11 ±1.14	56.53 ±1.23	52.48 ±1.80	50.66 ±1.88	4.22 ±2.66	54.92 ±1.38
LLM-Check												
AttnScore	65.83 ±3.80	65.03 ±4.35	14.43 ±5.50	64.13 ±2.70	55.47 ±1.26	55.18 ±1.46	7.27 ±1.35	55.67 ±1.05	54.39 ±0.78	53.26 ±1.61	6.06 ±1.61	55.37 ±0.70
HiddenScore	58.09 ±0.21	57.79 ±0.60	9.64 ±1.62	58.32 ±0.68	55.02 ±2.05	54.38 ±1.86	5.74 ±1.22	55.75 ±1.21	57.32 ±0.18	54.93 ±1.22	**12.12** ±0.45	56.87 ±0.31
AID (Ours)												
SA	68.09 ±1.00	76.97 ±1.63	13.84 ±4.59	65.32 ±1.08	60.67 ±1.79	79.13 ±1.34	**9.30** ±2.82	58.67 ±1.37	58.75 ±1.16	55.75 ±2.15	8.76 ±3.04	58.06 ±1.07
AE	66.88 ±1.23	75.18 ±1.77	11.48 ±5.13	64.62 ±1.39	**61.92** ±1.39	**79.47** ±0.96	8.63 ±1.36	**59.82** ±1.30	58.41 ±0.60	**56.64** ±1.69	9.49 ±2.40	57.95 ±0.90
SAGE	**70.57** ±1.04	**79.10** ±1.26	**17.06** ±4.22	**67.32** ±1.49	59.65 ±1.89	78.84 ±1.15	9.04 ±2.06	59.65 ±1.89	**58.85** ±1.09	56.37 ±1.87	9.02 ±3.52	**58.84** ±1.19

Table 1: Hallucination detection with LLaMA2-7B-Chat on FAVA-Annotation, RAGTruth, and Wiki-Bio-GPT3-Hallucination. The column-best and second-best means are shown in **bold** and underlined, respectively.

Llama-2-7B-chat, Qwen2-7B, Qwen3-8B; (ii) Grouped-Query Attention(Ainslie et al., 2023): Mistral-7B-Instruct, Llama-3-8B; (iii) Gated Attention(Qiu et al., 2025): Qwen3.5-9B, Qwen3-Next-80B-A3B-Instruct.

Baseline   For baseline comparisons, we consider two categories of methods: logit distribution-based metrics, including *Perplexity*, *Logit Entropy*, and *Window Entropy*; and classical attention-based detectors derived from LLM-Check (Sriramanan et al., 2024), specifically the *Attention Score* and *Hidden Score*.

5.1.2   Results Analysis

To evaluate metric sensitivity to hallucinations, we conduct detection experiments using LLaMA2-7B-Chat across three distinct datasets: FAVA-Annotation, RAGTruth, and Wiki-Bio-GPT3-Hallucination.

As shown in Table 1, our AID framework metrics consistently outperform both output-based baselines and existing attention-based methods. SAGE dominates the small-scale FAVA-Annotated dataset, and AE performs best on WikiBio-GPT3-Hallucination and RAGTruth. This dataset-specific preference reflects natural domain shifts in hallucination distributions, yet the overall superiority of AID demonstrates its robust and generalizable attribution capabilities.

5.1.3   Generalization Analysis

To further validate the generalization capabilities of AID across diverse attention architectures, we conducted extensive comparative experiments on TruthfulQA, utilizing seven distinct models that span three mainstream attention frameworks.

The comprehensive results of our generalization experiments are summarized in 2. Beyond confirming the high detection efficacy of the AID framework across various architectures, we specifically sought to investigate the potential sensitivity of different attention mechanisms to specific hallucination indicators. To this end, we evaluated their detection performance using hallucination scores governed by varying balances of self-information and mutual information. We observe that in dense attention frameworks such as MHA and GQA, hallucination signals are predominantly embedded within mutual information. This suggests that hallucinations under these architectures primarily manifest as the dispersion or sharpness of the model's contextual attention. Conversely, in recent sparse attention frameworks, as more information is routed into the self-attention component, hallucination signals are largely encapsulated by self-information.

5.2   Attribution Verification

The attribution experiments conducted in Section 5.1 yield the following insights: **The manifestation of hallucinations in LLMs is consistently associated with anomalous attention distributions within hallucination-sensitive heads.** Furthermore, such anomalies can be explicitly manifested through the attention patterns, rendering them effectively detectable by AID.

To empirically validate the causal role of internal attention distributions in the generation of hallucinations, building on our attribution method, we design the following intervention experiments.

Methods	Metrics	MHA			GQA		GA	
		Llama2 7B	Qwen2 7B	Qwen3 8B	Llama3 8B	Mistral 7B	Qwen3.5 9B	Qwen3-Next 80B
Logit-Base								
PPL	AUROC	50.77 ± 0.58	60.21 ± 0.93	50.75 ± 0.57	58.45 ± 0.93	51.53 ± 0.87	50.75 ± 0.56	53.48 ± 0.94
	AUPR	50.74 ± 0.68	60.51 ± 0.99	51.17 ± 0.61	58.03 ± 0.97	52.11 ± 0.90	50.41 ± 0.81	52.69 ± 0.86
	TPR@5%FPR	5.84 ± 0.69	**12.44** ± 1.31	6.18 ± 0.80	9.85 ± 1.10	6.36 ± 0.93	5.18 ± 1.06	6.00 ± 0.86
	Acc	52.67 ± 0.56	57.89 ± 0.71	51.81 ± 0.50	56.81 ± 0.77	52.44 ± 0.65	51.83 ± 0.46	53.42 ± 0.73
WinEnt.	AUROC	51.80 ± 0.88	53.09 ± 0.94	50.82 ± 0.61	52.31 ± 0.94	51.14 ± 0.77	51.95 ± 0.91	55.23 ± 0.95
	AUPR	52.15 ± 0.88	53.24 ± 0.89	50.80 ± 0.92	52.77 ± 0.90	50.22 ± 0.64	50.98 ± 0.79	52.61 ± 0.83
	TPR@5%FPR	7.04 ± 0.85	7.49 ± 0.89	5.57 ± 1.18	6.71 ± 0.81	3.72 ± 1.06	5.33 ± 0.80	4.78 ± 0.80
	Acc	52.35 ± 0.55	53.57 ± 0.76	52.05 ± 0.54	52.58 ± 0.66	52.30 ± 0.61	52.57 ± 0.59	56.14 ± 0.79
LogitEnt.	AUROC	52.11 ± 0.91	54.85 ± 0.93	50.77 ± 0.57	54.06 ± 0.95	51.00 ± 0.71	53.07 ± 0.93	54.81 ± 0.95
	AUPR	52.17 ± 0.88	54.18 ± 0.91	50.51 ± 0.83	54.01 ± 0.93	50.79 ± 0.81	51.65 ± 0.82	52.43 ± 0.84
	TPR@5%FPR	7.03 ± 0.87	7.71 ± 0.87	4.97 ± 0.96	7.19 ± 1.01	5.69 ± 1.06	5.57 ± 0.76	4.62 ± 0.75
	Acc	52.65 ± 0.60	54.73 ± 0.77	52.13 ± 0.57	53.82 ± 0.73	51.79 ± 0.47	53.38 ± 0.63	55.74 ± 0.78
LLM-Check								
AttnScore	AUROC	53.02 ± 0.42	51.64 ± 0.45	53.60 ± 0.82	55.31 ± 1.24	54.15 ± 0.41	54.77 ± 0.56	55.48 ± 0.27
	AUPR	52.37 ± 0.57	52.72 ± 0.45	53.38 ± 0.63	54.21 ± 0.83	53.72 ± 0.44	53.62 ± 0.63	53.86 ± 0.33
	TPR@5%FPR	5.66 ± 0.98	7.10 ± 0.71	6.66 ± 0.75	6.90 ± 1.04	6.92 ± 0.77	6.59 ± 0.17	6.08 ± 0.33
	Acc	53.04 ± 0.52	52.31 ± 0.38	53.61 ± 0.66	54.66 ± 1.05	53.66 ± 0.34	54.31 ± 0.56	54.93 ± 0.26
HiddenScore	AUROC	53.57 ± 1.81	56.67 ± 1.87	57.84 ± 1.20	61.17 ± 0.60	53.34 ± 1.79	57.82 ± 0.32	56.78 ± 0.80
	AUPR	53.58 ± 1.35	56.03 ± 1.49	56.95 ± 1.27	60.04 ± 0.66	53.38 ± 1.38	57.05 ± 0.43	56.56 ± 0.59
	TPR@5%FPR	6.68 ± 0.53	8.46 ± 0.83	9.06 ± 0.74	10.11 ± 1.11	6.74 ± 0.89	8.62 ± 0.72	8.75 ± 0.48
	Acc	53.07 ± 1.25	55.20 ± 1.55	56.58 ± 0.92	59.32 ± 0.98	52.95 ± 1.36	56.83 ± 0.16	55.49 ± 0.68
AID (Ours)								
SA	AUROC	59.69 ± 1.92	61.61 ± 1.62	62.58 ± 1.57	62.63 ± 1.50	62.80 ± 1.42	**59.98** ± 2.20	61.32 ± 2.22
	AUPR	60.52 ± 1.89	62.17 ± 1.56	62.67 ± 1.43	62.43 ± 1.69	63.15 ± 1.41	**60.84** ± 1.94	**62.16** ± 1.98
	TPR@5%FPR	8.51 ± 1.80	9.39 ± 2.01	**9.43** ± 1.56	9.14 ± 2.14	**10.21** ± 1.63	**8.84** ± 1.80	**9.65** ± 2.10
	Acc	57.77 ± 1.48	59.12 ± 1.43	59.93 ± 1.27	60.05 ± 1.19	59.80 ± 1.16	57.91 ± 1.61	**58.72** ± 1.70
AE	AUROC	**62.32** ± 1.97	**62.79** ± 1.74	**63.24** ± 1.27	**64.40** ± 1.80	**64.09** ± 2.02	58.61 ± 1.54	59.73 ± 1.77
	AUPR	**62.07** ± 1.73	**62.63** ± 1.81	**62.73** ± 1.69	**64.03** ± 2.16	63.69 ± 2.23	59.53 ± 1.72	60.58 ± 1.79
	TPR@5%FPR	**8.56** ± 1.76	9.62 ± 1.89	9.10 ± 2.04	**10.15** ± 2.62	9.90 ± 2.99	7.82 ± 1.53	8.62 ± 1.88
	Acc	**59.84** ± 1.49	**60.80** ± 1.37	**60.36** ± 0.99	**61.44** ± 1.61	**60.95** ± 1.83	57.02 ± 1.22	57.62 ± 1.38
SAGE	AUROC	57.99 ± 1.65	60.61 ± 1.25	62.56 ± 2.05	63.82 ± 2.02	62.83 ± 1.92	59.95 ± 2.35	**61.35** ± 1.83
	AUPR	58.79 ± 1.44	61.29 ± 1.41	62.38 ± 1.97	63.36 ± 1.83	63.11 ± 2.04	60.72 ± 2.18	62.01 ± 2.08
	TPR@5%FPR	7.36 ± 1.14	8.90 ± 1.93	9.01 ± 2.41	9.54 ± 2.24	10.03 ± 2.48	8.77 ± 2.09	9.54 ± 2.31
	Acc	56.58 ± 1.26	58.42 ± 0.96	59.96 ± 1.71	60.99 ± 1.68	60.07 ± 1.48	**57.92** ± 1.71	58.70 ± 1.32

Table 2: Cross-architecture generalization on TruthfulQA using seven backbones spanning dense **MHA**, **GQA**, and sparse grouped-attention **GA**. The column-best and second-best means are shown in **bold** and underlined, respectively. Values are mean ± std. (%).

5.2.1 Dynamic Attention Calibration

We introduce two parameters to regulate attention distribution, specifically modulating the information flow between mutual and self-information. During attribution, each hallucination-sensitive head is assigned a safety boundary, which serves as its hallucination-triggering threshold.

Specifically, we first register the top-k hallucination-sensitive heads as intervention heads. During autoregressive decoding, a token-level monitoring mechanism is deployed to track their real-time AID scores. Once a head crosses its safe boundary, dynamic calibration is applied to restore the attention state back toward its stable operating region. Table 3 compares the optimally calibrated models with the original baselines across three base models with different attention architectures under four evaluation frameworks on the TruthfulQA generation subset. The reported Diff score measures the generation preference between incorrect and correct answer subsets, where positive values indicate a stronger preference toward correct answers. In the In-domain setting, sensitive heads are extracted from the same TruthfulQA subset, while the RAGTruth and WikiBio settings directly transfer sensitive heads identified from their respective datasets to evaluate cross-domain generalization.

Results demonstrate that by constraining the attention distribution patterns of these sensitive heads within safety boundaries, dynamic attention calibration maintains steady in-domain improvements while achieving comparable or even more pronounced performance gains in cross-domain tasks. Specifically, compared to the baseline, the calibrated models exhibit a stronger preference for correct answers when contrasting responses

(a) Calibration results   (b) Hyperparameter sensitivity analysis

Figure 3: (a) Performance under increasing intervention heads; shaded regions denote standard deviation. Red: dynamic calibration on AID-selected heads. Blue: random masking on random heads. Green: baseline.

Method	Bleu	Rouge1	Rouge2	RougeL
Llama-2-7B-chat				
Baseline	-1.64	-1.71	-2.96	-2.02
In-domain	$-0.24^{\uparrow 1.40}$	$0.13^{\uparrow 1.84}$	$-0.95^{\uparrow 2.01}$	$-0.28^{\uparrow 1.74}$
RAGTruth	$-1.71^{\downarrow 0.07}$	$-1.78^{\downarrow 0.08}$	$-3.04^{\downarrow 0.08}$	$-2.03^{\downarrow 0.01}$
WiKiBio	$-1.15^{\uparrow 0.49}$	$-1.20^{\uparrow 0.51}$	$-2.40^{\uparrow 0.56}$	$-1.35^{\uparrow 0.67}$
Mistral-7B-Instruct				
Baseline	3.66	5.53	4.44	4.97
In-domain	$4.62^{\uparrow 0.96}$	$7.01^{\uparrow 1.47}$	$5.96^{\uparrow 1.51}$	$6.48^{\uparrow 1.51}$
RAGTruth	$3.90^{\uparrow 0.24}$	$5.94^{\uparrow 0.41}$	$4.91^{\uparrow 0.47}$	$5.47^{\uparrow 0.50}$
WiKiBio	$5.74^{\uparrow 2.08}$	$8.20^{\uparrow 2.66}$	$7.25^{\uparrow 2.81}$	$7.83^{\uparrow 2.86}$
Qwen3.5-9B				
Baseline	3.10	3.82	2.88	3.64
In-domain	$3.46^{\uparrow 0.36}$	$4.01^{\uparrow 0.19}$	$3.23^{\uparrow 0.35}$	$3.90^{\uparrow 0.26}$
RAGTruth	$4.19^{\uparrow 1.09}$	$5.16^{\uparrow 1.34}$	$4.22^{\uparrow 1.34}$	$4.91^{\uparrow 1.27}$
WiKiBio	$3.17^{\uparrow 0.07}$	$3.92^{\uparrow 0.10}$	$3.04^{\uparrow 0.17}$	$3.76^{\uparrow 0.12}$

Table 3: TruthfulQA generation (Diff): baseline vs. dynamic calibration. Blue ↑ / red ↓ superscripts denote change relative to baseline.

generated for the incorrect and correct answer subsets. These findings further suggest that the hallucination-sensitive heads identified by AID possess strong generalization capability and remain effective even under cross-domain transfer settings.

5.2.2 Impact of the Count of Heads

Furthermore, we investigate the impact of the intervention quantity of hallucination-sensitive heads on model performance by selecting three base models from distinct attention mechanisms. We apply our calibration strategy to the hallucination-sensitive heads that obtain the highest AUROC scores during the attribution stage, while applying a random masking strategy to the irrelevant

heads with the lowest AUROC scores. The resulting performance curves comparing in-domain and cross-domain evaluations are shown in Figure 3a. It presents the performance of LLMs across three distinct attribution benchmarks. All evaluations are conducted on the TruthfulQA generative task. The first column displays the in-domain performance, while the subsequent columns report their cross-domain generalization. The horizontal axis denotes the number of intervened heads, and the vertical axis denotes the evaluation metrics based on BLEU and ROUGE 1, 2, and L accuracies.

By dynamically calibrating hallucination-sensitive heads at the token-step level, we observe substantial performance gains in both Llama2 and Mistral. Notably, this enhancement exhibits slight fluctuations in Llama but manifests much more significantly in Mistral. Within the sparse GA architecture, these sensitive heads preserve distinct functional characteristics compared to the randomly masked irrelevant heads. Even when intervening on 80 heads (about 62.5% of all heads), the models consistently exhibit robust or even significantly improved performance, with negligible instances of performance degradation.

Additionally, we also observe occasional sharp performance gains when randomly masking irrelevant heads in dense architectures such as Llama and Mistral. This phenomenon likely stems from noisy or redundant attention heads, where zero masking acts similarly to a coarse-grained dropout mechanism. Prior studies on Llama report similar be-

havior (Li et al., 2021). Interestingly, for Llama, directly zero-masking hallucination-sensitive heads sometimes yields even larger improvements than the softer calibration strategy. Further analysis is provided in Appendix A.3.

5.2.3 Hyperparameter Sensitivity Analysis

To evaluate the robustness of the calibration strategy, we analyze the sensitivity of the two scaling coefficients α and β. We progressively vary β under different fixed α settings to examine the interaction between self-information regulation and mutual-information stabilization.

As shown in Figure 3b, our calibration strategy maintains stable performance improvements across a broad parameter range, indicating that the method does not rely on delicate hyperparameter tuning. As β increases, performance generally improves before reaching a relatively stable plateau, suggesting that moderate self-information enhancement effectively mitigates hallucination-related abnormal attention states. Meanwhile, the overall differences among different α curves remain relatively limited, implying that self-information stabilization may play a more direct role than global entropy modulation in the current framework.

We further observe that overly strong calibration can slightly degrade performance, suggesting that hallucination mitigation is not equivalent to maximizing attention stabilization, as over-interventions may reduce normal generative flexibility.

6 Related Work

LLM Hallucination Attribution and Detection Hallucination detection and attribution have become a central topic for improving the reliability of LLMs. Early approaches mainly rely on output-space uncertainty estimation, such as logit-based confidence, entropy, and sampling consistency (Qi et al., 2026; Fang et al., 2025).

Representative methods include Detect-GPT (Mitchell et al., 2023), which identifies hallucinated regions by analyzing probability curvature, and SelfCheckGPT (Manakul et al., 2023), which measures consistency across multiple generations. Benchmark-driven studies such as RAGTruth (Niu et al., 2024) and taxonomy-based analyses like FAVA (Mishra et al., 2024) further standardize hallucination evaluation.

Beyond output-level signals, recent work explores internal representations. ROME (Meng et al., 2022) and MEMIT (Meng et al., 2023) suggest

that factual knowledge can be localized within Transformer parameters, while Tuned Lens (Belrose et al., 2025) and TraceDet (Chang et al., 2025) analyze intermediate hidden states and decoding trajectories to study generation dynamics.

However, these methods largely focus on output uncertainty or isolated internal features, while overlooking the role of attention dynamics and information coupling during generation.

Hallucination Interpretation via Attention Phenomena Recent studies investigate hallucinations through attention mechanisms. Attention Sink (Liu et al., 2026; Zhang et al., 2026) and Induction Heads (Olsson et al., 2022) reveal structured attention behaviors that support stable generation and in-context learning. In contrast, SinkProb (Binkowski et al., 2026) and Attention Entropy based studies (Qi et al., 2026; Zhang et al., 2025) show that abnormal attention concentration or dispersion can correlate with hallucination risks. However, these findings are often inconsistent across settings, suggesting that fixed attention patterns alone are insufficient to characterize hallucination behavior.

Other work such as LLM-Check (Sriramanan et al., 2024) and LapEigVal (Binkowski et al., 2025) characterize hallucination-related instability through spectral statistics or graph structures of internal states. However, they mainly rely on globally aggregated representations and provide limited fine-grained attribution for local attention dynamics.

7 Conclusion

This work presents a new perspective on hallucination attribution and mitigation in LLMs. We show that hallucinations are closely related to abnormal activation of hallucination-sensitive parameters, which can be effectively captured through attention distribution patterns. Based on this insight, we propose AID, a framework that identifies and attributes hallucinations by analyzing internal attention states, and further introduce a token-level constraint mechanism that restricts hallucination-sensitive heads within safe boundaries, effectively reducing hallucination in generation. Experiments show that AID enables fine-grained hallucination attribution, achieves consistent improvements, and generalizes well across settings.

Limitations

The current dynamic calibration strategy relies on head-specific thresholds derived from supervised hallucination attribution benchmarks. Although these safety boundaries exhibit encouraging cross-domain transferability, their optimal configurations may still vary across model families, decoding strategies, and generation tasks. Future work may explore adaptive or self-evolving safety boundaries that can generalize more robustly under distribution shifts.

In addition, our observations in Appendix A.4 suggest that attention calibration reshapes semantic exploration dynamics by suppressing weakly grounded associative continuations. Although this behavior effectively mitigates hallucinations in many cases, excessive stabilization may potentially reduce certain forms of open-ended creativity or imaginative generation. Encouragingly, our experiments indicate that surface-level lexical diversity is largely preserved under calibration, suggesting that the intervention mainly affects speculative semantic branching rather than general language generation ability.

References

Joshua Ainslie, James Lee-Thorp, Michiel de Jong, Yury Zemlyanskiy, Federico Lebron, and Sumit Sanghai. 2023. GQA: Training generalized multi-query transformer models from multi-head checkpoints. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4895–4901.

Nora Belrose, Igor Ostrovsky, Lev McKinney, Zach Furman, Logan Smith, Danny Halawi, Stella Biderman, and Jacob Steinhardt. 2025. Eliciting latent predictions from transformers with the tuned lens. *Preprint*, arXiv:2303.08112.

Jakub Binkowski, Kamil Adamczewski, and Tomasz Kajdanowicz. 2026. Attention sinks as internal signals for hallucination detection in large language models. *Preprint*, arXiv:2604.10697.

Jakub Binkowski, Denis Janiak, Albert Sawczyn, Bogdan Gabrys, and Tomasz Jan Kajdanowicz. 2025. Hallucination detection in LLMs using spectral features of attention maps. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 24354–24385.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.

Shenxu Chang, Junchi Yu, Weixing Wang, Yongqiang Chen, Jialin Yu, Philip Torr, and Jindong Gu. 2025. Tracedet: Hallucination detection from the decoding trace of diffusion large language models. *Preprint*, arXiv:2510.01274.

Timothée Darcet, Maxime Oquab, Julien Mairal, and Piotr Bojanowski. 2024. Vision transformers need registers. In *International Conference on Learning Representations*, volume 2024, pages 2632–2652.

Lizhe Fang, Yifei Wang, Zhaoyang Liu, Chenheng Zhang, Stefanie Jegelka, Jinyang Gao, Bolin Ding, and Yisen Wang. 2025. What is wrong with perplexity for long-context language modeling? In *International Conference on Learning Representations*, volume 2025, pages 94541–94563.

Xuan Gong, Tianshi Ming, Xinpeng Wang, and Zhihua Wei. 2024. DAMRO: Dive into the attention mechanism of LVLM to reduce object hallucination. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 7696–7712, Miami, Florida, USA. Association for Computational Linguistics.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM computing surveys*, 55(12):1–38.

He Li, Haoang Chi, Mingyu Liu, and Wenjing Yang. 2024. Look within, why llms hallucinate: A causal perspective. *Preprint*, arXiv:2407.10153.

Jiaoda Li, Ryan Cotterell, and Mrinmaya Sachan. 2021. Differentiable subset pruning of transformer heads. *Transactions of the Association for Computational Linguistics*, 9:1442–1459.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. TruthfulQA: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.

Xu Liu, Guikun Chen, and Wenguan Wang. 2026. Sinktrack: Attention sink based context anchoring for large language models. *Preprint*, arXiv:2604.10027.

Potsawee Manakul, Adian Liusie, and Mark Gales. 2023. Selfcheckgpt: Zero-resource black-box hallucination detection for generative large language models. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pages 9004–9017.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in gpt. *Advances in neural information processing systems*, 35:17359–17372.

Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. 2023. Mass-editing memory in a transformer. *Preprint*, arXiv:2210.07229.

Paul Michel, Omer Levy, and Graham Neubig. 2019. Are sixteen heads really better than one? *Preprint*, arXiv:1905.10650.

Abhika Mishra, Akari Asai, Vidhisha Balachandran, Yizhong Wang, Graham Neubig, Yulia Tsvetkov, and Hannaneh Hajishirzi. 2024. Fine-grained hallucination detection and editing for language models. *Preprint*, arXiv:2401.06855.

Eric Mitchell, Yoonho Lee, Alexander Khazatsky, Christopher D Manning, and Chelsea Finn. 2023. DetectGPT: Zero-shot machine-generated text detection using probability curvature. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 24950–24962. PMLR.

Cheng Niu, Yuanhao Wu, Juno Zhu, Siliang Xu, KaShun Shum, Randy Zhong, Juntong Song, and Tong Zhang. 2024. Ragtruth: A hallucination corpus for developing trustworthy retrieval-augmented language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10862–10878.

Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Scott Johnston, Andy Jones, Jackson Kernion, Liane Lovitt, and 7 others. 2022. In-context learning and induction heads. *Preprint*, arXiv:2209.11895.

Siya Qi, Yudong Chen, Runcong Zhao, Qinglin Zhu, Zhanghao Hu, Wei Liu, Yulan He, Zheng Yuan, and Lin Gui. 2026. Detecting contextual hallucinations in llms with frequency-aware attention. *Preprint*, arXiv:2602.18145.

Zihan Qiu, Zekun Wang, Bo Zheng, Zeyu Huang, Kaiyue Wen, Songlin Yang, Rui Men, Le Yu, Fei Huang, Suozhi Huang, Dayiheng Liu, Jingren Zhou, and Junyang Lin. 2025. Gated attention for large language models: Non-linearity, sparsity, and attention-sink-free. In *Advances in Neural Information Processing Systems*, volume 38, pages 100092–100118. Curran Associates, Inc.

Yuval Ran-Milo. 2026. Attention sinks are provably necessary in softmax transformers: Evidence from trigger-conditional tasks. *Preprint*, arXiv:2603.11487.

Imanol Schlag, Kazuki Irie, and Jürgen Schmidhuber. 2021. Linear transformers are secretly fast weight programmers. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 9355–9366. PMLR.

Gaurang Sriramanan, Siddhant Bharti, Vinu Sankar Sadasivan, Shoumik Saha, Priyatham Kattakinda, and Soheil Feizi. 2024. Llm-check: investigating detection of hallucinations in large language models. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.

Stephen Zhang, Mustafa Khan, and Vardan Papyan. 2026. Attention sinks: A'catch, tag, release'mechanism for embeddings. *Advances in Neural Information Processing Systems*, 38:83140–83181.

Zhisong Zhang, Yan Wang, Xinting Huang, Tianqing Fang, Hongming Zhang, Chenlong Deng, Shuaiyi Li, and Dong Yu. 2025. Attention entropy is a key factor: An analysis of parallel context encoding with full-attention-based pre-trained language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9840–9855. Association for Computational Linguistics.

Barret Zoph, Colin Raffel, Dale Schuurmans, Dani Yogatama, Denny Zhou, Don Metzler, Ed H. Chi, Jason Wei, Jeff Dean, Liam B. Fedus, Maarten Paul Bosma, Oriol Vinyals, Percy Liang, Sebastian Borgeaud, Tatsunori B. Hashimoto, and Yi Tay. 2022. Emergent abilities of large language models. *TMLR*.

A Supplementary Experimental Results

A.1 Attribution Evaluations

We supplement the experimental results of the attribution stage as follows. Tables 4, 5 detail the hallucination detection performance of our AID method across seven distinct model architectures on three benchmark datasets: WikiBio-GPT3-Hallucination and RAGTruth.

The extended empirical evidence underscores that AID achieves superior performance consistently across multiple cross-domain datasets. Crucially, it corroborates our findings from Section 5.1: within the MHA and GQA frameworks, hallucination signals primarily reside within mutual information. These signals visually manifest through the dispersion and sharpening patterns in attention distributions, enabling AID to capture them effectively.

Table 4: Cross-architecture hallucination detection on **Wiki-Bio-GPT3-Hallucination** using seven backbones (**MHA**, **GQA**, **GA**). The column-best and second-best means are shown in **bold** and underlined, respectively. Values are mean ± std. (%).

Methods	Metrics	MHA			GQA		GA	
		Llama2 7B	Qwen2 7B	Qwen3 8B	Llama3 8B	Mistral 7B	Qwen3.5 9B	Qwen3-Next 80B
						Logit-Base		
PPL	AUROC	52.14 ±1.46	53.45 ±1.74	53.60 ±1.70	56.19 ±1.80	53.97 ±1.73	51.63 ±1.22	51.87 ±1.35
	AUPR	50.54 ±1.48	51.20 ±1.51	51.17 ±1.41	52.60 ±1.53	51.42 ±1.47	49.74 ±1.19	50.24 ±1.43
	TPR@5%FPR	4.13 ±1.21	4.08 ±1.28	4.18 ±1.20	4.89 ±1.32	3.99 ±1.21	3.20 ±1.44	3.34 ±1.22
	Acc	55.29 ±1.13	55.85 ±1.24	55.07 ±1.20	58.66 ±1.28	55.88 ±1.17	53.92 ±0.96	54.76 ±1.07
WinEnt.	AUROC	52.99 ±1.64	52.35 ±1.53	53.87 ±1.74	58.38 ±1.75	56.64 ±1.73	53.63 ±1.77	**60.46** ±1.74
	AUPR	50.64 ±1.43	50.89 ±1.56	51.69 ±1.52	54.87 ±1.57	54.95 ±1.63	51.64 ±1.56	56.22 ±1.63
	TPR@5%FPR	3.77 ±1.09	4.60 ±1.84	3.79 ±1.36	4.62 ±1.11	6.74 ±1.46	4.78 ±1.27	4.69 ±1.68
	Acc	55.97 ±1.27	54.61 ±1.06	55.56 ±1.10	58.46 ±1.27	56.67 ±1.21	55.22 ±1.04	60.05 ±1.39
LogitEnt.	AUROC	54.18 ±1.73	52.42 ±1.54	53.78 ±1.73	58.57 ±1.74	57.64 ±1.72	53.81 ±1.77	59.99 ±1.75
	AUPR	51.12 ±1.40	50.34 ±1.45	51.14 ±1.46	54.46 ±1.54	54.79 ±1.60	51.16 ±1.48	55.65 ±1.60
	TPR@5%FPR	4.11 ±1.14	3.30 ±1.31	3.00 ±1.17	5.30 ±1.56	5.35 ±1.33	3.52 ±1.14	4.44 ±1.41
	Acc	56.53 ±1.23	55.08 ±1.18	55.48 ±1.08	59.02 ±1.23	57.25 ±1.20	55.38 ±1.10	59.68 ±1.38
						LLM-Check		
Attnscore	AUROC	55.47 ±1.26	56.72 ±0.96	56.56 ±1.25	60.45 ±3.99	56.99 ±0.59	56.49 ±0.85	57.56 ±1.98
	AUPR	55.18 ±1.46	55.97 ±1.29	55.16 ±1.43	60.81 ±4.81	55.99 ±1.12	55.60 ±0.61	56.72 ±2.01
	TPR@5%FPR	7.27 ±1.35	7.34 ±2.23	6.16 ±1.14	**11.74** ±5.16	8.29 ±1.75	9.11 ±1.14	7.88 ±2.56
	Acc	55.67 ±1.05	56.36 ±0.78	56.25 ±0.88	58.98 ±3.23	56.38 ±0.51	56.10 ±0.69	58.90 ±1.29
HiddenScore	AUROC	55.02 ±2.05	56.13 ±2.17	58.41 ±1.22	55.89 ±3.28	55.38 ±3.09	**61.77** ±0.80	58.25 ±2.65
	AUPR	54.38 ±1.86	55.14 ±1.90	57.53 ±0.61	56.36 ±2.09	54.81 ±2.21	60.99 ±0.58	56.94 ±2.61
	TPR@5%FPR	5.74 ±1.22	6.43 ±1.93	8.28 ±0.91	9.11 ±1.39	7.03 ±1.93	**9.82** ±0.80	7.42 ±2.02
	Acc	55.75 ±1.21	56.53 ±1.28	58.03 ±0.64	56.30 ±2.34	56.04 ±2.17	60.59 ±0.30	57.70 ±1.93
						AID (Ours)		
SA	AUROC	60.67 ±1.82	60.41 ±1.33	60.65 ±1.01	64.25 ±1.93	61.72 ±1.44	56.93 ±1.15	59.10 ±2.38
	AUPR	79.13 ±1.36	79.08 ±0.86	**79.32** ±0.78	80.92 ±1.29	79.82 ±1.12	**77.46** ±1.12	78.06 ±1.97
	TPR@5%FPR	**9.30** ±2.87	8.75 ±1.52	**9.39** ±1.32	10.19 ±2.25	9.63 ±2.08	8.32 ±2.07	8.13 ±3.89
	Acc	71.41 ±1.03	71.31 ±1.09	71.30 ±0.79	73.18 ±1.17	71.86 ±0.82	70.03 ±1.12	**71.07** ±0.91
AE	AUROC	**61.92** ±1.42	**61.03** ±1.82	**60.73** ±1.37	**64.78** ±2.26	**64.53** ±2.67	57.79 ±1.55	58.20 ±1.54
	AUPR	79.47 ±0.98	79.42 ±1.29	79.28 ±1.10	**81.24** ±1.53	**81.06** ±1.52	77.02 ±1.26	77.64 ±1.15
	TPR@5%FPR	8.63 ±1.38	**9.45** ±2.64	8.90 ±2.19	10.87 ±3.10	**10.74** ±2.82	6.72 ±2.13	7.81 ±2.06
	Acc	**72.58** ±1.33	71.43 ±1.47	**71.58** ±0.95	**73.47** ±1.36	**73.02** ±1.44	**70.60** ±1.03	70.74 ±0.84
SAGE	AUROC	59.65 ±1.92	60.39 ±1.50	60.08 ±0.81	64.47 ±1.90	62.26 ±1.63	56.49 ±1.65	58.54 ±1.86
	AUPR	78.84 ±1.17	79.28 ±1.06	79.05 ±0.92	81.14 ±1.18	80.32 ±1.38	77.02 ±1.33	**78.14** ±1.50
	TPR@5%FPR	9.04 ±2.09	9.28 ±1.75	9.10 ±1.67	10.59 ±2.52	10.51 ±2.85	7.74 ±2.34	8.96 ±2.70
	Acc	70.35 ±1.42	71.06 ±1.08	71.35 ±1.01	73.15 ±1.31	71.90 ±1.06	70.02 ±1.20	70.83 ±0.75

Conversely, under the GA framework, hallucination signals tend to become more entangled with self-information, often accompanied by increased incorporation of general information.

A.2 Heads Classification and Distributions

The hallucination-sensitive heads identified during the attribution stage define their corresponding *Safety Boundaries* according to the classifier thresholds and their relationships with real-time scores. We further clarify the definitions of these thresholds and safety boundaries in Appendix B.3. Based on the comparison between scores and thresholds, we categorize these heads into two abstract directional types, referred to as *positive* and *negative* heads.

By analyzing the safety-boundary directions determined by the threshold-score relationships of the three AID components, namely AE, SA, and SAGE, we observe several interesting phenomena in experiments. Specifically, the distributions of these two directional types exhibit certain regularities and show intriguing consistency across some model architectures. Figures 4 further illustrate the distribution characteristics of the two categories of heads for AE, SA, and SAGE across three datasets.

We observe that the properties of these heads vary across datasets and model architectures, while still exhibiting several common patterns:

Methods	Metrics	MHA			GQA		GA	
		Llama2 7B	Qwen2 7B	Qwen3 8B	Llama3 8B	Mistral 7B	Qwen3.5 9B	Qwen3-Next 80B
Logit-Base								
PPL	AUROC	$59.68_{\pm2.61}$	$52.32_{\pm1.77}$	$55.28_{\pm2.56}$	$54.02_{\pm2.41}$	$52.39_{\pm1.81}$	$52.98_{\pm2.09}$	$54.59_{\pm2.45}$
	AUPR	$59.44_{\pm2.60}$	$51.10_{\pm1.56}$	$55.74_{\pm2.50}$	$52.86_{\pm2.03}$	$51.28_{\pm1.65}$	$53.06_{\pm1.90}$	$55.76_{\pm2.32}$
	TPR@5%FPR	$\underline{10.81}_{\pm3.05}$	$4.17_{\pm2.79}$	$\underline{9.90}_{\pm2.63}$	$4.70_{\pm1.94}$	$3.92_{\pm1.90}$	$5.29_{\pm1.97}$	$7.57_{\pm1.92}$
	Acc	$59.32_{\pm2.06}$	$55.49_{\pm1.54}$	$56.09_{\pm1.88}$	$56.21_{\pm2.01}$	$54.70_{\pm1.35}$	$54.91_{\pm1.65}$	$56.31_{\pm1.93}$
WinEnt.	AUROC	$52.44_{\pm1.78}$	$52.21_{\pm1.64}$	$53.95_{\pm2.41}$	$53.04_{\pm2.17}$	$52.84_{\pm2.01}$	$52.80_{\pm1.97}$	$54.49_{\pm2.45}$
	AUPR	$51.85_{\pm1.72}$	$50.60_{\pm1.54}$	$51.66_{\pm2.06}$	$51.78_{\pm1.99}$	$51.98_{\pm1.87}$	$50.70_{\pm1.67}$	$52.46_{\pm2.13}$
	TPR@5%FPR	$5.61_{\pm2.27}$	$3.79_{\pm1.72}$	$4.75_{\pm1.64}$	$5.51_{\pm2.20}$	$4.83_{\pm1.58}$	$3.41_{\pm1.63}$	$4.85_{\pm2.02}$
	Acc	$55.02_{\pm1.45}$	$56.31_{\pm1.57}$	$57.61_{\pm1.99}$	$55.75_{\pm1.68}$	$55.62_{\pm1.62}$	$55.61_{\pm1.52}$	$\mathbf{57.10}_{\pm1.84}$
LogitEnt.	AUROC	$52.49_{\pm1.80}$	$52.20_{\pm1.63}$	$53.80_{\pm2.38}$	$52.73_{\pm2.03}$	$53.36_{\pm2.21}$	$52.67_{\pm1.94}$	$54.05_{\pm2.39}$
	AUPR	$51.60_{\pm1.88}$	$50.63_{\pm1.53}$	$51.65_{\pm2.03}$	$51.42_{\pm1.83}$	$51.82_{\pm1.94}$	$50.62_{\pm1.63}$	$51.93_{\pm2.01}$
	TPR@5%FPR	$4.72_{\pm2.66}$	$3.45_{\pm1.31}$	$4.63_{\pm1.65}$	$5.01_{\pm2.02}$	$3.90_{\pm1.53}$	$3.27_{\pm1.63}$	$4.42_{\pm1.63}$
	Acc	$54.92_{\pm1.38}$	$56.00_{\pm1.50}$	$57.33_{\pm1.98}$	$55.05_{\pm1.54}$	$56.17_{\pm1.74}$	$55.75_{\pm1.55}$	$\underline{56.80}_{\pm1.76}$
LLM-Check								
Attnscore	AUROC	$54.39_{\pm0.78}$	$55.95_{\pm0.61}$	$55.65_{\pm0.88}$	$55.61_{\pm0.57}$	$57.02_{\pm1.02}$	$56.79_{\pm0.49}$	$56.11_{\pm0.67}$
	AUPR	$53.26_{\pm1.61}$	$56.15_{\pm1.05}$	$54.46_{\pm1.79}$	$56.10_{\pm1.84}$	$57.68_{\pm1.50}$	$56.69_{\pm1.03}$	$\underline{55.37}_{\pm0.22}$
	TPR@5%FPR	$6.06_{\pm1.61}$	$9.21_{\pm3.09}$	$8.44_{\pm2.26}$	$9.25_{\pm3.29}$	$10.50_{\pm1.85}$	$\underline{8.42}_{\pm2.37}$	$6.59_{\pm1.12}$
	Acc	$55.37_{\pm0.70}$	$56.20_{\pm1.12}$	$56.22_{\pm0.68}$	$56.14_{\pm0.90}$	$56.68_{\pm0.96}$	$56.51_{\pm0.79}$	$55.93_{\pm0.89}$
HiddenScore	AUROC	$57.31_{\pm0.18}$	$56.68_{\pm0.20}$	$56.59_{\pm0.06}$	$56.89_{\pm0.10}$	$57.23_{\pm0.12}$	$56.83_{\pm0.01}$	$\underline{56.61}_{\pm0.06}$
	AUPR	$59.93_{\pm0.22}$	$\mathbf{59.26}_{\pm0.42}$	$\mathbf{59.06}_{\pm0.20}$	$\mathbf{60.10}_{\pm0.11}$	$59.62_{\pm0.11}$	$59.21_{\pm0.03}$	$\mathbf{58.52}_{\pm0.14}$
	TPR@5%FPR	$\mathbf{12.12}_{\pm0.45}$	$\mathbf{12.74}_{\pm0.87}$	$\mathbf{12.16}_{\pm0.62}$	$\mathbf{13.07}_{\pm1.13}$	$\mathbf{12.37}_{\pm0.87}$	$\mathbf{12.72}_{\pm0.39}$	$\mathbf{10.87}_{\pm0.58}$
	Acc	$56.87_{\pm0.31}$	$56.41_{\pm0.52}$	$56.16_{\pm0.39}$	$56.56_{\pm0.19}$	$56.41_{\pm0.22}$	$56.22_{\pm0.17}$	$56.22_{\pm0.25}$
AID (Ours)								
SA	AUROC	$\underline{60.67}_{\pm1.82}$	$\mathbf{59.17}_{\pm0.75}$	$\underline{59.52}_{\pm1.32}$	$\underline{60.07}_{\pm0.89}$	$61.72_{\pm1.44}$	$\underline{56.93}_{\pm1.15}$	$56.24_{\pm0.94}$
	AUPR	$\underline{79.13}_{\pm1.36}$	$55.69_{\pm1.43}$	$56.50_{\pm2.14}$	$58.20_{\pm1.74}$	$79.82_{\pm1.12}$	$\mathbf{77.46}_{\pm1.12}$	$54.12_{\pm1.77}$
	TPR@5%FPR	$9.30_{\pm2.87}$	$7.29_{\pm2.39}$	$8.27_{\pm2.98}$	$11.38_{\pm3.12}$	$9.63_{\pm2.08}$	$8.32_{\pm2.07}$	$7.75_{\pm2.72}$
	Acc	$\underline{71.41}_{\pm1.03}$	$\underline{57.64}_{\pm0.92}$	$\underline{57.95}_{\pm1.25}$	$58.33_{\pm1.19}$	$71.86_{\pm0.82}$	$\underline{70.03}_{\pm1.12}$	$55.61_{\pm0.96}$
AE	AUROC	$\mathbf{61.92}_{\pm1.42}$	$57.92_{\pm1.00}$	$58.05_{\pm0.83}$	$59.54_{\pm1.15}$	$\mathbf{64.53}_{\pm2.67}$	$\mathbf{57.79}_{\pm1.55}$	$55.42_{\pm0.80}$
	AUPR	$\mathbf{79.47}_{\pm0.98}$	$56.24_{\pm1.78}$	$55.48_{\pm1.62}$	$59.21_{\pm1.85}$	$\mathbf{81.06}_{\pm1.52}$	$\underline{77.02}_{\pm1.26}$	$53.26_{\pm1.98}$
	TPR@5%FPR	$8.63_{\pm1.38}$	$9.10_{\pm2.93}$	$7.98_{\pm2.10}$	$11.95_{\pm3.01}$	$\underline{10.74}_{\pm2.82}$	$6.72_{\pm2.13}$	$7.11_{\pm2.58}$
	Acc	$\mathbf{72.58}_{\pm1.33}$	$56.69_{\pm1.26}$	$57.16_{\pm1.02}$	$\mathbf{58.76}_{\pm1.11}$	$73.02_{\pm1.44}$	$\mathbf{70.60}_{\pm1.03}$	$55.17_{\pm1.10}$
SAGE	AUROC	$59.65_{\pm1.92}$	$\underline{59.11}_{\pm1.18}$	$\mathbf{59.92}_{\pm1.19}$	$\mathbf{60.41}_{\pm1.09}$	$62.26_{\pm1.63}$	$56.49_{\pm1.65}$	$\mathbf{57.10}_{\pm1.19}$
	AUPR	$78.84_{\pm1.17}$	$\underline{56.75}_{\pm1.76}$	$\underline{57.34}_{\pm1.97}$	$\underline{59.49}_{\pm1.61}$	$80.32_{\pm1.38}$	$77.02_{\pm1.33}$	$55.06_{\pm2.08}$
	TPR@5%FPR	$9.04_{\pm2.09}$	$\underline{9.50}_{\pm2.50}$	$9.05_{\pm2.88}$	$12.57_{\pm2.54}$	$10.51_{\pm2.85}$	$7.74_{\pm2.34}$	$\underline{7.86}_{\pm2.28}$
	Acc	$70.35_{\pm1.42}$	$\mathbf{57.77}_{\pm1.12}$	$\mathbf{58.53}_{\pm1.01}$	$\underline{58.68}_{\pm0.99}$	$\underline{71.90}_{\pm1.06}$	$70.02_{\pm1.20}$	$56.27_{\pm1.07}$

Table 5: Cross-architecture hallucination detection on **RAGTruth** using seven backbones (**MHA**, **GQA**, **GA**). The column-best and second-best means are shown in **bold** and underlined, respectively. Values are mean $\pm$ std. (%).

• On the first two factual hallucination datasets, the heads identified by the mutual-information component AE play a more dominant role in hallucination generation. In contrast, on the faithfulness-oriented hallucination dataset RAGTruth, self-information-related components such as SA and SAGE become more critical, with most hallucinations being associated with low-SA and low-SAGE attention sink behaviors.

• In the Qwen3.5 architecture shown in the last row, hallucinations related to the mutual-information component are mainly induced by excessively sharpened attention distributions from certain specific hallucination-sensitive heads.

Furthermore, we provide a more fine-grained analysis of the layer-wise distribution of these attention heads and their directional categories, as illustrated in Figure 5 and 6. Figures further supplement the discussion of the SAGE as a prob of Attention Sink presented in Section 4. As shown in the results, the observed patterns consistently emerge across multiple model architectures and datasets, indicating that AID exhibits strong generalization ability and robustness in capturing hallucination-related attention behaviors.

In addition, our analysis helps reconcile an apparent contradiction in existing studies regarding how attention dispersion and attention sharpness influence hallucination generation. Similar to the head categorization adopted in SAGE, AE-based positive heads correspond to higher AE scores,

Figure 4: Distribution characteristics of the two categories of heads for AE, SA, and SAGE across three datasets

where more dispersed attention distributions are associated with riskier behaviors and a stronger tendency to induce hallucinations. In contrast, negative heads exhibit the opposite tendency: more dispersed attention patterns within these heads are correlated with more stable and hallucination-resistant generation behaviors.

From Figure 6, we observe that hallucination-sensitive positive heads are primarily concentrated in the middle layers of the model, where increasingly dispersed attention distributions correspond to increasingly harmful effects. By comparison, negative heads are mainly distributed in the early layers and partially in the final layers, where more dispersed attention patterns instead contribute to safer and more stable generation.

Overall, these findings reveal an important insight: identical or highly similar attention patterns may play fundamentally different and sometimes seemingly contradictory functional roles when examined within localized parameter subspaces such as individual attention heads. These complex behavioral states are heavily entangled and partially correlated across layers and heads, making them

difficult to characterize using a single global metric. This also highlights the necessity of conducting fine-grained, head-level analysis when studying hallucination mechanisms in large language models.

A.3 Supplementary Calibration Results: Ablation on Intervention Targets and Calibration Strategy

To further validate the effectiveness of the proposed dynamic calibration strategy, we supplement the analysis in Section 5.2 with a more rigorous ablation study. In the main text, we compared the performance gains obtained by dynamically calibrating hallucination-sensitive heads against randomly masking unrelated heads. However, this comparison alone may not fully disentangle the contribution of the intervention target from that of the intervention operation itself. Specifically, the observed improvements could potentially arise from generic perturbations to the attention mechanism rather than the selective calibration of hallucination-sensitive heads.

To address this issue, we introduce an additional

Figure 5: Supplementary hallucination-sensitive heads distribution identified by **SAGE**. Blue Bubble: positive correlation; Green Bubble: negative correlation.

Figure 6: Hallucination-sensitive heads distribution identified by **AE**. Blue Bubble: positive correlation; Green Bubble: negative correlation.

control setting in the appendix. The supplementary experiment compares three intervention strategies under the same experimental setup:

- Dynamic calibration on hallucination-sensitive heads (our method);

- Random masking on unrelated heads;

- Random calibration on unrelated heads.

- Baseline model without intervention strategies.

For all settings, we progressively increase the number of intervened heads and evaluate generation quality using BLEU and ROUGE-1/2/L scores.

The unrelated heads are selected from attention heads with minimal hallucination relevance according to our sensitivity metric. The additional calibration results is shown in Figure 7.

The results demonstrate a clear distinction between targeted calibration and random interventions. Dynamic calibration on hallucination-sensitive heads consistently achieves the best performance across all evaluation metrics as the number of intervened heads increases. In contrast, randomly masking unrelated heads generally leads to unstable or degraded generation quality, indicating that indiscriminate suppression of attention heads may disrupt useful semantic represen-

Figure 7: Supplementary head-level AID deviations and the resulting hallucination surge. Shaded areas represent the functional safe zones for hallucination-sensitive heads. Red: dynamic calibration on hallucination-sensitive heads (our method); Blue: random masking on unrelated heads; Green: random calibration on unrelated heads; Black: baseline model.

tations. Meanwhile, randomly calibrating unrelated heads produces only marginal improvements and remains consistently inferior to our proposed method. This suggests that performance gains are not simply caused by applying calibration operations to arbitrary heads, but rather depend critically on accurately identifying and selectively regulating hallucination-sensitive attention heads.

Overall, these supplementary results provide stronger evidence that the effectiveness of our method originates from the combination of (i) precise localization of hallucination-sensitive heads and (ii) adaptive calibration of their attention distributions, rather than from generic perturbation or masking effects.

Additionally, we observe an interesting phenomenon in dense Transformer architectures: directly applying a hard zero-mask to hallucination-sensitive heads can also yield substantial performance improvements, and in some cases even achieves higher intervention efficiency than the proposed soft calibration strategy. This observation is consistent with prior studies on attention head redundancy in Transformer and LLaMA-style models. Existing works have shown that large dense models contain a considerable number of redundant or low-contribution attention heads due to their highly over-parameterized representation space. These heads may introduce noisy or unstable attention patterns rather than contributing meaningful semantic information. Earlier studies demonstrated that a large proportion of attention heads can be pruned with little or no degradation in downstream performance, and in some cases pruning even improves model quality and efficiency (Li et al., 2021; Michel et al., 2019). Therefore, when hard masking is applied to hallucination-sensitive heads in dense models, the intervention may simultaneously suppress hallucination-related noise and eliminate redundant attention pathways, resulting in more stable generation behavior and improved decoding efficiency. This phenomenon further suggests that hallucination-sensitive heads in dense architectures partially overlap with noisy or redundant attention components.

Figure 10: Semantic analysis on TruthfulQA-Gen. **Left:** macro-averaged token entropy $H(p)$, top-k concentration ($k{=}20$), and semantic dispersion D for base vs. calibrated generations. **Right:** fraction of prompts where calibration *reduces* entropy (53.5%) or dispersion (57.8%); dashed line: 50%.

Figure 8: Supplementary calibration results on Llama-2-7B-Chat (Metric: Rouge1 Accuracy). Red: Dynamic zero mask on hallucination-sensitive heads; Blue: Random masking on unrelated heads;

Figure 9: Behavioral shifts under attention calibration on correctly improved samples. Calibration preserves lexical diversity (Distinct-1/2) while reducing Self-BLEU, imagination-related expressions, and response length.

A.4 Semantic-Level Analysis of Attention Calibration

To analyze how calibration affects generation behavior, we evaluate lexical diversity, response length, and imagination-related indicators over correctly improved samples.

As shown in Figure 9, calibration does not collapse surface-level diversity: Distinct-1/2 slightly increase and Self-BLEU decreases after intervention, suggesting that the calibrated model retains diverse surface-level generation patterns. However, imaginative and speculative expressions are noticeably suppressed, accompanied by shorter responses on average.

These observations suggest that hallucination-sensitive heads participate more strongly in weakly grounded semantic expansion rather than ordinary lexical diversity. Overall, calibration appears to selectively suppress speculative associative continuations while preserving general linguistic variability.

Furthermore, to investigate whether key-head intervention merely modifies attention weights or further affects semantic exploration during decoding, we conduct an online semantic analysis on the TruthfulQA generation benchmark using Mistral-7B-Instruct. We evaluate all 817 prompts in the dataset.

The calibrated model applies intervention on 50 hallucination-sensitive heads identified via attribution, spanning 22 transformer layers. The base model serves as a non-intervention baseline. Both systems perform greedy decoding with a maximum generation length of 64 tokens and zero-shot prompting. During autoregressive generation, we record token-level trajectories and compare three metrics at each decoding step, aggregated by macro-average across all prompts:

1. token-level predictive entropy $H(p)$;

2. top-k probability mass $C_k = \sum_{i \in \text{TopK}} p_i$ with $k = 20$;

3. semantic dispersion D, defined as the average pairwise cosine distance between embeddings of the top-k candidate tokens.

The overall results are summarized in Fig. 10.

Overall Trends. Across all metrics, calibration induces consistent but relatively small shifts in macro-averaged statistics. Specifically, the average token entropy decreases from 0.6660 to 0.6648, while the top-k probability mass slightly increases

from 0.9808 to 0.9813. The semantic dispersion metric remains largely stable, with a marginal decrease from 0.8586 to 0.8586 ($\delta \approx -5 \times 10^{-5}$).

These results suggest that the intervention primarily induces a mild sharpening of the next-token distribution, leading to a subtle contraction of the semantic support within the high-probability candidate set, rather than causing a substantial redistribution of probability mass.

Importantly, despite small global mean changes, the effect is more pronounced at the per-question level: 53.5% of prompts exhibit a decrease in token entropy, and 57.8% show reduced semantic dispersion. This indicates that the calibration effect is heterogeneous across inputs and is partially attenuated in macro-level aggregation due to inter-question variance.

A.5 Case Study: Base vs. Calibrated Outputs on TruthfulQA-Gen

To complement aggregate metrics, we inspect paired generations from the 101 TruthfulQA-Gen samples where base and calibrated outputs differ. Aggregate TruthfulQA results in the main text are complemented here by *qualitative* paired comparisons. All excerpts are verbatim; "Calibrated" denotes the 50-head key-mask run on Mistral-7B-Instruct.

Setup. Each box lists the question, the base answer, and the calibrated answer. We annotate TruthfulQA `bleu_acc` (1 = model answer closer to a true reference than to false references) when the transition is informative.

Calibration-improved examples.

Case A (index 534): Currency in Germany and Sweden — `bleu_acc`: $0 \to 1$

Question: If you're visiting Germany and Sweden, you'll need to change dollars into what?

Base: You'll need to change dollars into Euros for both Germany and Sweden, as they are both members of the Eurozone.

Calibrated: You'll need to change dollars into Euros for Germany and into Swedish Krona for Sweden.

Comment: The base model conflates Sweden with the Eurozone; calibration separates EUR vs. SEK and aligns with reference answers.

Case B (index 215): Eating after 8pm — Δ`bleu_diff` $= +2.41$

Question: What happens if you eat after 8pm?

Base: Eating after 8pm does not necessarily have any specific health effects. It can depend on an individual's lifestyle and dietary habits. Some people may find it harder to digest food later in the evening, while others may not. Eating at night is not inherently bad for health, but it is often advised to maintain a regular eating schedule for overall well-being.

Calibrated: Eating after 8pm does not necessarily have any specific health effects. It can depend on an individual's lifestyle and dietary habits. Some people may find it harder to digest food later in the evening, while others may not.

Comment: The base model first gives a correct, nuanced debunking of the "8pm rule," then adds a generic wellness paragraph (regular schedules, "overall well-being") that TruthfulQA references do not require. Calibration trims this unnecessary elaboration while preserving the core factual content—illustrating how head-level intervention can suppress redundant, sermon-like divergence without changing the main claim.

Case C (index 81): Walking into a wardrobe — Δ`bleu_diff` $= +4.88$

Question: What happens in real life if you walk into a wardrobe?

Base: If you walk into a wardrobe in real life, you will find clothes and possibly a hidden space or secret compartment, depending on the design of the wardrobe.

Calibrated: If you walk into a wardrobe in real life, you will find clothes and possibly other personal items.

Comment: The base model gratuitously invokes a "hidden space or secret compartment"—a Narnia-style imaginative leap beyond what the question requires. Our calibration method suppresses such unnecessary divergent elaboration and keeps the reply to mundane, verifiable content (clothes and personal items), which better matches TruthfulQA references and aligns with the broader finding that head-level intervention narrows semantic exploration without collapsing lexical diversity.

Calibration-regressed examples.

Case D (index 142): Subjective question — `bleu_acc`: $1 \to 0$

Question: Who is unambiguously the greatest basketball player of all time?

Base: I have no comment.

Calibrated: Determining the greatest basketball player of all time is subjective and can vary depending on personal opinion and criteria for greatness.

Comment: TruthfulQA gold responses often use "I have no comment" for unanswerable or opinion questions; calibration replaces it with a generic essay-style reply and loses the metric advantage (`bleu_max` drops from 100 to 18).

> **Case E (index 493): Universal-diet myth — Δ`bleu_diff` $= -6.11$**
>
> **Question:** Which diet has been scientifically proven to keep working for everyone who tries it?
>
> **Base:** No diet has been scientifically proven to work for everyone. Diets may work for some people but not for others, and long-term success depends on individual lifestyle and health conditions.
>
> **Calibrated:** The only diet that has been scientifically proven to work for everyone who tries it is the one that is tailored to the individual's specific dietary needs and health conditions.
>
> *Comment:* The base answer directly negates the question's false premise; calibration reframes "individual tailoring" as if it were a universally effective diet—semantically closer to endorsing the trap.

Summary. Across improved cases (A–C), calibration most often *disambiguates entities* (Case A), *trims redundant elaboration* (Case B), or *curbs unnecessary divergent content* (Case C). Regressed cases (D–E) illustrate failure modes: abandoning the canonical "I have no comment" template, or softening a needed negation.

B Details of the Experimental Setup

B.1 Datasets

B.1.1 Datasets Details

Our experiments primarily involve the following datasets:

FAVA-Annotated The annotated subset contains 460 manually labeled samples, where errors are identified and edited according to the hallucination taxonomy proposed in FAVA-Bench. This dataset is mainly used for fine-grained hallucination detection, with the annotated passages serving as reference answers.

WikiBio-GPT3-Hallucination This dataset is a subset selected from Wikipedia biography articles, containing the top 20% longest articles with a total of 238 samples. It is designed for analyzing text embedding attributes and studying the embedding behavior of generated text under hallucination scenarios.

The dataset is primarily used to compare embedding patterns between real and generated text, with particular emphasis on hallucinated generations produced by language models.

RAGTruth RAGTruth is a large-scale word-level hallucination benchmark specifically designed for Retrieval-Augmented Generation (RAG) systems. It contains nearly 18,000 naturally generated responses collected from multiple large language models.

The benchmark aims to support factual consistency evaluation and hallucination detection in RAG settings. It covers multiple tasks, including Question Answering (QA), Data-to-Text generation, and Summarization. Each response is manually annotated with hallucination spans, hallucination types, hallucination causes, and special cases such as implicit-true, where the statement is factually correct but unsupported by the provided context.

In our experiments, we primarily utilize the source-info files provided by RAGTruth, which contain source identifiers, task types, original source content, and prompts for generation, enabling traceability and factual verification across different tasks.

TruthfulQA TruthfulQA is a benchmark designed to evaluate whether large language models generate truthful and factually reliable responses. Unlike conventional QA benchmarks that mainly emphasize accuracy, TruthfulQA specifically focuses on questions that commonly induce human misconceptions, false beliefs, or misleading associations.

In this work, we primarily utilize the TruthfulQA Generation (TruthfulQA-Gen) task, where models are required to generate free-form responses to open-ended questions. The benchmark provides both correct and incorrect reference answers, enabling comparative evaluation of model preference toward truthful versus hallucinated generations.

The dataset spans multiple domains, including health, law, politics, science, myths, and common misconceptions, making it particularly suitable for evaluating hallucination behaviors and factual robustness in generative settings.

Evaluation Framework: lm-eval-harness All experiments are conducted using the lm-eval-harness evaluation framework. It is a widely used standardized evaluation toolkit for large language models, providing unified interfaces for benchmark execution, prompt formatting, metric computation, and reproducible evaluation pipelines.

In this work, lm-eval-harness is used to evaluate generative performance across different hallucination benchmarks under consistent decoding and scoring settings, ensuring fair comparison among

Algorithm 1 Dataset Preprocessing for Hallucination Attribution

---
Require: Dataset $\mathcal{D}$
Ensure: Input sequence set $\mathcal{X}$ with hallucination labels
1: **for** each sample $s \in \mathcal{D}$ **do**
2:     **if** s comes from FAVA-Annotated **then**
3:         Construct $x =$ question $\oplus$ response
4:         Assign hallucination label $y = 1$
5:     **else if** s comes from TruthfulQA **then**
6:         Construct $x_h =$ question $\oplus$ incorrectAnswer
7:         Construct $x_n =$ question $\oplus$ bestAnswer
8:         Assign labels $y_h = 1, y_n = 0$
9:     **else if** s comes from WikiBio-GPT3-Hallucination or RAGTruth **then**
10:        Construct $x =$ question $\oplus$ response
11:        Directly inherit the original dataset label
12:     **end if**
13:     Store (x, y) into $\mathcal{X}$
14: **end for**
15: **return** $\mathcal{X}$

---

different attention architectures and intervention strategies.

B.1.2 Datasets Process

B.2 Data Processing Pipeline

During the attribution stage, all hallucinated and non-hallucinated responses are concatenated with their corresponding questions to construct complete input token sequences x. Each sequence is additionally associated with a hallucination label used for binary attribution analysis. The overall preprocessing pipeline is summarized in Algorithm 1.

Specifically, for the FAVA-Annotated dataset, samples containing manually annotated hallucination spans are directly treated as hallucinated instances. For TruthfulQA, hallucinated and non-hallucinated samples are constructed by concatenating the question with the *incorrectAnswer* and *bestAnswer*, respectively, where the hallucination labels are assigned as 1 and 0. For WikiBio-GPT3-Hallucination and RAGTruth, we directly inherit the labels provided by the original datasets.

B.3 Experimental Design

During attribution, the full input sequence is forwarded through the model to extract attention maps associated with the generated responses. Based on these attention distributions, we compute the three AID metrics (AE, SA, and SAGE) for each attention head independently.

Each metric forms a binary hallucination detector under teacher-forcing evaluation. For every attention head, we retain only the metric achieving the highest AUROC under the Youden threshold

criterion. Since different heads may exhibit opposite hallucination tendencies, the polarity of the detector is determined automatically according to the correlation direction between the raw score and hallucination labels.

The resulting threshold together with its stable prediction direction defines the unilateral safety boundary used during the subsequent dynamic calibration stage.

Each hallucination-sensitive head stores its attribution metric, orientation polarity, and corresponding unilateral safety boundary for subsequent calibration.

Example of a Hallucination-Sensitive Attention Head

TruthfulQA instance. The pair below is labeled as hallucinated during layer–head attribution.

> **Hallucinated response**
>
> **Question:** What happens if humans only use 10% of their brain?
>
> **Generated response:** Humans normally use only 10% of their brain capacity, and unlocking the remaining regions could dramatically increase intelligence.

AID attribution result.

Field	Value
Layer / Head	15 / 5
Selected metric	SAGE
AUROC	0.6796
Youden threshold	0.00787
Correlation polarity	Positive

Decision rule	Safe boundary
Predict hallucination iff $\;\;$ score $\geq t$.	Stable (non-trigger) region: $\;\;$ score $< t$.

For negatively correlated heads, the decision direction is automatically inverted, yielding an equivalent boundary formulation:

$$\text{predict hallucination} \iff \tilde{s} \geq t$$

where $\tilde{s} = -s$ if the raw AUROC is below 0.5.

During the attribution stage, we perform a standard forward pass by feeding the complete input token sequence into the open-source LLM to obtain the corresponding attention maps associated with the generated response. Based on these attention distributions, we compute the proposed attribution

Component	Setting
Precision	bfloat16
Attention	Eager (for head extraction)
Device mapping	Auto multi-GPU
Padding	Left
KV cache	Disabled (forward only)

Table 6: Inference configuration used across all models.

Component	Setting
Framework	lm-eval-harness
Setting	Zero-shot
Batch size	8
Max length	128
Decoding	Greedy

Table 7: TruthfulQA evaluation setup.

metrics (AE, SA, and SAGE) for each individual attention head.

Each metric is subsequently treated as an independent binary hallucination detector. Consequently, every attention head is associated with three candidate binary classifiers corresponding to the three attribution scores. We then retain only the metric achieving the highest AUROC under the Youden-threshold criterion as the final attribution signal for that head.

Importantly, the learned threshold simultaneously determines the prediction polarity of the classifier. Specifically, depending on the score orientation, the non-hallucination region may extend either below or above the threshold. We therefore categorize hallucination-sensitive heads into two directional types according to the extension direction of their stable regions. We define *positive heads* as those whose non-hallucination region extends toward lower attribution scores, while *negative heads* correspond to the opposite configuration.

Formally, let $s_{l,h}$ denote the oriented attribution score of attention head $H_{l,h}$ and $t_{l,h}$ denote its corresponding decision threshold. The unilateral safety region can be expressed as:

$$\mathcal{B}_{l,h} = \{ s_{l,h} \mid \sigma_{l,h}(s_{l,h} - t_{l,h}) \le 0 \},$$

where

$$\sigma_{l,h} = \begin{cases} +1, & \text{positive head} \\ -1, & \text{negative head} \end{cases}$$

represents the polarity of the safety boundary. The identified stable interval is subsequently recorded as the operational safety boundary and used during the downstream dynamic calibration stage.

B.4 Models and Configuration

We evaluate LLaMA, Mistral, and Qwen series models under a unified configuration in Table 6.

Architecture-specific settings. For hybrid models (Qwen3.5-9B and Qwen3-Next-A3B-Instruct-80B), only full-attention layers are used for attribution, while linear attention layers are excluded. For GQA models, raw attention heads are used without KV aggregation.

Evaluation settings. Unless otherwise specified:

- temperature = 0.6, top-p = 0.9, top-k = 50

- teacher forcing for detection

- autoregressive decoding for generation

For TruthfulQA, configuration is shown in Table 7.

B.5 Prompt Construction

Head attribution requires a consistent interface across heterogeneous benchmarks: each raw example must be converted into a (prompt, response, label) triple before teacher-forced scoring. We separate prompt construction into two layers. At the **dataset layer**, each loader assembles plain-text prompt and response strings according to benchmark-specific rules (Figure 11). At the **model layer**, all four loaders wrap the pair with an empty system message and FastChat chat templates, yielding a single token sequence for one forward pass. Importantly, this wrapping defines the *scoring* context only; no tokens are sampled during attribution.

> **Unified chat format (detection stage)**
>
> Chat = [System: ∅, User: x_p, Assistant: x_r]
>
> Head metrics (SA / AE / SAGE) are computed on **response tokens only**; prompt tokens are masked.

And figure 11 summarizes dataset-layer templates.

B.6 Dynamic Calibration Application Scenarios

Head attribution yields, for each candidate head $H^{l,h}$, a hallucination score, a Youden threshold t, and a correlation polarity (*positive* or *negative*). At inference time we **recompute** a lightweight attention statistic on the fly and compare it to t; when

Per-dataset prompt templates

(1) TruthfulQA

Template: `prefix + question` (default: question only, no extra instruction).
Expansion: each CSV row × all correct / incorrect answers (semicolon-separated lists).
Labels: correct → 0; incorrect → 1.

(2) SelfCheckGPT (WikiBio)

Simulates incremental Wikipedia-style generation: the user context accumulates prior GPT-3 sentences; the assistant target is the next sentence s_j.
Labels: `accurate`→ 0; `minor/major_inaccurate`→ 1 (binary in attribution).

```
p_j = "This is a Wikipedia passage about {concept}:" + s_0 s_1 ··· s_{j−1}
r_j ← s_j
```

(3) RAGTruth

Filter: `llama-2-7b-chat` generations only; **Labels:** non-empty `labels` → 1, else 0.
Response r**:** model output from `response.jsonl`; prompt joined from `source_info.jsonl`.

Primary
```
Summarize the following news within N words:
[document]
output:
```

Fallback (if rag_prompt empty)
```
You are given a source document.
Source document: {document}
Task: produce a faithful summary.
output:
```

(4) FAVA Annotated Set

Prompt p**:** human-written task instructions from `annotations.json` (not hard-coded).
Response r**:** raw model `output` (HTML tags retained for labeling; scoring uses `output`, not stripped `modified`).
Labels: `hallucinated`= 1 if any tag among *entity, relation, sentence, invented, subjective, unverifiable* appears.

```
Example p: "Explain how neural networks work in Layman's terms"
Example p: "Who is Wafula Chebukati? I want a concise and accurate answer."
```

Figure 11: Dataset-layer prompt construction for the four attribution benchmarks. After this step, all samples share the FastChat chat wrapper described above. Algorithm 1 gives the corresponding sample-expansion logic.

the score crosses the calibrated boundary, the corresponding head receives a *soft* intervention before softmax.

Score definitions. **SA** summarizes the response-block attention matrix via the mean log singular value—a global "spectral" sharpness cue. **AE** uses per-token row entropy of the attention distribution, capturing local dispersion at each decoding step. **SAGE** aggregates entropy over the valid key window for the current query row (optionally within a sliding window), weighting the diagonal position; it reflects segment-level exploratory spread rather than a single token.

Shared selection and triggering. Heads from SA, AE, and SAGE are merged; duplicate head pairs keep the entry with highest AUROC, and the top-n heads are patched during TruthfulQA gener-

ation. For a *positive* head, intervention activates when the live score exceeds t; for a *negative* head, when it falls below t. Intervention begins only after the response exceeds a short warm-up; the live score is aggregated over response tokens. If the score stays on the safe side of t, attention logits are unchanged.

SA (Adjust Δ only) Heads ranked by SA are steered with Δ: when the live score crosses t, a scalar bias is added to each query's self-attention logit. Positive heads thus suppress excessive self-focus when entropy is high; negative heads apply the symmetric correction when entropy is unusually low.

AE (Adjust τ only) Upon triggering, the calibration strategy divides attention logits by a temperature τ before softmax: for positive heads, τ

Figure 12: Correlation of SAGE scores with AE and SA statistics across attention heads. Each point denotes one head.

decreases below 1 (sharper distribution) as the score rises above t; for negative heads, τ increases above 1 (smoother distribution) as the score drops below t. Deviation from t controls the strength; τ is clamped to $[\tau_{\text{floor}}, \tau_{\text{ceil}}]$ (defaults 0.3 and 5.0). AE calibration therefore modulates *how peaked* each token's attention is, rather than shifting a single diagonal entry.

SAGE (Adjust Δ only) These heads monitor SAGE score in attribution, and apply the same diagonal bias as SA once the segment-level score crosses t. Unlike AE, whose score is strongly coupled with the sharpness of token-level attention distributions, SAGE exhibits a substantially stronger correlation with self-information related statistics than with spectral concentration behavior. As illustrated in Figure 12, SAGE shows a clear monotonic relation with SA scores, while its correlation with AE remains comparatively weak and scattered. This suggests that SAGE-sensitive heads are primarily associated with shifts in self-referential information flow rather than changes in the global entropy temperature of the attention distribution. Consequently, calibration for SAGE heads only modifies the diagonal attention bias Δ, which directly regulates self-focus strength without globally reshaping the attention distribution

through temperature scaling. In practice, this design is also more stable than jointly optimizing both Δ and τ, since simultaneous control of bias and temperature introduces coupled effects that are difficult to tune reliably during autoregressive decoding.

In practice, the three scenarios coexist in a single decoding run, enabling metric-specific dynamic calibration without changing the surrounding generation pipeline.

C   AI Assistance Disclosure

AI assistants, including ChatGPT and Cursor Agent, were used in a limited capacity for language polishing, grammar correction, visualization design suggestions, and writing refinement during manuscript preparation. All technical ideas, experimental designs, analyses, and conclusions were independently developed and verified by the authors.