Perceptual Score: Measuring Perceptiveness of Multi-Modal Classifiers

Abstract

Machine learning advances in the last decade have relied significantly on large-scale datasets that continue to grow in size. Increasingly, those datasets also contain different data modalities. However, large multi-modal datasets are hard to annotate, and annotations may contain biases that we are often unaware of. Deep-net-based classifiers, in turn, are prone to exploit those biases and to find shortcuts. To study and quantify this concern, we introduce the perceptual score, a metric that assesses the degree to which a model relies on the different subsets of the input features, *i.e.*, modalities. Using the perceptual score, we find a surprisingly consistent trend across four popular datasets: recent, more accurate state-of-the-art multi-modal models for visual question-answering or visual dialog tend to perceive the visual data less than their predecessors. This trend is concerning as answers are hence increasingly inferred from textual cues only. Using the perceptual score also helps to analyze model biases by decomposing the score into data subset contributions. We hope to spur a discussion on the perceptiveness of multi-modal models and also hope to encourage the community working on multi-modal classifiers to start quantifying perceptiveness via the proposed perceptual score.

1 Introduction

Machine learning advances over the last decade are remarkable. Challenges that seemed daunting merely ten years ago are now a breeze, and new applications that we barely dared to dream about seem achievable within the next few years. Indeed, accuracy metrics on tasks like visual question answering and reasoning suggest significant improvements.

Reported improvements are to a large extent due to the availability of large datasets [1–3], computational performance advances, *e.g.*, for GPUs, and a better understanding about how to encode inductive biases into deep-nets, *e.g.*, by using rectified linear units [4], normalization [5], skip connections [6], encoder-decoder structures [7], *etc*. However, importantly, developed deep-net architectures are not guaranteed to solve a given task. There is a chance that they may instead exploit dataset biases as illustrated in Fig. 1a.

This concern is surely in part due to non-robust training techniques, and a plethora of methods improve classifier robustness [8–10]. However, datasets play an important role in controlling the extracted bias as well. For instance, if correct answers in a question-answering task are significantly shorter than incorrect ones, classifier training should not use answer length as a cue. Although this seems reasonable, for audio-visual scene aware dialog, Schwartz et al. [11] find for example that in many cases the question alone is sufficient to generate a scene-aware dialog response, avoiding the need to look at the video. Hence, in order to assess the suitability of a classifier, we need to understand how much it relies on different data modalities.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

(a) Two models: one perceives the image (green), and the other only perceive the question (red).

(b) Progress of VQA-CP models.

Figure 1: Multi-modal datasets often have undesired biases: (a) To identify those biases we suggest the perceptual score as a new metric. It assesses the change in prediction when a model's input for some modalities is permuted during testing. If the classifier output remains identical despite permutation, a model doesn't perceive the modality. (b) Using the perceptual score we identify that recent progress of VQA models may not be entirely due to better reasoning.

To quantify how much a classifier relies on its different input modalities, we introduce the perceptual score. The perceptual score assesses the degree to which a model relies on a modality. To do so the perceptual score permutes the features of a modality across samples in the test set after the classifier was trained. If the classifier's performance drops to or below chance level, the perceptual score is high. This intuitively applies to single-modality models too: randomly permuting test data and labels after training results in chance-level classification accuracy.

Using the perceptual score, we find a surprisingly consistent trend across four popular datasets (VQA, VQA-CP, Visual Dialog, SocialIQ): recent, more accurate state-of-the-art multi-modal models for visual question-answering or visual dialog tend to perceive the visual data less than their predecessors (see Fig. 1b). This trend is concerning as answers are hence increasingly inferred from textual cues only. Using the perceptual score also helps to analyze model biases by decomposing the score into data subset contributions. For example, the perception of an image and question varies depending on the question type. None of the recent VQA-CP models showed high image perception scores for 'number'-type questions. A surprisingly low image perception score is obtained for the state-of-the-art model when confronted with 'yes/no' questions.

We hope the perceptual score spurs a discussion regarding the perceptiveness of multi-modal models and we also hope to encourage the community working on multi-modal classifiers to start quantifying perceptiveness of models.

Our contributions:

- We propose the Perceptual score, a simple yet effective method for assessing the perceptiveness of multi-modal models towards a modality.
- Our experiments span multiple datasets and models. We find that multi-modal models tend to ignore some modalities while taking shortcuts.
- Consequently, we investigate the sources of bias on popular multi-modal datasets such as VQA-CP and SocialIQ: We find that SocialIQ is biased by sentiment, and bias in the VQA-CP model results from shifting the training priors to more closely resemble those in the test set.

2   Related Work

The perceptual score assesses the degree to which a classifier relies on a particular input modality. This is related to studying datasets and their biases, methods which aim to reduce the biases captured by classifiers and work which studies the importance of features. We review all three areas next.

Datasets and bias: Data has been a central element for machine learning progress [12–14] in the last two to three decades. The ImageNet challenge [2] and the development of AlexNet [15] sparked the deep learning era. But as datasets grow, biases emerge which may go undetected for a long time. For

instance, the background in ImageNet can reveal information about the object class [16]. Also, with the increasing popularity of crowdsourcing systems like Amazon Mechanical Turk, many datasets are annotated in uncontrolled environments. Different annotators are hence injecting unknown socio-economic properties into dataset annotations [17]. Those dataset biases can be detrimental to the considered task. For instance, meticulously collected visual question answering (VQA) data [1] aims to provide a platform for exciting research to advance image-language understanding. However, it is non-trivial to remove biases from this type of data. Indeed, it was reported that the question solely is sufficient to detect the correct answer [18], *i.e.*, no image information is required. In an attempt to fix this bias, the dataset was re-annotated [19], or the train and test split were re-organized [20]. Similarly, Schwartz et al. [11] reported that in Audio-visual-scene-aware dialog (AVSD) [21], the question cue is often stronger, making the desired video and sound reasoning implausible or unnecessary. Likewise, SNLI [22], aims to determine the correctness of a hypothesis given a premise. However, Gururangan et al. [23] point out that an internal bias exists: linguistic features not related to the premise correlate with the label. Further, the Story Cloze [24] dataset permits to develop models which estimate the correct ending of a story. Schwartz et al. [25] show that, for this dataset, length alone is a powerful feature to determine the correct ending.

Recently, Zadeh et al. [26] proposed SocialIQ, a dataset intended to reason about social situations in videos, specifically, emotion detection in a social situation. In this dataset, given a video and a question, the correct social situation should be recognized, *e.g.*, "The man is upset because he is being insulted." We show that it is easy to pick the correct statement using only the text data. This is possible because the statement's correctness often correlates with the statement's sentiment. Again, much like for VQA and AVSD, image information doesn't seem to be necessary for reasonably accurate performance. Hence, biases exist which permit to 'address the dataset' without addressing the task. For SocialIQ, we attribute these biases to the fact that social reasoning is considered difficult, even for humans. Hence an annotator's expertise is particularly important.

Importantly, going forward, we think it is elusive that we will be able to create unbiased datasets. We hence need techniques to automatically measure biases. In this work, we provide a mechanism that permits to do this for any dataset.

Methods to reduce bias: Several methods have been suggested to reduce bias from a dataset. Some techniques require prior knowledge of the biased variables, for instance, gender bias in vision is addressed by masking related features (*e.g.*, faces) [27–36]. Also, some techniques require access to the test set to re-balance it [37]. Additionally, various approaches were proposed for visual question answering [38–40]. These methods use a classifier trained only on the question modality to regularize bias directly. Cadene et al. [38] suggest to mask a model's softmax prediction with a softmax prediction of a subset classifier trained on the question modality. Clark et al. [39] use an ensemble method of a full classifier paired with a question subset classifier using products of experts [41]. Common to all those approaches is the use of a subset classifier to indicate reliance on subset of the data. In contrast, we assess the perceptiveness of the original model based on permutations of subset of data.

Feature importance methods: Also relevant to our work are techniques that measure feature-importance. These works generally focus on understanding why a model made a particular prediction. To this end, Ribeiro et al. [42] introduce LIME, a local explanation method that approximates a linear explanation model around a given example. Later, Shrikumar et al. [43] proposed DeepLift specifically for deep net models. Lundberg and Lee [44] introduced SHapley Additive exPlanations (SHAP), a method to estimate feature importance using an approximation of the features Shapley values. LIME assumes that the local model is linear, while SHAP does not have any such assumptions. Lundberg and Lee [44] show a connection between DeepLIFT and Shapely values introduced as 'Deep SHAP.' Each of those techniques concentrates on the importance of features, whereas we focus on the importance of a modality as a whole.

3 The Perceptual Score

The *perceptual score* quantifies the degree to which a model relies on the input data or a subset thereof. Said differently, the perceptual score assesses the importance of data or a subset of the data for a model's result. For instance, if a model answers questions about an image without using cues extracted from the image modality, the model does not perceive the image modality. In this case we

124 want the perceptual score for the image modality to be lower than that of a model which relies heavily
125 on the image modality.

126 We believe that reporting the perceptual score of a model in addition to its accuracy is particularly
127 important in a multi-modal setting. As a community we are developing increasingly complex models.
128 However, to date we know very little about what parts of the data these models rely on. We think
129 this lack in our understanding is due to a missing easy way to quantify how much a model relies on
130 available data modalities. To rectify this we hope to illustrate that a simple yet intuitive score like the
131 proposed perceptual score is very useful and easy to report too.

132 The following sections describe the perceptual score of a modality for a given model and dataset.

3.1 Setup

134 Let $\mathcal{D} = \{(x_1, y_1), \ldots, (x_{|\mathcal{D}|}, y_{|\mathcal{D}|})\}$ denote the test set data, where $|\mathcal{D}|$ refers to the number of
135 samples in the dataset. Each sample is a pair consisting of the input data $x_i \in \mathcal{X}$ and its corresponding
136 label $y_i \in \mathcal{Y}$. Here, $\mathcal{Y}$ is a finite set of possible classes. In multi-modal datasets which we
137 consider here, the data x_i can be separated naturally into different parts. For instance, in the
138 SocialIQ task, we can partition the data into video-related, question-related and answer-related
139 parts. Formally, let $\mathcal{M} = \{M_1, \ldots, M_{|\mathcal{M}|}\}$ be a set of modalities of size $|\mathcal{M}|$, $e.g.$, the video-, the
140 question- and the answer-modality. We partition the data x_i into its modalities using a set notation,
141 $i.e.$, $x_i = \{x_i^{M_1}, \ldots, x_i^{M_{|\mathcal{M}|}}\}$. We use $x_i^{\{M_1, M_2\}} = \{x_i^{M_1}, x_i^{M_2}\}$ to refer to the first two modalities,
142 $i.e.$, the superscript can be a set.

3.2 Perceptual Score of a Data Modality

144 The perceptual score $P_{f,\mathcal{D}}(M_m)$ of a model $f : \mathcal{X} \to \mathcal{Y}$ towards modality M_m on data $\mathcal{D}$ is defined
145 as

$$P_{f,\mathcal{D}}(M_m) = \frac{1}{Z} \left(\mathbb{E}_{(x,y)\sim\mathcal{D}}[P_{f,x,y}(M_m)] \right), \tag{1}$$

146 $i.e.$, as the normalized expectation of sample perceptual scores $P_{f,x,y}(M_m)$. Here, Z indicates the
147 normalization factor, which can either be determined by the dataset alone ($i.e.$, $Z = Z_{\mathcal{D}}$) or based on
148 both the dataset and the model ($i.e.$, $Z = Z_{f,\mathcal{D}}$). We discuss the normalization in Sec. 3.2.2.

149 The sample perceptual score $P_{f,x,y}(M_m)$ aims to measure the degree to which a model $f : \mathcal{X} \to \mathcal{Y}$
150 relies on a modality M_m for prediction of sample $x \in \mathcal{X}$. To do so we define the sample perceptual
151 score for modality $M_m \in \mathcal{M}$ as the normalized difference between the accuracy of a model which
152 uses all data modalities, and the accuracy of a model which doesn't use modality M_m for prediction,
153 $i.e.$, as

$$P_{f,x,y}(M_m) = \text{Acc}_{f,x,y}(\mathcal{M}) - \text{Acc}_{f,x,y}(\mathcal{M} \setminus \{M_m\}). \tag{2}$$

154 Here, $\mathcal{M} \setminus \{M_m\}$ is an operator that removes the influence of modality M_m from the set of all
155 modalities $\mathcal{M}$. We define this operation formally in Sec. 3.2.1. Note, $\text{Acc}_{f,x,y}(\mathcal{M})$ refers to the
156 classical prediction accuracy of a dataset sample (x, y) for a given trained model f with $\mathcal{M}$ the set of
157 all modalities used for prediction, $i.e.$, $\text{Acc}_{f,x,y}(\mathcal{M}) = \mathbb{1}_{f(x^{\mathcal{M}})=y}$.

158 Intuitively, the sample perceptual score $P_{f,x,y}(M_m)$ is high if the accuracy of a model that does not
159 consider modality M_m for prediction is significantly smaller than the accuracy of a model which uses
160 all data modalities $\mathcal{M}$. Conversely, if the accuracy doesn't change, irrespective of whether modality
161 M_m is available or not, the model f doesn't perceive the modality M_m. Note that in cases where the
162 modality M_m irritates the model, the perceptual score can be negative.

163 In the following we discuss how to 'remove' a modality M_m from a model f (Sec. 3.2.1) and how to
164 compute the normalization constant Z (Sec. 3.2.2).

3.2.1 Removing Modality Influence

166 Removing a modality from a trained model is difficult since typical models entangle modalities and
167 compute high-order correlations. Ideally, we need a tool that minimizes the impact of one modality
168 while maintaining the other components' functionality. To achieve this, we study a permutation-based
169 approach, $i.e.$, we randomly permute the modality-related features among the test set data $\mathcal{D}$. We

think permutation is particularly useful for the perceptual score because it is hyper-parameter free. This ensures that the perceptual score defined in Eq. (1) is unambiguous.

Formally, to compute $\text{Acc}_{f,x,y}(\mathcal{M} \setminus \{M_m\})$ we don't use all modalities from data x_i. Instead, we use all modalities but M_m, *i.e.*, $x_i^{\mathcal{M} \setminus M_m}$ and append the data $x_j^{M_m}$ of modality M_m from another data point x_j. Hereby j is drawn uniformly from $\{1, \ldots, |\mathcal{D}|\}$, *i.e.*, from $\mathcal{U}(1, |\mathcal{D}|)$. Taken together we compute the accuracy via

$$\text{Acc}_{f,x,y}(\mathcal{M} \setminus \{M_m\}) = \mathbb{E}_{j \sim \mathcal{U}(1,|\mathcal{D}|)}[\mathbb{1}_{f(\{x^{\mathcal{M} \setminus M_m}, x_j^{M_m}\})=y}]. \tag{3}$$

In the following we discuss how to compute the normalization Z employed in Eq. (1).

3.2.2 Normalization

Normalization enables comparability. For this, normalization aims for consistency of the perceptual score between models designed for the same task and between models designed for different tasks. Two types of normalization are useful to consider: 1) a *task-normalization*, which enables a more meaningful comparison of the perceptual score across different tasks; and 2) a *model-normalization* that enables a meaningful comparison of the perceptual score within the same task. We think models should be analyzed with both kinds of normalization in mind.

Task-normalization: The degree of difficulty of the task matters when comparing a model's perceptual score for a modality. Without normalization, the comparison of models designed for different tasks is inconsistent. For instance, if a task is relatively easy, removing a modality won't significantly affect the accuracy. This would result in a perceptual score close to zero, which isn't compelling because, in this case, even a marginal reduction in performance might be significant.

To incorporate the difficulty of a task we compare the perfect accuracy to the accuracy of a majority vote classifier. We note that the majority vote classifier always predicts the majority class of the employed training set. We use $\widehat{\text{Acc}}_{\mathcal{D}}$ to refer to the accuracy of the majority vote classifier evaluated on the test set $\mathcal{D}$ and compute the normalization factor via

$$Z_{\mathcal{D}} = 1 - \widehat{\text{Acc}}_{\mathcal{D}}. \tag{4}$$

Intuitively, the normalization factor is the gap between the perfect accuracy (*i.e.*, 1) and the accuracy of the majority vote classifier, *i.e.*, $\widehat{\text{Acc}}_{\mathcal{D}}$. We note that this normalization may result in perceptual score higher than one since the majority vote may be superior to the permuted accuracy. However, this case is unlikely in practice and did not occur in any of our experiments. Notably, this normalization is limited by the fact that the model accuracy is not considered, as we will discuss next.

Model-normalization: The performance of a model is an important factor. Suppose for two different classifiers permutation of a modality results in the same accuracy as that of the majority vote classifier. As a result, the initially stronger model will attain a higher perceptual score. This property can be desirable since one may want the perceptual score to reflect both perception and the ability to address a task. However, in this case the perceptual score does not solely reflect the degree to which a model considers a particular modality for decision making. Instead the perceptual score for a modality would be conflated with the model's accuracy.

To obtain a score which solely reflects the degree to which a model considers a particular modality, we normalize by the model's accuracy. Formally, we normalize via

$$Z_{\mathcal{D},f} = \mathbb{E}_{(x,y) \sim \mathcal{D}}[\text{Acc}_{f,x,y}(\mathcal{M})]. \tag{5}$$

4 Evaluation of Perceptual Scores

In the following, we assess the perceptual score using popular multi-modal datasets. Specifically, in Sec. 4.1, we study visual question answering (VQA, VQA-CP). We examine video social reasoning (*i.e.*, SocialIQ) in Sec. 4.2. In Sec. 4.3, we assess visual dialog models. Our analysis shows that state-of-the-art models exploit biases that haven't been documented. We study the bias by investigating samples with low perceptual scores and discover its cause.

Experimental setup: We train each model with five different seeds and report the mean accuracy. We compute the perceptual score based on five permutations per sample and report mean along with the standard deviations. For all the models, we used the official implementations.

Table 1: Accuracy and perceptual scores on VQAv2 and VQA-CP for different baselines and question types: number (Num), yes/no (Y/N), and other. We report the accuracy ($Acc_{\mathcal{M}}$), the accuracy after removing a modality's influence ($Acc_{\mathcal{M}\setminus\{V\}}$, $Acc_{\mathcal{M}\setminus\{Q\}}$), the perceptual score without normalization (P_V, P_Q), the perceptual score with task normalization ($P_V/Z_{\mathcal{D}}$, $P_Q/Z_{\mathcal{D}}$), the perceptual score with model normalization ($P_Q/Z_{\mathcal{D},f}$, $P_V/Z_{\mathcal{D},f}$), and majority-vote accuracy ($\widehat{Acc_{\mathcal{D}}}$). Means and standard deviations are provided.

| Model | Q. Type | $Acc_{\mathcal{M}}$ | Image | | | | Question | | | | $\widehat{Acc_{\mathcal{D}}}$ |
			$Acc_{\mathcal{M}\setminus\{V\}}$	P_V	$P_V/Z_{\mathcal{D}}$	$P_V/Z_{\mathcal{D},f}$	$Acc_{\mathcal{M}\setminus\{Q\}}$	P_Q	$P_Q/Z_{\mathcal{D}}$	$P_Q/Z_{\mathcal{D},f}$	
					VQAv2						
LXMERT	All	68.97	36.46	32.51	47.40 ± 0.40	47.16 ± 0.37	27.41	41.56	60.60 ± 0.38	60.26 ± 0.38	31.42
LMH	All	54.33	27.90	26.43	38.54 ± 0.32	48.64 ± 0.29	22.82	31.51	45.94 ± 0.30	57.99 ± 0.31	31.42
BAN	All	65.67	35.09	30.58	44.59 ± 0.38	46.56 ± 0.39	28.25	37.43	54.57 ± 0.36	56.99 ± 0.32	31.42
BUTD	All	63.09	34.38	28.71	41.86 ± 0.36	45.52 ± 0.38	28.78	34.31	50.03 ± 0.35	54.33 ± 0.34	31.42
LXMERT	Num	52.73	14.55	38.18	47.14 ± 0.28	72.40 ± 0.00	13.04	39.69	49.01 ± 0.25	49.00 ± 0.25	19.01
LMH	Num	37.58	15.64	21.94	27.09 ± 0.26	58.38 ± 0.26	13.75	23.82	29.41 ± 0.22	63.40 ± 0.27	19.01
BAN	Num	48.62	18.55	30.07	37.13 ± 0.28	61.84 ± 0.29	16.07	32.55	40.19 ± 0.24	66.95 ± 0.27	19.01
BUTD	Num	42.46	21.04	21.41	26.44 ± 0.25	50.47 ± 0.24	18.39	24.06	29.71 ± 0.22	56.29 ± 0.26	19.01
LXMERT	Other	60.86	16.81	44.05	45.63 ± 0.27	72.37 ± 0.27	3.47	57.39	59.45 ± 0.08	94.30 ± 0.09	3.47
LMH	Other	54.29	13.72	40.58	42.04 ± 0.21	74.73 ± 0.21	4.30	49.99	51.79 ± 0.09	92.08 ± 0.08	3.47
BAN	Other	56.99	16.37	40.62	42.08 ± 0.25	71.27 ± 0.25	4.17	52.82	54.72 ± 0.10	92.68 ± 0.06	3.47
BUTD	Other	54.99	14.29	40.70	42.16 ± 0.22	73.93 ± 0.22	4.53	50.46	52.27 ± 0.09	91.74 ± 0.07	3.47
LXMERT	Y/N	85.30	64.58	20.72	41.02 ± 0.40	24.29 ± 0.32	63.84	21.46	42.49 ± 0.32	25.16 ± 0.38	49.49
LMH	Y/N	60.24	50.80	9.43	18.68 ± 0.33	15.66 ± 0.42	50.29	9.94	19.68 ± 0.29	16.50 ± 0.39	49.49
BAN	Y/N	83.03	65.44	17.59	34.82 ± 0.36	21.18 ± 0.29	64.09	18.93	37.48 ± 0.33	22.80 ± 0.32	49.49
BUTD	Y/N	80.94	65.42	15.52	30.73 ± 0.32	19.27 ± 0.33	64.24	16.69	33.05 ± 0.30	20.63 ± 0.25	49.49
					VQA-CP						
CSS	All	57.89	36.46	21.43	26.43 ± 0.41	37.01 ± 0.27	7.93	49.96	61.61 ± 0.21	86.30 ± 0.31	18.91
RMFE	All	54.20	29.91	24.29	27.11 ± 0.34	47.17 ± 0.31	7.65	46.55	51.95 ± 0.17	55.91 ± 0.24	10.40
LMH	All	52.23	27.14	25.09	28.00 ± 0.32	45.35 ± 0.24	7.13	45.10	50.33 ± 0.14	54.08 ± 0.27	10.40
CSS	Num	51.34	44.50	6.84	7.20 ± 0.38	13.32 ± 0.08	13.04	38.30	40.34 ± 0.29	74.60 ± 0.31	5.06
RMFE	Num	44.03	37.25	6.77	7.13 ± 0.33	18.84 ± 0.33	34.05	9.97	10.51 ± 0.30	26.51 ± 0.33	5.06
LMH	Num	37.40	30.35	7.05	7.43 ± 0.28	15.39 ± 0.28	27.48	9.92	10.45 ± 0.25	22.65 ± 0.28	5.06
CSS	Other	46.48	10.12	36.36	37.57 ± 0.15	78.22 ± 0.15	4.12	42.36	43.77 ± 0.16	91.13 ± 0.14	3.23
RMFE	Other	45.97	10.08	35.89	37.09 ± 0.17	77.94 ± 0.18	4.15	41.82	43.22 ± 0.11	91.14 ± 0.21	3.23
LMH	Other	46.10	10.17	35.93	37.13 ± 0.18	78.07 ± 0.19	4.08	42.02	43.42 ± 0.11	90.96 ± 0.23	3.23
CSS	Yes/No	83.11	82.52	0.59	0.71 ± 0.04	3.16 ± 0.04	43.84	39.27	100.0 ± 0.00	47.25 ± 0.33	64.46
RMFE	Yes/No	74.47	62.49	11.98	18.58 ± 0.31	17.99 ± 0.31	59.31	15.16	23.51 ± 0.28	21.68 ± 0.31	35.52
LMH	Yes/No	73.75	60.49	13.27	20.58 ± 0.32	16.08 ± 0.32	57.76	16.00	24.81 ± 0.29	20.35 ± 0.32	35.52

4.1 Visual Question Answering

The visual question answering task reasons about an image given a question. We use the VQAv2 dataset [19], which contains 443,757 image-question pairs in the train set and 214,354 in the validation set. We also assess the perceptiveness of models trained on Visual Question Answering: Changing Priors (VQA-CP) data [20], which was released after several studies suggested that VQAv2 models heavily rely on answer priors. For instance, 'how many' questions are typically answered with '2.' To overcome this shortcoming, VQA-CP suggested a new train-test-split. As a result, the train and test sets have different prior distributions for each question type. The new split consists of 438,183 training samples, and 219,928 samples for validation.

Baselines: We use four baselines for VQAv2: 1) BUTD [45], an early competitive approach that used detector-based features pre-trained on VisualGenome [46]; 2) BAN [47], a baseline that uses an effective multi-modal bilinear attention; 3) LMH [39], originally crafted for VQA-CP, this approach removes superficial question patterns; and 4) LXMERT [48] a large-scale Transformer-based model that is pre-trained with large amounts of image-text pairs.

4.1.1 Quantitative Analysis

In Tab. 1, we provide the perceptual score and the accuracy for different baselines and questions. We start by analyzing the perceptual scores of the vision and language modalities. In most cases, models perceive the question better (i.e., $P_Q > P_V$). Studying the accuracy, LXMERT has the highest accuracy (68.97%). In contrast, LMH, which reduces the reliance on question priors, achieves the lowest accuracy (54.33%). However, the model-normalized perceptual score for the visual modality ($P_V/Z_{\mathcal{D},f}$) suggests: LMH perceives image data similarly to other models. Studying the

Table 2: Proportion of yes/no ratios for different kinds of questions. The initial token categorizes questions. We report proportion in the train set, the test set, and the model prediction. '# Train' indicates the number of samples in the train set, '# Test' is the number of samples in the test set.

Token	Model	Predicted Yes	Predicted No	Test Yes	Test No	Train Yes	Train No	# Test	# Train
'has'	CSS	1.0	0.0	0.88	0.12	0.5	0.5	1330	2784
	LMH	0.47	0.53	0.88	0.12	0.0	1.0	1330	1392
'can'	CSS	0.94	0.06	0.65	0.35	0.5	0.5	2664	2670
	LMH	0.38	0.62	0.65	0.35	0.0	1.0	2664	1235
'is a'	CSS	0.01	0.99	0.0	1.0	0.5	0.5	305	610
	LMH	0.37	0.63	0.0	1.0	0.89	0.11	305	305
'do'	CSS	0.99	0.01	0.9	0.1	0.5	0.5	1328	10844
	LMH	0.42	0.58	0.9	0.1	0.39	0.61	1328	5422

task normalized perceptual score for the visual modality ($P_V/Z_\mathcal{D}$) suggests: despite the high accuracy on 'Y/N' questions, their image and question perceptual scores are very low, *i.e.*, models mostly ignore the visual data and rely on priors.

Next, we show metrics for VQA-CP, a variant designed to reduce bias caused by answer priors. We compare different models on all the data by analyzing the model-normalized perceptual score for both visual and question modalities ($P_V/Z_{\mathcal{D},f}$ and $P_Q/Z_{\mathcal{D},f}$). Interestingly, the state-of-the-art model, CSS, has the lowest image perceptual score (37.01%) and the highest question perceptual score (86.30%), suggesting that the question modality may serve as a shortcut to answer without perceiving the image. Further, by analyzing the different question types via the task-normalized score ($P_V/Z_\mathcal{D}$), we note that CSS has a perceptual score for the image modality of only 3.6% for 'Y/N' questions. One possible explanation: CSS generates new samples, which in turn alter priors. We further investigate this bias next.

4.1.2 Bias Analysis for CSS

The Counterfactual Samples Synthesizing (CSS) model produces counterfactual training samples by masking either critical objects in images or words in questions, and by assigning different ground-truth answers. Our perceptiveness study above shows that the CSS model has a significantly lower perceptual score for the visual modality, despite being state-of-the-art on VQA-CP with a substantial accuracy gap of 6.5% over LMH. Why?

The first thing to note: CSS generates new samples which may shift prior distributions. Recalling that VQA-CP was introduced to prevent benefiting from answer priors in VQAv2 reveals a potential reason for the improvements of CSS.

Use of the sample perceptual score permits a more in-depth analysis. In Tab. 2, we identify popular question start tokens with low sample perceptual scores for the visual modality ('do,' 'has,' 'can,' 'is a'). We further examine their prediction accuracy using both CSS and LMH. We find that the proportion of 'yes' and 'no' answers between the train and the test set differ: the yes answer is correct for 88% of the questions in the test set starting with 'has,' while the yes answer is *never* correct for the corresponding training set questions. For CSS, counterfactual samples, however, produce equal proportions. As a result, CSS seemingly alleviates the prior inconsistency and adjusts the majority of its predictions to 'yes,' which more closely resembles the test set.

Use of the perceptual scores hence permits to hypothesize: improvements in CSS can be attributed to a shifted prior distribution instead of a complex counterfactual data-manipulation. To test this hypothesis we train the LMH model using samples obtained from CSS training. Importantly, we did not modify the image or the question. *Without even any changes to the input*, we obtain an accuracy of 57.54%, only 0.3% lower than CSS and within standard deviation.

4.2 Video Social Reasoning

SocialIQ [26] proposes an unconstrained benchmark, specifically designed to understand social situations. More concretely, given an input tuple of a video, a question, and an answer, the task is to

Table 3: Accuracy and perceptual scores on SocialIQ. For different modalities (1st column), we report the accuracy ($\text{Acc}_{\mathcal{M}}$), the accuracy after removing the modality's influence ($\text{Acc}_{\mathcal{M}\setminus\{M\}}$), the perceptual score without normalization (P_M), the perceptual score with task normalization ($P_M/Z_{\mathcal{D}}$), the perceptual score with model normalization ($P_M/Z_{\mathcal{D},f}$), and the majority-vote accuracy ($\widehat{\text{Acc}_{\mathcal{D}}}$).

Modality M	Model	$\text{Acc}_{\mathcal{M}}$	$\text{Acc}_{\mathcal{M}\setminus\{M\}}$	P_M	$P_M/Z_{\mathcal{D}}$	$P_M/Z_{\mathcal{D},f}$	$\widehat{\text{Acc}_{\mathcal{D}}}$
Answer	Baseline	64.84	56.73	8.11	18.92 ± 0.13	12.51 ± 0.03	57.14
	FGA	67.38	57.11	10.27	23.96 ± 0.21	15.24 ± 0.10	57.14
Question	Baseline	64.84	64.32	0.52	1.21 ± 0.02	0.80 ± 0.03	57.14
	FGA	67.38	65.19	2.19	5.11 ± 0.11	3.25 ± 0.08	57.14
Video	Baseline	64.84	63.79	1.05	2.45 ± 0.05	1.62 ± 0.03	57.14
	FGA	67.38	64.42	2.96	6.91 ± 0.16	4.39 ± 0.15	57.14
-	NLTK-Sentiment	66.70	56.14	11.18	26.08 ± 0.19	16.36 ± 0.09	57.14
-	Answer-Only	68.65	57.29	11.39	26.57 ± 0.21	16.59 ± 0.06	57.14

Question: How does the person in the middle feel about the system?
Answer: The person in the middle is confused
Ground Truth: False
NLTK sentiment: Neutral

Question: How does the audience react when they end the phone call?
Answer: The audience cheers.
Ground Truth: True
NLTK sentiment: Positive

Question: What is conveyed by the posture of the two girls?
Answer: They are hostile and unfriendly
Ground Truth: False
NLTK sentiment: Negative

Figure 2: SocialIQ data samples. On the left, we show a sample with a high perceptual score towards video data. Neither a positive nor a negative sentiment is evident in this sample. Hence, the video is required for prediction. We illustrate two samples (marked with a red border) that received a low perceptual score. There is a sentiment-based correlation between the label and the answer in these samples. For simplicity, we highlight with red color words that exhibit sentiment.

predict whether the answer is correct or not. The videos were collected from YouTube and annotated by students. The dataset is split into 37,191 training samples, and 5,320 validation set samples.

Baseline: We were able to reproduce the SocialIQ baseline [26] and achieve an accuracy of 64.84% using all feature modalities during training. In fact, we achieved an accuracy of 67.38% by changing the baseline's model to FGA [49] and by using GloVe [50] instead of BERT features [51].

4.2.1 Quantitative Analysis

In Tab. 3 we show scores for different metrics. The task-normalized perceptual scores ($P_M/Z_{\mathcal{D}}$) for different modalities M (1st column) of FGA and the baseline reveals heavy reliance on the answer modality, and low dependence on the video modality (*i.e.*, 15.24 *vs.* 3.25). To verify that the answer is indeed the only important modality, we train a classifier using *only* the answer modality and observe: we can surpass the original paper's baseline by 4% when *only* using answer features, achieving 68.65% accuracy. Again, the perceptual score helped us understand shortcomings of a model. Upon analyzing the bias source, we observe a sentiment bias, which we discuss next.

4.2.2 Bias Analysis for SocialIQ

Assessing samples with low sample perceptual scores can reveal biases. Our study suggests that the labels correlate strongly with the sentiment. In Fig. 2, we marked with a red border two videos with a low sample perceptual score for the video modality. Studying those and similar samples we find: 1) when the answer is True, the answer has positive sentiment; 2) in contrast, when the answer is False, the answer contains words with negative connotation (*e.g.*, 'hostile,' 'unfriendly').

We hypothesize: successful prediction of the answer by just looking at the answer modality for SocialIQ data is due to sentiment-biased annotations. To validate this hypothesis, we use an off-the-shelf sentiment classifier from the NLTK package [52]. When applied to SocialIQ *without any*

Table 4: Perceptual scores on VisDial v1.0. We show that the perceptual score can be computed using metrics other than accuracy (*i.e.*, MRR and NDCG).

Modality M	Model	MRR						NDCG					
		$MRR_{\mathcal{M}}$	$MRR_{\mathcal{M}\setminus\{M\}}$	P_M	$P_M/Z_{\mathcal{D}}$	$P_M/Z_{\mathcal{D},f}$	$\widetilde{MRR}_{\mathcal{D}}$	$NDCG_{\mathcal{M}}$	$NDCG_{\mathcal{M}\setminus\{M\}}$	P_M	$P_M/Z_{\mathcal{D}}$	$P_M/Z_{\mathcal{D},f}$	$\widetilde{NDCG}_{\mathcal{D}}$
Question	LS (CE)	52.21	32.48	19.73	29.11 ± 0.02	37.79 ± 0.03	32.22	75.24	20.35	54.89	73.86 ± 0.04	72.95 ± 0.03	25.68
	LS	69.00	47.96	21.04	31.04 ± 0.03	30.49 ± 0.03	32.22	64.89	23.92	40.97	55.13 ± 0.02	63.14 ± 0.01	25.68
	FGA	66.14	32.23	33.91	50.03 ± 0.02	51.26 ± 0.03	32.22	56.00	30.74	25.26	33.99 ± 0.02	45.11 ± 0.02	25.68
Image	LS (CE)	52.21	34.94	17.27	25.48 ± 0.02	33.08 ± 0.02	32.22	75.24	57.45	17.79	23.94 ± 0.02	23.64 ± 0.03	25.68
	LS	69.00	52.06	16.94	24.99 ± 0.01	24.55 ± 0.03	32.22	64.89	51.50	13.39	18.02 ± 0.01	20.63 ± 0.03	25.68
	FGA	66.14	52.15	14.00	20.65 ± 0.01	21.16 ± 0.02	32.22	56.00	46.73	9.27	9.27 ± 0.03	16.55 ± 0.02	25.68
Caption	LS (CE)	52.21	52.18	0.03	0.00 ± 0.00	0.06 ± 0.00	32.22	75.24	75.19	0.05	0.07 ± 0.00	0.07 ± 0.01	25.68
	LS	69.00	69.00	0.00	0.00 ± 0.00	0.00 ± 0.00	32.22	64.89	64.89	0.00	0.00 ± 0.00	0.00 ± 0.00	25.68
	FGA	66.14	64.93	1.21	1.79 ± 0.02	1.83 ± 0.02	32.22	56.00	55.32	0.68	0.92 ± 0.01	1.22 ± 0.01	25.68

training, we obtain a remarkable answer prediction accuracy of 66.7%. This matches our reported result of 68.65% quite reasonably and outperforms the SocialIQ baseline [26].

4.3 Visual Dialog

The visual dialog task encourages models to ask *and* answer questions about visual input. Notably, each dialog-interaction employs many modalities (*e.g.*, image, question, caption, dialog-history). We show our results on the VisDial v1.0 dataset, where 123,287 images are used for training, 2,000 images for validation, and 8,000 images for testing [53]. Each image is associated with ten questions, and each question has 100 corresponding answer candidates.

Instead of accuracy $Acc_{f,x,y}(\mathcal{M})$, here, we use ranking-based metrics as the Visual Dialog dataset primarily uses two metrics: MRR and NDCG. In short, the MRR metric examines the rank of a single ground-truth response (*i.e.*, sparse annotations), while the NDCG metric measures the cumulative gain in the case of multiple correct answers (*i.e.*, dense annotations). We computed the majority ranking based on answer frequency in the train set. See appendix for more.

Baselines: We use two baselines for VisDial v1.0: 1) FGA [49], an attention unit inspired from graphical models that infers an attention map for each modality; and 2) LS [54], which pre-trains on related vision-language datasets, *e.g.*, Conceptual Captions and Visual Question Answering [1, 55]. We also report LS (CE), which finetunes on the dense annotations, at the expense of MRR performance.

4.3.1 Quantitative Analysis

In Tab. 4, we show the perceptual scores for different modalities (*i.e.*, M), and for two metrics: MRR and NDCG. We find: 1) using the MRR metric, the model-normalized perceptual score for the question modality of FGA is relatively high compared to LS (*i.e.*, 51.26% *vs.* 30.49%). However, when we employ the NDCG metric, the LS model perceives the question better (*i.e.*, 63.14% *vs.* 45.11%). 2) analyzing the only model optimized for NDCG, *i.e.*, LS (CE), reveals: When analyzed using the NDCG metric, the model-normalized perceptual score for both image and question is significantly higher than for MRR. Interestingly, the LS (CE) model-normalized perceptual score for the image modality is on par with the other models when we use the MRR metric. However, the question perceptual score is low, which suggests the reason for the low MRR performance may be related to the low utilization of the question. Finally, we note that all models, on both metrics, seem to ignore the caption, which suggests caption information is redundant.

5 Conclusion

We introduced the perceptual score of a multi-modal classifier towards a data modality. The perceptual score assesses a classifier's perceptiveness of a modality and reveals exciting insights if analyzed carefully. We hope that this is demonstrated by our studies which reveal that 1) shifted prior distributions seam to help CSS achieve state-of-the-art results, 2) SocialIQ data exhibits a sentiment bias, and 3) Visual Dialog caption information appears less informative. We hope that researchers working on multi-modal models see the use of the perceptual score and will start to report the perceptual score in addition to classical accuracy metrics.

Limitations: We propose perceptual scores, a novel metric that conveys information about multi-modal classifiers. The two limitations we can see: 1) a small computational overhead; 2) a false sense of security. Perceptual scores don't alleviate the need to carefully study results. However we think the societal and scientific benefits of reporting this novel metric outweigh any concerns.

References

[1] Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C. Lawrence Zitnick, and Devi Parikh. VQA: Visual Question Answering. In *ICCV*, 2015. 1, 3, 9

[2] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009. 2

[3] Lin Tsung-Yi, Maire Michael, Belongie Serge, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. In *ECCV*, 2014. 1

[4] Vinod Nair and Geoffrey E. Hinton. Rectified linear units improve restricted boltzmann machines. In *ICML*, 2010. 1

[5] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015. 1

[6] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *CVPR*, 2016. 1

[7] Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. In *NeurIPS*, 2014. 1

[8] A. Liu and Brian Ziebart. Robust classification under sample selection bias. In *NeurIPS*, 2014. 1

[9] Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *JMLR*, 2014.

[10] Pierre Stock and Moustapha Cisse. Convnets and imagenet beyond accuracy: Understanding mistakes and uncovering biases. In *ECCV*, 2018. 1

[11] Idan Schwartz, Alexander G. Schwing, and Tamir Hazan. A simple baseline for audio-visual scene-aware dialog. In *CVPR*, 2019. 1, 3

[12] Yann Lecun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. In *Proceedings of the IEEE*, 1998. 2

[13] Sameer A. Nene, Shree K. Nayar, and Hiroshi Murase. Columbia object image library (coil-20). Technical report, Columbia, 1996.

[14] Erik F. Tjong Kim Sang and Fien De Meulder. Introduction to the CoNLL-2003 shared task: Language-independent named entity recognition. In *NAACL*, 2003. 2

[15] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*, 2012. 2

[16] C. Szegedy, Wei Liu, Yangqing Jia, P. Sermanet, S. Reed, D. Anguelov, D. Erhan, V. Vanhoucke, and A. Rabinovich. Going deeper with convolutions. In *CVPR*, 2015. 3

[17] M. Geva, Y. Goldberg, and J. Berant. Are we modeling the task or the annotator? an investigation ofannotator bias in natural language understanding datasets. In *EMNLP*, 2019. 3

[18] Allan Jabri, Armand Joulin, and Laurens van der Maaten. Revisiting visual question answering baselines. In *ECCV*, 2016. 3

[19] Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the V in VQA matter: Elevating the role of image understanding in Visual Question Answering. In *CVPR*, 2017. 3, 6

[20] Aishwarya Agrawal, Dhruv Batra, Devi Parikh, and Aniruddha Kembhavi. Don't just assume; look and answer: Overcoming priors for visual question answering. In *CVPR*, 2018. 3, 6

[21] Huda Alamri, Vincent Cartillier, Abhishek Das, Jue Wang, Anoop Cherian, Irfan Essa, Dhruv Batra, Tim K. Marks, Chiori Hori, Peter Anderson, Stefan Lee, and Devi Parikh. Audio-visual scene-aware dialog. In *CVPR*, 2019. 3

[22] Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. A large annotated corpus for learning natural language inference. In *EMNLP*, 2015. 3

[23] Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel Bowman, and Noah A. Smith. Annotation artifacts in natural language inference data. In *NAACL (Short Papers)*, 2018. 3

[24] Nasrin Mostafazadeh, Nathanael Chambers, Xiaodong He, Devi Parikh, Dhruv Batra, Lucy Vanderwende, Pushmeet Kohli, and James Allen. A corpus and cloze evaluation for deeper understanding of commonsense stories. In *NAACL*, 2016. 3

[25] Roy Schwartz, Maarten Sap, Ioannis Konstas, Leila Zilles, Yejin Choi, and Noah A. Smith. The effect of different writing tasks on linguistic style: A case study of the ROC story cloze task. In *CoNLL*, 2017. 3

[26] Amir Zadeh, Michael Chan, Paul Pu Liang, Edmund Tong, and Louis-Philippe Morency. Social-iq: A question answering benchmark for artificial social intelligence. In *CVPR*, 2019. 3, 7, 8, 9

[27] Mohsan S. Alvi, Andrew Zisserman, and Christoffer Nellåker. Turning a blind eye: Explicit removal of biases and variation from deep neural network embeddings. In *ECCV (Workshop)*, 2018. 3

[28] Shikha Bordia and Samuel R. Bowman. Identifying and reducing gender bias in word-level language models. In *NAACL (Workshop)*, 2019.

[29] Thomas Davidson, Debasmita Bhattacharya, and Ingmar Weber. Racial bias in hate speech and abusive language detection datasets. In *ACL*, 2019.

[30] Lisa Anne Hendricks, Kaylee Burns, Kate Saenko, Trevor Darrell, and Anna Rohrbach. Women also snowboard: Overcoming bias in captioning models. In *ECCV*, 2018.

[31] Julio Cezar Silveira Jacques, Cagri Ozcinar, Marina Marjanovic, Xavier Baró, Gholamreza Anbarjafari, and Sergio Escalera. On the effect of age perception biases for real age regression. *FG 2019*, 2019.

[32] Kimmo Kärkkäinen and Jungseock Joo. Fairface: Face attribute dataset for balanced race, gender, and age, 2019. URL https://arxiv.org/pdf/1908.04913.pdf.

[33] Byungju Kim, Hyunwoo Kim, Kyungsu Kim, Sungjin Kim, and Junmo Kim. Learning not to learn: Training deep neural networks with biased data. In *CVPR*, 2018.

[34] Tianlu Wang, Jieyu Zhao, Mark Yatskar, Kai-Wei Chang, and Vicente Ordonez. Balanced datasets are not enough: Estimating and mitigating gender bias in deep image representations. In *ICCV*, 2019.

[35] Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Gender bias in coreference resolution: Evaluation and debiasing methods. In *NAACL*, 2018.

[36] Ran Zmigrod, Sabrina J. Mielke, Hanna Wallach, and Ryan Cotterell. Counterfactual data augmentation for mitigating gender stereotypes in languages with rich morphology. In *ACL*, 2019. 3

[37] Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Men also like shopping: Reducing gender bias amplification using corpus-level constraints. In *EMNLP*, 2017. 3

[38] Remi Cadene, Corentin Dancette, Matthieu Cord, Devi Parikh, et al. Rubi: Reducing unimodal biases for visual question answering. In *NeurIPS*, 2019. 3

[39] Christopher Clark, Mark Yatskar, and Luke Zettlemoyer. Don't take the easy way out: Ensemble based methods for avoiding known dataset biases. In *EMNLP*, 2019. 3, 6

[40] Sainandan Ramakrishnan, Aishwarya Agrawal, and Stefan Lee. Overcoming language priors in visual question answering with adversarial regularization. In *NeurIPS*, 2018. 3

[41] Geoffrey E Hinton. Training products of experts by minimizing contrastive divergence. *Neural computation*, 2002. 3

[42] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Why should I trust you?: Explaining the predictions of any classifier. In *SIGKDD*, 2016. 3

[43] Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *ICML*, 2017. 3

[44] Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *NeurIPS*, 2017. 3

[45] Peter Anderson, Xiaodong He, Chris Buehler, Damien Teney, Mark Johnson, Stephen Gould, and Lei Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In *CVPR*, 2018. 6

[46] Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, Michael Bernstein, and Li Fei-Fei. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International journal of computer vision*, 2017. 6

[47] Jin-Hwa Kim, Jaehyun Jun, and Byoung-Tak Zhang. Bilinear attention networks. In *NeurIPS*, 2018. 6

[48] Hao Tan and Mohit Bansal. Lxmert: Learning cross-modality encoder representations from transformers. *EMNLP*, 2019. 6

[49] Idan Schwartz, Seunghak Yu, Tamir Hazan, and Alexander G. Schwing. Factor graph attention. In *CVPR*, 2019. 8, 9

[50] Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In *EMNLP*, 2014. 8

[51] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *NAACL*, 2019. 8

[52] Edward Loper and Steven Bird. Nltk: The natural language toolkit. In *ACL*, 2004. 8

[53] Abhishek Das, Satwik Kottur, Khushi Gupta, Avi Singh, Deshraj Yadav, José MF Moura, Devi Parikh, and Dhruv Batra. Visual dialog. In *CVPR*, 2017. 9

[54] Vishvak Murahari, Dhruv Batra, Devi Parikh, and Abhishek Das. Large-scale pretraining for visual dialog: A simple state-of-the-art baseline. *ECCV*, 2020. 9

[55] Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *ACL*, 2018. 9