Pareto-Optimal Diagnostic Policy Learning in Clinical Applications via Semi-Model-Based Deep Reinforcement Learning

Abstract

Dynamic diagnosis is desirable when medical tests are costly or time-consuming. In this work, we use reinforcement learning (RL) to find a dynamic policy that selects lab test panels sequentially based on previous observations, ensuring accurate testing at a low cost. Clinical diagnostic data are often highly imbalanced; therefore, we aim to maximize the F1 score instead of the error rate. However, the F_1 score cannot be written as a cumulative sum of rewards, which invalidates standard RL methods. To remedy this issue, we develop a reward shaping approach, leveraging properties of the F_1 score and duality of policy optimization, to provably find the set of all Pareto-optimal policies for budget-constrained F_1 score maximization. To handle the combinatorially complex state space, we propose a Semi-Model-based Deep Diagnosis Policy Optimization (SM-DDPO) framework that is compatible with end-to-end training and online learning. SM-DDPO is tested on diverse clinical tasks: ferritin abnormality detection, sepsis mortality prediction, and acute kidney injury diagnosis. Experiments with real-world data validate that SM-DDPO trains efficiently and identifies all Pareto-front solutions. Across all tasks, SM-DDPO is able to achieve state-of-the-art diagnosis accuracy (in some cases higher than conventional methods) with up to 85% reduction in testing cost.

1 Introduction

In clinical practice, physicians usually order multiple panels of lab tests on patients and their interpretations depend on medical knowledge and clinical experience. Each test panel is associated with certain financial cost. For lab tests within the same panel, automated instruments will simultaneously provide all tests, and eliminating a single lab test without eliminating the entire panel may only lead to a small reduction in laboratory cost (Huck & Lewandrowski, 2014). On the other hand, concurrent lab tests have been shown to exhibit significant correlation with each other, which can be utilized to estimate unmeasured test results (Luo et al., 2016). Thus, utilizing the information redundancy among lab tests can be a promising way of optimizing which test panel to order when balancing comprehensiveness and cost-effectiveness. The efficacy of the lab test panel optimization can be evaluated by assessing the predictive power of optimized test panels on supporting diagnosis and predicting patient outcomes.

We investigate the use of reinforcement learning (RL) for lab test panel optimization. Our goal is to dynamically prescribe test panels based on available observations, in order to maximize diagnosis/prediction accuracy while keeping testing at a low cost. It is quite natural that sequential test panel selection for prediction/classification can be modeled as a Markov decision process (MDP).

However, application of reinforcement learning (RL) to this problem is nontrivial for practical considerations. One practical challenge is that clinical diagnostic data are often highly imbalanced, in some cases with <5% positive cases (Khushi et al., 2021; Li et al., 2010; Rahman & Davis, 2013). In supervised learning, this problem is typically addressed by optimizing towards accuracy metrics suitable for unbalanced data. The most prominent metric used by clinicians is the F1 score, i.e., the harmonic mean of a prediction model's recall and precision, which balances type I and type II errors in a single metric. However, the F1 score is not a simple weighted error rate - this makes designing the reward function hard for RL. Another challenge is that, for cost-sensitive diagnostics, one hopes to view this as a multi-objective optimization problem and fully characterize the cost-accuracy tradeoff, rather than finding an ad-hoc solution on the tradeoff curve. In this work, we aim to provide a tractable algorithmic framework, which provably identifies the set of all Pareto-front policies and trains efficiently. Our main contributions are summarized as follows:

- We formulate cost-sensitive diagnostics as a multi-objective policy optimization problem. The goal is to find all optimal policies on the Pareto front of the cost-accuracy tradeoff.
- To handle severely imbalanced clinical data, we focus on maximizing the F_1 score directly. Note that F_1 score is a nonlinear, nonconvex function of true positive and true negative rates. *It cannot be formulated as a simple sum of cumulative rewards, thus invalidating standard RL solutions.* We leverage monotonicity and hidden minimax duality of the optimization problem, showing that the Pareto set can be achieved via a reward shaping approach.
- We propose a Semi-Model-based Deep Diagnostic Policy Optimization (SM-DDPO) method for learning the Pareto solution set from clinical data. Its architecture comprises three modules and can be trained efficiently by combing pretraining, policy update, and model-based RL.
- We apply our approach to real-world clinical datasets. Experiments show that our approach exhibits good accuracy-cost trade-off on all tasks compared with baselines. Across the experiments, our method achieves state-of-the-art accuracy with up to 80% reduction in cost. Further, SM-DDPO is able to compute the set of optimal policies corresponding to the entire Pareto front.

2 RELATED WORK

Reinforcement learning (RL) has been applied in multiple clinical care settings to learn optimal treatment strategies for sepsis Komorowski et al. (2018), to customize antiepilepsy drugs for seizure control Guez et al. (2008) etc. See survey Yu et al. (2021) for more comprehensive summary. Guidelines on using RL for optimizing treatments in healthcare has also been proposed around the topics of variable availability, sample size for policy evaluation, and how to ensure learned policy works prospectively as intended Gottesman et al. (2019). However, using RL for simultaneously reducing the healthcare cost and improving patient's outcomes has been underexplored.

Our problem of cost-sensitive dynamic diagnosis/prediction is closely related to feature selection in supervised learning. The original static feature selection methods, where there exists a common subset of features selected for all inputs, were extensively discussed Guyon & Elisseeff (2003), including filter models (e.g., variable ranking), wrapper approaches Kohavi & John (1997), as well as integration of the feature selection in the learning process by using ℓ1-norm and ℓ0-norm Bi et al. (2003); Weston et al. (2003; 2000). Dynamic feature selection methods He et al. (2012), also named as adaptive feature acquisition Contardo et al. (2016) or feature selection with budget Karayev et al. (2013), were then proposed to take the difference between inputs into account. Different subsets of features are selected with respect to different inputs. By defining certain information value of the features Fahy & Yang (2019); Bilgic & Getoor (2007), or estimating the gain of acquiring a new feature would yield Chai et al. (2004), these methods are able to select appropriate features in an adaptive way to balance the costs of the selected features and the learning quality.

Recently, reinforcement learning based approaches Ji & Carin (2007); Trapeznikov & Saligrama (2013); Janisch et al. (2019); Yin et al. (2020); Li & Oliva (2021); Nam et al. (2021) are also proposed to dynamically select features for prediction/classification. *All these related works are directly given, or pre-define a sum of rewards as objectives.* While our task of deriving the cost-F_1 Pareto front, or maximizing F_1 score under cost budget constraints, is much harder and cannot be expressed using pre-defined reward functions. Work Nam et al. (2021); Ji & Carin (2007); Yin et al. (2020) models the feature selection process as a partially observed Markov Decision Process (POMDP). Ji & Carin (2007) points out that POMDP solutions are hard to train and cannot handle continuous-valued observations. A similar approach is proposed by Janisch et al. (2019) using a deep Q learning method. In our approach, we use a modular network and a combination of various training schemes for more efficient RL. Trapeznikov & Saligrama (2013) ranks features in a prefixed order and only requires the agent to decide if it will add a next feature or stop. The prefixed ranked order makes the problem easier to solve, but it is suboptimal compared to fully dynamic policies.

3 PARETO-FRONT PROBLEM FORMULATION

3.1 MARKOV DECISION PROCESS (MDP) MODEL

We model the dynamic diagnosis/prediction process for a new patient as an episodic Markov decision process (MDP) $\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, R, \gamma, \xi)$. As illustrated in Figure 1, the state of a patient is described by $s = \mathbf{x} \odot M$, where $\mathbf{x} \in \mathbb{R}^d$ denotes d medical tests of a patient, $M \in \{0, 1\}^d$ is a binary mask indicating whether the entries of $\mathbf{x}$ are observed or missing. Let there be D test panels, whose union is the set of all d tests. The action set $\mathcal{A} = \{1, 2, \cdots, D\} \sqcup \{P, N\}$ contains two sets of actions – observation actions and prediction/diagnosis actions. At each stage, one can either pick an action $a \in \{1, 2, \cdots, D\}$ from any one of the available panels, indicating choosing a test panel a to observe,

which will incur a corresponding observation cost $c(a)$; Or one can terminate the episode by directly picking a prediction action $a \in \{P, N\}$, indicating diagnosing the patient as positive class (P) or negative class (N). A penalty will generated if the diagnosis does not match the ground truth y. An example of this process in sepsis mortality prediction is illustrated in Figure 1. We considers the initial distribution ξ to be patients with only demographics panel observed and discount factor $\gamma = 1$.

Figure 1: Illustration of the RL episodic structure.

3.2 Multi-Objective Policy Optimization Formulation

Let $\pi : \mathcal{S} \to \mathcal{A}$ be the overall policy, a map from the set of states to the set of actions. We optimize π towards two objectives:

● **Maximizing prediction accuracy.** Due to severely imbalanced data, we choose to maximize the F_1 score, denoted by $F_1(\pi)$, as a function of policy π. F_1 score measures the performance of the diagnosis by considering both type I and type II errors, which is defined as:

$$F_1(\pi) = \frac{\text{TP}(\pi)}{\text{TP}(\pi) + \frac{1}{2}(\text{FP}(\pi) + \text{FN}(\pi))} = \frac{2\text{TP}(\pi)}{1 + \text{TP}(\pi) - \text{TN}(\pi)}$$

where $\text{TP}(\pi), \text{TN}(\pi), \text{FP}(\pi), \text{FN}(\pi)$ are normalized true positive, true negative, false positive and false negative rates that sum up to 1. Remark that $\text{TP}(\pi), \text{TN}(\pi), \text{FP}(\pi), \text{FN}(\pi)$ can all be expressed as sum of rewards/costs over the MDP's state trajectories. *However, $F_1(\pi)$ is nonlinear with respect to the MDP's state-action occupancy measure, thus it cannot be expressed as any cumulative sum of rewards.*

● **Lowering cost**. Define the testing cost by $\text{Cost}(\pi) = \mathbb{E}^{\pi}[\sum_{t \geq 0} \sum_{k \in [D]} c(k) \cdot \mathbf{1}\{a_t = k\}]$, where $\mathbb{E}^{\pi}$ denotes expectation under policy π, $c(k)$ is the cost of panel k.

In this work, we hope to solve for cost-sensitive policies for all possible testing budget. In other words, we aim to find the cost-sensitive Pareto front as follows.

Definition 3.1 (Cost-F_1 Pareto Front of Multi-Objective Policy Optimization). *The Pareto front Π^* for cost-sensitive dynamic diagnosis/prediction is the set of policies such that*

$$\Pi^* = \cup_{B>0} \, \underset{\pi}{\text{argmax}}\{F_1(\pi) \text{ subject to } \text{Cost}(\pi) \leq B\} \tag{1}$$

Finding Π^* requires novel solutions beyond standard RL methods. Challenges are two-folded: **(1)** Even in the single-objective case, $F_1(\pi)$ is a nonlinear, non-concave function of $\text{TP}(\pi), \text{TN}(\pi)$. Although both $\text{TP}(\pi), \text{TN}(\pi)$ can be formulated as expected sum of rewards in the MDP, the F_1 score is never a simple sum of rewards. Standard RL methods do not apply to maximizing such a function. **(2)** We care about finding the set of all Pareto-optimal policies when there are two conflicting objectives, rather than an ad hoc point on the trade-off curve.

4 Finding Cost-F_1 Pareto Front via Reward Shaping

The F_1 score is a nonlinear and nonconvex function of true positive, true negative, false positive, false negative rates. It cannot be expressed by sum of rewards. This invalidates all existing RL methods even in the unconstrained case, creating tremendous challenges.

Despite the non-concavity and nonlinearity of F_1, we will leverage the mathematical nature of Markov decision process and properties of the F1 score to solve problem (1). In this section, we provide an optimization duality analysis and show how to find solutions to problem (1) via reward shaping and solving a reshaped cumulative-reward MDP.

Step 1: utilizing monotonicity of F_1 score To start with, we note that F_1 score is monotonically increasing in both TP and TN. Assume, for any given cost budget B, the optimal policy $\pi^*(B)$ achieves the highest F_1 score. Then $\pi^*(B)$ is also optimal to the following program:

$$\max_{\pi} \{\text{TN}(\pi) \text{ subject to } \text{Cost}(\pi) \leq B, \text{TP}(\pi) \geq \text{TP}(\pi^*(B))\},$$

indicating the Pareto front of F_1 score is a subset of

$$\Pi^* \subseteq \cup_{B>0, K\in[0,1]} \underset{\pi}{\mathrm{argmax}} \{\mathrm{TN}(\pi) \text{ subject to } \mathrm{Cost}(\pi) \leq B, \mathrm{TP}(\pi) \geq K\}. \tag{2}$$

Step 2: reformulation using occupancy measures Fix any specific pair (B, B'). Consider the equivalent dual linear program form Zhang et al. (2020) of the above policy optimization problem (2). It is in terms of the cumulative state-action occupancy measure $\mu : \Delta_{\mathcal{A}}^{\mathcal{S}} \to \mathbb{R}_{\geq 0}^{\mathcal{S} \times \mathcal{A}}$, defined as: $\mu^\pi(s, a) := \mathbb{E}^\pi \left[\sum_{t \geq 0} \mathbf{1}(s_t = s, a_t = a)\right], \forall s \in \mathcal{S}, a \in \mathcal{A}$. Then the program (2) is equivalent to:

$$\max_\mu \mathrm{TN}(\mu) \text{ subject to } \mathrm{Cost}(\mu) \leq B, \ \mathrm{TP}(\mu) \geq K, \ \sum_a \mu(s, a) = \sum_{s', a' \in [D]} \mu(s', a')P(s|s', a') + \xi(s), \forall s$$

where $\xi(\cdot)$ denotes initial distribution, and TP, TN and cost are reloaded in terms of occupancy μ as:

$$\mathrm{TP}(\mu) = \sum_{y=\mathrm{P}, a=\mathrm{P}} \mu(s, a), \ \mathrm{TN}(\mu) = \sum_{y=\mathrm{N}, a=\mathrm{N}} \mu(s, a), \ \mathrm{Cost}(\mu) = \sum_{k \in [D]} c(k) \cdot \sum_{s, a=k} \mu(s, a).$$

Step 3: utilizing hidden minimax duality The above program can be equivalently reformulated as a max-min program:

$$\max_\mu \min_{\lambda \geq 0, \rho \leq 0} \mathrm{TN}(\mu) + \lambda \cdot (\mathrm{TP}(\mu) - K) + \rho \cdot (\mathrm{Cost}(\mu) - B)$$

$$\text{subject to } \sum_a \mu(s, a) = \sum_{s', a' \in [D]} \mu(s', a')P(s|s', a') + \xi(s), \forall s.$$

Note the max-min objective is linear in terms of λ, ρ and μ. Thus, minimax duality holds, then we can swap the min and max to obtain the equivalent form:

$$\min_{\lambda \geq 0, \rho \leq 0} \max_\mu \mathrm{TN}(\mu) + \lambda \cdot (\mathrm{TP}(\mu) - K) + \rho \cdot (\mathrm{Cost}(\mu) - B)$$

$$\text{subject to } \sum_a \mu(s, a) = \sum_{s', a' \in [D]} \mu(s', a')P(s|s', a') + \xi(s), \forall s.$$

For any fixed pair of (λ, ρ), the inner maximization problem of the above can be rewritten equivalently into an unconstrained policy optimization problem: $\max_\pi \mathrm{TN}(\pi) + \lambda \cdot \mathrm{TP}(\pi) + \rho \cdot \mathrm{Cost}(\pi)$. This is finally a standard cumulative-sum MDP problem, with reshaped reward: reward $\rho \cdot c(t)$ for the action of choosing test panel t, reward λ for the diagnosis/prediction action and get a true positive, reward 1 for getting a true negative. Putting together three steps, we can show the following theorem. The full proof can be found in Appendix D.

Theorem 4.1. *The Cost-F_1 Pareto front defined in* (1) *is a subset of the collection of all reward-shaped solutions, given by*

$$\Pi^* \subseteq \overline{\Pi} := \cup_{\lambda \geq 0, \rho \leq 0} \underset{\pi}{\mathrm{argmax}} \{TN(\pi) + \lambda \cdot TP(\pi) + \rho \cdot Cost(\pi)\}.$$

Thus, to learn the full Pareto front, it suffices to solve a collection of unconstrained policy optimization problems with reshaped cumulative rewards.

5 METHOD

In this section, we propose a deep reinforcement learning pipeline for Pareto-optimal dynamic diagnosis policies. We use a modular architecture for efficient encoding of partially-observed patient information, policy optimization and reward learning.

5.1 ARCHITECTURE

Our Semi-Model-based Deep Diagnostic Policy Optimization (SM-DDPO) framework is illustrated in Figure 2. The complete dynamic testing policy π comprises three models: (1) a posterior state encoder for mapping partially-observed patient information to an embedding vector; (2) a state-to-diagnosis/prediction classifier which can be reviewed as a reward function approximator; (3) a test panel selector that outputs an action based on the encoded state. This modular architecture makes RL tractable via a combination of pre-training, policy update and model-based RL.

5.2 POSTERIOR STATE ENCODER

We borrowed the idea of imputation to map the partially observed patient information to a posterior embedding vector. In this work, we consider a flow-based deep imputer named *EMFlow*[1]. Given the

---

[1] The *EMFlow imputation method is originally proposed in Ma & Ghosh (2021) that maps the data space to a Gaussian latent space via normalizing flows. We give a more detailed discussion of this method in Appendix B.*

Figure 2: Dynamic diagnostic policy learning via semi-model-based proximal policy optimization. The full policy π comprises of three modules: posterior state encoder, classifier, and panel selector.

imputer $\text{Imp}_\theta(\cdot)$ parameterized by θ, the RL agent observes tests $\mathbf{x} \odot M$ and calculates $\text{Imp}_\theta(\mathbf{x} \odot M) \in \mathbb{R}^d$ as a posterior state encoder. Unlike conventional imputation, our posterior state encoder aims at resolving exponentially many possible missing patterns. Therefore, we pretrain it on unlabeled augmented data, constructed by repeatedly and randomly masking entries as additional samples.

5.3 END-TO-END TRAINING VIA SEMI-MODEL-BASED POLICY UPDATE

Training the overall policy using a standard RL algorithm alone (such as Q learning, or policy gradient) would suffer from the complex state and action spaces. To ease the heavy training, we design a semi-model-based *modular* approach to train the panel selector and classifier concurrently but in different manners:

• The classifier $f_\phi(\cdot) : \mathbb{R}^d \to \mathbb{R}^C$, parameterized by ϕ, maps the posterior encoded state $\text{Imp}_\theta(\mathbf{x} \odot M)$ to a probability distribution over labels. It is trained by directly minimizing the cross entropy loss ℓ_c from collected data[2]. This differs from typical classification in that the data are collected adaptively by RL, rather than sampled from a prefixed source.

• The panel selector, a network module parameterized by ψ, takes the following as input

$$s_{\theta,\phi}^{\text{emb}}(s) = s_{\theta,\phi}^{\text{emb}}(\mathbf{x} \odot M) = (\text{Imp}_\theta(\mathbf{x} \odot M), f_\phi(\text{Imp}_\theta(\mathbf{x} \odot M)), M), \qquad (3)$$

and maps it to a probability distribution over actions. We train the panel selector by using the classical proximal policy updates (PPO) Schulman et al. (2017), which aims at maximizing a clipped surrogate objective regularized by a square-error loss of the value functions and an entropy bonus. We denote this loss function as ℓ_{rl} and relegate its expanded form to Appendix C.

• The full algorithm updates panel selector and classifier concurrently, given in Algorithm 1 and visualized in Figure 2. We call it "semi-model-based" because it maintains a running estimate of the classifier (which is a part of the reward model of the MDP) while making proximal policy update. Such a hybrid RL technique of model learning and policy updates has been used for solving complex games, where a notable example is Deepmind's Muzero Schrittwieser et al. (2020). Further, we remark that Algorithm 1 does end-to-end training. Thus, it is compatible with on-the-fly learning. The algorithm can start with as little as zero knowledge about the prediction task, and it can keep improving on new incoming patients by querying test panels and finetuning the state encoder.

6 EXPERIMENTS

We test the method on three clinical tasks using real-world datasets. See Table 1 for a summary. We split each dataset into 3 parts: training set, validation set, and test set. Training data is further split into two disjoint sets, one for pretraining the state encoder and the other one for end-to-end RL training. Validation set is used for tuning hyperparameters [3]. During RL training[4], we sample

---

[2]The expanded forms of ℓ_c and ℓ_{rl} are given in Appendix C

[3]Detailed data splitting, hyperparameter choices and searching ranges are presented in Appendix A.

[4]Our codes used the implementation of PPO algorithm in package Raffin et al. (2021).

Algorithm 1 Semi-Model-Based Deep Diagnosis Policy Optimization (SM-DDPO)

Initialize: Imp_θ, Classifier $f_{\phi^{(0,0)}}$, Panel/Prediction Selection Policy $\pi_{\psi^{(0,0)}}$, number of loops L, L_1, L_2, stepsize η;
for $i = 0, 1, \cdots, L$ **do** $\triangleright$ End-to-end training outer loop
    Construct RL environment using state embedding $s^{\text{emb}}_{\theta,\phi^{(i,0)}}$ defined in (3)
    for $j = 1, 2, \cdots, L_1$ **do** $\triangleright$ Policy update inner loop
        Run RL policy in environment for T timesteps and save observations in Q
        Update panel selection policy by $\psi^{(i,j)} = \text{argmax}_\psi \ell_{rl}(\psi; \psi^{(i,j-1)})$
    end for
    Set $\psi^{(i+1,0)} = \psi^{(i,L_1)}$
    for $j = 1, 2, \cdots, L_2$ **do** $\triangleright$ Classifier update inner loop
        Sample minibatch B_j from Q
        Update classifier by $\phi^{i,j} = \phi^{i,j-1} - \eta \cdot \nabla_\phi \frac{1}{|B_j|} \sum_{k \in B_j} \ell_c(\phi^{i-1}; (\mathbf{x_k}, M_k))$
    end for
    Set $\phi^{(i+1,0)} = \phi^{(i,L_2)}$
end for
Output: Classifier $f_{\phi^{(L+1,0)}}$, Policy $\pi_{\psi^{(L+1,0)}}$.

---

a random patient and a random subset of test results as initial observations at the beginning of an episode, for sufficient exploration. We evaluate the trained RL policy on patients from the test sets, initialized at a state with zero observed test result, and report F1 score and AUROC.

Table 1: Summary statistics of ferritin, AKI and sepsis datasets

Dataset	# of tests	# test panels	# patients	% positive class	#training	#validation	#held-out testing
Ferritin	39	6	43,472	8.9%	32,602	6,522	4,248
AKI	19	4	23,950	16.5%	17,964	3,600	2,386
Sepsis	28	4	5,783	14.5%	4,335	869	579

6.1 CLINICAL TASKS

We briefly describe three clinical tasks for our experiments. For more details on background, please see Appendix A.

Ferritin abnormality detection   Blood ferritin level can indicate abnormal iron storage, which is commonly used to diagnose iron deficiency anemia Short & Domagalski (2013) or hemochromatosis (iron overload) Crownover & Covey (2013). Machine learning models can predict abnormal ferritin levels using concurrent laboratory measurements routinely collected in primary care Luo et al. (2016); Kurstjens et al. (2022). These predictive models achieve promising results, e.g. around 0.90 AUC using complete blood count and C-reactive protein Kurstjens et al. (2022), and around 0.91 AUC using common lab tests Luo et al. (2016). However, both studies required the full observation of all selected predictors without taking the financial costs into consideration.

We applied our proposed models to a ferritin dataset from a tertiary care hospital (approved by Institutional Review Board), following the steps described in Luo et al. (2016). Our dataset includes 43,472 patients, of whom 8.9% had ferritin levels below the reference range that should be considered abnormal. We expected to predict abnormal ferritin results using concurrent lab testing results and demographic information. These lab tests were ordered through and can be dynamically selected from 6 lab test panels, including basic metabolic panel (BMP, n=9, [estimated national average] cost=$36), comprehensive metabolic panel (CMP, n=16, cost=$48), basic blood count (BBC, n=10, cost=$26), complete blood count (CBC, n=20, cost=$44), transferrin saturation (TSAT, n=2, cost=$40) and Vitamin B-12 test (n=1, cost=$66).

Acute Kidney Injury Prediction   Acute kidney injury (AKI) is commonly encountered in adults in the intensive care unit (ICU), and patients with AKI are at risk for adverse clinical outcomes such as prolonged ICU stays and hospitalization, need for renal replacement therapy, and increased mortality Kellum & Lameire (2013). AKI usually occurs over the course of a few hours to days and the efficacy of intervention greatly relies on the early identification of deterioration Kellum & Lameire (2013). Prior risk prediction models for AKI based on EHR data yielded modest performance, e.g.,

around 0.75 AUC using a limited set of biomarkers Perazella (2015) or a specific group of patients Sanchez-Pinto & Khemani (2016), or around 0.8 AUC using comprehensive lab panels of general adult ICU populations such as from the MIMIC datasetZimmerman et al. (2019); Sun et al. (2019).

In this experiment, we followed steps in Zimmerman et al. (2019) to extract 23,950 ICU visits of 19,811 patients from the MIMIC-III dataset Johnson et al. (2016), among which 16.5% patients develop AKI during their ICU stay. We aimed at predicting the AKI onset within 72 hours of ICU admission using a total of 31 features including demographics, physiologic measurements, and lab testing results extracted within 24 hours of ICU admission. The lab tests were categorized into 4 panels, i.e. CBC (n=3, cost=$44), CMP (n=8, cost=$48), the arterial blood gas panel (ABG, n=2, cost=$473) and the activated partial thromboplastin time panel (APTT, n=6, cost=$26). The demographic information and physiologic measurements were collected before test panel selection, thus they are considered visible.

Sepsis Mortality Prediction for ICU Patients Sepsis is a life-threatening organ dysfunction, and is a leading cause of death and cost overruns in ICU patients Angus & Van der Poll (2013) Early identification of risk of mortality in septic patients is important to evaluate the patients' status and improve their clinical outcomes Moreno et al. (2008). Most of the previous sepsis mortality prediction models use all available test results as predictors, without balancing the cost of ordering all the associated test panels Lee et al. (2020); Ding & Luo (2021); Shin et al. (2021); Moreno et al. (2008).

We followed steps in Shin et al. (2021) to collect 5,783 septic patients from the MIMIC-III dataset Johnson et al. (2016) according to the Sepsis-3 criteria Singer et al. (2016). The in-hospital mortality rate of this cohort is 14.5%. We focused on predicting in-hospital mortality for these sepsis patients using demographics information, medical histories, mechanical ventilation status, the first present lab testing results and physiologic measurements within 24 hours of ICU admission, and the Sequential Organ Failure Assessment (SOFA) score. Similarly to the setup in the AKI experiment, the lab tests were also categorized into 4 panels of CBC (n=5), CMBP (n=15), ABG (n=6) and APTT (n=2). The components of SOFA score may be based on the lab testing results in CBC, CMP or ABG panels Singer et al. (2016). Demographic features are considered visible.

6.2 PERFORMANCE RESULTS

Our method is tested with comparison to a number of baselines that use either full/partial test results or statically/dynamically selected tests for prediction. They include logistic regression, random forest Ho (1995), XGBoost Chen & Guestrin (2016), LightGBM Ke et al. (2017), a 3-layer multi-layer perceptron, as well as RL-based approach Janisch et al. (2019). Experiments results, such as F1 score, AUROC and testing costs are reported in Table 2. We emphasize that these baselines are incapable to handle the task of finding the Pareto front. Thus, we only test them under no budget constraints.

• **Comparisons with baseline models using full observation of data.** The results are presented in Table 2. Across all three clinical tasks, our proposed model can achieve comparable or even state-of-the-art performance, while significantly reducing the financial cost. On sepsis dataset, SM-DDPO$_{end2end}$ yielded better results (F$_1$=0.562, AUROC=0.845) than the strongest baseline models, LightGBM (F$_1$=0.517, AUROC=0.845), when saving up to 84% in test cost. On ferritin dataset, LightGBM (F$_1$=0.627, AUROC=0.948) performed slightly better than our model (F$_1$=0.624, AUROC=0.928), however, by using 5x testing cost. On AKI dataset, SM-DDPO$_{end2end}$ (F$_1$=0.495, AUROC=0.795) achieved comparable results to the optimal full observation model, 3-layer MLP (F$_1$=0.494, AUROC=0.802), while saving the testing cost from $591 to $90.

• **Comparisons with other test selection strategies.** Our proposed SM-DDPO$_{end2end}$, using RL-inspired dynamic selection strategy, consistently yielded better performance and required less testing cost across all three datasets, when compared to the models using fixed or random selection strategy. For fixed test selection strategy, we first tested the classification methods using the two most relevant panels: CBC and CMP. These baselines with reduced testing cost still behaved much worse than our approach in both F_1 score and AUROC. We also tested another fixed selection (FS) baseline, where we chose to always observe 2 most selected test panels reported in our approach for all patients, while keeping other modules the same. Our approach outperformed FS on both F_1 score and AUROC while having a similar testing cost. The random selection (RS) baseline selected test panels uniformly at random and had a worse performance. Q-learning for classification with costly features (CWCF) Janisch et al. (2019) performed poorly on all three clinical datasets. We believe this is because the model uses the same network for selecting tests and learning rewards (Q-value of

Table 2: Model performance, measured by F_1 score, area under ROC (AUC), and testing cost, for three real-world clinical datasets. The tested models include logistic regression (LR), random forests (RF), gradient boosted regression trees (XGBoost Chen & Guestrin (2016) and LightGBM Ke et al. (2017)), 3-layer multi-layer perceptron, Q-learning for classification with costly features (CWCF)Janisch et al. (2019), Random Selection (RS), Fixed Selection (FS). All models were fine-tuned to maximize the F_1 score. The model yielded the highest F_1 score is in bold. The model required the least testing cost is underlined. More detailed results of this table with more dynamic baselines and standard deviations reported in Appendix A.

Models	Ferritin			AKI			Sepsis			Test Selection
Metrics	F_1	*AUC*	*Cost*	F_1	*AUC*	*Cost*	F_1	*AUC*	*Cost*	Strategy
LR	0.539	0.935	$290	0.452	0.797	$591	0.506	0.825	$591	Full
RF	0.605	0.938	$290	0.439	0.764	$591	0.456	0.801	$591	Full
XGBoost	0.617	0.938	$290	0.404	0.785	$591	0.431	0.828	$591	Full
LightGBM	**0.627**	**0.941**	**$290**	0.474	0.790	$591	0.500	0.844	$591	Full
3-layer DNN	0.616	0.938	$290	0.494	0.802	$591	0.517	0.845	$591	Full
LR (2 panels)	0.401	0.859	$92	0.473	0.797	$92	0.488	0.811	$92	Fixed
RF (2 panels)	0.504	0.887	$92	0.425	0.768	$92	0.478	0.828	$92	Fixed
XGBoost (2 panels)	0.519	0.895	$92	0.410	0.781	$92	0.459	0.877	$92	Fixed
LightGBM (2 panels)	0.571	0.901	$92	0.491	0.792	$92	0.502	0.864	$92	Fixed
FS	0.585	0.927	$74	0.434	0.787	$98	0.500	0.837	$90	Fixed
RS	0.437	0.845	$145	0.424	0.748	$295	0.473	0.789	$295	Random
CWCF	0.554	0.718	$256	0.283	0.510	$326	0.112	0.503	$301	Dynamic
SM-DDPO$_{pretrained}$	0.607	0.925	$80	**0.519**	**0.789**	**$90**	0.567	0.836	**$85**	Dynamic
SM-DDPO$_{end2end}$	0.624	0.928	$62	0.495	0.795	$97	0.562	0.845	$90	Dynamic

classification action). For such imbalanced datasets, this may make the training unstable and difficult to optimize.

• **Efficiency and accuracy of end-to-end training.** The classifier and panel selector of SM-DDPO$_{end2end}$ are **both trained from the scratch**, using Algorithm 1. As in Table 2, this end-to-end training scheme gives comparable accuracy with policies that rely on a heavily pretrained classifier (SM-DDPO$_{pretrain}$). If a brand-new diagnostic/predictive task is given, our algorithm can be trained without prior data/knowledge about the new disease. It can adaptively prescribe lab tests to learn the disease model and test selection policy in an online fashion. End-to-end training is also more data-efficient and runtime efficient.

• **Interpretability.** Our algorithm is able to select test panels that are clinically relevant. For ferritin prediction, our algorithm identifies TSAT as a most important panel, which is indeed useful for detecting iron deficiency. For AKI prediction, our algorithm recommends serum creatinine level test as an important predictor for 95% of subjects, i.e., current and past serum creatinine is indicative of future AKI, expanding its utility as a biomarker de Geus et al. (2012).

6.3 TRAINING CURVES

We present the training curves of Algorithm 1 on AKI dataset in Figure 3 and 4.

• **Policy improvement during RL training.** In Figure 3, we showed the performance of the RL policies evaluated on train, validation and test sets. We note that the three curves closely match one another, confirming the generalizability of the learned dynamic classification policy.

• **SM-DDPO learns the disease model.** In end-to-end training, the diagnostic classifier is trained from the scratch. It maps any partially-observed patient state to a diagnosis/prediction. We evaluate this classifier on static data distributions, in order to eliminate the effect of dynamic test selection and focus on classification quality. Figure 4 shows that the classifier learns to make the right prediction with improved quality during RL, via training only on data selected by the RL algorithm.

6.4 COST-F_1 PARETO FRONT

Figure 5 illustrates the Pareto fronts learned on all three datasets. We trained for optimal policies on 190 MDP instances specified by different value pairs of (λ, ρ) in Theorem 4.1, and present the corresponding performance on F_1 score (red) and AUROC (blue) evaluated on the test sets. We identify the Pareto front as the upper envelope of these solutions, which are the yellow curves in Figure 5. These results present the full tradeoff between testing cost and diagnostic/predictive accuracy. As a corollary, given any cost budget B, one is able to obtain the best testing strategy with the optimal F_1 performance directly from Figure 5. We present a zoom-in version in Appendix A.

Figure 3: RL training curves on AKI Dataset. We evaluate the policy and classifier learned during the end-to-end training phase on both train, validation and test set. The matching curve confirms generalizability of the learned policies.

Figure 4: Classifier improvement during RL training on AKI Dataset. Accuracy of the learned classifier is evaluated on static patient distributions, with 1) random missing pattern, where we uniformly at random augment the test data; 2) missing pattern of the optimal policy's state distribution. During the end-to-end RL training, the classifier gradually improves and has higher accuracy with the second missing pattern.

Figure 5: Cost-F_1 Pareto Front for maximizing F_1-score on Ferritin, AKI and Sepsis Datasets

7 SUMMARY

In this work, we consider the task of maximizing F_1 score via cost-sensitive dynamic testing. Such nonlinear/non-Markovian, non-concave reward functions invalidates standard RL solutions. We formulate it as a Markov decision process via rigorously showing the whole cost-F_1 Pareto front can be obtained via reshaping the reward functions of the MDPs. To handle the exponential complexity of the state missing patterns, we propose a Semi-Model-based Deep Diagnosis Policy Optimization (SM-DDPO) framework that is compatible with end-to-end training and online learning. Our approaches are validated on diverse real-world clinical tasks: ferritin abnormality detection, sepsis mortality prediction, and acute kidney injury prediction, by showing state-of-art diagnosis/prediction performance with up to 85% reduction in testing cost.

REFERENCES

Derek C Angus and Tom Van der Poll. Severe sepsis and septic shock. *N Engl J Med*, 369:840–851, 2013.

Jinbo Bi, Kristin Bennett, Mark Embrechts, Curt Breneman, and Minghu Song. Dimensionality reduction via sparse support vector machines. *Journal of Machine Learning Research*, 3(Mar): 1229–1243, 2003.

Mustafa Bilgic and Lise Getoor. Voila: Efficient feature-value acquisition for classification. In *Proceedings of the national conference on artificial intelligence*, volume 22, pp. 1225. Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2007.

Xiaoyong Chai, Lin Deng, Qiang Yang, and Charles X Ling. Test-cost sensitive naive bayes classification. In *Fourth IEEE International Conference on Data Mining (ICDM'04)*, pp. 51–58. IEEE, 2004.

Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*, pp. 785–794, 2016.

Gabriella Contardo, Ludovic Denoyer, and Thierry Artières. Sequential cost-sensitive feature acquisition. In *International symposium on intelligent data analysis*, pp. 284–294. Springer, 2016.

Brian K Crownover and Carlton Covey. Hereditary hemochromatosis. *American family physician*, 87 (3):183–190, 2013.

Hilde RH de Geus, Michiel G Betjes, and Jan Bakker. Biomarkers for the prediction of acute kidney injury: a narrative review on current status and future challenges. *Clinical kidney journal*, 5(2): 102–108, 2012.

Menghan Ding and Yuan Luo. Unsupervised phenotyping of sepsis using nonnegative matrix factorization of temporal trends from a multivariate panel of physiological measurements. *BMC Medical Informatics and Decision Making*, 21(5):1–15, 2021.

Conor Fahy and Shengxiang Yang. Dynamic feature selection for clustering high dimensional data streams. *IEEE Access*, 7:127128–127140, 2019.

Omer Gottesman, Fredrik Johansson, Matthieu Komorowski, Aldo Faisal, David Sontag, Finale Doshi-Velez, and Leo Anthony Celi. Guidelines for reinforcement learning in healthcare. *Nature medicine*, 25(1):16–18, 2019.

Arthur Guez, Robert D Vincent, Massimo Avoli, and Joelle Pineau. Adaptive treatment of epilepsy via batch-mode reinforcement learning. In *AAAI*, pp. 1671–1678, 2008.

Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of machine learning research*, 3(Mar):1157–1182, 2003.

He He, Hal Daumé III, and Jason Eisner. Cost-sensitive dynamic feature selection. In *ICML Inferning Workshop*, 2012.

Tin Kam Ho. Random decision forests. In *Proceedings of 3rd international conference on document analysis and recognition*, volume 1, pp. 278–282. IEEE, 1995.

Amelia Huck and Kent Lewandrowski. Utilization management in the clinical laboratory: an introduction and overview of the literature. *Clinica Chimica Acta*, 427:111–117, 2014.

Jaromír Janisch, Tomáš Pevnỳ, and Viliam Lisỳ. Classification with costly features using deep reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 3959–3966, 2019.

Shihao Ji and Lawrence Carin. Cost-sensitive feature acquisition and classification. *Pattern Recognition*, 40(5):1474–1485, 2007.

Alistair EW Johnson, Tom J Pollard, Lu Shen, Li-wei H Lehman, Mengling Feng, Mohammad Ghassemi, Benjamin Moody, Peter Szolovits, Leo Anthony Celi, and Roger G Mark. Mimic-iii, a freely accessible critical care database. *Scientific data*, 3(1):1–9, 2016.

Sergey Karayev, Mario J Fritz, and Trevor Darrell. Dynamic feature selection for classification on a budget. In *International conference on machine learning (ICML): Workshop on prediction with sequential models*. Citeseer, 2013.

Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. Lightgbm: A highly efficient gradient boosting decision tree. *Advances in neural information processing systems*, 30, 2017.

John A Kellum and Norbert Lameire. Diagnosis, evaluation, and management of acute kidney injury: a kdigo summary (part 1). *Critical care*, 17(1):204, 2013.

Matloob Khushi, Kamran Shaukat, Talha Mahboob Alam, Ibrahim A Hameed, Shahadat Uddin, Suhuai Luo, Xiaoyan Yang, and Maranatha Consuelo Reyes. A comparative performance analysis of data resampling methods on imbalance medical data. *IEEE Access*, 9:109960–109975, 2021.

Ron Kohavi and George H John. Wrappers for feature subset selection. *Artificial intelligence*, 97 (1-2):273–324, 1997.

Matthieu Komorowski, Leo A Celi, Omar Badawi, Anthony C Gordon, and A Aldo Faisal. The artificial intelligence clinician learns optimal treatment strategies for sepsis in intensive care. *Nature medicine*, 24(11):1716–1720, 2018.

Steef Kurstjens, Thomas de Bel, Armando van der Horst, Ron Kusters, Johannes Krabbe, and Jasmijn van Balveren. Automated prediction of low ferritin concentrations using a machine learning algorithm. *Clinical Chemistry and Laboratory Medicine (CCLM)*, 2022.

Eun Hye Lee, Mi Hwa Shin, Jong-Min Park, Sang-Guk Lee, Nam Su Ku, Young Sam Kim, Moo Suk Park, Jae-Chul Pyun, and Kyung Soo Chung. Diagnosis and mortality prediction of sepsis via lysophosphatidylcholine 16: 0 measured by maldi-tof ms. *Scientific reports*, 10(1):1–9, 2020.

Der-Chiang Li, Chiao-Wen Liu, and Susan C Hu. A learning method for the class imbalance problem with medical data sets. *Computers in biology and medicine*, 40(5):509–518, 2010.

Yang Li and Junier Oliva. Active feature acquisition with generative surrogate models. In *International Conference on Machine Learning*, pp. 6450–6459. PMLR, 2021.

Yuan Luo, Peter Szolovits, Anand S Dighe, and Jason M Baron. Using machine learning to predict laboratory test results. *American journal of clinical pathology*, 145(6):778–788, 2016.

Qi Ma and Sujit K Ghosh. Emflow: Data imputation in latent space via em and deep flow models. *arXiv preprint arXiv:2106.04804*, 2021.

Rui P Moreno, Barbara Metnitz, Leopold Adler, Anette Hoechtl, Peter Bauer, and Philipp GH Metnitz. Sepsis mortality prediction based on predisposition, infection and response. *Intensive care medicine*, 34(3):496–504, 2008.

HyunJi Alex Nam, Scott Fleming, and Emma Brunskill. Reinforcement learning with state observation costs in action-contingent noiselessly observable markov decision processes. *Advances in Neural Information Processing Systems*, 34:15650–15666, 2021.

Mark A Perazella. The urine sediment as a biomarker of kidney disease. *American Journal of Kidney Diseases*, 66(5):748–755, 2015.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 22(268):1–8, 2021. URL http://jmlr.org/papers/v22/20-1364.html.

M Mostafizur Rahman and Darryl N Davis. Addressing the class imbalance problem in medical datasets. *International Journal of Machine Learning and Computing*, 3(2):224, 2013.

L Nelson Sanchez-Pinto and Robinder G Khemani. Development of a prediction model of early acute kidney injury in critically ill children using electronic health record data. *Pediatric Critical Care Medicine*, 17(6):508–515, 2016.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *Nature*, 588(7839):604–609, 2020.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Jiyoung Shin, Yikuan Li, and Yuan Luo. Early prediction of mortality in critical care setting in sepsis patients using structured features and unstructured clinical notes. In *2021 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pp. 2885–2890. IEEE, 2021.

Matthew W Short and Jason E Domagalski. Iron deficiency anemia: evaluation and management. *American family physician*, 87(2):98–104, 2013.

Mervyn Singer, Clifford S Deutschman, Christopher Warren Seymour, Manu Shankar-Hari, Djillali Annane, Michael Bauer, Rinaldo Bellomo, Gordon R Bernard, Jean-Daniel Chiche, Craig M Coopersmith, et al. The third international consensus definitions for sepsis and septic shock (sepsis-3). *Jama*, 315(8):801–810, 2016.

Mengxin Sun, Jason Baron, Anand Dighe, Peter Szolovits, Richard G Wunderink, Tamara Isakova, and Yuan Luo. Early prediction of acute kidney injury in critical care setting using clinical notes and structured multivariate physiological measurements. *MedInfo*, 264:368–372, 2019.

Kirill Trapeznikov and Venkatesh Saligrama. Supervised sequential classification under budget constraints. In *Artificial intelligence and statistics*, pp. 581–589. PMLR, 2013.

Jason Weston, Sayan Mukherjee, Olivier Chapelle, Massimiliano Pontil, Tomaso Poggio, and Vladimir Vapnik. Feature selection for svms. *Advances in neural information processing systems*, 13, 2000.

Jason Weston, André Elisseeff, Bernhard Schölkopf, and Mike Tipping. Use of the zero norm with linear models and kernel methods. *The Journal of Machine Learning Research*, 3:1439–1461, 2003.

Haiyan Yin, Yingzhen Li, Sinno Jialin Pan, Cheng Zhang, and Sebastian Tschiatschek. Reinforcement learning with efficient active feature acquisition. *arXiv preprint arXiv:2011.00825*, 2020.

Chao Yu, Jiming Liu, Shamim Nemati, and Guosheng Yin. Reinforcement learning in healthcare: A survey. *ACM Computing Surveys (CSUR)*, 55(1):1–36, 2021.

Junyu Zhang, Alec Koppel, Amrit Singh Bedi, Csaba Szepesvari, and Mengdi Wang. Variational policy gradient method for reinforcement learning with general utilities. *Advances in Neural Information Processing Systems*, 33:4572–4583, 2020.

Lindsay P Zimmerman, Paul A Reyfman, Angela DR Smith, Zexian Zeng, Abel Kho, L Nelson Sanchez-Pinto, and Yuan Luo. Early prediction of acute kidney injury following icu admission using a multivariate panel of physiological measurements. *BMC medical informatics and decision making*, 19(1):1–12, 2019.