ADAPTIVE GRADIENT METHODS CAN BE PROVABLY FASTER THAN SGD WITH RANDOM SHUFFLING

ABSTRACT

Adaptive gradient methods have been shown to outperform SGD in many tasks of training neural networks. However, the acceleration effect is yet to be explained in the non-convex setting, since the best convergence rate of adaptive gradient methods is worse than that of SGD in literature. In this paper, we prove that adaptive gradient methods exhibit an $\tilde{O}(T^{-1/2})$-convergence rate for finding first-order stationary points under some mild assumptions, which improves previous best convergence results of adaptive gradient methods and SGD by factors of $O(T^{-1/4})$ and $O(T^{-1/6})$, respectively. In particular, we study two variants of AdaGrad with random shuffling and identify a novel consistency condition from general experiments result. Our analysis suggests that the combination of random shuffling and adaptive learning rates gives rise to better convergence.

1 INTRODUCTION

We consider the finite sum minimization problem in stochastic optimization:

$$\min_{\boldsymbol{x} \in \mathbb{R}^d} \quad f(\boldsymbol{x}) = \frac{1}{n} \sum_{i=1}^{n} f_i(\boldsymbol{x}), \tag{1}$$

where f is the objective function and its component functions $f_i : \mathbb{R}^d \rightarrow \mathbb{R}$ are smooth and possibly non-convex. This formulation has been used extensively in training neural networks today. Stochastic gradient descend (SGD) and its variants have shown to be quite effective for solving this problem, whereas recent works demonstrate another prominent line of gradient-based algorithms by introducing adaptive step sizes to automatically adjust the learning rate (Duchi et al., 2011; Tieleman & Hinton, 2012; Kingma & Ba, 2014).

Despite the superior performance of adaptive gradient methods in many tasks (Devlin et al., 2019; Vaswani et al., 2017), their theoretical convergence remains the same or even worse for non-convex objectives, compared to SGD. In general non-convex settings, it is often impractical to discuss optimal solutions. Therefore, the attention of analysis turns to stationary points instead. Many works have been proposed to study first-order (Chen et al., 2019; Zhou et al., 2018; Zaheer et al., 2018; Ward et al., 2018; Zhou et al., 2018) and second-order (Allen-Zhu, 2018; Staib et al., 2019) stationary points. Table 1 summarized some previous best-known results for finding first-order stationary points. One might notice that the best dependence on the total epoch number T of adaptive gradient methods matches that of vanilla SGD. In addition, with the introduction of incremental sampling techniques, an even better convergence of SGD can be obtained (Haochen & Sra, 2019; Nguyen et al., 2020).

This gap between theory and practice of adaptive gradient methods has been an open problem that we aim to solve in this paper. Motivated by the analysis of sampling techniques, we rigorously prove that adaptive gradient methods exhibit a faster convergence rate that surpasses the best result on SGD. In particular, we make the following contributions:

- Our main contribution (Theorem 1,2,3) is to prove that two variants of AdaGrad can find $\tilde{O}(T^{-1/2})$-approximate first-order stationary points within T epochs under some mild assumptions. This improves previous best convergence results of adaptive gradient methods and shuffling SGD by factors of $O(T^{-1/4})$ and $O(T^{-1/6})$, respectively. As a result, this bridges the gap between analysis and practice of adaptive gradient methods by proving that adaptive gradient methods can be faster than SGD in theory.

Table 1: Convergence rate comparisons for the non-convex optimization problem in Equation (1)

	Algorithm	Assumptions (L-smooth+)	$\|\nabla f(\boldsymbol{x})\|$-convergence T
SGD	vanilla SGD	• σ^2 bounded gradient variance	$O\left(T^{-1/4}\right)$
	Random Shuffling SGD (Nguyen et al., 2020)	• bounded gradients	$\tilde{O}\left(T^{-1/3}\right)$
Adaptive Gradient Methods	AMSGrad, AdaFom (Chen et al., 2019)	• bounded gradients
• initial gradient lower bound	$\tilde{O}\left(T^{-1/4}\right)$
	AMSGrad, Padam (Zhou et al., 2018)	• bounded gradients
• gradient sparsity	$O\left(T^{-1/4}\right)$
	RMSProp, Yogi (Zaheer et al., 2018)	• bounded gradients
• σ^2 bounded gradient variance	$O\left(T^{-1/2} + \sigma\right)$
	AdaGrad-NORM (Ward et al., 2018)	• bounded gradients
• σ^2 bounded gradient variance	$\tilde{O}\left(T^{-1/4}\right)$
	GGT (Agarwal et al., 2019)	• σ^2 bouned gradient variance	$O\left(T^{-1/4}\right)$
	Ours	• bounded gradients
• bounded consistency ratio	$\tilde{O}\left(T^{-1/2}\right)$

T denotes the number of epoch; $\boldsymbol{x}_t$ is the parameter returned at the end of epoch t; $\boldsymbol{x}^*$ is the optimal solution; The minimization is taken with respect to $1 \leq t \leq T$. We ignore the orders of n in the convergence results.

- We identity a new consistency condition from a general phenomenon in experiments. This condition is easy to verify and should be beneficial for future analysis as well as design for better algorithms.

- We conduct preliminary experiments to demonstrate the combined acceleration effect of random shuffling and adaptive learning rates.

Our analysis points out two key components that lead to better convergence results of adaptive gradient methods: the epoch-wise analysis of random shuffling can incorporate the benefit of full gradients; the adaptive learning rates provide better improvement of objective value in consecutive epochs.

2 PRELIMINARIES

A typical setting of machine learning using gradient methods is the finite sum minimization in equation (1). In this problem, the number of samples n is usually very large, rendering the evaluation of full gradients expensive. Therefore, a mini-batch gradient is introduced to approximate the full gradient. Mini-batch gradient descent is often carried out in epochs, where each epoch includes several iterations of parameter updates. This epoch-wise implementation can easily incorporate shuffling techniques which have proven to be effective for SGD both in theory and practice.

We aim to analyze the convergence rate of adaptive gradient methods under this framework, where the objective can be non-convex. Throughout this paper, we restrict the discussions of convergence to achieving ϵ-approximate first-order stationary point defined as $\boldsymbol{x}$ satisfying $\|\nabla f(\boldsymbol{x})\| \leq \epsilon$. We leave for future work analysis related to saddle points and second-order stationary point. We want to show that adaptive gradient methods can find $\boldsymbol{x}$ such that $\|\nabla f(\boldsymbol{x})\| = \tilde{O}(T^{-1/2})$ in T epochs.

Notations. $\boldsymbol{v}^2$ denotes the matrix $\boldsymbol{v}\boldsymbol{v}^\top$ and $\|\boldsymbol{v}\|$ is the l_2-norm of vector $\boldsymbol{v}$; $\operatorname{diag}(\boldsymbol{V}), \|\boldsymbol{V}\|, \lambda_{\min}(\boldsymbol{V})$ and $\lambda_{\max}(\boldsymbol{V})$ are the diagonal matrix, the spectral norm, the largest and smallest non-zero eigenvalues of the matirx $\boldsymbol{V}$, respectively. For alphabets with subscripts, $\boldsymbol{v}_{i:j}$ denotes the collection of $\{\boldsymbol{v}_i, \boldsymbol{v}_{i+1}, ..., \boldsymbol{v}_j\}$ and $\boldsymbol{v}_:$ denotes the entire set of $\boldsymbol{v}_:$; similar notations are used for alphabets with double subscripts. Let $[n] = \{1, ..., n\}$, $O(\cdot), \tilde{O}(\cdot)$ be the standard asymptotic notations. Denote $\boldsymbol{e}_i$ as the unit vector with its i-th component being 1 and $\boldsymbol{e}$ the all-one vector whose dimension depend on the context.

AdaGrad-type methods. As opposed to SGD, adaptive gradient methods assign a coordinate-wise adaptive learning rate to the stochastic gradient. We formulate the generic AdaGrad-type optimizers, including their full and diagonal versions, as follows. At the i-th iteration of epoch t, the parameter is updated by:

$$\boldsymbol{x}_{t,i+1} = \boldsymbol{x}_{t,i} - \eta_t \boldsymbol{V}_{t,i}^{-1/2} \boldsymbol{g}_{t,i}, \qquad\qquad \text{(full version)}$$

$$\boldsymbol{x}_{t,i+1} = \boldsymbol{x}_{t,i} - \eta_t \text{diag}(\boldsymbol{V}_{t,i})^{-1/2} \boldsymbol{g}_{t,i}, \qquad\qquad \text{(diagonal version)}$$

where $\boldsymbol{g}_{t,i}$ is the mini-batch gradient of the objective at $\boldsymbol{x}_{t,i}$, the matrix $\boldsymbol{V}_{t,i}$ contains second-moment calculated using all the past stochastic gradients and η_t is the step size of epoch t. The full version is impractical for high-dimensional $\boldsymbol{x}$. Thus the diagonal version is often preferred in literature. As an example, the second-moment matrix in AdaGrad is taken to be $\boldsymbol{V}_{t,i} = (\sum_{s=1}^{t-1} \sum_{j=1}^{m} \boldsymbol{g}_{s,j}^2 + \sum_{j=1}^{i} \boldsymbol{g}_{t,j}^2)/t$ where we have m iterations in each epoch. SGD can also be written into this general form where we set $\boldsymbol{V}_{t,i}$ to be the identity matrix.

Sampling Strategy. Random shuffling, also known as sampling without replacement, is an often-used technique to accelerate the convergence of SGD. The idea is to sample a random permutation of function indices $[n]$ for each epoch and slide through this permutation to get the mini-batch gradients for the iterations in this epoch. Some implementations shuffle the set $[n]$ uniformly independently for each epoch while others shuffle the set once during initialization and use the same permutation for all epochs. Generally speaking, suppose we have a permutation $\sigma = (\sigma_1, ..., \sigma_n)$ at epoch t, we define the set $\mathbb{B}_{t,i} = \{\sigma_j : (i-1)\frac{n}{m} < j \leq i\frac{n}{m}\}$ where m is the number of iterations in one epoch. Then the mini-batch gradient is taken to be $\boldsymbol{g}_{t,i} = m/n \cdot \sum_{j \in \mathbb{B}_{t,i}} \nabla f_j(\boldsymbol{x}_{t,i})$.

This sampling method of mini batches benefits the theoretical analysis of SGD by providing a bounded error between the full gradient and the aggregation of mini-batch gradients in one epoch (Haochen & Sra, 2019; Nguyen et al., 2020). A naive observation that backups this point can be made by assuming $\boldsymbol{x}_{t,1} = ... = \boldsymbol{x}_{t,m}$, since $\cup_{i=1}^{m} \mathbb{B}_{t,i} = [n]$, we would have $\sum_{i=1}^{m} \boldsymbol{g}_{t,i} = \nabla f(\boldsymbol{x}_{t,1})$. Then full gradient can be used to obtain convergence better than plain SGD.

Random shuffling for AdaGrad. Unlike SGD, in adaptive methods, it is hard to approximate the full gradient with the aggregation of mini-batch gradient updates in one epoch due to the presence of the second moments. As we will show in experiments, the simple shuffling variant that only changes the sampling method of mini batches in AdaGrad does not lead to better convergence. The major difficulty hampering the analysis of this variant is that the second-moment matrix uses all the gradient information in history without distinguishment. Thus to be able to leverage the benefit of full gradient, we propose to study a slight modification of AdaGrad. Formally, we shuffle the set $[n]$ once at initialization and obtain the mini-batch gradients in a random shuffling manner. We update the parameters by the same rules of AdaGrad-type methods described above where the second-moment matrix is taken to be:

$$\boldsymbol{V}_{t,i} = \sum_{j=i+1}^{m} \boldsymbol{g}_{t-1,j}^2 + \sum_{j=1}^{i} \boldsymbol{g}_{t,j}^2. \qquad\qquad \text{(AdaGrad-window)}$$

The difference between AdaGrad-window and AdaGrad is that the former only use the latest m mini-batch gradients instead of an epoch-wise average of all the mini-batch gradients in history. The step size is $\eta_t = \eta/\sqrt{t}$ where η is a constant for both methods. The updates of AdaGrad-window is also very similar to the GGT method (Agarwal et al., 2019) without momentum. However GGT uses the full matrix inversion where our analysis applies to both full and diagonal versions.

3 MAIN RESULTS

We will show that AdaGrad-window has the convergence rate of $\tilde{O}(T^{-1/2})$ for non-convex problems under some mild assumptions. This is a significant improvement compared with previous best convergence results of adaptive gradient methods and random shuffling SGD, which are of order $O(T^{-1/4})$ and $\tilde{O}(T^{-1/3})$ respectively. The *key* towards our convergence rate improvement are two-fold: the epoch-wise analysis of random shuffling enables us to leverage the benefit of full

gradients; the adaptive learning rates endow a better improvement of objective value in consecutive epochs.

In order to achieve this better convergence, we first state the assumptions and important concepts used in the proof. Apart from the general assumptions (A1) and (A2) used in previous analysis (Fang et al., 2018; Zaheer et al., 2018; Ward et al., 2018), we pose another assumption described below in (A3) to characterize the consistency between the mini-batch gradients in one epoch.

Assumptions. We assume the following for AdaGrad-window:

(A1) The objective function is lower bounded and component-wise L-smooth, i.e. $\exists f^* \in \mathbb{R}$ s.t. $f(\boldsymbol{x}) \geq f^* > -\infty, \forall \boldsymbol{x}$ and $\|\nabla f_i(\boldsymbol{x}) - \nabla f_i(\boldsymbol{y})\| \leq L \|\boldsymbol{x} - \boldsymbol{y}\|, \forall \boldsymbol{x}, \boldsymbol{y}, i$.

(A2) The mini-batch gradients in the algorithm are uniformly upper bounded, i.e. $\exists G \in \mathbb{R}$ s.t. $\|\boldsymbol{g}_{t,i}\| \leq G, \forall t, i$.

(A3) Denote $\boldsymbol{G}_t = [\boldsymbol{g}_{t,1}, ..., \boldsymbol{g}_{t,m}] \in \mathbb{R}^{d \times m}$ and define the *consistency ratio* as: $r_t = (\|\boldsymbol{G}_t \boldsymbol{e}_1\|^2 + ... + \|\boldsymbol{G}_t \boldsymbol{e}_m\|^2)^{1/2}/(\|\boldsymbol{G}_t \boldsymbol{e}\|)$. This consistency ratio is uniformly upper bounded by some constant r for all t, i.e. $r_t \leq r, \forall t$.

The consistency ratio assumption is essentially enforcing the mini-batch gradients in one epoch to decrease at the similar rate as the aggregation of them. As we will show in experiments, this assumption is very easy to verify. We would like point out that Staib et al. (2019) assumed the condition number of $\boldsymbol{G}_t^\top \boldsymbol{G}_t$ is bounded when analyzing second-order stationary points. It is not hard to see that the consistency ratio assumption we used here is inherit if $\boldsymbol{G}_t^\top \boldsymbol{G}_t$ has bounded condition number. However, bounded condition number is a much stronger assumption, and we will see in the appendix that this does hold for AdaGrad-type optimizers.

Under these assumptions, the following theorems show our convergence result for the full and diagonal versions of AdaGrad-window.

Theorem 1 (The convergence rate of full AdaGrad-window). *For any $T > 4$, set $\eta = m^{-5/4}$, denote $C_1 = m^{5/4}\sqrt{1+r^2} \left(f(\boldsymbol{x}_{1,1}) - f^* + G\right)/\sqrt{2}$ and $C_2 = 5m^{5/4}\sqrt{1+r^2}L/\sqrt{2}$ as constants independent of T. We have:*

$$\min_{1 \leq t \leq T} \|\nabla f(\boldsymbol{x}_{t,1})\| \leq \frac{1}{\sqrt{T}}(C_1 + C_2 \ln T). \tag{2}$$

Theorem 2 (The convergence rate of diagonal AdaGrad-window). *For any $T > 4$, set $\eta = m^{-5/4}$, denote $C_1' = m^{5/4}\sqrt{1+r^2} \left(f(\boldsymbol{x}_{1,1}) - f^* + G\sqrt{d}\right)/\sqrt{2}$ and $C_2' = 5m^{5/4}\sqrt{1+r^2}d^{3/2}L/\sqrt{2}$ as constants independent of T. We have:*

$$\min_{1 \leq t \leq T} \|\nabla f(\boldsymbol{x}_{t,1})\| \leq \frac{1}{\sqrt{T}}(C_1' + C_2' \ln T). \tag{3}$$

The interpretation of these two theorems is that we are able to find an approximate first-order stationary point such that $\|\nabla f(\boldsymbol{x})\| = \tilde{O}(T^{-1/2})$ within T epochs using both versions. We notice that the convergence rate of AdaGrad-window matches that of GD when $m = 1$, which denotes that our results are relatively tight with respect to T. The complete proof is included in the appendix. We will give the intuition and key lemmas explaining how to utilize random shuffling and second moments to obtain these results in the next section.

In addition, we also prove for another variant of AdaGrad, namely, AdaGrad-truncation with second-moment matrix defined as $\boldsymbol{V}_{1,i} = m \cdot \boldsymbol{I}$ and $\boldsymbol{V}_{t,i} = m\|\sum_{j=1}^m \boldsymbol{g}_{t-1,j}\|^2 \cdot \boldsymbol{I}$ when $t > 1$. This second-moment matrix is very similar to the norm version of AdaGrad (Ward et al., 2018) whereas we use the aggregation of mini-batch gradients in the previous epoch as the coefficient. AdaGrad-truncation is beneficial since the formulation leads to a fast and simple implementation without needing to discuss the full and diagonal versions. Due to the space limitation, we list the result below and defer the discussions to the appendix.

Theorem 3 (The convergence rate of AdaGrad-truncation). *For any $T > 4$, set $\eta_t = r/(Lr + 1) \cdot \sqrt{2\left(f(\boldsymbol{x}_{1,1}) - f^* + G^2\right)L/(3(rLm^{1/2} + 2m))} \cdot T^{-1/2}$, denote $C = 24mrL\sqrt{(f(\boldsymbol{x}_{1,1}) - f^* + G^2)r}$ as constants independent of T. We have:*

$$\min_{1 \leq t \leq T} \|\nabla f(\boldsymbol{x}_{t,1})\| \leq \frac{C}{\sqrt{T}}. \tag{4}$$

4 Overview of Analysis

The goal of this section is to give the key intuitions for proving Theorem 1 and Theorem 2. In the following, we use the full version as an example where similar results can be obtained for the diagonal version by adding a dependency on dimension d. Proof details of both versions are included in the appendix. The key towards proving Theorem 1 is to establish the following lemma.

Lemma 1. *For any $t > 1$, in the full version of AdaGrad-window, denote $c_1 = \eta/\sqrt{1 + r^2}, c_2 = 5\eta^2 m^2 L/2 + 5\eta^2 m^{5/2} L/\pi$ as constants independent of t. We have:*

$$\frac{1}{\sqrt{t}} \cdot c_1 \|\nabla f(\boldsymbol{x}_{t,1})\| \leq f(\boldsymbol{x}_{t,1}) - f(\boldsymbol{x}_{t,m+1}) + \frac{1}{t} \cdot c_2. \tag{5}$$

The deduction of convergence rate is straightforward based on this lemma. By summing up for $t = 2, ..., T$, the coefficients are approximately $\sqrt{T}$ on the left and $\ln T$ on the right thus leading to Theorem 1. Therefore, we turn to the proof of this lemma instead. Under the L-smooth assumption, we have the standard descent result for one epoch $\nabla f(\boldsymbol{x}_{t,1})^\top (\boldsymbol{x}_{t,1} - \boldsymbol{x}_{t,m+1}) \leq f(\boldsymbol{x}_{t,1}) - f(\boldsymbol{x}_{t,m+1}) + L/2 \cdot \|\boldsymbol{x}_{t,m+1} - \boldsymbol{x}_{t,1}\|^2$ (we refer the proof of to (Nesterov, 2018)). Rewrite the equation by replacing $\boldsymbol{x}_{t,m+1} - \boldsymbol{x}_{t,1}$ on the left with the AdaGrad-window updates:

$$\frac{\eta}{\sqrt{t}} \cdot \underbrace{\nabla f^\top(\boldsymbol{x}_{t,1}) \boldsymbol{V}_{t,m}^{-1/2} (\sum_{i=1}^m \boldsymbol{g}_{t,i})}_{S1} \leq f(\boldsymbol{x}_{t,1}) - f(\boldsymbol{x}_{t,m+1}) + \frac{L}{2} \|\boldsymbol{x}_{t,m+1} - \boldsymbol{x}_{t,1}\|^2$$

$$+ \frac{\eta}{\sqrt{t}} \cdot \underbrace{\nabla f(\boldsymbol{x}_{t,1})^\top \left[\boldsymbol{V}_{t,m}^{-1/2} \sum_{i=1}^m \boldsymbol{g}_{t,i} - \sum_{i=1}^m \boldsymbol{V}_{t,i}^{-1/2} \boldsymbol{g}_{t,i} \right]}_{S2}.$$

The idea behind this decomposition is to split out the term S1 that behaves similarly to the full gradient and control the remaining terms. Similar to other analysis of adaptive methods, the term $\|\boldsymbol{x}_{t,m+1} - \boldsymbol{x}_{t,1}\|^2$ on the right can be upper bound by a constant times $1/t$ (we refer scalars that does not depend on t to constants). This can be done by simply plugging in the update rules, the details of which are showed in the appendix. Next we show how to bound term S1 and S2 in order to prove Lemma 1.

4.1 Lower bound of S1

To obtain the lower bound of S1, we need two steps. The first step stems from the idea in random shuffling SGD (Haochen & Sra, 2019), which is to bound the difference between the full gradient and the aggregation of mini-batch gradients. Formally, we have the following lemma.

Lemma 2. *For any $t > 0$, in the full version of AdaGrad-window, denote constant $c_3 = \eta(m-1)L/2$, we have:*

$$\|\nabla f(\boldsymbol{x}_{t,1}) - \frac{1}{m} \sum_{i=1}^m \boldsymbol{g}_{t,i}\| \leq \frac{1}{\sqrt{t}} \cdot c_3. \tag{6}$$

Building on top of this lemma, term S1 can be written into a constant combination of $1/\sqrt{t}$ and $(\sum_{i=1}^m \boldsymbol{g}_{t,i})^\top \boldsymbol{V}_{t,m}^{-1/2} (\sum_{i=1}^m \boldsymbol{g}_{t,i})$, which leads to our second step. In the second step, we utilize the consistency ratio assumption to obtain a lower bound formulated as below.

Lemma 3. *For any $t > 0$, in the full version of AdaGrad-window, we have:*

$$(\sum_{i=1}^m \boldsymbol{g}_{t,i})^\top \boldsymbol{V}_{t,m}^{-1/2} (\sum_{i=1}^m \boldsymbol{g}_{t,i}) \geq \frac{1}{\sqrt{1 + r^2}} \| \sum_{i=1}^m \boldsymbol{g}_{t,i}\|. \tag{7}$$

This lemma shows that $(\sum_{i=1}^m \boldsymbol{g}_{t,i})^\top \boldsymbol{V}_{t,m}^{-1/2} (\sum_{i=1}^m \boldsymbol{g}_{t,i})$ can be lower bound by $\| \sum_{i=1}^m \boldsymbol{g}_{t,i}\|$ times a constant. Therefore, we are able to derive a constant combination of $\| \sum_{i=1}^m \boldsymbol{g}_{t,i}\|$ and $1/\sqrt{t}$ as the lower bound for S1, which is desired for Lemma 1.

We emphasize that the essential element of the convergence rate improvement lies in Lemma 3. For SGD, the matrix $\boldsymbol{V}_{t,m}$ is the identity matrix leading to a lower bound of $\|\sum_{i=1}^{m} \boldsymbol{g}_{t,i}\|^2$ instead of $\|\sum_{i=1}^{m} \boldsymbol{g}_{t,i}\|$. This lower order leads to a greater decrease of objective value between consecutive epochs as shown in Lemma 1. The reason that we are able to lower the order on $\|\sum_{i=1}^{m} \boldsymbol{g}_{t,i}\|$ is due to the presence of the second moments. However, as we will show in experiments, the simple second-moment matrix of AdaGrad does not lead to this lower order, making our modification AdaGrad-window necessary.

4.2 Upper bound of S2

To obtain the upper bound of S2, we can write $\boldsymbol{V}_{t,m}^{-1/2} \sum_{i=1}^{m} \boldsymbol{g}_{t,i}$ into $\sum_{i=1}^{m} \boldsymbol{V}_{t,m}^{-1/2} \boldsymbol{g}_{t,i}$. Therefore, we only need to take care of the second-moment matrices $\boldsymbol{V}_{t,m}$ and $\boldsymbol{V}_{t,i}$. As a matter of fact, we have the following lemma.

Lemma 4. *For any $t > 1$ and $1 \leq i \leq m$, in the full version of AdaGrad-window, denote $c_4 = 6\eta(m - i - 1)(m - i)L/\pi + 4\eta(m - i)(m + i + 1)L/\pi$ as constants independent of t, we have:*

$$\|\boldsymbol{V}_{t,m}^{1/2} - \boldsymbol{V}_{t,i}^{1/2}\| \leq \frac{1}{\sqrt{t}} \cdot c_4. \tag{8}$$

Based on this lemma, we can obtain an upper bound of S2 using the result below.

Lemma 5. *For any $t > 1$, in the full version of AdaGrad-window, denote $c_5 = 5\eta m^{5/2}/\pi L + \eta m^2 L$ as constants independent of t, we have:*

$$\nabla f(\boldsymbol{x}_{t,1})^\top \left[m \boldsymbol{V}_{t,m}^{-1/2} \nabla f(\boldsymbol{x}_{t,1}) - \sum_{i=1}^{m} \boldsymbol{V}_{t,i}^{-1/2} \boldsymbol{g}_{t,i} \right] \leq \frac{1}{\sqrt{t}} \cdot c_5. \tag{9}$$

With this upper bound derived, we are able to prove Lemma 1, which is the key intermediate result towards the convergence result in the Theorem 1.

5 Complexity Analysis

Based on Theorem 1 and 2, we discuss the computational complexity for two versions of AdaGrad-window. We compare the total complexity between AdaGrad-window and random shuffling SGD to demonstrate that this adaptive gradient method can be faster than SGD after finite epochs in theory.

Corollary 1 (The computational complexity of full-version AdaGrad-window)**.** *Let $\{\boldsymbol{x}_{t,1}\}_{t=1}^{T}$ be the sequence generated by AdaGrad-window. For given tolerance ϵ, to guarantee that $\min_{1 \leq t \leq T} \|\nabla f(\boldsymbol{x}_{t,1})\| \leq \epsilon$, the total number of gradient evaluation is nearly $O\left(m^{5/2} n \epsilon^{-2}\right)$, and the computational complexity is nearly $\tilde{O}\left(m^{5/2} n d^2 \epsilon^{-2}\right)$, if the eigenvalue decomposition of $\boldsymbol{V}_{t,i}$ is updated with Yu (1991).*

Compared with the full version, their diagonal version is more practical in modern neural network training. Fortunately, a similar result can be derived for the diagonal version.

Corollary 2 (The computational complexity of diagonal-version AdaGrad-window)**.** *Let $\{\boldsymbol{x}_{t,1}\}_{t=1}^{T}$ be the sequence generated by AdaGrad-window. For given tolerance ϵ, to guarantee $\min_{1 \leq t \leq T} \|\nabla f(\boldsymbol{x}_{t,1})\| \leq \epsilon$, the total number of gradient evaluation is nearly $O\left(m^{5/2} n d^3 \epsilon^{-2}\right)$, and the computational complexity is nearly $\tilde{O}\left(m^{5/2} n d^4 \epsilon^{-2}\right)$.*

For achieving the ϵ-approximate first-order stationary point, the total complexity required by random shuffling SGD is $O(nd\epsilon^{-3})$ (Haochen & Sra, 2019; Nguyen et al., 2020). In a rough comparison, the full and diagonal versions of AdaGrad-window have advantages over random shuffling SGD when $\epsilon = O(m^{-5/2} d^{-1})$ and $\epsilon = O(m^{-5/2} d^{-3})$, respectively. Therefore in theory, AdaGrad-window is more efficient when m and d are small. Recent works in deep neural net training (You et al., 2017; 2020) have showed that in large batch scenarios, adaptive methods tend to converge faster in training. Since m is the number of iterations in one epoch, meaning that small m gives large batch size, our theory supports these previous findings. However, the dependence on d could still be confounding; one possible explanation is that this number can be reduced when the gradients are sparse (Duchi et al., 2011).

6 EXPERIMENTS

In this section, we compare the empirical ormances of different methods on MNIST and CIFAR-10 to show the acceleration effect of adaptive step size and random shuffling. We also empirically study and validate the consistency assumption to show that this is easy to verify and reasonable to use.

6.1 COMPARISON ON MNIST AND CIFAR-10

To investigate the effect of adaptive step size and random shuffling, we test four different optimizers in our experiments. We include SGD and AdaGrad to confirm the existing phenomenon that adaptive ratio accelerates the convergence of training. We also show results of the modified counterparts, SGD-shuffle and AdaGrad-window, to demonstrate the additional benefits of shuffling in training. Both adaptive methods are taken to be the more practical diagonal version.

For our first experiment, we compare the results of four methods for logistic regression on MNIST. To further examine the ormance on nonconvex problems, we train ResNet-18 (He et al., 2015) for the classification problem on CIFAR-10. To back up our theoretical results in the last section where the convergence on the minimum of gradients across epochs is established, we report the best train loss and best test accuracy up-to-current-epoch in figure 1. We can see that adaptive methods perform better than SGD methods at the end in both training and testing. For the first few epochs of ResNet-18 training, we argue that the comparison seems off because of the constant effect in the convergence rate where this effect dies out when the epoch number increases. We can also see that SGD-shuffle and AdaGrad-window exhibit better convergence than their counterparts in training. The details for the experiments are in the appendix.

Figure 1: Left: best train loss and test accuracy up-to-current-epoch of logistic regression on MNIST. Right: best train loss and test accuracy up-to-current-epoch of ResNet-18 on CIFAR-10.

6.2 IS THE CONSISTENCY ASSUMPTION VALID?

To verify the consistency assumption, we create an $d \times m$ matrix $\boldsymbol{G}_t$ to save the m mini-batch gradients of each epoch. At the end of each epoch, we calculate $\|\boldsymbol{G}_t\boldsymbol{e}\|, \|\boldsymbol{G}_t\boldsymbol{e}_1\|, ..., \|\boldsymbol{G}_t\boldsymbol{e}_m\|$ and the corresponding consistency ratio. Then we clear the values in $\boldsymbol{G}_t$ and proceed to the next epoch.

In figure 2, we plot these squares of l_2-norms against epochs as well as the consistency ratio in training of the two experiments using AdaGrad-window in the previous subsection. It can be seen that $\|\boldsymbol{G}_t\boldsymbol{e}\|^2$ always floats on top of $\|\boldsymbol{G}_t\boldsymbol{e}_1\|^2, ..., \|\boldsymbol{G}_t\boldsymbol{e}_m\|^2$ throughout epochs, thus leading to the consistency ratio being upper bounded by some small constant in both cases. For the MNIST dataset, we plot out results of the first 100 epochs where the squares of l_2-norms stabilize after 30 epochs. The consistency ratio increases at first and then stays closed to a reasonable small constant after the l_2-norms stabilize. For the CIFAR-10 dataset, the consistency ratio shows a decreasing trend at first and then vibrates near 1. Furthermore, it can be seen that the minimum value of $\|\boldsymbol{G}_t\boldsymbol{e}\|$ up-to-current-epoch, i.e. $\min_{1 \le t \le T} \nabla f(\boldsymbol{x})$, is decreasing, which is consistent with our main theoretical findings.

Why won't a simple shuffling version of AdaGrad work? A simple modification of AdaGrad using shuffling would be using the same definition of the second-moment matrix $\boldsymbol{V}$ and sampling mini-batches in an epoch without replacement. However, this version does not exhibit better convergence since it would need an assumption of $\|\boldsymbol{G}_t\boldsymbol{e}\| \ge c(\sum_{s=1}^{t}\sum_{i=1}^{m}\|\boldsymbol{G}_s\boldsymbol{e}_i\|^2/t)^{1/2}$ for some constant c to guarantee that the sufficient descent can be written into the same order of gradient norms. However, this assumption does not hold for AdaGrad as we test in ResNet-18 on CIFAR-10. In figure 3, although $\|\boldsymbol{G}_t\boldsymbol{e}\|^2$ floats on top of $\|\boldsymbol{G}_t\boldsymbol{e}_1\|^2, ..., \|\boldsymbol{G}_t\boldsymbol{e}_m\|^2$ in each epoch. The ratio $(\sum_{s=1}^{t}\sum_{i=1}^{m}\|\boldsymbol{G}_s\boldsymbol{e}_i\|^2/t)^{1/2}/\|\boldsymbol{G}_t\boldsymbol{e}\|$ continues to increase.

Figure 2: Top: Squares of l_2-norms and consistency ratios of logistic regression on MNIST. Bottom: Squares of l_2-norms and consistency ratios of ResNet-18 on CIFAR-10. For the squares plot on the left, the connected red dots represent $\|\boldsymbol{G}_t e\|^2$ and the purple dots represent $\|\boldsymbol{G}_t e_1\|^2, ..., \|\boldsymbol{G}_t e_m\|^2$ in epoch t. Both uses the AdaGrad-window optimizer.

Figure 3: Squares of l_2-norms and the ratio $(\sum_{s=1}^{t} \sum_{i=1}^{m} \|\boldsymbol{G}_s e_i\|^2/t)^{1/2}/\|\boldsymbol{G}_t e\|$ of of the simple shuffling version of AdaGrad in ResNet-18 on CIFAR-10.

7 CONCLUSION

In this paper, we provide a novel analysis to demonstrate that adaptive gradient methods can be faster than SGD after finite epochs in non-convex and random shuffling settings. We prove that AdaGrad-window and AdaGrad-truncation obtain a convergence rate of $\tilde{O}(T^{-1/2})$ for first-order stationary points, a significant improvement compared with existing works. The key element is the new consistency assumption coming from a general phenomenon in experiments. We also investigate the computational complexity and show that our theory supports recent findings on training with large batch sizes. We believe that this paper is a good start that could lead to analysis and practice in more general settings.

REFERENCES

Naman Agarwal, Brian Bullins, Xinyi Chen, Elad Hazan, Karan Singh, Cyril Zhang, and Yi Zhang. Efficient full-matrix adaptive regularization. In *International Conference on Machine Learning*, pp. 102–110, 2019.

Zeyuan Allen-Zhu. Natasha 2: Faster non-convex optimization than sgd. In *Advances in neural information processing systems*, pp. 2675–2686, 2018.

Xiangyi Chen, Sijia Liu, Ruoyu Sun, and Mingyi Hong. On the convergence of a class of adam-type algorithms for non-convex optimization. In *International Conference on Learning Representations*, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(Jul):2121–2159, 2011.

Cong Fang, Chris Junchi Li, Zhouchen Lin, and Tong Zhang. Spider: Near-optimal non-convex optimization via stochastic path-integrated differential estimator. In *Advances in Neural Information Processing Systems*, pp. 689–699, 2018.

Jeff Haochen and Suvrit Sra. Random shuffling beats SGD after finite epochs. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *International Conference on Machine Learning*, volume 97, pp. 2624–2633, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Yurii Nesterov. *Lectures on Convex Optimization*. Springer Publishing Company, Incorporated, 2nd edition, 2018. ISBN 3319915770.

Lam M Nguyen, Quoc Tran-Dinh, Dzung T Phan, Phuong Ha Nguyen, and Marten van Dijk. A unified convergence analysis for shuffling-type gradient methods. *arXiv preprint arXiv:2002.08246*, 2020.

Matthew Staib, Sashank J Reddi, Satyen Kale, Sanjiv Kumar, and Suvrit Sra. Escaping saddle points with adaptive gradient methods. *arXiv preprint arXiv:1901.09149*, 2019.

T. Tieleman and G. Hinton. Lecture 6.5—RmsProp: Divide the gradient by a running average of its recent magnitude. COURSERA: Neural Networks for Machine Learning, 2012.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2017.

Rachel Ward, Xiaoxia Wu, and Leon Bottou. Adagrad stepsizes: Sharp convergence over nonconvex landscapes, from any initialization. *arXiv preprint arXiv:1806.01811*, 2018.

Yang You, Igor Gitman, and Boris Ginsburg. Large batch training of convolutional networks, 2017.

Yang You, Jing Li, Sashank Reddi, Jonathan Hseu, Sanjiv Kumar, Srinadh Bhojanapalli, Xiaodan Song, James Demmel, Kurt Keutzer, and Cho-Jui Hsieh. Large batch optimization for deep learning: Training bert in 76 minutes. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=Syx4wnEtvH.

K-B Yu. Recursive updating the eigenvalue decomposition of a covariance matrix. *IEEE Transactions on Signal Processing*, 39(5):1136–1145, 1991.

Manzil Zaheer, Sashank Reddi, Devendra Sachan, Satyen Kale, and Sanjiv Kumar. Adaptive methods for nonconvex optimization. In *Advances in neural information processing systems*, pp. 9793–9803, 2018.

Dongruo Zhou, Yiqi Tang, Ziyan Yang, Yuan Cao, and Quanquan Gu. On the convergence of adaptive gradient methods for nonconvex optimization. *arXiv preprint arXiv:1808.05671*, 2018.