Sequence-to-Set Generative Models

Abstract

In this paper, we propose a sequence-to-set method that can transform any sequence generative model based on maximum likelihood to a set generative model where we can evaluate the utility/probability of any set. An efficient importance sampling algorithm is devised to tackle the computational challenge of learning our sequence-to-set model. We present GRU2Set, which is an instance of our sequence-to-set method and employs the famous GRU model as the sequence generative model. To further obtain permutation invariant representation of sets, we devise the SetNN model which is also an instance of the sequence-to-set model. A direct application of our models is to learn an order/set distribution from a collection of e-commerce orders, which is an essential step in many important operational decisions such as inventory arrangement for fast delivery. Based on the intuition that small-sized sets are usually easier to learn than large sets, we propose a size-bias trick that can help learn better set distributions with respect to the ℓ_1-distance evaluation metric. Two e-commerce order datasets, TMALL and HKTVMALL, are used to conduct extensive experiments to show the effectiveness of our models. The experimental results demonstrate that our models can learn better set/order distributions from order data than the baselines. Moreover, no matter what model we use, applying the size-bias trick can always improve the quality of the set distribution learned from data.

1   Introduction

Learning a generative model [Goodfellow et al., 2014, Kingma and Welling, 2014] from data to generate random samples is a fundamental unsupervised learning task. In many real applications, the data, such as customer orders and drug packages, can be represented by sets. Learning a set generative model can boost many important applications such as simulating users' demand of e-commerce orders for inventory arrangement [Wu et al., 2021]. However, in literature, little attention has been paid to generative models for sets.

In this paper, we study the problem of learning a set generative model from data. Specifically, we study sets containing some categorical items from a finite ground set. Some previous studies [Benson et al., 2018, Wu et al., 2021] proposed traditional statistical models to learn the set generative model, while how to employ deep learning to design set generative models remains largely untouched. Meanwhile, deep generative models for sequence data [Hochreiter and Schmidhuber, 1997, Schäfer and Zimmermann, 2006, Cho et al., 2014, Devlin et al., 2018] have been extensively studied. Since the only difference between a sequence and a set is that the order of items does not matter in a set, we propose to leverage a sequence generative model to build a set generative model.

A natural idea of converting a random sequence to a random set is to just ignore the order of items. However, for a set, the number of possible sequences that can be regarded as equivalent to the set is exponential to the number of items. This brings us a serious computational challenge where we need to enumerate all the equivalent sequences for a set when learning the parameters of the

model. Traditional statistical models [Benson et al., 2018, Wu et al., 2021] along this line either make unrealistic independent assumptions on items or run a learning algorithm of complexity exponential to set sizes to only deal with small sets. These constrained treatments undermine the model's ability to capture the complex correlations among items in sets.

To tackle the computational challenge while still well capturing the correlations among items, in this paper, we make the following technical contributions.

In Section 3, we first show that we can convert any sequence generative model based on maximum likelihood, such as RNN [Schäfer and Zimmermann, 2006] and DeepDiffuse [Islam et al., 2018], to a set generative model. We call our method Sequence-to-Set. To address the computational challenge, we propose an efficient importance sampling algorithm to estimate the gradient of the log-likelihood function of our Sequence-to-Set model.

In Section 4, to capture the complex item correlations, we propose two deep models GRU2Set and SetNN, which are instances of our Sequence-to-Set model. GRU2Set directly uses the GRU as an essential building block, while SetNN is designed for obtaining permutation invariant set embeddings when learning a set generative model. We discuss that GRU2Set and SetNN can express any set distributions as long as we increase the model capacity.

To learn a better set distribution from data, in Section 5, we reveal that we often need to modify the empirical size distribution of the training data and propose a heuristic to do so. This size-bias trick can be applied to all set generative models aiming at learning a set distribution.

We conduct extensive experiments using two e-commerce datasets TMALL and HKTVMALL, and report the experimental results in Section 6. The experimental results clearly show the superiority of our models to the baselines and the effectiveness of our size-bias trick.

2   Related Work

Learning a set generative model is often regarded as learning a choice model for subset selection. Along this line, Benson et al. [2018] proposed a discrete choice model (DCM) to model the utility/probability that users select a specific set. Wu et al. [2021] utilized representation learning to design a parameterized Markov Random Walk to model how users select random sets from an item graph. Both [Benson et al., 2018] and [Wu et al., 2021] are set generative models, though they are not deep models. To achieve practical computational efficiency, both [Benson et al., 2018] and [Wu et al., 2021] only handle small sets and compromise on modeling high-order item correlations.

To model the permutation invariant nature of sets, Ruiz et al. [2017] used the sum or max of item embedding as the set embedding. Zaheer et al. [2017] systematically investigated the theory of permutation invariant functions. Stelzner et al. [2020] proposed a generative model for point clouds based on GAN [Goodfellow et al., 2014] and Set Transformer [Lee et al., 2019]. Although a point cloud is a set of 2D-coordinates, we cannot use the point cloud generative model [Stelzner et al., 2020] to solve our problem as the model outputs continuous random variables instead of categorical data. Kosiorek et al. [2020] presented another generative model for sets of real-valued vectors based on Set Transformer [Lee et al., 2019] and their generating process is based on VAE [Kingma and Welling, 2014]. A disadvantage of using GAN or VAE to train a generative model is that it would be difficult to evaluate the probability density of a random sample. Normalizing Flows are powerful generative models based on solid statistical theories. However, the study of Discrete Flows is still in its infancy [Hoogeboom et al., 2019, Tran et al., 2019] and no existing works have investigated using Discrete Flows to learn set distributions.

To sum up, existing works on set generative models either deal with sets of real-valued vectors which are different from categorical sets, or adopt non-deep models which need to compromise on capturing item correlations to make the computation efficient. It is still urgent to design deep generative models for categorical sets and propose efficient algorithms to deal with computational challenges.

3   Sequence-to-Set Generative Models

In this section, we introduce how to convert a sequence generative model to a set generative model and how to optimize the model parameters.

3.1 Converting Sequences to Sets

We first characterize the sequence generative model that we want to convert to a set generative model.

Definition 1 (Sequence Generative Model) *A sequence generative model is a model with a sequential generating process, which can be represented by a sequence of states and actions* $[s_0, a_0, s_1, a_1, ..., s_{T-1}, a_{T-1}, s_T]$, *where* s_i *is the state at time* i, a_i *is the action taken at time* i *and* s_T *is the end state. We call* $[s_0, a_0, s_1, a_1, ..., s_{T-1}, a_{T-1}, s_T]$ *a* **generating path**. *Like a finite-state machine, the sequence generative model uses each action* a_i *to* **deterministically** *update the current state* s_i *to* s_{i+1}. *For each state* s, *the sequence generative model has a corresponding probability distribution* $p(a \mid s; \theta)$ *indicating the probability of choosing action* a *when the current state is* s, *where* θ *is the parameters of the sequence generative model.*

Our definition of the sequence generative model can cover a wide range of models that can generate items in a sequential manner. For example, the commonly used sequence model RNN is an instance, where the state is the history vector H and an action is to choose the next word/item. Moreover, influence diffusion models such as the Independent Cascade (IC) model [Goldenberg et al., 2001] and the DeepDiffuse model [Islam et al., 2018] are also covered by Definition 1, since in these models the state at time t is the set of activated nodes until time t and the action a_t is to select the group of nodes to be activated at time $t + 1$.

To convert a sequence generative model in Definition 1 to a set generative model, we need to associate each state s with a **state-associated set** S_s. For example, in an RNN, we can define S_{s_t} as the set of items generated in the first t steps. In the IC model, we can define S_{s_t} as the set of nodes activated at or before time t.

We say that a generating path $l = [s_0, a_0, \ldots, s_{T-1}, a_{T-1}, s_T]$ can **induce** a set S if $S = S_{s_T}$. Let $L(S) = \{l \mid l \text{ can induce } S\}$ be the **path set** of S. As the sequence generative model has the probability distribution $p(a \mid s; \theta)$ indicating the probability of take a as the next action given the current state s, we can derive the probability of having a path $l = [s_0, a_0, \ldots, s_{T-1}, a_{T-1}, s_T]$ as

$$p(l; \theta) = p(a_0 \mid s_0; \theta) \times p(a_1 \mid s_1; \theta) \times \cdots \times p(a_T \mid s_T; \theta).$$

Therefore, given a sequence generative model with parameters θ, the probability to induce a set S is

$$p(S; \theta) = \sum_{l \in L(S)} p(l; \theta).$$

3.2 Parameter Learning

Suppose we have a collection (multiset) of observed sets $\mathcal{S} = \{S_1, S_2, ..., S_N\}$. We want to use $\mathcal{S}$ as the training data to learn a sequence model which can generate the observed sets. We adopt maximum likelihood estimation to learn the parameters θ. Specifically, the loss function is

$$\mathcal{L}(\theta) = -\sum_{i=1}^{N} \log p(S_i; \theta) = -\sum_{i=1}^{N} \log \left(\sum_{l \in L(S_i)} p(l; \theta) \right)$$

We apply stochastic gradient descent based algorithms to minimize the loss function. The stochastic gradient w.r.t. an observation S is $\nabla \log p(S; \theta) = \nabla \log \left(\sum_{l \in L(S)} p(l; \theta) \right)$. As in the log-sum term of $p(S; \theta)$, the number of paths that can induce S is often exponential to $|S|$ (in some sequence generative model the number of such paths is even infinite), it is very challenging to evaluate $\nabla \log p(S; \theta)$ exactly.

To tackle the computational challenging in computing $\nabla \log p(S; \theta)$, we first find that $\nabla \log p(S; \theta)$ can be regarded as an expectation as follows.

$$\nabla \log p(S; \theta) = \frac{\sum_{l \in L(S)} \nabla p(l; \theta)}{p(S; \theta)} = \frac{\sum_{l \in L(S)} p(l; \theta) \nabla \log p(l; \theta)}{p(S; \theta)} = E_{l \sim p(l|S;\theta)}[\nabla \log p(l; \theta)],$$

where $p(l \mid S; \theta) = \frac{p(l;\theta)}{p(S;\theta)}$ is a posterior distribution indicating the probability that a given set S is generated by the path l. Therefore, $\nabla \log p(S; \theta)$ can be seen as the expected value of $p(l; \theta)$ where the random variable l follows the posterior distribution $p(l \mid S; \theta)$.

129 We can apply Monte Carlo method to estimate $\nabla \log p(S; \theta) = E_{l \sim p(l|S;\theta)}[\nabla \log p(l; \theta)]$, where the
130 key point is to sample generating paths from $p(l|S; \theta)$. A naive idea is to use rejection sampling,
131 where we use the model with parameters θ to generate random paths and reject those that cannot
132 induce S. Obviously such a naive implementation would be extremely inefficient as the rejection rate
133 would be very high.

To sample l from $p(l|S)$ more efficiently, we devise an important sampling method as follows. Let
$\tau(a, s, S)$ be an indicator function, where $\tau(a, s, S) = 1$ if $\exists l = [s_0, a_0, \ldots, s_{T-1}, a_{T-1}, s_T]$ such
that l induces S and $\exists i \in \{0, 1, \ldots, T-1\}$, $s_i = s \wedge a_i = a$. In our sampling algorithm, for a state
s_t, we only consider actions a_t such that $\tau(a_t, s, S) = 1$. We take such an action a_t with probability

$$q(a_t \mid s; \theta, S) = \frac{p(a_t \mid s; \theta)}{\sum_{a:\tau(a,s,S)=1} p(a \mid s; \theta)}.$$

134 Therefore, for the proposal distribution $q(l; \theta, S)$ for $l = [s_0, a_0, \ldots, s_{T-1}, a_{T-1}, s_T]$ in our impor-
135 tance sampling is

$$q(l; \theta, S) = q(a_0 \mid s_0; \theta, S) \times q(a_1 \mid s_2; \theta, S) \times \cdots \times q(a_{T-1} \mid s_{T-1}; \theta, S)$$

136 The (unnormalized) importance weight of l is

$$r(l; \theta) = \left(\sum_{a:\tau(a,s_0,S)=1} p(a \mid s_0; \theta) \right) \times \left(\sum_{a:\tau(a,s_1,S)=1} p(a \mid s_1; \theta) \right) \times \cdots \times \left(\sum_{a:\tau(a,s_{T-1},S)=1} p(a \mid s_{T-1}; \theta) \right)$$

137 Clearly, we have

$$r(l; \theta)q(l; \theta, S) \propto p(a_0|s_0; \theta)p(a_1|s_1; \theta)...p(a_{T-1}|s_{T-1}; \theta) = p(l; \theta).$$

138 This shows the correctness of the sampling method.

139 **An EM perspective** Using our importance sampling algorithm to estimate $\nabla \log p(S; \theta)$ in min-
140 imizing the loss function $\mathcal{L}(\theta)$ can be interpreted from an Expectation-Maximization algorithm's
141 perspective. Our method is actually a Monte Carlo EM algorithm if we treat a generating path l
142 as a latent variable. In the E-step, we sample the latent variable l from the posterior distribution
143 $p(l|S; \theta^{old})$. Our importance sampling can boost the efficiency of the E-step. In the M-step, we
144 reconstruct an object function which is $\sum_i^M r(l_i)R^{-1} \log p(l_i; \theta^{old})$, where M is the number of
145 samples and $R = \sum_{i=1}^M r(l_i)$. To maximize this function, we update θ by gradient based meth-
146 ods, such as $\theta^{new} = \theta^{old} + \eta \sum_{i=1}^M r(l_i)R^{-1}\nabla_\theta \log p(l_i; \theta^{old})$, where η is the learning rate and
147 $\sum_{i=1}^M r(l_i)R^{-1}\nabla_\theta \log p(l_i; \theta^{old})$ is estimated by our importance sampling algorithm.

148 **MRW as an instance of Sequence2Set** We show that the Markov Random Walk(MRW) model
149 [Wu et al., 2021] is also an instance of our Sequence2Set model. The sequence model in MRW is
150 a random walk on the item graph [Wu et al., 2021] where a node is an item and we have a special
151 stop item κ. The state s_t at time t is associated with a set S_{s_t} which includes all the items visited
152 until time t. An action a_t taken at time t given the state s_t is to jump to an item i_t from i_{t-1}, the item
153 visited at time $t-1$. Once the stop item κ is visited, the random walk terminates. The probability
154 of jumping from i_{t-1} to $i_t = i$ is parameterized as $p(i_t = i \mid s_{t-1}; \theta)$, where θ is the embeddings
155 of items. Specifically, in MRW, $p(i_t = i \mid s_{t-1}; \theta) = \frac{\exp(e_i^\top e_{i_{t-1}})}{\sum_j \exp(e_j^\top e_{i_{t-1}})}$, where e_i is the embedding
156 vector of item i. When an action a is jumping to an item $i \neq \kappa$, the indicator $\tau(a, s, S) = 1$ if $i \in S$.
157 When an action a is jumping to the stop item κ, $\tau(a, s, S) = 1$ if $S_s = S$. Wu et al. [2021] propose
158 an algorithm of complexity exponential to $|S|$ to calculate the gradient $\nabla \log p(S; \theta)$ for learning the
159 item embeddings and thus, only small sets of size at most 4 are considered in [Wu et al., 2021]. If we
160 adopt our important sampling algorithm, we can deal with large sets.

4 GRU2Set and SetNN

162 In this section, we propose two deep Sequence-to-Set models which are called GRU2Set and Set
163 Neural Networks (SetNN). We first introduce some general settings that will be used in both GRU2Set
164 and SetNN.

165 **Item embedding and stop item**   We also adopt item embeddings, which should be learned from
166 the training dataset, to parameterize the probability $p(a \mid s; \theta)$ in the sequence generative model. We
167 assign an embedding vector $e_i \in \mathbb{R}^d$ to each item i. Similar to MRW [Wu et al., 2021], we also add a
168 stop item κ where once we add κ to the set associated to the current state, we stop the generating
169 process. The stop item κ also has an embedding vector $e_\kappa \in \mathbb{R}^d$.

170 **Sparse item graph**   In our Sequence-to-Set model, the indicator func-
171 tion $\tau(a, s, S)$ is a key for us to efficiently sample generating paths from
172 the posterior distribution $p(l \mid S; \theta)$. Intuitively, $\tau(a, s, S)$ indicates
173 what actions are valid given the current state s and the induced set S.
174 To further boost the efficiency of our importance sampling algorithm,
175 we make extra constraints on the items that can be added in the next
176 step when we are given the current state s. To do so, we build an item
177 graph $G = \langle V, E \rangle$, where V is the set of items plus the stop item κ and
178 $(i, j) \in E$ if there is a set S in the training dataset $\mathcal{S}$ such that $i \in S$
179 and $j \in S$. The stop item is connected to all the other items. When
180 using our importance sampling algorithm, given the current state s as-
181 sociated with a set $S_s \subseteq S$, $\tau(a, s, S) = 1$ if action a is adding an item
182 $i \in S \cap \text{Neighbor}(S_s)$, where $\text{Neighbor}(S_s)$ is the set of neighbors to
183 items in S_s. When starting from the first state s_0 associated with a set

Figure 1: An example of
sparse item graph. The
item κ is the stop item.

184 $S_{s_0} = \emptyset$, we set $\text{Neighbor}(S_s) = V \setminus \{\kappa\}$. In real set datasets such as TMALL and HKTVMALL
185 used in our experiments, such an item graph built from training datasets is often very sparse. There-
186 fore, we call the item graph the **sparse item graph**. Clearly, the sparsity of the item graph can help
187 boost the efficiency of generating random sets from a learned model.

188 **Choice vector**   In our model design, the conditional probability $p(a \mid s; \theta)$ is the key to control the
189 generating process. Exploiting the idea of representation learning, we represent each state s with an
190 embedding vector $c_s \in \mathbb{R}^d$. We call c_s the **choice vector** of s. Given s, we control the probability of
191 adding i as the next item as

$$p(i \mid s; \theta) = \frac{\exp(c_s^\top e_i)}{\sum_{j \in \text{Neighbor}(S_s)} \exp(c_s^\top e_j)}.$$

192 The sparsity of the item graph can make computing the normalization term in $p(i \mid s; \theta)$ efficient.
193 Note that in MRW [Wu et al., 2021], the choice vector c_s is the embedding of the last item visited so
194 far. We will see that in GRU2Set and SetNN, we use deep neural nets to aggregate the embeddings of
195 all the items visited so far to obtain the choice vector c_s. The initial choice vector c_{s_0} is trainable.

4.1   GRU2Set

197 We leverage GRU [Cho et al., 2014] to build our first sequence-to-set model, since GRU is one of the
198 most popular sequential model based on RNN and its computational cost is low. We set the history
199 vector H of GRU as a d-dimensional vector and H is regarded as the choice vector of the current
200 state. The initial history vector H_0 is trainable and H is updated according to the design of GRU.
201 The state-associated set S_{s_t} for the state s_t at time t is just the set of items added in the first t steps of
202 the sequence generating process of GRU. When the stop item is added, we terminate the generating
203 process. Due to limited space, the overview of GRU2Set is put in Appendix.

4.2   SetNN

205 The choice vector c_s can be regarded as the embedding of the set S_s. In GRU2Set, the choice vector,
206 which is the history vector H, is sensitive to the order of items added to S_s. As sets are permutation
207 invariant, we hope to have a sequence-to-set model which can also produce permutation invariant
208 representations of sets. Therefore, we develop the Set Neural Networks (SetNN) where the key idea is
209 to design a permutation invariant aggregation of embeddings of items in a set. The following theorem
210 by Zaheer et al. [2017] guides our model design.

211 **Theorem 1** *([Zaheer et al., 2017]) A function $f(X)$ operating on a set X having elements from a*
212 *countable universe, is a set function, i.e., invariant to the permutation of instances in X, iff it can be*
213 *decomposed in the form $\rho(\sum_{x \in X} \Phi(x))$ for suitable transformations Φ and ρ.*

Figure 2: Overview of SetNN. We don't show the situation when we add stop item. If the action is adding the stop item, we end the process immediately.

$\Phi(x)$ can be viewed as the embedding of x and the sum over $\Phi(x)$ can be replaced by other aggregate operators such as mean or pooling. In SetNN, we use an MLP to express the function ρ in Theorem 1 to obtain the embedding (choice vector) c_s of S_s for any state s. Fig 2 shows the overview of SetNN.

4.3 Expressive Power of GRU2Set and SetNN

Compared to SetNN, our GRU2Set model uses the history vector H. By the expressive power of RNN [Schäfer and Zimmermann, 2006], as we increase the embedding dimension d, hidden neural units and layers in GRU module, the history vector H of GRU2Set can approximate any function on a finite history path arbitrarily close. Then, of course, H can express any permutation invariant function on sets which implies that the expressive power of GRU2Set is more than SetNN.

To explore the expressive power of SetNN, we first give a recursive definition of the probability that a set S is generated by SetNN, denoted by $p(S)$, as follows.

$$
\begin{aligned}
p(S) &= p(\kappa|S)\gamma(S) \quad (\kappa \text{ is the stop item}) \\
\gamma(S) &= \sum_{x \in S} p(x|S \setminus \{x\})\gamma(S \setminus \{x\}) \\
\gamma(\emptyset) &= 1,
\end{aligned}
\tag{1}
$$

where $p(x|S \setminus \{x\})$ is the conditional probability of adding item x to the set $S \setminus \{x\}$ and $\gamma(S)$ is the probability of reaching a state s such that $S_s = S$ in SetNN. The following theorem shows that Eq. (1) is general enough to cover all possible set distributions.

Theorem 2 *For any distribution Q on all subsets of a ground set of items, there exists a group of transition probabilities $p(x|S)$ and $p(\kappa|S)$, such that $q(S) = p(S)$ hold for any S, where $p(S)$ is defined in Eq. (1).*

The proof of Theorem 2 can be found in Appendix B. As we increase the capacity of the MLP in SetNN, SetNN can represent any conditional probability $p(x|S)$ and $p(\kappa|S)$, and as a result of Theorem 2, SetNN and GRU2Set can express any set distributions.

5 Size-Bias Trick for Improving Learned Set Distributions

In this section, we propose a **size-bias** trick that can help reduce the distance between the ground truth set distribution $p^*(S)$ and the learned distribution $p(S)$, where $p(S)$ can be learned by any generative model not limited to our Sequence-to-Set models. We first decompose the ground truth distribution $p^*(S)$ when $|S| = k$ as

$$
p^*(S) = p^{*(k)}(S)p_k^*,
$$

where $p_k^* = \sum_{A:|A|=k} p(A)$ is the total probability mass of sets of size k, and $p^{*(k)}(S) = \frac{p(S)}{p_k^*}$ is the probability that a random set is S conditioned on that the set size is k. Suppose we know the real size distribution p_k^* and we have $q^{(k)}(S)$ as an estimation of $p^{*(k)}(S)$ for each k. How can we construct a distribution $q(S)$ close to $p^*(S)$? An intuitive way is combine $q^{(k)}(S)$ and p_k^* such that $q(S) = q^{(k)}(S)p_k^*$ if $|S| = k$ [Stelzner et al., 2020, Benson et al., 2018]. But is this intuitive way always the best? The answer is no.

Let K be the largest possible set size. To find the best size distribution q_k for our estimation $q^{(k)}$, we consider the following optimization aiming at minimizing the KL-divergence between the distribution $q(S) = q^{(k)}(S)q_k$ and the ground truth $p^*(S)$.

$$
\begin{aligned}
\min_{q_k} \quad & KL(q||p^*) = \sum_S q(S) \log \frac{q(S)}{p^*(S)} \\
s.t. \quad & q(S) = q_k \times q^{(k)}(S), \ \forall |S| = k \\
& 0 \le q_k \le 1, \forall k \\
& \sum_{k=1}^K q_k = 1
\end{aligned}
\tag{2}
$$

Since we do not know $p^*(S)$, we cannot solve Eq. (2) exactly. However, we still can tell if setting $q_k = p_k^*$ is the optimal solution to some extend.

Let $f_k(q_k) = \sum_{S:|S|=k} q(S) \log \frac{q(S)}{p^*(S)}$. We have $KL(q||p^*) = \sum_k f_k(q_k)$. Note that $f_k(q_k)$ only depends on q_k. We can interpret Eq. (2) as a portfolio optimization problem. There are K projects, q_k is the investment for project k and $-f_k(q_k)$ is the revenue of project k. To decide the best portfolio q_k, we check the derivative of $f_k(q_k)$, which indicates the marginal revenue. We have

$$
f_k'(q_k) = 1 + \sum_{S:|S|=k} q^{(k)}(S) \log \frac{q(S)}{p^*(S)}
$$

By taking $q_k = p_k^*$, we have

$$
f_k'(p_k^*) = 1 + \sum_{S:|S|=k} q^{(k)}(S) \log \frac{q^{(k)}(S)}{p^{*(k)}(S)} = 1 + KL\left(q^{(k)}(S)||p^{*(k)}(S)\right)
$$

As the estimation quality of $q^{(k)}(S)$ often varies for different k, the derivative $f_k'(p_k^*)$ probably also varies for different k, making $q_k = p_k^*$ not a stationary point. Therefore, we probably need to set q_k different from p_k^* for solving Eq. (2). We first make the following reasonable assumption.

Assumption 1 *Small-sized sets are easier to learn than large sets. In other words, $q^{(k)}(S)$ estimates $p^{*(k)}(S)$ better as the set size k decreases.*

Based on Assumption 1, compared to p_k^*, we should "invest" more on small set sizes to construct the "portfolio" (size distribution) q_k. Therefore, we set q_k slightly bigger than p_k^* for small k, and set q_k smaller than p_k^* for big k. To address the issue of not knowing p_k^*, we can resort to the empirical size distribution of the training dataset, which is a good estimation of the real size distribution p^*. We construct a biased size distribution q_k by adopting the following heurisitc.

Constructing Biased Size Distribution Suppose the empirical size distribution of the training data $\mathcal{S}$ is $[p_1, p_2, ..., p_K]$. We first calculate the rest proportion by $r_k = p_k/(p_k + p_{k+1} + ... + p_K)$, which means $p_i = (1 - r_1)...(1 - r_{i-1})r_i$. Then we calculate $r_k' = \max\{r_k + k\sqrt{|V|/|\mathcal{S}|}, 1\}$, where V is the set of all items. We construct a biased size distribution $[q_1, q_2, \ldots, q_K]$ by setting $q_i = (1 - r_1')...(1 - r_{i-1}')r_i'$.

6 Experiments

Datasets We did our empirical study on two rea-world datasets which are both the orders form online e-commerce platforms. This first dataset is TMALL (https://www.tmall.com) dataset

Table 1: Basic statistics

dataset	#item	#training sets	average #testing sets	average #edge
TMALL	1,363	100,000	393,226	60,956
HKTVMALL	782	200,000	616,652	53,853

Table 2: Size distribution of TMALL and HKTVMALL

	1	2	3	4	5	6	≥ 7
TMALL	38%	18%	14%	10%	7%	5%	8%
HKTVMALL	42%	17%	11%	8%	6%	5%	12%

which contains **1363** items and orders from August 2018 to March 2019. We treated the collection of orders in each month as an instance and in total we have 8 instances for the TMALL dataset. The second dataset is HKTVMALL (https://www.hktvmall.com) which contains **728** items form the supermarket sector and orders from February 2020 to September 2020. Similar to TMALL, we also treated HKTVMALL as 8 instances where each instance is the collection of orders in each month. For both dataset, We split all the orders in a month to a training dataset $\mathcal{S}_{train}$ and a testing dataset $\mathcal{S}_{test}$, where the size of $\mathcal{S}_{train}$ is 100,000 for Tmall and 200,000 for HKTVmall. The datasets can be found in the source code. We report the sparsity of item graphs and statistics of the datasets in Table 1. The set size distribution of each dataset is shown in Table 2.

Experiment Setting and Evaluation We treat the method of directly using the histogram of $\mathcal{S}_{train}$ as the benchmark method, as it is a natural and unbiased method to estimate the set distribution. Note that this benchmark method has a major disadvantage that its cannot model probabilities of any sets not showing in $\mathcal{S}_{train}$. We also choose two methods to compare which are DCM (Discrete Choice Model) [Benson et al., 2018] and MRW [Wu et al., 2021].

Following [Wu et al., 2021], for each method (except the baseline), we generate a collection $\mathcal{S}_{pred}$ of 10,000,000 random sets and use the empirical set distribution of $\mathcal{S}_{pred}$ to approximate the set distribution learned by the model. We regard the empirical distribution of the testing data $\mathcal{S}_{test}$ as the pseudo ground truth. Since the bigger $\mathcal{S}_{test}$ is, the more accurate the pseudo ground truth is, we set the size of $\mathcal{S}_{test}$ bigger than $\mathcal{S}_{train}$ as shown in Table 1. Denote by $N_{test}(S)$ the number of sets that are S in $\mathcal{S}_{test}$. Let $N_{pred}(S)$ be the number of sets that are S in $\mathcal{S}_{pred}$. We use the ℓ_1-distance between a model's (approximate) distribution and the pseudo ground truth to evaluate the effectiveness of the model. Specifically, the ℓ_1-distance can be calculated as follows.

$$\ell_1(\mathcal{S}_{test}, \mathcal{S}_{pred}) = \sum_{S \in \mathcal{S}_{test} \cup \mathcal{S}_{pred}} |\frac{N_{test}(S)}{|\mathcal{S}_{test}|} - \frac{N_{pred}(S)}{|\mathcal{S}_{pred}|}| \tag{3}$$

We set the embedding dimension of all methods as 10. For each training and testing dataset, the size bias distribution is the same for all methods and is obtained by the heuristic introduced at the end of Section 5. For all experiments, the MLP of SetNN only has one hidden layer which contains 50 neural units. All the experiments are ran on a 10 cores CPU. The optimizer we use is RMSProp with default parameter in PyTorch. The source code and data used in our experiments can be found at https://github.com/AnonymousNeurIPS2022/SetLearning.

Experiment Results Due to limited space, we only report the main experimental results. More detailed experimental results can be found in Appendix D and E.

Table 3 and Table 4 show the experimental results. We place the results of using size-bias trick below the original results. We find that both DCM and MRW never beat the benchmark method, no matter the size-bias trick is played or not. A possible reason is that in our experiments we do not make size constraints on sets, while Wu et al. [2021] constrained the set size to be at most 4 and Benson et al. [2018] set the maximum size of sets to be 5. Big sets in our data may have negative effects on learning both DCM and MRW.

We can see that applying the size-bias trick can always reduce the ℓ_1-distance significantly, which demonstrates the effectiveness of this trick. Before applying the size-bias trick, the benchmark method has the best performance which is slightly better than our models GRU2Set and SetNN.

Table 3: The performance of each groups on TMALL

Groups	0	1	2	3	4	5	6	7	Average	STDEV
Benchmark	1.11	1.02	0.91	0.90	0.94	0.94	0.93	0.85	0.95	0.07
+Size Bias	1.06	0.97	0.87	0.86	0.90	0.90	**0.89**	0.81	0.91	0.07
DCM	1.17	1.08	0.95	0.94	1.00	0.99	0.99	0.89	1.00	0.08
+Size Bias	1.10	1.01	0.90	0.89	0.94	0.93	0.93	0.84	0.94	0.07
MRW	1.14	1.07	0.99	0.96	1.02	1.02	1.03	0.92	1.02	0.06
+Size Bias	1.06	0.97	0.88	0.87	0.90	0.92	0.95	0.84	0.92	0.06
SetNN	1.12	1.01	0.92	0.89	0.90	0.91	1.01	0.89	0.96	0.08
+Size Bias	**1.04**	**0.93**	**0.84**	**0.82**	**0.85**	**0.87**	**0.89**	**0.79**	**0.88**	0.07
GRU2Set	1.11	1.04	0.89	0.90	0.94	0.94	1.00	0.90	0.97	0.07
+Size Bias	**1.02**	**0.93**	**0.83**	**0.82**	**0.85**	**0.86**	**0.89**	**0.80**	**0.87**	0.06

Table 4: The performance of each groups on HKTVMALL

Groups	0	1	2	3	4	5	6	7	Average	STDEV
Benchmark	0.73	0.87	0.91	0.84	0.81	0.87	0.81	0.80	0.83	0.05
+Size Bias	**0.70**	0.83	0.88	0.81	**0.79**	0.84	0.78	**0.77**	0.80	0.05
DCM	0.76	0.89	0.93	0.88	0.84	0.89	0.84	0.82	0.86	0.05
+Size Bias	0.72	0.84	0.89	0.83	0.80	0.85	0.79	0.78	0.81	0.05
MRW	0.80	0.91	0.94	0.88	0.88	0.90	0.85	0.85	0.88	0.04
+Size Bias	0.74	0.84	0.88	0.82	0.83	0.85	0.79	0.80	0.82	0.04
SetNN	0.82	0.86	1.00	0.84	0.89	0.92	0.84	0.84	0.88	0.05
+Size Bias	**0.71**	**0.82**	**0.87**	**0.79**	**0.79**	**0.83**	**0.76**	0.78	**0.79**	0.04
GRU2Set	0.83	0.87	0.94	0.84	0.93	0.94	0.86	0.82	0.88	0.05
+Size Bias	**0.70**	**0.80**	**0.85**	**0.78**	**0.79**	**0.82**	**0.75**	**0.75**	**0.78**	0.04

However, after applying the size-bias trick, our GRU2Set model becomes the best and it outperforms the benchmark method by 4% on TMALL and 2.5% on HKTVMALL. SetNN also outperforms the benchmark method after using the size-bias trick. This suggests that GRU2Set and SetNN may learn probabilities of small sets better than the benchmark method.

The SetNN model performs slightly worse than GRU2Set but the gap between them is small. A possible reason is that GRU2Set has stronger expressive power than SetNN as illustrated in Section 4.3. GRU2Set records the order of items added to the set, while SetNN ignores such order to achieve permutation invariant set embeddings. This shows that GRU2Set includes more information in the generating process than SetNN. However, we want to emphasize that SetNN can produce permutation invariant set embeddings while GRU2Set cannot. So if we have a downstream task that needs set embeddings, SetNN may have more advantages in this case.

7 Conclusion

In this paper, we present a Sequence-to-Set method to build generative models for set data and the SOTA method MRW is an instance of our method. To utilize deep learning in learning set distributions, we further design two models, GRU2Set and SetNN, which are two instances of our Sequence-to-Set model. To learn better set distributions from data, we also propose a size-bias trick. Experimental results on two e-commerce order datasets clearly show that our models outperform the baselines including two SOTA methods in this line of research.

For future work, we will explore using more sophisticated deep learning modules in more, such as replacing the MLP in our SetNN model with Set Transformer and substituting the RNN in GRU with more advanced sequence models. For potential negative societal impacts, learning the embeddings of items and sets might cause user privacy leakage as many other embeddings might do. Research on how to hide personal information on set data could help protect users' privacy.

References

Austin R. Benson, Ravi Kumar, and Andrew Tomkins. A discrete choice model for subset selection. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining, WSDM 2018*. ACM, 2018.

Kyunghyun Cho, Bart van Merrienboer, Çaglar Gülçehre, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder-decoder for statistical machine translation. *CoRR*, abs/1406.1078, 2014.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Jacob Goldenberg, Barak Libai, and Erika Muller. Using complex systems analysis to advance marketing theory development. 2001.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial networks. *CoRR*, 2014.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Emiel Hoogeboom, Jorn W.T. Peters, Rianne van den Berg, and Max Welling. *Integer Discrete Flows and Lossless Compression*. Curran Associates Inc., Red Hook, NY, USA, 2019.

Mohammad Raihanul Islam, Sathappan Muthiah, Bijaya Adhikari, B Aditya Prakash, and Naren Ramakrishnan. Deepdiffuse: Predicting the'who'and'when'in cascades. In *2018 IEEE International Conference on Data Mining (ICDM)*, pages 1055–1060. IEEE, 2018.

Sudeep Kamath, Alon Orlitsky, Dheeraj Pichapati, and Ananda Theertha Suresh. On learning distributions from their samples. In *Conference on Learning Theory*, pages 1066–1100. PMLR, 2015.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

Adam R. Kosiorek, Hyunjik Kim, and Danilo J. Rezende. Conditional set generation with transformers. *CoRR*, 2020.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam R. Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *ICML 2019*. PMLR, 2019.

Francisco J. R. Ruiz, Susan Athey, and David M. Blei. SHOPPER: A probabilistic model of consumer choice with substitutes and complements. *CoRR*, abs/1711.03560, 2017.

Anton Maximilian Schäfer and Hans Georg Zimmermann. Recurrent neural networks are universal approximators. In Stefanos D. Kollias, Andreas Stafylopatis, Włodzisław Duch, and Erkki Oja, editors, *Artificial Neural Networks – ICANN 2006*, pages 632–640, Berlin, Heidelberg, 2006. Springer Berlin Heidelberg.

Karl Stelzner, Kristian Kersting, and Adam R Kosiorek. Generative adversarial set transformers. In *Workshop on Object-Oriented Learning at ICML*, volume 2020, 2020.

Dustin Tran, Keyon Vafa, Kumar Krishna Agrawal, Laurent Dinh, and Ben Poole. *Discrete Flows: Invertible Generative Models of Discrete Data*. Curran Associates Inc., Red Hook, NY, USA, 2019.

Tongwen Wu, Yu Yang, Yanzhi Li, Huiqiang Mao, Liming Li, Xiaoqing Wang, and Yuming Deng. *Representation Learning for Predicting Customer Orders*. Association for Computing Machinery, New York, NY, USA, 2021. ISBN 9781450383325.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.