Beyond Consensus: Perspectivist Modeling and Evaluation of Annotator Disagreement in NLP

Abstract

Annotator disagreement is widespread in NLP, particularly for subjective and ambiguous tasks such as toxicity detection and stance analysis. While early approaches treated disagreement as noise to be removed, recent work increasingly models it as a meaningful signal reflecting variation in interpretation and perspective. This survey provides a unified view of disagreement-aware NLP methods. We first present a domain-agnostic taxonomy of the sources of disagreement spanning data, task, and annotator factors. We then synthesize modeling approaches using a common framework defined by prediction targets and pooling structure, highlighting a shift from consensus learning toward explicitly modeling disagreement, and toward capturing structured relationships among annotators. We review evaluation metrics for both predictive performance and annotator behavior, noting that most fairness evaluations remain descriptive rather than normative. We conclude by identifying open challenges and future directions, including integrating multiple sources of variation, developing disagreement-aware interpretability frameworks, and grappling with the practical tradeoffs of perspectivist modeling.

1 Introduction

NLP applications largely rely on supervised learning, which depends on annotated data. Annotation is often operationalized through majority voting, an assumption that can be problematic—particularly for complex tasks where true experts may be outnumbered, or for inherently ambiguous tasks that admit multiple valid interpretations. Majority aggregation can also obscure minoritized perspectives, leading to biased models and representational harm (Blodgett et al., 2020; Gordon et al., 2021). This "single ground truth" assumption has been increasingly challenged, especially with the rise of subjective NLP tasks such as toxic language detection and quality estimation. Early critiques

appear in Aroyo and Welty (2015), which questions the existence of a unique truth in crowd-sourced annotation. This shift aligns with broader efforts to make NLP systems more inclusive, as consensus-based labels often disadvantage minority viewpoints (Blodgett et al., 2020; Gordon et al., 2021). Building on this, Cabitza et al. (2023) formalized *perspectivism* in NLP, advocating for models that integrate diverse human viewpoints rather than collapsing them into gold standards.

We formalize a taxonomy of disagreement by synthesizing prior work into three sources: data, task, and annotator factors. We trace the evolution of NLP approaches for learning from disagreement, from latent-truth models to multi-annotator, embedding-based methods. To unify these developments, we introduce a synthesis table highlighting key trends, including the shift from treating disagreement as noise to modeling it as a prediction target, and the growing emphasis on structured relationships among annotators. We also survey evaluation practices and fairness considerations. Finally, we outline open challenges and future directions, including jointly modeling multiple sources of variation and navigating the practical tradeoffs of perspectivist approaches. Our contributions are: (1) **A unified taxonomy of disagreement** across data-, task-, and annotator-driven sources; (2) **A synthesis of disagreement-aware methods**, mapping approaches to disagreement sources, prediction targets, and pooling.

Two recent surveys are closely related but differ in scope: Frenda et al. (2024) offers a broad conceptual overview of perspectivist NLP, while Uma et al. (2021) emphasizes empirical training and evaluation across vision and NLP. We build on both, shifting toward a model-centric, NLP-focused analysis that jointly examines disagreement sources, modeling, and evaluation across 110+ prior works. We discuss survey scope and selection criteria in A.1.

2 Data

Research in perspectivist modeling has been constrained by the availability of disaggregated datasets with annotator information. Frenda et al. (2024) present a comprehensive selection of disaggregated datasets, highlighting that only a few report information about annotator identity. Since that survey, more public data has been released, accelerating progress in modeling (Table 2), spanning multi-modal and multi-lingual contexts.

3 Sources of Disagreement

Prior work analyzes disagreement sources across tasks and domains. Basile et al. (2021) identify three broad contributors: individual differences (partly linked to sociodemographics), stimulus characteristics (linguistic or task ambiguity), and contextual inconsistency. Sandri et al. (2023) propose a finer split—sloppy annotations, ambiguity, missing information, and subjectivity—finding subjectivity dominant in offensive language detection. In legal NLP, Xu et al. (2024b) highlight narrative uncertainty and annotation context. These taxonomies are largely domain-specific, emphasizing different facets depending on task formulation.

3.1 Taxonomy of disagreement

We propose a unifying, domain-agnostic taxonomy (Fig. 1) that synthesizes these views into three sources of disagreement: data factors (e.g., ambiguity and data quality), task factors (e.g., formulation and interface design), and annotator factors (e.g., demographics, preferences, and errors). Different sources of disagreement can interact with one another. Unclear task formulation can lead to inconsistent annotation. Linguistic ambiguity can lead to disagreement that varies with annotators' individual and group identities, leading to systematically different interpretations of the same text.

3.2 Data Factors

Prior work identifies three data-driven sources of disagreement: data quality issues, linguistic ambiguity, and epistemic uncertainty (Poesio, 2020; Uma et al., 2021; Pavlick and Kwiatkowski, 2019). Missing context or noisy inputs exacerbate inconsistency, especially for short text (Plank et al., 2014). Language is inherently ambiguous, and in many subjective tasks disagreement reflects irreducible multiplicity rather than annotation error (Pavlick and Kwiatkowski, 2019).

3.3 Annotator Factors

Individual identities. Prior work documents stable, annotator-specific biases that introduce variance into training data and directly affect model performance (Otterbacher, 2018; Larimore et al., 2021; Pavlick and Kwiatkowski, 2019; Geva et al., 2019). Beyond general disagreement, psychological and moral traits systematically correlate with annotation behavior. Personality dimensions such as agreeableness and conscientiousness are associated with evaluative leniency (Mieleszczenko-Kowszewicz et al., 2023), while moral values exert stronger influence on judgments of offensiveness than geographic or cultural background (Davani et al., 2024a). Together, these findings show that annotators bring stable individual preferences that shape how they interpret and label language.

Group identities. Group-level attributes such as gender, race, age, and political orientation influence annotation behavior, particularly in socially grounded tasks. Gender-linked variation has been observed in hate speech detection (Wojatzki et al., 2018) and even in syntactic tasks (Garimella et al., 2019), aligning with sociolinguistic evidence of gendered language use (Mondorf, 2002). In subjective domains such as toxicity or sentiment, demographic shifts can substantially affect model performance (Ding et al., 2022). Qualitative work further shows that lived experience shapes interpretation: community insiders label gang-related language differently from academic annotators (Patton et al., 2019), and political or racial attitudes correlate with toxicity judgments, including treatment of African American English (Sap et al., 2022; Sang and Stanton, 2021; Luo et al., 2021). In these settings, disagreement often reflects social perspective rather than noise (Chulvi et al., 2023). However, identity effects are task-dependent. For less socially salient tasks (e.g., word similarity, sentiment, NLI), demographic attributes do not consistently explain annotation differences (Biester et al., 2022), and explicitly modeling sociodemographics may yield limited gains (Orlikowski et al., 2023). These findings caution against ecological fallacies (Robinson, 1950): group-level identity does not uniformly predict individual annotation behavior.

Annotator behavioral inconsistencies. Abercrombie et al. (2025) found that annotators give inconsistent responses around 25% of the time across four different NLP tasks. Clark et al. (2021) also show that untrained annotators identify GPT-3- versus

Figure 1: Taxonomy of sources of annotator disagreement, with key citations for each sub-category. For each source of disagreement, we denote systematic variation using solid lines, and random variation using dotted.

human-written text only at chance levels. Annotators may also produce low-quality or strategically chosen labels to maximize pay (Hovy et al., 2013).

3.4 Task Factors

Annotation task design, including its formulation, structure, and presentation, strongly shapes disagreement. Ambiguous or underspecified tasks permit multiple valid interpretations, leading to systematic divergence; in LLM-as-Judge settings, ambiguous prompts elicit different interpretive strategies (Zhang et al., 2025b). Interface design also affects agreement: unclear guidelines increase inconsistency, while alternative interfaces can surface ambiguity rather than suppress it (Chang et al., 2017). Annotation schemas and scales further modulate disagreement: finer-grained ratings amplify variability relative to binarized labels (Mieleszczenko-Kowszewicz et al., 2023), and different schemas (e.g., scalar ratings vs. pairwise preferences) capture related but distinct judgments, particularly in RLHF (Dsouza and Kovatchev, 2025). Presentation and labor conditions matter: order effects, fatigue, and satisficing shift responses over time (Strack, 1992; Krosnick et al., 1996; Galesic and Bosnjak, 2009; Beck et al., 2024). Fine-grained schemes may inflate disagreement due to degraded consistency under poor working conditions (Valette, 2024; Yang et al., 2023). Data and task factors are not independent: the same text can be unambiguous under one task formulation but ambiguous under another, since task difficulty reflects the interaction between label schema and text properties.

4 Learning from Disagreement

We discuss three families of disagreement modeling, tracing NLP's shift from treating disagreement as noise to modeling it as structured variation.

4.1 Latent Truth & Annotator Reliability Modeling

Models in this family attribute disagreement to annotator reliability, bias, or task difficulty, aiming to infer latent true labels while estimating annotator behavior. They span various contributing factors, capturing task factors (e.g., difficulty), annotator factors (e.g., competence), and approaches that condition annotator behavior on the input. Dawid and Skene (1979) introduced a foundational EM-based framework jointly inferring latent labels and annotator error rates from noisy annotations, underpinning many later Bayesian and discriminative models. Later work adds task characteristics, modeling difficulty (Whitehill et al., 2009; Ma et al., 2015) or expertise-aligned latent topics (Fan et al., 2015; Ma et al., 2015; Zhao et al., 2015; Welinder et al., 2010), or focuses on annotator competence as scalar accuracies (Demartini et al., 2012; Karger et al., 2011; Liu et al., 2012), confusion matrices (Dawid and Skene, 1979; Raykar et al., 2010; Liu et al., 2012), or bias–variance decompositions (Welinder et al., 2010; Raykar et al., 2010). Confusion-matrix models are more expressive and typically outperform simpler ones (Zheng et al., 2017). Formally, these models posit a single hidden label z_i per item, treating disagreement as noise around it. They model annotations as $p(y_{ij} \mid z_i, a_j)$, where a_j denotes annotator-

specific parameters (e.g., a confusion matrix), and marginalize over z_i at inference. The objective (Dawid and Skene, 1979; Hovy et al., 2013) maximizes the marginal likelihood over a single true label per item: $\max_{\{a_j\}} \sum_i \log \sum_{z_i} p(z_i) \prod_j p(y_{ij} \mid z_i, a_j)$. Disagreement thus reflects annotator unreliability rather than item ambiguity.

Later work integrates these ideas into learning architectures. Neural extensions such as CrowdLayer (Rodrigues and Pereira, 2018) and label-transfer approaches (Tanno et al., 2019) replace explicit confusion matrices with differentiable components, while other models introduce worker weighting or structured noise modeling (Gao et al., 2022; Cao et al., 2023; Wei et al., 2022; Chu et al., 2021). Paun et al. (2018) show that partial pooling—i.e., drawing annotator parameters from a shared population distribution—best balances expressivity and generalization. Despite their strengths, latent truth models can struggle with scalability and estimation under sparse labeling or weakly differentiated answers. To address this, CROWDLAB (Goh et al., 2023) combines annotator statistics with task-level features by treating classifier predictions as an additional annotator, improving robustness without iterative inference. Recent work further incorporates task features and demographic structure: Simpson et al. (2015) jointly models text, annotator bias, and latent truth, while NUTMEG (Ivey et al., 2025) extends truth inference to demographic subpopulations, estimating competence and predicting labels per group rather than collapsing to a single consensus (Hovy et al., 2013; Paun et al., 2018).

4.2 Task-based Annotator Models

This model family treats each annotator as a distinct task, modeling labeling behavior directly rather than collapsing annotations into a single truth. This family reframes disagreement from noise to a structured signal, and primarily focuses on annotator factors. Given an input x_i, a shared encoder produces a representation $h_i = f(x_i)$, and each annotator j defines a task-specific predictor $p^{(j)}(y \mid x_i)$. Model parameters are learned by minimizing a supervised loss over annotator–item pairs, $\min_\theta \quad \sum_i \sum_{j \in \mathcal{A}_i} \ell\left(y_{ij}, \, p_\theta^{(j)}(y \mid x_i)\right)$. θ is all model parameters (shared encoders and annotator-specific heads), $\mathcal{A}_i$ is set of annotators who labeled i, and $\ell(\cdot, \cdot)$ is typically cross-entropy for classification or squared error for regression. Disagreement is captured implicitly through divergence across annotator-specific predictions.

Early work by Cohn and Specia (2013) models annotators as correlated tasks in a Gaussian Process framework, using an inter-annotator covariance matrix to control pooling. This nonparametric analogue to hierarchical Bayesian models identifies annotator similarity and outliers, with partial pooling performing best (Paun et al., 2018). Neural extensions implement this idea via shared backbones and annotator-specific heads: CrowdLayer (Rodrigues and Pereira, 2018) adds a per-annotator layer that learns each labeler's reliability and bias end-to-end through backpropagation, while Guan et al. (2018) model each labeler with a dedicated head and learn sample-specific weights to combine them. Fornaciari et al. (2021) further reinterpret disagreement as a regularization signal to reduce overconfidence on ambiguous inputs, learning from both the gold labels and the distribution over multiple annotators (which they treat as soft label distributions in a single auxiliary task). More recent work models richer annotator structure. Mixture-of-experts approaches capture feature-level heterogeneity (Han et al., 2025), while multi-head Transformers preserve uncertainty aligned with empirical disagreement (Davani et al., 2022). Group-aware and loss-based extensions incorporate demographic structure or explicit tradeoffs between denoising and minority perspectives (Fleisig et al., 2023; Jinadu and Ding, 2024). Collectively, task-based models capture structured perspective variation beyond latent-truth formulations.

4.3 Embedding-based Annotator Models

Focusing on data and annotator factors, the third family of embedding-based models departs from latent-truth paradigms by treating disagreement as systematic variation in annotator behavior rather than noise around a hidden true label. Instead of assigning each annotator a separate prediction head, these approaches encode annotator differences in a shared latent space, enabling scalability to thousands of annotators with sparse labels, an important limitation of task-based methods. Embedding-based models parameterize annotator-level predictions as $p(y_{ij} \mid h_i, e_j)$, where $h_i = f(x_i)$ is an embedding of the input item and $e_j = g(a_j)$ is an embedding of the annotator j. The loss function optimizes standard supervised losses over annotator–item pairs, where θ is all model parameters (shared encoders and annotator-specific heads), $\mathcal{A}_i$ is the set of annotators who labeled i,

and $\ell(\cdot, \cdot)$ is typically instantiated as cross-entropy for classification or squared error for regression: $\min_\theta \sum_i \sum_{j \in \mathcal{A}_i} \ell(y_{ij}, p_\theta(y \mid h_i, e_j))$. Disagreement is formalized as the interaction between item and annotator embeddings.

Early work introduced annotator embeddings to capture individual biases in subjective NLP tasks (Kocoń et al., 2021). AART (Mokhberian et al., 2024) extends this idea to large-scale crowdsourcing with regularization for robustness and fairness. Subsequent models enrich the framework by incorporating annotation embeddings (Deng et al., 2023) or demographic structure. Jury Learning (Gordon et al., 2022) combines content, annotator, and demographic embeddings to predict individual votes and compose configurable juries, while DEM-MoE (Xu et al., 2025) explicitly models demographic structure via a mixture-of-experts to capture intersectional variation. Recent work further improves scalability by replacing stored embeddings with hypernetwork-generated, annotator-specific LoRA adapters(Ignatev et al., 2025). Embedding-based models show a progression in the granularity of disagreement they represent: from individual annotators (Kocoń et al., 2021), to demographic groups (Gordon et al., 2022), to population-level distributions (Weerasooriya et al., 2023b). This trajectory points toward an important future direction: estimating subgroup-specific disagreement rather than averaging across populations. Building on prior work (Sap et al., 2022; Lakkaraju et al., 2015), future work could focus on inferring how social subgroups interpret the same item, enabling perspective-aware predictions that surface when disagreement reflects broader social divides.

Direct disagreement modeling. A subset of embedding-based models *predicts* disagreement directly rather than treating it as noise. These approaches vary in how disagreement is represented—implicitly via soft supervision, as a scalar score, or explicitly as a label distribution—but share the goal of modeling disagreement as the prediction target. Embedding-based architectures are well-suited to this setting because they enable generalization across annotators, conditioning on demographic attributes, and marginalization over annotator populations. Implicit approaches predict aggregate disagreement without explicitly modeling a distribution. For example, Xu et al. (2024a) predict empirical label proportions from text using cross-entropy against soft labels, while Wan et al. (2023) conditions predictions on annotator

Figure 2: The distribution of the three main methods across our identified taxonomy of sources of disagreement. The lack of work modeling data and task factors point to future directions.

demographics and regresses a scalar disagreement score. In contrast, distributional modeling treats disagreement itself as the target, enabling prediction even when not all annotators are observed by directly parameterizing an item-level label distribution: $p(y \mid x_i)$, where y is the expected distribution of annotators that would be produced by the population, for instance x_i. Distributional models typically optimize a composite objective (Parappan and Henao, 2025; Weerasooriya et al., 2023b), combining supervised alignment with individual annotations and a divergence-based term (e.g., KL or JSD) that aligns predicted and empirical item-level distributions. The first term enforces annotator-level alignment, and the second distributional alignment: $\min_\theta \sum_i \sum_{j \in \mathcal{A}_i} \ell(y_{ij}, p_\theta(y \mid x_i, a_j)) + \lambda \sum_i \mathcal{D}(\tilde{p}_i(y) \parallel p_\theta(y \mid x_i))$. DisCo (Weerasooriya et al., 2023b) models disagreement at the response, item, and population levels, aggregating over annotators at inference to estimate population-level disagreement. The Learning Subjective Label Distribution framework (Parappan and Henao, 2025) extends this by conditioning distributions on sociodemographic attributes and semantic perspectives, enabling subgroup-specific disagreement estimates. Collectively, these approaches move toward unified representations of individual-, group-, and population-level variation.

5 Mapping Models to Disagreement Sources

We map the three model families onto our taxonomy in Figure 2. Latent truth models span multiple regions—task factors, annotator factors, and

Figure 3: Prediction targets and pooling assumptions across methods for learning from annotator disagreement. The table maps existing approaches by what they predict (consensus labels, individual annotator responses, group-level outputs, or full disagreement distributions) and how they pool information across annotators. Fig. 4 is more detailed with representative work.

input-conditioned annotator behavior. Within the annotator–data intersection, we distinguish implicit from explicit data features. Implicit approaches incorporate the input via shared encoders or embeddings without explicitly modeling item ambiguity as a source of disagreement (Goh et al., 2023; Raykar et al., 2010; Rodrigues and Pereira, 2018; Gordon et al., 2022). CrowdLayer (Rodrigues and Pereira, 2018) and embedding-based models (Gordon et al., 2022) condition predictions on text but treat it primarily as contextual information. In contrast, explicit data modeling treats properties of the input itself as a structured source of annotator variation (Simpson et al., 2015; Ivey et al., 2025). For instance, Ivey et al. (2025) condition annotator competence on item features to capture systematic subgroup responses. This category also includes distributional approaches that directly predict item-level disagreement distributions, explicitly representing data ambiguity (Weerasooriya et al., 2023b; Parappan and Henao, 2025). Notably, the relative scarcity of modeling data factors alone—or jointly integrating data with task and annotator factors—highlights promising directions for future research.

6 Prediction Targets and Pooling

We introduce a synthesis table (Figure 3) organized along prediction target and pooling structure. Prediction targets include consensus (a single label

per item), annotator (one prediction per annotator), group (one prediction per annotator group), and distribution (the full label distribution across annotators). Pooling (Paun et al., 2018) is generalized across three model classes. Group pooling forces all annotators to share a single labeling function. Unpooled models treat annotators independently. Partial pooling encodes structured relationships among annotators or between annotators and the (sub)population, though it is instantiated differently across paradigms. In Bayesian latent-truth models, annotator reliabilities are drawn from a shared population prior. Gaussian process multi-task models (Cohn and Specia, 2013) treat annotators as correlated tasks, while neural multi-task models (Rodrigues and Pereira, 2018) use shared backbones with annotator-specific heads. Embedding-based approaches (Mokhberian et al., 2024) instead represent annotators as points in a latent population space. Notably, none of the surveyed disagreement-aware models employ full group pooling. While group pooling corresponds to majority vote or fixed aggregation, once annotator behavior is modeled, methods adopt unpooled or partially pooled structures. We highlight these temporal trends:

The field is gradually formalizing disagreement as an object of prediction, not a source of noise. Modeling has shifted from consensus prediction to individual annotators, to groups, and recently to population or subgroup distributions, an upward movement along the target axis over time.

Across pooling structures, the field has moved from unpooled to partial pooling. The most successful models use partial pooling (hierarchical priors (Paun et al., 2018), inter-annotator kernels (Cohn and Specia, 2013), demographic-informed MoE (Xu et al., 2025), and subgroup-aware distributions (Parappan and Henao, 2025)) improving generalization and fairness. Partial pooling of annotators or groups is the most expressive and successful regime, and most existing methods fall here, offering generalization to new annotators and scalability under sparse labels.

Few works model disagreement distributions, but newer architectures are converging toward distribution-level modeling (Fornaciari et al. (2021) as a task-based model; Parappan and Henao (2025); Weerasooriya et al. (2023b) as embedding-based models). Predicting how much people disagree is becoming as important as predicting labels.

7 Evaluation Metrics

Evaluation metrics for modeling disagreement broadly fall into two classes: those that compare the predictions to the true annotations, and those that evaluate annotator behavior, aiming to recover latent structure such as inter-annotator relationships. Hard metrics (accuracy, precision, recall) assume a single gold label, problematic for subjective or ambiguous tasks (Poesio and Artstein, 2005; Plank et al., 2014), motivating a shift toward probabilistic and soft metrics. Aggregation models such as Dawid–Skene (Dawid and Skene, 1979) and MACE (Hovy et al., 2013) use likelihood or accuracy against inferred latent truth, while latent-truth and reliability models adopt ROC–AUC, negative log probability, predictive density, and entropy-based measures (Raykar et al., 2010; Paun et al., 2018; Simpson et al., 2015; Ivey et al., 2025). As models predict heterogeneous judgments, evaluation extends to per-annotator metrics (MAE, RMSE, macro F1) (Cohn and Specia, 2013; Davani et al., 2022) and group-level/distributional divergences (KL, JSD) (Mokhberian et al., 2024; Gordon et al., 2022; Weerasooriya et al., 2023b). However, recent work (Rizzi et al., 2024) has shown that Cross Entropy (and to a lesser extent divergence-based measures) may violate desirable properties like symmetry or fair penalization, potentially obscuring meaningful differences between models that aim to reproduce disagreement distributions.

A complementary set of metrics evaluates annotator quality directly. Likelihood-based measures and annotator–model correlations assess inferred behavior (Passonneau and Carpenter, 2014; Paun et al., 2018), while agreement metrics like Krippendorff's α and Cohen's κ quantify consistency but conflate ambiguity with unreliability (Krippendorff, 1980; Viera and Garrett, 2005). CrowdTruth (Inel et al., 2014) treats disagreement as signal via worker-, item-, and label-level metrics, later extended to model their interactions (Dumitrache et al., 2018). Recent work targets latent structure more directly, using intra-annotator consistency (Gordon et al., 2021) and relational metrics (DIC, BAE) to test whether models preserve agreement geometry (Zhang et al., 2025a). Overall, evaluation increasingly emphasizes models' preservation of disagreement structure, not merely match labels.

Evaluating Fairness. Fairness becomes relevant when disagreement is systematic and socially structured, reflecting genuine differences in perspective tied to demographics or lived experience (Aroyo and Welty, 2013; Pavlick and Kwiatkowski, 2019). Collapsing annotations into a single consensus can erase minority viewpoints, rendering pooling a normative—rather than purely technical—choice. Although fairness is increasingly invoked in disagreement-aware modeling, most evaluations remain descriptive (Binns, 2018). Disaggregated and group-level metrics reveal disparities (Gordon et al., 2022; Xu et al., 2025), but do not specify what outcomes should count as fair. Diagnostic frameworks such as AART (Mokhberian et al., 2024) and PERSEVAL (Lo et al., 2025) report parity gaps without explicit normative grounding. This gap motivates adapting fairness-in-ML frameworks — such as statistical parity, equalized opportunity, and subgroup fairness (Caton and Haas, 2024) — to disagreement-aware modeling. One concrete operationalization is to evaluate whether the relational structure of disagreement across annotators and groups is preserved, using metrics such as DIC and BAE (Zhang et al., 2025a), moving toward explicit normative reasoning about what kind of fairness models ought to achieve.

8 Ethics of Disagreement Modeling

Demographic-aware disagreement modeling aims at inclusive representation, yet operationalizing demographic identity as input introduces risks, many beginning at data collection (Andrus and Villeneuve, 2022): individual risks of privacy encroachment and identity misrepresentation, and community risks of reifying social constructs by treating demographics as isolated variables rather than structural, institutional, and relational phenomena (Hanna et al., 2020). Model design choices likewise encode a moral stance (Binns, 2018; Heidari et al., 2019; Mehrabi et al., 2021; Friedler et al., 2021): consensus pooling risks averaging away minority viewpoints, while partial pooling toward demographic groups can reify group boundaries and flatten within-group variation. As noted in Section 2, group identity does not uniformly predict individual behavior (Robinson, 1950), so models that assume it does risk an ecological fallacy with normative, not just predictive, consequences. More subtly, models meant to amplify minority perspectives can misrepresent them; under coarse demographic conditioning or sparse subgroup data, predictions may reflect stereotypes (Lee et al., 2023; Santurkar et al., 2023; Hu and Collier, 2024). Finally, since

current evaluations largely report disparities without specifying what counts as fair (Binns, 2018), we advocate adapting fairness-in-ML frameworks to the disagreement-aware setting and grounding evaluation in epistemic justice (Fricker, 2007) to assess whether diverse viewpoints and the structure of disagreement are faithfully preserved.

9 Challenges and Future Work

LLM-based simulation of annotator variation. LLMs are increasingly used to simulate annotator variation (through persona prompting and reasoning-based approaches) but these methods remain methodologically limited. These approaches are largely unpooled (e.g., personas are simulated independently), highly sensitive to prompts and model choice, and risk amplifying stereotypes (Lee et al., 2023; Durmus et al., 2023; Santurkar et al., 2023; Blodgett et al., 2020). Empirically, persona variables explain only a small fraction of variance (Hu and Collier, 2024), and fine-tuning with demographic metadata appears to rely more on annotator-specific signals than generalizable group structure (Orlikowski et al., 2025). More broadly, LLM judgments compress human disagreement and rely on opaque priors, raising concerns about reliability and epistemic validity of replacing human annotation labor (Durmus et al., 2023; Cazzaniga et al., 2024). Recent work has explored whether reasoning can help LLMs capture disagreement, with mixed results. When LLMs reason internally, naive Chain-of-Thought improves disagreement modeling of RLHF LLMs (Ni et al., 2026), but long CoT primarily resolves the final answer rather than calibrating label distributions (Chen et al., 2026). Even when external human expert reasoning is provided as context, fine-tuning smaller models on the resulting LLM-generated distributions produces inconsistent results (Chen et al., 2024).

Modeling task-induced disagreement. While annotator- and data-level variation are increasingly modeled, task-level sources of disagreement remain underexplored. Instruction phrasing, label schema design, presentation order, and interface choices can systematically shape disagreement, yet are rarely represented explicitly. Prior work shows that task design strongly influences annotation outcomes (Zhang et al., 2025b; Dsouza and Kovatchev, 2025), but most models incorporate task information only indirectly. Future work could embed task schemas directly, enabling models to capture how task framing interacts with annotators and data.

Integrating task, annotator, and data variation. Most existing methods focus primarily on annotator bias as the source of disagreement. A few latent-truth models and embedding models jointly consider annotator and task factors, but task-based approaches typically do not. Developing models that integrate all three sources, task, annotator, and data, remains an open challenge, partly constrained by data availability.

Interpretability of disagreement-aware models. Explainability remains underdeveloped for disagreement-aware NLP models. Most methods for model interpretability target single-label predictions and do not explain why annotators or groups disagree (Molnar, 2020). While recent multi-annotator models offer feature- or attention-based explanations, these are rarely validated against real annotator behavior. Emerging metrics such as Behavior Alignment Explainability (Zhang et al., 2025a) point toward more principled evaluation, but robust disagreement-aware interpretability remains an open problem.

Generalization and practical tradeoffs. Annotator disagreement is highly dataset- and domain-specific, and evidence on the benefits of demographic conditioning is mixed (Gordon et al., 2022; Orlikowski et al., 2023). Models risk overfitting to dataset-specific noise, suggesting a need for cross-dataset and cross-domain training. Perspectivist models introduce tradeoffs: they require richer annotations and greater computation, complicate filtering decisions, and raise normative questions about whose perspectives should be preserved. As a result, adopting disagreement-aware modeling is not merely a technical choice, but a value-laden one balancing fairness, interpretability, efficiency, and annotation labor conditions (Valette, 2024).

10 Conclusion

We present a unified view of disagreement-aware modeling, treating disagreement as signal rather than noise. Our taxonomy spans data-, task-, and annotator-driven sources, tracing the shift toward multi-annotator and persona-conditioned models. Key gaps remain (limited distributional modeling and descriptive fairness evaluation), motivating future work on integrated, interpretable, and normatively grounded approaches.

11 Limitations

We recognize that our work has several limitations. While thorough, decades of work in disagreement make a fully exhaustive survey difficult. Our survey reviews over 120 papers, and our selection reflects methodological relevance to disagreement-aware modeling. As a result, some related approaches, such as LLM simulations of annotator personas, or other methods that engage with human perspectives tangentially rather than as a modeling target, have been excluded. Additionally, the taxonomy we propose is a simplification. In real-world settings, data, task, and annotator factors sometimes cannot be separated cleanly. Future approaches, particularly those that integrate the interaction between various factors, might require extensions to this taxonomy. Lastly, our discussion of open challenges and future directions reflects our interpretations of the most important gaps in the literature. These should not be interpreted as a comprehensive or normative research agenda. Other researchers might prioritize different directions, such as efficiency, model deployment concerns, or annotation practice design to produce meaning disagreement.

A key limitation of the disagreement-aware literature (and thus our synthesis) is that disagreement is often treated as an observed property of datasets rather than as an outcome of annotation practice design. Observed disagreement may conflate meaningful perspective variation with annotator factors such as confusion and fatigue. This limits cross-paper comparability. Developing and standardizing annotation practices that intentionally elicit meaningful disagreement remains an important direction for future work.

References

Gavin Abercrombie, Tanvi Dinkar, Amanda Cercas Curry, Verena Rieser, and Dirk Hovy. 2025. Consistency is key: Disentangling label variation in natural language processing with intra-annotator agreement. *Preprint*, arXiv:2301.10684.

Gavin Abercrombie, Nikolas Vitsakis, Aiqi Jiang, and Ioannis Konstas. 2024. Revisiting annotation of online gender-based violence. In *Proceedings of the 3rd Workshop on Perspectivist Approaches to NLP (NLPerspectives) @ LREC-COLING 2024*, pages 31–41, Torino, Italia. ELRA and ICCL.

Dina Almanea and Massimo Poesio. 2022. ArMIS – the Arabic misogyny and sexism corpus with annotator subjective disagreements. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 2282–2291. European Language Resources Association.

McKane Andrus and Sarah Villeneuve. 2022. Demographic-reliant algorithmic fairness: Characterizing the risks of demographic data collection in the pursuit of fairness. In *Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '22, page 1709–1721, New York, NY, USA. Association for Computing Machinery.

Lora Aroyo, Alex S. Taylor, Mark Diaz, Christopher M. Homan, Alicia Parrish, Greg Serapio-García, Vinodkumar Prabhakaran, and Ding Wang. 2023. DICES dataset: Diversity in conversational AI evaluation for safety. *arXiv preprint arXiv:2306.11247*.

Lora Aroyo and Chris Welty. 2013. Crowd truth: Harnessing disagreement in crowdsourcing a relation extraction gold standard.

Lora Aroyo and Chris Welty. 2015. Truth is a lie: Crowd truth and the seven myths of human annotation. *AI Magazine*, 36(1):15–24.

Valerio Basile, Michael Fell, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, Massimo Poesio, and Alexandra Uma. 2021. We need to consider disagreement in evaluation. In *Proceedings of the 1st Workshop on Benchmarking: Past, Present and Future*, pages 15–21, Online. Association for Computational Linguistics.

Jacob Beck, Stephanie Eckman, Bolei Ma, Rob Chew, and Frauke Kreuter. 2024. Order effects in annotation tasks: Further evidence of annotation sensitivity. In *Proceedings of the 1st Workshop on Uncertainty-Aware NLP (UncertaiNLP 2024)*, pages 81–86, St Julians, Malta. Association for Computational Linguistics.

Laura Biester, Vanita Sharma, Ashkan Kazemi, Naihao Deng, Steven Wilson, and Rada Mihalcea. 2022. Analyzing the effects of annotator gender across NLP tasks. In *Proceedings of the 1st Workshop on Perspectivist Approaches to NLP @LREC2022*, pages 10–19, Marseille, France. European Language Resources Association.

Reuben Binns. 2018. Fairness in machine learning: Lessons from political philosophy. In *Proceedings of the 2018 Conference on Fairness, Accountability, and Transparency*, volume 81 of *Proceedings of Machine Learning Research*, pages 149–159. PMLR.

Su Lin Blodgett, Solon Barocas, Hal Daumé III, and Hanna Wallach. 2020. Language (technology) is power: A critical survey of "bias" in NLP. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5454–5476, Online. Association for Computational Linguistics.

Federico Cabitza, Andrea Campagner, and Valerio Basile. 2023. Toward a perspectivist turn in ground

truthing for predictive computing. *Proceedings of the AAAI Conference on Artificial Intelligence*, 37(6):6860–6868.

Z. Cao, E. Chen, Y. Huang, S. Shen, and Z. Huang. 2023. Learning from crowds with annotation reliability. In *Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2103–2107.

Silvia Casola, Simona Frenda, Soda Marem Lo, Erhan Sezerer, Antonio Uva, Valerio Basile, Cristina Bosco, Alessandro Pedrani, Chiara Rubagotti, Viviana Patti, and Davide Bernardi. 2024. MultiPICo: Multilingual perspectivist irony corpus. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16008–16021, Bangkok, Thailand. Association for Computational Linguistics.

Simon Caton and Christian Haas. 2024. Fairness in machine learning: A survey. *ACM Comput. Surv.*, 56(7).

Mauro Cazzaniga, Florence Jaumotte, Longji Li, Giovanni Melina, Augustus J. Panton, Carlo Pizzinelli, Emma J. Rockall, and Marina Mendes Tavares. 2024. Gen-ai: Artificial intelligence and the future of work. Technical Report 2024/001, International Monetary Fund.

Jonathan P. Chang, Saleema Amershi, and Jaime Teevan. 2017. Revolt: Collaborative crowdsourcing for labeling tasks. In *Proceedings of CHI*.

Beiduo Chen, Tiancheng Hu, Caiqi Zhang, Robert Litschko, Anna Korhonen, and Barbara Plank. 2026. Decoupling the effect of chain-of-thought reasoning: A human label variation perspective. *Preprint*, arXiv:2601.03154.

Beiduo Chen, Xinpeng Wang, Siyao Peng, Robert Litschko, Anna Korhonen, and Barbara Plank. 2024. "seeing the big through the small": Can llms approximate human judgment distributions on nli from a few explanations? *Preprint*, arXiv:2406.17600.

Z. Chu, J. Ma, and H. Wang. 2021. Learning from crowds by modeling common confusions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 5832–5840.

Berta Chulvi, Lara Fontanella, Roberto Labadie Tamayo, and Paolo Rosso. 2023. Social or individual disagreement? perspectivism in the annotation of sexist jokes. In *NLPerspectives@ECAI*.

Elizabeth Clark, Tal August, Sofia Serrano, Nikita Haduong, Suchin Gururangan, and Noah A. Smith. 2021. All that's 'human' is not gold: Evaluating human evaluation of generated text. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 7282–7296, Online. Association for Computational Linguistics.

Trevor Cohn and Lucia Specia. 2013. Modelling annotator bias with multi-task Gaussian processes: An application to machine translation quality estimation. In *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 32–42, Sofia, Bulgaria. Association for Computational Linguistics.

Aida Davani, Mark Díaz, Dylan Baker, and Vinodkumar Prabhakaran. 2024a. Disentangling perceptions of offensiveness: Cultural and moral correlates. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '24, page 2007–2021, New York, NY, USA. Association for Computing Machinery.

Aida Davani, Mark Díaz, and Vinodkumar Prabhakaran. 2022. Dealing with disagreements: Looking beyond the majority vote in subjective annotations. *Transactions of the Association for Computational Linguistics*, 10:92–110.

Aida Mostafazadeh Davani, Mark Díaz, Dylan Baker, and Vinodkumar Prabhakaran. 2024b. D3CODE: Disentangling disagreements in data across cultures on offensiveness detection and evaluation. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 18511–18526. Association for Computational Linguistics.

A. P. Dawid and A. M. Skene. 1979. Maximum likelihood estimation of observer error-rates using the em algorithm. *Applied Statistics*, 28(1):20–28.

Gianluca Demartini, Djellel Eddine Difallah, and Philippe Cudré-Mauroux. 2012. Zencrowd: Leveraging probabilistic reasoning and crowdsourcing techniques for large-scale entity linking. In *Proceedings of the 21st International Conference on World Wide Web (WWW)*, pages 469–478, Lyon, France. Association for Computing Machinery.

Naihao Deng, Xinliang Zhang, Siyang Liu, Winston Wu, Lu Wang, and Rada Mihalcea. 2023. You are what you annotate: Towards better models through annotator representations. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12475–12498, Singapore. Association for Computational Linguistics.

Yi Ding, Jacob You, Tonja-Katrin Machulla, Jennifer Jacobs, Pradeep Sen, and Tobias Höllerer. 2022. Impact of annotator demographics on sentiment dataset labeling. *Proc. ACM Hum.-Comput. Interact.*, 6(CSCW2).

Russel Dsouza and Venelin Kovatchev. 2025. Sources of disagreement in data for LLM instruction tuning. In *Proceedings of Context and Meaning: Navigating Disagreements in NLP Annotation*, pages 20–32, Abu Dhabi, UAE. International Committee on Computational Linguistics.

Anca Dumitrache, Oana Inel, Lora Aroyo, Benjamin Timmermans, and Chris Welty. 2018. Crowdtruth 2.0: Quality metrics for crowdsourcing with disagreement. *Preprint*, arXiv:1808.06080.

Esin Durmus, Karina Nyugen, Thomas I. Liao, Nicholas Schiefer, Amanda Askell, Anton Bakhtin, Carol Chen, Zac Hatfield-Dodds, Danny Hernandez, Nicholas Joseph, Liane Lovitt, Sam McCandlish, Orowa Sikder, Alex Tamkin, Janel Thamkul, Jared Kaplan, Jack Clark, and Deep Ganguli. 2023. Towards measuring the representation of subjective global opinions in language models. *CoRR*, abs/2306.16388.

Jing Fan, Guoliang Li, Beng Chin Ooi, Kian-Lee Tan, and Jun Feng. 2015. icrowd: An adaptive crowdsourcing framework. In *Proceedings of the 2015 ACM SIGMOD International Conference on Management of Data*, pages 1015–1030, Melbourne, Victoria, Australia. Association for Computing Machinery.

Eve Fleisig, Rediet Abebe, and Dan Klein. 2023. When the majority is wrong: Modeling annotator disagreement for subjective tasks. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6715–6726, Singapore. Association for Computational Linguistics.

Tommaso Fornaciari, Alexandra Uma, Silviu Paun, Barbara Plank, Dirk Hovy, and Massimo Poesio. 2021. Beyond black & white: Leveraging annotator disagreement via soft-label multi-task learning. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2591–2597, Online. Association for Computational Linguistics.

Simona Frenda, Gavin Abercrombie, Valerio Basile, Alessandro Pedrani, Raffaella Panizzon, Alessandra Teresa Cignarella, Cristina Marco, and Davide Bernardi. 2024. Perspectivist approaches to natural language processing: A survey. *Language Resources and Evaluation*.

Simona Frenda, Alessandro Pedrani, Valerio Basile, Soda Marem Lo, Alessandra Teresa Cignarella, Raffaella Panizzon, Cristina Marco, Bianca Scarlini, Viviana Patti, Cristina Bosco, and Davide Bernardi. 2023. EPIC: Multi-perspective annotation of a corpus of irony. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13844–13857. Association for Computational Linguistics.

Miranda Fricker. 2007. *Epistemic Injustice: Power and the Ethics of Knowing*. Oxford University Press.

Sorelle A. Friedler, Carlos Scheidegger, and Suresh Venkatasubramanian. 2021. The (im)possibility of fairness: different value systems require different mechanisms for fair decision making. *Commun. ACM*, 64(4):136–143.

Mirta Galesic and Michael Bosnjak. 2009. Effects of questionnaire length on participation and indicators of response quality in a web survey. *Public Opinion Quarterly*, 73(2):349–360.

Z. Gao, F.-K. Sun, M. Yang, S. Ren, Z. Xiong, M. Engeler, A. Burazer, L. Wildling, L. Daniel, and D. S. Boning. 2022. Learning from multiple annotator noisy labels via sample-wise label fusion. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 407–422. Springer.

Aparna Garimella, Carmen Banea, Dirk Hovy, and Rada Mihalcea. 2019. Women's syntactic resilience and men's grammatical luck: Gender-bias in part-of-speech tagging and dependency parsing. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3493–3498, Florence, Italy. Association for Computational Linguistics.

Mor Geva, Yoav Goldberg, and Jonathan Berant. 2019. Are we modeling the task or the annotator? an investigation of annotator bias in natural language understanding datasets. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 1161–1166, Hong Kong, China. Association for Computational Linguistics.

Hui Wen Goh, Ulyana Tkachenko, and Jonas Mueller. 2023. Crowdlab: Supervised learning to infer consensus labels and quality scores for data with multiple annotators. *Preprint*, arXiv:2210.06812.

Mitchell L. Gordon, Michelle S. Lam, Joon Sung Park, Kayur Patel, Jeff Hancock, Tatsunori Hashimoto, and Michael S. Bernstein. 2022. Jury learning: Integrating dissenting voices into machine learning models. In *CHI Conference on Human Factors in Computing Systems*, CHI '22, page 1–19. ACM.

Mitchell L. Gordon, Kaitlyn Zhou, Kayur Patel, Tatsunori Hashimoto, and Michael S. Bernstein. 2021. The disagreement deconvolution: Bringing machine learning performance metrics in line with reality. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, CHI '21, New York, NY, USA. Association for Computing Machinery.

Nitesh Goyal, Ian Kivlichan, Rachel Rosen, and Lucy Vasserman. 2022. Is your toxicity my toxicity? exploring the impact of rater identity on toxicity annotation. *Preprint*, arXiv:2205.00501.

M. Guan, V. Gulshan, A. Dai, and G. Hinton. 2018. Who said what: Modeling individual labelers improves classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Tao Han, Huaixuan Shi, Xinyi Ding, Xiao Ma, Huamao Gu, and Yili Fang. 2025. Mixture of experts based multi-task supervise learning from crowds. *Preprint*, arXiv:2407.13268.

Alex Hanna, Remi Denton, Andrew Smart, and Jamila Smith-Loud. 2020. Towards a critical race methodology in algorithmic fairness. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, FAT* '20, page 501–512, New York, NY, USA. Association for Computing Machinery.

Hoda Heidari, Chiara Ferrari, Krishna P. Gummadi, and Andreas Krause. 2019. A moral framework for understanding fair ML through economic models of equality of opportunity. *Proceedings of the ACM Conference on Fairness, Accountability, and Transparency (FAT*)*, pages 1–10.

Dirk Hovy, Taylor Berg-Kirkpatrick, Ashish Vaswani, and Eduard Hovy. 2013. Learning whom to trust with MACE. In *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1120–1130, Atlanta, Georgia. Association for Computational Linguistics.

Tiancheng Hu and Nigel Collier. 2024. Quantifying the persona effect in llm simulations. *Preprint*, arXiv:2402.10811.

Daniil Ignatev, Denis Paperno, and Massimo Poesio. 2025. Hypernetworks for perspectivist adaptation. *Preprint*, arXiv:2510.13259.

Oana Inel, K Khamkham, T Cristea, A Dumitrache, H Rutjes, R-J Sips, J van Ossenbruggen, and K Crowston. 2014. Crowdtruth: Machine-human computation framework for harnessing disagreement in gathering annotated data. In *The Semantic Web – ISWC 2014*, volume 8797 of *Lecture Notes in Computer Science*, pages 486–504, Cham. Springer.

Jonathan Ivey, Susan Gauch, and David Jurgens. 2025. Nutmeg: Separating signal from noise in annotator disagreement. *Preprint*, arXiv:2507.18890.

Hyewon Jang, Bettina Braun, and Diego Frassinelli. 2023. Intended and perceived sarcasm between close friends: What triggers sarcasm and what gets conveyed? In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 45.

Hyewon Jang and Diego Frassinelli. 2024. Generalizable sarcasm detection is just around the corner, of course! In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 4238–4249, Mexico City, Mexico. Association for Computational Linguistics.

Uthman Jinadu and Yi Ding. 2024. Noise correction on subjective datasets. *Preprint*, arXiv:2311.00619.

David R. Karger, Sewoong Oh, and Devavrat Shah. 2011. Iterative learning for reliable crowdsourcing systems. In *Advances in Neural Information Processing Systems*, volume 24, pages 1953–1961.

Hannah Rose Kirk, Alexander Whitefield, Paul Röttger, Andrew Bean, Katerina Margatina, Juan Ciro, Rafael Mosquera, Max Bartolo, Adina Williams, He He, Bertie Vidgen, and Scott A. Hale. 2024. The prism alignment dataset: What participatory, representative and individualised human feedback reveals about the subjective and multicultural alignment of large language models. *Preprint*, arXiv:2404.16019.

Jan Kocoń, Marcin Gruza, Julita Bielaniewicz, Damian Grimling, Kamil Kanclerz, Piotr Miłkowski, and Przemysław Kazienko. 2021. Learning personal human biases and representations for subjective tasks in natural language processing. In *2021 IEEE International Conference on Data Mining (ICDM)*, pages 1168–1173.

Klaus Krippendorff. 1980. *Content Analysis: An Introduction to Its Methodology*. Sage Publications.

Jon A. Krosnick, Sowmya Narayan, and Wendy R. Smith. 1996. Satisficing in surveys: Initial evidence. *New Directions for Evaluation*, 1996(70):29–44.

Deepak Kumar, Patrick Gage Kelley, Sunny Consolvo, Joshua Mason, Elie Bursztein, Zakir Durumeric, Kurt Thomas, and Michael Bailey. 2021. Designing toxic content classification for a diversity of perspectives. *Preprint*, arXiv:2106.04511.

Himabindu Lakkaraju, Jure Leskovec, Jon Kleinberg, and Sendhil Mullainathan. 2015. A bayesian framework for modeling human evaluations. In *Proceedings of the 2015 SIAM International Conference on Data Mining (SDM)*, pages 181–189.

Savannah Larimore, Ian Kennedy, Breon Haskett, and Alina Arseniev-Koehler. 2021. Reconsidering annotator disagreement about racist language: Noise or signal? In *Proceedings of the Ninth International Workshop on Natural Language Processing for Social Media*, pages 81–90, Online. Association for Computational Linguistics.

Nayeon Lee, Chani Jung, Junho Myung, Jiho Jin, Jose Camacho-Collados, Juho Kim, and Alice Oh. 2024. Exploring cross-cultural differences in English hate speech annotations: From dataset construction to analysis. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 4205–4224, Mexico City, Mexico. Association for Computational Linguistics.

Noah Lee, Na Min An, and James Thorne. 2023. Can large language models capture dissenting human voices? In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4569–4585, Singapore. Association for Computational Linguistics.

Elisa Leonardelli, Silvia Casola, Siyao Peng, Giulia Rizzi, Valerio Basile, Elisabetta Fersini, Diego Frassinelli, Hyewon Jang, Maja Pavlovic, Barbara Plank, and Massimo Poesio. 2025. LeWiDi-2025 at NLPerspectives: Third edition of the learning with disagreements shared task. In *Proceedings of the The 4th Workshop on Perspectivist Approaches to NLP*, pages 182–195, Suzhou, China. Association for Computational Linguistics.

Qiang Liu, Jian Peng, and Alexander T. Ihler. 2012. Variational inference for crowdsourcing. In *Advances in Neural Information Processing Systems*, volume 25, pages 692–700.

Soda Marem Lo, Silvia Casola, Erhan Sezerer, Valerio Basile, Franco Sansonetti, Antonio Uva, and Davide Bernardi. 2025. PERSEVAL: A framework for perspectivist classification evaluation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 22345–22370, Suzhou, China. Association for Computational Linguistics.

Yiwei Luo, Dallas Card, and Dan Jurafsky. 2021. Detecting stance in media on global warming. *Preprint*, arXiv:2010.15149.

Fenglong Ma, Yaliang Li, Qi Li, Minghui Qiu, Jing Gao, Shi Zhi, Lu Su, Bo Zhao, Heng Ji, and Jiawei Han. 2015. Faitcrowd: Fine grained truth discovery for crowdsourced data aggregation. In *Proceedings of the 21st ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 745–754, Sydney, NSW, Australia. Association for Computing Machinery.

Marlon May, Lucie Flek, and Charles Welch. 2024. A perspectivist corpus of numbers in social judgements. In *Proceedings of the 3rd Workshop on Perspectivist Approaches to NLP (NLPerspectives) @ LREC-COLING 2024*, pages 42–48, Torino, Italia. ELRA and ICCL.

Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. 2021. A survey on bias and fairness in machine learning. *ACM Computing Surveys*, 54(6):1–35.

Wiktoria Mieleszczenko-Kowszewicz, Kamil Kanclerz, Julita Bielaniewicz, Marcin Oleksy, Marcin Gruza, Stanisław Woźniak, Ewa Dzieciol, Przemyslaw Kazienko, and Jan Kocoń. 2023. Capturing human perspectives in nlp: Questionnaires, annotations, and biases. In *NLPerspectives@ECAI*.

Negar Mokhberian, Myrl Marmarelis, Frederic Hopp, Valerio Basile, Fred Morstatter, and Kristina Lerman. 2024. Capturing perspectives of crowdsourced annotators in subjective learning tasks. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 7337–7349, Mexico City, Mexico. Association for Computational Linguistics.

Christoph Molnar. 2020. *Interpretable Machine Learning: A Guide for Making Black Box Models Explainable*. Lulu.com.

Britta Mondorf. 2002. Gender differences in english syntax. *Journal of English Linguistics*, 30(2):158–180.

Jingwei Ni, Yu Fan, Vilém Zouhar, Donya Rooein, Alexander Miserlis Hoyle, Mrinmaya Sachan, Markus Leippold, Dirk Hovy, and Elliott Ash. 2026. Can reasoning help large language models capture human annotator disagreement? In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 36–54, Rabat, Morocco. Association for Computational Linguistics.

Matthias Orlikowski, Jiaxin Pei, Paul Röttger, Philipp Cimiano, David Jurgens, and Dirk Hovy. 2025. Beyond demographics: Fine-tuning large language models to predict individuals' subjective text perceptions. *Preprint*, arXiv:2502.20897.

Matthias Orlikowski, Paul Röttger, Philipp Cimiano, and Dirk Hovy. 2023. The ecological fallacy in annotation: Modeling human label variation goes beyond sociodemographics. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1017–1029, Toronto, Canada. Association for Computational Linguistics.

Jahna Otterbacher. 2018. Social cues, social biases: Stereotypes in annotations on people images. In *Proceedings of the AAAI Conference on Human Computation and Crowdsourcing*, volume 6, pages 136–144.

Mohammed Fayiz Parappan and Ricardo Henao. 2025. Learning subjective label distributions via sociocultural descriptors. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 20333–20349, Suzhou, China. Association for Computational Linguistics.

Rebecca J. Passonneau and Bob Carpenter. 2014. The benefits of a model of annotation. *Transactions of the Association for Computational Linguistics*, 2:311–326.

Desmond Patton, Philipp Blandfort, William Frey, Michael Gaskell, and Svebor Karaman. 2019. Annotating social media data from vulnerable populations: Evaluating disagreement between domain experts and graduate student annotators. In *Proceedings of the 52nd Hawaii International Conference on System Sciences (HICSS-52)*.

Silviu Paun, Bob Carpenter, Jon Chamberlain, Dirk Hovy, Udo Kruschwitz, and Massimo Poesio. 2018. Comparing bayesian models of annotation. *Transactions of the Association for Computational Linguistics*, 6:571–585.

Ellie Pavlick and Tom Kwiatkowski. 2019. Inherent disagreements in human textual inference. In *Proceedings of ACL*.

Jiaxin Pei and David Jurgens. 2023. When do annotator demographics matter? measuring the influence of annotator demographics with the POPQUORN dataset. In *Proceedings of the 17th Linguistic Annotation Workshop (LAW-XVII)*, pages 252–265. Association for Computational Linguistics.

Tiancheng Pi and 1 others. 2025. iNews: A multimodal dataset for modeling personalized affective responses to news. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*.

Barbara Plank, Dirk Hovy, and Anders Søgaard. 2014. Learning part-of-speech taggers with inter-annotator agreement loss. In *Proceedings of the 14th Conference of the European Chapter of the Association for Computational Linguistics*, pages 742–751, Gothenburg, Sweden. Association for Computational Linguistics.

Massimo Poesio. 2020. Ambiguity. In Daniel Gutzmann, Lisa Matthewson, Cécile Meier, Hotze Rullmann, and Thomas Ede Zimmermann, editors, *The Companion to Semantics*. Wiley.

Massimo Poesio and Ron Artstein. 2005. The reliability of anaphoric annotation, reconsidered: Taking ambiguity into account. In *Proceedings of the Workshop on Frontiers in Corpus Annotations II: Pie in the Sky*, pages 76–83, Ann Arbor, Michigan. Association for Computational Linguistics.

Vikas C. Raykar, Shipeng Yu, Linda H. Zhao, Gerardo Hermosillo Valadez, Charles Florin, Luca Bogoni, and Linda Moy. 2010. Learning from crowds. *Journal of Machine Learning Research*, 11(Apr):1297–1322.

Giulia Rizzi, Elisa Leonardelli, Massimo Poesio, Alexandra Uma, Maja Pavlovic, Silviu Paun, Paolo Rosso, and Elisabetta Fersini. 2024. Soft metrics for evaluation with disagreements: an assessment. In *Proceedings of the 3rd Workshop on Perspectivist Approaches to NLP (NLPerspectives) @ LREC-COLING 2024*, pages 84–94, Torino, Italia. ELRA and ICCL.

W. S. Robinson. 1950. Ecological correlations and the behavior of individuals. *American Sociological Review*, 15(3):351–357.

F. Rodrigues and F. Pereira. 2018. Deep learning from crowds. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 1611–1618.

Pratik Sachdeva, Renata Barreto, Geoff Bacon, Alexander Sahn, Claudia von Vacano, and Chris Kennedy. 2022. The measuring hate speech corpus: Leveraging rasch measurement theory for data perspectivism. In *Proceedings of the 1st Workshop on Perspectivist Approaches to NLP @LREC2022*, pages 83–94. European Language Resources Association.

Marta Sandri, Elisa Leonardelli, Sara Tonelli, and Elisabetta Jezek. 2023. Why don't you do it right? analysing annotators' disagreement in subjective tasks. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 2428–2441, Dubrovnik, Croatia. Association for Computational Linguistics.

Yisi Sang and Jeffrey Stanton. 2021. The origin and value of disagreement among data labelers: A case study of the individual difference in hate speech annotation. *Preprint*, arXiv:2112.04030.

Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. 2023. Whose opinions do language models reflect? In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202, pages 29971–30004, Honolulu, Hawaii, USA. PMLR.

Sebastin Santy, Jenny Liang, Ronan Le Bras, Katharina Reinecke, and Maarten Sap. 2023. NLPositionality: Characterizing design biases of datasets and models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9080–9102, Toronto, Canada. Association for Computational Linguistics.

Maarten Sap, Swabha Swayamdipta, Laura Vianna, Xuhui Zhou, Yejin Choi, and Noah A. Smith. 2022. Annotators with attitudes: How annotator beliefs and identities bias toxic language detection. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5884–5906. Association for Computational Linguistics.

Olufunke O. Sarumi, Charles Welch, and Daniel Braun. 2026. Fine-grained perspectives: Modeling explanations with annotator-specific rationales. *Preprint*, arXiv:2604.21667.

Edgar D. Simpson, Matteo Venanzi, Pushmeet Kohli, John Guiver, Gianluca Kazai, and Milad Shokouhi. 2015. Language understanding in the wild: Combining crowdsourcing and machine learning. In *Proceedings of the 24th International Conference on World Wide Web (WWW 2015)*, pages 992–1002, Florence, Italy. Association for Computing Machinery.

Fritz Strack. 1992. "order effects" in survey research: Activation and information functions of preceding questions. In Norbert Schwarz and Seymour Sudman, editors, *Context Effects in Social and Psychological Research*, chapter 3. Springer, New York, NY.

Lucky Susanto, Musa Izzanardi Wijanarko, Prasetia Anugrah Pratama, Traci Hong, Ika Idris, Alham Fikri Aji, and Derry Wijaya. 2025. Indotoxic2024: A demographically-enriched dataset of hate speech and toxicity types for indonesian language. *Preprint*, arXiv:2406.19349.

R. Tanno, A. Saeedi, S. Sankaranarayanan, D. C. Alexander, and N. Silberman. 2019. Learning from noisy labels by regularized estimation of annotator confusion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11244–11253.

Jackson Trager, Alireza S. Ziabari, Elnaz Rahmati, Aida Mostafazadeh Davani, Preni Golazizian, Farzan Karimi-Malekabadi, Ali Omrani, Zhihe Li, Brendan Kennedy, Georgios Chochlakis, Nils Karl Reimer, Melissa Reyes, Kelsey Cheng, Mellow Wei, Christina Merrifield, Arta Khosravi, Evans Alvarez, and Morteza Dehghani. 2026. The moral foundations reddit corpus. *Preprint*, arXiv:2208.05545.

Enrica Troiano, Laura Oberländer, and Roman Klinger. 2023. Dimensional modeling of emotions in text with appraisal theories: Corpus creation, annotation reliability, and prediction. *Computational Linguistics*, 49(1):1–72.

Alexandra Uma, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, and Massimo Poesio. 2021. Learning from disagreement: A survey. *Journal of Artificial Intelligence Research*, 72:1385–1470.

Mathieu Valette. 2024. What does perspectivism mean? an ethical and methodological countercriticism. In *Proceedings of the 3rd Workshop on Perspectivist Approaches to NLP (NLPerspectives) @ LREC-COLING 2024*, pages 111–115, Torino, Italia. ELRA and ICCL.

Anthony J. Viera and Joanne M. Garrett. 2005. Understanding interobserver agreement: The kappa statistic. *Family Medicine*, 37(5):360–363.

Ruyuan Wan, Jaehyung Kim, and Dongyeop Kang. 2023. Everyone's voice matters: Quantifying annotation disagreement using demographic information. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 14523–14530.

Tharindu Cyril Weerasooriya, Sujan Dutta, Tharindu Ranasinghe, Marcos Zampieri, Christopher M. Homan, and Ashiqur R. KhudaBukhsh. 2023a. Vicarious offense and noise audit of offensive speech classifiers: Unifying human and machine disagreement on what is offensive. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 11648–11668. Association for Computational Linguistics.

Tharindu Cyril Weerasooriya, Alexander Ororbia, Raj Bhensadadia, Ashiqur KhudaBukhsh, and Christopher Homan. 2023b. Disagreement matters: Preserving label diversity by jointly modeling item and annotator label distributions with DisCo. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 4679–4695, Toronto, Canada. Association for Computational Linguistics.

H. Wei, R. Xie, L. Feng, B. Han, and B. An. 2022. Deep learning from multiple noisy annotators as a union. *IEEE Transactions on Neural Networks and Learning Systems*.

Peter Welinder, Steve Branson, Pietro Perona, and Serge J. Belongie. 2010. The multidimensional wisdom of crowds. In *Advances in Neural Information Processing Systems*, volume 23, pages 2424–2432.

Jacob Whitehill, Ting fan Wu, Jacob Bergsma, Javier R. Movellan, and Paul L. Ruvolo. 2009. Whose vote should count more: Optimal integration of labels from labelers of unknown expertise. In *Advances in Neural Information Processing Systems*, volume 22, pages 2035–2043.

Michael Wojatzki, Tobias Horsmann, Darina Gold, and Torsten Zesch. 2018. Do women perceive hate differently: Examining the relationship between hate speech, gender, and agreement judgments. In *Conference on Natural Language Processing*.

Jin Xu, Mariët Theune, and Daniel Braun. 2024a. Leveraging annotator disagreement for text classification. In *Proceedings of the 7th International Conference on Natural Language and Speech Processing (IC-NLSP 2024)*, pages 1–10, Trento. Association for Computational Linguistics.

Shanshan Xu, T. Y. S. S Santosh, Oana Ichim, Isabella Risini, Barbara Plank, and Matthias Grabmair. 2024b. From dissonance to insights: Dissecting disagreements in rationale construction for case outcome classification. *Preprint*, arXiv:2310.11878.

Yinuo Xu, Veronica Derricks, Allison Earl, and David Jurgens. 2025. Modeling annotator disagreement with demographic-aware experts and synthetic perspectives. *Preprint*, arXiv:2508.02853.

Tianling Yang, Christian Strippel, Alexandra Keiner, Dylan Baker, Alexis Chávez, Krystal Kauffman, Marc Pohl, Caroline Sinders, and Milagros Miceli. 2023. Ethics of data work: Principles for academic data work requesters. Weizenbaum discussion paper, Weizenbaum Institute for the Networked Society.

Lily Hong Zhang, Smitha Milli, Karen Jusko, Jonathan Smith, Brandon Amos, Wassim Bouaziz, Manon Revel, Jack Kussman, Yasha Sheynin, Lisa Titus, Bhaktipriya Radharapu, Jane Yu, Vidya Sarma, Kris Rose, and Maximilian Nickel. 2026. Cultivating pluralism in algorithmic monoculture: The community alignment dataset. *Preprint*, arXiv:2507.09650.

Liyun Zhang, Jingcheng Ke, Shenli Fan, Xuanmeng Sha, and Zheng Lian. 2025a. A unified evaluation framework for multi-annotator tendency learning. *Preprint*, arXiv:2508.10393.

Michael JQ Zhang, Zhilin Wang, Jena D. Hwang, Yi Dong, Olivier Delalleau, Yejin Choi, Eunsol Choi, Xiang Ren, and Valentina Pyatkin. 2025b. Diverging preferences: When do annotators disagree and do models know?

Zhao Zhao, Fang Wei, Ming Zhou, Wei Chen, and Wilfred Ng. 2015. Crowd-selection query processing in crowdsourcing databases: A task-driven approach. In *Proceedings of the 18th International Conference on Extending Database Technology (EDBT)*, pages 397–408. OpenProceedings.org.

Yudian Zheng, Guoliang Li, Yuanbing Li, Caihua Shan, and Reynold Cheng. 2017. Truth inference in crowdsourcing: is the problem solved? *Proc. VLDB Endow.*, 10(5):541–552.

A Appendix

A.1 Survey Scope and Selection

This survey focuses on research in NLP that studies, models, or evaluates annotator disagreement in text-based tasks. We restrict our scope to NLP settings where disagreement is theoretically meaningful, such as toxicity detection, stance analysis, sentiment, and other subjective or socially grounded judgments, rather than domains where disagreement primarily reflects measurement error. Our goal is not to exhaustively catalog all work on annotation variability (of which there is decades of work), but to synthesize lines of research that treat disagreement as a signal relevant to learning, evaluation, or model design, with a slight focus on connecting the most recent work.

We survey over 110 prior works spanning disagreement sources, modeling methods, and evaluation paradigms. We queried venues such as ACL Anthology, Google Scholar, Semantic Scholar, and arXiv. We use keywords including "annotator disagreement", "learning from crowds", "multi-annotator learning", "annotator bias", "subjective NLP", "label distribution", and "perspectivist NLP". We prioritized publications in major NLP venues (ACL, EMNLP, NAACL, EACL, TACL, Findings of ACL), as well as interdisciplinary venues where annotator modeling is prominent (AAAI, NeurIPS, CHI, FAccT). We emphasized recent work from 2010-2025, focusing on developments after 2018, for two reasons. First, earlier work on learning from disagreement, which was dominated by latent-truth models, is already thoroughly surveyed by Uma et al. (2021), which scope spans both computer vision and NLP. Second, around 2018, the modeling of individual annotators moved toward neural architectures: the per-annotator output heads introduced by Crowd-Layer (Rodrigues and Pereira, 2018) and Guan et al. (2018) became the architectural template that subsequent task-based work builds on, and that later embedding-based methods reformulate to scale to many annotators under sparse labels. This marks a shift from recovering a single ground truth toward preserving individual and group perspectives.

Table 1 provides the counts of papers surveyed in each category we focus on. Papers may appear in multiple categories when relevant. We also reviewed 9 papers on large language model–based persona prompting and demographic conditioning; however, because most of this work focuses on

Survey Category	# Papers
Sources of Disagreement	30
Disaggregated Datasets (Data)	24
Latent Truth & Reliability Modeling	21
Task-Based Multi-Annotator Learning	8
Embedding-Based Multi-Annotator Learning	11
Evaluation Metrics	14
LLM-Based Persona Simulation	9
Total Unique Papers Surveyed	**117**

Table 1: Distribution of papers surveyed across categories. Each paper is counted once, in its primary category.

simulating personas rather than explicitly modeling annotator structure or disagreement, we discuss these primarily in the Challenges and Future Work section.

We include work that makes a substantive methodological contribution, defined as proposing a learning algorithm, prediction target, or evaluation framework that explicitly accounts for multiple annotators or divergent interpretations. For each of the three modeling families that we identify (latent truth modeling, task-based multi-annotator learning, and embedding-based approaches), we include seminal and highly-cited work (e.g., Dawid and Skene, 1979; Cohn and Specia, 2013; Kocoń et al., 2021) in order to contrast witih representative recent advances. The review was conducted iteratively. We first followed citation chains from seminal works and tracked emerging work from the Workshop on Perspectivist Approaches to NLP[1] and related venues. Our taxonomy of disagreement sources was refined in parallel with the literature review.

Taken together, this scope allows us to position our survey as a complement to existing work. Whereas prior surveys are either primarily conceptual (Frenda et al., 2024) or modality-general (Uma et al., 2021), we center NLP as a domain where disagreement is deeply tied to task design, interpretation practices, and annotator identities. By jointly examining modeling approaches, evaluation practices, and their fairness implications within a unified framework, we aim to provide a more technically-grounded synthesis of perspectivist modeling that has not yet been articulated in existing surveys.

---

[1] https://nlperspectives.di.unito.it/

Dataset	Task / Domain	Language	Annotator metadata reported
Kumar et al. Toxicity-Perspectives (Kumar et al., 2021)	Toxicity rating on subjective scale	English (Twitter, Reddit, 4chan)	Gender, age, race/ethnicity, sexual orientation, education, political affiliation, religion, parenthood status, prior experience with toxicity
Measuring Hate Speech (Sachdeva et al., 2022)	Hate speech scoring	English	Race, gender, sexuality, age, education, income, political ideology; decision difficulty & survey bias
ArMIS (Almanea and Poesio, 2022)	Misogyny & sexism	Arabic	Religious beliefs, gender
Google Specialized Rater Pools (Goyal et al., 2022)	Toxicity classification	English	Target-identity rater pools: African American, LGBTQ, US control
Annotators with Attitudes (Sap et al., 2022)	Toxic / hate speech	English	Sociodemographics; racial attitudes, free-speech beliefs, conservatism
POPQUORN (Pei and Jurgens, 2023)	Offensiveness, politeness, QA, rewriting	English	US-representative: sex, age, race, education
DICES (Aroyo et al., 2023)	Conversational AI safety	English	Gender, age, race/ethnicity, education
EPIC (Frenda et al., 2023)	Irony detection	English (5 varieties)	Age, gender, nationality/variety
VOICED (Weerasooriya et al., 2023a)	Vicarious offense / noise audit	English	Age, gender, race, political leaning
crowd-enVENT (Troiano et al., 2023)	Emotion + 21 appraisal dimensions over event descriptions	English	Demographics (gender, age, education), Big-Five personality, current emotional state for both authors and reader annotators
NLPositionality (Santy et al., 2023)	Social-acceptability and toxicity judgements	English (global participants)	Country, age, gender, race/ethnicity, education, religion, native language
MultiPICo (Casola et al., 2024)	Irony (short conversations)	Multilingual	Age, gender, ethnicity, country, employment status
D3CODE (Davani et al., 2024b)	Offensive language (cross-cultural)	Multiling. (21 countries)	Age, gender, SES, country/region; 6 moral foundations

Dataset	Task / Domain	Language	Annotator metadata reported
IndoToxic2024 (Susanto et al., 2025)	Hate speech & toxicity subtypes	Indonesian	Disability, ethnicity, religion, gender, LGBTQ+, age, education, job status, presidential vote
CREHate (Lee et al., 2024)	Cross-cultural English hate speech	English (AU, GB, SG, US, ZA)	Country of residence (5 Anglophone countries), gender, ethnicity
CSC (Jang and Frassinelli, 2024; Jang et al., 2023)	Sarcasm rating (6-point Likert)	English	gender, age, ethnicity, annotator general sarcasm, personality traits
PRISM Alignment Dataset (Kirk et al., 2024)	LLM preference / value-laden conversations	English (participants from 75 countries)	Age, gender, employment, marital status, education, ethnicity, religion, English proficiency, country of birth/residence, LLM familiarity
A Perspectivist Corpus of Numbers in Social Judgment(May et al., 2024)	Social/moral judgments with numerical reasoning	English	Gender identity, nationality, age, religion, political orientation, education
GBV dataset (Abercrombie et al., 2024)	Online Gender-Based Violence	English	Gender, age, ethnicity, social psychology surveys
iNews (Pi et al., 2025)	Affective response to news	Multilingual	Age, gender, income, education; Big Five, PANAS, CRT; news trust, consumption, politics
LeWiDi-2025 "Par" (Leonardelli et al., 2025)	Paraphrase detection	English (Quora Question Pairs)	Gender, age, nationality, education
VariErrNLI (Sarumi et al., 2026)	NLI labels + label-explanation validity judgments	English	Gender, age, nationality (CN, DE), education
Community Alignment Dataset (Zhang et al., 2026)	Multi-turn LLM preference with negatively-correlated candidate sampling	English, French, Italian, Hindi, Portuguese	Country, language, plus age, gender, education

Dataset	Task / Domain	Language	Annotator metadata reported
MFRC (Trager et al., 2026)	Moral sentiment (Care, Equality, Proportionality, Authority, Loyalty, Purity, Thin Morality)	English	gender, sexual orientation, age, household income, first language, political ideology along a liberal-conservative scale, religious affiliation, and moral values via the Moral Foundation Questionnaire

Table 2: Disaggregated datasets reporting annotator identity or sociodemographic metadata.

A.2 Detailed Synthesis Table of Prediction Targets and Pooling Structures

We provide a detailed table mapping representative work in each modeling family to the axis of prediction target and pooling structures (Fig. 4).

POOLING

	PATIAL POOLING	UNPOOLED
DISTRIBUTION	*Jinadu et al. (2024)* — subjectivity-tunable loss distinguishing noise vs disagreement.

Weerasooriya et al. (2023, DisCo) — predicts joint item + annotator label distributions.

Parappan and Henao (2025) -- predicts label distribution using sociodemographics + LLM-generated perspectives | *Fornaciari et al. (2021)* — MTL with soft labels as ambiguity-based regularization |
| **GROUP** | **NUTMEG (Ivey et al, 2025)** -- Hierarchical Bayesian annotator model with demographic priors

Fleisig et al. (2024) — stakeholder-aware MTL predicting harmed-group ratings.

Gordon et al. (2022) — "jury" model combining demographic subgroup embeddings.

Xu et al. (2025) — DEM-MoE experts specialized by demographic/intersectional traits. | *Fleisig et al. (2024)* — aggregates group-specific predictions for fairness-aware consensus. |
| **ANNOTATOR** | *Cohn & Specia (2013)* — multi-task GP with learned inter-annotator kernel B.

Rodrigues & Pereira (2018) — Crowd Layer learning bias transforms via backprop.

Guan et al. (2017) — per-doctor CNN heads with reliability weighting.

Mokhberian et al. (2023, AART) — scalable annotator embeddings + sparsity regularization.

Gordon et al. (2022)
Xu et al. (2025) | *Davani et al. (2022)* — multi-head BERT predicting each annotator's view.

Kocoń et al. (2021) — introduced annotator embedding for personal bias.

Deng et al. (2023) — injects annotator + annotation embeddings into Transformer.

Ignatev et al. (2025) -- parameter-efficient annotator-specific LORA weights |
| **CONSENSUS** | *Paun et al. (2018)* — hierarchical Bayes comparison of pooling schemes.
Simpson et al. (2015) — BCCWords links linguistic features with bias.
Goh et al., (2023) — ensemble using task-level classifier as pseudo-annotator for consensus. | *Dawid & Skene (1979)* — EM model inferring latent truth + error rates.

Raykar et al. (2010) — jointly learns annotator expertise + logistic regressor. |

PREDICTION TARGET

LATENT TRUTH ANNOTATOR MODELING
TASK-BASED MULTI-ANNOTATOR MODELING
EMBEDDING-BASED MULTI-ANNOTATOR MODELING

Figure 4: Prediction targets and pooling assumptions across methods for learning from annotator disagreement. The table maps existing approaches by what they predict (consensus labels, individual annotator responses, group-level outputs, or full disagreement distributions) and how they pool information across annotators. Modeling choices implicitly encode different assumptions about population structure, perspective aggregation with recent work increasingly favoring partial pooling and distributional targets.