Integrating linguistic knowledge into DNNs: Application to online grooming detection

Abstract

Online grooming (OG) of children is a pervasive issue in an increasingly interconnected world. We explore various complementary methods to incorporate Corpus Linguistics (CL) knowledge into accurate and interpretable Deep Learning (DL) models. They provide an implicit text normalisation that adapts embedding spaces to the groomers' usage of language, and they focus the DNN's attention onto the expressions of OG strategies. We apply these integration to two architecture types and improve on the state-of-the-art on a new OG corpus.

1 Introduction

Online grooming (OG) is a communicative process of entrapment in which an adult lures a minor into taking part in sexual activities online and, at times, offline (Lorenzo-Dus et al., 2016; Chiang & Grant, 2019). The aim of this work is to detect instances of OG through classification of whole conversations. In a context of law enforcement investigation, the main aim of such automatic processing of large databases is to allow human investigators to review in more detail those conversations that are flagged as at risk. This classification requires the ability to capture subtleties in the language used by groomers. Corpus Linguistic (CL) analysis provides a detailed characterisation of language in large textual datasets (McEnery & Wilson, 2003; Sinclair, 1991). We argue that, when integrated into ML models, the products of CL analysis may allow a better capture of language subtleties, while simplifying and guiding the learning task. We consider two types of CL products and explore strategies for their integration into several stages of DNNs. Moreover, we show that CL knowledge may help law enforcement in interpreting the ML decision process, towards the production of evidences for potential prosecution.

OG detection is performed on text that heavily uses slang and sms-style writing, as many real-world Natural Language Processing (NLP) tasks for chat logs. Text normalisation methods were proposed to reduce variance and simplify learning, e.g. for sms-style writing (Mansfield et al., 2019). However, they do not account for the final text analysis goal and may discard some informative variance, e.g. the use of certain forms of slang possibly indicative of a user category. CL analysis provides with the preferred usage of spelling variants or synonyms. We propose to use this domain knowledge to selectively normalise chat logs while preserving the informative variance for the classification task.

As demonstrated by the CL analysis in (Lorenzo-Dus et al., 2016), the theme and immediate purpose of groomer messages may vary throughout the conversation, in order to achieve the overarching goal of entrapping the victims. Groomers use a series of inter-connected "sub-goals", referred to as *OG processes* here, namely gaining the child's trust, planning activities, building a relationship, isolating them emotionally and physically from his/her support network, checking their level of compliance, introducing sexual content and trying to secure a meeting off-line. The language used within these processes is not always sexually explicit, which makes their detection more challenging. However, CL analysis additionally flags some contexts associated to the OG processes, in the form of word collocations (i.e. words that occur within a same window of 7 words) that tend to occur more frequently in, and therefore can be associated with, OG processes. We propose to exploit the relations between the OG processes and their overarching goal of OG to improve the final OG classification. We use the CL identified context windows to guide the learning of our DNN.

The main contributions of this paper are: 1) We explore different strategies for integrating CL knowledge into DNNs. They are applied to two architecture types and demonstrated on OG detection, but may generalise to other NLP applications that involve real-world chat language and/or complex

conversational strategies. 2) The principle and several implementations of selectively normalising text through modifying a word semantics representation (WSR) in support to classification. 3) The decomposition of conversation analysis into identifying the conversation's sub-goals. Our DNN implicitly models the relations between these sub-goals and the conversation's overarching final goal. 4) A new attention mechanism for LSTM based on the direct stimulation of its input gates, with two proposed implementations. 5) A state-of-the-art (SoTA) and interpretable OG detector. 6) A new corpus for OG detection, to be publicly released on demand, and that extends PAN2012 with more conversations and with products of CL analysis.

2 RELATED WORK

A DNN was used to detect OG chat logs by classifying binary bag-of-words in (Villatoro-Tello et al., 2012). This simple approach highlights the importance of commonly used words amongst groomers which we exploit for selective normalisation. This is emphasised in (Vartapetiance & Gillam, 2014; Hidalgo & Díaz, 2012) where a set of phrases are derived from the important features of a Naïve Bayes classifier to describe common behaviours among groomers. Liu et al. (2017) obtained the current SoTA for OG detection using a WSR that captures important words and a two-layer LSTM.

Integrating domain knowledge into DNNs is often done with additional losses that assist with sparse and low quality data. (Muralidhar et al., 2018) penalise a DNN's output violating logical rules w.r.t. the input features. (Hu et al., 2018) use the posterior regularisation framework of (Ganchev et al., 2010) to encode domain constraints for generative models. A teacher-student architecture in (Hu et al., 2016) incorporates first-order logic rules to create an additional loss for the student network. Other works integrated prior knowledge in the design of the DNN architecture. In BrainNetCNN (Kawahara et al., 2017), the convolutions of a convolutional neural network (CNN) are defined based on the graph data's locality to account for the brain's connectivity. The training procedure may also integrate priors without modifying the DNN's architecture. Derakhshani et al. (2019) use assisted excitation of CNN neurons in the images' areas of interest, thus providing both localisation and semantic information to the DNN. An attention mechanism was used in a supervised way to focus a DNN on important words in (Nguyen & Nguyen, 2018). We experiment with these various approaches and adapt them to our domain knowledge and DNN architectures.

3 AUGMENTED PAN2012 DATASET

PAN2012 (Inches & Crestani, 2012) is a standard corpus for OG detection. It was gathered from Omegle (one-to-one conversations with random users), IRC (technical discussions in groups), and the Perverted Justice (PJ) website[1] (chat logs from convicted groomers interacting with trained adult decoys, for a debate on the usability of this data, see (Chiang & Grant, 2019; Schneevogt et al., 2018), with 396 groomers and 5700 / 216,121 OG / non-OG conversations. Some non-OG chat logs contain sexual wording, making the OG classification more challenging. Conversations are truncated to 150 messages each, which limits both CL and ML analyses. To resolve this limitation, we augment the corpus with full conversations (avg. 431 messages per conversation) and the addition of new groomers from PJ, totalling 623 groomers in 6204 OG conversations (same negatives). Detailed statistics on the dataset content are provided in the sup. materials.

Our dataset also includes the results of a CL analysis of the new corpus using the method described in (Lorenzo-Dus et al., 2016), which involves a heavy use of manual analysis by CL experts. As part of data preparation for CL analysis, *word variants* are identified, which are either spelling variations (mistakes or intentional e.g. 'looool' → 'lol'), or the same semantic meaning behind two terms (e.g. 'not comfy' → 'uncomfortable'). These variants are not specific to OG, but are valid for other real-world chat conversations. However, the CL analysis also identified the variants that are most used among groomers. The CL products in our dataset include: 1) the set of variants both general and groomer-preferred, 2) a set of frequent 3-word collocates (not necessarily direct neighbours, but located within a window of 7 words) that are used among many different users (known as *highly-dispersed* in CL), and 3) a manual annotation of 2100 samples of OG processes (there are 7 types of OG processes, as listed in the introduction and detailed in the sup. materials) that could be associated to 3-word collocates and the context windows that these latter define. These CL

---

[1] http://perverted-justice.com

Figure 1: Base models #1 (left) & #2 (right), for integration of CL priors. Orange and green indicate where word variants and OG processes priors may be integrated, respectively.

products are sensitive data that might be used to help groomers refine their strategies, therefore they will only be shared on demand. They are used in Sections 4-5 to train a DNN model, but this model does not require CL analysis to be performed at testing phase, as it takes raw text only as input.

4 METHODOLOGY

Overarching vision and general applicability – We integrate two CL priors into DNNs: the word variants and the identification of OG processes. Word variants provide knowledge of same semantic meaning, which allows reducing variance in the text. The knowledge of groomer's preferred variants brings an implicit and selective text normalisation that supports the classification task. It is achieved through a reduction of distances between non-discriminative variants in a WSR space. This selective normalisation is applicable to other classification tasks from real-world chat logs, provided an updated selection of the preferred and discriminative variants, and is applicable to all DNNs that use a WSR.

The use of OG processes aides in differentiating between causal conversations involving sexual language, and OG conversations with complex strategies and sub-goals (i.e. OG processes). The language associated to OG processes, reflected by the 3-word collocates and context windows that they define, may be more informative than simple sexual wording in making this distinction. We propose 3 strategies to integrate this knowledge, namely the definition of sub-tasks and two stimulations of DNN attention. They all guide the learning by providing focus on contexts of interest (a valuable complement to attention mechanisms, as demonstrated in our experiments), and by implicitly modelling the relation between sub-goals and final goal. This CL knowledge integration principle is also generally applicable to the analysis of complex conversations, provided an appropriate CL identification of the conversation's sub-goals and their associated language through context windows. Our stimulation of DNN attention may be more generally used to focus a DNN's attention on *a priori* known important elements of a training dataset.

Base models – We demonstrate the general applicability of our CL integration strategies by applying them to two DNN architecture types representative of the two NLP standards of recurrent and transformer models. The recurrent DNN of Liu et al. (2017) is the current SoTA for OG classification. It comprises a language model that builds a WSR, and an OG classifier with two LSTMs and a linear projection. Our *base model #1* is a modified version (Fig. 1 left) with the WSR's embedding provided as input to the OG classifier in place of a sentence embedding. This WSR will be more directly impacted by our CL integration, and it increases explainability as will be seen next. It may be replaced by similar WSRs, and we also present results using the pre-trained GloVe WSR (Pennington et al., 2014). Further, to compensate for the loss of sentence structure modelling previously provided by the sentence embedding, and to account for the longer sequences of inputs into the classifier, we add an unsupervised attention mechanism (Luong et al., 2015) into the classifier.

The XLNet (Yang et al., 2019) transformer model is the SoTA for NLP. It iteratively refines word embeddings, from a WSR similar to that of Liu et al. (2017) to richer word representations to account for their relationships, to be classified by linear projection. This projection fails to handle our class imbalance, and thus a two-layer LSTM is added to form *base model #2* (Fig. 1 right).

Input to the models – The text analysis is performed on whole conversations, with conversation messages separated by the [SEP] token, so that inter-text representations can be modelled. Messages from both users are included with no distinction. The final OG/non-OG classification is obtained for the whole conversation, rather than per-message. All base and CL-augmented DNNs take raw text as

input only. The only text preparation prior to the DNN is tokenisation of named entities, as actual names are irrelevant to OG detection. We do not apply text normalisation such as (Mansfield et al., 2019), since the methodological premise of the paper is the design of a hybrid approach where an ML model incorporates its own normalisation informed by CL knowledge.

4.1 IMPLICIT AND SELECTIVE TEXT NORMALISATION BASED ON WORD VARIANTS

The natural stage of DNNs to integrate knowledge on word variants is the WSR that captures word semantic. The mean occurrence frequency of variants in the OG corpus is significantly larger, by two orders of magnitude, than that of all words (see sup. materials). Therefore, using these common words to modify the WSR may have a strong impact on classification. We propose 3 strategies to modify the WSR based on our set of N pairs of variants $\{(v_1^i, v_1^j), ..., (v_N^i, v_N^j)\}$ using the principle that *words with same semantic should be moved closer to each other in the WSR space*.

Although variants have same intended meaning, some may be discriminative of groomers' language. Hence, it may be useful for OG classification to keep them apart in the WSR space. The significance of word w for classification is determined based on the absolute difference of empirical occurrence in OG and non-OG conversations within the training set: $\delta p(w) = |p(w|y_{pos}) - p(w|y_{neg})|$. If $\delta p(v_k^i)$ or $\delta p(v_k^j)$ are high (i.e. within the last 5 percentiles for all words), *we do not use the pair for modification of the WSR*. We considered increasing the separation between these variants, but we found that this modifies too much the embedding and reduces its semantics representation power. Out of 4590 pairs of variants, we retain 2955 for modification of the WSR. In effect, this selective WSR modification applies an implicit and selective text normalisation which supports the OG classification.

We experiment with 3 implementations that may apply to different usage scenarios such as training a new language space (supervised WSR modification), or modifying an existing one before training a new classifier (manifold-based) or before fine-tuning an already existing classifier (elastic pulling).

Supervised WSR modification – A regularisation term is added with weight λ to the language modelling loss $\mathcal{L}_{WSR}$ to minimise the L_2 distance $\mathcal{D}$ between the selected word variants' embeddings: $\tilde{\mathcal{L}}_{WSR} = (1 - \lambda)\,\mathcal{L}_{WSR} + \lambda\left[\frac{1}{N}\sum_{k=1}^{N}\mathcal{D}(v_k^i, v_k^j)\right]$.

Manifold learning – We perform a global transformation of the existing WSR space by building, using manifold learning, a new space from an edited pairwise distance matrix with $\tilde{\mathcal{D}}(v_k^i, v_k^j) = \lambda \mathcal{D}(v_k^i, v_k^j)$ where $\lambda \in [0, 1]$ modulates the strength of distance reduction between selected variants. We use Robust Diffusion Map (Paiement et al., 2014), but other manifold learning methods could be explored. This implementation requires re-training subsequent modules from scratch, as words' new embeddings may be very different from initial ones. Note that we make an unusual use of manifold learning for WSR modification rather than for dimensionality reduction. It is possible reduce dimensionality, which may help to combat overfitting for classification, as discussed in (Yin & Shen, 2018). However, the dimensionality of the WSR is unchanged in our experiments.

Elastic pulling – Our third implementation modifies the existing WSR space 'in place' through local movements that pull together the selected variants. This mostly preserves all words' original embedding coordinates, thus limiting the amount of change needed for the classifier to simple fine-tuning. Two variants v_k^i and v_k^j of coordinates $\mathbf{x}_k^i$ and $\mathbf{x}_k^j$ are pulled towards their centre $\hat{\mathbf{x}}_k = \frac{\mathbf{x}_k^i + \mathbf{x}_k^j}{2}$ by the amount $\delta_{\mathbf{x}_k^i} = \hat{\mathbf{x}}_k - \mathbf{x}_k^i$ modulated by $\lambda \in [0, 1]$: $\tilde{\mathbf{x}}_k^i = \mathbf{x}_k^i + \lambda \delta_{\mathbf{x}_k^i}$. We propagate the pull operation to neighbouring words, with strength of pull decreasing with distance (i.e. modulated by a radial basis function (RBF) ϕ_k^i centred on $\mathbf{x}_k^i$), so as to preserve the pairwise relationships between variants and their neighbours: $\tilde{\mathbf{x}} = \mathbf{x} + \lambda\,\phi_k^i(\mathbf{x})\,\delta_{\mathbf{x}_k^i}$. We use an inverse multiquadric $\phi_k^i(\mathbf{x}) = (||\mathbf{x} - \mathbf{x}_k^i||^2 + \gamma^2)^{-\frac{\beta}{2}}$, with global support so that all words can be considered without costly intersection tests needed, and with β and γ tuning the RBF's decay rate i.e. the locality of propagated pull. We found that the method is not very sensitive to these values as long as the pull's reach is sufficient, within a radius of the order of magnitude of $\delta_{\mathbf{x}_k^i}$, and we set them empirically to 1.0 and 3.0 respectively.

4.2 INTEGRATING KNOWLEDGE ON OG PROCESSES

Our annotated samples of OG processes are associated to 3-word collocates, which are used to identify contexts of interest. We define a continuous representation of the presence of the 7 OG processes using 7 Gaussian Mixture Models (GMM) with components centred on the 3-word collocates and std the span of each collocate (max. 7 words as mentioned in Section 3). We propose 3 uses to focus the attention of the DNN on parts of the conversations that implement the OG processes and on the associated language, and to implicitly model the relations between OG processes and OG.

Auxiliary OG process detection – A second output branch is added to the DNN after the LSTMs, with a fully-connected layer and MSE loss, to estimate the pseudo occurrence probability of the 7 OG processes provided by their GMMs, at each word location. For base model #1, we experimented with adding an attention block as in the main branch, but found that this didn't help with the OG process detection, probably because this task is more local and doesn't need to consider as large a context as classification of whole conversation. The new branch also serves as additional regularisation to prevent overfitting given the class imbalance between (non-)OG chat logs. Further, it allows for an OG process-based interpretation of what the DNN considers as relevant clues for OG classification.

Stimulating attention – Both the unsupervised attention of Luong et al. (2015) in base model #1, and the self-attention layers of base model #2, compute an attention energy e_t for word at position t. It may be stimulated during training to guide the DNN's attention on occurrences of OG processes[2]. We propose two strategies: a) through **supervision** by the sum $\mathcal{G}$ of GMMs used as ground-truth distribution of the salient locations and attention energies: $\mathcal{L}_{\text{attention}} = \frac{1}{T} \sum_{t=1}^{T} (e_t - \mathcal{G}(t))^2$, with T the length of messages from both users. This is similar to (Nguyen & Nguyen, 2018), but with $\mathcal{G}$ highlighting higher-level OG processes rather than single important words. b) through direct **excitation** of the attention energies, inspired by (Derakhshani et al., 2019) that excited CNN's activations to speed up localisation learning in images. We propose two possible implementations: A) $\tilde{e}_t = e_t + \mathcal{G}(t)\, e_t$, and B) $\tilde{e}_t = e_t + \mathcal{G}(t)$.

Stimulating LSTM input gates – An alternative (or complement) to stimulating an attention mechanism is to stimulate LSTM cells directly, during training[2], in locations containing OG processes indicated by $\mathcal{G}$. This is a new way to stimulate attention and to encourage the LSTM to recognise and focus on the contexts of OG processes. We propose two implementations: a) through **supervision** by minimising the loss between the average input gates' activations i_t and the combined GMMs: $\mathcal{L}_{\text{stimulation}} = \frac{1}{T} \sum_{t=1}^{T} (i_t - \mathcal{G}(t))^2$; b) through **excitation** of activations, following the same idea as for exciting attention. The input gate activation i_t^d of each LSTM cell d is augmented during OG processes, indicated by a peak of $\mathcal{G}$, through: $\tilde{i}_t^d = i_t^d + \frac{\mathcal{G}(t)}{D} \sum_{d=1}^{D} h_t^d$. We average over the hidden states h_t^d of the D LSTM cells in the layer, by analogy to (Derakhshani et al., 2019) that averaged over all channels of a CNN's activation map.

5 EXPERIMENTS

Both original and modified base model #1 are trained from random weights on our dataset. Experiments with the GloVe WSR use pre-trained weights from Common Crawl 840B (Pennington et al., 2014). The XLNet part of base model #2 is pre-trained on BookCorpus and English Wikipedia, see (Yang et al., 2019). Detailed training procedures are provided in the sup. materials. For base model #2, the selective normalisation is not tested due to lack of time in fine-tuning XLNet. The attention is stimulated in the final self-attention layer only, and future experiments may test other locations.

We divide the corpus into 30% of users for training, 70% for testing, and 30% of training for validation, using a similar ratio as Inches & Crestani (2012). This division based on users ensures that the model may not recognise the specific language of a groomer, but focuses on trends in OG language. OG classification is evaluated by: area under precision-recall curve (AUPR) to account for the class label imbalance, F_{max} the F_1 score from best position on the PR curve, F_1 score, and the $F_{0.5}$ score used in (Inches & Crestani, 2012) to weight the precision metric higher. The effects of selective normalisation are further measured by their proportion of distance reduction

---

[2] No annotation of OG processes (i.e. GMM) is required at testing time.

Table 1: Impact of each CL augmentation on OG classification. Bold are improved results.

Model	Strategy		AUPR	F_{max}	F_1	$F_{0.5}$	$\Delta\mathcal{D}$	$\overline{\mathcal{D}}$
#1	No augmentation		0.867	0.832	0.829	0.851	–	3.72
	Supervised WSR modification		0.824	0.801	0.798	0.819	0.75	0.91
	Manifold learning		0.809	0.823	0.820	0.781	0.65	1.29
	Elastic pulling		**0.877**	**0.842**	**0.841**	**0.863**	0.83	0.61
	Aux. OG process detection		**0.873**	0.825	0.825	**0.863**	–	–
	Stim. attention	supervised	**0.879**	0.822	0.821	0.832	–	–
		excitation (A)	**0.877**	0.823	0.820	0.821	–	–
		excitation (B)	**0.906**	**0.838**	**0.838**	**0.857**	–	–
		superv.+excit. (A)	**0.897**	**0.846**	**0.838**	0.851	–	–
		superv.+excit. (B)	**0.908**	**0.849**	0.824	**0.884**	–	–
	Stim. LSTM	supervised	**0.891**	0.831	0.829	**0.883**	–	–
		excitation	0.863	0.827	0.825	0.843	–	–
		superv.+excit.	**0.901**	**0.841**	**0.839**	**0.878**	–	–
#1 w. GloVe	No augmentation		0.861	0.834	0.832	0.860	–	8.90
	Supervised WSR modification		0.834	0.801	0.798	0.839	0.90	0.93
	Manifold learning		0.839	0.804	0.791	0.851	0.85	1.23
	Elastic pulling		**0.862**	0.821	0.823	0.856	0.92	0.73
#2	No augmentation		0.940	0.889	0.886	0.894	–	–
	Aux. OG process detection		**0.943**	**0.895**	**0.889**	**0.906**	–	–
	Stim. Attention	supervised	**0.994**	**0.893**	**0.890**	**0.907**	–	–
		excitation (A)	**0.945**	**0.900**	**0.889**	0.892	–	–
		excitation (B)	0.940	**0.897**	**0.891**	**0.906**	–	–
		superv.+excit. (A)	**0.941**	**0.898**	0.886	0.889	–	–
		superv.+excit. (B)	**0.941**	**0.891**	**0.889**	**0.906**	–	–
	Stim. LSTM	supervised	**0.944**	**0.897**	**0.896**	**0.921**	–	–
		excitation	**0.944**	**0.896**	**0.887**	0.892	–	–
		superv.+excit.	**0.945**	**0.901**	**0.899**	**0.935**	–	–

between selected variants $\Delta\mathcal{D} = \frac{1}{N}\sum_k \frac{|\mathcal{D}(v_k^i, v_k^j)^{new} - \mathcal{D}(v_k^i, v_k^j)^{old}|}{\mathcal{D}(v_k^i, v_k^j)^{old}}$ and average resulting distance $\overline{\mathcal{D}} = \frac{1}{N}\sum_k \mathcal{D}(v_k^i, v_k^j)$. Accuracy, precision, and recall are provided in the sup. materials.

5.1 Evaluations of the individual CL-knowledge integration strategies

We evaluate the different CL augmentations individually in Table 1. We also try combining the two supervised and excitation-based methods for stimulating attention and LSTM input gates. For a fairer comparison of the selective normalisations, their modulation parameters λ are approximately adjusted to provide a loosely similar $\Delta\mathcal{D}$, as reported in the sup. materials.

Base model #1 (before augmentations) obtains similarly good results using both WSRs, even though GloVe encompasses more words in a larger embedding, with resulting larger $\overline{\mathcal{D}}$. Base model #1 generally responds well to all CL-integrations (with some implementations of the selective normalisation performing better than others, as discussed next). The selective normalisation is less effective on GloVe, maybe due to a more drastic reduction of its larger initial distances. A grid search on λ may be performed in the future to investigate this behaviour. Base model #2 outperforms base model #1, which confirms XLNet's NLP SoTA status. It also responds well to augmentations based on knowledge of OG processes, with all metrics consistently improved. Thus, the selective normalisation for XLNet's WSR remains an interesting strategy to evaluate in future experiments.

Among the 3 proposed implementations of selective normalisation, only the pulling version provided an improvement, while the other two hindered OG classification in spite of a smaller reduction of distances between selected variants. For the supervised approach, this may be explained by the new loss term conflicting with the original WSR loss. For manifold learning, although the algorithm preserves pairwise distances by design (as verified in sup. materials), this does not seem enough to fully preserve the semantic representation power of the WSR. On the other hand, the more gentle

Table 2: Comparative evaluation of OG classification methods

Method	Precision	Recall	AUPR	F_1	$F_{0.5}$
Naive Bayes	0.240	**0.974**	0.727	0.385	0.283
SVM	**0.997**	0.337	0.748	0.504	0.716
Decision Tree	0.693	0.642	0.637	0.667	0.682
Random Forest	0.987	0.400	0.718	0.569	0.763
Liu et al. (2017)	0.919	0.735	0.885	0.817	0.875
BERT	0.837	0.711	0.815	0.711	0.808
Base model #1	0.867	0.794	0.867	0.829	0.851
Base model #1 + L1 Regularisation	0.880	0.759	0.857	0.815	0.853
Base model #1 + L2 Regularisation	0.896	0.783	0.890	0.835	0.871
Base model #2	0.900	0.871	0.940	0.886	0.894
Base model #2 + L1 Regularisation	0.885	0.881	0.940	0.883	0.883
Base model #2 + L2 Regularisation	0.913	0.865	0.941	0.888	0.903
Augmented model #1	0.930	0.777	0.924	0.847	0.895
Augmented model #2	0.953	0.853	**0.948**	**0.900**	**0.931**

elastic pulling could preserve the original semantic description of the WSR while introducing an implicit normalisation of the selected word variants that supports OG classification.

All integrations of knowledge on OG processes improved the performance of the models. This demonstrates that focusing the attention of the DNNs on the language associated with OG processes does help capturing subtleties of grooming language. The 3 strategies seem roughly equally helpful at focusing the DNN's attention and capturing these subtleties, and future work will explore their combinations. Improvements are more consistent for AUPR and precision (through $F_{0.5}$). This may be due to this capturing of language subtleties helping with distinguishing OG conversations from neutral but sexually-oriented ones, hence generating fewer false positives.

For both stimulation strategies (attention mechanism and LSTM input gates) combining the supervision and excitation approaches provides better results than using them individually. This suggests that these two processes support each other during optimisation. Indeed, improved DNN's attention (expressed in e_t and i_t) from excitation may assist with the supervised attention task. In addition, improved attention from supervision may also reinforce the excitation and allow it to work at its best.

5.2 OG CLASSIFICATION PERFORMANCE

The prior integration methods are combined into fully augmented models #1 and #2. All 3 algorithms for selective normalisation have same aim, thus we only retain the best performing elastic pulling. As suggested by the previous discussion on the supervision-excitation symbiosis, the different strategies and their implementations for integrating knowledge on OG processes may be complementary. Thus, we include all 3 strategies in our final augmented models, combining supervision and excitation for both stimulation strategies, and choosing excitation B over A due to its better results. For augmented model #2, only the augmentations tested individually in Table 1 are used. Comparative results on OG classification are provided in Table 2 over baselines and SoTA NLP models.

Although base model #1 does slightly worse than (Liu et al., 2017), its augmented version outperforms it by a margin. XLNet of base model #2 is the best performing of non-CL-augmented models. Its augmentation by the combined integration of CL knowledge on word variants and OG processes significantly improves its performance and produces the new SoTA.

For both base models, the combined augmentations (Table 2) add up to improvements that are superior to those of individual augmentations (Table 1). This is particularly true for augmented model #1 that accumulates all 4 augmentations, while augmented model #2 is limited to 3. Its SoTA may be further improved in the future through adding the selective normalisation. In the sup. materials, we further explore how the individual augmentations add up through their progressive additions to a simple LSTM model similar to base model #1. We observe that their respective benefits are complementary.

In order to verify that the improved results do come from a better understanding of language provided by CL knowledge, rather than merely from additional regularisation, we also compare against L1 and

Figure 2: Visualisation of detecting the *Compliance testing* OG process.

L2 regularised version of both base models. Although regularisation does improve the results, the performance gains from integrating CL knowledge are significantly superior for both models.

Visualisation – Since the augmented models make use of OG processes' recognition to capture the language associated with grooming, their auxiliary OG process detection may be used to highlight, at word level, those parts of the conversation that the model associates to OG processes. These are visualised in Fig. 2, where the estimated likelihood of the *Compliance testing* process is indicated in shades of red. The DNN focused on questions about personal situation and on invitations to talk over the phone, as indicators of compliance testing happening, in line with our general understanding of this OG process. While these elements of discussion may seem neutral enough and may not be captured by generic OG classifiers, the DNN's understanding of OG processes and of their relation to OG made it increase the OG classification score at each detection of OG process. In future work, a similar visualisation could be performed using the attention energies e_t and LSTM input gate activations i_t, to assess the better capturing of subtle language clues provided by the two other strategies for integrating knowledge on OG processes, and their effect on OG classification.

6 CONCLUSION

We have explored the integration of CL knowledge in a hybrid (data- and knowledge-driven) DNN. We considered two types of CL knowledge, namely: 1) variants of semantically equivalent words that are, or not, discriminative of OG, and which we use to perform a selective text normalisation in support of classification. Existing normalisation methods would apply to full text with no such distinction, thus failing to provide this support. 2) The identification of some OG processes and their associated language, which we use to focus the attention of the DNN on subtle language clues. We compared several integration approaches, including a new method for stimulating an LSTM's attention directly through its input gates, without the need for an external attention mechanism. For our final augmented model, we selected a gentle pulling method for selective normalisation as well as a combination of auxiliary tasks, and supervision and excitation for stimulated attention and stimulated LSTM, those benefits add up to produce the SoTA. We demonstrated the general applicability of our approaches on two architecture types of recurrent and transformer neural networks and two WSRs of different complexities. Our results show performance improvements over base and SoTA models for both architectures, while allowing for a CL based interpretation of the classification decision through visualisation of predicted OG processes and DNN's attention. While our work was applied to OG classification, we encourage the use of these methods for other language tasks where similar CL knowledge may be obtained.

While we have demonstrated the applicability of these methodologies for CL knowledge, we see the potential for other domains that utilise similar representations or model architectures. The selective text normalisation that we propose is more generally applicable to other classification tasks, and its proposed implementations are usable on other DNN that are based on a WSR. It may also be generally useful to estimate auxiliary quantities that are known to be relevant to the task and that may usefully constrain the DNN's attention and learnt features. Our two other methods for focusing the DNN's attention (i.e. stimulated attention and stimulated LSTM input gates) may be generally used to weight more some important elements of the training data.

Perspectives for OG prevention – The proposed OG classification method has been designed based on requirements from specialised law enforcement to assist in the investigation of large quantities of chat logs. Its intended usage is to facilitate triage by law enforcement, with flagged conversations being investigated more thoroughly by a human expert, helped by the proposed visualisation. Mitigation measures should be put in place, but these are outside the scope of this work.

REFERENCES

Emily Chiang and Tim Grant. Deceptive identity performance: Offender moves and multiple identities in online child abuse conversations. *Applied Linguistics*, 40(4):675–698, 2019.

Mohammad Mahdi Derakhshani, Saeed Masoudnia, Amir Hossein Shaker, Omid Mersa, Mohammad Amin Sadeghi, Mohammad Rastegari, and Babak N. Araabi. Assisted Excitation of Activations: A Learning Technique to Improve Object Detectors. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9201–9210, 2019.

Kuzman Ganchev, Jennifer Gillenwater, and Ben Taskar. Posterior regularization for structured latent variable models. *Journal of Machine Learning Research*, 11(Jul):2001–2049, 2010.

Jos Mara Gmez Hidalgo and Andrs Alfonso Díaz, Caurcel. Combining Predation Heuristics and Chat-Like Features in Sexual Predator Identification. *CLEF (Online Working Notes/Labs/Workshop*, 2012.

Zhiting Hu, Xuezhe Ma, Zhengzhong Liu, Eduard Hovy, and Eric Xing. Harnessing Deep Neural Networks with Logic Rules. In *arXiv preprint arXiv:1603.06318*, 2016.

Zhiting Hu, Zichao Yang, Ruslan Salakhutdinov, Xiaodan Liang, Lianhui Qin, Haoye Dong, and Eric Xing. Deep Generative Models with Learnable Knowledge Constraints. In *Advances in Neural Information Processing Systems*, pp. 10501–10512, 2018.

Giacomo Inches and Fabio Crestani. Overview of the International Sexual Predator Identification Competition at PAN-2012. In *CLEF 2012 Evaluation Labs and Workshop Working Notes Papers*, volume 30, 2012.

Jeremy Kawahara, Colin J. Brown, Steven P. Miller, Brian G. Booth, Vann Chau, Ruth E. Grunau, Jill G. Zwicker, and Ghassan Hamarneh. BrainNetCNN: Convolutional Neural Networks for Brain Networks; Towards Predicting Neurodevelopment. *NeuroImage*, 146:1038–1049, 2017.

Dan Liu, Ching Yee Suen, and Olga Ormandjieva. A Novel Way of Identifying Cyber Predators. In *arXiv preprint arXiv:1712.03903*, 2017.

Nuria Lorenzo-Dus, Cristina Izura, and Roco Pérez-Tattam. Understanding Grooming Discourse in Computer-mediated Environments. *Discourse, Context and Media*, 12:40–50, 2016.

Minh Thang Luong, Hieu Pham, and Christopher D Manning. Effective approaches to attention-based neural machine translation. In *Empirical Methods in Natural Language Processing*, pp. 1412–1421. Association for Computational Linguistics, 2015.

Courtney Mansfield, Ming Sun, Yuzong Liu, Ankur Gandhe, and Björn Hoffmeister. Neural text normalization with subword units. In *North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2019.

Tony McEnery and Andrew Wilson. Corpus linguistics. *The Oxford handbook of computational linguistics*, pp. 448–463, 2003.

Nikhil Muralidhar, Mohammad Raihanul Islam, and Manish Marwah. Incorporating Prior Domain Knowledge into Deep Neural Networks. *IEEE Big Data*, pp. 36–45, 2018.

Minh Nguyen and Thien Huu Nguyen. Who is Killed by Police: Introducing Supervised Attention for Hierarchical LSTMs. In *International Conference on Computational Linguistics*, pp. 2277–2287, 2018.

Adeline Paiement, Lili Tao, Massimo Camplani, Sion Hannuna, Dima Damen, and Majid Mirmehdi. Online quality assessment of human movement from skeleton data. In *British Machine Vision Conference*, pp. 153–166, 2014.

Jeffrey Pennington, Richard Socher, and Christopher D. Manning. GloVe: Global vectors for word representation. In *Empirical Methods in Natural Language Processing*, pp. 1532–1543, 2014.

Daniela Schneevogt, Emily Chiang, and Tim Grant. Do perverted justice chat logs contain examples of overt persuasion and sexual extortion? a research note responding to chiang and grant (2017, 2018). *Language and Law= Linguagem e Direito*, 5(1):97–102, 2018.

John Sinclair. *Corpus, concordance, collocation*. Oxford University Press, 1991.

Anna Vartapetiance and Lee Gillam. "Our Little Secret": pinpointing potential predators. *Security Informatics*, 3(1):3, 2014.

Esa Villatoro-Tello, Antonio Juárez-González, Hugo Jair Escalante, Manuel Montes-y Gómez, and Luis Villaseñor-Pineda. A Two-step Approach for Effective Detection of Misbehaving Users in Chats - Notebook for PAN at CLEF 2012. In *CLEF (Notebook Papers/Labs/Workshop)*, 2012.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. XLNet: Generalized Autoregressive Pretraining for Language Understanding. In *Advances in Neural Information Processing Systems*, pp. 5754–5764, 2019.

Zi Yin and Yuanyuan Shen. On the Dimensionality of Word Embedding. In *Advances in Neural Information Processing Systems*, pp. 894–905, 2018.