A STRONG ON-POLICY COMPETITOR TO PPO

ABSTRACT

As a recognized variant and improvement for Trust Region Policy Optimization (TRPO), proximal policy optimization (PPO) has been widely used with several advantages: efficient data utilization, easy implementation and good parallelism. In this paper, a first-order gradient on-policy learning algorithm called Policy Optimization with Penalized Point Probability Distance (POP3D), which is a lower bound to the square of total variance divergence is proposed as another powerful variant. The penalty item has dual effects, prohibiting policy updates from overshooting and encouraging more explorations. Carefully controlled experiments on both discrete and continuous benchmarks verify our approach is highly competitive to PPO.

1 INTRODUCTION

With the development of deep reinforcement learning, lots of impressive results have been produced in a wide range of fields such as playing Atari game Mnih et al. (2015); Hessel et al. (2018), controlling robotics Lillicrap et al. (2015), Go Silver et al. (2017), neural architecture search Tan et al. (2019); Pham et al. (2018).

The basis of a reinforcement learning algorithm is generalized policy iteration Sutton & Barto (2018), which states two essential iterative steps: policy evaluation and improvement. Among various algorithms, policy gradient is an active branch of reinforcement learning whose foundations are $Policy\ Gradient\ Theorem$ and the most classical algorithm REINFORCEMENT Sutton & Barto (2018). Since then, handfuls of policy gradient variants have been proposed, such as Deep Deterministic Policy Gradient (DDPG) Lillicrap et al. (2015), Asynchronous Advantage Actor Critic (A3C) Mnih et al. (2016), Actor Critic using Kronecker-factored Trust Region (ACKTR) Wu et al. (2017), Proximal Policy Optimization (PPO) Schulman et al. (2017).

Improving the strategy monotonically had been nontrivial before the trust region policy optimization(TRPO) was proposed Schulman et al. (2015a). Hessian-free strategy: Fisher vector product is utilized to cut down the computing burden. Specifically, Kullback–Leibler divergence(**KLD**) acts as a hard constraint in place of objective, because its corresponding coefficient is difficult to set for different problems. However, TRPO still has several drawbacks: too complicated, inefficient data usage. Quite a lot of efforts have been devoted to improving TRPO since then and the most commonly used one is PPO.

PPO can be regarded as a first-order variant of TRPO and have obvious improvements in several facets. In particular, a pessimistic clipped surrogate objective is proposed where TRPO's hard constraint is replaced by the clipped action probability ratio. In such a way, it constructs an unconstrained optimization problem so that any first-order stochastic gradient optimizer can be directly applied. Besides, it's easier to be implemented, more robust against various problems and achieves an impressive result on Atari games Brockman et al. (2016). However, the cost of data sampling is not always cheap. Haarnoja et al. (2018) design an off-policy algorithm called Soft Actor-Critic and achieves state of the art result by encouraging better exploration using maximum entropy.

In this paper, we focus on the on-policy improvement to improve PPO and answer the question: how to successfully leverage penalized optimization to solve the constrained one which is formulated by Schulman et al. (2015a).

1. It proposes a simple variant of TRPO called POP3D along with a new surrogate objective containing a point probability penalty item, which is symmetric lower bound to the square

of the total variance divergence of policy distributions. Specifically, it helps to stabilize the learning process and encourage exploration. Furthermore, it escapes from penalty item setting headache along with penalized version TRPO, where is arduous to select one fixed value for various environments.

2. It achieves state-of-the-art results among on-policy algorithms with a clear margin on 49 Atari games within 40 million frame steps based on two shared metrics. Moreover, it also achieves competitive results compared with PPO in the continuous domain. It dives into the mechanism of PPO's improvement over TRPO by the perspective of solution manifold, which also plays an important role in our method.

3. It enjoys almost all PPO's advantages such as easy implementation, fast learning ability.

We provide the code and training logs to make our work reproducible.

2 PRELIMINARY KNOWLEDGE AND RELATED WORK

2.1 POLICY GRADIENT

Agents interact with the environment and receive rewards which are used to adjust their policy in turn. At state s_t, one agent takes strategy π and transfers to a new state s_{t+1}, rewarded r_t by the environment. Maximizing discounted return (accumulated rewards) R_t is its objective. In particular, given a policy π, R_t is defined as

$$R_t = \sum_{n=0}^{\infty} (r_t + \gamma r_{t+1} + \gamma^2 r_{t+2} + ... + \gamma^n r_{t+n}). \tag{1}$$

γ is the discounted coefficient to control future rewards, which lies in the range (0, 1). Regarding a neural network with parameter θ, the policy $\pi_\theta(a|s)$ can be learned by maximizing Equation 1 using the back-propagation algorithm. Particularly, given $Q(s, a)$ which represents the agent's return in state s after taking action a, the objective function can be written as

$$\max_\theta \quad \mathbb{E}_{s,a} \log \pi_\theta(a|s) Q(s, a). \tag{2}$$

Equation 2 lays the foundation for handfuls of policy gradient based algorithms, Another variant can be deduced by using

$$A(s, a) = Q(s, a) - V(s) \tag{3}$$

to replace $Q(s, a)$ in Equation 2 equivalently, $V(s)$ can be any function so long as V depends on s but not a. In most cases, state value function is used for V, which not only helps to reduce variations but has clear physical meaning. Formally, it can be written as

$$\max_\theta \quad \mathbb{E}_{s,a} \log \pi_\theta(a|s) A(s, a). \tag{4}$$

2.2 ADVANTAGE ESTIMATE

One commonly used method for advantage calculation is one step estimation, which estimates

$$A(s_t, a) = Q(s_t, a) - V(s_t) = r_t + \gamma V(s_{t+1}) - V(s_t). \tag{5}$$

A better estimate for advantage called generalized advantage estimation is proposed in Schulman et al. (2015b), where one, two, three, up to ∞ time step estimate are combined and summarized using λ based weights, which helps to estimate more accurately. The generalized advantage estimator is defined as

$$\hat{A}_t^{GAE(\gamma,\lambda)} = \sum_{l=0}^{\infty} (\gamma\lambda)^l \delta_{t+l}^V$$

$$\delta_{t+l}^V = r_{t+l} + \gamma V(s_{t+l+1}) - V(s_{t+l}). \tag{6}$$

The parameter λ meets $0 \le \lambda \le 1$, which controls the trade-off between bias and variance.

2.3 TRUST REGION POLICY OPTIMIZATION

Schulman *et al.* propose TRPO to update the policy monotonically. In particular, its mathematical form is

$$\max_{\theta} \quad \mathbb{E}_t[\frac{\pi_\theta(a_t|s_t)}{\pi_{\theta_{old}}(a_t|s_t)}\hat{A}_t] - C\mathbb{E}_t[KL[\pi_{\theta_{old}}(\cdot|s_t), \pi_\theta(\cdot|s_t)]]$$
$$\epsilon = \max_s E_{a\sim\pi_\theta(a|s)}[A_{\pi_{\theta_{old}}}(s,a)])$$

(7)

where C is the penalty coefficient, $C = \frac{2\epsilon\gamma}{(1-\gamma)^2}$.

In practice, the policy update steps would be too small if C is valued as Equation 7. In fact, it's intractable to calculate C beforehand since it requires traversing all states to reach the maximum. Moreover, inevitable bias and variance will be introduced by estimating the advantages of old policy while training. Instead, a surrogate objective is maximized based on the KLD constraint between the old and new policy, which can be written as below,

$$\max_{\theta} \quad \mathbb{E}_t[\frac{\pi_\theta(a_t|s_t)}{\pi_{\theta_{old}}(a_t|s_t)}\hat{A}_t]$$
$$s.t. \quad \mathbb{E}_t[KL[\pi_{\theta_{old}}(\cdot|s_t), \pi_\theta(\cdot|s_t)]] \leq \delta$$

(8)

where δ is the KLD upper limitation. In addition, the conjugate gradient algorithm is applied to solve Equation 8 more efficiently. Two major problems have yet to be addressed: one is its complexity even using the conjugate gradient approach, another is compatibility with architectures that involve noise or parameter sharing tricks Schulman et al. (2017).

2.4 PROXIMAL POLICY OPTIMIZATION

To overcome the shortcomings of TRPO, PPO replaces the original constrained problem with a pessimistic clipped surrogate objective where KL constraint is implicitly imposed. The loss function can be written as

$$L^{CLIP}(\theta) = \mathbb{E}_t[\min(r_t(\theta)\hat{A}_t, clip(r_t(\theta), 1-\epsilon, 1+\epsilon)\hat{A}_t)]$$
$$r_t(\theta) = \frac{\pi_\theta(a_t|s_t)}{\pi_{\theta_{old}}(a_t|s_t)},$$

(9)

where ϵ is a hyper-parameter to control the clipping ratio. Except for the clipped PPO version, KL penalty versions including fixed and adaptive KLD. Besides, their simulation results convince that clipped PPO performs best with an obvious margin across various domains.

3 POLICY OPTIMIZATION WITH PENALIZED POINT PROBABILITY DISTANCE

Before diving into the details of POP3D, we review some drawbacks of several methods, which partly motivate us.

3.1 DISADVANTAGES OF KULLBACK-LEIBLER DIVERGENCE

TRPO Schulman et al. (2015a) induced the following inequality,

$$\eta(\pi_\theta) \leq L_{\pi_{\theta_{old}}}(\pi_\theta) + \frac{2\epsilon\gamma}{(1-\gamma)^2}\alpha^2$$
$$\alpha = D_{TV}^{\max}(\pi_{\theta_{old}}, \pi_\theta)$$
$$D_{TV}^{\max}(\pi_{\theta_{old}}, \pi_\theta) = \max_s D_{TV}(\pi_{\theta_{old}}||\pi_\theta)$$

(10)

TRPO replaces the square of total variation divergence $D_{TV}^{max}(\pi_{\theta_{old}}, \pi_\theta)$ by $D_{KL}^{\max}(\pi_{\theta_{old}}, \pi_\theta) = \max_s D_{KL}(\pi_{\theta_{old}}||\pi_\theta)$. Given a discrete distribution p and q, their total variation divergence

$D_{TV}(p||q)$ is defined by $\frac{1}{2} \sum_i |p_i - q_i|$. Obviously, D_{TV} is symmetric by definition, while KLD is asymmetric.

Formally, given state s, KLD of $\pi_{\theta_{old}}(\cdot|s)$ for $\pi_\theta(\cdot|s)$ can be written as

$$D_{KL}(\pi_{\theta_{old}}(\cdot|s)||\pi_\theta(\cdot|s)) = \sum_a \pi_{\theta_{old}}(a|s) \ln \frac{\pi_{\theta_{old}}(a|s)}{\pi_\theta(a|s)}. \tag{11}$$

Similarly, KLD in the continuous domain can be defined simply by replacing summation with integration. The consequence of KLD's asymmetry leads to a non-negligible difference of whether choose $D_{KL}(\pi_{\theta_{old}}||\pi_\theta)$ or $D_{KL}(\pi_\theta||\pi_{\theta_{old}})$. Sometimes, those two choices result in quite different solutions. Robert compared the forward and reverse KL on a distribution, one solution matches only one of the modes, and another covers both modes Murphy (2012). Therefore, KLD is not an ideal bound or approximation for the expected discounted cost.

3.2 DISCUSSION ABOUT PESSIMISTIC PROXIMAL POLICY

In fact, PPO is called pessimistic proximal policy optimization[1] in the meaning of its objective construction style. Without loss of generality, supposing $A_t > 0$ for given state s_t and action a_t, and the optimal choice is $a_t^\star$. When $a_t = a_t^\star$, a good update policy is to increase the probability of action to a relatively high value $a_t^\star$ by adjusting θ. However, the clipped item $clip(r_t(\theta), 1 - \epsilon, 1 + \epsilon)\hat{A}_t$ will fully contribute to the loss function by the minimum operation, which ignores further reward by zero gradients even though it's the optimal action. Other situation with $A_t < 0$ can be analyzed in the same manner.

However, if the pessimistic limitation is removed, PPO's performance decreases dramatically Schulman et al. (2017), which is again confirmed by our preliminary experiments. In a word, the pessimistic mechanism plays a very critical role for PPO by a relatively weak preference for good action decision for a given state, which in turn affects learning efficiency.

3.3 RESTRICTED SOLUTION MANIFOLD

To be simple, we don't take the model identifiability issues along with deep neural network into account here because they don't affect the following discussion much LeCun et al. (2015). Suppose $\pi_{\theta\star}$ is the optimal solution for a given environment, in most cases, more than one parameter set for θ can generate the ideal policy, especially when $\pi_{\theta\star}$ is learned by a deep neural network. In other words, the relationship between θ and $\pi_{\theta\star}$ is many to one. On the other hand, when agents interact with the environment using policy represented by neural networks, the action is taken approximately strongly corrected with the highest probability value. Although some strategies of enhancing exploration are applied, they don't affect the policy much in the meaning of expectation.

Taking the Atari-Pong game for example, when an agent sees a Pong ball is coming nearly, its optimal policy is moving the racket to the right position. The probability of this action is a relatively high value such as 0.95 and it's near to impossible that this value is 1.0 since it's produced by a softmax operation on the several discrete actions. In fact, we hardly obtained the optimal solution accurately, instead, our goal is a good enough answer. Namely, θ_1 outputting a probability 0.95 and θ_2 with 0.9 for the right action are both good answers. During the training process, these similar events occur frequently.

Using a penalty such as KLD cannot handle it effectively, because it involves all of the actions' probabilities. Moreover, it doesn't stop penalizing unless two distributions become exactly indifferent or the advantage item is large enough to compensate for the KLD cost. Therefore, even if θ outputs θ_{old} the same high probability for the right action, it's still penalized owing to probabilities mismatch for other uncritical actions. Indeed, when a person is asked to make the choice, corresponding action will be taken only if the probability is above a threshold. From the perspective of the manifold, if the optimal parameters constitute a solution manifold. The KLD penalty will act until θ exactly locates in the solution if possible. However, if the agent concentrates only on critical actions like a human, it's much easier to approach the manifold, which in fact, expands the solution manifold

---

[1]The word "pessimistic" is used by the PPO paper.

at least one dimension such as curves to surfaces and surfaces to spheres at best. Besides, since mini-batch is a commonly used trick for training neural networks, removing this unexpected penalty helps to decrease penalty noises, which are reflected by the corresponding gradient.

3.4 EXPLORATION

One shared highlight in reinforcement learning is the balance between exploitation and exploration. For a policy-gradient algorithm, entropy is added in the total loss to encourage exploration in most case. When included in loss function, KLD penalizes the old and new policy probability mismatch for all possible actions as Equation 11. This strict punishment for every action's probability mismatch, which discourages exploration.

3.5 POINT PROBABILITY DISTANCE

To overcome the above-mentioned shortcomings, we propose a surrogate objective with the point probability distance penalty, which is symmetric and more optimistic than PPO. In the discrete domain, when the agent takes action a, the point probability distance between $\pi_{\theta_{old}}(\cdot|s)$ and $\pi_\theta(\cdot|s)$ is defined by

$$D_{pp}(\pi_{\theta_{old}}(\cdot|s), \pi_\theta(\cdot|s)) = (\pi_{\theta_{old}}(a|s) - \pi_\theta(a|s))^2. \tag{12}$$

Attention should be paid to the penalty definition item, the distance is measured by the point probability, which emphasizes its mismatch for the **sampled** actions for a state. Undoubtedly, D_{pp} is symmetry by definition. Furthermore, it can be proved that D_{pp} is indeed a lower bound for the total variance divergence D_{TV}. As a special case, it can be easily proved that for binary distribution, $D_{TV}^2(p||q) = D_{pp}(p||q)$.

Theorem 3.1. *For two discrete probability distributions p and q with K values, then $D_{TV}^2(p||q) \geq D_{pp}(p||q)$ holds.*

Proof. Let $a = p_l, b = q_l$ for any l, and suppose $a \geq b$ without loss of generality. So,

$$
\begin{aligned}
D_{TV}^2(p||q) &= (\frac{1}{2}\sum_{i=1}^{K}|p_i - q_i|)^2 = (\frac{1}{2}\sum_{i=1,i\neq l}^{K}|p_i - q_i| + \frac{1}{2}|p_l - q_l|)^2 \\
&\geq (\frac{1}{2}|\sum_{i=1,i\neq l}^{K} p_i - q_i| + \frac{1}{2}(a-b))^2 = (\frac{1}{2}|1 - a - (1-b)| + \frac{1}{2}(a-b))^2 \\
&= (\frac{1}{2}(a-b) + \frac{1}{2}(a-b))^2 = D_{pp}(p||q)
\end{aligned}
$$

$\square$

Since $0 \leq \pi_\theta(a|s) \leq 1$ holds for discrete action space, D_{pp} has a lower and upper boundary: $0 \leq D_{pp} \leq 1$. Moreover, D_{pp} is less sensitive to action space dimension than KLD, which has a similar effect as PPO's clipped ratio to increase robustness and enhance stability. Equation 12 stays unchanged for the continuous domain, and the only difference is $\pi_\theta(a|s)$ represents point probability density instead of probability.

3.6 POP3D

After we have defined the point probability distance, we use a new surrogate objective for POP3D, which can be written as

$$\max_\theta \quad \mathbb{E}_t[\frac{\pi_\theta(a_t|s_t)}{\pi_{\theta_{old}}(a_t|s_t)}\hat{A}_t - \beta D_{pp}(\pi_{\theta_{old}}(\cdot|s), \pi_\theta(\cdot|s))], \tag{13}$$

where β is the penalized coefficient. These combined advantages lead to considerable performance improvement, which escapes from the dilemma of choosing preferable penalty coefficient. Besides, we use generalized advantage estimates to calculate $\hat{A}_t$. Algorithm 1 shows the complete iteration process of POP3D. Moreover, it possesses the same computing cost and data efficiency as PPO.

Algorithm 1 POP3D

1: **Input:** max iterations L , actors N, epochs K
2: **for** $iteration = 1$ **to** L **do**
3:    **for** $actor = 1$ **to** N **do**
4:       Run policy $\pi_{\theta_{old}}$ for T time steps
5:       Compute advantage estimations $\hat{A}_1, ..., \hat{A}_T$
6:    **end for**
7:    **for** $epoch = 1$ **to** K **do**
8:       Optimized loss objective wrt θ with mini-batch size $M \leq NT$, then update $\theta_{old} \leftarrow \theta$.
9:    **end for**
10: **end for**

3.7 RELATIONSHIP WITH PPO

To conclude this section, we take some time to see why PPO works by taking the above viewpoints into account. When we pour more attention to Equation 9, the ratio $r_t(\theta)$ only involves the probability for given action a, which is chosen by policy π. In other words, all other actions' probabilities except a are not activated, which no longer contribute to back-propagation and allow probability mismatch. Obviously, this procedure behaves similarly as POP3D, which expands the restricted solution manifold. Above all, POP3D is designed to conform with the regulations for overcoming above mentioned problems, and in the next section experiments from commonly used benchmarks will evaluate its performance.

4 EXPERIMENTS

4.1 CONTROLLED EXPERIMENTS SETUP

OpenAI Gym is a well-known simulation environment to test and evaluate various reinforcement algorithms, which is composed of both discrete (Atari) and continuous (Mujoco) domains Brockman et al. (2016). Most of recent deep reinforcement learning methods such as DQN variants Van Hasselt et al. (2016); Wang et al. (2016); Schaul et al. (2015); Bellemare et al. (2017); Hessel et al. (2018), A3C, ACKTR, PPO are evaluated using only one set of hyper-parameters[2]. Therefore, we evaluate POP3D's performance on 49 Atari games(v4, discrete action space) and 7 Mujoco (v2, continuous).

Since PPO is a distinguished RL algorithm which defeats various methods such as A3C, A2C ACKTR, we focus on a detailed quantitative comparison with fine-tuned PPO. And we don't consider large scale distributed algorithms Apex-DQN Horgan et al. (2018) and IMPALA Espeholt et al. (2018), because we concentrate on comparable and fair evaluation, while the latter is designed to apply with large scale parallelism. Nevertheless, some orthogonal improvements from those methods have the potentials to improve our method further. Furthermore, we include TRPO to acts as a baseline method. Engstrom et al. (2020) carefully study the underlying factor that helps PPO outperform TPRO. To avoid unfair comparsions, we carefully control the setting.s In addition, quantitative comparisons between KLD and point probability penalty helps to convince the critical role of the latter, where the former strategy is named fixed KLD in Schulman et al. (2017) and can act as another good baseline in this context, named by **BASELINE** below.

In particular, we retrained one agent for each game with fine-tuned hyper-parameters[3]. To avoid the problems of reproduction about reinforcement algorithms mentioned in Henderson et al. (2018), we take the following measures:

- Use the same training steps and make use of the same amount of game frames(40M for Atari game and 10M for Mujoco).

---

[2]DQN variants are evaluated in Atari environment since they are designed to solve problems about discrete action space. However, policy gradient based algorithms can handle both continuous and discrete problems.

[3] We use OpenAI's PPO and TRPO implementation, which provides a good baseline for various reinforcement learning algorithms: `https://github.com/openai/baselines.git`.

- Use the same neural network structures, which is CNN model with one action head and one value head for Atari game, and fully-connected model with one value head and one action head which produces the mean and standard deviation of diagonal Gaussian distribution as PPO.
- Initialize parameters using the same strategy as PPO.
- Keep Gym wrappers from Deepmind such as reward clipping and frame stacking unchanged for Atari domain, and enable 30 no-ops at the beginning of each episode.
- Use Adam optimizer Kingma & Ba (2014) and decrease α linearly from 1 to 0 for Atari domain as PPO.

To facilitate further comparisons with other approaches, we release the seeds and detailed results[4](across the entire training process for different trials). In addition, we randomly select three seeds from {0, 10, 100, 1000, 10000} for two domains, {10,100,1000} for Atari and {0,10,100} for Mujoco in order to decrease unfavorable subjective bias stated in Henderson et al. (2018).

4.2 Evaluation Metrics

PPO utilizes two score metrics for evaluating agents performance using various RL algorithms. One is the mean score of last 100 episodes $Score_{100}$, which measures how high a strategy can hit eventually. Another is the average score across all episodes $Score_{all}$, which evaluates how fast an agent learns. In this paper, we conform to this routine and calculate individual metric by averaging three seeds in the same way.

4.3 Discrete Domain Comparisons

Hyper-parameters We search hyper-parameter four times for the penalty coefficient β based on four Atari games while keeping other hyper-parameters unchanged as PPO and fix $\beta = 5.0$ to train all Atari games. For BASELINE, we also search hyper-parameter four times on penalty coefficient β and choose $\beta = 10.0$. To save space, detailed hyper-parameter setting can be found in Table 6 and 7.

This process is not beneficial for POP3D owing to missing optimization for all hyper-parameters. There are two reasons to make this choice. On the one hand, it's the simplest way to make a relatively fair comparison group such as keeping the same iterations and epochs within one loop to our knowledge. On the other hand, this process imposes low search requirements for time and resource. That's to say, we can draw a conclusion that our method is at least competitive to PPO if it performs better on benchmarks.

Comparisons The final score of each game is averaged by three different seeds and the highest is in bold. As Table 2 shows, POP3D outperforms 32 across 49 Atari games in view of the final score, followed by PPO with 11, BASELINE with 5 and TRPO with 1. Interestingly, for games that POP3D score highest, BASELINE score worse than PPO more often than the other way round, which means that POP3D is not just an approximate version of BASELINE.

For another metric, POP3D wins 20 out of 49 Atari games which matches PPO with 18, followed by BASELINE with 6, and last ranked by TRPO with 5. If we measure the stability of an algorithm by the score variance of different trials, POP3D scores high with good stability across various seeds. And PPO behaves worse in Game Kangaroo and UpNDown. Interestingly, BASELINE shows a large variance for different seeds for several games such as BattleZone, Freeway, Pitfall and Seaquest. POP3D reveals its better capacity to score high and similar fast learning ability in this domain. The detailed metric for each game is listed in Table 1 and 4.

4.4 Continuous Domain Comparisons

In this section, we focus on comparisons between POP3D and PPO in Mujoco domain.

Hyper-parameters For PPO, we use the same hyper-parameter configuration as Schulman et al. (2017). Regarding POP3D, we search on two games three times and select 5.0 as the penalty

---

[4]Experiment results can be downloaded from `https://drive.google.com/file/d/1c79TqWn74mHXhLjoTWaBKfKaQOsfD2hg/view?usp=sharing`.

Table 1: Mean final scores (last 100 episodes) of PPO, POP3D, BASELINE and TRPO on Atari games after 40M frames. The results are averaged on three trials.

game	POP3D	PPO	BASELINE	TPRO
Alien	**1510.80**	1431.17	1311.23	1110.40
Amidar	729.15	**790.75**	655.10	200.56
Assault	**5400.13**	4438.82	1846.75	1363.46
Asterix	**4310.67**	3483.17	3657.67	2651.33
Asteroids	**2488.10**	1605.33	1615.37	2205.70
Atlantis	**2193605.67**	2140536.33	1515993.33	1419104.67
BankHeist	**1212.23**	1206.67	1124.43	1125.17
BattleZone	**15466.67**	14766.67	14690.00	15123.33
BeamRider	4549.00	2624.19	**6898.09**	5073.75
Bowling	38.99	**47.27**	30.48	31.24
Boxing	**97.23**	93.70	65.33	50.07
Breakout	**458.41**	281.93	67.70	40.65
Centipede	3315.44	**3565.18**	3393.93	3353.14
Chopper-Command	**6308.33**	4872.67	2676.00	2286.67
CrazyClimber	**120247.33**	105940.00	98219.67	87522.33
DemonAttack	**61147.33**	26740.57	57476.65	21525.08
DoubleDunk	**-7.89**	-11.22	-8.61	-10.04
Enduro	459.85	**698.46**	518.41	365.95
FishingDerby	**28.99**	17.72	-64.27	-69.64
Freeway	**21.21**	21.11	18.37	20.89
Frostbite	**316.87**	280.30	280.30	291.77
Gopher	**6207.00**	1791.00	940.87	938.27
Gravitar	557.17	**753.50**	449.00	495.17
IceHockey	-4.12	-4.83	**-3.61**	-4.61
Jamesbond	527.17	488.17	685.17	**901.67**
Kangaroo	3891.67	**6845.00**	1850.00	1214.67
Krull	7715.68	**8329.08**	7204.95	4881.65
KungFuMaster	**33728.00**	29958.67	29843.67	26808.00
Montezuma-Revenge	0.00	**10.67**	0.67	0.00
MsPacman	1683.87	**1981.50**	1170.70	1133.57
NameThisGame	**6065.63**	5397.47	5672.60	5604.10
Pitfall	**0.00**	-2.32	-17.26	-43.60
Pong	20.50	**20.80**	20.79	19.63
PrivateEye	79.67	36.50	**99.67**	99.33
Qbert	**15396.67**	14556.83	4114.00	3781.58
Riverraid	**8052.23**	7360.40	7722.00	6773.67
RoadRunner	**44679.67**	36289.33	43626.33	24061.33
Robotank	4.60	14.15	**24.60**	24.18
Seaquest	**1807.47**	1470.60	1501.47	926.40
SpaceInvaders	**1216.15**	944.63	814.53	634.07
StarGunner	**48984.00**	33862.00	47738.00	33442.67
Tennis	**-8.32**	-13.74	-19.13	-18.40
TimePilot	3770.33	5321.33	**6278.33**	5701.00
Tutankham	**241.21**	177.58	135.80	136.21
UpNDown	**242701.51**	153160.66	11815.87	10949.53
Venture	**36.33**	0.00	4.00	0.00
VideoPinball	**37780.70**	31577.24	21438.64	25095.20
WizardOfWor	4704.00	**4886.67**	3533.67	3103.00
Zaxxon	**9472.00**	5728.67	1179.67	4796.67

Table 2: **Left** : The number of games "won" by each algorithm for Atari games. **Right**: The number of games won by each algorithm for Mujoco games. Each experiment is averaged across three seeds.

Metric	PPO	POP3D	BASELINE	TRPO	Metric	PPO	POP3D
$Score_{100}$	11	**32**	5	1	$Score_{100}$	1	**6**
$Score_{all}$	18	**20**	6	5	$Score_{all}$	**4**	3

Table 3: Mean final scores (last 100 episodes) of PPO ,POP3D on Mujoco games after 10M frames. The results are averaged by three trials.

game	PPO	POP3D
HalfCheetah	2726.03	**3184.54**
Hopper	**2027.21**	1452.09
InvertedDoublePendulum	4455.03	**4907.64**
InvertedPendulum	544.02	**741.94**
Reacher	-5.00	**-4.29**
Swimmer	111.88	**112.08**
Walker2d	1112.25	**3966.01**

coefficient. More details about hyper-parameters for PPO and POP3D are listed in Table 8. Unlike the Atari domain, we we utilize the constant learning rate strategy as Schulman et al. (2017) in the continuous domain instead of the linear decrease strategy.

Comparison Results The scores are also averaged on three trials and summarized in Table 2. POP3D occupies 6 out of 7 games on $Score_{100}$. Evaluation metrics of both across different games are illustrated in Table 3 and 5.

In summary, both metrics indicates that POP3D is competitive to PPO in the continuous domain.

5 CONCLUSION

In this paper, we introduce a new reinforcement learning algorithm called POP3D (Policy Optimization with Penalized Point Probability Distance), which acts as a TRPO variant like PPO. Compared with KLD that is an upper bound for the square of total variance divergence between two distributions, the penalized point probability distance is a symmetric lower bound. Besides, it equivalently expands the optimal solution manifold effectively while encouraging exploration, which is a similar mechanism implicitly possessed by PPO. The proposed method not only possesses several critical improvements from PPO but outperforms with a clear margin on 49 Atari games from the respective of final scores and meets PPO's match as for fast learning ability.

More interestingly, it not only suffers less from the penalty item setting headache along with TRPO, where is arduous to select one fixed value for various environments, but outperforms fixed KLD baseline from PPO. In summary, POP3D is highly competitive and an alternative to PPO.

REFERENCES

Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. *arXiv preprint arXiv:1707.06887*, 2017.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Firdaus Janoos, Larry Rudolph, and Aleksander Madry. Implementation matters in deep rl: A case study on ppo and trpo. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=r1etN1rtPB.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Volodymir Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. *arXiv preprint arXiv:1802.01561*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pp. 1861–1870, 2018.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Dan Horgan, John Quan, David Budden, Gabriel Barth-Maron, Matteo Hessel, Hado van Hasselt, and David Silver. Distributed prioritized experience replay. In *International Conference on Learning Representations*, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

Kevin P Murphy. *Machine learning: a probabilistic perspective*. MIT press, 2012.

Hieu Pham, Melody Guan, Barret Zoph, Quoc Le, and Jeff Dean. Efficient neural architecture search via parameters sharing. In *International Conference on Machine Learning*, pp. 4095–4104, 2018.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*, 2015.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pp. 1889–1897, 2015a.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015b.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2820–2828, 2019.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Thirtieth AAAI conference on artificial intelligence*, 2016.

Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Hasselt, Marc Lanctot, and Nando Freitas. Dueling network architectures for deep reinforcement learning. In *International conference on machine learning*, pp. 1995–2003, 2016.

Yuhuai Wu, Elman Mansimov, Roger B Grosse, Shun Liao, and Jimmy Ba. Scalable trust-region method for deep reinforcement learning using kronecker-factored approximation. In *Advances in neural information processing systems*, pp. 5279–5288, 2017.

A SCORE TABLES AND CURVES

Mean scores of various methods for Atari domain are listed in Table 4.

B EXPERIMENTS

B.1 HYPER-PARAMETERS

B.1.1 ATARI

PPO's and POP3D's hyper-parameters for Mujoco games are respectively listed in Table 6.

B.1.2 MUJOCO

PPO's and POP3D's hyper-parameters for Mujoco games are respectively listed in Table 8.

Table 4: All episodes mean scores of PPO, POP3D, BASELINE and TRPO on Atari games after 40M frames. The results are averaged by three trials.

game	POP3D	PPO BASELINE		TRPO
Alien	**1147.29**	1115.94	851.13	841.08
Amidar	299.55	**413.46**	295.91	169.12
Assault	2139.15	**2168.93**	1159.50	971.78
Asterix	2004.43	**2102.10**	1884.68	1342.83
Asteroids	1652.48	1470.46	1477.71	**1760.73**
Atlantis	488134.03	**596807.27**	192798.74	174394.94
BankHeist	662.26	643.94	**859.25**	831.95
BattleZone	11131.44	9387.77	11674.30	**12918.39**
BeamRider	1965.27	1460.59	**3321.25**	2431.63
Bowling	37.97	**39.41**	33.90	30.99
Boxing	**83.12**	78.61	27.92	23.07
Breakout	**143.60**	124.98	29.99	26.56
Centipede	3056.81	**3344.63**	3042.48	3142.22
Chopper-Command	**3269.47**	3106.14	1780.38	1595.82
CrazyClimber	**97257.52**	90169.60	69258.31	63189.78
DemonAttack	7611.27	7180.43	**9814.42**	6204.68
DoubleDunk	**-13.70**	-15.45	-15.93	-14.57
Enduro	107.84	**321.20**	92.59	140.67
FishingDerby	**-21.00**	-27.51	-81.90	-81.97
Freeway	**17.76**	15.87	15.93	17.33
Frostbite	**276.47**	267.73	270.42	270.57
Gopher	**1556.29**	1196.20	900.74	875.93
Gravitar	413.20	**509.81**	342.74	317.86
IceHockey	-4.67	-5.50	**-4.61**	-5.21
Jamesbond	358.54	394.45	380.91	**519.01**
Kangaroo	1614.63	**2199.74**	937.98	566.85
Krull	6538.16	**7195.24**	4760.66	3861.87
KungFuMaster	23253.96	**23283.31**	19637.58	18293.12
Montezuma-Revenge	0.14	**0.74**	0.22	0.12
MsPacman	1214.09	**1482.77**	860.63	864.84
NameThisGame	**5353.14**	5199.37	4562.32	4504.67
Pitfall	**-2.41**	-5.81	-31.27	-33.93
Pong	**13.24**	12.83	7.20	-2.91
PrivateEye	87.37	52.76	56.70	**98.79**
Qbert	5852.10	**6744.13**	1760.92	1679.03
Riverraid	5260.89	**5487.17**	5220.64	4549.22
RoadRunner	**25456.31**	24688.07	20385.91	16269.40
Robotank	3.08	8.65	13.89	**14.57**
Seaquest	**1487.84**	1120.15	1112.51	848.47
SpaceInvaders	**693.26**	632.17	552.50	483.48
StarGunner	14734.11	13643.80	**16288.35**	13341.23
Tennis	**-19.86**	-21.80	-21.84	-21.04
TimePilot	3396.61	4410.87	**4718.46**	4544.68
Tutankham	**179.96**	152.72	103.95	109.18
UpNDown	38728.48	**43208.99**	5430.22	7085.02
Venture	**15.89**	14.66	0.57	0.03
VideoPinball	27346.44	**27549.55**	23998.09	23705.39
WizardOfWor	2340.60	**2743.40**	2409.94	2045.17
Zaxxon	**3739.56**	1813.90	256.78	1521.28

Table 5: All episodes mean scores of PPO ,POP3D on Mujoco games after 10M frames. The results are averaged by three trials.

game	PPO	POP3D
HalfCheetah	**3250.22**	2373.30
Hopper	**1767.14**	1257.72
InvertedDoublePendulum	**3684.92**	2561.77
InvertedPendulum	531.77	**552.98**
Reacher	**-5.94**	-8.05
Swimmer	94.01	**108.27**
Walker2d	1770.37	**2439.54**

Table 6: **Left**: PPO's hyper-parameters for Atari games. **Right**:POP3D's hyper-parameters for Atari games.

Hyper-parameter	Value	Hyper-parameter	Value
Horizon (T)	128	Horizon (T)	128
Adam step-size	$2.5 \times 10^{-4} \times \alpha$	Adam step-size	$2.5 \times 10^{-4} \times \alpha$
Num epochs	3	Num epochs	3
Mini-batch size	32×8	Mini-batch size	32×8
Discount (γ)	0.99	Discount (γ)	0.99
GAE parameter (λ)	0.95	GAE parameter (λ)	0.95
Number of actors	8	Number of actors	8
Clipping parameter	$0.1 \times \alpha$	VF coeff.	1
VF coeff.	1	Entropy coeff.	0.01
Entropy coeff.	0.01	KL penalty coeff.	5.0

Table 7: BASELINE's hyper-parameters for Atari games.

Hyper-parameter	Value
Horizon (T)	128
Adam step-size	$2.5 \times 10^{-4} \times \alpha$
Num epochs	3
Mini-batch size	32×8
Discount (γ)	0.99
GAE parameter (λ)	0.95
Number of actors	8
VF coeff.	1
Entropy coeff.	0.01
KL penalty coeff.	10.0

Table 8: **Left**: PPO's hyper-parameters for Mujoco games. **Right**:POP3D's hyper-parameters for Mujoco games.

Hyper-parameter	Value	Hyper-parameter	Value
Horizon (T)	2048	Horizon (T)	2048
Adam step-size	3×10^{-4}	Adam step-size	3×10^{-4}
Num epochs	10	Num epochs	10
Mini-batch size	64	Mini-batch size	64
Discount (γ)	0.99	Discount (γ)	0.99
GAE parameter (λ)	0.95	GAE parameter (λ)	0.95
Clipping parameter	0.2	KL penalty coeff.	5.0