CROSS-MODAL DOMAIN ADAPTATION FOR REINFORCEMENT LEARNING

ABSTRACT

Domain adaptation is a promising direction for deploying RL agents in real-world applications, where vision-based robotics tasks constitute an important part. Current methods that train polices on simulated images not only require a delicately crafted simulator, but also add extra burdens to the training process. In this paper, we propose a method that can learn a mapping from high-dimensional images to low-level simulator states, allowing agents trained on the source domain of state input to transfer well to the target domain of image input. By fully leveraging the sequential information in the trajectories and incorporating the policy to guide the training process, our method overcomes the intrinsic ill-posedness in cross-modal domain adaptation when structural constraints from the same modality are unavailable. Experiments on MuJoCo environments show that the policy, once combined with the mapping function, can be deployed directly in the target domain with only a small performance gap, while current methods designed for same-modal domain adaptation fail on this problem.

1 INTRODUCTION

Deep Reinforcement Learning (DRL) for vision-based robotic-control tasks has achieved remarkable success in recent years (Francis et al., 2020; Zhang et al., 2019; Zeng et al., 2018; Riedmiller et al., 2018; Levine et al., 2018). However, current RL algorithms necessitate a substantial number of interactions with the environment, which is costly both in time and money on real robots. An appealing alternative is to train policies in simulators, then transfer these policies onto real-world systems (Rao et al., 2020; James et al., 2019; Yan et al., 2017).

Due to inevitable differences between simulators and the real world, which is also known as the "reality gap" (Jakobi et al., 1995), applying policies trained in one domain directly to another almost surely fail, especially in visual-input tasks, due to the poor generalization of RL polices (Cobbe et al., 2019). Domain adaptation is a common way to improve transferability by mapping inputs from two domains to an aligned distribution. Although distribution alignment is difficult with limited data, many recent works have adopted unsupervised visual domain adaptation (Hoffman et al., 2018; Ganin et al., 2017; Yi et al., 2017; Kim et al., 2017) to learn the mapping function without a ground-truth pairing. These adaptation methods exploit structural constraints (Fu et al., 2019) in two same-modal domains (i.e. learned on simulated **images** and deployed on real **images**) to overcome the intrinsic ill-posedness of distribution matching as shown in Fig. 1(a) — mapping an instance in the target domain to anything of a similar probability in the source domain is "reasonable" if we only consider distribution matching.

However, training on simulated images introduces unwanted costs and difficulties, which are ignored in current works. First, a rendering engine needs more human engineering and runs much slower (can be up to 20x slower according to Xia et al. (2018)) than a pure rigid body simulator, which adds considerable cost to the overall process. Second, using RL methods to train a policy with image inputs is usually harder than training with state inputs (Kaiser et al., 2020; Tenenbaum, 2018), resulting in a sub-optimal simulation policy. An ideal solution to avoid such problems is to train policies with simulated states and adapt the learned polices to real-world images. However, all the structural constraints based on the modality consistency can not be used and the distribution alignment task by learning a mapping function becomes hard to solve.

(a) Mapping without Sequential Structure   (b) Mapping with Sequential Structure

Figure 1: Illustration of mapping functions with and without sequential structure from the target domain (left) to the source domain (right). Shaded regions denote data distributions, where the darker the color, the higher the probability. In Fig. 1(a), both s_t and s'_t are "realisic" source domain instances, but only s_t is correct. Since they are of similar probabilities, distribution matching may map o_t to any of them. In RL, the policy may output unreliable actions when taking these incorrectly mapped states as inputs. In Fig. 1(b), a sequential structure can help rule out the wrong mapping based on trajectory contexts.

In this paper, we propose Cross-mOdal Domain Adaptation with Sequential structure (CODAS) that learns a mapping function from images in the target domain (real world) to states in the source domain (simulation). The policy trained in the simulator can be deployed in the real world directly with the help of the learned mapping function. Specifically, based on the sequential nature of reinforcement learning problems, we formulate the cross-domain adaptation problem as a sequential variational inference problem and derive a series of solvable optimization objectives in CODAS. It is worth noting that our work is different from recent works that learn state embeddings from image inputs, which map images to an arbitrary subspace in a low-dimensional vector space. In CODAS, we embed the image space into a vector space with clear meanings (defined in the state-based simulator), which improves the interpretability of the policy when deployed in the real world.

We evaluate our method on 6 MuJoCo (Todorov et al., 2012) environments provided in OpenAI Gym (Brockman et al., 2016), where we treat states/rendered images as the source/target domain, respectively. We do the experiments in the scenario where only offline real data are available. Experiment results show that the mapping function learned by our method can help transfer the policy to real-world images with a small performance degradation. Previous methods that use unaligned Generative Adversarial Networks (GANs) suffer from a severe performance degradation on this cross-modal transfer problem.

2 RELATED WORK

To our best knowledge, this work is the first to address cross-modal domain adaptation in RL setting. We will discuss two research areas closely related to this topic, which are, (1) unsupervised visual domain adaptation in RL and (2) image-input representation learning in RL.

Unsupervised visual domain adaptation aims to map the source domain and the target domain to an aligned distribution without pairing the data. Prior methods fall into two major categories: feature-level adaptation, where domain-invariant features are learnt (Gopalan et al., 2011; Caseiro et al., 2015; Long et al., 2015; Ganin et al., 2017), and pixel-level adaptation, where pixels from a source image used to generate an image that looks like one from the target domain (Bousmalis et al., 2017; Yoo et al., 2016; Taigman et al., 2017; Hoffman et al., 2018).

Pixel-level adaptation is challenging when data from two domains are unpaired. Prior works tackle this problem by using GANs (Goodfellow et al., 2014) conditioned on simulated images to generate realistic images. Gamrian & Goldberg (2019) transfers policies from Atari Games (Bellemare et al., 2013) to modified variants by training a GAN to map images from the target domain to the source domain. GraspGAN (Bousmalis et al., 2018) addresses domain adaptation in robotic grasping by having the GAN reproduce the segmentation mask for the simulated image as an auxiliary task, including the robot arm, objects, and the bin. RCAN (James et al., 2019) adopts ideas from domain randomization by learning a mapping of images from randomized simulations to a canonical simulation and treating the real world just as one of the random simulations. RL-CycleGAN (Rao

et al., 2020) unifies the learning of a CycleGAN (Zhu et al., 2017) and an RL policy, claiming better performance by learning features that are most crucial to the Q-function in RL.

Image-to-image domain adaptation can somewhat bypass the ill-posedness for distribution matching (See Fig. 1(a)) since it often enjoys an implicit advantage that images differ locally, e.g. in color, textile, lighting, but resembles globally between two domains, while images and states differ essentially. Some works impose extra structural constraints (e.g. segmentation, geometry) (Fu et al., 2019; Bousmalis et al., 2018), but such tricks fail in image-to-state domain adaptation either. In this work, we force the mapped states to follow transition consistency by using a recurrent structure (See Fig. 1(b)) and to be able to recover the pre-learned policy. We also employ a stochastic mapping function with the help of a variational encoder that is more robust to real-world data noise.

Representation learning aims to transform high-dimensional data into lower-dimensional vector representations, which suit RL better. It is widely accepted that learning policies from states (embeddings) is significantly more sample-efficient than learning from pixels, both empirically (Kaiser et al., 2020; Tenenbaum, 2018; Tassa et al., 2018) and theoretically (Jin et al., 2020).

Sequential auto-encoder is a common network structure to learn state representations by minimizing reconstruction loss. Early works on DRL from images (Ha & Schmidhuber, 2018; Lange et al., 2012; Lange & Riedmiller, 2010) use a two-step learning process where an auto-encoder is first trained to learn a low-dimensional representation, and subsequently a policy or model is learned based on this representation. Later works on model-based RL improve representation learning by jointly training the encoder and the dynamics model end-to-end (Watter et al., 2015) – this has been proved effective in learning useful task-oriented representations. PlaNet (Hafner et al., 2019) learns a hybrid of stochastic and deterministic latent state models using a reconstruction loss. Solar (Zhang et al., 2019) combines probabilistic graphic models with a simple network structure to fit local linear transitions. Some recent works adopt advancements in unsupervised representation learning. CURL (Laskin et al., 2020b) utilizes contrastive learning methods to capture essential information in an image that distinguishes from others, though later works (Laskin et al., 2020a; Kostrikov et al., 2020) point out that data augmentation may play the major role here.

Our work utilizes a sequential variational encoder structure to capture sequential information from trajectories. The main difference between our work and representation learning is whether the state space is predefined. We add extra supervised information to guide the training of the mapping by minimizing the distance between the distributions of the mapped states and the original states, and by enforcing the policy to recover the actions from the mapped states. As a result, we successfully learn states that match the ground-truth simulator states well. The mapped states can be directly fed into the pre-trained policy network.

3 CROSS-MODAL DOMAIN ADAPTATION WITH SEQUENTIAL STRUCTURE

Our work follows the problem setting similar to previous methods that tackle visual domain adaptation problems in RL. We have a policy π pre-trained in the source domain (state) and a dataset pre-collected in the target domain (image). The task is to learn a mapping q_ϕ from images to states. In the deployment, agents interact with a new policy $\tilde{\pi}(o) = (\pi \circ q_\phi)(o)$, where $\circ$ denotes function composition. During the training of the mapping function, only the source domain is accessible.

This section is organized as follows. Sec. 3.1 formulates the cross-modal domain adaptation as a variational inference problem. Sec. 3.2 decomposes the variational inference problem into several feasible optimization objectives. Sec. 3.3 proposes a residual network structure to handle the complex long-horizon training of the sequential structure.

3.1 DOMAIN ADAPTATION AS VARIATIONAL INFERENCE

The goal of domain adaptation is to find a mapping from the target domain to the source domain, which is images to states in our case. We first formulate the generation process of the real world and simulation and the connection between them, as illustrated in Fig. 2. The initial state follows distribution $p(s_1)$. The transition function $\hat{p}_\varphi(s_t \mid s_{t-1}, a_{t-1})$, modeled as a feed-forward neural network with parameters φ, predicts the current state from the previous state and previous action. The decoder $p_\theta(o_t \mid s_t, a_{t-1}, o_{t-1})$, modeled as a deconvolution network with parameters θ, reconstructs the current observation from the current state, previous observation and previous action. In practice,

(a) generation process of real world   (b) generation process of simulation

Figure 2: Illustration of the generation in the real world and simulation domains respectively. All nodes are random variables. Shaded nodes are observable variables. The solid line denotes the generation process and dashed lines denote the inference process. There is an unpaired correspondence between two state trajectories surrounded by the rounded rectangle. Note that we include policy π in both generation process, which corresponds to the edge from state s_t to action a_t.

we model observations and states as multivariate Gaussian distributions. We allow $p_\theta(o_t \mid \cdot)$ dependent on o_{t-1} so that some irrelevant patterns in images can be reconstructed in an auto-regressive manner. Such a conditional distribution is feasible in practice since we always have ground-truth $o_{0:t-1}$ at timestep t in both training and deployment phases. Such a generation process enjoys an extra benefit of solving Partially Observable Markov Decision Process (POMDP) since a single image generally does not reveal the full state of the environment.

The key point that distinguishes our method from conventional representation learning is the additional constraint that the mapped state trajectories should match the simulation state trajectories. See rounded rectangle parts in Fig. 2. Such a constraint may somewhat require that the underlying transition dynamics are the same in two domains. Introducing distributions can to some extent relax the assumption and increase robustness when there is a small mismatch between source and target transition dynamics.

$$s_1 \sim p\left(s_1\right) \quad s_t \sim p\left(s_t \mid s_{t-1}, a_{t-1}\right) \quad o_t \sim p\left(o_t \mid s_t, a_{t-1}, o_{t-1}\right) \tag{1}$$

The overall optimization problem can be formulated as a variational inference problem described in Eq.2, where we want to learn a posterior distribution to approximate the ground-truth distribution.

$$\min \mathbb{E}_{\tau^r}\left[\mathcal{D}_{\mathrm{KL}}\left[q_\phi(\tau^s \mid \tau^r) \mid\mid p(\tau^s \mid \tau^r)\right]\right] \tag{2}$$

where τ is a trajectory, s and r indicate whether the trajectory is from the simulator or the real world, $p(\cdot)$ is the ground-truth distribution, $q_\phi(\cdot)$ is the mapping function we want to learn, and D_{KL} computes the Kullback-Leibler divergence. Modeling the optimization as a trajectory distribution matching can naturally handle the stochasticity of environments and policies, and the possible noise in data collected in the real world. The Evidence Lower Bound (ELBO) of this variational problem can be formulated as:

$$\max \mathbb{E}_{\tau^r}\left[\mathbb{E}_{q_\phi(\tau^s \mid \tau^r)}\left[\log p_\theta\left(\tau^r \mid \tau^s\right)\right] - \mathcal{D}_{\mathrm{KL}}\left[q_\phi\left(\tau^s \mid \tau^r\right) \mid\mid p^\pi\left(\tau^s\right)\right]\right] \tag{3}$$

The derivation of ELBO follows a common practice using Jensen inequality. A detailed derivation can be found in Appendix A. The first term maximizes the reconstruction probability, in order to enforce that the mapped states $\hat{s}$ can recover both observations o and action a. The second term enforces the alignment of the distributions of the mapped trajectories and the trajectories collected in the simulator. The policy π in source domains included in the second term does introduce a new assumption that real-world data are collected by a known behavioral policy. This assumption is mild and is implicitly or explicitly introduced in previous works (Kim et al., 2020; Gamrian & Goldberg, 2019).

3.2 DIFFERENTIABLE OPTIMIZATION OBJECTIVES

The ELBO defined in Eq. 3 contains terms involving distributions over the entire trajectory, and thus is impractical to solve directly. Given the generation process defined in the previous section, we can

---

Algorithm 1 Training Procedure of CODAS

Input: Simulator with oracle dynamics p; Policy $\pi(a \mid s)$ pre-trained in the simulated dynamics
$p(s' \mid s, a)$; Real-world Trajectory Dataset $\mathcal{D}^r = \{(o_0^r, a_0^r, ..., o_T^r)_i\}$; Number of iteration N.
Output: Mapping function $f : \mathcal{O} \to \mathcal{S}$.
   Initialize the sequential mapping function $f(s_t \mid s_{t-1}, a_{t-1}, o_t^r)$.
   for $n = 1$ to N **do**
      Sample a batch of real-world trajectories $\tau^r = \{(o_0^r, a_0^r, ..., o_T^r)_i\}$ from $\mathcal{D}^r$
      Initialize RNN with a zero state.
      Infer the corresponding state trajectories $\tau^s = \{(\hat{s}_1, ..., \hat{s}_T)_i\}$ via the mapping function f;
      Rollout one step with the oracle simulation dynamics $p(s' \mid s, a)$ for each state-action pair
         in τ^s to construct the transition dataset $\mathcal{D}_{\hat{s}} = \{(\hat{s}_i, a_i, s_{i+1})\}$;
      for $d = 1$ to D **do**
         Update the discriminator D by maximizing Eq.13;
      end for
      Update the mapping function (details in Algorithm 2);
   end for

---

decompose the joint probability into the multiplication of one-step probabilities. Eq. 4 shows the result after the decomposition. For brevity, we will use $\hat{s}, \hat{o}$ to denote s, o outputted by networks and omit the networks themselves.

$$\max \mathbb{E}_{\tau^r}[\sum_{t=1}^{T} \mathbb{E}_{q_\phi(\hat{s}_t|o_t,\hat{s}_{t-1},a_{t-1})}[\log p_{\theta_s}(\hat{o}_t^r \mid o_{t-1}, \hat{s}_t, a_{t-1}) + \log p_{\theta_\pi}(a_{t-1}|s_{t-1})]$$
$$- \mathcal{D}_{\mathrm{KL}}[q_\phi^\pi(\tau_s \mid \tau_r) \mid p^\pi(\tau_s)] \quad (4)$$

A direct computation of the second term $\mathcal{D}_{\mathrm{KL}}$ is intractable. Following the idea that the optimization process of GAN is equivalent to minimizing a certain distance measure between two distributions (Nowozin et al., 2016), we can use the optimization objective of GAN as the surrogate objective of minimizing the $\mathcal{D}_{\mathrm{KL}}[q_\phi(\tau^s \mid \tau^r) \| p^\pi(\tau^s)]$. For implementation simplicity and training stability, we still choose to optimize the original GAN optimization objective, which is formulated as Eq.14.

$$\ell_{\mathrm{D}}(\theta, \omega) = \mathbb{E}_{s \sim D^s}[D_\omega(s, a)] + \mathbb{E}_{\tau^r \sim D^r}[\log(1 - D_\omega(\hat{s}, a))] \quad (5)$$

Here, the discriminator takes state, rather than trajectory, as input for better practicality, where "real" samples are simulation states and "fake" samples are mapped states. The latter term is the objective of the generator - q_ϕ in our case. The sequential structure is preserved in the generator. This part is different from VAE-GAN (Larsen et al., 2016), which discriminates the reconstructed output of the variational encoder-decoder. Instead, we discriminate against the states after the variational encoder. GAN merely acts as an optimizer to minimize an intractable divergence between the distributions here.

The reconstruction of action a can be optimized in an end-to-end manner. However, if a differentiable π_b is available, we can replace p_{θ_π} with π, resulting an objective in Eq. 6. A fixed π here can guide p_{θ_s} to output states that yields similar a. There is a similar empirical observation that recovering a is helpful in improving the representation learning in RL (Schrittwieser et al., 2019).

$$\ell_{\mathrm{policy}} = \mathbb{E}_{(\tau^r \sim D^r}[\sum_{t=1}^{T} [\log \pi(a_t^r \mid \hat{s}_t))] \quad (6)$$

Combining all the aforementioned losses together, i.e, reconstruction loss, policy loss and generation loss, the complete optimization objective of the mapping function is as follows:

$$\ell_{\mathrm{mapping}} = \mathbb{E}_{\tau^r \sim D^r} \sum_{t=1}^{T} \log p(\hat{o}_t \mid o_t) + \lambda_D \log(1 - D_\omega(\hat{s}_t)) + \lambda_\pi \log \pi(a_t^r \mid \hat{s}_t)) \quad (7)$$

Algorithm 2 Detailed Training Procedure of Mapping Function

Input: Simulator with oracle dynamics p; Policy $\pi(a \mid s)$ pre-trained in the simulation dynamics
$p(s' \mid s, a)$;
Initialization.
Pre-train DM t_φ with $\mathcal{D}^s = \{(s_i, a_i, s_{i+1})\}$.
Update per iteration.
Update the the DM t_φ $\hat{p}$ by minimizing Eq.8 using $\mathcal{D}^{\hat{s}}$ and $\mathcal{D}^s$;
Copy the new parameters φ of DM t_φ to the embed-DM in q_ϕ;
for $m = 1$ to M **do**
    Update the mapping function q_ϕ by minimizing Eq.7;
    Update the reconstruction function p_θ by minimizing the first term in Eq.7;
end for

---

where λ_D and λ_π are hyper-parameters. Both the decoder and the policy are fixed during the training process of the mapping function. The loss function for p_θ is just the first term in Eq.7. Similarly, the mapping function q_ϕ is fixed during the training process of the reconstruction function p_θ.

3.3 STATE INFERENCE MODEL WITH EMBEDDED DYNAMICS

Since a trajectory of practical RL problems often lasts hundreds or thousands timesteps, training RNN on such a long-horizon trajectory is difficult. The previous success of ResNet (He et al., 2016) empirically shows that a residual structure can simplify the learning target by predicting small residuals, resulting in a remarkable performance increase in learning ultra-deep neural networks.

Adopting a similar idea, we incorporate a residual structure in the RNN to help stabilize the training process. We have a Dynamics Model (*DM*) trained independently using transition tuples collected in the simulator. This structure further forces the mapped states to follow the simulation dynamics. Its parameters are periodically updated to *embed-DM*, in order to provide an "average" estimation of the next states $\bar{s}_t$ (See Fig. 3). The job of the rest part, instead, is simplified to just output a correction. With the proposed structure model, the mapped states follow the transition dynamics in the simulator better.

Figure 3: Model structure with embed-DM

DM is first trained using batches of transition tuples collected in the simulator. During the training process of the mapping function, the dynamics model is trained online using $D^{\hat{s}} = \{(\hat{s}_t, a_t, s_{t+1} \sim p(s'|\hat{s}_t, a_t)\}$ and is periodically updated to the mapping function. That is, we reset the simulator to the mapped states $\hat{s}_t$ and then rollout with a one-step oracle simulation transition to get s_{t+1}. The optimization objective of the dynamics model is an MSE loss in Eq. 8. Algorithm 2 demonstrates a detailed training and updating procedure of the dynamics model and the entire mapping function. If the simulation itself is differentiable, e.g. DiffTaichi (Hu et al., 2020), we can plug it into the *embed-DM* directly without extra learning and updating mentioned above.

$$\ell_{\text{dynamics}} = \mathbb{E}_{(s,a,s')\sim D^s \cup D^{s'}} [(t_\varphi(s,a) - s')^2] \tag{8}$$

4 EXPERIMENTS

We evaluate our method in 6 MuJoCo environments from OpenAI Gym, namely InvertedPendulum, InvertedDoublePendulum, HalfCheetah, Hopper, Swimmer and Walker2d. We define the rendered images as the target domain, and the original observations as the source domain. The pre-collected dataset in the target domain contains 600 trajectories and is collected by a sub-optimal policy. Please refer to Appendix C for a detailed experiment setting.

We modify state-of-the-art methods in same-modal domain adaptation for comparison. We also compare with Behavioral Cloning (BC) considering target domain data are collected by a sub-optimal policy. BC trains a policy in a supervised manner using $(o_t^r, a_t^r) \sim D^r$. To mitigate the

partial observability issue mentioned in Sec. 3, we stack every 4 consecutive images as the new input to the BC algorithm. All methods are trained until convergence. Implementation details for all methods can be found in Sec. B. Due to some numerical instabilities inside MuJoCo, we cannot get the oracle transition function in HalfCheetah and InvertedDoublePendulum. CODAS in these two environments are implemented without embed-DM.

Experiment results in this section will answer the following three questions: (1) Does CODAS enable polices transfer from states to images? Does CODAS outperform state-of-the-art methods? (2) Does every component in CODAS contribute to the overall performance? (3) Is CODAS robust to small mismatches in environment dynamics between two domains?

4.1 PERFORMANCE

(a) Inverted Pendulum   (b) Inverted Double Pendulum   (c) HalfCheetah

(d) Hopper   (e) Swimmer   (f) Walker2d

Figure 4: Training curves of different methods on cross-modal domain adaptation

Training curves of all methods are shown in Fig. 4, x-axis being training iterations, y-axis being the ratio of discounted return after the adaptation of the original optimal policy. Each iteration, every method is updated using a batch 20 trajectories. CODAS reaches an average of 70% reward ratio after adaptation, providing an optimistic result on future applications of cross-modal domain adaptation. BC performs well in simple environments (e.g. HalfCheetah and Inverted Pendulum), but poorly in rest environments, especially in those with early termination. Surprisingly, GAN performs worse than BC in most environments, which suggests mapping images to a predefined interpretable and meaningful state space is more difficult than end-to-end policy learning.

A visual illustration of the accuracy of the mapped states is shown in Fig. 5. Both reconstructed images and re-rendered images match the original ones well. It is worth noting that re-rendered images can match the last falling frames, which are sparse in the dataset, well. Quantitative results on mapping states errors of GAN and our methods can be found in Sec. D.2.

Figure 5: A visual illustration of (a) original images (b) reconstructed images (c) re-rendered images by setting the simulator to mapped states.

4.2 ABLATION STUDIES

Since CODAS contains multiple ideas, we conduct additional experiments to understand the contribution of each component to the overall performance. We conduct ablation studies to demonstrate (1) if sequential structure matters in the cross-modal domain adaptation in RL and (2) if embed-DM improves the long-horizon inference. Since the embed-DM is based on sequential structure, we only test on two ablated variants, i.e., CODAS w/o embed-DM and w/o both embed-DM and RNN.

A comparison of all ablated variants is shown in Fig. 6. Both axes are of the same meanings as above. In all the environments, mapping functions with sequential structure yield better deployment performance. In four environments where embed-DM is applicable, embed-DM helps further improve the performance. As we expect, the major purpose of incorporating embed-DM is to simplify the learning process. If RNN itself can learn a reasonable mapping, the improvement of embed-DM will be marginal (e.g. in Walker2d). The learning process is also a little unstable in InvertedDoublePendulum, where embed-DM is not available.

Figure 6: Ablation studies by removing embed-DM and RNN in CODAS

4.3 ROBUSTNESS TO DYNAMICS MISMATCH

To analyze the CODAS's robustness to dynamics mismatch, we modify the dynamics in the source domain. Specifically, we reconfigure the friction coefficient in Hopper. The result can be found in Figure 11. The results in Hopper both with 105% and 120% friction still demonstrate a robust mapping. Besides, the mismatch of dynamics even not slow down the speed of learning. The result suggests that the CODAS technique has the potential to be deployed in more realistic applications where the dynamics in two domains can not match exactly. We leave this analysis in future works.

5 CONCLUSION

In this work, we propose Cross-Modal Domain Adaptation with Sequential structure (CODAS). CODAS defines a new paradigm of Sim2Real - adapting policies trained on simulated states to real-world with image inputs. We believe this setting is valuable in real-world applications of RL by exempting us from the tedious work of building and running rendering engines. Previous methods that use GANs fail on this problem since global structural resemblance between two domains no longer exists, while our method succeeds by fully leveraging the sequential structure and other auxiliary information provided by the underlying RL problem. We first formulate the cross-modal domain adaptation problem as a variational inference problem and decompose it into several feasible optimization objectives. To better solve the complex long-horizon sequential mapping problem, we propose a residual network structure. We validate the proposed method by adapting policies from images to states on various MuJoCo environments. Our results further suggest that cross-modal domain adaptation is a promising field for low-cost Sim2Real.

REFERENCES

Marc G. Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *J. Artif. Intell. Res.*, 47:253–279, 2013.

Konstantinos Bousmalis, Nathan Silberman, David Dohan, Dumitru Erhan, and Dilip Krishnan. Unsupervised pixel-level domain adaptation with generative adversarial networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 95–104, 2017.

Konstantinos Bousmalis, Alex Irpan, Paul Wohlhart, Yunfei Bai, Matthew Kelcey, Mrinal Kalakrishnan, Laura Downs, Julian Ibarz, Peter Pastor, Kurt Konolige, Sergey Levine, and Vincent Vanhoucke. Using simulation and domain adaptation to improve efficiency of deep robotic grasping. In *2018 IEEE International Conference on Robotics and Automation*, pp. 4243–4250, 2018.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Rui Caseiro, João F. Henriques, Pedro Martins, and Jorge Batista. Beyond the shortest path: Unsupervised domain adaptation by sampling subspaces along the spline flow. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3846–3854, 2015.

Karl Cobbe, Oleg Klimov, Christopher Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pp. 1282–1289, 2019.

Anthony G. Francis, Aleksandra Faust, Hao-Tien Lewis Chiang, Jasmine Hsu, J. Chase Kew, Marek Fiser, and Tsang-Wei Edward Lee. Long-range indoor navigation with PRM-RL. *IEEE Trans. Robotics*, 36(4):1115–1134, 2020.

Huan Fu, Mingming Gong, Chaohui Wang, Kayhan Batmanghelich, Kun Zhang, and Dacheng Tao. Geometry-consistent generative adversarial networks for one-sided unsupervised domain mapping. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2427–2436, 2019.

Shani Gamrian and Yoav Goldberg. Transfer learning for related reinforcement learning tasks via image-to-image translation. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pp. 2063–2072, 2019.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor S. Lempitsky. Domain-adversarial training of neural networks. In *Domain Adaptation in Computer Vision Applications*, pp. 189–209. 2017.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial networks. *CoRR*, abs/1406.2661, 2014.

Raghuraman Gopalan, Ruonan Li, and Rama Chellappa. Domain adaptation for object recognition: An unsupervised approach. In Dimitris N. Metaxas, Long Quan, Alberto Sanfeliu, and Luc Van Gool (eds.), *Proceedings of the IEEE International Conference on Computer Vision*, pp. 999–1006, 2011.

David Ha and Jürgen Schmidhuber. Recurrent world models facilitate policy evolution. In *Advances in Neural Information Processing Systems*, pp. 2451–2463. 2018.

Danijar Hafner, Timothy P. Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pp. 2555–2565, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016.

Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alexei A. Efros, and Trevor Darrell. CyCADA: Cycle-consistent adversarial domain adaptation. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pp. 1994–2003, 2018.

Yuanming Hu, Luke Anderson, Tzu-Mao Li, Qi Sun, Nathan Carr, Jonathan Ragan-Kelley, and Frédo Durand. DiffTaichi: Differentiable programming for physical simulation. In *International Conference on Learning Representations*, 2020.

Nick Jakobi, Phil Husbands, and Inman Harvey. Noise and the reality gap: The use of simulation in evolutionary robotics. In *Advances in Artificial Life*, pp. 704–720, Berlin, Heidelberg, 1995. ISBN 978-3-540-49286-3.

Stephen James, Paul Wohlhart, Mrinal Kalakrishnan, Dmitry Kalashnikov, Alex Irpan, Julian Ibarz, Sergey Levine, Raia Hadsell, and Konstantinos Bousmalis. Sim-to-real via sim-to-sim: Data-efficient robotic grasping via randomized-to-canonical adaptation networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 12627–12637, 2019.

Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I. Jordan. Provably efficient reinforcement learning with linear function approximation. In *2020 Conference on Learning Theory*, volume 125, pp. 2137–2143, 2020.

Lukasz Kaiser, Mohammad Babaeizadeh, Piotr Milos, Blazej Osinski, Roy H. Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, Afroz Mohiuddin, Ryan Sepassi, George Tucker, and Henryk Michalewski. Model based reinforcement learning for Atari. In *International Conference on Learning Representations*, 2020.

Kuno Kim, Yihong Gu, Jiaming Song, Shengjia Zhao, and Stefano Ermon. Domain adaptive imitation learning. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

Taeksoo Kim, Moonsu Cha, Hyunsoo Kim, Jung Kwon Lee, and Jiwon Kim. Learning to discover cross-domain relations with generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pp. 1857–1865, 2017.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *CoRR*, abs/2004.13649, 2020.

Sascha Lange and Martin A. Riedmiller. Deep auto-encoder neural networks in reinforcement learning. In *International Joint Conference on Neural Networks*, pp. 1–8, 2010.

Sascha Lange, Martin A. Riedmiller, and Arne Voigtländer. Autonomous reinforcement learning on raw visual input data in a real world application. In *International Joint Conference on Neural Networks*, pp. 1–8, 2012.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. In *Proceedings of the 33rd International Conference on Machine Learning*, volume 48, pp. 1558–1566, 2016.

Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *CoRR*, abs/2004.14990, 2020a.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, 2020b.

Sergey Levine, Peter Pastor, Alex Krizhevsky, Julian Ibarz, and Deirdre Quillen. Learning hand-eye coordination for robotic grasping with deep learning and large-scale data collection. *I. J. Robotics Res.*, 37(4-5):421–436, 2018.

Mingsheng Long, Yue Cao, Jianmin Wang, and Michael I. Jordan. Learning transferable features with deep adaptation networks. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37, pp. 97–105, 2015.

Sebastian Nowozin, Botond Cseke, and Ryota Tomioka. f-GAN: Training generative neural samplers using variational divergence minimization. In *Advances in Neural Information Processing Systems*, pp. 271–279, 2016.

Kanishka Rao, Chris Harris, Alex Irpan, Sergey Levine, Julian Ibarz, and Mohi Khansari. RL-CycleGAN: Reinforcement learning aware simulation-to-real. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 11154–11163, 2020.

Martin A. Riedmiller, Roland Hafner, Thomas Lampe, Michael Neunert, Jonas Degrave, Tom Van de Wiele, Vlad Mnih, Nicolas Heess, and Jost Tobias Springenberg. Learning by playing solving sparse reward tasks from scratch. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pp. 4341–4350, 2018.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy P. Lillicrap, and David Silver. Mastering Atari, go, chess and shogi by planning with a learned model. *CoRR*, abs/1911.08265, 2019.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017.

Yaniv Taigman, Adam Polyak, and Lior Wolf. Unsupervised cross-domain image generation. In *International Conference on Learning Representations*, 2017.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, Timothy P. Lillicrap, and Martin A. Riedmiller. Deepmind control suite. *CoRR*, abs/1801.00690, 2018.

Josh Tenenbaum. Building machines that learn and think like people. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 5, 2018.

Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033, 2012.

Tingwu Wang, Xuchan Bao, Ignasi Clavera, Jerrick Hoang, Yeming Wen, Eric Langlois, Shunshi Zhang, Guodong Zhang, Pieter Abbeel, and Jimmy Ba. Benchmarking model-based reinforcement learning. *CoRR*, abs/1907.02057, 2019.

Manuel Watter, Jost Tobias Springenberg, Joschka Boedecker, and Martin A. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. In *Advances in Neural Information Processing Systems*, pp. 2746–2754, 2015.

Fei Xia, Amir R. Zamir, Zhi-Yang He, Alexander Sax, Jitendra Malik, and Silvio Savarese. Gibson env: real-world perception for embodied agents. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9068–9079, 2018.

Mengyuan Yan, Iuri Frosio, Stephen Tyree, and Jan Kautz. Sim-to-real transfer of accurate grasping with eye-in-hand observations and continuous control. *CoRR*, abs/1712.03303, 2017.

Zili Yi, Hao (Richard) Zhang, Ping Tan, and Minglun Gong. DualGAN: Unsupervised dual learning for image-to-image translation. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2868–2876, 2017.

Donggeun Yoo, Namil Kim, Sunggyun Park, Anthony S. Paek, and In-So Kweon. Pixel-level domain transfer. In *Proceedings of the 14th European Conference on Computer Vision*, volume 9912, pp. 517–532, 2016.

Andy Zeng, Shuran Song, Stefan Welker, Johnny Lee, Alberto Rodriguez, and Thomas A. Funkhouser. Learning synergies between pushing and grasping with self-supervised deep reinforcement learning. In *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 4238–4245, 2018.

Marvin Zhang, Sharad Vikram, Laura Smith, Pieter Abbeel, Matthew J. Johnson, and Sergey Levine. SOLAR: deep structured representations for model-based reinforcement learning. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pp. 7444–7453, 2019.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A. Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2242–2251, 2017.

A   DERIVATION OF OPTIMIZATION OBJECTIVES

Assume the distribution of trajectories in the simulator $p^{\pi}(\tau_s)$ is calculated from the real world trajectories τ_r. We want to match $q_{\phi}^{\pi}(\tau_s|\tau_r)$ to the ground-truth distribution $p_{\theta}^{\pi}(\tau_s|\tau_r)$, leading to the optimization objective:

$$\min \mathbb{E}_{\tau^r}[\mathcal{D}_{\mathrm{KL}}[q_{\phi}^{\pi}(\tau_s|\tau_r)||p_{\theta}^{\pi}(\tau_s|\tau_r)]] \tag{9}$$

To maximize the objective, we first transform it into the Evidence Lower Bound (ELBO):

$$\mathcal{D}_{\mathrm{KL}}[q_{\phi}^{\pi}(\tau_s|\tau_r)||p_{\theta}^{\pi}(\tau_s|\tau_r)]$$
$$=\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log \frac{q_{\phi}^{\pi}(\tau_s|\tau_r)}{p_{\theta}^{\pi}(\tau_s|\tau_r)}]$$
$$=\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log q_{\phi}^{\pi}(\tau_s|\tau_r) - \log \frac{p_{\theta}^{\pi}(\tau_s, \tau_r)}{p^{\pi}(\tau_r)}]$$
$$=\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log q_{\phi}^{\pi}(\tau_s|\tau_r) - \log p_{\theta}^{\pi}(\tau_r, \tau_s)] + \log p_{(}^{\pi}\tau_r)$$

The last term $p_{\theta}^{\pi}(\tau_r)$ is a constant with regards to the parameter θ, and thus can be ignored in the optimization process. The minimization can be reduced to $\min . \mathbb{E}_{\tau^r}[\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log q_{\phi}^{\pi}(\tau_s|\tau_r) - \log p_{\theta}^{\pi}(\tau_r, \tau_s)]]$. Since the sampled trajectories can be considered as an i.i.d., the first term of expectation can be further re-written as

$$\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log q_{\phi}^{\pi}(\tau_s|\tau_r) - \log p_{\theta}^{\pi}(\tau_r, \tau_s)]$$
$$=\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log \frac{q_{\phi}^{\pi}(\tau_s|\tau_r)}{(p_{\theta}^{\pi}(\tau_r|\tau_s)p_{\theta}^{\pi}(\tau_s))}] \tag{10}$$
$$=-\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log p_{\theta}^{\pi}(\tau_r|\tau_s) - \mathcal{D}_{\mathrm{KL}}[q_{\phi}^{\pi}(\tau_s|\tau_r) \, || \, p^{\pi}(\tau_s)]$$

Based on the generation process, we can decompose the first term based on trajectories to multiplication of terms based on states.

$$q_{\phi}^{\pi}(\tau^s \mid \tau^r) = \prod_{t=1}^{T_{\tau}} q_{\phi}(s_t \mid s_{t-1}, o_t, a_{t-1}^r), \quad o_t, a_{t-1} \sim \tau^r$$
$$p_{\theta}^{\pi}(\tau^r \mid \tau^s) = \prod_{t=1}^{T_{\tau}} p_{\theta}(o_t \mid o_{t-1}, s_t, a_{t-1}), \quad s_t, a_{t-1} \sim \tau^s \tag{11}$$

$$\mathbb{E}_{\tau^r}[\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\log p_{\theta}^{\pi}(\tau_r|\tau_s)]$$
$$=\mathbb{E}_{\tau^r}[\mathbb{E}_{q_{\phi}^{\pi}(\tau_s|\tau_r)}[\sum_{t=1}^{T} \log p_{\theta}(\hat{o}_t|o_{t-1}, \hat{s}_t, a_{t-1})] \tag{12}$$
$$=\mathbb{E}_{\tau^r}[\sum_{t=1}^{T}(\mathbb{E}_{q_{\phi}(\hat{s}_t|o_t, \hat{s}_{t-1}, a_{t-1})}[\log p_{\theta}(\hat{o}_t|o_{i-1}, \hat{s}_t, a_{i-1})]]$$

A direct computation of the second term $\mathcal{D}_{\mathrm{KL}}$ is intractable. Following the idea that the optimization process of GAN is equivalent to minimizing a certain distance measure between two distributions (Nowozin et al., 2016), we can use the optimization objective of GAN as the surrogate objective of minimizing the $\mathcal{D}_{\mathrm{KL}}[q_{\phi}(\tau^s \mid \tau^r) \, || \, p^{\pi}(\tau^s)]$ by introducing a new discriminator D_{ω} parameterized by ω that maximizes Eq. 13,

$$\ell_{\mathrm{D}}(\theta, \omega) = \mathbb{E}_{s \sim D_s}[1 + \log \frac{D_{\omega}(s)}{1 - D_{\omega}(s)}] + \mathbb{E}_{\tau^r \sim D^r}[\frac{D_{\omega}(\hat{s})}{1 - D_{\omega}(\hat{s})}] \tag{13}$$

For implementation simplicity and training stability, $(\frac{D_\omega(s)}{1-D_\omega(s)})$ can become arbitrarily large, we still choose to optimize the original GAN optimization objective, which is formulated as Eq.14.

$$\ell_D(\theta, \omega) = \mathbb{E}_{s \sim D_s}[D_\omega(s)] + \mathbb{E}_{s \sim f_\theta(o^r)}[\log(1 - D_\omega(s))] \tag{14}$$

B   IMPLEMENTATION DETAILS

Figure 7: Illustration of full network structure. Blue parts denote mapping function q_ϕ; Yellow and green parts denote reconstruction function p_θ. Green part is always fixed in the entire training process.

Fig. B gives an illustration of the overall structure of our method. Detailed network structure and hyperparameters are listed in Sec. B.1, all of which are the same for every environment. To help balance the influence of the residual Δs_t, we introduce a new hyperparameter λ_{res}, s.t,

$$\hat{s}_t = \bar{s}_t + \lambda_{res}\Delta s_t \tag{15}$$

B.1   HYPERPARAMETERS AND NETWORK STRUCTURE

Table 1: Hyperparameters for the Reconstruction Network

Hyperparameter	Value
General	
λ_D	50.0
λ_π	1.0
λ_{res}	1.5
batch size	20 (trajs)
mapping update iter M	5
discriminator update iter D	1
DM update iter	10
DM batch size	512
DM sync freq	1
grad clip norm	10

Table 2: Hyperparameters for the Reconstruction Network (Cont.d)

Hyperparameter	Value
RNN	
RNN type	GRU
RNN hidden size	128, 128
Dynamics Model	
Hidden sizes	512, 512, 512
Activation function	tanh
Learning rate	1×10^{-4}
Policy	
Hidden sizes	64, 64
Activation function	tanh
Discriminator	
Hidden sizes	256, 256, 256, 256, 256
Activation function	relu
Layer norm	true
Learning rate	5×10^{-5}
Visual Encoder	
Hidden sizes	Conv (4, 4, 32), Conv (4, 4, 64), , Conv (4, 4, 128), Conv (4, 4, 256), 256, 256, 256
Activation function	relu
Layer norm	true
Learning rate	5×10^{-5}
Visual Decoder	
Hidden sizes	256, 256, 1024, Deconv (4, 4, 256), Deconv (4, 4, 128), , Deconv (4, 4, 64), Conv (4, 4, 32),
Activation function	relu
Layer norm	true
Learning rate	5×10^{-5}

C   EXPERIMENT SETTING

We evaluate our method in 6 MuJoCo environments from OpenAI Gym, namely InvertedPendulum, InvertedDoublePendulum, HalfCheetah, Hopper, FixedSwimmer and Walker2d. FixedSwimmer is based on modifications proposed in previous works (Wang et al., 2019) to avoid sub-optimal policies by changing one sensor position. We treat the simulation observations as low dimensional simulation states s and rendered images as real images.

Images are collected by "track camera" in HalfCheetah, Hopper, FixedSwimmer and Walker2d and "default camera" in InvertedPendulum and InvertedDoublePendulum. All images are resized to $[64, 64, 3]$ without any further pre-processing techniques in all environments. Examples of rendered images are shown in Fig. 8.

Two polices are independently trained until convergence using PPO (Schulman et al., 2017) for every environment. One of them is regarded π_{real} a human expert to collect the "real" image dataset. We use a stochastic policy to mimic the real data collection process. The other is regarded as a pre-trained simulator policy π_{sim}. The real-world dataset contains 600 episodes, each being truncated to a max length of 500.

(a) Pendulum   (b) HalfCheetah   (c) Hopper   (d) Swimmer   (e) Walker2d

Figure 8: Examples of rendered images of MuJoCo environments

D MORE EXPERIMENT RESULTS

D.1 ABSOLUTE RESULTS ON REWARDS

Table 3: Average reward ratios over all environments.

Method	CODAS(ours)	GAN	BC(max)	BC(final)
Reward Ratio	**70.1%**	42.8%	47.83%	34.91%

D.2 QUANTITATIVE RESULTS OF STATE MAPPING ERROR

Figure 9: Mean squared error between mapped states and ground-truth states.

D.3 TRAINING CURVES OF BEHAVIORAL CLONING

Figure 10: Training curves of Behavior Cloning.

D.4 ROBUSTNESS TO DYNAMICS MISMATCH

Figure 11: Reward ratio in Hopper when small dynamics mismatches exist.

D.5 TRAINING CURVES OF CYCLEGAN

We planned to use CycleGAN, one of the state-of-the-art methods in domain adaptation, for comparison. Concretely, we remove the identity loss and use the network structure as ours (See Visual Encoder/Visual Decoder in Sec. B) as the generator network structure. However, the changes in the loss function and network structure may require a complete hyperparameter setting from image-to-image translation. We fail to get a workable CycleGAN in most environments. The best results so far are shown in Fig. D.5.

Figure 12: Training curves of CycleGAN.