Meta-Complementing the Semantics of Short Texts in Neural Topic Models

Abstract

Topic models infer latent topic distributions based on observed word co-occurrences in a text corpus. While typically a corpus contains documents of variable lengths, most previous topic models treat documents of different lengths uniformly, assuming that each document is sufficiently informative. However, shorter documents may have only a few word co-occurrences, resulting in inferior topic quality. Some other previous works assume that all documents are short, and leverage external auxiliary data, e.g., pretrained word embeddings and document connectivity. Orthogonal to existing works, we remedy this problem within the corpus itself by proposing a Meta-Complement Topic Model, which improves topic quality of short texts by transferring the semantic knowledge learned on long documents to complement semantically limited short texts. As a self-contained module, our framework is agnostic to auxiliary data and can be further improved by flexibly integrating them into our framework. Specifically, when incorporating document connectivity, we further extend our framework to complement documents with limited edges. Experiments demonstrate the advantage of our framework.

1 Introduction

Topic models help to understand the main themes within documents. The quality of topic distribution of each document depends on sufficient word co-occurrences. Real-word corpora contain documents of *variable lengths*. Academic papers vary from journal manuscripts to conference papers to extended abstracts. News articles could be headlines, short or full articles, or detailed commentaries. Fig. 1(a) illustrates an academic paper corpus where the distribution of document lengths exhibits a long-tail distribution. Despite variable lengths (with different degrees of sufficiency of word co-occurrences), existing works, e.g., ProdLDA [31] and GATON [37], treat documents uniformly, resulting in inferior topic quality for short texts. Evidentially, Fig. 1(b) presents document classification accuracy on four subsets of corpus with descending lengths. Accuracies gradually drop as the length decreases. The inferior topic quality of short texts limits the overall performance of a topic model.

Challenges. Most existing topic models optimize the learning process by averaging the generative losses of different documents, without paying special attention to semantically limited short texts. A few studies, e.g., OTLDA [15], take weighted summation of losses based on document lengths, they compute the weights by dividing the length of each document by the length of the whole corpus, which further deemphasizes the importance of short text modeling. Thus, we seek to improve short text topic modeling within a *variable-length* corpus, without hurting topic quality of long documents.

To mitigate the scarcity of word co-occurrences in short texts, some works leverage auxiliary knowledge to enhance topic modeling. ETM [8] exploits pretrained word embeddings [27, 29] to capture word similarities. RTM [5] constructs a document network, e.g., paper citation network, to aggregate topics of connected documents. However, they rely on the availability of auxiliary data.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: Illustration of (a) a paper corpus with various-length documents, (b) classification accuracy on four subsets of the corpus by descending length, and (c) semantic transfer and complement.

Approach. We propose **M**eta-**C**omplement **T**opic **M**odel (MCTM). Since a corpus contains variable lengths of documents, we are motivated to learn the transferable semantic knowledge on long documents, and complement the semantics-scarce short texts and enhance the latter's topic distributions. As illustrated by Fig. 1(c), we learn a function g on long document A with abundant content, and use it to predict missing semantics (red box) for short document B to complement its content for a more expressive topic distribution. Since meta-learning [10] is emerging to improve model performance with few labeled observations, but no one explores its design in topic modeling. We are thus motivated to integrate it and optimize the proposed MCTM by a meta-learning objective.

Orthogonal to existing works relying on auxiliary data, our framework is self-contained, assuming only in-corpus information, which offers a new direction to improve short text topic modeling. When auxiliary data are available, our framework can be further improved by flexibly incorporating them. In particular, when incorporating document network structure, we discover that document degrees also exhibit a similar long-tail distribution, i.e., some structure-abundant documents link to sufficient neighbors as auxiliary, while others contain scarce links. Besides *textual* semantic complement at Fig. 1(c), we extend MCTM to further complement *structural* semantics on the document network.

Contributions. *First*, we propose MCTM, which learns how to complement textual semantics by semantic knowledge transfer. *Second*, we derive two alternatives to implement missing semantics prediction function g to capture document similarities. *Third*, although agnostic to auxiliary data, MCTM can also flexibly integrate them to further improve the performance. We demonstrate our adaptability by modeling pretrained word embeddings and document networks. For the latter, we extend MCTM to further complement structural semantics. *Fourth*, extensive experiments verify the effectiveness of MCTM. Code and datasets are submitted and will be released upon publication.

2 Problem Formulation and Preliminaries

We are given a corpus of N documents $\mathcal{D} = \{\mathbf{d}_i\}_{i=1}^N$. Each document $\mathbf{d} \in \mathbb{R}^{|\mathcal{V}|}$ is a vector in the vocabulary space $\mathcal{V}$. $l_d = \sum_{w \in \mathcal{V}} d_w$ is the length of document d where d_w is the word count of w in d. When word embeddings are available, we have $\mathcal{H} = \{\mathbf{h}_w\}_{w \in \mathcal{V}}$ where $\mathbf{h}_w$ is the embedding of word w. Documents may link to others in a document network $\mathcal{G} = \{\mathcal{D}, \mathcal{E}\}$, with documents $\mathcal{D}$ and network connectivity $\mathcal{E} = \{e_{ij}\}_{i,j=1}^N$. If document d links to d', $e_{d,d'} = 1$, otherwise $e_{d,d'} = 0$. $\mathcal{N}(d)$ is the set of neighbors of d. We consider an undirected network, $e_{d,d'} = e_{d',d}$. Corpus $\mathcal{D}$ contains documents of variable lengths $\{l_i\}_{i=1}^N$. We introduce a hyperparameter $\mathscr{L}$ as the threshold where short documents are those with fewer observed words, $\mathcal{D}_{\text{short}} = \{\mathbf{d}_i | l_i < \mathscr{L}\}$, and long documents are defined symmetrically, $\mathcal{D}_{\text{long}} = \{\mathbf{d}_i | l_i \geq \mathscr{L}\}$. We consider $\mathscr{L}$ as a predefined hyperparameter and leave other designs as future work. See supplementary materials for a summary of math notations.

Given a variable-length corpus $\mathcal{D}$ (as well as word embeddings $\mathcal{H}$ and network $\mathcal{E}$ if observed) as input, we aim to output topic distributions for documents where the topic quality of short documents is improved, without hurting long documents. Note that our goal is not to allow short texts to reach the performance of long documents, but to improve short text topic modeling as much as possible.

Meta-Learning. Meta-learning [10] optimizes globally shared parameters, a.k.a. prior knowledge, over meta-training tasks, so as to rapidly adapt the model to previously unseen meta-testing tasks with only a few observed data. Since topic models generally learn topics by a content generative process, here we consider generating observed words for a document d as a task $\mathcal{T}_d$. A meta-training task $\mathcal{T}_d$ corresponds to a training document d and consists of a support set and a query set, $\mathcal{T}_d = \{\mathcal{S}_d, \mathcal{Q}_d\}$. Each set contains randomly sampled words from document d, such that support words and query words are mutually exclusive, $\mathcal{S}_d \cap \mathcal{Q}_d = \emptyset$ and $\mathcal{S}_d \cup \mathcal{Q}_d = \mathbf{d}$. *Meta-training* has two steps:

Figure 2: Model architecture of Meta-Complementing Topic Model, MCTM.

1. Local update. Given a topic model f_θ with parameter θ, f_θ is first updated from the globally shared parameter θ to document-specific local parameter θ_d w.r.t. loss on d's support words $\mathcal{S}_d$.

$$\theta_d = \theta - \alpha\nabla_\theta\mathcal{L}(\theta, \mathcal{S}_d) \quad \text{where} \quad \mathcal{T}_d = \{\mathcal{S}_d, \mathcal{Q}_d\} \in \mathcal{T}_{\text{tr}}. \tag{1}$$

α is meta-learning rate, ∇ is gradient, $\mathcal{L}$ is loss function, $\mathcal{T}_{\text{tr}}$ is a set of meta-training tasks (documents).

2. Global update. After obtaining θ_d for each document d, we compute the loss on query words $\mathcal{L}(\theta_d, \mathcal{Q}_d)$. Together with other training tasks, we optimize the globally shared parameter θ.

$$\theta^* = \min_\theta \sum_{\mathcal{T}_d \in \mathcal{T}_{\text{tr}}} \mathcal{L}(\theta_d, \mathcal{Q}_d) = \min_\theta \sum_{\mathcal{T}_d \in \mathcal{T}_{\text{tr}}} \mathcal{L}(\theta - \alpha\nabla_\theta\mathcal{L}(\theta, \mathcal{S}_d), \mathcal{Q}_d). \tag{2}$$

θ^* is the new globally shared parameter and will replace θ at Eq. 1–2 for the next iteration. After convergence, the final global parameter θ^* can easily be adapted to meta-testing tasks.

Meta-testing tasks $\mathcal{T}_{\text{te}}$ are unseen test documents. All the observed words are support words, $\mathcal{T}_d = \mathcal{S}_d = \mathbf{d}$. During meta-testing, topic model f_{θ^*} with optimized global parameter θ^* is updated w.r.t. $\mathcal{S}_d$ by Eq. 1 and obtain θ_d^*. The topic distribution of testing document is inferred by $\mathbf{z}_d = f_{\theta_d^*}(\mathbf{d})$.

3 Methodology

We introduce **Meta-Complement Topic-Model** (MCTM) at Fig. 2. Below we elaborate three components, graph convolutional encoder, missing semantics prediction, and meta-learning optimization.

3.1 Graph Convolutional Topic Encoding

We follow GATON [37] and first present a graph convolutional encoder f_θ (Fig. 2(a)), which projects documents to K-dimensional topic distributions. We defer the discussion on short text modeling to the following subsections. Given a corpus $\mathcal{D}$, considering documents and words as vertices, we construct a bipartite graph, the links represent word occurrences in the documents. Since documents and words preserve heterogeneous feature spaces, we project them to the same topic space by learnable matrix,

$$\tilde{\mathbf{z}}_d^{(l+1)} = \mathbf{W}_1^{(l+1)}\mathbf{z}_d^{(l)}, \qquad \tilde{\mathbf{z}}_w^{(l+1)} = \mathbf{W}_2^{(l+1)}\mathbf{z}_w^{(l)}, \quad \text{where} \quad d \in \mathcal{D}, w \in \mathcal{V}. \tag{3}$$

l is the l-th convolutional layer. $\mathbf{z}_d^{(0)}$ and $\mathbf{z}_w^{(0)}$ are inputs, i.e., Bag-of-Words and one-hot, respectively.

To differentiate the importance of words, we evaluate attention between document d and its observed support words at Eq. 4 and aggregate words at Eq. 5 where $[\cdot||\cdot]$ is concatenation.

$$a_{d,w} = \text{softmax}\left(\tanh(\mathbf{b}_1^{(l+1)\top}[\tilde{\mathbf{z}}_d^{(l+1)}||\tilde{\mathbf{z}}_w^{(l+1)}])\right) \quad \text{where} \quad w \in \mathcal{S}_d \tag{4}$$

$$\mathbf{z}_d^{(l+1)} = \tanh\left(\frac{1}{2}(\tilde{\mathbf{z}}_d^{(l+1)} + \sum_{w \in \mathcal{S}_d} a_{d,w}\tilde{\mathbf{z}}_w^{(l+1)})\right). \tag{5}$$

Symmetrically, we modify Eq. 4 and obtain $a_{w,d}$, i.e., the attention between word w and documents it appears in. After symmetric aggregation at Eq. 5, we obtain $\mathbf{z}_w^{(l+1)}$ for word w. So far, we complete the convolution from l-th to $(l+1)$-th layer. For simplicity, we summarize aggregation at Eq. 3–5 by

$$\mathbf{z}_d^{(l+1)} = \text{AGG}(\mathbf{W}_1^{(l+1)}\mathbf{z}_d^{(l)}, \mathbf{W}_2^{(l+1)}\mathbf{z}_w^{(l)}|w \in \mathcal{S}_d), \quad \mathbf{z}_w^{(l+1)} = \text{AGG}(\mathbf{W}_2^{(l+1)}\mathbf{z}_w^{(l)}, \mathbf{W}_1^{(l+1)}\mathbf{z}_d^{(l)}|\forall d : w \in \mathcal{S}_d). \tag{6}$$

We repeat Eq. 6 for maximum L layers and obtain K-dimensional topics $\mathbf{z}_d = \mathbf{z}_d^{(L)}$ for document d and $\mathbf{z}_w = \mathbf{z}_w^{(L)}$ for word w. The complete encoder is Eq. 7. θ is the set of all encoding parameters.

$$\mathbf{z}_d, \mathbf{z}_w = f_\theta(\mathbf{z}_d^{(l=0)}, \mathbf{z}_w^{(l=0)}|d \in \mathcal{D}, w \in \mathcal{V}). \tag{7}$$

3.2 Missing Semantics Prediction with Contrastive Learning

A short document with few words leaves some content poorly described, resulting in incomplete topic distribution $\mathbf{z}_d$. As a toy example, document B at Fig. 1(c) contains limited words, e.g., gene and clone, and leaves other contents, e.g., protein and cell, uncovered. We aim to complement the topics of short documents. For a document d, regardless of long or short, we complement its semantics by

$$\mathbf{z}_d^* = \mathbf{z}_d + \mathbf{m}_d. \tag{8}$$

We name $\mathbf{m}_d \in \mathbb{R}^K$ *missing semantics* of document d. If d is a long document with complete semantics, $\mathbf{m}_d$ is a zero vector. A function g_μ predicts missing semantics at Eq. 9 with topic distributions of d and its support words as inputs. We will elaborate the design of function g_μ shortly.

$$\mathbf{m}_d = g_\mu(\mathbf{z}_d, \mathbf{z}_w | w \in \mathcal{S}_d). \tag{9}$$

Contrastive Learning. Long documents contain relatively more sufficient word co-occurrences than short documents. Thus, we learn missing semantics prediction function g_μ on long documents, and then transfer the learned semantic knowledge to complement short documents. On one hand, a long document d with enough content does not need semantic complement. Thus we have below constraint

$$\mathbf{m}_d \rightarrow \mathbf{0} \quad \text{where} \quad d \in \mathcal{D}_{\text{long}}. \tag{10}$$

On the other hand, although we aim to transfer the semantic knowledge from long to short documents, there does not exist a one-to-one correspondence in corpus $\mathcal{D}$. As a result, we may transfer semantics of a long document (e.g., machine learning concepts) to a short one describing completely distinct content (e.g., biology). To overcome this limitation, we introduce another constraint with contrastive objective. For a long document d with support words $\mathcal{S}_d$, we randomly hide a proportion of words to mimic a short document, denoted as d' with remaining observed words $\mathcal{S}_{d'} \subset \mathcal{S}_d$. Then, for both long document d and its pruned short version d', we predict their missing semantics by Eq. 9, and obtain $\mathbf{m}_d$ and $\mathbf{m}_{d'}$, respectively. $\mathbf{m}_{d'}$ should complement the previously hidden semantics, i.e., $\mathcal{S}_d - \mathcal{S}_{d'}$,

$$\mathbf{z}_{d'} + \mathbf{m}_{d'} \rightarrow \mathbf{z}_d + \mathbf{m}_d \quad \Rightarrow \quad \mathbf{z}_{d'}^* \rightarrow \mathbf{z}_d^* \quad \text{where} \quad d \in \mathcal{D}_{\text{long}}. \tag{11}$$

Together with above Eq. 10, which forces $\mathbf{z}_d^* = \mathbf{z}_d + \mathbf{m}_d$ to approach $\mathbf{z}_d$, Eq. 11 actually has

$$\mathbf{z}_{d'} + \mathbf{m}_{d'} \rightarrow \mathbf{z}_d \quad \Rightarrow \quad \mathbf{m}_{d'} \rightarrow \mathbf{z}_d - \mathbf{z}_{d'} \quad \text{where} \quad d \in \mathcal{D}_{\text{long}}. \tag{12}$$

To summarize, we arrive at the following constraint loss.

$$\mathcal{L}_{\text{con}}(d) = -\log \sigma(\cos(\mathbf{m}_{d'}, \mathbf{z}_d - \mathbf{z}_{d'})) \quad \text{where} \quad d \in \mathcal{D}_{\text{long}}. \tag{13}$$

$\sigma(x) = \frac{1}{1+\exp(-x)}$ is sigmoid function, and $\cos(\cdot, \cdot)$ is cosine similarity.

Missing Semantics Prediction. We now define the function of missing semantics prediction g_μ. Given topic distributions of a document and its observed support words as input, a desirable function should aggregate them and output a single missing semantics vector. We propose two alternatives.

1. *GNN function.* The first is to implement g_μ using a graph neural network, see Fig. 2(b).

$$\mathbf{m}_d = g_\mu(\mathbf{z}_d, \mathbf{z}_w | w \in \mathcal{S}_d) = \text{AGG}(\mathbf{U}_1 \mathbf{z}_d, \mathbf{U}_2 \mathbf{z}_w | w \in \mathcal{S}_d). \tag{14}$$

A corpus $\mathcal{D}$ contains documents with diverse themes. For example, some documents discuss machine learning, while others describe biology. However, the assumption of corpus-level shared parameter $\mathbf{U}_1$ and $\mathbf{U}_2$ is not flexible to model diverse documents for missing semantics prediction, since different documents may have distinct optimal parameters, which are sometimes even in opposing direction. As a result, the predicted missing semantics $\mathbf{m}_d$ centers its mass around the most frequent topics and leaves other distinct topics uncovered. We seek to *personalize* $\mathbf{U}_1$ and $\mathbf{U}_2$ for each document d to recover the distinct missing semantics. Formally, we introduce a function ϕ, which transforms $\mathbf{U}_1$ and $\mathbf{U}_2$ to document-specific parameters $\mathbf{U}_{d,1}$ and $\mathbf{U}_{d,2}$ by scaling and shifting. Taking $\mathbf{U}_1$ as example,

$$\mathbf{U}_{d,1} = \phi(\mathbf{U}_1, \mathbf{z}_d, \mathbf{z}_w | w \in \mathcal{S}_d) = \mathbf{U}_1 \odot \left[(\boldsymbol{\gamma}_d + \mathbf{1})_{\times K}\right] + \left[(\boldsymbol{\beta}_d)_{\times K}\right]. \tag{15}$$

$\boldsymbol{\gamma}_d$ and $\boldsymbol{\beta}_d$ are document-specific vectors for scaling and shifting shared parameter $\mathbf{U}_1$. $\odot$ is element-wise product. $[(\mathbf{x})_{\times K}]$ is a matrix with K identical column vector $\mathbf{x}$. $\mathbf{1}$ is a vector of ones, ensuring the scaling matrix centers around one. $\mathbf{U}_{d,2}$ is similarly defined. Eq. 15 allows each document d to

147 have its own parameters, while all documents still share the common knowledge. Similar documents
148 scale and shift $\mathbf{U}_1$ and $\mathbf{U}_2$ to similar directions. Different documents push them to distinct directions.

149 We define scaling $\boldsymbol{\gamma}_d$ and shifting $\boldsymbol{\beta}_d$, parameterized by topics of document d and its support words.

$$\boldsymbol{\gamma}_d = \tanh(\mathbf{W}_\gamma \mathbf{z}_d + \mathbf{W}'_\gamma \bar{\mathbf{z}}_{\mathcal{S}_d}), \quad \boldsymbol{\beta}_d = \tanh(\mathbf{W}_\beta \mathbf{z}_d + \mathbf{W}'_\beta \bar{\mathbf{z}}_{\mathcal{S}_d}). \tag{16}$$

150 $\bar{\mathbf{z}}_{\mathcal{S}_d} = \frac{1}{|\mathcal{S}_d|} \sum_{w \in \mathcal{S}_d} \mathbf{z}_w$ is the average of d's words. In summary, we use Eq. 14 to predict d's missing
151 semantics, except that shared parameters $\mathbf{U}_1$ and $\mathbf{U}_2$ are replaced by d-specific ones, $\mathbf{U}_{d,1}$ and $\mathbf{U}_{d,2}$.

152 2. *Clustering function.* We propose an alternative method by semantic clustering to recover distinct
153 missing semantics, Fig. 2(c). Documents with similar content fall into related clusters, while unique
154 documents belong to different ones. If we assign each cluster a set of parameters for missing semantics
155 prediction, similar documents would recover their own distinct topics. Specifically, we introduce R
156 centroids $\{\mathbf{c}_r\}_{r=1}^R$, each corresponding to one cluster. Given topic distributions of document d and its
157 support words, we first evaluate the assignment probability between document d and each cluster by

$$\Pr(r) = \operatorname{softmax}(-\frac{1}{2}||\mathbf{h}_0 - \mathbf{c}_r||_2^2) = \frac{\exp(-\frac{1}{2}||\mathbf{h}_0 - \mathbf{c}_r||_2^2)}{\sum_{r'=1}^R \exp(-\frac{1}{2}||\mathbf{h}_0 - \mathbf{c}_{r'}||_2^2)}. \tag{17}$$

158 $\mathbf{h}_0 = [\mathbf{z}_d||\bar{\mathbf{z}}_{\mathcal{S}_d}]$ is the concatenation of $\mathbf{z}_d$ and $\bar{\mathbf{z}}_{\mathcal{S}_d}$. We then assign parameters to each cluster,

$$\mathbf{m}_d = \mathbf{h}_1 = \sum_{r=1}^R \Pr(r) \times \operatorname{ReLU}(\mathbf{W}_r \mathbf{h}_0 + \mathbf{b}_r). \tag{18}$$

159 Therefore, related documents obtain similar clustering probabilities and missing semantics.

160 Above process is a flat clustering. Our function can be extended to multiple clustering layers. Each
161 layer s consists of $R^{(s)}$ centroids. After obtaining the output from previous layer, $\mathbf{h}_{s-1}$, we repeat Eq.
162 17–18 by replacing $\mathbf{h}_0$ with $\mathbf{h}_{s-1}$, and obtain the output of the current layer s, i.e., $\mathbf{h}_s$. For maximum
163 S layers, we get $\mathbf{m}_d = \mathbf{h}_S$. We leave adaptive learning of number of clusters R as future work.

3.3 Probabilistic Decoding with Meta-Learning Optimization

165 After semantic complement, we obtain $\{\mathbf{z}_d^*\}_{d \in \mathcal{D}}$ at Sec. 3.2. We use $\mathbf{Z}_\mathcal{V} = [\mathbf{z}_{w_1}; \mathbf{z}_{w_2}; ...; \mathbf{z}_{w_{|\mathcal{V}|}}] \in$
166 $\mathbb{R}^{K \times |\mathcal{V}|}$ to represent topic-word distribution where each column $\mathbf{z}_w$ is topic distribution of a word w,
167 and each row is to the distribution of a topic over the vocabulary. As in previous topic models [3, 31],
168 we generate the observed support words $\mathcal{S}_d$ by $\hat{\mathbf{d}}_{\mathcal{S}_d} = \sigma(\mathbf{Z}_\mathcal{V} \mathbf{z}_d^*)$. Compared to the ground-truth
169 support words $\mathbf{d}_{\mathcal{S}_d}$, we minimize the generative loss $\mathcal{L}_{\text{gen}} = ||\mathbf{d}_{\mathcal{S}_d} - \hat{\mathbf{d}}_{\mathcal{S}_d}||_2^2$. However, this loss
170 requires inefficient computation over the whole vocabulary. We instead use negative sampling [27].

$$\mathcal{L}_{\text{gen}}(d) = \sum_{w \in \mathcal{S}_d} \Big[(d_w - \hat{d}_w)^2 + \sum_{m=1}^M \mathbb{E}_{w' \sim \Pr_n(w)} (d_{w'} - \hat{d}_{w'})^2 \Big]. \tag{19}$$

171 M is the number of negative samples, and $\Pr_n(w)$ is a noise distribution over vocabulary. $\hat{d}_w =$
172 $\sigma(\mathbf{z}_d^{*\top} \mathbf{z}_w)$. $d_w = 1$ if $w \in \mathcal{S}_d$, otherwise $d_w = 0$. In addition, if d is a long document $d \in \mathcal{D}_{\text{long}}$, we
173 also created its corresponding pruned short version d' with a subset of support words $\mathcal{S}_{d'} \subset \mathcal{S}_d$ at Sec.
174 3.2. Although we do not observe the complete support words for d', its complete topic distribution
175 $\mathbf{z}_{d'}^*$ after semantic complement at Eq. 8 should be able to generate the complete support words $\mathcal{S}_d$.
176 Therefore, together with semantic complement constraint at Eq. 13, we arrive at the complete loss.

$$\mathcal{L}(d) = \mathcal{L}_{\text{gen}}(d) + \mathcal{L}_{\text{con}}(d) + \lambda_{\text{reg}} \mathcal{L}_{\text{reg}}(\theta)$$
$$\text{where} \quad \mathcal{L}_{\text{gen}}(d) = \mathcal{L}_{\text{gen}}(d) + \mathbb{I}(d \in \mathcal{D}_{\text{long}})\lambda_{\text{gen}} \mathcal{L}_{\text{gen}}(d'), \quad \mathcal{L}_{\text{con}}(d) = \mathbb{I}(d \in \mathcal{D}_{\text{long}})\mathcal{L}_{\text{con}}(d). \tag{20}$$

177 $\mathcal{L}_{\text{gen}}(d)$ is generative loss, consisting of document d in the corpus $d \in \mathcal{D} = \mathcal{D}_{\text{long}} \cup \mathcal{D}_{\text{short}}$ and the
178 corresponding pruned short version d' (if $d \in \mathcal{D}_{\text{long}}$). $\mathbb{I}(d \in \mathcal{D}_{\text{long}}) = 1$ if $d \in \mathcal{D}_{\text{long}}$, otherwise 0.
179 $\mathcal{L}_{\text{reg}}(\theta)$ is L2 regularizer for encoding parameters θ. λ_{gen} and λ_{reg} are hyperparameters.

180 **Optimization.** Finally, with the objective of meta-learning at Sec. 2, we reach the optimization:

181 1. *Local update.* Given topic encoder f_θ defined at Sec. 3.1, we optimize encoding parameter θ w.r.t.
182 the generative loss $\mathcal{L}_{\text{gen}}(d)$ on support words $\mathcal{S}_d$ by Eq. 1 and obtain θ_d for each document.

183 2. *Global update.* With encoding parameter θ_d, we compute the overall loss $\mathcal{L}(d)$ on query words
184 $\mathcal{Q}_d$ and optimize all parameters $\Phi = \{\theta, \mu\}$, including encoder parameters θ and parameters μ of
185 missing semantics prediction function g_μ. α_1 and α_2 are local and global learning rate, respectively.

$$\Phi^* = \min_\Phi \sum_{d \in \mathcal{D}} \mathcal{L}(\{\theta_d, \mu\}, \mathcal{Q}_d) \quad \Rightarrow \quad \Phi^* = \Phi - \alpha_2 \nabla_\Phi \sum_{d \in \mathcal{D}} \mathcal{L}(\theta - \alpha_1 \nabla_\theta \mathcal{L}_{\text{gen}}(\{\theta, \mu\}, \mathcal{S}_d), \mathcal{Q}_d).$$
(21)

186 With new parameter $\Phi^* = \{\theta^*, \mu^*\}$, we substitute it for Φ for the next iteration. In contrast to
187 previous topic models that generate the content of given documents only, we further create the short
188 version of long documents for semantic complement, and jointly optimize them.

3.4 Extensions with Auxiliary Data

190 **MCTM with Pretrained Word Embeddings.** Pretrained word embeddings [27, 29] encode word
191 similarity. As in previous works [7, 43], we incorporate them into topic-word distribution $\mathbf{Z}_\mathcal{V} = [z_{k,w}]$
192 to improve topic modeling. We introduce topic embedding $\{\mathbf{t}_k\}_{k=1}^K$ and evaluate cosine similarity
193 between topic k and word w by $\cos(\mathbf{t}_k, \mathbf{h}_w)$. We then combine it with topic-word distribution by
194 $z'_{k,w} = \frac{1}{2}(z_{k,w} + \cos(\mathbf{t}_k, \mathbf{h}_w))$ and obtain a new topic-word distribution $\mathbf{Z}'_\mathcal{V} = [z'_{k,w}]$ for decoding.

195 **MCTM with Document Network.** A document network (e.g., citation network) reveals semantic
196 similarities between connected documents (cited papers discuss related research). A document's
197 degree or number of links exhibits a long-tail distribution. Some link to many neighbors, others to a
198 few. Previously focus was on *textual* semantic complement. We extend MCTM to model *structural*
199 semantic complement for link-scarce documents. We consider generating both observed words and
200 neighbors as a task $\mathcal{T}_d$. As for words, we split the neighbors $\mathcal{N}(d)$ of a document d into support and
201 query neighbors $\mathcal{T}_d = \{\mathcal{S}_d, \mathcal{S}_{\mathcal{N}(d)}, \mathcal{Q}_d, \mathcal{Q}_{\mathcal{N}(d)}\}$, $\mathcal{S}_d$ and $\mathcal{S}_{\mathcal{N}(d)}$ denote support words and neighbors,
202 respectively, and ditto for query sets. We correspondingly extend three modeling components.

203 1. *Encoding.* Previously, we inferred topic distribution $\mathbf{z}_d$ of document d by its textual words at Eq. 6.
204 Here, we extend this process by designing a structural convolutional module.

$$\boldsymbol{\kappa}_d^{(l+1)} = \text{AGG}(\mathbf{W}_3^{(l+1)} \boldsymbol{\kappa}_d^{(l)}, \mathbf{W}_3^{(l+1)} \boldsymbol{\kappa}_{d'}^{(l)} | d' \in \mathcal{S}_{\mathcal{N}(d)}).$$
(22)

205 The topic distribution from encoder f_θ is $\mathbf{z}_d := \frac{1}{2}(\mathbf{z}_d + \boldsymbol{\kappa}_d)$, with both texts $\mathcal{S}_d$ and structure $\mathcal{S}_{\mathcal{N}(d)}$.

206 2. *Semantics complement.* For a long document d, in addition to randomly hiding some words, we
207 also drop some neighbors and create a pruned version d'. Now the missing semantics $\mathbf{m}_d$ should
208 contain both textual and structural information. For GNN function g_μ, we extend Eq. 14 by

$$\mathbf{m}_d = g_\mu(\mathbf{z}_d, \mathbf{z}_w, \mathbf{z}_{d'} | w \in \mathcal{S}_d, d' \in \mathcal{S}_{\mathcal{N}(d)}) = \text{AGG}(\mathbf{U}_{d,1}\mathbf{z}_d, \mathbf{U}_{d,2}\mathbf{z}_w, \mathbf{U}_{d,3}\mathbf{z}_{d'} | w \in \mathcal{S}_d, d' \in \mathcal{S}_{\mathcal{N}(d)}).$$
(23)

209 Scaling has extra input, $\boldsymbol{\gamma}_d = \tanh(\mathbf{W}_\gamma \mathbf{z}_d + \mathbf{W}'_\gamma \bar{\mathbf{z}}_{\mathcal{S}_d} + \mathbf{W}''_\gamma \bar{\mathbf{z}}_{\mathcal{S}_{\mathcal{N}(d)}})$, ditto for shifting. $\bar{\mathbf{z}}_{\mathcal{S}_{\mathcal{N}(d)}} =$
210 $\frac{1}{|\mathcal{S}_{\mathcal{N}(d)}|} \sum_{d' \in \mathcal{S}_{\mathcal{N}(d)}} \mathbf{z}_{d'}$. For Clustering g_μ, we extend input by $\mathbf{h}_0 = [\mathbf{z}_d || \bar{\mathbf{z}}_{\mathcal{S}_d} || \bar{\mathbf{z}}_{\mathcal{S}_{\mathcal{N}(d)}}]$.

211 3. *Decoding with meta-learning.* In addition to generating support words using complemented $\mathbf{z}_d^*$, we
212 also generate support neighbors. The generative loss is similar to Eq. 19 except that *i*) we replace
213 d_w with $e_{d,d'}$, the ground-truth link between d and d'; *ii*) $\hat{e}_{d,d'} = \sigma(\mathbf{z}_d^{*\top} \mathbf{z}_{d'}^*)$. Finally, meta-learning
214 learns how to accurately predict missing semantics $\mathbf{m}_d$ for both textual and structural complement.

4 Experiments

216 The goal of experiments is to evaluate if our model MCTM can improve short text topic modeling
217 through evaluative tasks, e.g., document classification, link prediction, and topic analysis.

218 **Datasets.** Since our model is flexible to incorporate auxiliary data, we rely on four datasets with
219 textual documents, auxiliary word embeddings, and auxiliary network links for experiments. Cora
220 [24] is corpus of academic papers with citations as links. We created two independent datasets,
221 Machine Learning (**ML**) and Programming Language (**PL**). In addition, **HEP-TH** [21] is a corpus of
222 Physics papers with their citations. **Web** [20] is a Web page hyperlink network where each page is a
223 news article, and the hyperlinks connect related articles. See Table 1 for dataset statistics.

224 **Baselines.** Since our model has three variants, i.e., MCTM with plain texts, with auxiliary word
225 embeddings, and with auxiliary document networks, we correspondingly compare to three categories

Table 2: Classification accuracy (in percentage) on four subsets of test set with descending length. Best baselines are underlined. We show improvement of MCTM (G) over GATON and best baseline.

Model	ML					PL				
	Overall	0-25%	25%-50%	50%-75%	75%-100%	Overall	0-25%	25%-50%	50%-75%	75%-100%
ProdLDA	58.5±3.2	69.7±1.0	59.1±4.6	55.8±5.0	48.7±4.6	45.0±2.1	51.4±6.0	48.7±3.6	41.6±2.3	40.1±3.9
WLDA	31.3±0.7	30.9±2.9	31.6±2.2	34.3±1.2	28.2±2.2	33.2±1.8	37.4±1.5	40.0±5.3	28.1±3.9	23.8±1.8
GATON	60.3±2.0	69.3±2.7	62.8±2.5	57.4±1.8	50.8±6.6	47.6±1.5	53.8±3.1	52.4±3.9	44.5±4.9	39.0±3.4
MCTM (G)	**67.1±2.1**	**73.7±3.6**	**68.7±4.3**	**66.4±3.0**	**60.1±1.9**	**53.5±0.8**	59.8±3.5	**57.3±2.8**	**52.9±5.7**	**45.5±2.0**
MCTM (C)	66.9±1.4	73.6±1.5	68.3±2.0	65.2±1.9	58.9±1.8	53.4±0.9	**60.6±3.1**	56.3±1.6	52.5±2.0	42.9±1.3
improvement	11.4% 11.4%	6.3% 5.7%	9.4% 9.4%	15.7% 15.7%	18.3% 18.3%	12.3% 12.3%	11.2% 11.2%	9.3% 9.3%	18.8% 18.8%	16.8% 13.6%
ETM	50.6±2.2	60.4±3.3	52.9±2.5	48.8±2.1	39.4±3.0	43.8±2.0	48.5±2.8	47.9±2.7	42.4±1.9	35.9±4.1
NSTM	45.2±2.6	53.6±1.9	42.4±7.5	43.0±2.3	41.1±4.7	41.3±3.2	47.2±5.3	45.0±5.1	39.8±4.6	33.1±2.4
GATON+WE	63.8±1.5	72.4±2.3	67.0±3.2	60.5±2.2	54.8±2.3	50.2±1.5	57.4±2.3	53.7±3.3	48.7±2.7	40.2±3.1
MCTM+WE (G)	**66.8±2.0**	**72.9±5.1**	**67.7±2.4**	65.3±3.8	**61.6±4.9**	**52.7±1.7**	**60.7±6.1**	**53.9±3.1**	**51.8±1.6**	**43.8±2.6**
MCTM+WE (C)	66.0±1.4	70.9±1.9	67.1±3.1	**67.1±2.8**	58.3±2.7	52.1±1.5	**60.7±2.7**	53.1±2.8	50.5±4.8	43.6±3.6
improvement	4.6% 4.6%	0.7% 0.7%	1.0% 1.0%	7.9% 7.9%	12.3% 12.3%	5.0% 5.0%	5.7% 5.7%	0.3% 0.3%	6.3% 16.3%	9.0% 9.0%
RTM	64.2±2.3	72.9±3.6	71.0±1.7	61.5±4.0	50.6±3.4	53.3±1.1	58.7±3.5	58.9±3.0	52.4±3.4	42.6±2.0
Adj-Enc	71.0±0.4	78.9±0.7	74.6±1.9	72.4±2.1	57.8±1.4	60.4±1.1	63.6±1.9	63.8±1.5	62.6±2.1	52.1±3.7
LANTM	72.1±1.6	74.9±3.1	77.2±1.3	71.6±2.2	64.5±4.5	60.8±0.9	66.5±3.1	61.4±1.5	62.4±1.7	52.4±3.7
GATON+DN	67.7±1.2	74.7±3.3	71.5±3.1	67.8±4.2	58.2±4.7	58.5±2.0	65.4±2.0	62.2±3.1	61.0±1.7	44.3±3.8
meta-tail2vec	58.7±1.6	65.8±4.5	62.0±2.9	59.0±3.7	47.2±4.0	44.9±3.0	51.9±2.6	48.7±3.1	46.6±4.1	31.4±6.8
MCTM+DN (G)	**83.3±1.7**	**86.2±2.9**	**82.7±2.1**	**81.9±2.6**	82.1±2.4	**72.9±1.0**	**77.2±4.3**	**73.9±3.8**	**71.9±3.9**	68.1±2.8
MCTM+DN (C)	83.0±1.2	85.9±0.7	82.0±1.3	81.2±1.1	**82.8±3.9**	71.9±0.7	73.7±3.3	72.9±3.0	71.0±2.1	**70.0±2.5**
improvement	22.9% 15.4%	15.3% 9.2%	15.6% 7.1%	20.9% 13.1%	41.1% 27.3%	24.6% 19.8%	18.2% 16.1%	18.7% 15.7%	18.0% 14.9%	53.7% 29.9%

of baselines. *i*) **Topic models with plain texts**, ProdLDA [31], WLDA [28], and GATON [37]. They model all documents uniformly without dealing with short texts. We compare to them and show the advantage of MCTM on improving short texts. *ii*) **Topic models with word embeddings**, ETM [8] and NSTM [43]. Since our model is built on top of GATON, we also compare to GATON with word embeddings, denoted as GATON+WE. By comparing to them, we verify the effectiveness of semantic complement meta-learning to further improve topic quality. *iii*) **Topic models with document networks**, RTM [5], Adjacent-Encoder [40], LANTM [35], and GATON+DN, which is the extension of GATON with document networks. For document network scenario, we include a graph embedding model, meta-tail2vec [23], which uses meta-learning to improve nodes with low degrees, but is not a topic model and ignores variable lengths of node attributes, i.e., texts.

We set $L = 2$ convolutional layers. $\lambda_{\text{gen}} = 2$ and $\lambda_{\text{reg}} = 0.05$. $M = 5$ and $R = 5$. $\mathscr{L}$ is the median length of the corpus. Local and global learning rates are $\alpha_1 = 0.001$ and $\alpha_2 = 0.0005$. We use 300D Glove embeddings. We experiment with 5 independent runs, report mean and std.dev. All the experiments were conducted on Linux server with a Tesla K80 GPU with 11441MiB. Code and datasets are submitted, to be released upon publication.

Table 1: Dataset statistics.

Name	#Documents	#Links	Vocabulary	#Labels	Avg. #words/doc	Std.Dev. of #words/doc
ML	2,947	8,146	5,814	7	66.7	34.0
PL	2,449	7,274	5,066	9	66.0	36.9
HEP-TH	20,151	234,193	5,001	N.A.	48.4	22.9
Web	116,544	309,499	5,021	N.A.	34.1	70.0

4.1 Quantitative Evaluation

Document Classification. Documents from the same category discuss related topics. As in LDA [3], we conduct classification to evaluate topic quality. We split 80% documents for training (10% are for validation). Labels are not involved during training. After convergence, we train a kNN classifier ($k = 5$) [2] with training documents and predict the labels of test documents. We set 64 topics. We compare our models within each category of baselines and report classification accuracy at Table 2. We split the test set into four subsets with descending document length and report the result of both overall test and each subset. 0-25% at Table 2 means the subset with the longest 25% test documents. MCTM (G) and MCTM (C) denote our model with GNN and Clustering function, respectively.

Our models significantly outperform baselines within each category. We outperform GATON, the best baseline in the plain text and word embedding category, since textual semantic complement improves short texts, and the overall test set is also improved. MCTM (G) performs slightly better than MCTM (C), potentially because GNN recognizes importance of words with attention, while the Clustering function takes simple average. To show our models indeed improve short text quality, we present the improvement of MCTM (G) over both GATON and the best baseline. Our performance generally improves more as the length decreases, which verifies the advantage of semantic complement.

Topic Coherence. Each row of topic-word distribution $\mathbf{Z}_{\mathcal{V}} \in \mathbb{R}^{K \times |\mathcal{V}|}$ is the distribution of one topic over the vocabulary, and the key words of this topic correspond to the highest values on this row. As in ProdLDA [31], we evaluate the coherence of key words by Google Web 1T 5-gram Version 1 [9], with NPMI as metric. Table 3 (left) summarizes the results. Topic-word distribution $\mathbf{Z}_{\mathcal{V}}$ is model

Table 3: Topic coherence NPMI (left, in percentage) and perplexity (right) at $K = 64$.

Model	Topic Coherence NPMI				Perplexity			
	ML	PL	HEP-TH	Web	ML	PL	HEP-TH	Web
ProdLDA	6.3±0.2	9.4±0.5	10.3±0.6	16.2±1.4	7.19±0.00	7.21±0.00	7.72±0.00	8.34±0.00
WLDA	9.7±0.2	11.6±0.1	**13.7±0.4**	**23.9±0.8**	18.90±0.73	19.57±0.30	44.31±0.18	45.22±0.00
GATON	9.9±0.9	8.4±1.5	8.9±1.5	4.8±1.1	9.64±0.27	9.17±0.10	8.79±0.57	8.52±0.12
MCTM (G)	**10.0±1.4**	12.1±1.2	**13.7±1.7**	13.5±2.5	3.81±0.24	3.60±0.51	3.98±0.29	3.27±0.41
MCTM (C)	9.9±2.0	12.0±1.8	13.2±2.1	16.1±1.1	**3.76±0.17**	3.63±0.20	4.12±0.30	**3.13±0.13**
ETM	5.5±0.1	7.7±0.2	7.2±0.4	16.4±0.7	8.67±0.00	8.52±0.00	8.51±0.00	8.52±0.00
NSTM	16.0±1.0	18.6±0.6	18.2±0.5	**27.9±0.6**	8.46±0.00	8.34±0.00	8.39±0.00	8.30±0.00
GATON+WE	16.1±1.4	12.9±1.5	16.9±1.1	12.4±1.1	5.50±0.21	5.56±0.48	8.36±0.02	7.98±0.02
MCTM+WE (G)	**17.6±1.2**	19.1±2.8	18.2±1.3	23.6±0.4	**4.43±0.17**	**4.23±0.56**	**3.36±0.10**	3.18±0.12
MCTM+WE (C)	16.8±1.1	**20.3±1.5**	**18.7±0.9**	23.8±1.0	4.62±0.16	4.62±0.24	3.50±0.17	**3.04±0.12**
RTM	7.3±0.2	8.9±0.5	6.6±0.3	**18.0±0.4**	8.07±0.01	7.93±0.01	8.04±0.00	8.96±0.13
Adj-Enc	8.4±0.4	10.5±0.1	6.4±0.4	7.2±0.5	7.41±0.01	7.34±0.13	7.45±0.19	7.65±0.00
LANTM	9.9±1.2	9.8±0.7	10.4±1.5	N.A.	8.63±0.00	8.48±0.00	8.50±0.00	N.A.
GATON+DN	10.3±0.7	10.7±1.1	9.7±0.8	7.7±2.0	8.58±0.02	8.43±0.00	8.33±0.01	8.13±0.02
MCTM+DN (G)	**11.9±2.0**	**11.1±2.0**	10.6±1.7	15.5±1.1	4.07±0.27	4.12±0.31	**3.99±0.40**	3.21±0.25
MCTM+DN (C)	11.6±1.5	10.3±1.4	10.4±1.5	17.0±1.1	**3.41±0.36**	**3.63±0.46**	4.13±0.23	3.75±0.43

Table 5: Link prediction (in percentage) on overall test set and the shorter half of the test set. Best baselines are underlined. We show the improvement of MCTM (G) over GATON and best baseline.

Model	ML		PL		HEP-TH		Web	
	Overall	Short	Overall	Short	Overall	Short	Overall	Short
RTM	71.4±0.9	67.0±0.6	68.2±0.4	62.2±0.3	69.7±0.8	65.1±0.6	69.9±0.1	75.3±0.1
Adj-Enc	88.1±0.2	86.2±0.3	79.6±0.3	73.8±0.2	88.9±0.1	88.4±0.1	82.7±0.1	78.5±0.2
LANTM	76.5±1.2	76.1±1.6	73.9±0.9	70.5±1.1	86.6±0.0	85.2±0.0	N.A.	N.A.
GATON+DN	74.2±0.4	71.6±0.9	71.6±0.8	65.8±0.6	90.1±0.2	89.1±1.2	74.3±0.2	71.7±0.3
meta-tail2vec	69.7±2.3	66.5±1.5	68.7±1.7	64.3±1.5	N.A.	N.A.	N.A.	N.A.
MCTM+DN (G)	**94.0±0.5**	91.9±1.4	**91.5±0.1**	**90.6±0.8**	**93.9±0.2**	**93.9±0.1**	**83.4±0.1**	**80.5±0.1**
MCTM+DN (C)	93.4±0.5	**92.7±0.7**	91.2±0.8	90.2±0.9	92.5±0.3	92.4±0.4	80.6±0.2	77.5±0.2
improvement	26.6% 6.7%	28.4% 6.6%	27.9% 15.0%	37.7% 22.8%	4.2% 4.2%	5.4% 5.4%	12.2% 0.8%	12.3% 2.5%

parameter and is separate from document length, thus we can not report results of different lengths. LANTM cannot run on large dataset Web. Meta-tail2vec is not a topic model, thus is excluded. Overall, our models outperform baselines on ML and PL and are competitive with the best baseline on HEP-TH and Web. This indicates that our models at least do not hurt topic coherence, but can significantly improve other tasks, e.g., classification. Compared to GATON, our models significantly improve it, verifying the advantage of semantic complement. To understand what topics our models capture, we randomly present two topics with top-5 key words at Table 4. MCTM (G) captures *statistics* and *computational genetics*, while MCTM (C) reveals *scalability* and *geometric learning*.

Perplexity. Topic model should generalize to unseen documents. Following [3], we evaluate perplexity. Since perplexity is exponential and varies much w.r.t. its power, we report its power, $-\frac{\log \Pr(\mathcal{D}_{\text{test}})}{\sum_{d \in \mathcal{D}_{\text{test}}} l_d}$ (lower is better). Table 3 (right) reveals that our models generate high likelihood to unseen documents, which we attribute to semantic complement meta-learning module.

Table 4: Topic interpretability.

Topic	Key words of MCTM (G)
1	variance, probability, generalize, covariance, approximation
2	non-genetic, rnn, stimulus-response, epistasis, mismatch

Topic	Key words of MCTM (C)
1	scalability, multiprocessor, obviate, compute, algorithm
2	sphere, tangent, three-dimensional, vector, geometrical

Link Prediction. A good model should infer similar topics for potentially linked documents. Since we model document network as auxiliary data, we follow RTM [5] and predict links. As in [40], the probability of a link is $p(e_{d,d'}) \propto \exp(-||\mathbf{z}_d^* - \mathbf{z}_{d'}^*||_2^2)$. We predict the links within test documents and compare with the ground-truth links with AUC as metric. Since only the third category (network models) incorporate links, we mainly compare the MCTM+DN version to these network baselines. Table 5 indicates that our models predict links more accurately than baselines. The comparison to network baselines demonstrates the effectiveness of both textual and structural semantic complement.

4.2 Model Analysis

Effect of Semantic Complement. To see if semantic complement helps short texts, we remove it from the complete model and present classification accuracy at Table 6 (left). We show the plain

Table 6: Effect of semantic complement and meta-learning on document classification on ML.

| Model | Effect of Semantic Complement | | | | Effect of Meta-Learning | | | |
| | Overall test set | | Short subset | | Overall test set | | Short subset | |
	with	without	with	without	with	without	with	without
MCTM (G) (decline)	**67.1±2.1**	58.2±2.4 (13.3%)	**60.1±1.9**	50.8±3.8 (15.5%)	**67.1±2.1**	65.9±1.3 (1.8%)	**60.1±1.9**	57.0±3.5 (5.2%)
MCTM (C) (decline)	**66.9±1.4**	56.7±3.1 (15.2%)	**58.9±1.8**	49.4±2.9 (16.1%)	**66.9±1.4**	65.6±1.0 (1.9%)	**58.9±1.8**	56.1±2.4 (4.8%)

text results, and put the auxiliary data version in supplementary. Models do better with semantic complement than without. The accuracy on short subset declines more than the overall test set, which reveals that semantic complement improves short texts, and removing it hurts short documents more.

Effect of Meta-Learning. To analyze if meta-learning benefits the optimization with a few observed words, we replace it with the commonly used stochastic gradient descend. Table 6 (right) shows that result drops more on short subset than on the overall test set, which verifies that meta-learning is good at optimization with only a few observed words and improves short text modeling.

Table 7: Effect of scaling-and-shifting and clustering.

| Model | Scaling and Shifting | | Effect of Clustering | |
	with	without	with	without
MCTM	**67.1±2.1**	65.7±2.9	**66.9±1.4**	62.7±1.6
MCTM+WE	**66.8±2.0**	65.9±1.0	**66.0±1.4**	62.4±1.9
MCTM+DN	**83.3±1.7**	82.4±1.4	**83.0±1.2**	82.4±1.4

Effect of Scaling and Shifting. The GNN version of our model uses scaling-and-shifting method to recover distinct topics. To test its usefulness, we disregard it and summarize classification accuracy on ML at Table 7 (left). Removing scaling and shifting leads to worse performance, since we can not personalize shared parameters to each document to recover its distinct missing topics for complement.

Effect of Clustering. We set the number of clusters R to 1, all documents share the same parameters for missing semantics prediction with no clustering. Table 7(right) concludes that clustering is helpful to share common semantics for related documents and distinguish documents of different clusters.

5 Related Work

Traditional topic models are graphical models [3, 13]. Recent ones are neural models [26], mainly variants of VAE [17]. ProdLDA [31] and DVAE [4] analyze Dirichlet prior. WHAI [41] looks into Gamma prior. The variational divergence metric also attracts attention. WLDA [28] and WAE [32] apply mean maximum discrepancy and generative adversarial network [12]. KATE [6] increases topic sparsity. More recently, topic models are built with graph neural networks [18], e.g., GATON [37], GraphBTM [44], etc. They average losses of all documents regardless of lengths. MCTM designs semantic complement to predict missing semantics for short texts to improve topic quality.

To alleviate scarce word co-occurrences of short texts, existing works leverage auxiliary data, such as word embeddings [27, 29]. Graphical models include GLDA [7], GPUMM [22], LCTM [14], MetaLDA [42], WDL [36], and OTLDA [15]. Neural models include ETM [8] and NSTM [43]. Another category improves short text modeling with document networks, e.g., citation network. RTM [5] and NetPLSA [25] are graphical models. Neural models include NRTM [1], Adjacent-Encoder [40], and LANTM [35]. In contrast, our semantic complement module is agnostic to auxiliary data.

Here, we also briefly review meta-learning works. One category is metric-based, e.g., ProtoNet [30] and MatchingNet [33], which learn a metric function over tasks. Gradient-based meta-learning works optimize model parameters for quick adaptation to new tasks [10, 16, 11, 34, 19, 38, 39].

6 Conclusion

We improve short text topic modeling with semantic complement meta-learning. We complement the semantics for short documents by contrastive learning and design two alternatives for missing semantics prediction. Meta-learning learns how to optimize and predict the missing semantics. One limitation is to assume a variable-length corpus with both long and shot documents for semantic transfer. We also assume the content is truthful. If the corpus is infiltrated by fake news, those may appear in some topics. As future work, we will explore *online learning* to speed up training.

References

[1] Haoli Bai, Zhuangbin Chen, Michael R Lyu, Irwin King, and Zenglin Xu. Neural relational topic models for scientific article analysis. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management*, pages 27–36, 2018.

[2] Christopher M Bishop. *Pattern recognition and machine learning*. springer, 2006.

[3] David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *the Journal of machine Learning research*, 3:993–1022, 2003.

[4] Sophie Burkhardt and Stefan Kramer. Decoupling sparsity and smoothness in the dirichlet variational autoencoder topic model. *Journal of Machine Learning Research*, 20(131):1–27, 2019.

[5] Jonathan Chang and David Blei. Relational topic models for document networks. In *Artificial intelligence and statistics*, pages 81–88. PMLR, 2009.

[6] Yu Chen and Mohammed J Zaki. Kate: K-competitive autoencoder for text. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 85–94, 2017.

[7] Rajarshi Das, Manzil Zaheer, and Chris Dyer. Gaussian lda for topic models with word embeddings. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 795–804, 2015.

[8] Adji B Dieng, Francisco JR Ruiz, and David M Blei. Topic modeling in embedding spaces. *Transactions of the Association for Computational Linguistics*, 8:439–453, 2020.

[9] Stefan Evert. Google web 1t 5-grams made easy (but not for the computer). In *Proceedings of the NAACL HLT 2010 Sixth Web as Corpus Workshop*, pages 32–40, 2010.

[10] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International conference on machine learning*, pages 1126–1135. PMLR, 2017.

[11] Chelsea Finn, Kelvin Xu, and Sergey Levine. Probabilistic model-agnostic meta-learning. *Advances in neural information processing systems*, 31, 2018.

[12] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

[13] Thomas Hofmann. Probabilistic latent semantic indexing. In *Proceedings of the 22nd annual international ACM SIGIR conference on Research and development in information retrieval*, pages 50–57, 1999.

[14] Weihua Hu and Jun'ichi Tsujii. A latent concept topic model for robust topic inference using word embeddings. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 380–386, 2016.

[15] Viet Huynh, He Zhao, and Dinh Phung. Otlda: A geometry-aware optimal transport approach for topic modeling. *Advances in Neural Information Processing Systems*, 33:18573–18582, 2020.

[16] Taesup Kim, Jaesik Yoon, Ousmane Dia, Sungwoong Kim, Yoshua Bengio, and Sungjin Ahn. Bayesian model-agnostic meta-learning. *arXiv preprint arXiv:1806.03836*, 2018.

[17] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[18] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *ICLR*, 2016.

[19] Yoonho Lee and Seungjin Choi. Gradient-based meta-learning with learned layerwise metric and subspace. In *International Conference on Machine Learning*, pages 2927–2936. PMLR, 2018.

[20] Jure Leskovec, Lars Backstrom, and Jon Kleinberg. Meme-tracking and the dynamics of the news cycle. In *Proceedings of the 15th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 497–506, 2009.

[21] Jure Leskovec, Jon Kleinberg, and Christos Faloutsos. Graphs over time: densification laws, shrinking diameters and possible explanations. In *Proceedings of the eleventh ACM SIGKDD international conference on Knowledge discovery in data mining*, pages 177–187, 2005.

[22] Chenliang Li, Haoran Wang, Zhiqian Zhang, Aixin Sun, and Zongyang Ma. Topic modeling for short texts with auxiliary word embeddings. In *Proceedings of the 39th International ACM SIGIR conference on Research and Development in Information Retrieval*, pages 165–174, 2016.

[23] Zemin Liu, Wentao Zhang, Yuan Fang, Xinming Zhang, and Steven CH Hoi. Towards locality-aware meta-learning of tail node embeddings on networks. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management*, pages 975–984, 2020.

[24] Andrew Kachites McCallum, Kamal Nigam, Jason Rennie, and Kristie Seymore. Automating the construction of internet portals with machine learning. *Information Retrieval*, 3(2):127–163, 2000.

[25] Qiaozhu Mei, Deng Cai, Duo Zhang, and ChengXiang Zhai. Topic modeling with network regularization. In *Proceedings of the 17th international conference on World Wide Web*, pages 101–110, 2008.

[26] Yishu Miao, Lei Yu, and Phil Blunsom. Neural variational inference for text processing. In *International conference on machine learning*, pages 1727–1736. PMLR, 2016.

[27] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. *Advances in Neural Information Processing Systems*, 2013.

[28] Feng Nan, Ran Ding, Ramesh Nallapati, and Bing Xiang. Topic modeling with wasserstein autoencoders. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 6345–6381, 2019.

[29] Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

[30] Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, 30, 2017.

[31] Akash Srivastava and Charles Sutton. Autoencoding variational inference for topic models. *ICLR*, 2017.

[32] Ilya Tolstikhin, Olivier Bousquet, Sylvain Gelly, and Bernhard Schoelkopf. Wasserstein auto-encoders. *arXiv preprint arXiv:1711.01558*, 2017.

[33] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. *Advances in neural information processing systems*, 29, 2016.

[34] Risto Vuorio, Shao-Hua Sun, Hexiang Hu, and Joseph J Lim. Multimodal model-agnostic meta-learning via task-aware modulation. *Advances in Neural Information Processing Systems*, 32, 2019.

[35] Yiming Wang, Ximing Li, and Jihong Ouyang. Layer-assisted neural topic modeling over document networks. In *International Joint Conference on Artificial Intelligence*, pages 3148–3154, 2021.

[36] Hongteng Xu, Wenlin Wang, Wei Liu, and Lawrence Carin. Distilled wasserstein learning for word embedding and topic modeling. *Advances in Neural Information Processing Systems*, 31, 2018.

[37] Liang Yang, Fan Wu, Junhua Gu, Chuan Wang, Xiaochun Cao, Di Jin, and Yuanfang Guo. Graph attention topic modeling network. In *Proceedings of The Web Conference 2020*, pages 144–154, 2020.

[38] Huaxiu Yao, Ying Wei, Junzhou Huang, and Zhenhui Li. Hierarchically structured meta-learning. In *International Conference on Machine Learning*, pages 7045–7054. PMLR, 2019.

[39] Huaxiu Yao, Xian Wu, Zhiqiang Tao, Yaliang Li, Bolin Ding, Ruirui Li, and Zhenhui Li. Automated relational meta-learning. In *International Conference on Learning Representations*, 2019.

[40] Ce Zhang and Hady W Lauw. Topic modeling on document networks with adjacent-encoder. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 6737–6745, 2020.

[41] Hao Zhang, Bo Chen, Dandan Guo, and Mingyuan Zhou. Whai: Weibull hybrid autoencoding inference for deep topic modeling. *ICLR*, 2018.

[42] He Zhao, Lan Du, Wray Buntine, and Gang Liu. Metalda: A topic model that efficiently incorporates meta information. In *2017 IEEE International Conference on Data Mining (ICDM)*, pages 635–644. IEEE, 2017.

[43] He Zhao, D Phung, V Huynh, T Le, and W Buntine. Neural topic model via optimal transport, 2020.

[44] Qile Zhu, Zheng Feng, and Xiaolin Li. Graphbtm: Graph enhanced autoencoded variational inference for biterm topic model. In *Conference on Empirical Methods in Natural Language Processing (EMNLP 2018)*, 2018.