Predictive State Propensity Subclassification: A causal inference algorithm for optimal data-driven propensity score stratification

Abstract

We introduce Predictive State Propensity Subclassification (PSPS), a novel learning algorithm for causal inference from observational data. PSPS combines propensity and outcome models into one encompassing probabilistic framework, which can be jointly estimated using maximum likelihood or Bayesian inference. The methodology applies to both discrete and continuous treatments and can estimate unit-level and population-level average treatment effects. We describe the neural network architecture and its TensorFlow implementation for likelihood optimization. Finally we demonstrate via large-scale simulations that PSPS outperforms state-of-the-art algorithms – both on bias for average treatment effects (ATEs) and RMSE for unit-level treatment effects (UTEs).

Keywords: causal inference; multi-task learning; predictive state representation; propensity matching

1. Introduction

Measuring the impact of an intervention on an outcome of interest is ubiquitous across science, business, and engineering. For example, researchers want to find out whether a new drug has the desired effect on blood pressure reduction; advertisers would like to know whether an ad worked to increase sales; or a software company wants to evaluate the impact of a new feature launch on improved user experience. In an ideal world a randomized experiment would be run to estimate the impact of each of these interventions. Randomization ensures balance in expectation on important confounders – variables that affect both who got treated and the outcome – across the different treatment arms allowing for unbiased estimates of the causal effect of the intervention. An experimenter may furthermore block or stratify on certain features in order to ensure balance across treatment assignments for a particular randomization (Bernstein, 1927).

Randomized experiments, however, are not always feasible due to time, cost, legal, or ethical reasons – to name a few. In that case the decision maker has to rely on observational data – otherwise known as a *natural experiment*. The lack of randomization in natural experiments leads to feature imbalances between the treatment arms and thus make identification and estimation of causal effects difficult. Causal inference algorithms for natural experiments cannot rely on randomization, but have to use other means to mitigate the imbalances. As such they are often viewed as tools to help fix broken randomized experiments (Rubin, 2008), by trying to re-create balance between different treatment levels that did not occur due to the lack of randomization.

It is important to emphasize that in order to make good data-driven decisions on how to intervene in real world settings, algorithms have be able to provide unbiased and low-variance causal effect estimates. Learning algorithms that solely optimize for predictive accuracy are likely diametrical to accurate causal effect estimates as they fall victim to selection bias & confounding in natural experiments (Bareinboim et al., 2014).

In this work we introduce *Predictive State Propensity Subclassification* (PSPS), a novel causal learning algorithm that leverages multi-task learning (Ruder, 2017). PSPS follows the Rubin Causal Model (RCM) framework (Imbens and Rubin, 2010) and is in the same vein as matching, IPW and traditional subclassification that aim to fix the broken design of the experiment. Our key contributions are three-fold: a) we incorporate predictive state smoothing (PRESS) (Goerg, 2017, 2018) for the propensity score, which yields a principled data-driven way to obtain the *strata* or *blocks* used in traditional matching approaches; b) the entire causal inference algorithm can be represented as an end-to-end multi-task neural network, which allows for – statistically and computationally – efficient training and inference through a single computational graph; c) we derive a causal loss function that balances predictive performance with properly accounting for selection bias.

1.1. Literature Review

Existing methods that aim to fix broken natural experiments are often based on matching methods (Stuart, 2010) or inverse propensity weighting (IPW) coupled with some outcome modeling. The latter include entropy balancing (Hainmueller, 2012) and double robust estimation (Robins and Rotnitzky, 1995; Hirano et al., 2003; Lunceford and Davidian, 2004). *Subclassification* addresses feature imbalance by creating strata of observations such that within each stratum there is approximate feature balance between treated and control units (Cochran, 1968). While we do not use *do*-calculus (Pearl, 1995), it is worth pointing out that PSPS is a fully probabilistic framework. It is thus straightforward to use its causal predictions and conditional and joint distribution estimates as plug-in to a *do*-calculus based causal inference.

Recently causal inference has also received attention in the machine learning community: for example via counterfactual representation learning (Johansson et al., 2016) or *Dragonnet* (Shi et al., 2019). Section 4 compares PSPS to various methods on causal benchmark datasets.

2. Methodology, Neural Network Architecture & Learning Objectives

Let T be the treatment variable, Y the observed outcome, and $\mathbf{X}$ is a collection of pre-treatment features. For example, the canonical causal estimation scenario is the case of binary treatment, $T \in \{0,1\}$, with continuous outcome $Y \in \mathbb{R}$, and k-dimensional feature space $\mathbf{X} \in \mathbb{R}^k$. We will revisit an example of continuous treatment in Sections 3. Unless specified otherwise though, we intentionally leave the dimensionality and variable types of $(T, Y, \mathbf{X})$ unspecified as the core concepts and derivations also hold for multivariate outcomes and multi-level or continuous treatments.

2.1. Factorization of the Joint Distribution of Treatment & Outcome

Statistically, treatment assignment and application are confounded when learning from non-randomized observational data. In essence many causal methods aim to break this confounding between assignment and the application effect of treatment on the outcome. In PSPS this dual role of treatment is made explicit by decomposing the joint distribution

$$p(Y, T \mid \mathbf{X}) = p_{\theta_Y}(Y \mid T, \mathbf{X}) \cdot p_{\theta_T}(T \mid \mathbf{X}) = p_{\theta_Y}(Y \mid T_{apply}, \mathbf{X}) \cdot p_{\theta_T}(T_{assign} \mid \mathbf{X}), \tag{1}$$

where θ_Y and θ_T parameterize the conditional distributions of Y and T, respectively. The factorization in (1) makes it explicit that T plays two roles: i) once as the output of a propensity model (treatment assignment, T_{assign}), and ii) as an input to an outcome model (treatment application, T_{apply}).

(a) PRESS network with J states for the propensity score $P(T_{assign} \mid \mathbf{X})$.

(b) PSPS as a multi-input multi-output network.

Figure 1: PSPS model architecture: propensity model $P(T \mid \mathbf{X})$ with J states and the full joint model $P(Y, T \mid \mathbf{X})$, where $\mathbf{X}$ are features, T is the treatment, and Y is the outcome; each state s_j has a separate outcome model for $P(Y \mid \mathbf{X}, S = s_j)$. The dual role of treatment T in (1) is explicit as 2 distinct nodes T_{apply} & T_{assign} in the computational graph.

Since assignment and application are confounded we modulate the distribution on the observed outcome $(Y \mid T_{apply}, \mathbf{X})$ with the fact that there was self-selection to treatment $(T_{assign} \mid \mathbf{X})$. This distinction also illustrates that practicioners are truly interested in the effect of *applying* treatment t on unit i with observed features $\mathbf{x}_i$, i.e. $p_{\theta_Y}(Y_i \mid T_{apply} = t, \mathbf{X} = \mathbf{x}_i)$. While treatment assignment and application are the same random variable and data, respectively, we keep the distinction for clarity on the computational graph. Figure 1 shows that T_{assign} and T_{apply} play two different roles: T_{assign} is an output while T_{apply} is an input. It is important to have separate nodes – rather than a single "T" node – as this would result in an incorrect computational representation, and hence implementation.

2.2. Propensity Score Subclassification

Under a randomized-block experiment the propensity score $P(T \mid \mathbf{X})$ is known by construction and the properties of randomization meet the ignorable treatment assignment ("ignorability") assumption (Rosenbaum and Rubin, 1983) allowing for the identification and estimation of causal effects.[1] In a natural experiment treatment assignment is typically unknown and as such the ignorability assumption is usually made on a leap of faith after adjusting for any observed imbalances.

To deal with potential self-selection bias and imbalances between treated and control units, Rosenbaum and Rubin (1985) proposed *subclassification*, which stratifies units by a coarsened value of predicted propensity scores $\hat{P}(T \mid \mathbf{X})$, – usually achieved by binning; it is also often accompanied by a model-based adjustment to deal with any remaining imbalances. The idea being that obser-

---

1. Causal effect identification and the assumptions needed to link potential outcomes under different treatments to the observed data are well established and will not be examined in detail (see Rubin, 2005). Although we too make these assumptions, our focus is on creating an estimator with good performance that adjusts for the observed imbalances.

vations within each bin have approximately the same propensity score and thus are more robust to any misspecification in the outcome models of each bin. The (predicted) outcome for treated and controls can then be compared within each stratum to estimate the effect of treatment.

One common problem with propensity score subclassification is that there are little to no guidelines on how to actually create the subclasses. Common heuristics are to a) bin on quantiles, b) have equally sized bins, or c) try to at least make the largest bin size moderately small. Imbens and Rubin (2015) create bins recursively by testing equality of propensity score means between treated and control via a t-test. If the difference is significant then the stratum is split at the median and the procedure repeats on sub-strata until the test statistic is not significant or a pre-specified minimum number of treated and controls are met. The end result, however, is inevitably an ad-hoc heuristic.

2.3. Predictive States As The Optimal Data-Driven Subclassification

PSPS follows the same experimental design as traditional subclassification except for how subclasses are created and how subsequent analyses take place. The core causal assumptions such as "ignorability" are the same and we rely on these established results (Imbens and Rubin, 2015).

PSPS puts the goal of constructing subclasses front and center by learning the optimal stratification directly from the observed data using Predictive State Smoothing (PRESS) (Goerg, 2017, 2018). PRESS represents the conditional predictive distribution $p(T \mid \mathbf{X})$ as a mixture over J latent predictive states, $\{s_1(\mathbf{X}), \ldots, s_J(\mathbf{X})\}$ (Figure 1). Each state is an equivalence class over distribution space such that observations with the same conditional distribution are in the same predictive state. That is $\mathbf{X}_{i_1}$ and $\mathbf{X}_{i_2}$ have the same state s_j if and only if

$$p(T \mid \mathbf{X}_{i_1}) \equiv p(T \mid \mathbf{X}_{i_2}) = p(T \mid s_j). \tag{2}$$

The key insight here is that predictive states are exactly the strata $\{s_1, \ldots, s_J\}$ that would have ideally been blocked on when assigning treatment: knowing the predictive state of observation i – which is unobserved in a natural experiment –would be sufficient to knowing the propensity score distribution of all observations in that state.

Predictive states are also minimal sufficient for prediction, i.e., they make T conditionally independent of $\mathbf{X}$ given s_j (Goerg, 2017). Hence the propensity score equals

$$p(T \mid \mathbf{X}) = \sum_{i=1}^{J} p(S = s_j \mid \mathbf{X}) \cdot p(T \mid S = s_j, \mathbf{X}) = \sum_{i=1}^{J} w_j(\mathbf{X}) \cdot p(T \mid S = s_j), \tag{3}$$

where $w_j(\mathbf{X}) := p(S = s_j \mid \mathbf{X})$ denote the probability that $\mathbf{X}$ belongs to state s_j.

We use the weight-vector notation $\mathbf{w} = (w_1, \ldots, w_J)$ as the representation of the state space mapping; by definition $\sum_{j=1}^{J} w_j = 1$ and $w_j \geq 0$. It is easy to see that two observations i_1 and i_2 – with potentially different features $\mathbf{X}_{i_1}$ and $\mathbf{X}_{i_2}$ – that are mapped to the same predictive state with same probabilities, i.e., $\mathbf{w}_{i_1} \equiv \mathbf{w}_{i_2}$, necessarily have the same treatment distribution since $p(T_i \mid \mathbf{X}_i) = \sum_{j=1}^{J} w_{i,j} \cdot p(T_i \mid s_j)$. Put in other words, if i_1 and i_2 have different observed features, $\mathbf{x}_{i_1}$ and $\mathbf{x}_{i_2}$, but are in the same state, s_j, then they have the same propensity score:

$$P(T_i \mid \mathbf{X} = \mathbf{x}_{i_1}, S = s_j) = P(T_j \mid S_j) = P(T_j \mid \mathbf{X} = \mathbf{x}_{i_2}, S = s_j). \tag{4}$$

This is exactly the underlying goal of traditional subclassification by Imbens and Rubin (2015). Another way of thinking about it is that each state is a matched group where matching occurs based on an optimal distance between units i_1 and i_2 with features $\mathbf{X}_{i_1}$ and $\mathbf{X}_{i_2}$ measured as the distance between propensity score distributions $P(T_{i_1} \mid \mathbf{X}_{i_1})$ and $P(T_{i_2} \mid \mathbf{X}_{i_2})$.

2.4. Combining Outcome Models Across Predictive States

After constructing the subclasses, PSPS follows the traditional subclassifcation philosophy of training an outcome model in each subclass (Figure 1). This has the effect of adjusting for features if the PRESS propensity model is misspecified. Even when it is correctly specified, more accurate outcome models can further reduce the variability in causal effect estimates (Rosenbaum, 2002).

To replicate the behavior of estimating the causal effect within each subclass we use the propensity model predictive states to factorize the conditional outcome distribution in (1) as

$$
\begin{aligned}
p(Y_i \mid T_i, \mathbf{X}_i) &= \sum_{j=1}^{J} p(S = s_j \mid \mathbf{X}_i, T_i) \times p(Y_i \mid T_i, \mathbf{X}_i, S = s_j) \\
&= \sum_{j=1}^{J} \frac{p(T_i \mid S = s_j)}{p(T_i \mid \mathbf{X}_i)} \cdot P(S = s_j \mid \mathbf{X}_i) \times p_{\theta_Y^{(j)}}(Y_i \mid T_i, \mathbf{X}_i), \\
&= \sum_{j=1}^{J} (\rho_{i,j} \cdot w_{i,j}) \times p_{\theta_Y^{(j)}}(Y_i \mid T_i, \mathbf{X}_i),
\end{aligned}
\tag{5}
$$

where the lift ratio $\rho_{i,j} \in [0, \infty)$ quantifies how much the state predictive distribution, $p(T_i \mid s_j)$, differs from the point prediction of the propensity score for feature $\mathbf{x}_i$, $p(T_i \mid \mathbf{X}_i = \mathbf{x}_i)$, and $\theta_Y^{(j)}$ parameterizes the outcome model in state j. Since $v_{i,j} := \rho_{i,j} \cdot w_{i,j} = P(S = s_j \mid \mathbf{X}_i, T_i)$ is a proper probability mass function for each i, the decomposition in (5) is a mixture over state-conditional outcome models, $p_{\theta_Y^{(j)}}(Y \mid T, \mathbf{X})$, where model j contributes with weight $v_{i,j}$ to the final estimate for unit i. That means observation i is only partially contributing to state j and also explains why, in general, outcome model parameter estimates will be different for every state.[2]

Consider the special case where each unit i is mapped exactly to one state with probability 1 (i.e., a deterministic mapping), then also $\rho_{i,j} = 1$ for exactly one j and 0 otherwise. In that case,

$$
p(Y_i \mid T_i, \mathbf{X}_i) = \sum_{j=1}^{J} p_{\theta_Y^{(j)}}(Y_i \mid T_i, \mathbf{X}_i, S = s_j) \cdot \mathbb{1}(S = s_j)_{\mathbf{X}_i},
\tag{6}
$$

which is equivalent to binning propensity scores and training an outcome model in each bin. Thus, PSPS is a probabilistic generalization of traditional – and often heuristic – propensity score binning.

2.5. Model Training via Multi-Task Learning

Since PSPS provides a consistent causal probabilistic framework, we use maximum likelihood estimation (MLE) as the primary learning strategy; we leave Bayesian inference for future work.

Decomposing the joint distribution in (1) allows us to specify propensity model and outcome models separately, yet link them through their joint log-likelihood function as

$$
\ell(\theta_Y, \theta_T; Y, \mathbf{X}, T) = \ell(\theta_Y; Y, \mathbf{X}, T_{apply}) + \ell(\theta_T; \mathbf{X}, T_{assign}),
\tag{7}
$$

where $\ell(\tau; Z) := \log p_\tau(Z)$ is the log-likelihood of τ for data Z. This decomposition, also used for Targeted MLE (TLME) (Van der Laan and Rose, 2011), naturally leads to framing parameter

---

2. Each state could be equipped with their own model class, e.g., a Random Forest in j_1, a linear model in j_2, and a deep net in j_3. In practice, they are usually of the same model family – with different (estimated) parameters per state.

estimation as a multi-task learning problem (Ruder, 2017) with a negative log-likelihood loss

$$L(Y,T,\hat{Y}(\theta_Y,\theta_T;\mathbf{X},T_{apply}),\hat{T}_{assign}(\theta_T;\mathbf{X})) = L(Y,\hat{Y}(\theta_Y,\theta_T;\mathbf{X},T_{apply})) + L(T_{assign},\hat{T}_{assign}(\theta_T;\mathbf{X})),$$
$$\text{joint loss} = \text{outcome model loss} + \text{propensity model loss},$$
$$(8)$$

where $\hat{T}_{assign}(\theta_T;\mathbf{X})$ is the predicted propensity of assigning treatment and $\hat{Y}(\theta_Y,\theta_T;\mathbf{X},T_{apply})$ is the predicted outcome when applying treatment. The MLE can be obtained by solving

$$\widehat{(\theta_Y,\theta_T)}_{MLE} = \arg\min_{\theta_Y,\theta_T} L(Y,T,\hat{Y}(\theta_Y,\theta_T;\mathbf{X},T_{apply}),\hat{T}_{assign}(\theta_T;\mathbf{X})). \qquad (9)$$

For randomized experiments the second term (8) is constant since T is independent $\mathbf{X}$; hence PSPS reduces to a simple outcome model when faced with properly randomized treatment.

2.6. Separation of Design and Analysis

In observational studies, practitioners often face a choice between only training an outcome model ($P(Y \mid T,\mathbf{X})$) or a two-step procedure of training a propensity model first ($P(T \mid \mathbf{X})$) and an adjusted/weighted outcome model later. PSPS includes both approaches as special cases, and allows practitioners to gradually move between them using a tunable hyperparameter.

The decomposition in (8) can be seen as trying to find an optimal outcome model, but with a penalty for bad propensity models. It is then natural to introduce a penalty parameter, $\lambda \in [0,\infty)$,

$$L(Y,\hat{Y}(\theta_Y,\theta_T)) + \lambda \cdot L(T,\hat{T}(\theta_T)), \qquad (10)$$

which reduces to (8) when $\lambda = 1$. This can be interpreted as just training a single outcome model $Y \mid T,\mathbf{X}$, with a penalty $L(T,\hat{T}(\theta_T))$ that adjusts for feature distribution imbalances between treated and controls (see also counterfactual representation learning in Johansson et al., 2016).

When $\lambda = 0$ the second term vanishes from (10) and the optimizer only focuses on outcome models, weighted by a random mixture of predictive state weights from each state, which – in expectation – is just a simple overall outcome model. For $\lambda \to \infty$ the optimizer first tries to obtain optimal propensity score, and only then will it further tune the outcome model parameters to improve total loss (at the given optimal propensity score loss). Thus for $\lambda \to \infty$ optimizing (10) approximates the standard two-step approach that separates design and analysis stages of an experiment.

2.7. Binary Treatment & Gaussian Outcomes

In this section we describe parameter estimation in randomized or natural experiments for the most comment practical scenario: binary treatment and a continuous, univariate outcome.[3] It is also this scenario that we evaluate through simulation studies in Section 4.

For binary treatment the negative log-likelihood for observation i is binary cross-entropy

$$L(T_i,\hat{T}_i(\theta_T)) = -\left[T_i \cdot \log(\hat{T}_i(\theta_T)) + (1-T_i) \cdot \log(1-\hat{T}_i(\theta_T)) \right]. \qquad (11)$$

---

3. Other scenarios such as continuous treatment can be handled analogously by adapting the likelihood functions.

Algorithm 1: Two-step iterative training for PSPS
Input: number of states J; data: treatment $\mathbf{t}$; features $\mathbf{X}$; outcome $\mathbf{y}$
Output: trained models: 1 propensity model and J outcome models

1. Train PRESS model for $P(T \sim \mathbf{X})$ with J predictive states $\{s_1, \ldots s_J\}$.

2. Compute predicted weights $w_{i,j} = \hat{p}(s_j \mid \mathbf{X}_i)$ and $v_{i,j} = \hat{p}(s_j \mid \mathbf{X}_i, T_i)$.

3. for $j = 1, \ldots, J$:
      Train a *weighted* outcome model for $P(Y \mid \mathbf{X}, T)$, where sample i is weighted by $v_{i,j}$.

   The outcome models could be a neural net, a regression, or even just the sample mean of the response; $Y \mid \mathbf{X}, T = 1$ and $Y \mid \mathbf{X}, T = 0$ can also be modeled separately.

For univariate continuous outcomes a Normal log-likelihood, $N(y \mid x, \sigma_\varepsilon^2)$, is a natural candidate leading to a weighted sum of outcome losses for each state:

$$L(Y_i, \hat{Y}_i(\theta_Y); \theta_T, \mathbf{X}_i) = -\log(\sigma_\varepsilon) + \frac{1}{2\sigma_\varepsilon^2} \sum_{j=1}^{J} v_{i,j}(\mathbf{X}_i, \theta_T) \cdot (Y_i - \hat{Y}_i(\theta_{Y,j}))^2, \qquad (12)$$

where $v_{i,j}(\mathbf{X}_i, \theta_T)$ is the probability of unit i belonging to state j, $\hat{Y}_i(\theta_Y)$ is the outcome model prediction for Y_i, and $\theta_Y = \{\sigma_\varepsilon\} \cup \{\theta_j \mid j = 1, \ldots, J\}$ are all free parameters of the outcome model, with $\sigma_\varepsilon \in \theta_Y$ as the unknown standard deviation of the residual, $Y_i - \hat{Y}_i$. The average loss across N observations equals

$$\frac{1}{N} \sum_{i=1}^{N} L(Y_i, \hat{Y}_i(\theta_Y); \theta_T, \mathbf{X}_i) - \frac{1}{N} \sum_{i=1}^{N} \left[T_i \cdot \log(\hat{T}_i(\theta_T; \mathbf{X}_i)) + (1 - T_i) \cdot \log(1 - \hat{T}_i(\theta_T; \mathbf{X}_i)) \right]. \qquad (13)$$

It is worth to point out that the PRESS propensity model parameters, θ_T, do not only enter (13) via the binary crossentropy propensity loss in (11), but also affect the outcome loss (12) through the weighting over the J states, $v_{i,j}(\mathbf{X}_i, \theta_T)$.

Algorithm 1 describes an iterative learning procedure to optimize (13). However, since PSPS models the joint distribution directly, it can be expressed as a single computational graph using standard neural network architectures (Fig. 2.1). This has the benefit of training all parameters and predictive states jointly, which avoids the – statistically and computationally – inefficient iterative procedure. In particular, the proposed MLE optimization and causal effect inference runs entirely within a single TensorFlow graph (Abadi et al., 2016), which in turn can be easily incorporated into larger graphs that rely on causal inference as part of their computation.

2.8. Model Complexity and Parameter Tuning

PSPS is built on a single PRESS model to approximate $P(T \mid \mathbf{X})$ using J states, while simultaneously training outcome models in all J states at once. There are no restrictions on the complexity of the function spaces to approximate $P(Y \mid \mathbf{X}, T)$ and $P(T \mid \mathbf{X})$, respectively. One thus faces a trade-off between better approximating $p(T \mid \mathbf{X})$ by increasing J versus reducing J to avoid over-parameterization of the full model – especially the J outcome model parameters $(\theta_1, \ldots, \theta_J)$.

We can give a rule-of-thumb for this trade-off based on double robustness (Robins and Rotnitzky, 1995), which states that causal effects can be estimated consistently even if one of the propensity or the outcome model is misspecified. From that point of view, it is clearly preferable to get *one* propensity model right, rather than trying to specify *all J* outcome models correctly.

This aligns with simulation findings that a more complex propensity model (e.g., several hidden layers feeding into predictive states) combined with simple (e.g., linear) outcome models is sufficient to get unbiased causal effect estimates. We also found that shallow neural networks with standard activation functions help reduce variance of treatment effect estimates. For specific datasets in practice we recommend selecting J and the neural network architectures based on cross-validation.

3. Estimating Causal Effects

Once the predictive state mapping and all outcome models have been trained, unit-level treatment effect (UTE) can be obtained as a weighted average of UTEs within each state:

$$\hat{\Delta}_i^{t+\varepsilon} = \sum_{j=1}^{J} \hat{v}_{i,j} \cdot \Delta_i^{t+\varepsilon}(j) = \sum_{j=1}^{J} P(s_j \mid \mathbf{x}_i, \hat{\theta}_T) \cdot \left(\mathbb{E}(y \mid t_i = t + \varepsilon, \mathbf{x}_i; \hat{\theta}_j) - \mathbb{E}(y \mid t_i = t, \mathbf{x}_i; \hat{\theta}_j) \right), \quad (14)$$

where $\hat{\Delta}_i(j)$ is the estimated treatment effect for unit i from outcome model j, and ε is a discrete (continuous) value for categorical (continuous) treatment. Estimates for sample, population and conditional treatment effects can be obtained by aggregating over the appropriate (sub-)sample of observations. For example, average treatment effect (ATE) and average treatment effect on the treated (ATT) can be estimated as

$$\hat{\Delta}_{\text{ATE}}^{t+\varepsilon} = \frac{1}{N} \sum_{i=1}^{N} \hat{\Delta}_i^{t+\varepsilon} \quad \text{and} \quad \hat{\Delta}_{\text{ATT}}^{t+\varepsilon} = \frac{1}{\sum_{i=1}^{N} T_i} \sum_{i=1}^{N} T_i \cdot \hat{\Delta}_i^{t+\varepsilon}. \quad (15)$$

3.1. Uncertainty Estimates

While in predictive learning tasks point predictions are of primary interest, in causal inference tasks getting accurate uncertainty estimates around the causal effect are equally – if not more – important. A good causal estimator produces narrow confidence intervals with proper coverage. For simulations in Section 4, we use standard bootstrap procedures (Efron and Tibshirani, 1986) to obtain empirical confidence intervals for Δ_i and Δ_{ATE} in (14) and (15), respectively.

4. Model Evaluation: Simulation Study

We compare PSPS to several state-of-the-art causal inference methods: an elastic net linear outcome model (Zou and Hastie, 2005), doubly robust inverse propensity weighted (DRIPW) models (Chan et al., 2010) – both linear and Random Forest (Breiman, 2001) versions –, entropy balancing (Hainmueller, 2012), a PRESS outcome model (Goerg, 2017)[4] and *Dragonnet* (Shi et al., 2019).[5]

---

4. This PRESS outcome model is not tied to the PRESS architecture underlying the PSPS propensity model. It is simply an alternative neural network outcome model for $P(Y \mid \mathbf{Z})$, with $\mathbf{Z} = (\mathbf{X}, T)$ as the features, which happens to use a PRESS architecture – with entirely different hyperparameters and output activations. The states from this outcome-only model are not related to the PSPS predictive states.

5. To make Dragonnet comparable to PSPS we ensured that both network architectures contain the roughly same number of trainable parameters and only used Scaled Exponential Linear Unit (SELU) activations (Klambauer et al., 2017).

All of the above algorithms – with the exception of entropy balancing – can not only estimate the average treatment effect (ATE), but also unit-level treatment effects (UTE) (this is equivalent to the conditional average treatment effect (CATE) in our setup). We conduct a simulation study on standard causal inference benchmarks and examine performance on ATE bias and UTE RMSE:

$$\text{ATE bias} = \Delta_{ATE} - \hat{\Delta}_{ATE} \text{ and RMSE UTE} = \sqrt{\frac{1}{N}\sum_{n=1}^{N}(\Delta_i^{0\rightarrow1} - \hat{\Delta}_i^{0\rightarrow1})^2}. \qquad (16)$$

For each simulation we train a $J = 10$ PSPS model on an 80/20 train/test split and early stopping.

Figures 2 and 3 depict each run from a single simulated dataset as a point in the graph. The boxplots give a sense of bias and spread of ATE, where a method with the same average (median) bias but smaller variance is preferred. Similarly, the boxplots of RMSE summarize UTE estimation performance for each simulation. This visualization is in lieu of the average bias as by construction the sample mean of the estimated UTEs for each dataset in the simulation is the estimated ATE for that dataset (see (15)); hence the average bias is equivalent to the bias for ATE.

4.1. Kang & Schafer: Learning Non-Linear Causal Effects

Kang and Schafer (2007) present a simulation based on a real case study, where four features are drawn independently from a standard Normal, $\mathbf{z} = (z_1, z_2, z_3, z_4) \sim N(0, I_4)$, and the outcome and true propensity score π are generated as

$$y = 210 + 27.4z_1 + 13.7z_2 + 13.7z_3 + 13.7z_4 + \varepsilon, \quad \pi = \text{expit}(-z_1 + 0.5z_2 - 0.25z_3 - 0.1z_4)$$

respectively ($\varepsilon \sim N(0,1)$). The original features (z_1, z_2, z_3, z_4) are then transformed as

$$x_1 = \exp(z_1/2), \quad x_2 = x_2/(1 + \exp(z_1)) + 10 \quad x_3 = (z_1 z_3/25 + 0.6)^3, \quad x_4 = (z_2 + z_4 + 20)^2.$$

This allows us to evaluate causal methods against correctly and incorrectly specified models by either using the original ($\mathbf{z}$) or transformed features ($\mathbf{x}$). This is particularly important for practitioners to see how well methods such as PSPS, PRESS, Dragonnet, and DRIPWRandomForest can approximate – in practice unknown – non-linear dependencies in real world data.

Figure 2 summarizes the results on bias & RMSE. In the "Original" (linear) case, only entropy balancing and PSPS are unbiased; all other methods show medium to strong bias. Interestingly, the elastic net LinearOutcomeModel is slightly biased on the causal estimate with very small RMSE, even though the true response surface is linear in the features. We hypothesize that this can be attributed to incorrectly tuned ℓ_1 and ℓ_2 penalties in the elastic net cross validation, as it optimizes for predictive power, not accurate causal estimation.

In the "Transformed" case entropy balancing does significantly worse on ATE bias.[6] PSPS on the contrary is effectively unbiased and has the smallest UTE RMSE amongst all methods. Given that in practice, cause and effect are rarely – if ever – linearly related, this comes to show that PSPS is a great choice for estimating causal effects from data collected in real world – non-linear – settings. Figure 2 shows that only PSPS and entropy balancing have close to proper confidence interval coverage with small widths in the "Original" case; in the "Transformed" case PSPS is the only algorithm that has proper confidence intervals. Interestingly, PSPS not only outperforms

---

6. Recall that entropy balancing is not able to provide UTE estimates.

(a) ATE bias and UTE RMSE.

(b) 95% bootstrap confidence interval coverage and width. DRIPW linear model results are outliers in "Transformed" case and thus not shown for better visualization (CI width of 45.2; coverage of 0.7).

Figure 2: Model comparison for Kang & Schafer (Section 4.1)

parametric & linear models but also significantly improves on Dragonnet, which shows significant bias for ATE and is unable to produce confidence intervals at any reliability even in the linear case.

4.2. Lunceford & Davidian: Feature Selection

Lunceford and Davidian (2004) proposed another benchmark simulation where the data also consists of $\{(\mathbf{X}_i, \mathbf{Z}_i, T_i, Y_i), i = 1, \cdots, n\}$, but all of them are observed. Both $\mathbf{X}_i$ and $\mathbf{Z}_i$ are three dimensional vectors. The propensity score is only related to $\mathbf{X}$ – not $\mathbf{Z}$ – through $\pi = \text{expit}\left(\beta_0 + \sum_{j=1}^{d} \beta_j \mathbf{X}_{i,j}\right)$, where β controls the association between $\mathbf{X}$ and T. We follow the original work and use

$$\beta^{no} = (0,0,0,0)^T, \quad \beta^{moderate} = (0,0.3,-0.3,0.3)^T, \quad \beta^{strong} = (0,0.6,-0.6,0.6)^T.$$

The response Y is generated according to

$$Y_i = \nu_0 + \sum_{j=1}^{3} \nu_j \mathbf{X}_{ij} + \nu_4 T_i + \sum_{j=1}^{3} \xi_j Z_{ij} + \varepsilon_i, \quad \varepsilon_i \sim N(0,1) \tag{17}$$

where $\nu = (0,-1,1,-1,2)^T$. Similarly to β, ξ controls the association between $\mathbf{Z}$ and Y:

$$\xi^{no} = (0,0,0)^T, \quad \xi^{moderate} = (-0.5,0.5,0.5)^T, \quad \xi^{strong} = (-1,1,1)^T.$$

The joint distribution of $(\mathbf{X}_i, \mathbf{Z}_i)$ is given by $\mathbf{X}_{i3} \sim$ Bernoulli(0.2), then generate $\mathbf{Z}_{i3}$ as Bernoulli with $P(\mathbf{Z}_{i3} = 1 \mid \mathbf{X}_{i3}) = 0.75 \cdot \mathbf{X}_{i3} + 0.25 \cdot (1 - \mathbf{X}_{i3})$. Conditional on $\mathbf{X}_{i3}$, $(\mathbf{X}_{i1}, \mathbf{Z}_{i1}, \mathbf{X}_{i2}, \mathbf{Z}_{i2})$ is then generated as multivariate normal $N(a_{\mathbf{X}_{i3}}, B_{\mathbf{X}_{i3}})$, where $a_1 = (1,1,-1,-1)^T, a_0 = (-1,-1,1,1)^T$ and

$$B_0 = B_1 = \begin{pmatrix} 1 & 0.5 & -0.5 & -0.5 \\ 0.5 & 1 & -0.5 & -0.5 \\ -0.5 & -0.5 & 1 & 0.5 \\ -0.5 & -0.5 & 0.5 & 1 \end{pmatrix}. \tag{18}$$

(a) ATE bias (top) and UTE RMSE (bottom).

(b) 95% bootstrap confidence interval coverage and width

Figure 3: Model comparison for Lunceford & Davidian (Section 4.2)

This data generation process yields a true population ATE of $\Delta_{ATE} \equiv 2$. Estimating the ATE accurately is challenging in this simulation scenario given various inter- and intra-dependence of $\mathbf{X}$ and $\mathbf{Z}$, while $\mathbf{Z}$ is only influencing the outcome – not the propensity score.

Figure 3 shows that PSPS, linear DRIPW, entropy balancing, and DRIPW perform equally well in all cases. As for Kang & Schafer this is quite compelling for PSPS as it is on par with parametric linear models, while being able to learn non-linearities if data supports it. Random Forest outcome models and Dragonnet increase in ATE bias for stronger associations. Interestingly, both a linear and Random Forest DRIPW model have difficulty estimating UTEs – compared to competing models with low RMSE. Whilst consistently having the second lowest RMSE (after LinearOutcomeModel) the ATE bias of Dragonnet increases as the association between features and treatment increases. Appendix B has additional results from another causal simulation benchmark (Radcliffe, 2007).

4.3. Balancing Outcome and Treatment Model Performance

A key aspect of PSPS compared to other causal or solely predictive models is the joint optimization of the (treatment, outcome) loss. The decomposition in (10) makes it clear that solely maximizing predictive power for the outcome will produce substantially worse causal estimates compared to an algorithm that strikes a balance between a good treatment model at the cost of some reduction in predictive power in the outcome models.

The simulation study allows us to replicate this empirically. Figure 4 shows the R-squared of the underlying outcome model when predicting $\hat{y}$ versus the ATE bias for each dataset. As expected, methods with a higher R-squared are not guaranteed to achieve a better ATE bias reduction: PSPS often achieves zero bias even though it has a lower R-squared than other methods; vice-versa, even though RandomForestDRIPW and Dragonnet have the best predictive performance they fail to obtain unbiased ATE estimates.

Figure 4: R-squared of outcome model vs. ATE bias. For marginal bias see Figure 2 and 3.

4.4. Selecting the Number of States

The number of states J is a hyperparameter of PRESS that controls the smoothness of the learned prediction function. The degenerate $J = 1$ case corresponds to a single outcome model with all observations falling in the same global state. As J increases, the propensity score distribution can be approximated more closely while at the same time the number of observations per state decreases at a rate of J^{-1}. To explore how the choice of J affects PSPS performance we undertake a simulation study where we train PSPS models with $J = 1$ (degenerate), 2, 3, 5, 10, and 20.

We observe that as long as J is in a *reasonable* range of $O(1) - O(10)$ the models differ only slightly in their estimation performance.[7] The results also align with the theoretical underpinning of PRESS being a semi-parametric kernel smoother that is quite robust to too large values of J: as long as J is sufficiently large to obtain good coverage on the unit (propensity score) interval, the actual choice of J is secondary to obtain well-performing causal estimates.

5. Discussion

We introduce *predictive state propensity subclassification* (PSPS), a novel algorithm for causal inference that follows the Rubin Causal Model (RCM) framework by adjusting natural experiments through propensity models following a subclassification approach. However, rather than using ad-hoc procedures to bin observations by propensity score, PSPS estimates outcome models, propensity models, and optimal strata simultaneously as part of a joint probabilistic model. This yields efficient training algorithms that can be easily implemented in deep learning frameworks like TensorFlow. We show on several benchmark simulations that PSPS has excellent statistical properties, with practically zero bias & low variance and the only method with proper confidence interval coverage compared to several state-of-the-art causal inference algorithms in the statistical and machine learning literature.

---

7. See Appendix B.2 for detailed results.

References

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Gregory S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian J. Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Józefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Gordon Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul A. Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda B. Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. Tensorflow: Large-scale machine learning on heterogeneous distributed systems. *CoRR*, abs/1603.04467, 2016. URL http://arxiv.org/abs/1603.04467.

Elias Bareinboim, Jin Tian, and Judea Pearl. Recovering from selection bias in causal and statistical inference. *Proceedings of the AAAI Conference on Artificial Intelligence*, 28(1), Jun. 2014. URL https://ojs.aaai.org/index.php/AAAI/article/view/9074.

Serge Bernstein. Sur l'extension du théorème limite du calcul des probabilités aux sommes de quantités dépendantes. *Mathematische Annalen*, 97(1):1–59, 1927.

Leo Breiman. Random forests. *Mach. Learn.*, 45(1):5–32, October 2001. ISSN 0885-6125. doi: 10.1023/A:1010933404324. URL https://doi.org/10.1023/A:1010933404324.

David Chan, Rong Ge, Ori Gershony, Tim Hesterberg, and Diane Lambert. Evaluating online ad campaigns in a pipeline: Causal models at scale. In *Proceedings of the 16th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '10, pages 7–16, New York, NY, USA, 2010. ACM. ISBN 978-1-4503-0055-1. doi: 10.1145/1835804.1835809. URL http://doi.acm.org/10.1145/1835804.1835809.

William G Cochran. The effectiveness of adjustment by subclassification in removing bias in observational studies. *Biometrics*, pages 295–313, 1968.

Thomas M. Cover and Joy A. Thomas. *Elements of Information Theory (Wiley Series in Telecommunications and Signal Processing)*. Wiley-Interscience, USA, 2006. ISBN 0471241954.

B. Efron and R. Tibshirani. Bootstrap methods for standard errors, confidence intervals, and other measures of statistical accuracy. *Statist. Sci.*, 1(1):54–75, 02 1986. doi: 10.1214/ss/1177013815. URL https://doi.org/10.1214/ss/1177013815.

Georg M. Goerg. Predictive State Smoothing (PRESS): Scalable non-parametric regression for high-dimensional data with variable selection. Technical report, Google, 2017. URL https://ai.google/research/pubs/pub46141.

Georg M. Goerg. Classification using Predictive State Smoothing (PRESS): A scalable kernel classifier for high-dimensional features with variable selection. Technical report, Google, 2018. URL https://ai.google/research/pubs/pub46767.

Jens Hainmueller. Entropy balancing for causal effects: A multivariate reweighting method to produce balanced samples in observational studies. *Political Analysis*, 20(1):25–46, 2012.

Keisuke Hirano, Guido W Imbens, and Geert Ridder. Efficient estimation of average treatment effects using the estimated propensity score. *Econometrica*, 71(4):1161–1189, 2003.

Guido W Imbens and Donald B Rubin. Rubin causal model. In *Microeconometrics*, pages 229–241. Springer, 2010.

Guido W. Imbens and Donald B. Rubin. *Causal Inference for Statistics, Social, and Biomedical Sciences: An Introduction*. Cambridge University Press, 2015. doi: 10.1017/CBO9781139025751.

Fredrik D. Johansson, Uri Shalit, and David Sontag. Learning representations for counterfactual inference. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, ICML'16, pages 3020–3029. JMLR.org, 2016. URL http://dl.acm.org/citation.cfm?id=3045390.3045708.

Joseph D. Y. Kang and Joseph L. Schafer. Demystifying double robustness: A comparison of alternative strategies for estimating a population mean from incomplete data. *Statist. Sci.*, 22(4):523–539, 11 2007. doi: 10.1214/07-STS227. URL https://doi.org/10.1214/07-STS227.

Günter Klambauer, Thomas Unterthiner, Andreas Mayr, and Sepp Hochreiter. Self-normalizing neural networks. *CoRR*, abs/1706.02515, 2017. URL http://arxiv.org/abs/1706.02515.

Jared K Lunceford and Marie Davidian. Stratification and weighting via the propensity score in estimation of causal treatment effects: a comparative study. *Statistics in medicine*, 23(19):2937–2960, 2004.

Jörg Lücke and Dennis Forster. k-means as a variational EM approximation of Gaussian mixture models. *Pattern Recognition Letters*, 125:349–356, Jul 2019. ISSN 0167-8655. doi: 10.1016/j.patrec.2019.04.001. URL http://dx.doi.org/10.1016/j.patrec.2019.04.001.

Judea Pearl. Causal Diagrams for Empirical Research. *Biometrika*, 82(4):669–688, 1995. ISSN 00063444. URL http://www.jstor.org/stable/2337329.

Nicholas Radcliffe. Using control groups to target on predicted lift: Building and assessing uplift model. *Direct Marketing Analytics Journal*, pages 14–21, 2007.

Nicholas J. Radcliffe and Patrick D. Surry. Real-world uplift modelling with significance-based uplift trees. Technical report, Stochastic Solutions, 2011.

James Robins, Mariela Sued, Quanhong Lei-Gomez, and Andrea Rotnitzky. Comment: Performance of double-robust estimators when" inverse probability" weights are highly variable. *Statistical Science*, 22(4):544–559, 2007.

James M Robins and Andrea Rotnitzky. Semiparametric efficiency in multivariate regression models with missing data. *Journal of the American Statistical Association*, 90(429):122–129, 1995.

Paul R. Rosenbaum. Covariance adjustment in randomized experiments and observational studies. *Statist. Sci.*, 17(3):286–327, 08 2002. doi: 10.1214/ss/1042727942. URL https://doi.org/10.1214/ss/1042727942.

Paul R Rosenbaum and Donald B Rubin. The central role of the propensity score in observational studies for causal effects. *Biometrika*, 70(1):41–55, 1983.

Paul R Rosenbaum and Donald B Rubin. Constructing a control group using multivariate matched sampling methods that incorporate the propensity score. *The American Statistician*, 39(1):33–38, 1985.

Donald B Rubin. Causal inference using potential outcomes. *Journal of the American Statistical Association*, 100(469):322–331, 2005. doi: 10.1198/016214504000001880. URL https://doi.org/10.1198/016214504000001880.

Donald B. Rubin. For objective causal inference, design trumps analysis. *Ann. Appl. Stat.*, 2 (3):808–840, 09 2008. doi: 10.1214/08-AOAS187. URL https://doi.org/10.1214/08-AOAS187.

Sebastian Ruder. An overview of multi-task learning in deep neural networks. *ArXiv*, abs/1706.05098, 2017.

Claudia Shi, David M Blei, and Victor Veitch. Adapting neural networks for the estimation of treatment effects. *arXiv preprint arXiv:1906.02120*, 2019.

Elizabeth A Stuart. Matching methods for causal inference: A review and a look forward. *Statistical science: a review journal of the Institute of Mathematical Statistics*, 25(1):1, 2010.

Mark J Van der Laan and Sherri Rose. *Targeted learning: causal inference for observational and experimental data*. Springer Science & Business Media, 2011.

Hui Zou and Trevor Hastie. Regularization and variable selection via the elastic net. *Journal of the Royal Statistical Society. Series B (Statistical Methodology)*, 67(2):301–320, 2005. ISSN 13697412, 14679868. URL http://www.jstor.org/stable/3647580.

Appendix A. Methodology

A.1. Deterministic Assignment to States

Without restricting $w_{i,j}(\mathbf{X})$ Algorithm 1 is not *identical* to traditional subclassification, since each observation probabilistically maps to all states at once, rather than a deterministic $\mathbf{x}_i \mapsto s_j$ mapping. In that sense PSPS is a soft-clustering generalization of classic subclassification – akin to Gaussian mixture modeling (GMM) being a generalization of K-means (Lücke and Forster, 2019).

If practitioners want to obtain such a deterministic (hard-clustering) strata assignment, we suggest to add an entropy based penalty regularization of the form

$$\lambda_e \cdot \sum_{i=1}^{N} \left(- \sum_{j=1}^{J} w_{i,j} \log_2 w_{i,j} \right) = \lambda_e \cdot \sum_{i=1}^{N} \text{entropy}_i. \tag{19}$$

Adding (19) to (13) allows to control with how much certainty observations are mapped to predictive states. For sufficiently large $\lambda_e \gg 0$ (19) is minimized for deterministic mappings, $w_{i,j} = 0$ for all but one j for each i, i.e., it assigns observations to exactly one state with probability 1.

We want to emphasize though that without any prior knowledge of a deterministic mapping we suggest to keep the soft-thresholding property of PRESS, as from a likelihood point of view it leads to better models. Similarly to how a GMM usually gives higher quality results compared to a hard-thresholding K-means. In practice a small λ_e can be beneficial to make $\mathbf{w}_j$ more sparse.

A.2. Trimming

Using predictive states in the propensity model allows us to easily assess "treatment vs. control" balance within each predictive state and then drop states from inference for which balance is deemed inadequate. A simple suggestion is to ensure that there are enough treated and control units in each state with respect to the complexity of the outcome model; alternatively balance of individual features or their products may be assessed via methods such as t-tests, etc.

Appendix B. Additional Simulation Study: Radcliffe & Surrey

This data generating process is taken from Radcliffe (2007) and Radcliffe and Surry (2011). Here treatment is randomly assigned to each unit with probability p. For each unit, x_1 and x_2 are drawn as independent uniform random integers in $U[0, B]$ for an upper bound B (here: $B = 99$). Unobserved variables u_1 and u_2 are then drawn uniformly from $U(0, x_i)$, $i = 1, 2$ respectively. Unit-level treatment effects and outcome regressions are then set as

$$ute_i = u_{2,i} \cdot s + c \tag{20}$$
$$y_i = u_{1,i} + T_i \cdot ute_i, \tag{21}$$

where T_i is the realization of a Bernoulli draw with probability p (here: $p = 0.5$). This specification yields a true ATE of

$$ATE = s \cdot \mathbb{E}(u_2) + c, \text{ where } \mathbb{E}(u_2) = B/4. \tag{22}$$

In simulations we explore whether the scaling factor s or shift c affect the ability to recover the true treatment effect. As for Lunceford & Davidian we consider three scenarios: $const = \{s = 0, c = 3\}$, $scale = \{s = 0.1, c = 0\}$, and $both = \{s = 0.1, c = 3\}$.

Figure 5 shows that – except for the outcome PRESS neural net – all models give unbiased ATE estimates; and again, linear and Random Forest DRIPW have difficult estimating unit-level effects. Results do not vary much between "const", "scale", or "both" except for RandomForestDRIPW, which performs worse as the association grows stronger.

B.1. Propensity Metrics and Near Positivity Violations

A common concern with propensity score methods, in particular inverse propensity weighting (IPW), are near positivity violations which are situations where the propensity to treat is close to 0 or 1 (Robins et al., 2007). Practically this means it is unlikely to find any matching control (treated) units. Statistically IPW algorithms run into near zero-division issues which result in high instability in the causal effect estimate.

We explore how estimators perform across two metrics on the propensity score distributions that measure important properties related to near-positivity violations:

- **Extremeness**: proportion of scores outside of $[0.05, 0.95]$. This highlights scenarios where the propensity model is close to near-positivity violations (Robins et al., 2007).

- **Flatness**: normalized Shannon entropy of the propensity score distribution (unconditional) (Cover and Thomas, 2006). This measures how flat (or peaked) the propensity distribution is. A score of 1.0 is a uniform distribution; a lower score corresponds to a more "peaky" distribution. Exactly zero score flatness occurs when the propensity scores reduce to singletons along the unit interval, and thus the continuous distribution degenerates to delta functions. This can happen for PSPS if the mapping from features to states ($p(s_j \mid \mathbf{X}_i)$) become deterministic, and only J propensity scores in the final propensity model remain.

Across all simulations we only found that one scenario resulted in non-trivial relationships between the propensity score distribution metrics above and the quality of the ATE estimates. For the original KangSchafer dataset, without transformations, we see that DoublyRobustIPW shows various degrees of flatness and extremeness, which result in improved ATE estimates (as flatness and extremeness increased). For PSPS on the other hand all scores are away from near-one violations (extremeness $= 0.0$ for all simulations) and propensity score flatness is close to 0.0 – which corresponds to predictive state mappings that are deterministic functions from features, $\mathbf{X}$, to one of the J states, $s_1, \ldots, s_J$. In either case, it had no impact on quality of ATE estimate in terms of bias.

An explanation for this lies in how PSPS uses (estimated) propensity scores to arrive at the final causal estimate: it computes a convex-combination, weighted average of the J individual outcomes models. The key here is that propensity scores are not inverted, as in any inverse-propensity weighting method, thus near-one (or near zero) propensity scores pose no problem for PSPS.

B.2. Sensitivity Analysis For Number of States

In most scenarios $J = 10$ was sufficient, and any further increases in J only yielded marginal (if any) improvements. In fact, Fig. 7 shows that increasing J decreases RMSE while in Fig. 8 decreasing J is beneficial with $J = 10$ a natural midpoint between the two. Even a single state PSPS architecture ($J = 1$) is competitive in certain scenarios. This is an interesting edge case as it is equivalent to a simple outcome model with averaging weights $w_{i,j} = w_{i,1} \equiv 1$ for each i.

These results highlight a useful practical guideline on how to use PSPS to empirically check whether simple outcome models are sufficient: if ATE estimates do not change for $J = 1$ vs. $J >$

(a) ATE bias (top) and UTE RMSE (bottom).

(b) 95% bootstrap confidence interval coverage and interval width

(c) Radcliffe & Surrey. For marginal bias distribution see Figure B.

Figure 5: Model comparison for Radcliffe & Surrey dataset (Section B)

1, a simple (non-linear) outcome model might be sufficient. This can be seen when comparing PSPS with $J = 1$ to other (non-PSPS) outcome model alternatives in each scenario. Interestingly,

(a) Kang & Schafer   (b) Lunceford & Davidian   (c) Radcliffe & Surry

Figure 6: Propensity metrics

(a) ATE bias and CATE RMSE for linear and non-linear dataset.

(b) 95% bootstrap confidence interval coverage and interval width

Figure 7: Model comparison for Kang & Schafer dataset (Section 4.1)

the coverage probability stays roughly constant for varying *J*, yet the confidence interval width decreases significantly as *J* increases. We hypothesize this is a result of lower variance estimates for a better outcome model approximation. If practitioners are concerned about getting narrow confidence intervals, we thus recommend increasing the number of states. The findings here on the choice of *J* are based entirely on the scenarios simulated here, with some general insights based on how the underlying PRESS model relies on *J* as an upper bound on the effective degrees of freedom of the predictive kernel smoother. In real world applications we recommend to run a cross-validation on the joint log-likelihood and choose that *J* that maximizes the out-of-sample likelihood in (13).

(a) ATE bias (top) and UTE RMSE (bottom).

(b) 95% bootstrap confidence interval coverage and interval width

Figure 8: Model comparison for Lunceford & Davidian dataset (Section 4.2)

(a) ATE bias and CATE RMSE for linear and non-linear dataset.

(b) 95% bootstrap confidence interval coverage and interval width

Figure 9: Model comparison for Radcliffe & Surry dataset (Section B)

(a) Kang & Schafer   (b) Lunceford & Davidian.   (c) Radcliffe & Surrey

Figure 10: R-squared of the Outcome Model vs. ATE Bias. For marginal bias distribution see Figures 7, 8, and 5.