Priors, Hierarchy, and Information Asymmetry for Skill Transfer in Reinforcement Learning

Abstract

The ability to discover behaviours from past experience and transfer them to new tasks is a hallmark of intelligent agents acting sample-efficiently in the real world. Equipping embodied reinforcement learners with the same ability may be crucial for their successful deployment in robotics. While hierarchical and KL-regularized reinforcement learning individually hold promise here, arguably a hybrid approach could combine their respective benefits. Key to these fields is the use of information asymmetry across architectural modules to bias which skills are learnt. While asymmetric choice has a large influence on transferability, existing methods base their choice primarily on intuition in a domain-independent, potentially suboptimal, manner. In this paper, we theoretically and empirically show the crucial *expressivity-transferability* trade-off of skills across sequential tasks, controlled by information asymmetry. Given this insight, we introduce **APES**, 'Attentive Priors for Expressive and Transferable Skills', a hierarchical KL-regularized method, heavily benefiting from both priors and hierarchy. Unlike existing approaches, APES *automates* the choice of asymmetry by *learning* it in a *data-driven*, *domain-dependent*, way based on our *expressivity-transferability* theorems. Experiments over complex transfer domains of varying levels of extrapolation and sparsity, such as robot block stacking, demonstrate the criticality of the correct asymmetric choice, with APES drastically outperforming previous methods.

1 Introduction

While Reinforcement Learning (RL) algorithms recently achieved impressive feats across a range of domains (Silver et al., 2017; Mnih et al., 2015; Lillicrap et al., 2015), they remain sample inefficient (Abdolmaleki et al., 2018; Haarnoja et al., 2018b) and are therefore of limited use for real-world robotics applications. Intelligent agents during their lifetime discover and reuse skills at multiple levels of behavioural and temporal abstraction to efficiently tackle new situations. For example, in manipulation domains, beneficial abstractions could include low-level instantaneous motor primitives as well as higher-level object manipulation strategies. Endowing lifelong learning RL agents (Parisi et al., 2019) with a similar ability could be vital towards attaining comparable sample efficiency.

To this end, two paradigms have recently been introduced. *KL-regularized* RL (Teh et al., 2017; Galashov et al., 2019) presents an intuitive approach for automating skill reuse in multi-task learning. By regularizing policy behaviour against a learnt task-agnostic prior, common behaviours across tasks are distilled into the prior, which encourages their reuse. Concurrently, *hierarchical* RL also enables skill discovery (Wulfmeier et al., 2019; Merel et al., 2020; Hausman et al., 2018; Haarnoja et al., 2018a; Wulfmeier et al., 2020) by considering a two-level hierarchy in which the high-level policy is task-conditioned, whilst the low-level remains task-agnostic. The lower level of the hierarchy therefore also discovers skills that are transferable across tasks. Both hierarchy and priors offer their own skill abstraction. However, when combined, *hierarchical KL-regularized* RL can discover multiple abstractions. Whilst prior methods attempted this (Tirumala et al., 2019; 2020; Liu et al., 2022; Goyal et al., 2019), the transfer benefits from learning both abstractions varied drastically, with approaches like Tirumala et al. (2019) unable to yield performance gains.

In fact, successful transfer for all approaches critically depends on the correct choice of information asymmetry (IA). IA more generally refers to an asymmetric masking of information across architectural modules. This masking forces independence to, and ideally generalisation across, the masked dimensions (Galashov et al., 2019). For example, for self-driving cars, by conditioning the prior only on proprioceptive information it discovers skills independent to, and shared across, global

coordinate frames. Therefore, IA crucially biases learnt behaviours and how they transfer across environments. Previous works *predefined* their IAs, which were primarily chosen on *intuition* and *independent* of domain. In addition, previously explored asymmetries were narrow (Table 1), which if sub-optimal, limit transfer benefits. We demonstrate that this indeed is the case for many methods on our domains (Galashov et al., 2019; Bagatella et al., 2022; Tirumala et al., 2019; 2020; Pertsch et al., 2021; Wulfmeier et al., 2019). A more systematic, *theoretically* and *data* driven, *domain* dependent, approach for choosing IA is thus required to maximally benefit from skills for transfer learning.

In this paper, we employ *hierarchical KL-regularized* RL to effectively transfer skills across sequential tasks. We begin by *theoretically* and *empirically* showing the crucial *expressivity-transferability* trade-off, controlled by choice of IA, of skills across sequential tasks. We demonstrate this by ablating over a wide range of asymmetries (including previously unexplored ones) between the hierarchical policy and prior. We show the inefficiencies of previous methods that choose highly sub-optimal IAs for our various domains, *drastically limiting* transfer performance. Given this insight, we introduce **APES**, 'Attentive Priors for Expressive and Transferable Skills' as a method that forgoes user intuition and *automates* the choice of IA in a *data* driven, *domain* dependent, manner. APES builds on our *expressivity-transferability* theorems to *learn* the choice of asymmetry between policy and prior. Specifically, APES conditions the prior on the entire history, allowing for *expressive* skills to be discovered, and learns a low-entropic attention-map over the input, paying attention only where necessary, to minimise *covariate shift* and improve *transferability* across domains. Experiments over a wide range of domains (including a complex robot block stacking one), of varying levels of sparsity and extrapolation, demonstrate APES' consistent superior performance over existing methods, whilst automating IA choice and by-passing arduous IA sweeps. Further ablations show the importance of combining hierarchy and priors for discovering *expressive* multi-modal behaviours.

2 SKILL TRANSFER IN REINFORCEMENT LEARNING

We consider multi-task reinforcement learning in Partially Observable Markov Decision Processes (POMDPs), defined by $M_k = (\mathcal{S}, \mathcal{X}, \mathcal{A}, r_k, p, p_k^0, \gamma)$, with tasks k sampled from $p(\mathcal{K})$. $\mathcal{S}, \mathcal{A}, \mathcal{X}$ denote observation, action, history spaces. $p(\mathbf{x}'|\mathbf{x}, \mathbf{a}) : \mathcal{X} \times \mathcal{X} \times \mathcal{A} \rightarrow \mathbb{R}_{\geq 0}$ is the dynamics model. We denote the history of observations $\mathbf{s} \in \mathcal{S}$, actions $\mathbf{a} \in \mathcal{A}$ up to timestep t as $\mathbf{x}_t = (\mathbf{s}_0, \mathbf{a}_0, \mathbf{s}_1, \mathbf{a}_1, \ldots, \mathbf{s}_t)$. Reward function $r_k : \mathcal{X} \times \mathcal{A} \times \mathcal{K} \rightarrow \mathbb{R}$ is history-, action- and task-dependent.

2.1 KL-REGULARIZED REINFORCEMENT LEARNING

The typical multi-task KL-regularized RL objective (Todorov, 2007; Kappen et al., 2012; Rawlik et al., 2012; Schulman et al., 2017) takes the form:

$$\mathcal{O}(\pi, \pi_0) = \mathbb{E}_{\substack{\tau \sim p_\pi(\tau), \\ k \sim p(\mathcal{K})}} \left[\sum_{t=0}^{\infty} \gamma^t \left(r_k(\mathbf{x}_t, \mathbf{a}_t) - \alpha_0 \mathrm{D}_{\mathrm{KL}} \left(\pi(\mathbf{a}|\mathbf{x}_t, k) \parallel \pi_0(\mathbf{a}|\mathbf{x}_t) \right) \right) \right] \quad (1)$$

where γ is the discount factor and α_0 weighs the individual objective terms. π and π_0 denote the task-conditioned policy and task-agnostic prior respectively. The expectation is taken over tasks and trajectories τ from policy π and initial state distribution $p_k^0(\mathbf{s}_0)$, (i.e. $p_\pi(\tau)$). Summation over t occurs across all episodic timesteps. When optimised with respect to π, this objective can be viewed as a trade-off between maximising rewards whilst remaining close to trajectories produced by π_0. When π_0 is learnt, it can learn shared behaviours across tasks and bias multi-task exploration (Teh et al., 2017). We consider the sequential learning paradigm, where skills are learnt from past tasks, $p_{source}(\mathcal{K})$, and leveraged while attempting the transfer set of tasks, $p_{trans}(\mathcal{K})$.

2.2 HIERARCHICAL KL-REGULARIZED REINFORCEMENT LEARNING

While KL-regularized RL has achieved success across various settings (Abdolmaleki et al., 2018; Teh et al., 2017; Pertsch et al., 2020; Haarnoja et al., 2018a), recently Tirumala et al. (2019) proposed a hierarchical extension where policy π and prior π_0 are augmented with latent variables, $\pi(\mathbf{a}, \mathbf{z}|\mathbf{x}, k) = \pi^H(\mathbf{z}|\mathbf{x}, k)\pi^L(\mathbf{a}|\mathbf{z}, \mathbf{x})$ and $\pi_0(\mathbf{a}, \mathbf{z}|\mathbf{x}) = \pi_0^H(\mathbf{z}|\mathbf{x})\pi_0^L(\mathbf{a}|\mathbf{z}, \mathbf{x})$, where subscripts H and L denote the higher and lower hierarchical levels. This structure encourages the shared low-level policy ($\pi^L = \pi_0^L$) to discover task-agnostic behavioural primitives, whilst the high-level discovers higher-level task relevant skills. By not conditioning the high-level prior on task-id, Tirumala et al. (2019) encourage the reuse of common high-level abstractions across tasks. They also propose the following upper bound for approximating the KL-divergence between hierarchical policy and prior:

$$D_{KL}\left(\pi(\mathbf{a}|\mathbf{x}) \| \pi_0(\mathbf{a}|\mathbf{x})\right) \leq D_{KL}\left(\pi^H(\mathbf{z}|\mathbf{x}) \| \pi_0^H(\mathbf{z}|\mathbf{x})\right) + \mathbb{E}_{\pi^H}\left[D_{KL}\left(\pi^L(\mathbf{a}|\mathbf{x},\mathbf{z}) \| \pi_0^L(\mathbf{a}|\mathbf{x},\mathbf{z})\right)\right] \quad (2)$$

We omit task conditioning and declaring explicitly shared modules to emphasise this bound is agnostic to these choices.

2.3 INFORMATION ASYMMETRY

Information Asymmetry (IA) is a key component in both of the aforementioned approaches, promoting the discovery of behaviours that generalise. IA can be understood as the masking of information accessible by certain modules. Not conditioning on specific environment aspects forces independence and generalisation across them (Galashov et al., 2019). In the context of (hierarchical) KL-regularized RL, the explored asymmetries between the (high-level) policy, $\pi^{(H)}$, and prior, $\pi_0^{(H)}$, have been narrow (Tirumala et al., 2019; 2020; Liu et al., 2022; Pertsch et al., 2020; 2021; Rao et al., 2021; Ajay et al., 2020; Goyal et al., 2019). Concurrent with our research, Bagatella et al. (2022) published work exploring a wider range of asymmetries, closer to those we explore. We summarise explored asymmetries in Table 1 (with $\mathbf{a}_{t-n:t}$ representing action history up to n steps in the past).

Table 1: Previously Explored IAs

Paper	$\pi_0^{(H)}$ input
(Tirumala et al., 2020; Liu et al., 2022)	$\mathbf{x}_t$
(Bagatella et al., 2022)	$\mathbf{a}_{t-n:t}$
(Bagatella et al., 2022)	$\mathbf{x}_{t-1:t}$
(Pertsch et al., 2020; 2021; Ajay et al., 2020)	$\mathbf{s}_t$
(Rao et al., 2021; Tirumala et al., 2019; 2020)	$\mathbf{z}_{t-1}$
(Tirumala et al., 2019; Goyal et al., 2019)	—

Choice of information conditioning heavily influences which skills can be uncovered and how well they transfer. For example, Pertsch et al. (2020) discover observation-dependent behaviours, such as navigating corridors in maze environments, yet are unable to learn history-dependent skills, such as never traversing the same corridor twice. In contrast, Liu et al. (2022), by conditioning on history, are able to learn these behaviours. However, as we will show, in many scenarios, naïvely conditioning on entire history can be detrimental for transfer, by discovering behaviours that do not *generalise* favourably across history instances, between tasks. Crucially, all previous works *predefine* the choice of asymmetry, based on the practitioner's intuition, that may be sub-optimal for skill transfer. By introducing theory behind the *expressivity-transferability* of skills, we present a simple data-driven method for *automating* the choice of IA, by *learning* it, yielding transfer benefits.

3 MODEL ARCHITECTURE AND THE EXPRESSIVITY-TRANSFERABILITY TRADE-OFF

To rigorously investigate the contribution of priors, hierarchy, and information asymmetry on skill transfer, it is important to isolate each individual mechanism while enabling the recovery of previous models of interest. To this end, we present the unified architecture in Fig. 1, which introduces *information gating functions* (IGFs) as a means of decoupling IA from architecture. Each component has its own IGF, depicted with colored rectangle. Every module is fed all environment information $\mathbf{x}_k = (\mathbf{x}, k)$ and distinctly chosen IGFs mask which part of the input each network has access to, thereby influencing which skills they learn. By presenting multiple priors, we enable a comparison with existing literature. With the right masking, one can recover previously investigated asymmetries (Tirumala et al., 2019; 2020; Pertsch et al., 2020; Bagatella et al., 2022; Goyal et al., 2019), explore additional ones, and also express purely hierarchical (Wulfmeier et al., 2019) and KL-regularized equivalents (Galashov et al., 2019; Haarnoja et al., 2018c).

Figure 1: Hierarchical KL-regularized architecture. The hierarchical policy modules π^H and π^L are regularized against their corresponding prior modules π_i^H and π_i^L. The inputs to each module are filtered by an information gating function, depicted with colored rectangle.

3.1 THE INFORMATION ASYMMETRY EXPRESSIVITY-TRANSFERABILITY TRADE-OFF

While existing works investigating the role of IAs for skill transfer have focused on *multi-task learning* (Galashov et al., 2019)[1] (specifically on policy π regularization), we focus on the *sequential*

---

[1]Concurrent with our research Bagatella et al. (2022) also investigated various IAs for sequential transfer.

a) CorridorMaze

b) Stack

Figure 2: *Environments. a) CorridorMaze:* A hard-exploration toy domain. The agent starts in the hallway and must traverse a given number of corridors in a given sequence. The agent completes a given corridor by traversing to its depth and back. *b) Stack:* A hard exploration, robotic, domain. The agent must stack the cubes in a given ordering over the light blue target pad.

task setting (particularly the prior's π_0 ability to handle covariate shift). In contrast to multi-task learning, in the sequential setting there exists abrupt non-stationarities for task $p(\mathcal{K})$ and trajectory $p_\pi(\tau)$ distributions. As such, here it is particularly important that priors handle non-stationarity and associated covariate shift (see Theorem 3.1 for definition). IA choice plays a crucial role, influencing the level of covariate shift encountered by the prior across tasks:

Theorem 3.1. *The more random variables a network depends on, the larger the covariate shift (input distributional shift, here represented by KL-divergence) encountered across sequential tasks. That is, for distributions p, q and inputs $\mathbf{b}$, $\mathbf{c}$ such that $\mathbf{b} = (b_0, b_1, ..., b_n)$ and $\mathbf{c} \subset \mathbf{b}$:*

$$\mathrm{D}_{\mathrm{KL}}\left(p(\mathbf{b}) \parallel q(\mathbf{b})\right) \geq \mathrm{D}_{\mathrm{KL}}\left(p(\mathbf{c}) \parallel q(\mathbf{c})\right).$$

Proof. See Appendix B.1. ∎

In our case, p and q can be interpreted as training $p_{source}(\cdot)$ and transfer $p_{trans}(\cdot)$ distributions over network inputs, such as history $\mathbf{x}_t$ for high-level prior π_0^H. Intuitively, Theorem 3.1 states that *the more variables you condition your network on, the less likely it will transfer* due to increased covariate shift encountered between source and transfer domains, thus promoting minimal information conditioning. For example, imagine conditioning the high-level prior on either the entire history $\mathbf{x}_{0:t}$ or a subset of it $\mathbf{x}_{t-n:t}$, $n \in [0, t-1]$ (the subscript referring to the range of history values). According to Theorem 3.1, the covariate shift across sequential tasks will be *smaller* if we condition on a subset of the history, $\mathrm{D}_{\mathrm{KL}}\left(p_{source}(\mathbf{x}_{0:t}) \parallel p_{trans}(\mathbf{x}_{0:t})\right) \geq \mathrm{D}_{\mathrm{KL}}\left(p_{source}(\mathbf{x}_{t-n:t}) \parallel p_{trans}(\mathbf{x}_{t-n:t})\right)$. Interestingly, covariate shift is upper-bounded by trajectory shift: $\mathrm{D}_{\mathrm{KL}}\left(p_{\pi_{source}}(\tau) \parallel p_{\pi_{trans}}(\tau)\right) \geq \mathrm{D}_{\mathrm{KL}}\left(p_{\pi_{source}}(\tau_f) \parallel p_{\pi_{trans}}(\tau_f)\right)$ (using Theorem 3.1), with the right hand side representing covariate shift over network inputs $\tau_f = IGF(\tau)$, filtered trajectories (e.g. $\tau_f = \mathbf{x}_{t-n:t}$, $\tau_f \subset \tau$), and π_{source}, π_{trans}, source and transfer domain policies. It is therefore crucial, if possible, to minimise *both* trajectory and covariate shifts across domains, to benefit from previous skills. Nevertheless, the less information a prior is conditioned on, the less knowledge that can be distilled and transferred:

Theorem 3.2. *The more random variables a network depends on, the greater its ability to distil knowledge in the expectation (output distributional shift between network and target distribution, here represented by the expected KL-divergence). That is, for target distribution p and network q with outputs a and possible inputs $\mathbf{b}$, $\mathbf{c}$, $\mathbf{d}$, such that $\mathbf{b} = (b_0, b_1, ..., b_n)$, $\mathbf{d} \subset \mathbf{c} \subset \mathbf{b}$, $\mathbf{e} \in \mathbf{d} \oplus \mathbf{c}$:*

$$\mathbb{E}_{q(\mathbf{e}|\mathbf{d})}\left[\mathrm{D}_{\mathrm{KL}}\left(p(a|\mathbf{b}) \parallel q(a|\mathbf{c})\right)\right] \leq \mathrm{D}_{\mathrm{KL}}\left(p(a|\mathbf{b}) \parallel q(a|\mathbf{d})\right).$$

Proof. See Appendix B.2. ∎

In this particular instance, p and q could be interpreted as policy π and prior π_0 distributions, a as action $\mathbf{a}_t$, b as history $\mathbf{x}_{0:t}$, and c, d, e as subsets of the history (e.g. $\mathbf{x}_{t-n:t}$, $\mathbf{x}_{t-m:t}$, $\mathbf{x}_{t-n:t-m}$ respectively, with $n > m$ and m & $n \in [0, t]$), with e denoting the set of variables in c but not d. Intuitively, Theorem 3.2 states *in the expectation, conditioning on more information improves knowledge distillation between policy and prior* (e.g. $\mathbb{E}_{\pi_0(\mathbf{x}_{t-n:t-m}|\mathbf{x}_{t-m:t})}\left[\mathrm{D}_{\mathrm{KL}}\left(\pi(\mathbf{a}_t|\mathbf{x}_{0:t}) \parallel \pi_0(\mathbf{a}_t|\mathbf{x}_{t-n:t})\right)\right] \leq \mathrm{D}_{\mathrm{KL}}\left(\pi(\mathbf{a}_t|\mathbf{x}_{0:t}) \parallel \pi_0(\mathbf{a}_t|\mathbf{x}_{t-m:t})\right)$, with $\pi_0(\mathbf{x}_{t-n:t-m}|\mathbf{x}_{t-m:t})$ the conditional distribution, induced by π_0, of history subset $\mathbf{x}_{t-n:t-m}$ given $\mathbf{x}_{t-m:t}$). Therefore, IA leads to an *expressivity-transferability* trade-off of skills (Theorems 3.1 and 3.2). Interestingly, hierarchy does *not* influence covariate shift and hence does *not* hurt *transferability*, but it does increase network *expressivity* (e.g. of the prior), enabling the distillation and transfer of rich *multi-modal* behaviours present in the real-world.

4 APES: ATTENTIVE PRIORS FOR EXPRESSIVE AND TRANSFERABLE SKILLS

While previous works chose IA on intuition (Tirumala et al., 2019; 2020; Galashov et al., 2019; Pertsch et al., 2020; Wulfmeier et al., 2019; Bagatella et al., 2022; Singh et al., 2020; Ajay et al., 2020; Liu et al., 2022) we propose *learning* it. Consider the *information gating functions* (IGFs) introduced in Section 3 and depicted in Figure 1. Existing methods can be recovered by having the IGFs perform hard attention: $IGF(\mathbf{x}_k) = \mathbf{m} \odot \mathbf{x}_k$, with $\mathbf{m} \in \{0, 1\}^{dim(\mathbf{x}_k)}$, predefined and static, and $\odot$ representing element-wize multiplication. In contrast, we propose performing soft attention with $\mathbf{m} \in [0, 1]^{dim(\mathbf{x}_k)}$ and *learn* $\mathbf{m}$ based on: 1) the hierarchical KL-regularized RL objective (Equations (1) and (2)); 2) $\mathcal{O}_{IGF}(\mathbf{m}) = -\mathcal{H}(\mathbf{m})$, $\mathcal{H}$ denoting entropy (calculated by turning $\mathbf{m}$ into a probability distribution by performing Softmax over it), thereby encouraging low entropic, sparse IGFs (similar to Salter et al. (2019) applying a related technique for sim2real transfer):

$$\mathcal{O}_{\text{APES}}(\pi, \pi_0) = \mathbb{E}_{\substack{\tau \sim p_\pi(\tau), \\ k \sim p(\mathcal{K})}} \left[\sum_{t=0}^{\infty} \gamma^t \left(r_k(\mathbf{x}_t, \mathbf{a}_t) - \alpha_0 D_{\text{KL}} \left(\pi(\mathbf{a}|\mathbf{x}_k) \,\|\, \pi_0(\mathbf{a}|\mathbf{x}_k) \right) \right) \right] \\ - \sum_i \alpha_{m_i} \mathcal{H}(\mathbf{m}_i) \quad (3)$$

With α_{m_i} weighing the relative importance of each objective for each attention mask $\mathbf{m}_i$ for each module using self-attention (e.g. π_0^H). We train off-policy akin to SAC (Haarnoja et al., 2018b), sampling experiences from the replay buffer, approximating the return of the agent using Retrace (Munos et al., 2016) and double Q-learning (Hasselt, 2010) to train our critic. Refer to Appendices A and D for full training details. By exposing the IGFs to all available information $\mathbf{x}_k$, we enable the discovery of *expressive* skills with complex, potentially long-range, temporal dependencies (Theorem 3.2). By encouraging low-entropic masks m_i, we promote *minimal information conditioning* (by limiting the IGF's channel capacity) whilst still capturing *expressive* behaviours. This is achieved by paying attention only where necessary to key environment aspects (Salter et al., 2022) that are crucial for decision making and hence heavily influence behaviour *expressivity*. Minimising the dependence on redundant information (aspects of the observation $\mathbf{s}$, action $\mathbf{a}$, or history $\mathbf{x}$ spaces that behaviours are independent to), we minimise *covariate shift* and improve the *transferability* of skills to downstream domains (Theorem 3.1). Consider learning the IGF of high-level prior π_0^H for a humanoid navigation task. Low-level skills π^L could correspond to motor-primitives, whilst the high-level prior could represent navigation skills. For navigation, joint quaternions are not relevant, but the Cartesian position is. By learning to mask parts of the state-space corresponding to joints, the agent becomes invariant and robust to covariate shifts across these dimensions (unseen joint configurations). We call our method APES, 'Attentive Priors for Expressive and Transferable Skills'.

4.1 TRAINING REGIME AND THE INFORMATION ASYMMETRY SETUP

We are concerned with investigating the roles of priors, hierarchy and IA for transfer in *sequential task learning*, where skills learnt over past tasks $p_{source}(\mathcal{K})$ are leveraged for transfer tasks $p_{trans}(\mathcal{K})$. While one can investigate IA between hierarchical levels (π^H, π^L) as well as between policy and prior (π, π_0), we concern ourselves solely with the latter. Specifically, to keep our comparisons with existing literature fair, we condition π^L on $\mathbf{s}_t$ and $\mathbf{z}_t$, and share it with the prior, $\pi^L = \pi_0^L$, thus enabling *expressive* multi-modal behaviours to be discovered with respect to $\mathbf{s}_t$ (Tirumala et al., 2019; 2020; Wulfmeier et al., 2019). In this paper, we focus on the role of IA between high-level policy π^H and prior π_0^H for supporting *expressive* and *transferable* high-level skills between tasks. Specifically, we learn skills over *source domains* using variational behavioural cloning from an expert policy π_e:

$$\mathcal{O}_{bc}(\pi, \pi_0) = \sum_{i \in \{0, e\}} \mathcal{O}_{\text{APES}}(\pi, \pi_i) \quad \text{with} \quad r_k = 0, \gamma = 1 \quad \text{and samples collected from } \pi_e. \quad (4)$$

Equation (4) can be viewed as hierarchical KL-regularized RL in the absence of rewards and with two priors: the one we learn π_0; the other the expert π_e. See Appendix A.2 for a deeper discussion on the similarities with KL-regularized RL. We then transfer the skills and solve the *transfer domains* using hierarchical KL-regularized RL (as per Equation (3)). To compare the influence of distinct IAs for transfer in a controlled way, we propose the following regime: **Stage 1)** train a *single* hierarchical policy π in the multi-task setup using Equation (4), but prevent gradient flow from prior π_0 to policy. Simultaneously, based on the ablation, train distinct priors (with differing IAs) on Equation (4) to imitate the policy. As such, we compare various IAs influence on skill *distillation* and *transfer* in a controlled manner, as they all distil behaviours from the *same policy*; **Stage 2)** freeze the shared

Figure 3: *Sparse 2 corr.* 4 rollouts shown for each method, with each episode rolled out horizontally. Corridors are colour coded and depth within them is denoted by shade; the darker the deeper. Hallway is white. See text for detailed analysis.

modules (π^L, π_0^H) and train a newly instantiated π^H on the transfer task. By freezing π^L, we assume the low-level skills from the *source domains* suffice for the *transfer domains*. If this assumption does not hold, one could either fine-tune π^L during transfer, which would require tackling the catastrophic forgetting of skills (Kirkpatrick et al., 2017), or train additional skills (by expanding $\mathbf{z}$ dimensionality for discrete $\mathbf{z}$ spaces). We leave this as future work. For further details refer to Appendices A and D.

5 EXPERIMENTS AND RESULTS

Our experiments are designed to answer the following sequential task learning questions: **(1)** Can we benefit from *both* hierarchy and priors for effective transfer? **(2)** How important is the choice of IA between high-level policy and prior, and does it lead to an impactful *expressivity-transferability* trade-off of behaviours? In practice, how detrimental is *covariate shift* for transfer? **(3)** How favourably does *APES automate* the choice of IA for effective transfer? Which IAs are discovered? **(4)** How important is hierarchy for transferring *expressive* skills? Is hierarchy necessary for effective transfer?

5.1 ENVIRONMENTS

We evaluate on two domains: one designed for controlled investigation of core agent capabilities and the another, more practical, robotics domain (see Figure 2). Both exhibit modular behaviours whose discovery could yield transfer benefits. See Appendix C for full environmental setup details.

- **CorridorMaze.** The agent must traverse corridors in a given ordering. We collect $4k$ trajectories from a scripted policy traversing any random ordering of two corridors ($p_{source}(\mathcal{K})$). For transfer ($p_{trans}(\mathcal{K})$), an inter- or extrapolated ordering must be traversed (number of sequential corridors $= \{2, 4\}$) allowing us to inspect the *generalization ability* of distinct priors to increasing levels of *covariate shift*. We also investigate the influence of *covariate shift* on effective transfer across reward sparsity levels: *s-sparse* (short for semi-sparse), rewarding per half-corridor completion; *sparse*, rewarding on task completion. Our transfer tasks are *sparse 2 corr* and *s-sparse 4 corr*.

- **Stack.** The agent must stack a subset of four blocks over a target pad in a given ordering. The blocks have distinct masses and only lighter blocks should be placed on heavier ones. Therefore, discovering temporal behaviours corresponding to sequential block stacking according to mass, is beneficial. We collect $17.5k$ trajectories from a scripted policy, stacking any *two blocks* given this requirement ($p_{source}(\mathcal{K})$). The *extrapolated* transfer task ($p_{trans}(\mathcal{K})$), called *4 blocks*, requires *all blocks* be stacked according to mass. Rewards are given per individual block stacked.

5.2 HIERARCHY AND PRIORS FOR KNOWLEDGE TRANSFER

Table 2: Average return across 100 episodes (mean $\pm$ standard deviation for 4 random seeds). Experiments that do not (*(Hier-)RecSAC)* / do leverage prior experience, were ran for 10^6 vs $1.5 * 10^5$ environment steps. *APES* employs hierarchy, priors and learns $\mathbf{m}$ for π_0^H. *APES-{H20 - S}* do not learn $\mathbf{m}$. The remainder do not employ priors.

Approach	Paper	π_0^H input	learn $\mathbf{m}$	sparse 2 corr (int)	s-sparse 4 corr (ext)	4 blocks (ext)
APES	-	$\mathbf{x}_{t-20:t}$	✓	**0.93 ± 0.05**	**7.03 ± 0.09**	**3.33 ± 0.18**
APES-H20	Tirumala et al. (2020)	$\mathbf{x}_{t-20:t}$	✗	0.16 ± 0.09	3.84 ± 0.19	1.03 ± 0.45
APES-H10	-	$\mathbf{x}_{t-10:t}$	✗	0.22 ± 0.09	4.03 ± 0.55	1.22 ± 0.26
APES-H1	Bagatella et al. (2022)	$\mathbf{x}_{t-1:t}$	✗	0.80 ± 0.03	6.37 ± 0.17	**3.11 ± 0.12**
APES-S	Galashov et al. (2019) Pertsch et al. (2020)	$\mathbf{s}_t$	✗	0.00 ± 0.00	3.03 ± 0.38	1.98 ± 0.16
APES-no_prior	Tirumala et al. (2019)	-	-	0.00 ± 0.00	2.34 ± 0.19	0.00 ± 0.00
Hier-RecSAC	Wulfmeier et al. (2019)	-	-	0.00 ± 0.00	0.07 ± 0.03	0.01 ± 0.01
RecSAC	Haarnoja et al. (2018b)	-	-	0.00 ± 0.00	0.08 ± 0.02	0.01 ± 0.01
		Expert		1	8	4

Our full setup, *APES*, leverages hierarchy *and* priors for skill transfer. The high-level prior is given access to the history (as is common for POMDPs) and *learns* sparse self-attention $\mathbf{m}$. To investigate the importance of priors, we compare against *APES-no_prior*, a baseline from Tirumala et al. (2019), with the full *APES* setup except *without* a learnt prior. Comparing transfer results in Table 2, we see *APES*' drastic gains highlighting the importance of *temporal* high-level behavioural priors. To inspect the transfer importance of the traditional hierarchical setup (with $\pi^L(\mathbf{s}_t, \mathbf{z}_t)$), we compare *APES-no_prior* against two baselines trained solely on the transfer task. *RecSAC* represents a history-dependent *SAC* (Haarnoja et al., 2018d) and *Hier-RecSAC* a hierarchical equivalent from Wulfmeier et al. (2019). *APES-no_prior* has *marginal* benefits showing the importance of *both* hierarchy and priors for transfer. See Table 6 for a detailed explanation of all baseline and ablation setups.

5.3 INFORMATION ASYMMETRY FOR KNOWLEDGE TRANSFER

To investigate the importance of IA for transfer, we *ablate* over high-level priors with increasing levels of asymmetry (each input a subset of the previous): *APES-{H20, H10, H1, S}*, *S* denoting an observation-dependent high-level prior, *Hi* a history-dependent one, $\mathbf{x}_{t-i:t}$. Crucially, these ablations *do not* do not learn $\mathbf{m}$, unlike *APES*, our full method. Ablating history lengths is a natural dimension for POMDPs where discovering belief states by history conditioning is crucial (Thrun, 1999). *APES-H1, APES-S*

Table 3: $\mathcal{H}(\mathbf{m})$ vs $\mathrm{D_{KL}}(\pi^H || \pi_0^H)$

Metric Domain	$\mathcal{H}(\mathbf{m})$ (Corr/Stack)	$\mathrm{D_{KL}}(\pi^H||\pi_0^H)$ (Corr/Stack)
APES-S	0.70/0.70	0.81/0.75
APES-H1	0.78/0.95	0.22/0.65
APES-H10	1.78/1.96	0.12/0.49
APES-H20	2.08/2.26	0.11/0.47
APES	0.26/1.20	0.16/0.49
Max	2.08/2.26	0.84/1.71
Min	0.00/0.00	0.00/0.00

are hierarchical extensions of Bagatella et al. (2022); Galashov et al. (2019) respectively, and *APES-H20* (representing *entire history conditioning*) is from Tirumala et al. (2020). *APES-S* is also an extension of Pertsch et al. (2020) with $\pi^L(\mathbf{s}_t, \mathbf{z}_t)$ rather than $\pi^L(\mathbf{z}_t)$. Table 2 shows the heavy IA influence, with the trend that conditioning on too little or much information limits performance. The level of influence depends on reward sparsity level: the sparser, the heavier influence, due to rewards guiding exploration less. Regardless of whether the transfer domain is interpolated or extrapolated, IA plays a important role, suggesting that *IA is important over a wide range of transfer tasks*.

5.4 THE EXPRESSIVITY-TRANSFERABILITY TRADE-OFF

To investigate whether Theorems 3.1 and 3.2 are the reason for the apparent *expressivity-transferability* trade-off seen in Table 2, we plot Figure 4 showing, on the vertical axis, the distillation loss $\mathrm{D_{KL}}\left(\pi^H \parallel \pi_0^H\right)$ at the end of training over $p_{source}(\mathcal{K})$, verses, on the horizontal axis, the increase in transfer performance (on $p_{trans}(\mathcal{K})$) when initialising π^H as a *task agnostic* high-level prior pretrained over $p_{source}(\mathcal{K})$ (instead of randomly, as is default). We

Figure 4: *Expressivity-Transferability Trade-Off*. Distillation loss vs transfer performance increase when pre-training π^H. The level of information conditioning is shown by marker size. Absolute transfer performance is shown by marker colour (red - high; blue - low). We fit a second order curve (in red) to show the general *expressivity-transferability* trend, per Theorems 3.1 and 3.2, that distilling more, by reducing IA, can hurt transfer, due to increased covariate shift. See Table 8 for detailed tabular results.

ran these additional pre-trained π^H experiments to investigate whether *covariate shift* is the culprit for the *degradation in transfer performance* when conditioning the high-level prior on additional information. By pre-training and transferring π^H, we reduce *initial trajectory shift* and thus *initial covariate shift* between source and transfer domains (see Section 2.3). This is as no networks are *reinitialized* during transfer, which would usually lead to an initial shift in *policy behaviour* across domains. As per Theorem 3.1, we would expect a *larger reduction* in covariate shift for the priors that condition on *more information*. If *covariate shift* were the culprit for *reduced transfer performance*, we would expect a *larger performance gain* for those priors conditioned on more *more information*. Figure 4 demonstrates that is the case in general, regardless of whether the transfer domain is inter- or extra-polated. The trend is significantly less apparent for the semi-sparse domain, as here denser rewards guide learning significantly, alleviating *covariate shift* issues. We show results for *APES-{H20, H10, H1, S}* as each input is a subset of the previous. These relations govern Theorems 3.1 and 3.2. In addition, Figure 4 and Table 3 show that conditioning on more information improves *expressivity* of the prior, reducing distillation losses, as per Theorem 3.2. These results together with

Table 2, show the impactful *expressivity-transferability* trade-off of skills, controlled by IA (as per Theorems 3.1 and 3.2), where conditioning on too little or much information limits performance.

5.5 APES: ATTENTIVE PRIORS FOR EXPRESSIVE AND TRANSFERABLE SKILLS

As seen in Table 2, *APES*, our full method, strongly outperforms (almost) *every* baseline and ablation on *each* transfer domain. Comparing *APES* with *APES-H20*, the most comparable approach with the prior fed the same input ($\mathbf{x}_{t-20:t}$), we observe drastic performance gains (of $581\%, 183\%, 323\%$ for *sparse 2*

Figure 5: *APES* attention for π_0^H, plotted as $\log(\mathbf{m})$, for each domain (key on right; red and blue as high and low values). We aggregate attention to the state/action levels. For sub-state/action attention visualisation see Figure 7. *APES* learns *sparse*, *domain* dependent, attention, primarily focusing on recent actions.

corr, *s-sparse 4 corr* and *4 blocks*, respectively). These results demonstrate the importance of reducing *covariate shift* (by minimising *information conditioning*), whilst still supporting *expressive* behaviours (by exposing the prior to *maximal information*), only achieved by *APES*. Table 3 shows $\mathcal{H}(\mathbf{m})$, each π_0^H mask's entropy (a proxy for the amount of *information conditioning*), vs $D_{KL}(\pi^H||\pi_0^H)$ (distillation loss), reporting max/min scores across all experiments cycles. We ran 4 random seeds but omit standard deviations as they were negligible. *APES* not only attends to minimal information ($\mathcal{H}(\mathbf{m})$), but for that given level achieves a far lower *distillation loss* than comparable methods. This demonstrates that *APES* learnt to pay attention only where *necessary*. We inspect *APES*' attention masks $\mathbf{m}$ in Figure 5. *APES* primarily pays attention to the recent history of actions. This is interesting, as is inline with recent work, performed concurrent with our research, by Bagatella et al. (2022) demonstrating the effectiveness of *state-free* priors, conditioned on a history of actions, for effective generalization. However, unlike Bagatella et al. (2022) that need exhaustive history lengths sweeps for effective transfer, our approach *learns* the length in an *automated*, *data* driven, *domain* dependent manner. As such, our learnt history lengths are distinct for *CorridorMaze* and *Stack*. Additionally, for *CorridorMaze*, some attention is paid to the most recent observation $\mathbf{s}_t$, which is unsurprising as this information is required to infer how to optimally act whilst at the end of a corridor. Refer to Appendix E.1 for a more in-depth analysis of *APES*' attention maps.

5.6 HIERARCHY FOR EXPRESSIVITY

To further investigate whether hierarchy is necessary for effective transfer, we compare *APES-H1* with *APES-H1-flat*, which has the same setup except with a flat, non-hierarchical prior (conditioned on $\mathbf{x}_{t-1:t}$). With a flat prior, KL-regularization must occur over the raw,

Table 4: Hierarchy Ablation

Transfer task	sparse 2 corr	s-sparse 4 corr
APES-H1	$\mathbf{0.80 \pm 0.03}$	$\mathbf{6.37 \pm 0.17}$
APES-H1-KL-a	0.76 ± 0.09	5.59 ± 0.17
APES-H1-flat	0.05 ± 0.035	4.52 ± 0.53
Expert	1	8

rather than latent, action space. Therefore, to adequately compare, we additionally investigate a hierarchical setup where regularization occurs only over the action-space, *APES-H1-KL-a*. Transfer results for *CorridorMaze* are shown in Table 4. Comparing *APES-H1-KL-a* and *APES-H1-KL-flat*, we see the *benefits that a hierarchical prior brings*, although less significant for less sparse domains. Upon inspection (see Section 5.7), *APES-H1-KL-flat* is unable to solve the task due to its inability to capture multi-modal behaviours (at corridor intersections). By contrasting *APES-H1* with *APES-H1-KL-a*, we see minimal benefits regularizing against latent actions, suggesting that with alternate methods for multi-modality, hierarchy may not be necessary.

5.7 EXPLORATION ANALYSIS

To gain a further understanding on the effects of hierarchy and priors, we visualise policy rollouts early on during transfer ($5 * 10^3$ steps). For *CorridorMaze* (Figure 3), with hierarchy and priors *APES* explores randomly at the corridor level. Hierarchy alone, unable to express preference over high-level skills, leads to temporally uncorrelated behaviours, unable to explore at the corridor level. The flat prior, unable to represent multi-modal behaviours, leads to suboptimal exploration at the intersection of corridors, with the agent often remaining static. Without priors nor hierarchy, exploration is further hindered, rarely traversing corridor depths. For *Stack* (Figure 6), the full setup explores at the individual block stacking level, alternating block orderings, but primarily stacking lighter upon heavier blocks. Hierarchy alone explores undirectedly without knowledge of what blocks to operate on, leading to temporally uncorrelated high-frequency switching of low-level manipulation skills.

i) Prior & Hierarchy   ii) Hierarchy

Figure 6: *4 Blocks*. Rollouts with end-effector and cube movement depicted by dotted and dashed lines, colour-coded per rollout. Each rollout's end position represented by cross or cube respectively. Cube numbers correspond to their inherent ordering. See text for detailed analysis.

6   RELATED WORK

Hierarchical frameworks have a long history (Sutton et al., 1999). The option RL literature tackle the semi-MDP setup and explore the benefits that hierarchy and temporal abstraction bring (Nachum et al., 2018; Wulfmeier et al., 2020; Igl et al., 2019; Salter et al., 2022; Kamat & Precup, 2020; Harb et al., 2018; Riemer et al., 2018). Approaches like Wulfmeier et al. (2019; 2020) use hierarchy to enforce knowledge transfer through shared hierarchical modules. However, for lifelong learning (Parisi et al., 2019; Khetarpal et al., 2020), where number of skills increase over time, it is unclear how well these approaches will fare, without priors to narrow skill exploration.

Priors have been used in various fields. In the context of offline-RL, Siegel et al. (2020); Wu et al. (2019) primarily use priors to tackle value overestimation (Levine et al., 2020). In the variational literature, priors have been used to guide latent-space learning (Hausman et al., 2018; Igl et al., 2019; Pertsch et al., 2020; Merel et al., 2018). Hausman et al. (2018) learn episodic skills, limiting their ability to transfer. Igl et al. (2019) learn options and priors, but are on-policy and therefore suffers from sample inefficiency, making the application to robotic domains challenging. In the multi-task literature, priors have been used to guide exploration (Pertsch et al., 2020; Galashov et al., 2019; Siegel et al., 2020; Pertsch et al., 2021; Teh et al., 2017), yet without hierarchy expressivity in learnt behaviours is limited. In the sequential transfer literature, priors have also been used to bias exploration (Pertsch et al., 2020; Ajay et al., 2020; Singh et al., 2020; Bagatella et al., 2022; Goyal et al., 2019; Rao et al., 2021; Liu et al., 2022), yet either do not leverage hierarchy (Pertsch et al., 2020) or condition on minimal information (Ajay et al., 2020; Singh et al., 2020; Rao et al., 2021), limiting expressivity, all choosing asymmetry on intuition. Unlike *APES*, methods like Singh et al. (2020); Bagatella et al. (2022) leverage flow-based transformations, instead of hierarchy, to achieve multi-modality. Tirumala et al. (2020) exploit hierarchical priors to transfer entire history-dependent high-level skills. However, their setup was in a diverse high-data regime ($1e9$ samples for pre-training skills), where covariate shift is less predominant. Unlike aforementioned works, we consider the POMDP setting, arguably more suited for real-world robotics, and *learn* what information to condition our priors on based on our *expressivity-transferability* theorems.

Whilst most previous works rely on IA, choice is primarily motivated by intuition. For example, Igl et al. (2019); Wulfmeier et al. (2019; 2020) only employ task or goal asymmetry and Tirumala et al. (2019); Merel et al. (2020); Galashov et al. (2019) use exteroceptive asymmetry. Salter et al. (2020) investigate a way of learning asymmetry for sim2real domain adaptation, but condition **m** on observation and state. We consider exploring this direction as future work. We provide a principled investigation on the role of IA for transfer, proposing a method for *automating* the choice.

7   CONCLUSION

We employ *hierarchical KL-regularized* RL to efficiently transfer skills across sequential tasks, showing the effectiveness of combining hierarchy and priors. We *theoretically* and *empirically* show the crucial *expressivity-transferability* trade-off, controlled by IA choice, of skills. Our experiments validate the importance of this trade-off for *both* interpolated and extrapolated domains. Given this insight, we introduce APES, 'Attentive Priors for Expressive and Transferable Skills' *automating* the IA choice for the high-level prior, by *learning* it in a *data* driven, *domain* dependent, manner. This is achieved by feeding the entire history to the prior, capturing *expressive* behaviours, whilst encouraging its *information gating function's* attention mask to be *low entropic*, minimising *covariate shift* and improving *transferability*. Experiments over several domains, of varying sparsity levels, demonstrate APES' consistent superior performance over existing methods, whilst by-passing arduous IA sweeps. Ablations demonstrate the importance of hierarchy for prior *expressivity*, by supporting multi-modal behaviours. Future work will focus on additionally learning the IGFs between hierarchical levels.

REFERENCES

Abbas Abdolmaleki, Jost Tobias Springenberg, Yuval Tassa, Remi Munos, Nicolas Heess, and Martin Riedmiller. Maximum a posteriori policy optimisation. *arXiv preprint arXiv:1806.06920*, 2018.

Anurag Ajay, Aviral Kumar, Pulkit Agrawal, Sergey Levine, and Ofir Nachum. Opal: Offline primitive discovery for accelerating offline reinforcement learning. *arXiv preprint arXiv:2010.13611*, 2020.

Marco Bagatella, Sammy Joe Christen, and Otmar Hilliges. Sfp: State-free priors for exploration in off-policy reinforcement learning. 2022.

Alexandre Galashov, Siddhant M Jayakumar, Leonard Hasenclever, Dhruva Tirumala, Jonathan Schwarz, Guillaume Desjardins, Wojciech M Czarnecki, Yee Whye Teh, Razvan Pascanu, and Nicolas Heess. Information asymmetry in kl-regularized rl. *arXiv preprint arXiv:1905.01240*, 2019.

Anirudh Goyal, Riashat Islam, Daniel Strouse, Zafarali Ahmed, Matthew Botvinick, Hugo Larochelle, Yoshua Bengio, and Sergey Levine. Infobot: Transfer and exploration via the information bottleneck. *arXiv preprint arXiv:1901.10902*, 2019.

Tuomas Haarnoja, Kristian Hartikainen, Pieter Abbeel, and Sergey Levine. Latent space policies for hierarchical reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2018a.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning (ICML)*, 2018b.

Tuomas Haarnoja, Aurick Zhou, Sehoon Ha, Jie Tan, George Tucker, and Sergey Levine. Learning to walk via deep reinforcement learning. *arXiv preprint arXiv:1812.11103*, 2018c.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018d.

Jean Harb, Pierre-Luc Bacon, Martin Klissarov, and Doina Precup. When waiting is not an option: Learning options with a deliberation cost. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

H. V. Hasselt. Double Q-learning. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 2613–2621, 2010.

Karol Hausman, Jost Tobias Springenberg, Ziyu Wang, Nicolas Heess, and Martin Riedmiller. Learning an embedding space for transferable robot skills. In *International Conference on Learning Representations*, 2018.

Maximilian Igl, Andrew Gambardella, Jinke He, Nantas Nardelli, N Siddharth, Wendelin Böhmer, and Shimon Whiteson. Multitask soft option learning. *arXiv preprint arXiv:1904.01033*, 2019.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Anand Kamat and Doina Precup. Diversity-enriched option-critic. *arXiv preprint arXiv:2011.02565*, 2020.

Hilbert J Kappen, Vicenç Gómez, and Manfred Opper. Optimal control as a graphical model inference problem. *Machine learning*, 87(2):159–182, 2012.

Khimya Khetarpal, Matthew Riemer, Irina Rish, and Doina Precup. Towards continual reinforcement learning: A review and perspectives. *arXiv preprint arXiv:2012.13490*, 2020.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114 (13):3521–3526, 2017.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

T. P. Lillicrap, J. J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Siqi Liu, Guy Lever, Zhe Wang, Josh Merel, SM Ali Eslami, Daniel Hennes, Wojciech M Czarnecki, Yuval Tassa, Shayegan Omidshafiei, Abbas Abdolmaleki, et al. From motor control to team play in simulated humanoid football. *Science Robotics*, 7(69):eabo0235, 2022.

Josh Merel, Leonard Hasenclever, Alexandre Galashov, Arun Ahuja, Vu Pham, Greg Wayne, Yee Whye Teh, and Nicolas Heess. Neural probabilistic motor primitives for humanoid control. *arXiv preprint arXiv:1811.11711*, 2018.

Josh Merel, Saran Tunyasuvunakool, Arun Ahuja, Yuval Tassa, Leonard Hasenclever, Vu Pham, Tom Erez, Greg Wayne, and Nicolas Heess. Catch & carry: reusable neural controllers for vision-guided whole-body tasks. *ACM Transactions on Graphics (TOG)*, 39(4):39–1, 2020.

V. Mnih, K. Kavukcuoglu, D. Silver, A. A Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Rémi Munos, Tom Stepleton, Anna Harutyunyan, and Marc G Bellemare. Safe and efficient off-policy reinforcement learning. *arXiv preprint arXiv:1606.02647*, 2016.

Ofir Nachum, Honglak Lee, Shixiang Gu, and Sergey Levine. Data-efficient hierarchical reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 2018-Decem, pp. 3303–3313, 2018. URL https://sites.google.com/view/efficient-hrl.

German I Parisi, Ronald Kemker, Jose L Part, Christopher Kanan, and Stefan Wermter. Continual lifelong learning with neural networks: A review. *Neural Networks*, 113:54–71, 2019.

Karl Pertsch, Youngwoon Lee, and Joseph J Lim. Accelerating reinforcement learning with learned skill priors. *arXiv preprint arXiv:2010.11944*, 2020.

Karl Pertsch, Youngwoon Lee, Yue Wu, and Joseph Lim. Guided reinforcement learning with learned skills. 2021.

Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*, 2018.

Dushyant Rao, Fereshteh Sadeghi, Leonard Hasenclever, Markus Wulfmeier, Martina Zambelli, Giulia Vezzani, Dhruva Tirumala, Yusuf Aytar, Josh Merel, Nicolas Heess, et al. Learning transferable motor skills with hierarchical latent mixture policies. *arXiv preprint arXiv:2112.05062*, 2021.

K. Rawlik, M. Toussaint, and S. Vijayakumar. On stochastic optimal control and reinforcement learning by approximate inference. *Robotics: Science and Systems (RSS)*, 2012.

Matthew Riemer, Miao Liu, and Gerald Tesauro. Learning abstract options. *Advances in neural information processing systems*, 31, 2018.

Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635. JMLR Workshop and Conference Proceedings, 2011.

Sasha Salter, Dushyant Rao, Markus Wulfmeier, Raia Hadsell, and Ingmar Posner. Attention privileged reinforcement learning for domain transfer. 2019.

Sasha Salter, Dushyant Rao, Markus Wulfmeier, Raia Hadsell, and Ingmar Posner. Attention-privileged reinforcement learning. In *Conference on Robot Learning*, 2020.

Sasha Salter, Markus Wulfmeier, Dhruva Tirumala, Nicolas Heess, Martin Riedmiller, Raia Hadsell, and Dushyant Rao. Mo2: Model-based offline options. *Conference on Lifelong Learning Agents*, 2022.

J. Schulman, P. Abbeel, and X. Chen. Equivalence between policy gradients and soft Q-learning. *arXiv preprint arXiv:1704.06440*, 2017.

Noah Y Siegel, Jost Tobias Springenberg, Felix Berkenkamp, Abbas Abdolmaleki, Michael Neunert, Thomas Lampe, Roland Hafner, Nicolas Heess, and Martin Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. *arXiv preprint arXiv:2002.08396*, 2020.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

Avi Singh, Huihan Liu, Gaoyue Zhou, Albert Yu, Nicholas Rhinehart, and Sergey Levine. Parrot: Data-driven behavioral priors for reinforcement learning. *arXiv preprint arXiv:2011.10024*, 2020.

Richard S Sutton. Learning to predict by the methods of temporal differences. *Machine learning*, 3 (1):9–44, 1988.

Richard S Sutton, Doina Precup, and Satinder Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2):181–211, 1999.

Yee Whye Teh, Victor Bapst, Wojciech Marian Czarnecki, John Quan, James Kirkpatrick, Raia Hadsell, Nicolas Heess, and Razvan Pascanu. Distral: Robust multitask reinforcement learning. *arXiv preprint arXiv:1707.04175*, 2017.

Sebastian Thrun. Monte carlo pomdps. *Advances in neural information processing systems*, 12, 1999.

Dhruva Tirumala, Hyeonwoo Noh, Alexandre Galashov, Leonard Hasenclever, Arun Ahuja, Greg Wayne, Razvan Pascanu, Yee Whye Teh, and Nicolas Heess. Exploiting hierarchy for learning and transfer in kl-regularized rl. *arXiv preprint arXiv:1903.07438*, 2019.

Dhruva Tirumala, Alexandre Galashov, Hyeonwoo Noh, Leonard Hasenclever, Razvan Pascanu, Jonathan Schwarz, Guillaume Desjardins, Wojciech Marian Czarnecki, Arun Ahuja, Yee Whye Teh, et al. Behavior priors for efficient reinforcement learning. *arXiv preprint arXiv:2010.14274*, 2020.

E. Todorov. Linearly-solvable Markov decision problems. In *Advances in Neural Information Processing Systems*, pp. 1369–1376. MIT Press, 2007.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

Markus Wulfmeier, Abbas Abdolmaleki, Roland Hafner, Jost Tobias Springenberg, Michael Neunert, Tim Hertweck, Thomas Lampe, Noah Siegel, Nicolas Heess, and Martin Riedmiller. Compositional Transfer in Hierarchical Reinforcement Learning. (1), 2019. URL http://arxiv.org/abs/1906.11228.

Markus Wulfmeier, Dushyant Rao, Roland Hafner, Thomas Lampe, Abbas Abdolmaleki, Tim Hertweck, Michael Neunert, Dhruva Tirumala, Noah Siegel, Nicolas Heess, et al. Data-efficient hindsight off-policy option learning. *arXiv preprint arXiv:2007.15588*, 2020.

A   METHOD

A.1   TRAINING REGIME

In this section, we algorithmically describe our training setup. We relate each training phase to the principle equations in the main paper, but note that Appendices A.2 and A.3 outline a more detailed version of these equations that were actually used. We note that during BC, we apply DAGGER (Ross et al., 2011), as per Algorithm 2, improving learning rates. For further details refer to Appendix D.

Algorithm 1 APES training regime

1: *# Full training and transfer regime. For BC, gradients are prevented from flowing from π_0 to π. In practice $\pi_0 = \{\pi_i\}_{i \in \{0,...,N\}}$, multiple trained priors. During transfer, π_H, is reinitialized.*
2:
3: *# Behavioral Cloning*
4: Initialize: policy π, prior π_0, replay R_{bc}, DAGGER rate r, environment env
5: **for** Number of BC training steps **do**
6:     $R_{bc}, env \leftarrow$ collect(π, R_{bc}, env, True, r)
7:     $\pi, \pi_0 \leftarrow$ BC_update(π, π_0, R_{bc}) *# Eq. 4*
8: **end for**
9: *# Reinforcement Learning*
10: Initialize: high level policy π^H, critics $Q_{k \in \{1,2\}}$, replay R_{rl}, transfer environment env_t
11: **for** Number of RL training steps **do**
12:     $R_{rl}, env_t \leftarrow$ collect(π, R_{rl}, env_t)
13:     $\pi^H \leftarrow$ RL_policy_update(π, π_0, R_{rl}) *# Eq. 3*
14:     $Q_k \leftarrow$ RL_critic_update(Q_k, π, R_{rl}) *# Eq. 9*
15: **end for**

Algorithm 2 collect

1: *# Collects experience from either π_i or π_e, applying DAGGER at a given rate if instructed, and updates R_j, env accordingly.*
2: **function** COLLECT(π_i, R_j, env, dag=False, r=1)
3:     $\mathbf{x} \leftarrow env$.observation()
4:     $\pi_e \leftarrow env$.expert()
5:     $\mathbf{a}_i \leftarrow \pi_i(\mathbf{x})$
6:     $\mathbf{a}_e \leftarrow \pi_e(\mathbf{x})$
7:     $\mathbf{a} \leftarrow$ Bernoulli([$\mathbf{a}_i, \mathbf{a}_e$], [$r$, 1 - r])
8:     $\mathbf{x}', r_k, env \leftarrow env$.step($\mathbf{a}$)
9:     **if** dag **then**
10:         $\mathbf{a}_f \leftarrow \mathbf{a}_e$
11:     **else**
12:         $\mathbf{a}_f \leftarrow \mathbf{a}_i$
13:     **end if**
14:     $R_j \leftarrow R_j$.update($\mathbf{x}, \mathbf{a}_f, r_k, \mathbf{x}'$)
15:     **return** R_j, env
16: **end function**

A.2   VARIATIONAL BEHAVIORAL CLONING AND REINFORCEMENT LEARNING

In the following section, we omit *APES'* specific *information gating function* objective $IGF(\mathbf{x}_k)$ for simplicity and generality. Nevertheless, it is trivial to extend the following derivations to *APES*.

Behavioral Cloning (BC) and KL-Regularized RL, when considered from the variational-inference perspective, share many similarities. These similarities become even more apparent when dealing with hierarchical models. A particularly unifying choice of objective functions for BC and RL that fit with off-policy, generative, hierarchical RL: desirable for sample efficiency, are:

$$O_{bc}(\pi, \{\pi_i\}^{i \in I}) = -\sum_{i \in I} D_{KL}(\pi(\tau) \| \pi_i(\tau)), \;\; O_{rl}(\pi, \{\pi_i\}^{i \subset I}) = E_\pi(\tau)[R(\tau)] + O_{bc}(\pi, \{\pi_i\}^{i \subset I})$$

(5)

O_{bc}, corresponds to the KL-divergence between trajectories from the policy, π, and various priors, π_i. For BC, $i \in \{0, u, e\}$, denote the learnt, uniform, and expert priors. For BC, in practice, we train multiple priors in parallel: $\pi_0 = \{\pi_i\}_{i \in \{0,...,N\}}$. We leave this notation out for the remainder of this section for simplicity. When considering only the expert prior, this is the reverse KL-divergence, opposite to what is usually evaluated in the literature, (Pertsch et al., 2020). O_{rl}, refers to a lower bound on the expected optimality of each prior $\log p_{\pi_i}(O = 1)$; O denoting the event of achieving maximum return (return referred to as $R(.)$); refer to (Abdolmaleki et al., 2018), appendix B.4.3 for proof, further explanation, and necessary conditions. During transfer using RL, we do **not** have access to the expert or its demonstrations ($i \subset I := i \in \{0, u\}$).

For hierarchical policies, the KL terms are not easily evaluable. $D_{KL}(\pi(\tau) \| \pi_i(\tau)) \leq \sum_t \mathbb{E}_{\pi(\tau)} \left[D_{KL}\left(\pi^H(\mathbf{z}_t|\mathbf{x}_k) \| \pi_i^H(\mathbf{z}_t|\mathbf{x}_k)\right) + \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_k)} \left[D_{KL}\left(\pi^L(\mathbf{a}_t|\mathbf{x}_k, \mathbf{z}_t) \| \pi_i^L(\mathbf{a}_t|\mathbf{x}_k, \mathbf{z}_t)\right) \right] \right]$

[2] (Tirumala et al., 2019), is a commonly chosen upper bound. If sharing modules, e.g. $\pi_i^L = \pi^L$, or using non-hierarchical networks, this bound can be simplified (removing the second or first terms respectively). To make both Eq. (5) amendable to off-policy training (experience from $\{\pi_e, \pi_b\}$, for BC/RL respectively; π_b representing behavioral policy), we introduce importance weighting (IW), removing off-policy bias at the expense of higher variance. Combining all the above with additional individual term weighting hyperparameters, $\{\beta_i^z, \beta_i^a\}$, we attain:

$$\tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)||\pi_i(\tau)) := \mathbb{E}_{q(\tau)}\left[\sum_t \nu^q[t] \cdot \left(\beta_i^z \cdot C_{i,h}(\mathbf{z}_t|\mathbf{x}_k) + \beta_i^a \cdot \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_k)}\left[C_{i,l}(\mathbf{a}_t|\mathbf{x}_k,\mathbf{z}_t)\right]\right)\right]$$

$$\zeta_i^n = \frac{\mathbb{E}_{\pi^H(z_i|\mathbf{x}_i,k)}\left[\pi^L(\mathbf{a}_i|\mathbf{x}_i,\mathbf{z}_i,k)\right]}{n(\mathbf{a}_i|\mathbf{x}_i,k)}, \ \nu^n = \left[\zeta_1^n, \zeta_1^n\zeta_2^n, \dots, \prod_{i=1}^{\tau_t}\zeta_i^n\right], \ C_{\mu,\epsilon}(y) = \log\left(\frac{\pi_\epsilon^r(y)}{\pi_{\mu,\epsilon}^r(y)}\right)$$

$$-D_{\mathrm{KL}}(\pi(\tau)||\pi_e(\tau)) \geq -\sum_{i\in\{0,u,e\}}\tilde{D}_{\mathrm{KL}}^{\pi_e(\tau)}(\pi(\tau)||\pi_i(\tau)) \tag{6}$$

$$\mathbb{E}_{\substack{p(\mathcal{K}),\\\pi_0(\tau)}}[\log(O=1|\tau,k)] \geq \mathbb{E}_{\pi_b(\tau)}\left[\sum_t \nu^{\pi_b}[t]\cdot r_k(\mathbf{x}_t,\mathbf{a}_t)\right] - \sum_{i\in\{0,u\}}\tilde{D}_{\mathrm{KL}}^{\pi_b(\tau)}(\pi(\tau)||\pi_i(\tau)) \tag{7}$$

Where $\tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)||\pi_i(\tau))$ (for $\{\beta_i^z, \beta_i^a\} = 1$) is an unbiased estimate for the aforementioned upper bound, using q's experience. ζ_i^n is the IW for timestep i, between π and arbitrary policy n. $\nu^n[t]$ is the t^{th} element of ν^n; the cumulative IW product at timestep t. Equations 6, 7 are the BC/RL lower bounds used for policy gradients. See Appendix B.4 for a derivation, and necessary conditions, of these bounds. For BC, this bounds the KL-divergence between hierarchical and expert policies, π, π_e. For RL, this bounds the expected optimality, for the learnt prior policy, π_0. Intuitively, maximising this particular bound, maximizes return for both policy and prior, whilst minimizing the disparity between them. Regularising against an uninformative prior, π_u, encourages highly-entropic policies, further aiding at exploration and stabilising learning (Igl et al., 2019).

In RL, IWs are commonly ignored (Lillicrap et al., 2015; Abdolmaleki et al., 2018; Haarnoja et al., 2018b), thereby considering each sample equally important. This is also convenient for BC, as IWs require the expert probability distribution: not usually provided. We did not observe benefits of using them and therefore ignore them too. We employ module sharing ($\pi_i^L = \pi^L$; unless stated otherwize), and freeze certain modules during distinct phases, and thus never employ more than 2 hyperparameters, β, at any given time, simplifying the hyperparameter optimisation. These weights balance an exploration/exploitation trade-off. We use a categorical latent space, explicitly marginalising over, rather than using sampling approximations (Jang et al., 2016). For BC, we train for 1 epoch (referring to training in the expectation once over each sample in the replay buffer).

A.3 CRITIC LEARNING

The lower bound presented in Eq. (7) is non-differentiable due to rewards being sampled from the environment. Therefore, as is common in the RL literature (Mnih et al., 2015; Lillicrap et al., 2015), we approximate the return of policy π with a critic, Q. To be sample efficient, we train in an off-policy manner with TD-learning (Sutton, 1988) using the Retrace algorithm (Munos et al., 2016) to provide a low-variance, low-bias, policy evaluation operator:

$$Q_t^{\mathrm{ret}} := Q'(\mathbf{x}_t,\mathbf{a}_t,k) + \sum_{j=t}^\infty \epsilon_j^t\left[r_k(\mathbf{x}_j,\mathbf{a}_j) + \mathbb{E}_{\substack{\pi^H(\mathbf{z}|\mathbf{x}_{j+1},k),\\\pi^L(\mathbf{a}'|\mathbf{x}_{j+1},\mathbf{z},k)}}\left[Q'(\mathbf{x}_{j+1},\mathbf{a}',k)\right] - Q'(\mathbf{x}_j,\mathbf{a}_j,k)\right] \tag{8}$$

$$L(Q) = \mathbb{E}_{\substack{p(\mathcal{K}),\\\pi_b(\tau)}}\left[(Q(\mathbf{x}_t,\mathbf{a}_t,k) - \arg\min_{Q_t^{\mathrm{ret}}}(Q_t^{\mathrm{ret}}))^2\right] \qquad \epsilon_j^t = \gamma^{j-t}\prod_{i=t+1}^j \zeta_i^b \tag{9}$$

---

[2]For proof refer to Appendix B.3

Where Q_t^{ret} represents the policy return evaluated via Retrace. Q' is the target Q-network, commonly used to stabilize critic learning (Mnih et al., 2015), and is updated periodically with the current Q values. IWs are not ignored here, and are clipped between $[0, 1]$ to prevent exploding gradients, (Munos et al., 2016). To further reduce bias and overestimates of our target, Q_t^{ret}, we apply the double Q-learning trick, (Hasselt, 2010), and concurrently learn two target Q-networks, Q'. Our critic is trained to minimize the loss in Eq. (9), which regularizes the critic against the minimum of the two targets produced by both target networks.

B THEORY AND DERIVATIONS

In this section we provide proofs for the theory introduced in the main paper and in Appendix A.

B.1 THEOREM 1.

Theorem 1. *The more random variables a network depends on, the larger the covariate shift (input distributional shift, here represented by KL-divergence) encountered across sequential tasks. That is, for distributions p, q*

$$
\begin{aligned}
\mathrm{D_{KL}}\left(p(\mathbf{b}) \parallel q(\mathbf{b})\right) &\geq \mathrm{D_{KL}}\left(p(\mathbf{c}) \parallel q(\mathbf{c})\right) \\
\text{with } \mathbf{b} &= (b_0, b_1, ..., b_n) \text{ and } \mathbf{c} \subset \mathbf{b}.
\end{aligned}
\tag{10}
$$

Proof

$$
\begin{aligned}
\mathrm{D_{KL}}\left(p(\mathbf{b}) \parallel q(\mathbf{b})\right) &= \mathbb{E}_{p(\mathbf{b})}\left[\log\left(\frac{p(\mathbf{b})}{q(\mathbf{b})}\right)\right] \\
&= \mathbb{E}_{p(\mathbf{d}|\mathbf{c}) \cdot p(\mathbf{c})}\left[\log\left(\frac{p(\mathbf{d}|\mathbf{c}) \cdot p(\mathbf{c})}{q(\mathbf{d}|\mathbf{c}) \cdot q(\mathbf{c})}\right)\right] \quad with \quad \mathbf{d} \in \mathbf{b} \oplus \mathbf{c} \\
&= \mathbb{E}_{p(\mathbf{c})}\left[\mathbb{E}_{p(\mathbf{d}|\mathbf{c})}[1] \cdot \log\left(\frac{p(\mathbf{c})}{q(\mathbf{c})}\right)\right] + \mathbb{E}_{p(\mathbf{c})}\left[\mathbb{E}_{p(\mathbf{d}|\mathbf{c})}\left[\log\left(\frac{p(\mathbf{d}|\mathbf{c})}{q(\mathbf{d}|\mathbf{c})}\right)\right]\right] \\
&= \mathrm{D_{KL}}\left(p(\mathbf{c}) \parallel q(\mathbf{c})\right) + \mathbb{E}_{p(\mathbf{c})}\left[\mathrm{D_{KL}}\left(p(\mathbf{d}|\mathbf{c}) \parallel q(\mathbf{d}|\mathbf{c})\right)\right] \\
&\geq \mathrm{D_{KL}}\left(p(\mathbf{c}) \parallel q(\mathbf{c})\right) \quad given \quad \mathbb{E}_{p(\mathbf{c})}\left[\mathrm{D_{KL}}\left(p(\mathbf{d}|\mathbf{c}) \parallel q(\mathbf{d}|\mathbf{c})\right)\right] \geq 0
\end{aligned}
\tag{11}
$$

B.2 THEOREM 2.

Theorem 2. *The more random variables a network depends on, the greater its ability to distil knowledge in the expectation (output distributional shift between network and target distribution, here represented by the expected KL-divergence). That is, for target distribution p and network q with outputs a and possible inputs $\mathbf{b}$, $\mathbf{c}$, $\mathbf{d}$, such that $\mathbf{b} = (b_0, b_1, ..., b_n)$ and $\mathbf{d} \subset \mathbf{c} \subset \mathbf{b}$*

$$
\mathbb{E}_{q(\mathbf{e}|\mathbf{d})}\left[\mathrm{D_{KL}}\left(p(a|\mathbf{b}) \parallel q(a|\mathbf{c})\right)\right] \leq \mathrm{D_{KL}}\left(p(a|\mathbf{b}) \parallel q(a|\mathbf{d})\right) \quad with \quad \mathbf{e} \in \mathbf{d} \oplus \mathbf{c}
\tag{12}
$$

Proof

$$
\begin{aligned}
\mathrm{D_{KL}}\left(p(a|\mathbf{b}) \parallel q(a|\mathbf{d})\right) &= \mathbb{E}_{p(a|\mathbf{b})}\left[\log\left(\frac{p(a|\mathbf{b})}{q(a|\mathbf{d})}\right)\right] \\
&= \mathbb{E}_{p(a|\mathbf{b})}\left[\log p(a|\mathbf{b}) - \log \mathbb{E}_{q(\mathbf{e}|\mathbf{d})}[q(a|\mathbf{c})]\right] \quad with \quad \mathbf{e} \in \mathbf{d} \oplus \mathbf{c} \\
&\geq \mathbb{E}_{p(a|\mathbf{b}) \cdot q(\mathbf{e}|\mathbf{d})}\left[\log\left(\frac{p(a|\mathbf{b})}{q(a|\mathbf{c})}\right)\right] \quad given \ Jensen's \ Inequality \\
&= \mathbb{E}_{q(\mathbf{e}|\mathbf{d})}\left[\mathrm{D_{KL}}\left(p(a|\mathbf{b}) \parallel q(a|\mathbf{c})\right)\right]
\end{aligned}
\tag{13}
$$

B.3 HIERARCHICAL KL-DIVERGENCE UPPER BOUND

All proofs in this section ignore multi-task setup for simplicity. Extending to this scenario is trivial.

Upper Bound

$$
\begin{aligned}
D_{\mathrm{KL}}\left(\pi(\tau) \| \pi_i(\tau)\right) \leq \sum_t \mathbb{E}_{\pi(\tau)}[&D_{\mathrm{KL}}\left(\pi^H(\mathbf{z}_t|\mathbf{x}_t) \| \pi_i^H(\mathbf{z}_t|\mathbf{x}_t)\right) \\
&+ \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_t)}\left[D_{\mathrm{KL}}\left(\pi^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t) \| \pi_i^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t)\right)\right]]
\end{aligned}
\tag{14}
$$

Proof

$$
\begin{aligned}
D_{\mathrm{KL}}\left(\pi(\tau) \| \pi_i(\tau)\right) &= \mathbb{E}_{\pi(\tau)}\left[\log\left(\frac{\pi(\tau)}{\pi_i(\tau))}\right)\right] \\
&= \mathbb{E}_{\pi(\tau)}\left[\log\left(\frac{p(\mathbf{s}_0) \cdot \prod_t p(\mathbf{s}_{t+1}|\mathbf{x}_t, \mathbf{a}_t) \cdot \pi(\mathbf{a}_t|\mathbf{x}_t)}{p(\mathbf{s}_0) \cdot \prod_t p(\mathbf{s}_{t+1}|\mathbf{x}_t, \mathbf{a}_t) \cdot \pi_i(\mathbf{a}_t|\mathbf{x}_t)}\right)\right] \\
&= \mathbb{E}_{\pi(\tau)}\left[\log\left(\prod_t \frac{\pi(\mathbf{a}_t|\mathbf{x}_t)}{\pi_i(\mathbf{a}_t|\mathbf{x}_t)}\right)\right] \\
&= \sum_t \mathbb{E}_{\pi(\tau)}\left[D_{\mathrm{KL}}\left(\pi(\mathbf{a}_t|\mathbf{x}_t) \| \pi_i(\mathbf{a}_t|\mathbf{x}_t)\right)\right] \\
&\leq \sum_t \mathbb{E}_{\pi(\tau)}[D_{\mathrm{KL}}\left(\pi(\mathbf{a}_t|\mathbf{x}_t) \| \pi_i(\mathbf{a}_t|\mathbf{x}_t)\right) + \\
&\quad \mathbb{E}_{\pi(\mathbf{a}_t|\mathbf{x}_t)}\left[D_{\mathrm{KL}}\left(\pi(\mathbf{z}_t|\mathbf{x}_t, \mathbf{a}_t) \| \pi(\mathbf{z}_t|\mathbf{x}_t, \mathbf{a}_t)\right)\right]] \\
&= \sum_t \mathbb{E}_{\pi(\tau)}\left[\mathbb{E}_{\pi(\mathbf{a}_t, \mathbf{z}_t|\mathbf{x}_t)}\left[\log\left(\frac{\pi(\mathbf{a}_t|\mathbf{x}_t)}{\pi_i(\mathbf{a}_t|\mathbf{x}_t)}\right) + \log\left(\frac{\pi(\mathbf{z}_t|\mathbf{x}_t, \mathbf{a}_t)}{\pi_i(\mathbf{z}_t|\mathbf{x}_t, \mathbf{a}_t)}\right)\right]\right] \\
&= \mathbb{E}_{\pi(\tau)}\left[D_{\mathrm{KL}}\left(\pi(\mathbf{a}_t, \mathbf{z}_t|\mathbf{x}_t) \| \pi_i(\mathbf{a}_t, \mathbf{z}_t|\mathbf{x}_t)\right)\right] \\
&= \sum_t \mathbb{E}_{\pi(\tau)}[D_{\mathrm{KL}}\left(\pi^H(\mathbf{z}_t|\mathbf{x}_t) \| \pi_i^H(\mathbf{z}_t|\mathbf{x}_t)\right) \\
&\quad + \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_t)}\left[D_{\mathrm{KL}}\left(\pi^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t) \| \pi_i^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t)\right)\right]]
\end{aligned}
\tag{15}
$$

B.4 POLICY GRADIENT LOWER BOUNDS

B.4.1 IMPORTANCE WEIGHTS DERIVATION

$$
\tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)\|\pi_i(\tau)) = ub(D_{\mathrm{KL}}\left(\pi(\tau) \| \pi_i(\tau)\right))
\tag{16}
$$

For $\beta_i^z, \beta_i^a = 1$, where $ub(D_{\mathrm{KL}}\left(\pi(\tau) \| \pi_i(\tau)\right))$ corresponds to the hierarchical upper bound introduced in Appendix A.2.

Proof

$$
\begin{aligned}
ub(D_{\mathrm{KL}}\left(\pi(\tau) \| \pi_i(\tau)\right)) &= \sum_t \mathbb{E}_{\pi(\tau)}[D_{\mathrm{KL}}\left(\pi^H(\mathbf{z}_t|\mathbf{x}_t) \| \pi_i^H(\mathbf{z}_t|\mathbf{x}_t)\right) \\
&\quad + \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_t)}\left[D_{\mathrm{KL}}\left(\pi^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t) \| \pi_i^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t)\right)\right]] \\
&= \sum_t \mathbb{E}_{q(\tau) \cdot \frac{\pi(\tau)}{q(\tau)}}[D_{\mathrm{KL}}\left(\pi^H(\mathbf{z}_t|\mathbf{x}_t) \| \pi_i^H(\mathbf{z}_t|\mathbf{x}_t)\right) \\
&\quad + \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_t)}\left[D_{\mathrm{KL}}\left(\pi^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t) \| \pi_i^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t)\right)\right]] \\
&= \sum_t \mathbb{E}_{q(\tau) \cdot \prod_{i=0}^t \frac{\pi(\mathbf{a}_i|\mathbf{x}_i)}{q(\mathbf{a}_i|\mathbf{x}_i)}}[D_{\mathrm{KL}}\left(\pi^H(\mathbf{z}_t|\mathbf{x}_t) \| \pi_i^H(\mathbf{z}_t|\mathbf{x}_t)\right) \\
&\quad + \mathbb{E}_{\pi^H(\mathbf{z}_t|\mathbf{x}_t)}\left[D_{\mathrm{KL}}\left(\pi^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t) \| \pi_i^L(\mathbf{a}_t|\mathbf{x}_t, \mathbf{z}_t)\right)\right]] \\
&= \tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)\|\pi_i(\tau))
\end{aligned}
\tag{17}
$$

B.4.2 BEHAVIORAL CLONING UPPER BOUND

$$-D_{\mathrm{KL}}(\pi(\tau)||\pi_e(\tau)) \geq - \sum_{i \in \{0,u,e\}} \tilde{D}_{\mathrm{KL}}^{\pi_e(\tau)}(\pi(\tau)||\pi_i(\tau)) \tag{18}$$
$$for \quad \beta_i^z, \beta_i^a \geq 1$$

Proof

$$\begin{aligned}
D_{\mathrm{KL}}\left(\pi(\tau) \parallel \pi_e(\tau)\right) &\leq \sum_{i \in \{0,u,e\}} D_{\mathrm{KL}}\left(\pi(\tau) \parallel \pi_i(\tau)\right) \\
&\leq \sum_{i \in \{0,u,e\}} ub(D_{\mathrm{KL}}\left(\pi(\tau) \parallel \pi_i(\tau)\right)) \\
&= \sum_{i \in \{0,u,e\}} \tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)||\pi_i(\tau)) \quad for \quad \beta_i^z, \beta_i^a = 1 \\
&\leq \sum_{i \in \{0,u,e\}} \tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)||\pi_i(\tau)) \quad for \quad \beta_i^z, \beta_i^a \geq 1
\end{aligned} \tag{19}$$

The last line holds true as each weighted term in $\tilde{D}_{\mathrm{KL}}^{q(\tau)}(\pi(\tau)||\pi_i(\tau))$ corresponds to KL-divergences which are positive.

B.4.3 REINFORCEMENT LEARNING UPPER BOUND

$$\mathbb{E}_{\substack{p(\mathcal{K}), \\ \pi_0(\tau)}}[\log(O = 1|\tau, k)] \geq \mathbb{E}_{\pi_b(\tau)}\left[\sum_t \nu^{\pi_b}[t] \cdot r_k(\mathbf{x}_t, \mathbf{a}_t)\right] - \sum_{i \in \{0,u\}} \tilde{D}_{\mathrm{KL}}^{\pi_b(\tau)}(\pi(\tau)||\pi_i(\tau)) \tag{20}$$
$$for \quad \beta_i^z, \beta_i^a \geq 1 \quad and \quad r_k < 0$$

Proof

$$\begin{aligned}
\mathbb{E}_{\substack{p(\mathcal{K}), \\ \pi_0(\tau)}}[\log(O = 1|\tau, k)] &\geq \mathbb{E}_{\pi_b(\tau)}\left[\sum_t \nu^{\pi_b}[t] \cdot r_k(\mathbf{x}_t, \mathbf{a}_t)\right] - D_{\mathrm{KL}}\left(\pi(\tau) \parallel \pi_i(\tau)\right) \\
&\geq \mathbb{E}_{\pi_b(\tau)}\left[\sum_t \nu^{\pi_b}[t] \cdot r_k(\mathbf{x}_t, \mathbf{a}_t)\right] - \tilde{D}_{\mathrm{KL}}^{\pi_b(\tau)}(\pi(\tau)||\pi_i(\tau)), \; for \; \beta_i^z, \beta_i^a = 1 \\
&\geq \mathbb{E}_{\pi_b(\tau)}\left[\sum_t \nu^{\pi_b}[t] \cdot r_k(\mathbf{x}_t, \mathbf{a}_t)\right] - \tilde{D}_{\mathrm{KL}}^{\pi_b(\tau)}(\pi(\tau)||\pi_i(\tau)), \; for \; \beta_i^z, \beta_i^a \geq 1 \\
&\geq \mathbb{E}_{\pi_b(\tau)}\left[\sum_t \nu^{\pi_b}[t] \cdot r_k(\mathbf{x}_t, \mathbf{a}_t)\right] - \sum_{i \in \{0,u\}} \tilde{D}_{\mathrm{KL}}^{\pi_b(\tau)}(\pi(\tau)||\pi_i(\tau)), \\
&\quad for \quad \beta_i^z, \beta_i^a \geq 1
\end{aligned} \tag{21}$$

For line 1 proof see (Abdolmaleki et al., 2018). The final 2 lines hold due to positive KL-divergences.

C ENVIRONMENTS

We continue by covering each environment setup in detail.

C.1 CORRIDORMAZE

Intuitively, the agent starts at the intersection of corridors, at the origin, and must traverse corridors, aligned with each dimension of the state space, in a given ordering. This requires the agent to reach the end of the corridor (which we call half-corridor cycle), and return back to the origin, before the corridor is considered complete.

$s \in \{0, l\}^c$, $p(s_0) = \mathbf{0}^c$, $k =$ one-hot task encoding, $a \in [0, 1]$, $r_k^{\text{semi-sparse}}(\mathbf{x}_t, \mathbf{a}_t) = 1$ *if* agent has correctly completed the entire or half-corridor cycle *else* 0, $r_k^{\text{sparse}}(\mathbf{x}_t, \mathbf{a}_t) = 1$ *if* task complete *else* 0. Task is considered complete when a desired ordering of corridors have been traversed. $c = 5$ represents the number of corridors in our experiments. $l = 6$, the lengths of each corridor. States transition according to deterministic transition function $s_{t+1}^{j_t} = f(\mathbf{s}_t^{j_t}, \mathbf{a}_t)$. j_t corresponds to the index of the current corridor that the agent is in (i.e. $j_t = 0$ if the agent is in corridor 0 at timestep t). $\mathbf{s}^i$ corresponds to the i^{th} dimension of the state. States transition incrementally or decrementally down a corridor, and given state dimension s^i, if actions fall into corresponding transition action bins ψ_{inc}, ψ_{dec}. We define the transition function as follows:

$$f(\mathbf{s}_t^{j_t}, \mathbf{a}_t) = \begin{cases} \mathbf{s}_t^{j_t} + 1, & \text{if } \psi_{inc}^w(\mathbf{a}_t, j_t). \\ \mathbf{s}_t^{j_t} - 1, & \text{elif } \psi_{dec}^w(\mathbf{a}_t, j_t). \\ 0, & \text{otherwise.} \end{cases} \tag{22}$$

$\psi_{inc}^w(\mathbf{a}_t, j) = \text{bool}(\mathbf{a}_t \text{ in } [j/c, (j + 0.5 \cdot w)/c])$, $\psi_{dec}^w(\mathbf{a}_t, j) = \text{bool}(\mathbf{a}_t \text{ in } [j/c, (2 \cdot j - 0.5 \cdot w)/c])$. The smaller the w parameter, the narrower the distribution of actions that lead to transitions. As such, w, together with r_k controls the exploration difficulty of task k. We set $w = 0.9$. We constrain the state transitions to not transition outside of the corridor boundaries. Furthermore, if the agent is at the origin, $s = \mathbf{0}^c$ (at the intersection of corridors), then the transition function is ran for all values of j_t, thereby allowing the agent to transition into any corridor.

C.2 STACK

This domain is adapted from the well known gym robotics FetchPickAndPlace-v0 environment (Plappert et al., 2018). The following modifications were made: 1) 3 additional blocks were introduced, with different colours, and a goal pad, 2) object spawn locations were not randomized and were instantiated equidistantly around the goal pad, see Fig. 2, 3) the number of substeps was increased from 20 to 60, as this reduced episodic lengths, 4) a transparent hollow rectangular tube was placed around the goal pad, to simplify the stacking task and prevent stacked objects from collapsing due to structural instabilities, 5) the arm was always spawned over the goal pad, see figure Fig. 2, 6) the state space corresponded to gripper position and grasp state, as well as the object positions and relative positions with respect to the arm: velocities were omitted as access to such information may not be realistic for real robotic systems. $k =$ one-hot task encoding, $r_k^{\text{sparse}}(\mathbf{x}_t, \mathbf{a}_t) = 1$ *if* correct object has been placed on stack in correct ordering *else* 0.

D EXPERIMENTAL SETUP

We provide the reader with the experimental setup for all training regimes and environments below. We build off the softlearning code base (Haarnoja et al., 2018b). Algorithmic details not mentioned in the following sections are omitted as are kept constant with the original code base. For all experiments, we sample *batch size* number of **entire episodes** of experience during training.

D.1 MODEL ARCHITECTURES

We continue by outlining the shared model architectures across domains and experiments. Each policy network (e.g. $\pi^H, \pi^L, \pi_0^H, \pi_0^L$) is comprized of a feedforward module outlined in Table 5. The softlearning repository that we build off (Haarnoja et al., 2018b), applies tanh activation over network outputs, where appropriate, to match the predefined outpute ranges of any given module. The critic is also comprized of the same feedforward module, but is not hierarchical. To handle historical inputs, we tile the inputs and flatten, to become one large input 1-dimensional array. We ensure the input always remains of fixed size by appropriately left padding zeros. For π^H, π_0^H we use a categorical latent space of size 10. We found this dimensionality sufficed for expressing the diverse behaviours exhibited in our domains. Table 6 describes the setup for all the experiments in the main paper, including inputs to each module, level over which KL-regularization occurs (z or a), which modules are shared (e.g. π^L and π_0^L), and which modules are reused across sequential tasks. For the covariate-shift designed experiments in Table 8, we additionally reuse π^H (or π^L for RecSAC) across domains, and whose input is $\mathbf{x}_t$. For all the above experiments, any reused modules are not

Table 5: Feedforward Module, $\pi_{(0)}^{\{H,L\}}$

hidden layers	$(512, 512)$
hidden layer activation	relu
output activation	linear

Table 6: Full experimental setup. Describes inputs to each module, level over which KL-regularization occurs, which modules are shared, and which are reused across training and transfer tasks.

Name	learn $\mathbf{m}$	π_0^H	π_0^L	π^L	π^H	KL level	$\pi^L = \pi_0^L$	reused modules
APES	✓	$\mathbf{x}_{t-20:t}$	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{x}_k$	z	✓	π_0^H, π_0^L, π^L
APES-H20	✗	$\mathbf{x}_{t-20:t}$	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{x}_k$	z	✓	π_0^H, π_0^L, π^L
APES-H10	✗	$\mathbf{x}_{t-10:t}$	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{x}_k$	z	✓	π_0^H, π_0^L, π^L
APES-H1	✗	$\mathbf{x}_{t-1:t}$	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{x}_k$	z	✓	π_0^H, π_0^L, π^L
APES-S	✗	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{x}_k$	z	✓	π_0^H, π_0^L, π^L
APES-no_prior	-	–	–	$\mathbf{s}_t$	$\mathbf{x}_k$	-	–	π^L
Hier-RecSAC	-	–	–	$\mathbf{s}_t$	$\mathbf{x}_k$	-	–	–
RecSAC	-	–	–	$\mathbf{x}_k$	–	-	–	–
APES-H1-KL-a	✗	$\mathbf{x}_{t-1:t}$	$\mathbf{s}_t$	$\mathbf{s}_t$	$\mathbf{x}_k$	a	✗	π_0^H, π_0^L
APES-H1-flat	✗	–	$\mathbf{x}_{t-1:t}$	$\mathbf{s}_t$	$\mathbf{x}_k$	a	✗	π_0^L

given access to task-dependent information, namely task-id (k) and exteroceptive information (cube locations for Stack domain). This choice ensures reused modules generalize across task instances.

D.2 BEHAVIOURAL CLONING

For the BC setup, we use a deterministic, noisy, expert controller to create experience to learn off. We apply DAGGER (Ross et al., 2011) during data collection and training of policy π as we found this aided at achieving a high success rate at the BC tasks. Our DAGGER setup intermittently during data collection, with a predefined rate, samples an action from π instead of π_e, but still saves BC target action a_t as the one that would have been taken by the expert for $\mathbf{x}_k$. This setup helps mitigate covariate shift during training, between policy and expert. Noise levels were chosen to be small enough so that the expert still succeeded at the task. We trained our policies for one epoch (once over each collected data sample in the expectation). It may be possible to be more sample efficient, by increasing the ratio of gradient steps to data collection, but we did not explore this direction. The interplay we use between data collection and training over the collected experience, is akin to the RL paradigm. We build off the softlearning code base (Haarnoja et al., 2018b), so please refer to it for details regarding this interplay.

Table 7: Full Training Setup

(a) Behavioural Cloning Setup

Environment	CorridorMaze	Stack
$\pi_{(i)}$ learning rate	$3e^{-4}$	$3e^{-4}$
z categorical size	10	10
π^H history-depth	24	5
β_u^z	$1e^{-3}$	$1e^{-3}$
β_u^a	$1e^{-2}$	$1e^{-2}$
β_e^a	1	1
$\beta_0^z = \beta_0^a$	1	1
α_m	$1e^{-1}$	$1e^{-1}$
DAGGER rate	0.1	0.1
batch size	128	128
episodic length	24	35

(b) Reinforcement Learning Setup

Environment	CorridorMaze		Stack
Reward Type	sparse	semi-sparse	sparse
Transfer task	2 corridor	4 corridor	4 blocks
Q learning rate	$3e^{-6}$	$3e^{-5}$	$3e^{-5}$
π learning rate	$3e^{-4}$	$3e^{-4}$	$3e^{-4}$
$\beta_0^{z/a}$	$1e^{-2}$	$1e^{-1}$	$5e^{-2}$
$\beta_u^{z/a}$	$1e^{-2}$	0	$5e^{-4}$
Q update rate	$6e^{-4}$	$6e^{-4}$	$6e^{-4}$
Retrace λ	0.99	0.99	0.99
batch size	128	128	128
episodic length	30	60	65

Refer to Table 7a for BC algorithmic details. It is important to note here that, although we report five β hyper-parameter values, there are only two degrees of freedom. As we stop gradients flowing from π_0 to π, choice of β_0 is unimportant (as long as it is not 0) as it does not influence the interplay between gradients from individual loss terms. We set these values to 1. β_e^a's absolute value is also unimportant, and only its relative value compared to β_u^z and β_u^a matters. We also set β_e^a to 1. For the remaining two hyper-parameters, β_u^z, β_u^a, we performed a hyper-parameter sweep over three orders of magnitude, three values across each dimension, to obtain the reported optimal values. In practice $\pi_0 = \{\pi_i\}_{i \in \{0,...,N\}}$, multiple trained priors each sharing the same β_0 hyper-parameters. For α_m, denoting the hyper-paramter in Equation (3) weighing the relative contribution of the π_0^H's self-attention entropy objective $IGF(\mathbf{x}_k)$ with relation to the remainder of the RL/BC objectives, we performed a sweep over three ordered of magnitude ($1e^0, 1e^{-1}, 1e^{-2}$). This sweep was ran independent of all the other sweeps, using the optimal setup for all other hyper-parameters. We chose the hyper-parameter with lowest $D_{KL}(\pi^H || \pi_0^H)$, $\mathcal{H}(\mathbf{m})$ combination. Four seeds were ran, as for all experiments. We observed very small variation in learning across the seeds, and used the best performing seed to bootstrap off for transfer. We separately also performed a hyper-parameter sweep over π learning rate, in the same way as before. We did not perform a sweep for batch size. We found for both BC and RL setups, that conditioning on entire history for π^H was not always necessary, and sometimes hurt performance. We state the history lengths used for π^H for BC in Table 7a. This value was also used for both π^H and Q for the RL setup.

We prevent gradient flow from π_0 to π, to ensure as fair a comparison between ablations as possible: each prior distils knowledge from the same, high performing, policy π and dataset. If we simultaneously trained multiple π and π_0 pairs (for each distinct prior), it is possible that different learnt priors would influence the quality of each policy π which knowledge is distilled off. In this paper, we are not interested in investigating how priors affect π during BC, but instead how priors influence what knowledge can be distilled and transferred. We observed prior KL-distillation loss convergence across tasks and seeds, ensuring a fair comparison.

D.3 REINFORCEMENT LEARNING

During this stage of training we freeze the prior and low-level policy (if applicable, depending on the ablation). In general, any reused modules across sequential tasks are frozen (apart from π^H for the covariate shift experiments in Table 8). Any modules that are not shared (such as π^H for most experiments), are initialized randomly across tasks. The RL setup is akin to the softlearning repository (Haarnoja et al., 2018b) that we build off. We note any changes in Table 7b. We regularize against the latent or action level for, depending on the ablation, whether or not our models are hierarchical, share low level policies, or use pre-trained modules (low-level policy and prior). Therefore, we only ever regularize against, at most, two β hyper-parameters. Hyper-parameter sweeps are performed in the same way as previously. We did not sweep over *Retrace* λ, *batch size*, or *episodic length*. For Retrace, we clip the importance weights between $[0, 1]$, like in Munos et al. (2016), and perform λ returns rather than n-step. We found the Retrace operator important for sample-efficient learning.

E FINAL POLICY ROLLOUTS AND ANALYSIS

E.1 ATTENTION ANALYSIS

We plot the full attention maps for *APES* in Figure 7, including intra- state and action attention. For *CorridorMaze*, attention is primarily paid to the most recent action $\mathbf{a}_t$. For most states in the environment (excluding end of the corridor or corridor intersection states), conditioning on the previous action suffices to infer the optimal next action (e.g. continue traversing the depths of a corridor).

Figure 7: *APES* attention for π_0^H, plotted as $\log(\mathbf{m})$, for each domain (key on right; red and blue as high and low values). *APES* learns *sparse*, *domain* dependent, attention.

Therefore, it is understandable that *APES* has learnt

Figure 8: *CorridorMaze 4 corridor*. 10 final policy rollouts (episodes vertically, rollouts horizontally) for most performant method. Task: (Blue, Orange, Green, Red) corridors. Policy distribution over categorical latent space for π^H and π_0^H plotted (between policy rollouts, denoted by x_t) as vertical histograms, with colour and width denoting category and probability.

such an attention mechanism. For the remainder of the environment states (such as corridor ends), conditioning on (a history of) states is necessary to infer optimal behaviour. As such *APES* pays some attention to states. For *Stack*, attention is primarily paid to a short recent history of actions, with the weights decaying further into the past. Interestingly, attention over actions corresponding to opening/closing the gripper (the bottom row of Figure 7) decay a lot quicker, suggesting that this information is redundant. This makes sense, as there exists strong correlation between gripper actions at successive time-steps, but this correlation decays very quickly. Additionally, *APES* does not pay attention to states corresponding to gripper position (the final 3 state rows in Figure 7), as this can be inferred from the remainder of the state-space as well as the recent history of *gripper actions*.

E.2 COVARIATE SHIFT ANALYSIS

In Table 8 we report *additional return* (over a randomly initialised π^H) achieved by pre-training (over $p_{source}(\mathcal{K})$) and transferring a *task-agnostic* high-level policy π^H during transfer ($p_{trans}(\mathcal{K})$). For experiments that are not hierarchical we pre-train an equivalent non-hierarchical agent. Theorem 3.1 suggests we'd expect a larger improvement in transfer performance for priors that condition on more information. Table 8 confirms this trend demonstrating the importance of prior *covariate shift* in transferability of behaviours. This trend is less apparent for the semi-sparse domain. Additionally, for the interpolated transfer task (2 corridor),

Table 8: *Covariate Shift Analysis*. In general, reduced IA benefits more from reduced covariate shift. Sparse domains suffer more from shift, seen by clearer IA covariate trends.

	CorridorMaze		Stack
	interpolate	extrapolate	extrapolate
	sparse	semi-sparse	sparse
Approach	2 corridor	4 corridor	4 blocks
APES-H20	**0.28 ± 0.03**	0.12 ± 0.22	0.84 ± 0.06
APES-H10	0.24 ± 0.07	**0.62 ± 0.30**	**1.20 ± 0.31**
APES-H1	0.13 ± 0.02	0.34 ± 0.32	0.22 ± 0.24
APES-S	0.00 ± 0.00	0.48 ± 0.21	0.00 ± 0.17
APES-no_prior	0.00 ± 0.00	0.09 ± 0.08	0.49 ± 0.26
Hier-RecSAC	0.00 ± 0.00	0.02 ± 0.03	0.00 ± 0.01
RecSAC	0.00 ± 0.00	0.27 ± 0.13	0.19 ± 0.05
Expert	0	0	0

the solution is entirely in the support of the training set of tasks. Naïvely, one would expect pre-training to fully recover lost performance and match the most performant method. However, this is not the case as the critic, trained solely on the transfer task, quickly encourages sub-optimal out-of-distribution behaviours.

E.3 FINAL POLICY ROLLOUTS

In this section, we show final policy performance (in terms of episodic rollouts) for *APES-H1*, across each transfer domain. We additionally display the categorical probability distributions for $\pi^H(\mathbf{x}_k)$ and $\pi_0^H(F(\mathbf{x}_k))$ across each rollout to analyse the behaviour of each. $F(.)$ denotes the chosen *information gating function* for the prior (referred to as $IGF(.)$ in the main text). For *CorridorMaze 2 and 4 corridor*, seen in Figs. 8 and 9(a), we see that the full method successfully solves each respective task, correctly traversing the correct ordering of corridors. The categorical distributions for these domains remain relatively entropic. In general, latent categories cluster into those that lead the agent deeper down a corridor, and those that return the agent to the hallway. Policy and prior align their categorical distributions in general, as expected. Interestingly, however, the two categorical distributions deviate the most from each-other at the hallway, the *bottleneck state* (Sutton et al., 1999),

((a)) *CorridorMaze 2 corridor*. 10 final policy rollouts (episodes vertically, rollouts horizontally) for most performant method. Task: (Blue, Orange) corridors. Policy distribution over categorical latent space for π^H and π_0^H plotted (between policy rollouts, denoted by x_t) as vertical histograms, with colour and width denoting category and probability. Colour here does not correlate to corridor.

((b)) *Stack 4 blocks. Top)* Policy rollouts for most performant method. Task: stack blocks in order $(0, 1, 2, 3)$. *Bottom)* policy distributions akin to Fig. 9(a). Horizontal dashed lines in bottom plots refer to current sub-task (block stack), vertically transitioning upon each completion.

Figure 9: Final transfer performance for most performant method. Tasks are solved. Displaying latent distribution for both policy and prior. For both domains, policy deviates most from prior at the bottleneck state (hallway/stacking zone, for CorridorMaze/Stack), where prior multimodality exists (e.g. which corridor/block to stack next), but where determinism is required for the task at hand.

where prior multimodality (for hierarchical π_0) exists most (e.g. which corridor to traverse next). In this setting, the policy needs to deviate from the multimodal prior, and traverse only the optimal next corridor. We also observe, for the hallway, that the prior allocates one category to each of the five corridors. Such behaviour would not be possible with a flat prior.

Fig. 9(b) plots the same information for *Stack 4 blocks*. APES-H1 successfully solves the transfer task, stacking all blocks according to their masses. Similar categorical latent-space trends exist for this domain as the previous. Most noteworthy is the behaviour of both policy and prior at the *bottleneck state*, the location above the block stack, where blocks are placed. This location is visited five times within the episode: at the start $\mathbf{s}_0$, and four more times upon each stacked block. Interestingly, for this state, the prior becomes increasingly less entropic upon each successive visit. This suggests that the prior has learnt that the number of feasible *high-level* actions (corresponding to which block to stack next), reduces upon each visit, as there remains fewer lighter blocks to stack. It is also interesting that for $\mathbf{s}_0$, the red categorical value is more favoured than the rest. Here, the red categorical value corresponds to moving towards cube 0, the heaviest cube. This behaviour is as expected, as during BC, this cube was stacked first more often than the others, given its mass. For this domain, akin to *CorridorMaze*, the policy deviates most from the prior at the bottleneck state, as here it needs to behave deterministically (regrading which block to stack next).