VIEW SYNTHESIS WITH SCULPTED NEURAL POINTS

ABSTRACT

We address the task of view synthesis, generating novel views of a scene given a set of images as input. In many recent works such as NeRF (17), the scene geometry is parameterized using neural implicit representations (MLPs). Implicit neural representations have achieved impressive visual quality but have drawbacks in computational efficiency. In this work, we propose a new approach that performs view synthesis using point clouds. It is the first point-based method that achieves better visual quality than NeRF while being $100\times$ faster in rendering speed. Our approach builds on existing works on differentiable point-based rendering but introduces a novel technique we call "Sculpted Neural Points (SNP)", which significantly improves the robustness to errors and holes in the reconstructed point cloud. We further propose to use view-dependent point features based on spherical harmonics to capture non-Lambertian surfaces, and new designs in the point-based rendering pipeline that further boost the performance. Finally, we show that our system supports fine-grained scene editing in a user-friendly way.

1 INTRODUCTION

We address the task of view synthesis: generating novel views of a scene given a set of images as input. It has important applications including augmented and virtual reality. View synthesis can be posed as the task of recovering from existing images a rendering function that maps an arbitrary viewpoint into an image. In many recent works, this rendering function is parameterized using neural implicit representations of scene geometry (17; 44; 19; 2; 20; 5; 18). In particular, NeRF (17) represents 3D geometry as a neural network that maps a 3D coordinate to a scalar indicating occupancy.

Figure 1: The overall pipeline of the Sculpted Neural Points. We first use an MVS network to extract a point cloud. We then sculpt the point cloud by pruning (blue points) and adding (red points). The featurized point cloud finally passes through a differentiable rendering module to produce the image.

Implicit neural representations have achieved impressive visual quality but are typically computationally inefficient. To render a single pixel, NeRF needs to evaluate the neural network at hundreds of 3D points along the ray, which is wasteful because most of the 3D spaces are unoccupied. NeRF's implicit representation also makes it inflexible for scene editing operations such as deformation, which is important for downstream applications including augmented reality and video games. Several works enable NeRF to do scene editing (14; 13; 37; 22), but either the way of editing is highly constrained, or images captured under all desired object poses are required.

On the other hand, this limitation is easily overcome by explicit representations such as meshes or point clouds. To rasterize a mesh or a point cloud, no computation is wasted on unoccupied 3D spaces. Scene editing such as composition and deformation is also straightforward. Moreover, rasterizing meshes or point clouds is a mature technology already widely deployed in the industry for movies and video games, capable of producing real-time performance and high realism.

An intriguing question is whether we can achieve state-of-the-art visual quality by using explicit representations such as point clouds. The basic framework of point-based neural rendering is to represent the scene as a featurized point cloud, which is reconstructed through a multiview stereo (MVS) system. The features are learned by maximizing photoconsistency on the input images via differentiable rendering. Although this framework has been studied in several recent works (1; 34; 10), the overall rendering quality still lags behind NeRF, mainly due to the ghosting effects and blurriness caused by the errors in geometry.

Our approach adopts this basic framework but introduces a novel technique we call "Sculpted Neural Points (SNP)", which significantly improves the robustness to the errors and holes in the reconstructed point cloud. The idea is to "sculpt" the initial point cloud reconstructed by the MVS system. In particular, we remove existing points and add additional points to improve the photo-consistency of the renders against input images. These sculpting decisions are discrete in nature, but are tightly coupled with gradient-based optimization of the continuous per-point features.

We further propose a few novel designs in the point-based rendering pipeline that boost the performance. We use spherical harmonics (SH) in high-dimensional point feature space to capture non-Lambertian visual effects, which is faster and better than using MLPs. Inspired by Dropout (31), we propose a point dropout layer that significantly improves the generalization to novel views. Last but not least, we find that it is essential to not use any normalization layers in the U-Net.

Compared to previous works that use point cloud-based representation, ours is the first model that achieves better rendering quality than NeRF, while being $100\times$ faster in rendering, and reducing the training time by 66%. We evaluate our method on common benchmarks including DTU (7), LLFF (16), NeRF-Synthetic (17), and Tanks&Temples (9), and our method shows better or comparable performance against all baselines. We encourage the reader to watch the supplementary video to compare our methods against baselines and see the effectiveness of point sculpting.

Finally, we show that our model allows fine-grained scene editing in a user-friendly way. Compared to previous works that can only do object-level composition (14; 43; 38) or require a special user interface (13), our point-based representation inherently supports editing at a finer resolution, and users can use existing graphics toolbox to edit the point cloud without any custom changes.

The main contributions of this paper are three-fold: 1) We propose a novel point-based approach to view synthesis, "Sculpted Neural Points", a technique that is key to achieving high quality and view-consistent output; 2) We demonstrate, for the first time, that a point-based method can achieve better visual quality than NeRF while being $100\times$ faster in rendering. 3) We propose several improvements to the point-based rendering pipeline that significantly boost the visual quality.

2   RELATED WORK

Methods for view synthesis can be categorized based on how they represent the scene geometry.

View Synthesis with Implicit Representations NeRF (17) uses a neural network to map a 3D spatial location to volume density. To render a pixel, the neural network needs to be repeatedly evaluated along the ray, making rendering computationally expensive. Followup works on NeRF (44; 43; 19) focus on improving the speed or the generalization ability to new scenes or with a limited number of reference views. Our method does not use an implicit representation; instead, we

explicitly represent the scene geometry using a point cloud, which allows much faster rendering, as well as easy and flexible scene editing.

View Synthesis with Voxels NV (14) first combines neural volume rendering with voxel grids, and NSVF (11) proposes to construct a progressive pruning process to obtain fine-grained and sparse voxels. Yu et al. (42) further combines the voxel representations with spherical harmonics, achieving a very fast training speed. To apply neural rendering, voxel-based methods generally need to traverse the entire voxel space along each ray, whereas with our point-based representation we only rasterize the points on the surfaces. The complexity and memory cost grows cubically for voxels as resolution increases while only quadratically for our method.

View Synthesis with Point Clouds To use point clouds for view synthesis, existing approaches typically use an external multiview stereo system to reconstruct a point cloud from the input images, and then optimize the features and 3D positions of each point through differentiable rendering.

NPBG (1) is the first work to combine neural rendering with point clouds; it uses a featurized point cloud to represent the scene, and rasterizes with one-pixel point splats at multiple scales followed by a post-processing U-Net to fill the holes. SynSin (34) proposes a soft rasterization pipeline that allows better gradient flow and produces smoother results. Our method achieves significantly better visual quality compared to them. Pulsar (10) uses featurized spheres to represent the scene, and proposes a very efficient soft rasterizer that can rasterize millions of spheres in less than 100 milliseconds. Pulsar qualitatively shows that geometry reconstruction can be done through its differentiable rendering system, but has shown no quantitative results on view synthesis. We adopt Pulsar as our rendering backbone.

There are a few concurrent works using point cloud representations. NPBG++ (23) focuses on lifting the requirement of per-scene optimization. It does not revise the geometry and is thus more sensitive to the point cloud quality compared to ours. It also proposes to use view-dependent point features, but parameterized as MLP rather than SH as we do. Point-NeRF (35) uses a featurized point cloud to represent the scene geometry, but renders with volume rendering instead of point rasterization. ADOP (26) mainly focuses on unbounded outdoor scenes with large exposure changes among views.

To revise the initial point cloud provided by an MVS system, existing differential renderers compute gradients with respect to the 3D coordinates of each point. Pulsar (10) approximates the gradient by modeling points as spheres with a certain radius, with the color blending weights changing smoothly with respect to the distance of the camera ray to the sphere center. ADOP (26) instead computes the partial derivatives of the photometric loss with respect to the point positions by taking the finite difference in the pixel space.

Our method builds upon existing techniques of differentiable point-based rendering but differs substantially in how we revise the initial point cloud given by an MVS system. Although we find prior methods capable of *local* revision around the existing points by adjusting their locations using the gradients, such local operations, however, cannot fill large holes or add new points in empty spaces far away. In contrast, our sculpting technique is global. It does not use gradients and can add new points in locations arbitrarily far away from existing points.

3 APPROACH OVERVIEW

An overview of our approach is illustrated in Fig. 1. The input is a set of $H \times W$ RGB images $\{I_1, \ldots I_m\}$ of m reference views and their corresponding intrinsics and extrinsics camera parameters, $\{C_1, \ldots C_m\}$. We define the camera projection function Π and its inverse Π^{-1} as follows:

$$\Pi(P, C) := [K_C (R_C P + t_C)]^{\downarrow}; \ \Pi^{-1}(p, d_p, C) := R_c^{-1} \left(K_C^{-1} d_p \left[\begin{array}{c} p \\ 1 \end{array} \right] - t_c \right) \qquad (1)$$

where K_C, R_C and t_C are the intrinsics, rotation, and translation of camera C. $P \in \mathbb{R}^3$ is a 3D point and $p \in \mathbb{R}^2$ is its 2D projection in the pixel space with depth d_p. Further, $([X, Y, Z]^T)^{\downarrow}$ is defined as $([X/Z, Y/Z]^T)$. Our approach consists of three main components: point cloud reconstruction, point cloud sculpting, and differentiable rendering. In this section, we describe the backbone of our approach with only point cloud reconstruction and differentiable rendering, and leave point cloud sculpting to Sec. 4.

3.1 Point Cloud Reconstruction

We use an MVS network (15) to extract a dense depth map $\{D_1, \ldots D_m\} \in \mathbb{R}^{\frac{H}{4} \times \frac{W}{4}}$ for each of the reference views. Each depth map is un-projected into a set of 3D points by applying the inverse projection in Eqn. 1. The points from all depth maps are combined, without any filtering, to form a larger set of *original* 3D points $P_o = \{p_1, ..., p_N\}$. We associate point $p_i \in \mathbb{R}^3$ with a learnable K-dimensional feature vector $f_i \in \mathbb{R}^K$ and a learnable scalar $o_i \in [0, 1]$ representing its *opacity*.

3.2 Differentiable Rendering

Given a featurized 3D point cloud and a target view, we use a differentiable rendering function with learnable parameters to map the point cloud into an RGB image. For each scene individually, we learn the parameters of this rendering function together with the point features through gradient descent to minimize photometric errors against the input images.

Spherical Harmonic Point Feature We use the spherical harmonics (SH) functions to model the view-dependent effects. Recently Yu et al. (43; 42) brings up the attention of using SH in neural rendering. Unlike previous works that use SH directly in RGB space, we propose to use SH in high-dimensional feature space, where we model each element of a vector with a set of SH coefficients.

Specifically, we use the SH basis up to degree 2, which yields 9 basis in total. For a 3D point p_i, the SH layer takes its feature vector f_i and a target view direction v as input, and outputs a feature vector $s_i \in \mathbb{R}^{\frac{K}{9}}$. Note that evaluating SH functions is cheap as it avoids matrix multiplication operations. We find that it leads to better performance and faster rendering speed compared to the MLP parameterization used in NeRF (17), as shown in Sec. 5.3.

Differentiable Soft Rasterization We use soft rasterization proposed in (12; 10) to convert the view-dependent features into a 2D feature map F given a target view. Soft rasterization blends the features of multiple points hit by a camera ray with weights depending on their depth and opacity values. We refer the readers to Pulsar (10) for details.

Note that in addition to updating f_i, we also compute the gradient of the photometric loss *w.r.t.* the point positions p_i and opacity o_i, and optimize them through gradient descent, following (10). Experiment results show that such gradient-based refinement helps improve fine geometric details.

Point Dropout Layer We find that the existing point rendering pipeline is prone to over-fitting, *i.e.,* the image quality on test views is much worse than on training views. The reasons are two-fold: **1.** The "training set" for view synthesis consists of only tens of images, and there are barely any data augmentation techniques that can be applied except random cropping. **2.** Some points are covered by their neighbors in training views, but get visible in test views. The features for these points are not well-optimized. The blending weights are very low for these points when the rasterizer is "soft".

To resolve the above issue, we propose to use a "Point Dropout Layer" before rasterization. In each forward pass, we randomly select a subset of points to feed into the rasterizer, whose size depends on the dropout rate p_d. Note that at inference time, we cannot simply rasterize all points and multiply the output by p_d as in the neural network (NN) case (31), because the rasterization operation is non-linear in contrast to the matrix multiplication in NN. Since it is impossible to traverse all subsets, we simply rasterize L multiple random subsets and average the output feature maps at inference time.

Intuitively, the point dropout layer allows us to train on an ensemble of point clouds, and give all points a chance to get optimized even if they are covered, and thus alleviating the over-fitting problem. As a side effect, we also gain a speed-up because fewer points get rasterized. Although the design is simple, this idea has not been explored in previous works, and our experiments show that it significantly improves the image quality on test views.

2-D Rendering without BatchNorm Given a target view, we convert the 2D feature map F into the RGB image I_t with a 2D ConvNet. We use a U-Net (25) with two downsampling layers and two upsampling layers, and optionally one more upsampling layer to produce high-resolution outputs.

Previous works (1; 23) directly use the original U-Net design with BatchNorm (6) layers, which we find unsuitable for view synthesis task for two reasons. First, the small training set size makes the estimation of the moving average in BatchNorm unstable. Second, the benefit of accelerated training is minimal since the network is shallow. Therefore, we use no normalization layer in our U-Net.

Figure 2: (a) The initial point cloud is incomplete and noisy. (b) The point cloud filtered with DCC (36) is accurate but incomplete. (c) The output of SNP. It removes most of the outliers and the points added (colored red) further fill the missing areas. (d) The closest training view, which shows what the actual geometry should look like. (e) The **blue** curve and dashed **black** curve represents the reconstructed surface and the actual surface, respectively. A set of candidates is generated along the ray from camera B. c is discarded because it occludes the existing surface in view A, and a is discarded because we only keep the closest $M = 5$ non-occluding points. Only b is added.

4 POINT SCULPTING

The point clouds reconstructed from MVS usually contain many errors, even with the state-of-the-art MVS systems. The errors typically take the form of distorted or incomplete geometry. If we directly use such point clouds, the synthesized views will have poor visual quality with salient artifacts. To address this issue, we introduce a new technique we call "point sculpting". It has two steps, *Point Pruning* and *Point Adding*. The sculpting procedure and outputs are illustrated in Fig. 2.

4.1 POINT PRUNING

The MVS system we use produces a dense depth map for each input image. Like other depth-based systems (39; 36; 3), it adopts a *fusion* step that merges the depth maps from different views into a final point cloud. A geometry consistency check is often used to remove outlier points. Using the depth maps, the consistency check projects a pixel into another view, reprojects the corresponding point back, and sees if the original pixel is recovered up to a threshold. For example, COLMAP (28; 27) defines the consistency error $\psi_{\boldsymbol{p}}^{i,j}$ between view i and j for pixel $\boldsymbol{p}$ as:

$$\boldsymbol{q} = \Pi(\Pi^{-1}(\boldsymbol{p}, d_{\boldsymbol{p}}^i, C^i), C^j); \ \psi_{\boldsymbol{p}}^{i,j} = \left\| \boldsymbol{p} - \Pi(\Pi^{-1}(\boldsymbol{q}, d_{\boldsymbol{q}}^j, C^j), C^i) \right\|_2 \tag{2}$$

where $\boldsymbol{q}$ is $\boldsymbol{p}$'s corresponding point in view j. Yan et al. (36) further propose an improved version, Dynamic Consistency Checking (DCC), which achieved the state-of-the-art filtering results.

The main problem of this type of forward-backward consistency check is that it tends to be over-aggressive in filtering out points, resulting highly incomplete geometry that is detrimental to view synthesis. In datasets such as DTU (7) and LLFF (16), many areas are only visible in a small number of views (or just a single view). Those areas can easily be filtered out by this check as no confident match could be found.

Therefore, we take the raw depth maps from the multiview stereo system and propose a new technique for our own consistency checking geared toward view synthesis. We check only the forward consistency to maximize completeness while still removing outliers. Formally, a pixel $\boldsymbol{p}$ in view i passes the check if and only if

$$\bigcap_{j=1}^{m} \left[D^j(\Pi^{-1}(\boldsymbol{p}, d_{\boldsymbol{p}}^i, C^i)) \geq \delta_d \cdot d_{\boldsymbol{q}}^j \right] \tag{3}$$

where $\boldsymbol{q}$ is $\boldsymbol{p}$'s corresponding point in view j (same as in Eqn. 2), $d_{\boldsymbol{q}}^j$ is the predicted depth of q in view j, $D^j(\cdot)$ is the depth of a point in view j (the z value of a 3D point in camera j's coordinate), and δ_d is a hyperparameter controlling the relative tolerance.

Intuitively, our point pruning method keeps a point as long as it is not significantly closer than the original surface to *any* reference view camera. It filters out the points that are floating in the free space between the actual surface and the camera, which are likely to be outliers. It also keeps all points that are only visible in a small number of views. Although the position of such points may not be accurate, it is useful to keep them as candidates for further optimization.

4.2 Point Adding

As Fig. 2 shows, after pruning, the point cloud can have holes, either due to points being pruned or incorrect depth estimates (e.g. depth estimates that are close to infinity or zero). Previous works (10; 41) tackled this problem by performing gradient-based updates to the point locations. However, such updates are limited to local changes of existing points and are unable to recover large areas of missing geometry.

We thus introduce a technique to add new points to the pruned point cloud. The basic idea is to find a set of 3D points that, if added to the point cloud, could help minimize the photometric error after optimization of the point features. Note that these new points do not need to be perfect; they just need to be a superset of the ground truth geometry, because the extraneous points can get optimized through the subsequent gradient-based optimization. On the other hand, an excessive number of new points can lead to overfitting and slower rendering, so a good balance is needed. Our point adding algorithm consists of two steps:

- *Optimizing with existing points:* We optimize the features and opacity of the current points through gradient descent until convergence. For the i-th input image, we extract an error map between the rendered and ground-truth image: $E_i = ||I_i^{gt} - I_i^{render}||_1$. Note that we directly treat point features as RGB values during rasterization and use no U-Net in this step, because U-Net hallucination is harmful.

- *Proposing new points:* For a pixel (u, v) in an input view i, we check if its rendering error $E_i(u, v)$ is bigger than a pre-defined threshold δ_e. If so, we sample 3D points uniformly along the ray of the pixel within the bounds of the scene, and search for points that do not occlude any of the existing points in any of the input views. If multiple such points exist, we propose the closest M points, where M is a hyperparameter. We go through all pixels in all input views, collect all the proposed points, and add them to the existing point cloud.

The design of this algorithm builds upon the assumption that our rendering pipeline can approximate the radiance of each point arbitrarily well on the *input images* and that any high rendering error can only be caused by incomplete geometry, as those areas having no points covered can only take the default background color. Based on this assumption, we propose new points for pixels with high rendering errors, but exclude points that occlude the existing surface in other views. We propose up to M closest points and choose $M = 5$ in our experiments to strike a good balance between geometry coverage and rendering speed.

We can alternate between gradient-based optimization and point adding for multiple rounds, but in practice we find one round of point adding to be sufficient for good results. We present the full details of the point adding algorithm in Appendix C.

5 Experiments

5.1 Experiment Details

Datasets We evaluate our method on DTU (7), LLFF (16; 17), NeRF's Realistic Synthetic 360° (17), and Tanks&Temples (9). The datasets we choose provide good coverage of both forward-facing and 360° scenes. We evaluate using PSNR, SSIM and LPIPS (47) metrics.

Baselines We compare our model with NeRF (17). On DTU and LLFF, we run the state-of-the-art point-based rendering methods NPBG (1) and SynSin (34) using the same external MVS system to reconstruct point clouds, with no pruning or adding. We additionally compare against other concurrent point-based methods including NPBG++ (23) and Point-NeRF (35).

Implementation Details We implement our method with PyTorch (21) and PyTorch3D (24). We experiment on a single RTX 3090 GPU. We optimize for 50,000 steps on each scene with a batch size of 1. We initialize all SH coefficients for each point as 0s and the point opacity as 1. We initialize the U-Net parameters randomly. We set the point radii to be a dataset-specific hyperparameter, which is the same for all points and fixed. The point dropout rate d_p is 0.5 for all experiments. See Appendix B for details of the MVS network and other implementations.

5.2 PRIMARY RESULTS

| NPBG | SynSin | NeRF | Ours | Ground Truth |

Figure 3: Qualitative comparison of our model v.s. baselines on the LLFF dataset.

Results on DTU The quantitative comparison is presented in Tab. 1. Results show that our model has better SSIM and LPIPS, and slightly worse PSNR compared to NeRF. We present the visualizations in Fig. 11, Appendix D. We claim to use LPIPS as the major quality metric, as we find that PSNR and SSIM may not reflect actual visual quality because they are highly sensitive to small pixel shifts (See Appendix. A).

Table 1: Quantitative results on the DTU and the LLFF dataset. For all tables in this paper, we mark the best number in **bold** and the second-best number with underline.

	DTU				LLFF			
Method	NPBG(1)	SynSin(34)	NeRF(17)	**SNP (ours)**	NPBG(1)	SynSin(34)	NeRF(17)	**SNP (ours)**
PSNR↑	19.38	21.04	**28.97**	26.68	19.98	22.34	**26.50**	25.32
SSIM↑	0.652	0.714	0.846	**0.884**	0.624	0.705	0.811	**0.817**
LPIPS↓	0.412	0.337	0.266	**0.156**	0.454	0.351	0.250	**0.229**

Results on LLFF The quantitative results are shown in Tab. 1. Similar to DTU, our method achieves consistently better SSIM and LPIPS, while being slightly worse in PSNR. Qualitative comparisons are shown in Fig. 3. Compared to NeRF, our model can reconstruct very fine details. Our method also has significantly better visual quality compared to the two point-based baselines.

Results on Tanks&Temples We present the numbers in Tab. 2. All baselines numbers are copied from Point-NeRF (35). Our method achieves comparable quality as Point-NeRF, while being significantly better than other baselines. We present qualitative comparisons in Fig. 14, Appendix D.

Table 2: Quantitative results on Tanks&Temples.

	Tanks&Temples				
Method	NV(14)	NeRF(17)	NSVF(11)	Point-NeRF(35)	**SNP (ours)**
PSNR↑	23.70	25.78	28.40	29.61	**29.78**
SSIM↑	0.848	0.864	0.900	**0.954**	0.942
LPIPS$_{Alex}$↓	0.260	0.198	0.153	0.080	**0.079**

Results on NeRF-Synthetic Results are shown in Tab. 3. Our method achieves comparable performance to NeRF while being worse than Point-NeRF, which is also reflected in Fig. 4. Our method is better at capturing the reflective drum surfaces, while struggles with the microphone which has fine geometry. Our explanation is that our view-dependent point features are very expressive in modeling high-frequency textures, while our point cloud is not accurate enough in case of fine geometries.

Table 3: Quantitative results on the NeRF-Synthetic dataset. NPBG++ only presents results on the hotdog, ficus, and mic scenes. All other baseline numbers are copied from the Point-NeRF paper.

	NeRF-Synthetic (all 8 scenes)				NeRF-Synthetic (3 scenes)	
Method	NPBG(1)	NeRF(17)	Point-NeRF(35)	**SNP (ours)**	NPBG++(23)	**SNP (ours)**
PSNR↑	24.56	31.01	**33.31**	27.47	28.67	**29.16**
SSIM↑	0.923	0.947	**0.978**	0.939	0.952	**0.961**
LPIPS↓	0.109	0.081	**0.049**	0.067	0.050	**0.037**

NPBG   NeRF   Point-NeRF   Ours   Ground Truth

Figure 4: Qualitative comparison of our model v.s. baselines on the NeRF-Synthetic dataset.

5.3 ABLATION STUDIES

Table 4: Ablation studies on the DTU dataset.

	View-dependent Layer Latency	Num. Points	Dropout Rate	PSNR↑	SSIM↑	LPIPS↓
Use DCC(36) Filtering	15ms	3.3M	50%	19.97	0.844	0.196
No Adding; No Pruning	15ms	4.2M	50%	25.06	0.836	0.201
No Adding	15ms	4.0M	50%	26.15	0.882	0.163
No Gradient-based Refine	15ms	4.4M	50%	26.52	0.880	0.157
No View Dependence	N/A	4.4M	50%	25.67	0.876	0.160
View Dependence w/ MLP	79ms	4.4M	50%	26.30	0.881	0.160
No Point Dropout	31ms	4.4M	0%	25.40	0.852	0.191
Low Dropout Rate	23ms	4.4M	25%	26.47	0.880	0.158
High Dropout Rate	8ms	4.4M	75%	26.46	0.883	0.157
BatchNorm(6) in UNet	15ms	4.4M	50%	25.19	0.857	0.171
InstanceNorm(32) in UNet	15ms	4.4M	50%	26.08	0.869	0.169
Complete Model	15ms	4.4M	50%	26.68	0.884	0.156

DCC   No Adding;   No Adding   No Grad-based   Ours   Ground Truth
Filtering   No Pruning   Refinement

Figure 5: Qualitative comparison of point sculpting v.s. baselines on the DTU dataset.

We conduct ablation studies of our proposed designs. We show results in Tab. 4. In the 1st block, We compare with several baselines on point cloud refinement, including 1) the filtering algorithm DCC (36) which achieves SOTA performance on MVS, 2) using the raw MVS point cloud without any pruning or adding, 3) pruning with the proposed *point pruning* but no *point adding*, 4) using the same pointcloud as the complete model, but keep the point positions and opacity values fixed during gradient updates. Also see Fig. 5 for qualitative comparisons. Results show that all proposed geometry refinement components contribute to the final model. While *point pruning* contributes to sharper object boundaries near the head of the plush, *point adding* is especially helpful for filling large holes on the table in the rabbit scene. See Fig. 9 in Appendix C for visualizations of the point cloud generated by each method. We also encourage the readers to watch the supplementary video to see that our method achieves better view consistency compared to baselines.

The 2nd block shows that using SH reduces the layer latency by 82% and improves the PSNR by 0.38dB compared to MLP. For the MLP baseline, we use a 2-layers MLP with 256 hidden units, which takes as input the concatenation of the point feature and the positional-encoded view direction, following NeRF. See also Fig. 12, Appendix D for visualization of the non-Lambertian effect learned

by our model. The 3rd block shows that using dropout layer improves the PSNR by 1.28dB, and the model is not sensitive to the dropout rate. The 4th block shows that not using any normalization layers improves the PSNR by 1.49dB compared to using BatchNorm, and by 0.60dB compared to using InstanceNorm.

5.4 SCENE EDITING

We show that our system supports, with high fidelity, scene editing operations such as scene composition, object deformation, and erasing. Results are shown in the inset figure on the right. Composition is achieved by first co-training two scenes with separate point features and a shared U-Net, then

Composition   Deformation   Erasing

putting the points into the same scene at inference time. For deformation, we export the sculpted point cloud into MeshLab (4), where we manually select the moving part and its axis of rotation. For erasing, we filter out points based on their z coordinates.

Compared to existing neural rendering pipelines that support scene editing, our system has two main advantages: **1. Fine-grained editing**: Previous works (14; 43; 38) use explicit representations like voxel grids, which are typically limited in resolution. Therefore, they can only achieve object-level operations such as composition. In comparison, we represent object surfaces densely with millions of points, so we can do fine-grained editing such as object deformation. **2. Ease of use**: Previous works doing scene editing with NeRF either require a special interface to take user inputs (13), or a complex pipeline that uses meshes as an intermediate representation (45). In contrast, our point cloud representation is directly supported by nearly all graphics toolboxes such as MeshLab or Blender, which allows users to edit the scene intuitively without any specialized tool.

5.5 INFERENCE SPEED, TRAINING TIME, AND MODEL SIZE

We compare our model's inference speed, training time, and model size with a few baselines on the NeRF-Synthetic dataset, shown in Tab. 5. All speeds are benchmarked using an RTX 3090 GPU. Compared to NeRF, our model is more than 100× faster in inference and requires only 33% training time. PlenOctrees (43) bakes the radiance field into a voxel-based cache, resulting in faster rendering speed but also significantly larger model size and longer training time. NPBG (1) achieves faster inference speed by their one-pixel point splats with the cost of worse visual quality. Finally, we are about 25× faster than Point-NeRF (35) in rendering while other metrics are roughly the same.

Table 5: On NeRF-Synthetic Dataset, we comparison on model inference speed, training time, model size, and rendering quality (measured in LPIPS).

	NeRF(17)	PlenOctrees(43)	NPBG(1)	Point-NeRF(35)	**SNP (ours)**
Inference↑ (FPS)	0.053	127	20.3	0.192	5.06
Training↓ (Hours)	20	50	6.9	8.0	6.6
Model Size↓	14MB	1.9GB	31MB	106MB	290MB
LPIPS↓	0.081	0.053	0.109	0.049	0.067

6 DISCUSSIONS AND LIMITATIONS

There are a few limitations that need to be addressed in future work: **1) MVS dependency**. Although the proposed point sculpting can partly solve this problem, the performance of the system still depends heavily on the MVS quality. That said, as MVS systems continue to improve, we do not see this as a fundamental limitation in the long run. **2) View Consistency**. Our system has a 2D U-Net and is thus only approximately 3D consistent. Especially when viewed in videos, some background areas have flickering effects due to the hallucination of U-Net. Doing away with a 2D post-processing network is a future direction. **3) Far-away background**. Our current system cannot deal with outdoor scenes with arbitrarily far-away objects (*e.g.* the sky or clouds). Using a spherical environment map as in (46; 26) could resolve this problem.

Reproducibility Statement

We provide the full implementation details of the algorithms and datasets we use in Appendix. B and Appendix. C. We also include an anonymous version of our source code in the supplementary materials. We will release all data pre-processing code, the model checkpoints, and the training code for all experiments in this paper after the reviewing process.

REFERENCES

[1] Aliev, K.A., Sevastopolsky, A., Kolos, M., Ulyanov, D., Lempitsky, V.: Neural point-based graphics. In: Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXII 16. pp. 696–712. Springer (2020)

[2] Chen, A., Xu, Z., Zhao, F., Zhang, X., Xiang, F., Yu, J., Su, H.: Mvsnerf: Fast generalizable radiance field reconstruction from multi-view stereo. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 14124–14133 (2021)

[3] Chen, R., Han, S., Xu, J., Su, H.: Visibility-aware point-based multi-view stereo network. IEEE transactions on pattern analysis and machine intelligence **43**(10), 3695–3708 (2020)

[4] Cignoni, P., Callieri, M., Corsini, M., Dellepiane, M., Ganovelli, F., Ranzuglia, G., et al.: Meshlab: an open-source mesh processing tool. In: Eurographics Italian chapter conference. vol. 2008, pp. 129–136. Salerno, Italy (2008)

[5] Garbin, S.J., Kowalski, M., Johnson, M., Shotton, J., Valentin, J.: Fastnerf: High-fidelity neural rendering at 200fps. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 14346–14355 (2021)

[6] Ioffe, S., Szegedy, C.: Batch normalization: Accelerating deep network training by reducing internal covariate shift. In: International conference on machine learning. pp. 448–456. PMLR (2015)

[7] Jensen, R., Dahl, A., Vogiatzis, G., Tola, E., Aanæs, H.: Large scale multi-view stereopsis evaluation. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 406–413 (2014)

[8] Kingma, D.P., Ba, J.: Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980 (2014)

[9] Knapitsch, A., Park, J., Zhou, Q.Y., Koltun, V.: Tanks and temples: Benchmarking large-scale scene reconstruction. ACM Transactions on Graphics (ToG) **36**(4), 1–13 (2017)

[10] Lassner, C., Zollhofer, M.: Pulsar: Efficient sphere-based neural rendering. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 1440–1449 (2021)

[11] Liu, L., Gu, J., Zaw Lin, K., Chua, T.S., Theobalt, C.: Neural sparse voxel fields. Advances in Neural Information Processing Systems **33**, 15651–15663 (2020)

[12] Liu, S., Li, T., Chen, W., Li, H.: Soft rasterizer: A differentiable renderer for image-based 3d reasoning. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 7708–7717 (2019)

[13] Liu, S., Zhang, X., Zhang, Z., Zhang, R., Zhu, J.Y., Russell, B.: Editing conditional radiance fields. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 5773–5783 (2021)

[14] Lombardi, S., Simon, T., Saragih, J., Schwartz, G., Lehrmann, A., Sheikh, Y.: Neural volumes: Learning dynamic renderable volumes from images. ACM Trans. Graph. **38**(4), 65:1–65:14 (2019)

[15] Ma, Z., Teed, Z., Deng, J.: Multiview stereo with cascaded epipolar raft. arXiv preprint arXiv:2205.04502 (2022)

[16] Mildenhall, B., Srinivasan, P.P., Ortiz-Cayon, R., Kalantari, N.K., Ramamoorthi, R., Ng, R., Kar, A.: Local light field fusion: Practical view synthesis with prescriptive sampling guidelines. ACM Transactions on Graphics (TOG) **38**(4), 1–14 (2019)

[17] Mildenhall, B., Srinivasan, P.P., Tancik, M., Barron, J.T., Ramamoorthi, R., Ng, R.: Nerf: Representing scenes as neural radiance fields for view synthesis. In: European conference on computer vision. pp. 405–421. Springer (2020)

[18] Niemeyer, M., Barron, J.T., Mildenhall, B., Sajjadi, M.S., Geiger, A., Radwan, N.: Regnerf: Regularizing neural radiance fields for view synthesis from sparse inputs. arXiv preprint arXiv:2112.00724 (2021)

[19] Park, K., Sinha, U., Barron, J.T., Bouaziz, S., Goldman, D.B., Seitz, S.M., Martin-Brualla, R.: Nerfies: Deformable neural radiance fields. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 5865–5874 (2021)

[20] Park, K., Sinha, U., Hedman, P., Barron, J.T., Bouaziz, S., Goldman, D.B., Martin-Brualla, R., Seitz, S.M.: Hypernerf: A higher-dimensional representation for topologically varying neural radiance fields. arXiv preprint arXiv:2106.13228 (2021)

[21] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., Chintala, S.: Pytorch: An imperative style, high-performance deep learning library. In: Wallach, H., Larochelle, H., Beygelzimer, A., d'Alché-Buc, F., Fox, E., Garnett, R. (eds.) Advances in Neural Information Processing Systems 32, pp. 8024–8035. Curran Associates, Inc. (2019)

[22] Pumarola, A., Corona, E., Pons-Moll, G., Moreno-Noguer, F.: D-nerf: Neural radiance fields for dynamic scenes. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 10318–10327 (2021)

[23] Rakhimov, R., Ardelean, A.T., Lempitsky, V., Burnaev, E.: Npbg++: Accelerating neural point-based graphics. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 15969–15979 (2022)

[24] Ravi, N., Reizenstein, J., Novotny, D., Gordon, T., Lo, W.Y., Johnson, J., Gkioxari, G.: Accelerating 3d deep learning with pytorch3d. arXiv:2007.08501 (2020)

[25] Ronneberger, O., Fischer, P., Brox, T.: U-net: Convolutional networks for biomedical image segmentation. In: International Conference on Medical image computing and computer-assisted intervention. pp. 234–241. Springer (2015)

[26] Rückert, D., Franke, L., Stamminger, M.: Adop: Approximate differentiable one-pixel point rendering. ACM Transactions on Graphics (TOG) **41**(4), 1–14 (2022)

[27] Schönberger, J.L., Zheng, E., Frahm, J.M., Pollefeys, M.: Pixelwise view selection for unstructured multi-view stereo. In: European Conference on Computer Vision. pp. 501–518. Springer (2016)

[28] Schönberger, J.L., Frahm, J.M.: Structure-from-Motion Revisited. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (2016)

[29] Schönberger, J.L., Zheng, E., Pollefeys, M., Frahm, J.M.: Pixelwise View Selection for Unstructured Multi-View Stereo. In: European Conference on Computer Vision (ECCV) (2016)

[30] Smith, L.N., Topin, N.: Super-convergence: Very fast training of neural networks using large learning rates. In: Artificial Intelligence and Machine Learning for Multi-Domain Operations Applications. vol. 11006, p. 1100612. International Society for Optics and Photonics (2019)

[31] Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., Salakhutdinov, R.: Dropout: a simple way to prevent neural networks from overfitting. The journal of machine learning research **15**(1), 1929–1958 (2014)

[32] Ulyanov, D., Vedaldi, A., Lempitsky, V.: Instance normalization: The missing ingredient for fast stylization. arXiv preprint arXiv:1607.08022 (2016)

[33] Wei, Y., Liu, S., Rao, Y., Zhao, W., Lu, J., Zhou, J.: Nerfingmvs: Guided optimization of neural radiance fields for indoor multi-view stereo. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 5610–5619 (2021)

[34] Wiles, O., Gkioxari, G., Szeliski, R., Johnson, J.: Synsin: End-to-end view synthesis from a single image. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 7467–7477 (2020)

[35] Xu, Q., Xu, Z., Philip, J., Bi, S., Shu, Z., Sunkavalli, K., Neumann, U.: Point-nerf: Point-based neural radiance fields. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 5438–5448 (2022)

[36] Yan, J., Wei, Z., Yi, H., Ding, M., Zhang, R., Chen, Y., Wang, G., Tai, Y.W.: Dense hybrid recurrent multi-view stereo net with dynamic consistency checking. In: European Conference on Computer Vision. pp. 674–689. Springer (2020)

[37] Yang, B., Zhang, Y., Xu, Y., Li, Y., Zhou, H., Bao, H., Zhang, G., Cui, Z.: Learning object-compositional neural radiance field for editable scene rendering. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 13779–13788 (2021)

[38] Yang, B., Zhang, Y., Xu, Y., Li, Y., Zhou, H., Bao, H., Zhang, G., Cui, Z.: Learning object-compositional neural radiance field for editable scene rendering. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 13779–13788 (2021)

[39] Yao, Y., Luo, Z., Li, S., Fang, T., Quan, L.: Mvsnet: Depth inference for unstructured multi-view stereo. In: Proceedings of the European Conference on Computer Vision (ECCV). pp. 767–783 (2018)

[40] Yao, Y., Luo, Z., Li, S., Zhang, J., Ren, Y., Zhou, L., Fang, T., Quan, L.: Blendedmvs: A large-scale dataset for generalized multi-view stereo networks. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 1790–1799 (2020)

[41] Yifan, W., Serena, F., Wu, S., Öztireli, C., Sorkine-Hornung, O.: Differentiable surface splatting for point-based geometry processing. ACM Transactions on Graphics (TOG) **38**(6), 1–14 (2019)

[42] Yu, A., Fridovich-Keil, S., Tancik, M., Chen, Q., Recht, B., Kanazawa, A.: Plenoxels: Radiance fields without neural networks. arXiv preprint arXiv:2112.05131 (2021)

[43] Yu, A., Li, R., Tancik, M., Li, H., Ng, R., Kanazawa, A.: Plenoctrees for real-time rendering of neural radiance fields. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 5752–5761 (2021)

[44] Yu, A., Ye, V., Tancik, M., Kanazawa, A.: pixelnerf: Neural radiance fields from one or few images. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 4578–4587 (2021)

[45] Yuan, Y.J., Sun, Y.T., Lai, Y.K., Ma, Y., Jia, R., Gao, L.: Nerf-editing: geometry editing of neural radiance fields. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 18353–18364 (2022)

[46] Zhang, K., Riegler, G., Snavely, N., Koltun, V.: Nerf++: Analyzing and improving neural radiance fields. arXiv preprint arXiv:2010.07492 (2020)

[47] Zhang, R., Isola, P., Efros, A.A., Shechtman, E., Wang, O.: The unreasonable effectiveness of deep features as a perceptual metric. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 586–595 (2018)

Appendix

A LIMITATION OF PSNR AND SSIM AS VIEW SYNTHESIS METRICS

PSNR, SSIM, and LPIPS are commonly used metrics to measure the similarity between two images. The LPIPS paper (47) found that LPIPS is significantly more robust than PSNR or SSIM under distortions such as random noise, blurring, and spatial shifts. Although the evidence is pretty strong for the 2D cases, the robustness of the three metrics is seldom discussed in the context of view synthesis, where 3D geometry plays a key role.

We here provide a detailed case study to show that LPIPS is more robust and consistent with human perception than PSNR and SSIM for the novel view synthesis task, and is more suitable as an evaluation metric.

A.1 MISALIGNMENT IN NOVEL VIEW SYNTHESIS

Our key observation is that spatial misalignment is a very common type of error in the view synthesis task. The misalignment could be caused by inaccurate camera intrinsics and extrinsics (e.g., the COLMAP camera pose used in LLFF). Even in the DTU dataset, where the cameras are carefully calibrated with a robotic arm, there is misalignment caused by the ambiguity in geometry. For example, many background objects are only visible in one view, which makes it impossible to synthesize pixels that are identical to the ground truth.

Such errors in the camera poses of existing views will cause small shifts in the rendering of a new target view. We find that PSNR and SSIM, especially PSNR, can drop significantly in the presence of such pixel shifts, even though they have no detectable impact on the perceived visual quality. In contrast, LPIPS is relatively more robust. In Fig. 6, we show by a synthetic experiment that a slight shift could cause a huge drop in PSNR, while LPIPS is robust to such shift, behaving more similar to the human perceptual system, which is very *insensitive* to such shift. See the figure caption for details.

(a)   (b)   (c)
7.17/0.095/**0.242** **7.54**/**0.237**/0.401   Ground Truth

Figure 6: The numbers under each image are PNSR, SSIM, and LPIPS. Based on the reference image (c), we create (a) by shifting 1 pixel, and (b) by adjusting the pixel intensities toward grey. Clearly (a) is visually more similar to the reference image, while only LPIPS agrees with the fact.

We also conduct an experiment on the NeRF-Synthetic dataset to demonstrate our findings, where the ground-truth camera poses are perfect. We apply a tiny noise $\sim \mathcal{N}(0, 0.01\mathbf{I})$ in the tangent space to the camera rotation. As shown in Tab. 6, under such a small perturbation, the PSNR and SSIM of our method and NeRF become even lower than the NPBG baseline, which has significantly worse visual quality, while our LPIPS score is consistently better. In Fig. 7, we show the visual effect of such perturbation.

Table 6: We apply an almost imperceptible random noise $\sim \mathcal{N}(0, 0.01\mathbf{I})$ to the camera rotation in the tangent space. While PSNR and SSIM are sensitive to such perturbation, LPIPS remains stable.

	NeRF	Ours	NPBG	NeRF	Ours
Camera Noise	✓	✓	✗	✗	✗
PSNR↑	24.21	22.70	24.56	31.01	27.47
SSIM↑	0.887	0.876	0.923	0.947	0.939
LPIPS↓	0.089	0.088	0.109	0.081	0.067

(a) Ours + Noise
19.05/0.888/0.080

(b) Reference

(c) Error Map
of (a)&(b)

(d) Ours
28.67/0.972/0.051

(e) NPBG
22.71/0.910/0.082

(f) NeRF + Noise
19.28/0.893/0.074

Figure 7: The numbers under each image are PSNR, SSIM, and LPIPS. We see from (a) and (b) that the tiny perturbation of camera poses is perceptually undetectable, unless visualized as the error map (c). Under perturbation, our method achieves better visual quality compared to NPBG (e), which is only reflected by LPIPS, but not PSNR or SSIM.

A.2 QUALITATIVE EVALUATION

We show qualitative results on the LLFF dataset in Fig. 8. Our rendering results have better visual quality and contain sharper details compared to NeRF, while having lower PSNR due to the misalignment caused by imperfect camera parameters. We further apply a 3×3 Gaussian blurring to our results, which leads to worse visual quality but higher PSNR. It indicates that blurred images could have advantages in PSNR under misalignment, whereas LPIPS always prefers our sharper results.

18.12/**0.666**/0.316   16.34/0.619/**0.259**   16.74/0.568/0.319

20.25/**0.591**/0.317   18.56/0.580/**0.223**   19.23/0.584/0.264

21.33/0.742/0.308   20.40/**0.824**/**0.197**   20.05/0.737/0.266

NeRF   Ours   Ours + blurring   Ground Truth

Figure 8: The numbers under each image are PNSR, SSIM, and LPIPS towards the reference image. See text for details.

B IMPLEMENTATION DETAILS

B.1 DATASETS

DTU We select 10 scenes from the DTU test set. We only use scenes from the test set because the training data of CER-MVS(15) includes the DTU training scenes. The render resolution is 400×300, following PixelNeRF (44). We reserve 1 in every 7 images for testing, resulting in 42 training views and 7 test views.

LLFF (16; 17) LLFF contains 8 forward-facing scenes. Following NeRF, we render under the resolution of 1008×720 and reserve $1/8$ of the views for testing.

NeRF-Synthetic We use the same setting as NeRF (17). The training set and test set for each scene contain 100 and 200 images respectively, and the resolution is 800×800.

Tanks&Temples We test on 5 scenes using the split and masks provided by NSVF (11). The render resolution is 1088×640, following Point-NeRF (35).

B.2 MVS RECONSTRUCTION

We use the CER-MVS (15) network to extract depth maps for all scenes. We scale the scenes so that the median depth is about 600, which is the depth scale that CER-MVS was trained on. For the DTU dataset, we use the CER-MVS trained on the DTU training set, which has no overlap with our test scenes. For the NeRF-Synthetic and the Tanks&Temples datasets, we use the CER-MVS trained on BlendedMVS (40). For LLFF, since the domain gap is large, we take the CER-MVS pre-trained on DTU and finetune the model individually for each scene with the dense depth map provided by COLMAP (28; 29). Specifically, we use COLMAP customized by the authors of NerfingMVS (33), which additionally generates a confidence mask based on the geometric consistency. We apply loss only to the areas with a positive mask. We finetune for 5k steps on each scene, which takes about 1 hour.

After the point sculpting step, we downsample the point cloud sizes to 500K for LLFF and NeRF-Synthetic, and 1M for DTU and Tanks&Temples, to make the training and inference speed roughly the same for all scenes.

B.3 MODEL DETAILS

The feature vector f_i attached to each point is 288-dim, and the shaded feature outputted by the SH layer is 32-dim. Unlike using the tiny 8-dim feature vector as in NPBG (1), we find that increasing the feature dimension would monotonically give better results. We choose the dimension by balancing the performance and speed/memory cost.

For the point dropout layer, we use a dropout rate $p_d = 0.5$. At inference time we rasterize $L = 2$ random subsets for all experiments. We empirically find that $L = 2$ gives a significant improvement in performance over $L = 1$, while the advantage is minimal for averaging more subsets.

The U-Net we use has two down-sampling layers and two up-sampling layers with skip connections between the feature maps with the same resolution. Empirically, we find that limiting the capacity of the U-Net could reduce artifacts and leads to better generalization to novel views. Therefore, we use a shallower network compared to the 5-layer U-Net used in NPBG (1). For the LLFF, NeRF-Synthetic, and Tanks&Temples datasets which have higher resolution, we rasterize at half resolution and add an additional up-sampling layer to output the high-resolution images.

We use an L_1 loss between the rendered image and the target. We also add a total variation loss on the 2D feature map to improve the smoothness of the output:

$$L_{TV}(F) = \sum_{i,j} |F_{i+1,j} - F_{i,j}| + |F_{i,j+1} - F_{i,j}| \qquad (4)$$

The final loss can be written as $L = L_1 + \lambda_{TV} \cdot L_{TV}$, where λ_{TV} is set to 0.01 in all experiments. The learning rates for the U-Net, the feature vectors f, the point position p, and the opacity o are set

to 10^{-4}, 10^{-2}, 10^{-4}, 10^{-4}, respectively. The rasterization "softness" hyper-parameter γ is selected to be 10^{-3}. The opacity is passed through a sigmoid layer to map its range into $[0, 1]$.

We use the Adam optimizer (8) with the OneCycleLR learning rate scheduler (30), and train the model with batch size of 1 for 50,000 steps for all experiments. No augmentation including random cropping is applied. We find using a larger batch size and augmentations are not helpful.

We set the point radius to be 1.5×10^{-3}, 1.0×10^{-3}, 7.5×10^{-3} for all scenes in DTU, LLFF and NeRF-Synthetic, respectively. For Tanks&Temples, since there is a large scale variance among scenes, we use different radius for each scene. Specifically, radius are 1.0×10^{-3} for "Ignatius" and "Family", 1.0×10^{-2} for "Truck" and "Caterpillar", and 5.0×10^{-3} for "Barn".

C THE POINT SCULPTING ALGORITHM

For point pruning, we set the depth tolerance threshold to $\delta_d = 0.8$ in all experiments.

The formal description of the point adding algorithm is presented in Alg. 1. The definition of Π, Π^{-1}, R_C and t_C are the same as Eqn. 1 in the main body of the paper.

For DTU, we set z_{near} and z_{far} to be 800 and 1400, respectively. For LLFF, since those are unbounded scenes, we borrow the idea of using inverse depth as the NDC parameterization in NeRF. We sample uniformly in the inverse depth space, and the equivalent z_{near} and z_{far} is 800 and $+\infty$. For NeRF-Synthetic, we use $z_{near} = 2.0$ and $z_{far} = 6.0$, and for Tanks&Temples we find the depth range for each scene using the bounding box provided by the NSVF (11) authors.

z_{step} is set so that there are 100 depth bins. The hyperparameters δ_e is set to $5 \cdot Avg(E)$, as we find that using δ_e relative to the average error improves the robustness. We keep the closest $M = 5$ points for each ray. Fig. 9 shows the visualization of the point cloud generated by DCC (36), the initial MVS point cloud ("No Adding; No Pruning"), the point cloud filtered by our pruning only ("No Adding"), and our point sculpting method. We see that most of the outlier points floating in free spaces are pruned by our method (blue points in "Pruning Only"). We also show how many points get pruned and added in Tab. 7. Note that the initial numbers of points for each scene are slightly different because we filter out the points based on the scene depth range z_{near} and z_{far}. More points are added for *scan110*, *scan114* and *scan118* (corresponding to the last 3 rows in Fig. 9), where the tables in the scene contain large holes in the initial point cloud.

Table 7: Number of points statistics for pruning and adding.

					Number of Points ($\times 10^5$)						
					Scan Id.						
	1	4	15	24	32	33	49	110	114	118	Avg.
Initial	42.93	39.53	43.51	45.20	42.61	45.30	43.64	37.42	39.42	40.11	41.97
Pruning	-1.75	-2.22	-0.86	-1.10	-2.71	-3.89	-1.87	-1.60	-1.38	-1.94	-1.93
Adding	1.34	0.80	1.31	1.32	1.71	1.60	1.42	8.87	8.93	11.50	3.88

Algorithm 1 Point Adding

1: **Input** Differentiable renderer R, Initial point cloud P_o, Cameras $\{C_{1:m}\}$,
2: Reference images $\{I_{1:m}^{ref}\}$, Depth maps $\{D_{1:m}\}$, Scene near bound z_{near},
3: Scene far bound z_{far}, Depth sampling stride z_{step}, Error map threshold δ_e,
4: Max candidates to keep for each ray M.
5: **Output** Updated point cloud P_o
6:
7: Train model R with current P_o on reference views until convergence.
8: Render images $\{I_{1:m}^{pred}\}$ and compute error maps $\{E_{1:m} = ||I_{1:m}^{pred} - I_{1:m}^{ref}||_1\}$.
9: Candidates $= \emptyset$
10: **for** $i = 0 : m$ **do**   ▷ loop over the views
11:     **for** $u = 0 : H, v = 0 : W$ **do**   ▷ loop over all pixels
12:         **if** $E_i(u, v) \geq \delta_e$ **then**   ▷ propose in the regions with large error
13:             Candidates $=$ SAMPLECANDIDATES($C_i, (u, v)$)
14:             counter $= 0$
15:             **for** c **in** Candidates **do**
16:                 **if** EVALUATECANDIDATES($c, C_{1:m}, D_{1:m}$) $== 1$ **then**
17:                     $P_o \leftarrow P_o \cup c$ ▷ add to the point cloud
18:                     counter $=$ counter $+ 1$
19:                 **end if**
20:                 **if** counter $\geq$ M **then**
21:                     **break**   ▷ break once we have M candidates
22:                 **end if**
23:             **end for**
24:         **end if**
25:     **end for**
26: **end for**
27:
28: **function** SAMPLECANDIDATES($C, (u, v)$)
29:     Candidates $= \emptyset$
30:     **for** $z = z_{near} : z_{step} : z_{far}$ **do**   ▷ linearly sample the depth
31:         Candidates $\leftarrow$ Candidates $\cup \Pi^{-1}([u, v]^T, z, C)$ ▷ add the 3D point
32:     **end for**
33:     **return** Candidates
34: **end function**
35:
36: **function** EVALUATECANDIDATES($c, C_{1:m}, D_{1:m}$)
37:     no_conflict $= 1$
38:     **for** $i = 0 : m$ **do**   ▷ loop over the views
39:         $(u_i, v_i) = \Pi(c, C_i)$ ▷ the corresponding 2D point
40:         $[x_i, y_i, z_i]^T = R_{C_i}c + t_{C_i}$ ▷ c in the i-th camera coordinates
41:         **if** $0 \leq u_i \leq H - 1, 0 \leq v_i \leq W - 1$ **and** $z_i < D_i(u_i, v_i)$ **then**
42:             no_conflict $= 0$ ▷ conflict if c occludes the existing surface
43:         **end if**
44:     **end for**
45:     **return** no_conflict
46: **end function**

| Closest Reference | DCC | No Adding; No Pruning | No Adding | Point Sculpting (Ours) |

Figure 9: Qualitative comparison of different point cloud refinement algorithms. Compared to the initial point cloud ("No Adding; No Pruning"), our point sculpting method removes the outliers (the blue ones in the "No Adding" column), and adds new points (the red ones) that further fill the missing areas. Although DCC (36) provides point clouds with higher accuracy in the foreground, the completeness is much worse than our results. For scenes where the initial point cloud quality is low (*e.g.,* the bottom 3 rows), more points are used to fill the holes. **Although the final sculpted point cloud can still contain outliers and small holes, those can be handled by the gradient-based refinement.**

D   MORE VISUALIZATIONS

Due to the limited space in the main body of the paper, we present more visualizations of our model in this section, to help the readers better compare our methods with the baselines. Results are presented in Fig. 10, 11, 12, 13, 14. See figure captions for detailed comparisons.

Figure 10: Compared to NeRF, our model can reconstruct very fine details such as the thin leaves in the *fern* scene; the cracks on the bones, the letters on the board, and the textures on the carpet in the *horns* scene; the strips on the flowers and leaves in the *orchids* and the *leaves* scene. Our method also has significantly better visual quality compared to the two point-based baselines

| | NPBG | SynSin | NeRF | Ours | Ground Truth |

Figure 11: Our model can capture fine details, such as the cracks on the statue, the antenna and tiles on the roof, and the letters on the soup can and the earphone. NeRF results are often over-smoothed. The NPBG results contain some degrees of detail but are noisy, while fine details are often missing in the SynSin results.

Figure 12: Qualitative results of the proposed spherical harmonics view-dependent shader. Two crops are rendered using the same camera pose and two different virtual viewing directions. Results show that our model can effectively learn the appearance of highly non-Lambertian surfaces.

NPBG   NeRF   Point-NeRF   Ours   Ground Truth

Figure 13: Qualitative comparison of our method against baselines on the NeRF-Synthetic dataset. Our method is especially good at capturing surfaces with complex textures and strong non-Lambertian effects, such as the glossy ball and the transparent drum surfaces. For tiny structures such as the microphone and the ficus leaves, our rendering tends to be over-smoothed compared to Point-NeRF.

Point-NeRF   Ours   Ground Truth

Figure 14: Qualitative comparison of our model v.s. Point-NeRF(35) on the Tanks&Temples dataset. Our model renders smoother results in general, especially on reflective or transparent surfaces (*e.g.*, the windows of the truck).

E PER-SCENE BREAKDOWN

We show the per-scene PSNR, SSIM and LPIPS in Tab. 8, 9, 10, 11 and 12.

PSNR↑										
	1	4	15	24	32	33	49	110	114	118
NPBG(1)	16.91	18.07	17.54	18.58	17.62	15.47	17.48	22.87	22.49	26.75
SynSin (34)	19.69	18.22	19.16	19.86	17.81	15.57	19.46	26.54	25.41	28.63
NeRF(17)	**28.43**	**26.74**	**25.79**	**28.03**	**26.87**	**26.49**	**28.35**	**31.34**	**29.10**	**38.55**
Ours	24.90	25.15	25.08	24.98	25.21	23.26	25.00	30.47	29.03	33.74

SSIM↑										
	1	4	15	24	32	33	49	110	114	118
NPBG(1)	0.576	0.558	0.640	0.615	0.644	0.604	0.687	0.733	0.711	0.756
SynSin(34)	0.681	0.638	0.698	0.639	0.726	0.629	0.760	0.813	0.771	0.789
NeRF(17)	0.818	0.737	0.830	0.793	0.878	0.888	0.888	0.878	0.841	**0.906**
Ours	**0.851**	**0.845**	**0.901**	**0.862**	**0.894**	**0.898**	**0.893**	**0.900**	**0.889**	0.904

LPIPS↓										
	1	4	15	24	32	33	49	110	114	118
NPBG(1)	0.411	0.417	0.410	0.407	0.429	0.476	0.423	0.391	0.373	0.384
SynSin(34)	0.322	0.345	0.333	0.334	0.329	0.348	0.340	0.324	0.341	0.351
NeRF(17)	0.236	0.341	0.242	0.253	0.180	0.169	0.212	0.370	0.369	0.283
Ours	**0.159**	**0.175**	**0.120**	**0.132**	**0.147**	**0.154**	**0.151**	**0.175**	**0.172**	**0.176**

Table 8: Per-scene quantitative results on the DTU dataset.

PSNR↑								
	Room	Fern	Fortress	Leaves	Orchids	Flower	T-Rex	Horns
NPBG(1)	22.75	19.33	24.35	15.71	15.95	21.06	19.86	20.79
SynSin(34)	26.81	20.37	28.04	16.80	16.43	25.03	21.59	23.64
NeRF(17)	**32.70**	**25.17**	**31.16**	**20.92**	**20.36**	27.40	**26.80**	**27.45**
Ours	30.35	23.80	30.88	18.76	20.14	**27.75**	24.73	26.14

SSIM↑								
	Room	Fern	Fortress	Leaves	Orchids	Flower	T-Rex	Horns
NPBG(1)	0.813	0.569	0.766	0.441	0.397	0.654	0.686	0.668
SynSin(34)	0.883	0.621	0.836	0.548	0.450	0.783	0.768	0.751
NeRF(17)	**0.948**	**0.792**	0.881	**0.690**	0.641	0.827	**0.880**	0.828
Ours	0.941	0.784	**0.901**	0.649	**0.677**	**0.859**	0.870	**0.853**

LPIPS↓								
	Room	Fern	Fortress	Leaves	Orchids	Flower	T-Rex	Horns
NPBG(1)	0.433	0.500	0.343	0.480	0.557	0.401	0.459	0.459
SynSin(34)	0.328	0.405	0.237	0.384	0.473	0.258	0.355	0.366
NeRF(17)	**0.178**	0.280	0.171	0.316	0.321	0.219	**0.249**	0.268
Ours	0.231	**0.230**	**0.149**	**0.289**	**0.248**	**0.185**	0.255	**0.242**

Table 9: Per-scene quantitative results on the LLFF dataset.

PSNR↑	Chair	Drums	Ficus	Hotdog	Lego	Mat.	Mic	Ship
NPBG(1)	26.47	21.53	24.60	29.01	24.84	21.58	26.62	21.83
NPBG++(23)	-	-	24.61	32.31	-	-	29.08	-
NeRF(17)	33.00	25.01	30.13	36.18	32.54	**29.62**	32.91	28.65
Point-NeRF(35)	**35.40**	**26.06**	**36.13**	**37.30**	**35.04**	29.61	**35.95**	**30.97**
Ours	30.49	22.78	25.43	33.24	27.94	26.02	28.80	25.07

SSIM↑	Chair	Drums	Ficus	Hotdog	Lego	Mat.	Mic	Ship
NPBG(1)	0.939	0.904	0.940	0.964	0.923	0.887	0.959	0.866
NPBG++(23)	-	-	0.925	0.964	-	-	0.967	-
NeRF(17)	0.967	0.925	0.964	0.974	0.961	0.949	0.980	0.856
Point-NeRF(35)	**0.991**	**0.954**	**0.993**	**0.991**	**0.988**	**0.971**	**0.994**	**0.942**
Ours	0.962	0.913	0.933	0.977	0.949	0.939	0.972	0.866

LPIPS↓	Chair	Drums	Ficus	Hotdog	Lego	Mat.	Mic	Ship
NPBG(1)	0.085	0.112	0.078	0.075	0.119	0.134	0.060	0.210
NPBG++(23)	-	-	0.070	0.050	-	-	0.029	-
NeRF(17)	0.046	0.091	0.044	0.121	0.050	0.063	0.028	0.206
Point-NeRF(35)	**0.023**	**0.078**	**0.022**	0.037	**0.024**	**0.072**	**0.014**	**0.124**
Ours	0.049	0.081	0.050	**0.036**	0.057	**0.072**	0.025	0.167

Table 10: Per-scene quantitative results on the NeRF-Synthetic dataset.

PSNR↑	Ignatius	Truck	Barn	Caterpillar	Family
NV(14)	26.54	21.71	20.82	20.71	28.72
NeRF(17)	25.43	25.36	24.05	23.75	30.29
NSVF(11)	27.91	26.92	27.16	26.44	33.58
Point-NeRF(35)	28.43	**28.22**	29.15	27.00	**35.27**
Ours	**29.62**	28.05	**29.80**	**27.37**	34.07

SSIM↑	Ignatius	Truck	Barn	Caterpillar	Family
NV(14)	0.992	0.793	0.721	0.819	0.916
NeRF(17)	0.920	0.860	0.750	0.860	0.932
NSVF(11)	0.930	0.895	0.823	0.900	0.954
Point-NeRF(35)	0.961	**0.950**	**0.937**	**0.934**	**0.986**
Ours	**0.968**	0.931	0.915	0.919	0.979

LPIPS$_{Alex}$↓	Ignatius	Truck	Barn	Caterpillar	Family
NV(14)	0.117	0.312	0.479	0.280	0.111
NeRF(17)	0.111	0.192	0.395	0.196	0.098
NSVF(11)	0.106	0.148	0.307	0.141	0.063
Point-NeRF(35)	0.069	**0.077**	0.120	**0.111**	0.024
Ours	**0.038**	0.096	**0.109**	0.135	**0.018**

Table 11: Per-scene quantitative results on the Tanks&Temples dataset.

PSNR↑										
	1	4	15	24	32	33	49	110	114	118
Use DCC(36) Filtering	13.03	16.10	20.81	19.44	17.76	13.87	16.61	27.74	26.14	28.16
No Adding; No Pruning	23.47	23.51	23.84	23.37	23.31	21.93	23.51	28.97	27.76	30.88
No Adding	25.06	25.33	24.98	24.60	25.10	23.19	24.78	28.65	28.43	31.42
No Gradient-based Refine	24.99	25.13	24.72	24.90	25.00	22.99	24.75	30.24	28.88	33.61
No View Dependence	24.07	24.52	24.07	23.49	24.45	22.70	23.63	28.81	28.02	32.95
View Dependence w/ MLP	24.56	24.96	24.53	24.50	24.74	23.06	24.05	29.96	28.91	33.70
No Point Dropout	24.05	23.85	24.34	23.81	23.97	22.70	23.96	29.40	25.21	32.75
Low Dropout Rate	24.75	25.09	24.63	24.78	24.97	23.01	24.67	30.25	28.95	33.61
High Dropout Rate	24.79	25.07	24.94	24.43	25.11	23.02	24.62	30.17	28.88	33.57
BatchNorm(6) in UNet	22.68	23.35	23.79	23.88	23.59	22.67	23.70	28.57	27.67	31.99
InstanceNorm(32) in UNet	24.89	24.83	23.56	24.76	25.03	21.72	24.52	30.01	28.50	32.96
Complete Model	24.90	25.15	25.08	24.98	25.21	23.26	25.00	30.47	29.03	33.74

SSIM↑										
	1	4	15	24	32	33	49	110	114	118
Use DCC(36) Filtering	0.772	0.790	0.888	0.846	0.861	0.824	0.850	0.872	0.862	0.870
No Adding; No Pruning	0.799	0.798	0.859	0.817	0.837	0.850	0.844	0.859	0.844	0.855
No Adding	0.853	0.847	0.902	0.868	0.897	0.898	0.894	0.886	0.887	0.892
No Gradient-based Refine	0.846	0.840	0.898	0.861	0.889	0.894	0.890	0.898	0.882	0.904
No View Dependence	0.837	0.832	0.890	0.857	0.889	0.892	0.887	0.890	0.884	0.901
View Dependence w/ MLP	0.845	0.838	0.897	0.862	0.893	0.895	0.889	0.898	0.890	0.906
No Point Dropout	0.815	0.870	0.817	0.834	0.854	0.865	0.859	0.870	0.856	0.876
Low Dropout Rate	0.848	0.841	0.895	0.858	0.890	0.893	0.890	0.897	0.885	0.901
High Dropout Rate	0.851	0.843	0.899	0.860	0.895	0.895	0.892	0.900	0.889	0.904
BatchNorm(6) in UNet	0.822	0.791	0.883	0.839	0.850	0.878	0.869	0.876	0.870	0.890
InstanceNorm(32) in UNet	0.849	0.841	0.873	0.856	0.888	0.848	0.879	0.885	0.881	0.894
Complete Model	0.851	0.845	0.901	0.862	0.894	0.898	0.893	0.900	0.889	0.904

LPIPS↓										
	1	4	15	24	32	33	49	110	114	118
Use DCC(36) Filtering	0.217	0.238	0.135	0.146	0.175	0.223	0.193	0.205	0.211	0.215
No Adding; No Pruning	0.205	0.220	0.169	0.185	0.208	0.213	0.200	0.198	0.200	0.209
No Adding	0.167	0.177	0.125	0.135	0.146	0.150	0.154	0.195	0.183	0.197
No Gradient-based Refine	0.158	0.176	0.123	0.133	0.149	0.153	0.154	0.175	0.174	0.178
No View Dependence	0.165	0.179	0.127	0.132	0.152	0.155	0.154	0.179	0.178	0.179
View Dependence w/ MLP	0.169	0.179	0.129	0.136	0.152	0.152	0.156	0.177	0.177	0.177
No Point Dropout	0.199	0.211	0.160	0.166	0.193	0.207	0.187	0.194	0.197	0.194
Low Dropout Rate	0.161	0.177	0.124	0.132	0.150	0.151	0.151	0.175	0.176	0.178
High Dropout Rate	0.158	0.172	0.121	0.131	0.147	0.155	0.153	0.177	0.176	0.180
BatchNorm(6) in UNet	0.180	0.192	0.136	0.146	0.164	0.160	0.159	0.190	0.188	0.191
InstanceNorm(32) in UNet	0.161	0.179	0.150	0.139	0.160	0.196	0.161	0.182	0.179	0.186
Complete Model	0.159	0.175	0.120	0.132	0.147	0.154	0.151	0.175	0.172	0.176

Table 12: Per-scene breakdown for the ablation studies on the DTU dataset.