Bessel Equivariant Networks for Inversion of Transmission Effects in Multi-Mode Optical Fibres

Abstract

We develop a new type of model for solving the task of inverting the transmission effects of multi-mode optical fibres through the construction of an $\mathrm{SO}^+(2,1)$-equivariant neural network. This model takes advantage of the of the azimuthal correlations known to exist in fibre speckle patterns and naturally accounts for the difference in spatial arrangement between input and speckle patterns. In addition, we use a second post-processing network to remove circular artifacts, fill gaps, and sharpen the images, which is required due to the nature of optical fibre transmission. This two stage approach allows for the inspection of the predicted images produced by the more robust physically motivated equivariant model, which could be useful in a safety-critical application, or by the output of both models, which produces high quality images. Further, this model can scale to previously unachievable resolutions of imaging with multi-mode optical fibres and is demonstrated on 256×256 pixel images. This is a result of improving the trainable parameter requirement from $\mathcal{O}(N^4)$ to $\mathcal{O}(m)$, where N is pixel size and m is number of fibre modes. Finally, this model generalises to new images, outside of the set of training data classes, better than previous models.

1 Introduction

Multi-mode fibres (MMF) have many potential applications in medical imaging, cryptography, and communications. In the medical domain, the use of multi-mode fibre imaging has potential to create hair-thin endoscopes for imaging sensitive areas of the body. However, to achieve these applications, the fibre transmission properties must be compensated for to return a clear image (Stasio, 2017). A MMF has multiple different fibre modes, each of which propagates at a different velocity. This leads to an amplitude and phase mixing of the image as it propagates through the fibre (Mitschke, 2016). As a result, an input image creates a complex-valued speckled pattern on the output of the MMF. The ability to accurately and in a scalable way learn to invert the transmission effects would unlock MMF imaging as a useful tool across a range of domains.

Inverting a speckled image is challenging for multiple reasons. Firstly, the speckled images have a non-local relationship with respect to the original images. As a result, solely local patch-based models, such as convolutional neural networks, do not make sense as a solution without some dense mapping function. Therefore, the non-locality necessitates mapping the speckled images into a spatial arrangement similar to the original images before typical image-based deep learning techniques can be used, such as convolutions and pooling. In addition, the speckled images have circular correlation, which could be taken advantage of, although as noted by Moran et al. (2018), finding these

requires solving the inversion, creating a chicken-and-egg problem. Finally, the fibre is equivalent to an unknown complex transmission matrix (TM) so, the inverse of this could be found using a complex-valued linear model, although this presents challenges in terms of memory requirements. A mapping between 350×350 original and speckled images would result in a TM with $350^4 \approx 15$ billion entries, requiring a linear model with as many parameters.

Previous work in inverting the transmission effects of MMFs has either required extensive experimentation to characterise the TM of the fibre (Čižmár & Dholakia, 2011, 2012; Choi et al., 2012; Mahalati et al., 2013; Papadopoulos et al., 2012; Plöschner et al., 2015; Leite et al., 2021), made use of dense linear models (Moran et al., 2018; Fan et al., 2019; Caramazza et al., 2019), or made use of convolutional models (Borhani et al., 2018; Rahmani et al., 2018). For the machine learning approaches to tackling the inversion task, those which make use of a dense linear model (Moran et al., 2018; Fan et al., 2019; Caramazza et al., 2019) can naturally account for the difference in spatial arrangement between speckled and original images, although they scale badly with the resolution of the images considered ($\mathcal{O}(N^4)$ for $N \times N$ resolution). On the other hand, in theory, the convolutional neural network (CNN) models (Borhani et al., 2018; Rahmani et al., 2018) improve upon the scalability issue, but in practise due to the need to approximate the transmission matrix and its non-local effects, the models require a large number of layers in order to be able to effectively map every pixel in the speckled image to every pixel in the original image, and hence in practice do not over come the scalability issues. All of these approaches are mostly expected to work for classes of objects that belong to the class that was used for training (Borhani et al., 2018), with Rahmani et al. (2018) making initial steps towards general imaging and Caramazza et al. (2019) demonstrating this for a more diverse testing dataset. We provide further details on each of the previous methods in Appendix A.1.

In this work we present a model which naturally accounts for the difference in spatial arrangement between speckled and original images and scales more efficiently than previous methods to higher resolution images. We believe this is the first method to demonstrate an ability to invert 256×256 pixel speckled images into 256×256 pixel original images. Our approach also takes advantage of the circular correlations in the speckled images, and improves upon previous general imaging results. Concerning the equivariance literature, we develop a model comprising of cylindrical harmonic basis functions, a basis set which has seen little attention in the equivariance literature, and make the connection between the transmission of light through a fibre and the group theoretic understanding used in developing equivariant neural networks. Our contributions are:

1. A more data-efficient, scalable model to solve the inversion of MMF transmission effects.

2. A model that provides better generalisation to out-of-training domain images.

3. A connection between group theoretic equivariant neural networks and the inversion of MMF transmission effects, providing a new type of model to tackle the problem.

2   Background

2.1   Multi-Mode Fibres

Multi-mode fibres present a clear advantage over single-mode fibre bundles due to having 1-2 orders of magnitude greater density of modes than a fibre bundle (Choi et al., 2012). Despite this the different propagation velocities of each mode, resulting in the fibre producing scrambled images, presents a significant challenge. If each propagation mode and velocity was known the TM could be computed, providing a linear system that inverts the transmission effects, although in general this is not known. Further, the mode mixing interference can lead to information loss such that inverting the transmission does not yield the true original input image, as is demonstrated in Figure 1. Therefore, a model which correctly models the physics of inverting the transmission effects should produce the inverted image in Figure 1 and producing the original image requires addition information to be learned. We provide further details into the propagation of light through

optical fibres and how we construct theoretical TMs in Appendix A.4 and further details in the inversion of the TM in Appendix A.5.

(a) Original   (b) Speckled   (c) Inverted

Figure 1: (a) Original image. (b) Speckled image from passing original images through a theoretical TM. (c) Inverted image created by passing speckled images through the inverted theoretical TM.

2.2 Equivariance

Equivariance in neural networks concerns the study of symmetries and uses these to build an inductive bias into a model (Cohen & Welling, 2016a; Bronstein et al., 2021). Equivariance as a property of a neural network guarantees that a transformation of the input data produces a predictable transformation of the predicted features (Worrall et al., 2017). Formally, we say that, given two transformations T and T' which are linear representations of a group G and a network or layer Φ, the network is equivariant if applying transform T_g to an input x and then passing it through the network Φ yields the same result as first passing x through Φ and then transforming by T'_g (Cohen & Welling, 2016a); that is,

$$\Phi T_g(x) = T'_g(\Phi(x)). \tag{1}$$

Convolutional neural networks (CNNs) are an early example of equivariance on images, where by design they are translation equivariant (LeCun et al., 1998). More recently, equivariance has been considered for other group actions than that of the translation group. The majority of works on images involve incorporating rotation or reflection equivariance into the model, where a variety of different group transformations have been considered (Cohen & Welling, 2016a,b; Weiler & Cesa, 2019; Murugan et al., 2019; Wiersma et al., 2020; De Haan et al., 2020; Franzen & Wand, 2021).

We are not interested in developing a group equivariant convolutional model here due to the non-similar spatial arrangements between the speckled and original image domains. Despite this, the concept of equivariance still applies, as the concept of learning a model from a fixed basis set, which guarantees symmetry properties are conserved, is relevant due to the nature of transmission through multi-mode optical fibres.

2.2.1 Cylindrical Harmonics

While the circular harmonics have seen some attention in the deep learning community due to the use in constructing rotational equivariant CNNs, the cylindrical harmonics have seen less attention (Klicpera et al., 2020). The cylindrical harmonics appear as a solution to Bessel functions for integer α and are therefore of interest for problems where information transformation is characterised by such functions. For example Bessel functions are used when solving wave or heat propagation. Bessel functions are solutions for different complex numbers α of Bessel's differential equation:

$$x^2 \frac{d^2y}{dx^2} + x \frac{dy}{dx} + (x^2 - \alpha^2)y = 0. \tag{2}$$

For integer values of α the Bessel function solutions are a linearly independent set of functions expressed in cylindrical coordinates. Each function consists of the product of three functions. The radially dependent term is typically called the cylindrical harmonics. Further details on the connection between group theory and the Bessel bases functions is provided in Appendix A.8.

3 Our Method

Our method comprises two models: a Bessel equivariant model and a convolutional post-processing model. The Bessel equivariant model uses a basis set comprising cylindrical harmonics and learns a complex mapping function to use the known symmetries in optical fibres. The Bessel equivariant model is constrained by the basis choice to produce circular images, which can have circular artifacts also seen in a true inversion, see Figure 1. The post-processing model is used to fill gaps in the corners, remove circular artifacts, and sharpen the images. The two stage approach is useful in safety-critical applications as users can inspect the output of both models, where the Bessel equivariant model output is less likely to depend on the training data due to the choice of inductive bias.

3.1 Bessel Basis Equivariant Model

The core of our model has an inductive bias that better replicates the physics of the task of inverting the transmission effects of MMF imaging. To achieve this we utilise prior knowledge of MMFs and the modes with which an image propagates through the fibre. Similar to the successes of rotation equivariant neural networks, which make use of circular harmonics to achieve rotation equivariance, we utilise cylindrical harmonics as an inductive bias of the model. This is motivated by the propagation modes of the fibre being characterised by Bessel functions, where the radially dependent solution is given by the cylindrical harmonics. We make the connection to the group theoretic development of equivariant neural networks in Appendix A.8, demonstrating the connection between the group $SO^+(2, 1)$, the light cone, and Bessel function solution to the wave equation.

The first stage of the model is the computation of two sets of basis functions. The first set transforms the input image into a function that lives on the group and the second transforms back into the image domain. The model's weight matrix linearly transforms the function mapped by the first basis set. The basis filters are computed in accordance with equations in Appendix A.4.

These functions are sampled on a grid given by the size of the speckled images for the first basis set and the original images for the second basis set. An example of the bases produced is given in Figure 8. The Bessel function bases are computed in a pre-training stage and therefore this step only has to be completed once when creating the model. Further, these bases are not trainable parameters and are not updated during training of the model. These basis functions are an alternative to those used in general rotation equivariant neural networks, which typically offer equivariance to the group $SO(2)$, except they correctly model the symmetry group, $SO^+(2, 1)$ of the task of inverting transmission effects of a MMF due to the added time dimension.

The model trainable parameters are complex-valued weights of size equal to the number of bases. The complex weight matrix is a diagonal matrix. The images transformed by the first basis set are multiplied by the weight matrix before being transformed by the second basis set to produce the predicted image. The overall model architecture is given in Figure 2.

Speckled Image Resolution Bessel Function Bases   Complex Weight Matrix   Output Image Resolution Bessel Function Bases   Post-Processing Model

Figure 2: Our two stage model architecture comprising of a Bessel equivariant model and post-processing model. Input (left) is speckled images. Output (right) is predicted image. The speckled image resolution Bessel function bases transform the speckled image into a mode space of the group $SO^+(2, 1)$. The complex weight matrix is diagonal. The original image resolution Bessel function bases provides a mapping from the mode space to the output image space. The trainable parameters of the Bessel equivariant model are the diagonal complex weight matrix only. The post-processing model is a convolutional model.

3.2 Post-Processing Model

As demonstrated in Section A.5 the limited number of modes means that the transmission effects of a MMF are typically not fully invertible leading to information loss. We would therefore not expect an equivariant model informed by the physics of the task to be able to fully invert the transmission effects. To overcome this we add a second model which is similar to a super-resolution model, except that it does not change the resolution and instead learns to remove circular artifacts, fill in gaps, and sharpen the images. It is a fully convolutional model comprising of convolutional layers and non-linearities. This model takes as input the output of our Bessel equivariant model, which we suspect will be similar to what is achievable by passing the speckled images through an inverted TM, and predicts the original images. This model is composed of eight convolutional layers with ReLU non-linearities. The motivation behind the explicit separation of the inversion and enhancement models is that in some applications, especially safety-critical applications, it is important to be able to see the results of an inversion conditioned on the observations alone, regardless of prior expectations.

4 Experiments

We investigate performance with both data generated with a theoretical TM and experimental data collected using a real MMF fibre. We provide details of the theoretical TM generation in Appendix A.4. We use the data from a real fibre, as described in Moran et al. (2018), to validate that our new approach can model the same data, despite using significantly fewer trainable model parameters. Further, we generate data using a theoretical TM as this allows us to flexibly adapt the parameters of the experiment and create new datasets to validate the new model design. Finally, the theoretical TM allows us to experiment with images with higher resolution than has been previously been considered. We provide details on the training of the models and datasets in Appendix A.2.

4.1 Real Multimode Fibre

We compare our model to the complex-valued linear model developed by Moran et al. (2018) by considering both MNIST and fMNIST data. For this we train and test separate models for the MNIST and fMNIST datasets. In addition, we compare multiple different versions of our model where the diagonal restriction of the mapping between bases is relaxed to allow for a block diagonal structure. We do this to account for manufacturing defects, sharp bends, dopant diffusion, elliptical cores which causes the diagonal mapping of the fibre matrix within the TM to be block diagonal (Carpenter et al., 2014). This relaxation allows for x-offsets above and below the main diagonal.

Table 1: Comparison of the loss values of each model trained with MNIST or fMNIST data.

Model	MNIST		fMNIST	
	Train Loss	Test Loss	Train Loss	Test Loss
Complex Linear	0.00396	0.00684	0.00509	0.01061
Bessel Equivariant Diag	0.03004	0.03125	0.02903	0.03140
Bessel Equivariant Diag + Post Proc	0.01317	0.01453	0.01609	0.01749
Bessel Equivariant 10 Off Diag + Post Proc	0.00488	0.00576	0.00943	0.01162
Bessel Equivariant Full	0.00300	0.00684	0.00548	0.01380
Bessel Equivariant Full + Post Proc	**0.00145**	**0.00378**	**0.00306**	**0.00964**

Table 1 shows that our model with a full mapping matrix between bases, i.e. full relaxation of the diagonal constraint, outperforms all other models. In addition, with a relaxation to allow for a 10 block diagonal structure our model performs comparably. On the other hand, the complex linear model outperforms our Bessel equivariant model when the diagonal restriction on the mapping function between bases is enforced. Despite this, our model still provides clear and accurate reconstructions of the target images whilst using orders of magnitude fewer trainable parameters. Additional results are presented in Tables 6 and 7. Further to a comparison of the loss values, we visually inspect the reconstruction quality in Figure 3, and we provide further visualisations in Figures 16 and 17. Thus despite

| (a) Input | (b) Target | (c) BEM | (d) BEM+PP | (e) Complex |

Figure 3: Comparison of predicted images from inverting transmission effects of a MMF. The upper row is fMNIST data, lower row MNIST data. (a) Input speckled image, (b) the target original image to reconstruct, (c) Output of the Bessel equivariant model, (d) Output of the combination of Bessel equivariant and post-processing model, and (e) the output of the complex-valued linear model.

our Bessel equivariant diagonal model achieving a larger loss value, the digit or item is still clearly visible in the prediction and is correctly sharpened to a realistic prediction of the original image by our post-processing model. The complex linear model can also be seen to predict a realistic looking output of the correct digit and object, although some noise does feature in the prediction. In addition, we visually compare each of our Bessel equivariant models with the diagonal restriction relaxed in Figures 10 and 11, which demonstrates that as the diagonal restriction is relaxed the model can better predict the original images with less noise in the prediction from the Bessel equivariant model.

We also compare the number of trainable parameters within the model in Table 2. This highlights that our model requires two orders of magnitude fewer parameters that the complex linear model when using the diagonal Bessel equivariant model. Therefore, our model has the potential to scale to higher resolution images where the complex linear model will run out of GPU memory. As the diagonal mapping between Bessel bases is relaxed to include 10-block diagonal structure the model still requires two order of magnitude fewer parameters. In the most flexible version of our model the number of trainable parameters is comparable with the complex Linear model, although we have demonstrated that this level of flexibility is not required to achieve good image reconstruction.

Table 2: Comparison of # trainable parameters in each model trained with MNIST or fMNIST data.

Model	Number of Trainable Parameters (Millions)
Complex Linear	78.826
Bessel Equivariant Diag + Post Proc	0.500
Bessel Equivariant 10 Off Diag + Post Proc	0.617
Bessel Equivariant Full + Post Proc	43.108

4.2 Theoretical TM

We compare our model to the complex linear model developed by Moran et al. (2018) with data created using a theoretical TM. We create multiple datasets one using 28×28 fMNIST images, with 180×180 speckled images, another with MNIST images, of the same size, and one with a subset of images from the ImageNet dataset (Deng et al., 2009) where we fix the resolution to be 256×256 of both the images and speckled images. Using fMNIST and MNIST with a theory TM is useful for developing understanding, due to the ease of creating different experiments and datasets, and for testing the generalisability of the model between the two datasets. We include the ImageNet-based dataset as these are higher resolution images containing more challenging information than fMNIST. To the best of our knowledge, demonstrating the ability to invert transmission effects of such high resolution images has not been previously achievable with a machine learning based approach.

4.2.1 Generalisability of Models

We provide a comparison of the predictions of a complex valued linear model (Moran et al., 2018), our equivariant model only, and our equivariant model coupled with a post-processing model trained on fMNIST images and tested on both fMNIST and MNIST to analyse to what extent the models can generalise to a new dataset. Table 3 presents the loss values for both the training and testing of each model. Considering the fMNIST data this shows that the complex linear and Bessel equivariant models achieve similar loss values. Although this is a result of the Bessel equivariant model under-performing due to not being able to reconstruct pixel values close to the edge of the image as a consequence of the circular nature of the Bessel bases functions, while the complex linear model under-performs due to failing to reconstruct higher frequency information and over-fitting to the general clothing categories. Finally, when our Bessel equivariant model is combined with the post-processing model it outperforms all other models. The ability to generalise to a new data is assessed through the MNIST dataset. This shows that our Bessel equivariant model significantly out-performs the complex linear model in generalising to a new dataset.

Table 3: Comparison of the loss values of each model trained with fMNIST data.

| Model | fMNIST | | MNIST |
	Train Loss	Test Loss	Test Loss
Complex Linear	0.0149	0.0146	0.0363
Bessel Equivariant	0.0141	0.0139	**0.0026**
Bessel Equivariant + Post Proc	**0.0032**	**0.0032**	0.0028

Figure 4 shows reconstructions produced by the three models, with further reconstructions provided in Figure 18. This demonstrates visually that our model, even without the post-processing part, is able to better reconstruct the original images. The post-processing model refines the output of the equivariant model and fills in gaps outside the fibre. Despite it being possible to estimate the general category of clothing from the outputs of the complex linear model, the higher frequency information has been lost, i.e. the pattern on the jumper or the curve in the trouser leg. On the other hand, our model is able to reconstruct this higher frequency information.

(a) Input   (b) Target   (c) BEM   (d) BEM + PP   (e) Complex

Figure 4: Comparison of predicted images from inverting transmission effects of a MMF. (a) Input speckled image, (b) Target original image to reconstruct, (c) Output of the Bessel equivariant model, (d) Output of the Bessel equivariant and post-processing model, and (e) Output of the complex valued linear model.

Previous works have demonstrated some ability to generalise to new data classes (Rahmani et al., 2018; Caramazza et al., 2019), although in each case the results are not perfect. Here we compare the different methods trained on fMNIST and then tested on MNIST data. Figure 5 demonstrates that our Bessel equivariant model generalises well to a new data domain, with further reconstructions provided in Figure 19. On the other hand, the complex linear model somewhat predicts the correct digits. In this out of training domain our post-processing model does not add any value to the original Bessel equivariant model. This highlights the benefit of our two-stage modelling approach as we have one robust model and a second model to sharpen the images, as a result if a user believes the situation could be unusual they could reliably use the output of our Bessel equivariant model and not the post-processing part. Further to achieving strong generalisation results, we also consider the effect of noise in the speckled images in Appendix A.7.

| (a) Input | (b) Target | (c) BEM | (d) BEM + PP | (e) Complex |

Figure 5: Comparison of predicted images from inverting transmission effects of a MMF. (a) Input speckled images, (b) Target original images, (c) Output of the Bessel equivariant model, (d) Output of Bessel equivariant and post-processing model, and (e) Output of the complex valued linear model.

Figure 7 shows how the number of trainable model parameters scale. Even for 28×28 images our model requires two orders of magnitude fewer trainable parameters than the complex linear model.

4.2.2 Scaling to Larger Images – ImageNet

We now experiment with a subset of images from the ImageNet dataset, where we fix the resolution to be 256×256. Inverting the transmission effects of such higher resolution images has not been previously achievable. We only compare our equivariant model with our equivariant model coupled with a fully convolutional post-processing model. The complex-valued linear model cannot fit in the GPU memory of an A6000 with 48.7GiB of memory with this resolution of image.

| (a) Input | (b) Target | (c) BEM | (d) BEM + PP |

Figure 6: Comparison of predicted images from inverting transmission effects of a MMF using high resolution ImageNet data. (a) Input speckled image, (b) Target original image to reconstruct, (c) Output of Bessel equivariant model (d) Output of Bessel equivariant and post-processing model.

We analyse our model visually, with Figure 6 showing that our Bessel equivariant model produces a reconstruction from which one can determine the type of dog and its activity, although the reconstruction does not capture all the high frequency information, and information in the corners is lost due to the circular nature of the fibre. Further reconstructions are provided in Figure 20. When we combine the two models some of the artifacts of the Bessel equivariant model are removed as the post-processing model fills in information towards the corners and sharpens the image.

Table 4: Comparison of the loss values of each model trained with ImageNet data.

Model	Train Loss	Test Loss
Bessel Equivariant	0.0541	0.0574
Bessel Equivariant + Post Proc	**0.0161**	**0.0159**

We present the loss values for both models in Table 4. This shows a similar result as for fMNIST, that our Bessel equivariant model can solve the task well, but requires the post-processing model to sharpen the image and fill in gaps in the corners. We compare the models' memory requirements in Figure 7. Note how fewer trainable parameters translate into significantly less memory use than the complex linear model. This effect is seen more drastically when scaling to high resolution images, where the complex linear model runs out of memory on a 24.2GiB Titan RTX for original and speckled images of resolution 180×180 pixels. Our model, in contrast, has been tested on 256×256 pixel images, requiring only 2.1GiB, and can scale to megapixel images.

Figure 7: (Upper Left) Comparison of number of trainable parameters v. TM size (dashed line indicates model cannot in practise be built due to large memory requirements). (Lower Left) Comparison of required GPU memory against TM size. Vertical grey lines indicate a given image size – our model can process 1024×1024 images on a single consumer-level Titan RTX GPU. (Lower Right) Comparison of reducing the size of the training dataset. All plots for a 1000 mode fibre.

Finally, we explore the impact on each model of reducing the size of the training dataset. Requiring a reduced dataset size minimises the time taken in a lab collecting data and has practical relevance as imaging cells, where imaging for an extended time can damage them. Figure 7 demonstrates that our model outperforms the complex linear model with $10\times$-less training data, reducing the need to collect 12000 samples to 1200. The reconstructions are visualised in Appendix A.14.

5 Conclusions

We present a new type of model for solving the task of inverting the transmission effects of a MMF through developing a $\mathrm{SO}^+(2,1)$-equivariant neural network and combining this with a post-processing network. This improves upon complex linear models through incorporating a useful physically informed inductive bias into the equivariant network. The equivariant network is shown to perform well on new image classes, providing a general model for fibre inversion. The post-processing network is is specific to an image domain, as it generalises to new image classes as well as a general convolutional network, although it improves the quality of returned images. The use of a theoretical TM allows us to compare an 'ideal' inverse with the output of previous models based on learning a full transmission matrix. This suggests that previous learned transmission matrices were combining elements of the actual transmission matrix with elements of the post-processing network, which would affect their ability to generalise to new images. We also anticipate that in interactive safety-critical applications users might want the ability to switch between modes, to be sure that the evidence was there, and not overly influenced by the priors in the training data.

This new model significantly improves the ability to scale to higher resolution images by improving the scaling law from $\mathcal{O}(N^4)$ to $\mathcal{O}(m)$, where N is pixel size and m is the number of fibre modes. We provide a comparison between our model and prior works on both data created using a real fibre and a theoretical TM, demonstrating in both cases that our model solves the task while using significantly less trainable parameters than the complex real model. In addition, we demonstrate results on high resolution 256×256 images, which has previously been unachievable due to the growth of parameters with previous models. Furthermore, we demonstrate the ability of our model to generalise to new data classes outside of the training data, outperforming prior works. The dramatic reduction in the number of parameters for each fibre configuration opens the way for future models which can learn mappings for high-resolution images, from a wider set of perturbed fibre poses and combine these using architectures such as VAEs.

References

Navid Borhani, Eirini Kakkava, Christophe Moser, and Demetri Psaltis. Learning to see through multimode fibers. *Optica*, 5(8):960–966, 2018.

Michael M Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *arXiv preprint arXiv:2104.13478*, 2021.

Piergiorgio Caramazza, Oisín Moran, Roderick Murray-Smith, and Daniele Faccio. Transmission of natural scene images through a multimode fibre. *Nature communications*, 10(1):1–6, 2019.

Joel Carpenter, Benjamin J Eggleton, and Jochen Schröder. Maximally efficient imaging through multimode fiber. In *CLEO: Science and Innovations*, pp. STh1H–3. Optical Society of America, 2014.

Youngwoon Choi, Changhyeong Yoon, Moonseok Kim, Taeseok Daniel Yang, Christopher Fang-Yen, Ramachandra R Dasari, Kyoung Jin Lee, and Wonshik Choi. Scanner-free and wide-field endoscopic imaging by using a single multimode optical fiber. *Physical review letters*, 109(20): 203901, 2012.

Tomáš Čižmár and Kishan Dholakia. Shaping the light transmission through a multimode optical fibre: complex transformation analysis and applications in biophotonics. *Optics express*, 19(20): 18871–18884, 2011.

Tomáš Čižmár and Kishan Dholakia. Exploiting multimode waveguides for pure fibre-based imaging. *Nature communications*, 3(1):1–9, 2012.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pp. 2990–2999. PMLR, 2016a.

Taco S Cohen and Max Welling. Steerable CNNs. *arXiv preprint arXiv:1612.08498*, 2016b.

Pim De Haan, Maurice Weiler, Taco Cohen, and Max Welling. Gauge equivariant mesh CNNs: Anisotropic convolutions on geometric graphs. *arXiv preprint arXiv:2003.05425*, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Pengfei Fan, Tianrui Zhao, and Lei Su. Deep learning the high variability and randomness inside multimode fibers. *Optics express*, 27(15):20241–20258, 2019.

Daniel Franzen and Michael Wand. General nonlinearities in SO(2)-Equivariant CNNs. *Advances in Neural Information Processing Systems*, 34, 2021.

Johannes Klicpera, Janek Groß, and Stephan Günnemann. Directional message passing for molecular graphs. *arXiv preprint arXiv:2003.03123*, 2020.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Ivo T Leite, Sergey Turtaev, Dirk E Boonzajer Flaes, and Tomáš Čižmár. Observing distant objects with a multimode fiber-based holographic endoscope. *APL Photonics*, 6(3):036112, 2021.

Reza Nasiri Mahalati, Ruo Yu Gu, and Joseph M Kahn. Resolution limits for imaging through multi-mode fiber. *Optics express*, 21(2):1656–1668, 2013.

Fedor Mitschke. *Fiber optics*. Springer, 2016.

Oisín Moran, Piergiorgio Caramazza, Daniele Faccio, and Roderick Murray-Smith. Deep, complex, invertible networks for inversion of transmission effects in multimode optical fibres. *Advances in Neural Information Processing Systems*, 31, 2018.

341 Muthuvel Murugan, KV Subrahmanyam, and Siruseri IT Park. SO (2)-equivariance in neural net-
342 works using tensor nonlinearity. *British Machine Vision Conference*, 2019.

343 Ioannis N Papadopoulos, Salma Farahi, Christophe Moser, and Demetri Psaltis. Focusing and scan-
344 ning light through a multimode optical fiber using digital phase conjugation. *Optics express*, 20
345 (10):10583–10590, 2012.

346 Martin Plöschner, Tomáš Tyc, and Tomáš Čižmár. Seeing through chaos in multimode fibres. *Nature
347 Photonics*, 9(8):529–535, 2015.

348 Babak Rahmani, Damien Loterie, Georgia Konstantinou, Demetri Psaltis, and Christophe Moser.
349 Multimode optical fiber transmission with a deep learning network. *Light: Science & Applica-
350 tions*, 7(1):1–11, 2018.

351 Nicolino Stasio. Multimode fiber optical imaging using wavefront control. Technical report, EPFL,
352 2017.

353 Maurice Weiler and Gabriele Cesa. General E(2)-equivariant steerable CNNs. *Advances in Neural
354 Information Processing Systems*, 32, 2019.

355 Ruben Wiersma, Elmar Eisemann, and Klaus Hildebrandt. CNNs on surfaces using rotation-
356 equivariant features. *ACM Transactions on Graphics (TOG)*, 39(4):92–1, 2020.

357 M.K.F. Wong. Unitary representations of $SO(n, 1)$. *Journal of Mathematical Physics*, 15(1):25–30,
358 1974.

359 Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic
360 networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE Conference on
361 Computer Vision and Pattern Recognition*, pp. 5028–5037, 2017.

362 Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-MNIST: a novel image dataset for bench-
363 marking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.