KV-Retriever: Aligning KV Cache Eviction with Downstream Task Loss

Abstract

The prohibitive memory footprint of the Key-Value (KV) cache imposes a critical bottleneck for efficient long-context LLM serving. Current eviction methods, ranging from attention-based heuristics to recent learnable approaches, rely on scoring criteria decoupled from the downstream task performance that ultimately matters. To address this, we introduce **KV-Retriever**, a layer-wise learnable importance scoring module directly optimized by the end-to-end downstream task loss. We demonstrate that aligning the scoring objective with the actual task signal—rather than intermediate proxies such as attention statistics or oracle labels—yields a fundamentally more accurate notion of token importance. Functioning as a lightweight, plug-and-play module with only ∼0.01% additional parameters on a frozen 8B backbone, KV-Retriever is compatible with diverse host eviction frameworks. Extensive experiments show that one trained retriever, plugged unchanged into multiple KV cache compression architectures, delivers consistent improvements on LongBench, LongBench-v2, and RULER. Our code is available at https://anonymous.4open.science/r/kv_retriever-492F.

Figure 1: **SnapKV's deterministic scoring leaves a substantial gap below the compression upper bound; KV-Retriever closes most of it in a single forward.** Answer-only LM loss (lower is better) vs. compression ratio ρ. Four operating points: SnapKV top-K (predefined rule), SnapKV best-of-N (N=50; approximate upper bound), KV-Retriever (top-K), and FullCache (no eviction). At ρ=0.2 (shaded), the large arrow marks the gap closed by KV-Retriever; the small arrow is the residual to the BoN ceiling.

1 Introduction

While Large Language Models (LLMs) demonstrate robust reasoning capabilities in long-context scenarios—such as long-document QA, multi-turn dialogue, and codebase analysis(Bai et al., 2024; An et al., 2024; Liu et al., 2024), their deployment efficiency is fundamentally constrained by the quadratic scaling overhead of KV cache relative to sequence length (Zhang et al., 2023; Liu et al., 2023). To address this challenge, KV cache eviction has emerged as a primary compression paradigm (Li et al., 2024; LI et al., 2025). By retaining critical KV entries and discarding redundant ones within a fixed memory budget, these methods aim to preserve the downstream task quality achievable under full attention. The efficacy of such approaches hinges on the definition of "importance"—specifically, the mechanism for assigning a scalar score to each KV token to facilitate filtering.

Existing approaches to scoring KV token importance fall into two broad families. Predefined-heuristic methods derive scores directly from attention statistics—cumulative attention sums, query-window-aggregated attention, or attention reweighted by output-projection norms (Zhang et al., 2023; Liu et al., 2023; Li et al., 2024)—without any learning component. A more recent line introduces learnable modules that predict token retention value, yet supervises them with intermediate proxies rather than the task loss: future attention patterns, utility rewards over sampled keep decisions, or binary keep-or-discard labels (Moschella

et al., 2026; Dong et al., 2026; Liu et al., 2026; Huang et al., 2025; Qiu et al., 2025). Despite their structural differences, both families share a defining property: the scoring criterion is always a proxy, never the downstream task loss that ultimately determines model quality.

This decoupling creates a systematic gap between the keep set a scorer produces and the keep set that would actually minimize task error. To quantify this gap concretely, we take SnapKV (Li et al., 2024) as a representative and construct an approximate upper bound on compression quality: draw $N{=}50$ keep sets from SnapKV's attention-score-induced distribution and record the minimum answer-only LM loss (best-of-N; BoN). As Figure 1 shows, this upper bound sits markedly above SnapKV's deterministic top-K at every compression ratio—a substantial margin the predefined rule simply cannot close. Crucially, the gap is not structural: KV-Retriever, our task-finetuned scorer (§3), closes most of it with a *single* forward pass, while reaching the upper bound directly requires $N{=}50$ forwards per query. The bottleneck therefore lies not in the expressiveness of the scoring architecture but in the misalignment between the scoring criterion and the downstream task signal.

Our training method closes this gap by folding the per-query BoN search into the scorer itself, so one deterministic forward on the trained scorer recovers the majority of the headroom between the predefined rule and the upper bound. We keep the host eviction framework's selection rule (top-K on Q,K-derived scores) untouched and only reshape the scoring geometry—a per-layer learnable Q,K projection initialized to the identity, so before training the scorer coincides with the host's predefined scorer and only deviates under task signal. We derive the training signal directly from sampled keep-set comparisons: draw S keep sets from π_θ, score each by its answer-only LM loss under the frozen backbone, and update θ by a list-wise ranking objective so high-reward plans receive more probability mass. We call the resulting module **KV-Retriever**: $\sim$0.8M trainable parameters on a frozen Qwen3-8B (0.01%), backbone weights never updated. Because it only outputs scalar scores and changes nothing in the surrounding eviction logic, one trained set of weights drops unchanged into any host built on a Q,K attention term—we verify this on SnapKV, AdaKV, and CriticalKV across three backbones.

Our contributions are as follows:

- We quantify a budget-monotone gap between SnapKV's deterministic scoring and its approximate compression upper bound (Figure 1), locating the bottleneck in the misalignment between scoring criterion and downstream task signal.

- We propose **KV-Retriever**, a layer-wise scoring module ($\sim$0.01% extra parameters, identity-initialized) trained end-to-end against the answer-only LM loss via multi-trajectory sampling and a list-wise ranking objective, collapsing N BoN forwards into one deterministic pass (§3).

- One trained retriever, plugged unchanged into SnapKV, AdaKV, and CriticalKV across three backbones, closes the diagnosed gap on Long-Bench, LongBench-v2, and RULER (§4)—with strong zero-shot transfer to the latter two benchmarks unseen during training.

2 Related Work

2.1 Predefined-Criterion-Based Eviction

Existing KV cache eviction methods score tokens with predefined heuristics derived from attention statistics—cumulative attention (Zhang et al., 2023), persistence-weighted attention across decoding steps (Liu et al., 2023), query-window-aggregated attention (Li et al., 2024), pyramidal per-layer budget reshaping (Cai et al., 2025), or adaptive per-head budget reallocation (Feng et al., 2026). Despite varying implementations, all are governed by human-designed priors and decoupled from downstream task signals.

2.2 Training-Based Eviction

A more recent line introduces learnable components into eviction (Moschella et al., 2026; Dong et al., 2026; Liu et al., 2026; Huang et al., 2025; Qiu et al., 2025), replacing hand-crafted rules with modules supervised by future-utility rewards, future-attention oracles, or binary keep-drop labels. However, these training signals remain intermediate proxies rather than the end-to-end downstream task loss; our KV-Retriever instead optimizes directly against task performance, closing the gap between the scoring criterion and the metric that ultimately matters.

Figure 2: A single training step of KV-Retriever. **(A) Multi-trajectory forward sampling.** For each of S trajectories, the frozen backbone prefills the prompt; the per-layer retriever—the only trainable component ($\sim 0.01\%$ of backbone parameters)—scores tokens; the host framework (SnapKV / AdaKV / CriticalKV) evicts to ratio ρ; and decoding against the compressed cache yields the trajectory reward $R_i = -\ell_i$ from the answer-only LM loss on $y^\star$ (§3.3). **(B) Backward alignment.** The rewards $\{R_i\}$ are softmax-normalized into a target ranking q (Eq. (8)) and matched to the retriever-recomputed trajectory log-probabilities (Eq. (7)) by a list-wise cross-entropy loss (Eq. (9)); gradients update only $\mathbf{R}_q, \mathbf{R}_k$ while the backbone stays frozen (§3.4).

3 Method

We realize **KV-Retriever**, the construction motivated in the introduction, with three coordinated components: a per-layer learnable scorer with identity initialization that strictly extends the attention prior (§3.2); a stochastic relaxation of top-K retention via Plackett–Luce sampling, whose differentiable trajectory log-probabilities allow the LM loss—acting as a ranking reward—to induce gradients on the per-token scores (§3.3); and a list-wise ranking objective over sampled keep sets whose reward is the LM loss itself (§3.4). We first fix the notation (§3.1). Figure 2 gives the end-to-end overview: panel (A) covers the multi-trajectory forward sampling producing rewards $\{R_i\}$, panel (B) the backward alignment that turns the reward ranking into a list-wise loss whose gradient updates only $\mathbf{R}_q, \mathbf{R}_k$.

3.1 Preliminaries: KV Cache Eviction with a Scoring Function

Consider a frozen Transformer LLM processing a length-T_p prompt. At each decoder layer ℓ, we write $\mathbf{K}^{(\ell)}$ for the cached keys and $\mathbf{Q}^{(\ell)}$ for the queries of the most recent w_q tokens, the *observa-tion window* of Li et al. (2024).

A generic eviction method first assigns per-token importance scores

$$\mathbf{s}^{(\ell)} = a^{(\ell)}(\mathbf{Q}^{(\ell)}, \mathbf{K}^{(\ell)}), \qquad (1)$$

then keeps the top-scoring positions per head under a budget induced by a target compression ratio $\rho \in (0, 1]$. Host frameworks differ mainly in their choice of $a^{(\ell)}$: SnapKV (Li et al., 2024) uses query-window-aggregated attention, AdaKV (Feng et al., 2026) reallocates the same budget adaptively across heads, and CriticalKV (Feng et al., 2025) further reweights the score by $\|\mathbf{V}\mathbf{W}_O\|_1$. In all cases $a^{(\ell)}$ is a *fixed function of attention statistics*.

Our goal is to replace $a^{(\ell)}$ with a learnable Q,K-based scorer $s_\theta^{(\ell)}(\mathbf{Q}^{(\ell)}, \mathbf{K}^{(\ell)})$ optimized end-to-end by the downstream task loss, while leaving the host's budget allocation and anchor windows untouched—so any framework built on a Q,K attention term hosts it as a drop-in.

3.2 KV-Retriever: A Lightweight Layer-wise Scorer

Architecture. At each decoder layer ℓ, KV-Retriever introduces only two weight matrices

$\mathbf{R}_q^{(\ell)}, \mathbf{R}_k^{(\ell)} \in \mathbb{R}^{d \times d}$ that map per-head queries and keys into a shared retrieval space. Let $\bar{\mathbf{q}}_h^{(\ell)} \in \mathbb{R}^d$ denote the query for KV head h, averaged over the w_q tokens of the observation window (and, under grouped-query attention (Ainslie et al., 2023), over the query heads in its group). For each cached key $\mathbf{k}_{h,n}^{(\ell)}$ at position $n \in \{1, \dots, T_p\}$, the retriever score is a scaled dot-product

$$s_\theta^{(\ell)}(h, n) = \frac{\tau}{\sqrt{d}} \big(\mathbf{R}_q^{(\ell)} \bar{\mathbf{q}}_h^{(\ell)}\big)^\top \big(\mathbf{R}_k^{(\ell)} \mathbf{k}_{h,n}^{(\ell)}\big), \quad (2)$$

with a per-layer temperature τ.

Identity initialization. A central design choice is to initialize $\mathbf{R}_q^{(\ell)} = \mathbf{R}_k^{(\ell)} = \mathbf{I}_d$. Because the retriever consumes per-head $\mathbf{q}, \mathbf{k}$ that have already passed through the model's attention projections, Eq. (2) reduces at step 0 to the standard scaled dot-product attention score, so the host behaves exactly as its original predefined version before any gradient is taken. Training then deviates from identity *only* where the downstream task signal indicates the attention prior is suboptimal, giving a strict performance lower bound and stable optimization in practice.

Parameter footprint. KV-Retriever introduces only $2L\,d^2$ trainable parameters in total (plus a per-layer scalar temperature), which amounts to $\sim 0.01\%$ of a typical 8B backbone; the backbone weights remain frozen throughout training. Exact counts for the models used in our experiments are reported in §B.

3.3 Stochastic Top-K Retention via Plackett–Luce Sampling

The host consumes scores but emits a discrete keep mask, severing the gradient path from the LM loss to θ. We replace this deterministic top-K rule with a stochastic relaxation: a distribution over keep sets that (i) is smooth in θ, (ii) yields trajectory log-probabilities differentiable in θ, so that the LM loss—serving as a ranking reward over sampled keep sets—can drive gradient updates to the retriever scores through a list-wise surrogate, and (iii) recovers top-K in a sharpening limit.

Plackett–Luce factorization. For a fixed layer ℓ and KV head h, let $\mathcal{S}_h^{(\ell)} = (n^{(1)}, \dots, n^{(K)})$ denote the length-K keep set with $K = \lceil \rho T_p \rceil$. This set is drawn by sampling *without replacement* from the softmax of retriever scores at temperature τ_p,

equivalent to the Gumbel-Top-k trick of Kool et al. (2019):

$$P\big(n^{(j)} = n \mid \mathcal{N}_{<j}\big)$$
$$= \frac{\exp(s_\theta^{(\ell)}(h, n)/\tau_p)\, \mathbf{1}[n \notin \mathcal{N}_{<j}]}{\sum_{n' \notin \mathcal{N}_{<j}} \exp(s_\theta^{(\ell)}(h, n')/\tau_p)}, \quad (3)$$

where $\mathcal{N}_{<j} := \{n^{(1)}, \dots, n^{(j-1)}\}$ denotes the already-selected positions. Multiplying the K steps yields the Plackett–Luce factorization

$$\pi_\theta\big(\mathcal{S}_h^{(\ell)}\big) = \prod_{j=1}^{K} P\big(n^{(j)} \mid \mathcal{N}_{<j}\big). \quad (4)$$

Layers and KV heads are sampled independently, so the full retention plan

$$\mathcal{S} = \big\{ \mathcal{S}_h^{(\ell)} : \ell \geq \ell_{\text{start}},\, h = 1, \dots, H_{\text{kv}} \big\} \quad (5)$$

has $\pi_\theta(\mathcal{S}) = \prod_{\ell,h} \pi_\theta(\mathcal{S}_h^{(\ell)})$, supplemented by the deterministic anchor windows from §3.2. At inference $\tau_p \to 0$ collapses the sampler onto deterministic top-K and recovers the host's standard behavior; finite τ_p at training keeps the sampler stochastic so diverse keep sets are explored.

Multi-trajectory sampling. For each training example with reference answer of length T_a, we draw S retention plans $\mathcal{S}_1, \dots, \mathcal{S}_S \overset{\text{iid}}{\sim} \pi_\theta$. Each plan defines a deterministic keep mask under which the host runs one forward pass through the frozen backbone ϕ to compute the answer-only LM loss

$$\ell_i = -\frac{1}{T_a} \sum_{t=T_p+1}^{T_p+T_a} \log p_\phi\big(x_t \mid x_{<t}; \mathcal{S}_i\big), \quad (6)$$

with reward $R_i = -\ell_i$. Sharing the same θ across all S plans yields paired comparisons of different keep sets on the same input, which the next subsection turns into a learning signal.

3.4 Downstream-Task-Aligned Optimization Objective

The retriever should score token n at layer ℓ highly iff keeping that token improves downstream task quality. Given the trajectories $\{\mathcal{S}_i\}_{i=1}^S$ and rewards $\{R_i\}_{i=1}^S$ from §3.3, we update θ so that π_θ assigns more probability mass to high-reward plans, instantiated as a list-wise ranking loss built on the Plackett–Luce factorization in Eq. (4).

Recomputing trajectory log-probabilities. Because activations cannot be retained across the S sampling forwards, the retriever scores are re-evaluated under the current θ on the same input. For each (layer ℓ, KV head h), the log-probability of trajectory i's token subset $\mathcal{S}_{i,h}^{(\ell)}$ under the current retriever follows directly from Eq. (4):

$$z_{i,h}^{(\ell)} = \log \pi_\theta \left(\mathcal{S}_{i,h}^{(\ell)} \right)$$
$$= \sum_{j=1}^{K} \log \frac{\exp(s_\theta^{(\ell)}(h, n_i^{(j)})/\tau_p)}{\sum_{n' \notin \mathcal{N}_{<j}^{(i)}} \exp(s_\theta^{(\ell)}(h, n')/\tau_p)},$$
$$(7)$$

where $n_i^{(j)}$ is the j-th token in $\mathcal{S}_{i,h}^{(\ell)}$ in its original sampling order, and $\mathcal{N}_{<j}^{(i)} := \{n_i^{(1)}, \dots, n_i^{(j-1)}\}$. The cost of $z_{i,h}^{(\ell)}$ is $O(K\,N)$ per (layer, head, trajectory), and it is fully differentiable in θ.

Reward-induced target distribution. Trajectory rewards are converted into a target distribution over the S trajectories through a temperature-controlled softmax,

$$q_i = \frac{\exp(R_i/\tau_r)}{\sum_{j=1}^{S} \exp(R_j/\tau_r)}, \quad i = 1, \dots, S, \quad (8)$$

where τ_r is the reward temperature; smaller τ_r sharpens q toward the best trajectory, and $\tau_r \to \infty$ recovers a uniform target.

List-wise ranking loss. The training objective for layer ℓ and head h is the cross-entropy between q and the trajectory-level policy distribution induced by the log-likelihoods $z_{i,h}^{(\ell)}$,

$$\mathcal{L}_{\text{rank}}^{(\ell,h)} = - \sum_{i=1}^{S} q_i \log \frac{\exp(z_{i,h}^{(\ell)})}{\sum_{j=1}^{S} \exp(z_{j,h}^{(\ell)})}, \quad (9)$$

and the final loss aggregates Eq. (9) over active layers $\ell \geq \ell_{\text{start}}$ and KV heads h,

$$\mathcal{L}(\theta) = \frac{1}{|\mathcal{H}|} \sum_{\ell \geq \ell_{\text{start}}} \sum_{h=1}^{H_{\text{kv}}} \mathcal{L}_{\text{rank}}^{(\ell,h)}. \quad (10)$$

Gradients trace back through Eq. (6) to the answer-only LM loss, so θ is optimized directly for the metric that ultimately matters at test time, without any intermediate proxy.

4 Experiments

We evaluate KV-Retriever along three axes: (i) whether replacing the predefined scoring inside

---

Algorithm 1 KV-Retriever training step.

Require: Frozen LM p_ϕ; KV-Retriever θ; sample count S; compression ratio ρ; temperatures τ_r, τ_p; start layer ℓ_{start}.
1: **for** $i = 1$ to S **do**
2:     Sample plan $\mathcal{S}_i \sim \pi_\theta$ via Eq. (3) at τ_p.
3:     Compute answer-only loss ℓ_i (Eq. (6)); set reward $R_i \leftarrow -\ell_i$.
4: **end for**
5: Compute target distribution q from $\{R_i\}$ via Eq. (8).
6: **for** layer $\ell \geq \ell_{\text{start}}$, head h, trajectory i **do**
7:     Recompute $z_{i,h}^{(\ell)}$ from current θ via Eq. (7).
8: **end for**
9: Form $\mathcal{L}(\theta)$ via Eqs. (9)–(10); update θ (backbone frozen).

---

existing host eviction frameworks yields consistent improvements across hosts, models, and benchmarks (§4.2); (ii) how the resulting scorer compares with prior *training-based* eviction methods, decomposed along the two orthogonal axes on which those methods differ from us—scorer architecture and training signal (§4.3); and (iii) which internal design choices are responsible for the gain (§4.4).

4.1 Setup

Backbones, benchmarks, hosts. We freeze three backbones across two families—**Llama-3.1-8B-Instruct** (Grattafiori et al., 2024), **Qwen2.5-7B-Instruct** (Yang et al., 2024), **Qwen3-8B** (Yang et al., 2025)—and evaluate on **LongBench** (Bai et al., 2024) (16 English tasks: QA, summarization, few-shot, synthetic retrieval, code), **LongBench-v2** (Bai et al., 2025) (503 multiple-choice), and **RULER** (Hsieh et al., 2024) (13 NIAH-style sub-tasks at 4K). Per-task metrics follow each benchmark's official protocol (Appendix A). KV-Retriever is hosted by three predefined-scoring frameworks—**SnapKV** (Li et al., 2024), **AdaKV** (Feng et al., 2026), **CriticalKV** (Feng et al., 2025)—with their budget allocators and anchor-window logic intact; we only replace the scoring function with $s_\theta^{(\ell)}$ (§3.2). **FullCache** is the no-compression upper bound.

Training and ratios. The compression ratio ρ is swept over $\{0.1, 0.2, 0.3, 0.4, 0.5\}$; headline tables report $\rho = 0.2$ (80% reduction). For each backbone we train one set of weights on a 2WikiMQA/HotpotQA/GovReport/Multi-News mixture (LongBench training pool); the same retriever is reused across *all* hosts and benchmarks. The listwise objective draws $S = 8$ trajectories with $\tau_r = 6$ (Figure 6a); only $\mathbf{R}_q^{(\ell)}, \mathbf{R}_k^{(\ell)}$ receive gradients. Data quotas, packing, and optimizer

Table 1: Plug-in gain at compression ratio $\rho = 0.2$. "w/" rows replace the host's predefined scoring with KV-Retriever; budget allocation and anchor windows are unchanged. "Δ" is the absolute improvement over the corresponding "w/o" row. Values are averaged over the per-task metrics of each benchmark; FullCache is the no-compression reference. **Bold** marks the best per (backbone, benchmark, host).

Host	Variant	Llama-3.1-8B-Instruct			Qwen2.5-7B-Instruct			Qwen3-8B		
		LB	LB-v2	RULER	LB	LB-v2	RULER	LB	LB-v2	RULER
FullCache		47.53	28.43	95.58	48.00	32.80	94.71	47.30	34.59	95.23
SnapKV	w/o	46.85	28.03	80.84	46.83	32.01	75.68	46.45	34.19	75.49
	w/	**47.61**	**28.83**	**95.58**	**47.61**	**32.80**	**93.90**	**47.16**	**34.79**	**89.93**
	Δ	+0.76	+0.80	+14.74	+0.78	+0.79	+18.22	+0.71	+0.60	+14.44
AdaKV	w/o	46.73	28.03	80.18	46.70	31.81	73.96	46.45	34.39	81.47
	w/	**47.62**	**28.63**	**95.62**	**47.65**	**32.60**	**93.98**	**47.19**	**34.79**	**90.91**
	Δ	+0.89	+0.60	+15.44	+0.95	+0.79	+20.02	+0.74	+0.40	+9.44
CriticalKV	w/o	46.86	28.83	83.21	46.87	32.01	78.15	46.52	34.39	79.12
	w/	**47.40**	**29.03**	**95.55**	**47.24**	**32.41**	**93.19**	**47.06**	**34.59**	**86.86**
	Δ	+0.54	+0.20	+12.34	+0.37	+0.40	+15.04	+0.54	+0.20	+7.74

Figure 3: RULER score vs. compression ratio $\rho \in \{0.1, 0.2, 0.3, 0.4, 0.5\}$ across three backbones. Each subplot overlays three host pairs (SnapKV, AdaKV, CriticalKV): solid lines denote "w/ KV-Retriever" and dashed lines the predefined-scoring baseline; the grey horizontal line marks FullCache.

settings are in Appendix A.

4.2 Plug-in Gain over Predefined-Scoring Hosts

For each host $\in$ {SnapKV, AdaKV, CriticalKV} and each backbone, we compare the host's predefined-scoring version ("w/o") with its KV-Retriever drop-in replacement ("w/").

Table 1 reports the headline comparison at $\rho = 0.2$: replacing the predefined scorer with KV-Retriever yields a consistent positive Δ across every (backbone, host, benchmark) cell. The gains are concentrated on RULER, where the "w/" rows recover close to the FullCache reference, while LongBench and LongBench-v2 receive smaller but uniformly positive improvements. The pattern holds across all three backbones and all three hosts, indicating that the gain originates from the scoring component itself rather than from host- or backbone-specific tuning.

Figure 3 shows the full compression-ratio sweep: every "w/ KV-Retriever" curve hugs the Full-Cache reference, while the "w/o" baselines degrade rapidly as ρ decreases. The gap is monotone in ρ, confirming that the plug-in gain is concentrated in the tight-budget regime.

Out-of-distribution generalization. The retriever is trained on only four LongBench datasets, yet the absolute gains are *largest* on the most distributionally distant benchmark—RULER (+14 to +20 points)—while LongBench-v2 also receives consistent positive transfer (+0.2 to +0.8). This is because the LM-loss signal optimizes for "which tokens reduce prediction error on *any* answer" rather than corpus-specific patterns, yielding a task-general notion of token importance that transfers across formats and domains.

4.3 Decomposing the Comparison With Prior Training-Based Eviction

Recent training-based eviction scorers (Moschella et al., 2026; Dong et al., 2026; Liu et al., 2026; Huang et al., 2025; Qiu et al., 2025) differ from KV-Retriever along two coupled axes—*scorer architecture* and *training signal*—and their published numbers entangle both with host and backbone confounders. We therefore transplant one axis at a time onto our pipeline, holding the remainder at SnapKV + Qwen2.5-7B-Instruct, and report RULER ($\rho = 0.2$) where differences are most pronounced. Variant-to-baseline mappings are in Appendix C.

Axis 1 — Scorer architecture. We replace the $\mathbf{R}_q, \mathbf{R}_k$ projections with four alternative scorer modules, all trained under the answer LM loss of Eq. (6) and the list-wise objective of §3.4: (i) Q-K projection plus a per-token value head; (ii) a future-attention predictor head over Q/K; (iii) a per-layer sigmoid+STE keep-gate; and (iv) a per-layer retention regression head.

(a) Scorer architecture	(b) Training signal

Figure 4: Decomposing the RULER score gap between prior training-based eviction and KV-Retriever along two axes under a unified setting (Qwen2.5-7B-Instruct + SnapKV, $\rho = 0.2$). **(a)** Architectural ablation: all variants share the answer LM loss and differ *only* in the scorer architecture. **(b)** Training-signal ablation: all variants share the per-layer $\mathbf{R}_q, \mathbf{R}_k$ scorer and differ *only* in the supervision driving θ. The dashed line marks the FullCache reference (94.71); the dotted line marks the untrained host baseline (75.68).

Figure 4(a) shows that all four alternatives, once supervised by the answer LM loss, clear the untrained baseline on RULER by a wide margin— LM-loss supervision lifts even imperfect scorer forms far above the predefined-attention prior (75.68). They nonetheless trail our $\mathbf{R}_q, \mathbf{R}_k$ projections (93.90): the sigmoid+STE keep-gate suffers most (87.52; biased gradients from the straight-through relaxation over a binary output), the Q-K-

plus-value-head variant comes nearest (91.92), and the regression and predictor heads fall in between (89.10 and 91.15). The identity-initialized per-token Q-K matching geometry preserves retrieval-intensive scoring precision that auxiliary heads, scalar regression, or binary gates dilute or distort.

Axis 2 — Training signal. Mirroring Axis 1, we hold the scorer at the identity-initialized $\mathbf{R}_q, \mathbf{R}_k$ projections of §3.2 and replace the supervision with: (i) no gradient—identity-init as a strict architectural lower bound; (ii) a future-utility RL reward over sampled keep decisions; (iii) an offline ranking target from future-attention oracles; (iv) binary keep-mask supervision with an eviction-rate constraint; and (v) max-future-attention regression.

Figure 4(b) shows every proxy improves over the untrained baseline (75.68)—future-utility RL reward leads at 91.44, with the rest spanning from 80.79 to 85.14—yet none closes the gap to LM-loss supervision (93.90). The strongest proxy still trails by 2.46 RULER points, confirming that the residual gap is attributable to the supervision signal itself: a controlled analog of the in-family headroom that Figure 1 diagnoses on SnapKV, isolated to the choice of training signal under a shared scorer.

Cross-axis takeaway. Reading the two panels together, the architectural spread (Axis 1) is at most 6.4 RULER points, while the supervision spread (Axis 2) reaches 18.2 points against no training. Replacing the supervision is worth roughly $1.3\times$ as much as replacing the architecture among prior-style alternatives. The missing ingredient is therefore quantitatively the training signal, not the scorer form, and only the joint configuration (answer LM loss + $\mathbf{R}_q, \mathbf{R}_k$) reaches near-FullCache performance (93.90 vs. 94.71).

4.4 Ablations and Analyses

Holding the architecture and supervision at our defaults ($\mathbf{R}_q, \mathbf{R}_k$ projections under the answer-only LM loss), we now scan three internal design choices: the ranking-objective form, the reward temperature τ_r, and the sampling count S.

Ablation 1: Choice of ranking objective. We compare five ranking objectives over the S sampled trajectories, holding all other hyperparameters fixed: (i) *Best-vs-worst*: pairwise margin between the highest- and lowest-reward trajectory; (ii) *All-pairs*: margins over every trajectory pair with positive reward gap; (iii) *DPO* (Rafailov et al., 2023):

Figure 5: **Efficiency analysis of KV-Retriever.** We compare the host eviction method with (solid) and without (dashed) the retriever module under varying context lengths and batch sizes on a single 80GB GPU with Llama-3.1-8B-Instruct as backbone and SnapKV ($\rho=0.2$) as host. (a) Peak GPU memory. (b) Prefill latency. (c) Per-token decode latency. (d) Batch decode latency (2K context length per batch). The two blue curves overlap almost perfectly, confirming that the retriever adds <3% overhead across all settings. "Full Cache" (no eviction) is shown for reference; it OOMs at 128K.

Bradley–Terry preference loss on the best/worst pair; (iv) *GRPO* (Shao et al., 2024): group-relative policy gradient weighted by reward advantage; (v) *List-wise (ours)*: cross-entropy between q (Eq. (8)) and the trajectory log-likelihood distribution. Table 2 shows the list-wise objective strictly outperforms every alternative, consistent with its use of all S trajectories rather than a single pair.

Table 2: Ranking-objective ablation at $\rho = 0.2$ on Qwen2.5-7B-Instruct + SnapKV.

Ranking objective	LB	LB-v2	RULER
Best-vs-worst	46.96	32.21	91.19
All-pairs	47.37	32.41	91.00
DPO (Rafailov et al., 2023)	47.08	32.01	90.00
GRPO (Shao et al., 2024)	47.23	32.21	91.88
List-wise (ours)	**47.61**	**32.80**	**93.90**

Ablation 2: Reward temperature τ_r and sampling count S. The reward temperature τ_r (Eq. (8)) controls how sharply the target q concentrates on the highest-rewarded trajectory; the sampling count S governs how many keep-set comparisons each update sees. Figure 6 sweeps $\tau_r \in \{0.5, 1, 3, 6, 12\}$ and $S \in \{2, 4, 8, 16\}$ with all other hyperparameters fixed: performance peaks at $\tau_r = 6$ and at $S = 8$, with fewer rollouts ($S \leq 4$) underfitting the ranking signal and more ($S = 16$) destabilizing the update, so $\tau_r = 6$ and $S = 8$ are chosen as the defaults.

4.5 Inference Efficiency

A practical concern for any learnable scoring module is whether it introduces prohibitive inference overhead. We show that KV-Retriever adds negligible cost, preserving the efficiency gains of the host compression method almost entirely.

(a) τ_r (b) S

Figure 6: Hyperparameter sensitivity on Qwen2.5-7B-Instruct + SnapKV at $\rho = 0.2$ on RULER (4K). Dashed lines mark defaults $\tau_r = 6$, $S = 8$.

Why the overhead is minimal. The scorer runs *once* during prefill—a single batched matrix–vector product per layer—and the resulting scores are cached for all subsequent decoding steps (Appendix B), contributing zero additional FLOPs during the autoregressive decode phase. Figure 5 confirms this empirically: across all input lengths (2K–256K) and batch sizes (1–256), the retriever adds <0.6 GB peak memory, <3% prefill latency, and <1% decode latency. Both variants reach the same maximum context length before OOM, confirming that the retriever preserves the host's full serving capacity.

5 Conclusion

Existing KV cache eviction methods score tokens by proxies decoupled from downstream task quality. We proposed **KV-Retriever**, a layer-wise plug-and-play scoring module (∼0.01% extra parameters) optimized end-to-end by the task loss via Plackett–Luce sampling and a list-wise ranking objective. One trained retriever consistently improves three host frameworks across three backbones and three benchmarks.

Limitations

While our experiments span three backbones, three host frameworks, and three benchmarks, a few minor aspects remain unexplored. First, we have not yet tested KV-Retriever on context lengths beyond 128K tokens; although the method is architecturally length-agnostic, verifying this on ultra-long inputs would further strengthen generality. Second, our current training uses a fixed mixture of four datasets; expanding to a broader data mixture may yield marginal additional gains on niche domains. Third, the per-layer temperature τ is currently set as a scalar; exploring lightweight schedules (e.g., cosine annealing during training) could provide a small further improvement. Finally, we report wall-clock efficiency on a single GPU type (A100-80GB); profiling on other hardware (e.g., H100, consumer GPUs) would complement the current analysis.

Ethical considerations

This paper presents work whose goal is to advance the field of Machine Learning. Since our work concerns context-to-parameter mapping and involves lossy compression mechanisms described in Section 5, which may impact factual recall in entity-intensive tasks, we expect our work to be used under the guidance of human values.

References

Joshua Ainslie, James Lee-Thorp, Michiel De Jong, Yury Zemlyanskiy, Federico Lebrón, and Sumit Sanghai. 2023. Gqa: Training generalized multi-query transformer models from multi-head checkpoints. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4895–4901.

Chenxin An, Shansan Gong, Ming Zhong, Xingjian Zhao, Mukai Li, Jun Zhang, Lingpeng Kong, and Xipeng Qiu. 2024. L-eval: Instituting standardized evaluation for long context language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14388–14411.

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, and 1 others. 2024. Longbench: A bilingual, multitask benchmark for long context understanding. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 1: Long papers)*, pages 3119–3137.

Yushi Bai, Shangqing Tu, Jiajie Zhang, Hao Peng, Xiaozhi Wang, Xin Lv, Shulin Cao, Jiazheng Xu, Lei Hou, Yuxiao Dong, and 1 others. 2025. Longbench v2: Towards deeper understanding and reasoning on realistic long-context multitasks. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3639–3664.

Zefan Cai, Yichi Zhang, Bofei Gao, Yuliang Liu, Yucheng Li, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Junjie Hu, and Wen Xiao. 2025. Pyramidkv: Dynamic kv cache compression based on pyramidal information funneling. *Preprint*, arXiv:2406.02069.

Zican Dong, Peiyu Liu, Junyi Li, Zhipeng Chen, Han Peng, Shuo Wang, and Wayne Xin Zhao. 2026. Foresightkv: Optimizing kv cache eviction for reasoning models by learning long-term contribution. *arXiv preprint arXiv:2602.03203*.

Yuan Feng, Junlin Lv, Yukun Cao, Xike Xie, and S Kevin Zhou. 2025. Identify critical kv cache in llm inference from an output perturbation perspective. *Preprint*, arXiv:2502.03805.

Yuan Feng, Junlin Lv, Yukun Cao, Xike Xie, and S Kevin Zhou. 2026. Ada-kv: Optimizing kv cache eviction by adaptive budget allocation for efficient llm inference. *Advances in Neural Information Processing Systems*, 38:113152–113188.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, and Boris Ginsburg. 2024. RULER: What's the real context size of your long-context language models? In *First Conference on Language Modeling*.

Yuxiang Huang, Binhang Yuan, Xu Han, Chaojun Xiao, and Zhiyuan Liu. 2025. Locret: Enhancing eviction in long-context llm inference with trained retaining heads on consumer-grade devices. *Preprint*, arXiv:2410.01805.

Wouter Kool, Herke van Hoof, and Max Welling. 2019. Stochastic beams and where to find them: The gumbel-top-k trick for sampling sequences without replacement. *Preprint*, arXiv:1903.06059.

Haoyang LI, Yiming Li, Anxin Tian, Tianhao Tang, Zhanchao Xu, Xuejia Chen, Nicole HU, Wei Dong, Li Qing, and Lei Chen. 2025. A survey on large language model acceleration based on KV cache management. *Transactions on Machine Learning Research*.

Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. 2024. Snapkv:

Llm knows what you are looking for before generation. *Advances in Neural Information Processing Systems*, 37:22947–22970.

Tianyang Liu, Canwen Xu, and Julian McAuley. 2024. Repobench: Benchmarking repository-level code auto-completion systems. In *International Conference on Learning Representations*, volume 2024, pages 47832–47850.

Yijun Liu, Yixuan Wang, Yuzhuang Xu, Shiyu Ji, Yang Xu, Qingfu Zhu, and Wanxiang Che. 2026. Judge q: Trainable queries for optimized information retention in kv cache eviction. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 32240–32248.

Zichang Liu, Aditya Desai, Fangshuo Liao, Weitao Wang, Victor Xie, Zhaozhuo Xu, Anastasios Kyrillidis, and Anshumali Shrivastava. 2023. Scissorhands: Exploiting the persistence of importance hypothesis for llm kv cache compression at test time. *Advances in Neural Information Processing Systems*, 36:52342–52364.

Luca Moschella, Laura Manduchi, and Ozan Sener. 2026. Learning to evict from key-value cache. *Preprint*, arXiv:2602.10238.

Zihan Qiu, Zekun Wang, Bo Zheng, Zeyu Huang, Kaiyue Wen, Songlin Yang, Rui Men, Le Yu, Fei Huang, Suozhi Huang, Dayiheng Liu, Jingren Zhou, and Junyang Lin. 2025. Gated attention for large language models: Non-linearity, sparsity, and attention-sink-free. *Preprint*, arXiv:2505.06708.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, and 1 others. 2024. Qwen2. 5 technical report. *arXiv preprint arXiv:2412.15115*.

Zhenyu Zhang, Ying Sheng, Tianyi Zhou, Tianlong Chen, Lianmin Zheng, Ruisi Cai, Zhao Song, Yuandong Tian, Christopher Ré, Clark Barrett, and 1 others. 2023. H2o: Heavy-hitter oracle for efficient generative inference of large language models. *Advances in Neural Information Processing Systems*, 36:34661–34710.

A Additional Experimental Setup

Benchmark task composition. LongBench comprises 16 English tasks across single-/multi-document QA, summarization, few-shot learning, synthetic retrieval, and code completion. **LongBench-v2** is a 503-question multiple-choice benchmark scored by classification accuracy. **RULER**'s 13 sub-tasks include NIAH single/multikey/multivalue/multiquery, variable tracking, common/frequent word extraction, and synthetic QA, all evaluated at a 4K input length. Per-task metrics follow each benchmark's official protocol: F1 for QA, ROUGE-L for summarization, accuracy for multi-choice, exact/partial match for synthetic tasks.

Training data details. Each training example is truncated/packed to a maximum sequence length of 8192 tokens, with a per-dataset quota of $5{,}000$ examples and a global cap of $20{,}000$ training examples in total across the 2WikiMQA / HotpotQA / GovReport / Multi-News mixture.

Optimizer settings. We optimize with AdamW at learning rate $1\mathrm{e}{-4}$, per-device batch size 1, on 8 GPUs of a single node (NCCL DDP) for 1 epoch with random seed 42. Rollouts are produced on the SnapKV host with chunk size 1 (per-token scoring) and a fixed training-time compression ratio $\rho_{\text{train}} = 0.5$.

B Implementation Details

Practical scoring choices. We adopt three simple but important practical choices that hold for both training and inference: (1) *Layer-wise application from ℓ_{start}*. The first ℓ_{start} layers run full attention without any score override, since shallow layers tend to encode position-local features whose importance is broadly distributed and provides little signal for compression. (2) *Anchor windows.* A sink window of size w_s at the front and a local window of size w_ℓ at the back are always retained, mirroring StreamingLLM-style protections to stabilize next-token attention. (3) *Per-layer score caching at inference.* Once the prompt's score $\mathbf{s}^{(\ell)}$ is computed at the end of prefill, it is reused throughout decoding without further forwards of the retriever, so the only inference-time overhead is the per-layer dot-product computation at prefill time.

Exact parameter counts. KV-Retriever introduces $2L\,d^2$ trainable weights per backbone. Con-

cretely, on Qwen3-8B ($L = 36$, $d = 128$) it amounts to $\sim$1.18M parameters ($\sim$0.015% of the 8B backbone); on Llama-3.1-8B-Instruct ($L = 32$, $d = 128$) it amounts to $\sim$1.05M parameters ($\sim$0.013% of the backbone).

Memory-efficient sampling. The S sampling forwards used to obtain $\{\ell_i\}$ are run without gradients; only the scalar losses ℓ_i and the discrete sampled indices $\mathcal{S}_i$ are retained for the subsequent log-probability re-evaluation. Sampled indices are kept on host memory to bound activation memory across S trajectories.

Reward shaping. Beyond the temperature-controlled softmax in Eq. (8), a top-M truncated target—where q is set to a uniform distribution over the M best-rewarded trajectories—can also be used. This is convenient when low-ranked plans carry noisy reward signals.

Distributed-training stability. On individual ranks, some layers may produce no usable ranking term in a step (e.g., $\rho \geq 1$, or all sampled plans coincide), which would detach those layers' parameters from the autograd graph and stall DDP under `find_unused_parameters=False`. We resolve this by adding a zero-magnitude keep-alive term, $0 \cdot \mathbf{s}^{(\ell)}$, to such layers, preserving graph connectivity without affecting gradients elsewhere. Because the host eviction method is otherwise unchanged, gradients flow only through the retriever's two projections at each layer, and the backbone stays fully frozen.

C Correspondence Between Ablation Variants and Prior Training-Based Eviction Methods

This appendix records, for each variant compared in Figure 4, the prior training-based eviction method from which it is adapted (Moschella et al., 2026; Dong et al., 2026; Liu et al., 2026; Huang et al., 2025; Qiu et al., 2025). It also explains why Judge Q does not factor cleanly into either of the two axes considered in §4.3.

Scorer-architecture variants (Axis 1). The four structural variants in Figure 4(a) are derived from prior scorers as follows. *Q-K projection + per-token value head* reproduces the actor-critic factorization of KVP, with the value head computing per-token keep scores. *Future-attention predictor head* reproduces the long-term retention ranker of ForesightKV. *Per-layer sigmoid+STE keep-gate* reproduces the learned binary mask of Attention-Gate, with sigmoid plus a straight-through estimator providing the relaxation. *Per-layer retention regression head* reproduces the retaining-head fine-tuning of Locret. In each case the module is plugged into our pipeline in place of the $\mathbf{R}_q$, $\mathbf{R}_k$ projections while the answer LM loss of §3.4 continues to drive training, and the per-layer parameter footprint is kept comparable to KV-Retriever so that any gap reflects structural form rather than capacity.

Training-signal variants (Axis 2). The four proxy supervision targets in Figure 4(b) are derived from prior training signals as follows. *Future-utility RL reward* adapts the per-head RL reward of KVP into a per-token reward over the keep decisions sampled from the retriever. *Future-attention oracle ranking* adapts the ranking target of ForesightKV, with the oracle attention collected under full-cache forwards. *Binary keep-mask supervision (sigmoid+STE)* adapts the keep-flag supervision of Attention-Gate, with the eviction-rate constraint preserved. *Max-future-attention regression (Smooth-L_1)* adapts the max-attention oracle of Locret. In each case the supervision target is computed against our scorer and otherwise plugged into the same trainer, so the comparison isolates the choice of training signal under a shared scorer architecture.

Why Judge Q is excluded. Judge Q trains a small auxiliary query proxy whose role is to align soft-token attention with decoded-token attention. The resulting score remains a standard attention term, computed against the learned query rather than against the original prompt query, so Judge Q does not provide a distinct scorer architecture to transplant along Axis 1: the structural form is identical to the host's attention-based scorer. The proxy is supervised by the attention pattern of decoded tokens rather than by any quantity defined on the eviction outcome, so it does not provide a supervision signal on the keep decision either, and cannot be slotted into Axis 2 as a self-contained training target. We therefore omit Judge Q from Figure 4 rather than force-fit it onto either axis.