Challenging Common Assumptions in Convex Reinforcement Learning

Abstract

The classic Reinforcement Learning (RL) formulation concerns the maximization of a *scalar* reward function. More recently, *convex* RL has been introduced to extend the RL formulation to all the objectives that are convex functions of the state distribution induced by a policy. Notably, convex RL covers several relevant applications that do not fall into the scalar formulation, including imitation learning, risk-averse RL, and pure exploration. In classic RL, it is common to optimize an *infinite trials* objective, which accounts for the state distribution instead of the empirical state visitation frequencies, even though the actual number of trajectories is always finite in practice. This is theoretically sound since the infinite trials and finite trials objectives are equivalent and thus lead to the same optimal policy. In this paper, we show that this hidden assumption does not hold in convex RL. In particular, we prove that erroneously optimizing the infinite trials objective in place of the actual *finite trials* one, as it is usually done, can lead to a significant approximation error. Since the finite trials setting is the default in both simulated and real-world RL, we believe shedding light on this issue will lead to better approaches and methodologies for convex RL, impacting relevant research areas such as imitation learning, risk-averse RL, and pure exploration among others.

1 Introduction

Standard Reinforcement Learning (RL) [27] is concerned with sequential decision-making problems in which the utility can be expressed through a linear combination of scalar reward terms. The coefficients of this linear combination are given by the state visitation distribution induced by the agent's policy. Thus, the objective function can be equivalently written as the inner product between the mentioned state distribution and a reward vector. However, not all the relevant objectives can be encoded through this linear representation [1]. Several works have thus extended the standard RL formulation to address non-linear objectives of practical interest. These include imitation learning [17], or the problem of finding a policy that minimizes the distance between the induced state distribution and the state distribution provided by experts' interactions [19, 20, 13], risk-averse RL [11], in which the objective is sensitive to the tail behavior of the agent's policy [e.g., 28, 23], pure exploration [16], where the goal is to find a policy that maximizes the entropy of the induced state distribution, diverse skills discovery [14, 10], constrained RL [2, 22], and others. All this large body of work has been recently unified into a unique framework, called *convex* RL [31, 30, 12], which admits as an objective any convex function of the state distribution induced by the agent's policy. The convex RL problem has been showed to be largely tractable either computationally, as it admits a dual formulation akin to standard RL [24], or statistically, as principled algorithms achieving sub-linear regret rates that are slightly worse than standard RL have been developed [31, 30].

However, we note that the usual convex RL formulation makes an implicit *infinite trials* assumption which is rarely met in practice. Indeed, the objective is written as a function of the state distribution, which is an expectation over the empirical state distributions that are actually obtained by running the policy in a given episode. In practice, we always run our policy for a finite number of episodes (or *trials*), which in general prevents the empirical state distribution from converging to its expectation. This has never been a problem in standard RL: due to the scalar objective, optimizing the policy over infinite trials or finite

Figure 1: Summary of the main finding of this paper: the equivalence between finite and infinite trials objectives does not hold for the convex RL formulation.

trials is equivalent, as it leads to the same optimal policy. Crucially, in this paper, we show that this property does not hold for the convex RL formulation: a policy optimized over infinite trials can be significantly sub-optimal when deployed over finite trials (Figure 1). In light of this observation, we reformulate the convex RL problem from a *finite trials* perspective, developing insights that can be used to partially rethink the way convex objectives have been previously addressed in RL, with potential ripple effects to research areas of significant interest, such as imitation learning, risk-averse RL, pure exploration, and others.

In this paper, we formalize the notion of a finite trials RL problem, in which the objective is a function of the empirical state distribution induced by the agent's policy over n trials rather than its expectation over infinite trials. As an illustrative example, consider a financial application, in which we aim to optimize a trading strategy. In the real world, we can only deploy the strategy over a single trial. Thus, we are only interested in the performance of the strategy in the real-world realization, rather than the performance of the strategy when averaging different realizations. Following this intuition, we first define the (linear) finite trial RL formulation (Section 3), for which it is trivial to prove the equivalence with standard RL. In Section 4, we provide the finite trial convex RL formulation, for which we prove an upper bound on the approximation error made by optimizing the infinite trials as a proxy of the finite trials objective. In light of this finding, we challenge the hidden assumption that **(1)** *convex RL can be equivalently addressed with an infinite trials formulation*, even if the setting is finite-trial. We corroborate this result with an additional numerical analysis showing that the approximation bound is non-vacuous for relevant applications (Section 6). Finally, in Section 5 we include an in-depth analysis of the *single trial* convex RL, which suggests that other common assumptions in the convex RL literature, i.e., that **(2)** *the problem is always computationally tractable* and that **(3)** *stationary policies are in general sufficient*, should be reconsidered as well. The proofs of the reported results can be found in the Appendix.

2 Preliminaries

In this section, we report the notation and background useful to understand the paper. We denote with $[H]$ a set of integers $\{1, \ldots, H\}$, and with a lower case letter a a scalar or a vector, according to the context. For two vectors $a, b \in \mathbb{R}^d$, we denote with $a \cdot b = \sum_{i=1}^{d} a_i b_i$ the inner product between a, b.

2.1 Probabilities and Percentiles

Let $\mathcal{X}$ denote a measurable space, we will denote with $\Delta(\mathcal{X})$ the probability simplex over $\mathcal{X}$, and with $p \in \Delta(\mathcal{X})$ a probability measure over $\mathcal{X}$. For two probability measures p, q over $\mathcal{X}$, we define their ℓ^p-distance as $\|p - q\|_p := \left(\sum_{x \in \mathcal{X}} |p(x) - q(x)|^p \right)^{1/p}$, and their Kullback-Leibler (KL) divergence as $KL(p\|q) := \sum_{x \in \mathcal{X}} p(x) \log \left(p(x)/q(x) \right)$. Let X be a random variable distributed according to p, having a cumulative density function $F_X(x) = Pr(X \leq x)$. We denote with $\mathbb{E}[X]$ its expected value, and its α-percentile is denoted as $\mathrm{VaR}_\alpha(X) = \inf \left\{ x \mid F_X(x) \geq \alpha \right\} = F_X^{-1}(\alpha)$, where $\alpha \in (0, 1)$ is a confidence level, and VaR_α stands for Value at Risk (VaR) at level α. We denote the expected value of X within its α-percentile as $\mathrm{CVaR}_\alpha(X) = \mathbb{E} \left[X \mid X \leq \mathrm{VaR}_\alpha(X) \right]$, where CVaR_α stands for Conditional Value at Risk (CVaR) at level α.

2.2 Markov Decision Processes

A finite Markov Decision Process (MDP) [24] is defined as $\mathcal{M} := (\mathcal{S}, \mathcal{A}, P, H, \mu, r)$, where $\mathcal{S}$ is a state space of size S, $\mathcal{A}$ is an action space of size A, P is a Markovian transition model $P : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$, such that $P(s'|s, a)$ denotes the conditional probability of the next state s' given the current state s and action a, H is the episode horizon, μ is an initial state distribution $\mu : \Delta(\mathcal{S})$, and r is a scalar reward function $r : \mathcal{S} \to \mathbb{R}$, such that $r(s)$ is the reward collected in the state s.

In the typical interaction episode, an agent first observes the initial state $s_0 \sim \mu$ of the MDP. Then, the agent select an action a_0, so that the MDP transitions to the next state $s_1 \sim P(\cdot|s_0, a_0)$, and the agent collects the reward $r(s_1)$. Having observed s_1, the agent then selects an action a_1 triggering a subsequent transition to $s_2 \sim P(\cdot|s_1, a_1)$. This process carries on repeatedly until the episode ends.

A policy π defines the behavior of an agent interacting with an MDP, i.e., the strategy for which an action is selected at any step of the episode. It consists of a sequence of decision rules $(\pi_t)_{t=0}^{\infty}$ that maps the current trajectory[1] $h_t = (s_i, a_i)_{i=0}^{t-1} \in \mathcal{H}_t$ with a distribution over actions $\pi_t : \mathcal{H}_t \to \Delta(\mathcal{A})$, where $\mathcal{H}_t$ denotes the set of trajectories of length t. A non-stationary policy is a sequence of decision rules $\pi_t : \mathcal{S} \to \Delta(\mathcal{A})$. A stationary (Markovian) policy is a time-consistent decision rule $\pi : \mathcal{S} \to \Delta(A)$, such that $\pi(a|s)$ denotes the conditional probability of taking action a in state s.

A trajectory h, obtained from an interaction episode, induces an empirical distribution d over the states of the MDP $\mathcal{M}$, such that $d(s) = \frac{1}{|h|} \sum_{s_t \in h} \mathbb{1}(s_t = s)$. We denote with p^π the probability of drawing d by following the policy π. For $n \in \mathbb{N}$, we denote with d_n the empirical distribution $d_n(s) = \frac{1}{n} \sum_{i=1}^{n} d_i(s)$, and with p_n^π the probability of drawing d_n by following the policy π for n episodes. Finally, we call the expectation $d^\pi = \mathbb{E}_{d \sim p^\pi}[d]$ the state distribution induced by π.

3 Reinforcement Learning in Finite Trials

In the standard RL formulation [27], an agent aims to learn an optimal policy by interacting with an unknown MDP $\mathcal{M}$. An optimal policy is a decision strategy that maximizes the expected sum of rewards collected during an episode. Especially, we can represent the value of a policy π through the value function $V_h^\pi(s) := \mathbb{E}_\pi \left[\sum_{h'=h}^{H} r(s_{h'}) \mid s_h = s \right]$. The value function allows us to write the RL objective as $\max_{\pi \in \Pi} \mathbb{E}_{s_1 \sim \mu}[V_1^\pi(s_1)]$, where Π is the set of all the stationary policies. Equivalently, we can rewrite the RL objective into its dual formulation [24], i.e.,

RL
$$\max_{\pi \in \Pi} \ \left(r \cdot d^\pi \right) =: \mathcal{J}_\infty(\pi) \tag{1}$$

where we denote with $r \in \mathbb{R}^S$ a reward vector, and with d^π the state distribution induced by π. We call the problem (1) the *infinite trials* RL formulation. Indeed, the objective $\mathcal{J}_\infty(\pi)$ considers the sum of the rewards collected during an episode, i.e., $r \cdot d^\pi$, that we can achieve on the average of an infinite number of episodes drawn with π. This is due to the state distribution d^π being an expectation of empirical distributions $d^\pi = \mathbb{E}_{d \sim p^\pi}[d]$. However, in practice, we can never draw infinitely many episodes following a policy π. Instead, we draw a small batch of episodes $d_n \sim p_n^\pi$. Thus, we can instead conceive a *finite trials* RL formulation that is closer to what is optimized in practice.

Finite Trials RL
$$\max_{\pi \in \Pi} \ \left(\mathbb{E}_{d_n \sim p_n^\pi} \left[r \cdot d_n \right] \right) =: \mathcal{J}_n(\pi) \tag{2}$$

One could then wonder whether optimizing the finite trials objective (2) leads to results that differ from the infinite trials one (1). To this point, it is straightforward to see that the two objective functions are actually equivalent

$$\mathcal{J}_n(\pi) = \mathbb{E}_{d_n \sim p_n^\pi} \left[r \cdot d_n \right] = r \cdot \mathbb{E}_{d_n \sim p_n^\pi} \left[d_n \right] = r \cdot d^\pi = \mathcal{J}_\infty(\pi),$$

since r is a constant vector and the expectation is a linear operator. It follows that the infinite trials and the finite trials RL formulations admit the same optimal policies. Hence, one can enjoy both

---

[1] We will call a sequence of states and actions a trajectory or a history indifferently.

Table 1: Various convex RL objectives and applications. The last column states the equivalence between infinite trials and finite trials settings, as derived in Proposition 1 (Appendix).

Objective $\mathcal{F}$		Application	Infinite $\equiv$ Finite
$r \cdot d$	$r \in \mathbb{R}^S, d \in \Delta(\mathcal{S})$	RL	✓
$\|d - d_E\|_p^p$ $KL(d\|d_E)$	$d, d_E \in \Delta(\mathcal{S})$	Imitation Learning	✗
$-d \cdot \log(d)$	$d \in \Delta(\mathcal{S})$	Pure Exploration	✗
$\text{CVaR}_\alpha[r \cdot d]$ $r \cdot d - \mathbb{V}\text{ar}[r \cdot d]$	$r \in \mathbb{R}^S, d \in \Delta(\mathcal{S})$	Risk-Averse RL	✗
$r \cdot d, \text{ s.t. } \lambda \cdot d \leq c$	$r, \lambda \in \mathbb{R}^S, c \in \mathbb{R}, d \in \Delta(\mathcal{S})$	Linearly Constrained RL	✓
$- \mathbb{E}_z \, d_{KL}\left(d_z \| \mathbb{E}_k \, d_k\right)$	$z \in \mathbb{R}^d, d_z, d_k \in \Delta(\mathcal{S})$	Diverse Skill Discovery	✗

the computational tractability of the infinite trials formulation and, at the same time, optimize the objective function that is employed in practice. In the next section, we will show that a similar result does not hold true for the convex RL formulation.

4 Convex Reinforcement Learning in Finite Trials

Even though the RL formulation covers a wide range of sequential decision-making problems, several relevant applications cannot be expressed by means of the inner product between a linear reward vector r and a state distribution d^π [1, 26]. These include imitation learning, pure exploration, constrained problems, and risk-sensitive objectives, among others. Recently, a *convex* RL formulation [31, 30, 12] has been proposed to unify these applications in a unique general framework, which is

Convex RL

$$\max_{\pi \in \Pi} \; \left(\mathcal{F}(d^\pi) \right) =: \zeta_\infty(\pi) \tag{3}$$

where $\mathcal{F} : \Delta(S) \to \mathbb{R}$ is a function[2] of the state distribution d^π. In Table 1, we recap some of the most relevant problems that fall under the convex RL formulation, along with their specific $\mathcal{F}$ function. As it happens for linear RL, in any practical simulated or real-world scenario, we can only draw finite number of episodes with a policy π. From these episodes, we obtain an empirical distribution $d_n \sim p_n^\pi$ rather than the actual state distribution d^π, where n is the number of episodes. This can cause a mismatch from the objective that is typically considered in convex RL [31, 30], and what can be optimized in practice. To overcome this mismatch, we define a finite trials formulation of the convex RL objective, as we did in the previous section for the linear RL formulation.

Finite Trials Convex RL

$$\max_{\pi \in \Pi} \; \left(\mathbb{E}_{d_n \sim p_n^\pi} \left[\mathcal{F}(d_n) \right] \right) =: \zeta_n(\pi) \tag{4}$$

Comparing objectives (3) and (4), one can notice that both of them include an expectation over the episodes, being $d^\pi = \mathbb{E}_{d \sim p^\pi}[d]$. Especially, we can write

$$\zeta_\infty(\pi) = \mathcal{F}(d^\pi) = \mathcal{F}(\mathbb{E}_{d_n \sim p_n^\pi}[d_n]) \leq \mathbb{E}_{d_n \sim p_n^\pi}[\mathcal{F}(d_n)] = \zeta_n(\pi)$$

through the Jensen's inequality. As a consequence, optimizing the infinite trials objective $\zeta_\infty(\pi)$ does not necessarily lead to an optimal behavior for the finite trials objective $\zeta_n(\pi)$. From a mathematical perspective, this is due to the fact that the empirical distributions d_n induced by the policy π are averaged by the expectation d^π before computing the $\mathcal{F}$ function into objective (3), thus losing a measure of the performance $\mathcal{F}$ for each batch of episodes, which we instead keep in the objective (4).

---

[2]In this context, we use the term *convex* to distinguish it from the standard *linear* RL objective. However, in the following we will consider functions $\mathcal{F}$ that are either convex, concave or even non-convex. In general, problem (3) takes the form of a max problem for concave $\mathcal{F}$, or a min problem for convex $\mathcal{F}$.

Figure 2: The two illustrations report an abstract visualization of ζ_n and ζ_∞ for small values of n (left) and large values of n (right) respectively. The green bar visualize the distance $\left\| d_n - d^{\pi^\star} \right\|_1$, in which $d_n \sim p_n^{\pi^\dagger}$. The blue bar visualize the distance $\left| \zeta_n(\pi^\dagger) - \zeta_\infty(\pi^\star) \right|$. The orange bar visualize the approximation error, i.e., the distance $\left| \zeta_n(\pi^\dagger) - \zeta_n(\pi^\star) \right|$.

4.1 Approximating the Finite Trials Objective with Infinite Trials

Despite the evident mismatch between the finite trials and the infinite trials formulation of the convex RL problem, most existing works consider (3) as the standard objective, even if only a finite number of episodes can be drawn in practice. Thus, it is worth investigating how much we can lose by approximating a finite trials objective with an infinite trials one. First, we report a useful assumption on the structure of the function $\mathcal{F}$.

Assumption 4.1 (Lipschitz). *A function $\mathcal{F} : \mathcal{X} \to \mathbb{R}$ is Lipschitz-continuous if it holds for some constant L*

$$\left| \mathcal{F}(x) - \mathcal{F}(y) \right| \leq L \left\| x - y \right\|_1, \qquad \forall (x,y) \in \mathcal{X}^2.$$

Then, we provide an upper bound on the approximation error in the following theorem.

Theorem 4.1 (Approximation Error). *Let $n \in \mathbb{N}$ be a number of trials, let $\delta \in (0,1]$ be a confidence level, let $\pi^\dagger \in \arg\max_{\pi \in \Pi} \zeta_n(\pi)$ and $\pi^\star \in \arg\max_{\pi \in \Pi} \zeta_\infty(\pi)$. Then, it holds with probability at least $1 - \delta$*

$$err := \left| \zeta_n(\pi^\dagger) - \zeta_n(\pi^\star) \right| \leq 4LH\sqrt{\frac{2S \log(4H/\delta)}{n}}$$

The previous result establishes an approximation error rate $err = O(LH\sqrt{S/n})$ that is polynomial in the number of episodes n. Unsurprisingly, the guarantees over the approximation error scales with $O(1/\sqrt{n})$, as one can expect the empirical distribution d_n to concentrate around its expected value for large n [29]. This implies that approximating the finite trials objective $\zeta_n(\pi)$ with the infinite trials $\zeta_\infty(\pi)$ can be particularly harmful in those settings in which n is necessarily small. As an example, consider training a robot through a simulator and deploying the obtained policy in the real world, where the performance measures are often based on a single episode ($n = 1$). The performance that we experience from the deployment can be much lower than the expected $\zeta_\infty(\pi)$, which might result in undesirable or unsafe behaviors. However, Theorem 4.1 only reports an instance-agnostic upper bound, and it does not necessarily imply that there would be a significant approximation error in a specific instance, i.e., a pairing of an MDP $\mathcal{M}$ and a function $\mathcal{F}$. Nevertheless, in this paper we argue that the upper bound of the approximation error is not vacuous in several relevant applications, and we provide an illustrative numerical corroboration of this claim in Section 6.

Challenged assumption 1. *The convex RL problem can be equivalently addressed with an infinite trials formulation.*

Finally, in Figure 2 we report a visual representation[3] of the approximation error defined in Theorem 4.1. Notice that the finite trials objective ζ_n converges uniformly to the infinite trials objective ζ_∞

---

[3]Note that it is not possible to represent the objective functions in two dimensions in general. Nevertheless, we provide an abstract one-dimensional representation of the policy space to bring the intuition.

183 as a trivial consequence of Theorem 4.1. This is particularly interesting as it results in $\pi^\dagger$ converging
184 to $\pi^\star$ in the limit of large n as shown Figure 1.

5 In-Depth Analysis of Single Trial Convex Reinforcement Learning Setting

186 Having established a significant mismatch between the infinite trials convex RL setting that is usually
187 considered in previous works, i.e., $\zeta_\infty(\pi)$, and the finite trials formulation that is actually targeted in
188 practice, i.e., $\zeta_n(\pi)$, it is now worth taking a closer look at the finite trials optimization problem (4).
189 Indeed, to avoid the approximation error that can occur by optimizing (4) through the infinite trials
190 formulation (Theorem 4.1), one could instead directly address the optimization of (4). Especially, how
191 does the finite trials convex RL problem compare to its infinite trials formulation and the linear RL
192 problem? What kind of policies do we need to optimize the finite trials objective? Is the underlying
193 learning process statistically harder than infinite trials convex RL? In this section, we investigate the
194 answers to these relevant questions. To this purpose, we will focus on a *single trial* setting, i.e., $\zeta_n(\pi)$
195 with $n = 1$, which allows for a clearer analysis, while analogous considerations should extend to a
196 general number of trials $n > 1$.

Single Trial Convex RL

$$\max_{\pi \in \Pi} \left(\mathbb{E}_{d \sim p^\pi} \left[\mathcal{F}(d) \right] \right) =: \zeta_1(\pi) \tag{5}$$

197

198 Taking inspiration from [30], we can cast the problem (5) defined over an MDP $\mathcal{M}$ into a *convex* MDP
199 $\mathcal{CM} := (\mathcal{S}, \mathcal{A}, P, H, \mu, \mathcal{F})$, where $\mathcal{S}, \mathcal{A}, P, H, \mu$ are defined as in a standard MDP (see Section 2),
200 and $\mathcal{F} : \Delta(\mathcal{S}) \to \mathbb{R}$ is a convex function that defines the objective $\zeta_1(\pi)$. Is solving a convex MDP
201 $\mathcal{CM}$ significantly harder than solving an MDP $\mathcal{M}$?

5.1 Extended MDP Formulation of the Single Trial Convex RL Setting

203 We can show that any finite-horizon convex MDP $\mathcal{CM}$ can be actually translated into an equivalent
204 MDP $\mathcal{M}_\ell = (\mathcal{S}_\ell, \mathcal{A}_\ell, P_\ell, \mu_\ell, r_\ell)$, which we call an *extended* MDP. The main idea is to temporally-
205 extend $\mathcal{CM}$ so that each state contains the information of the full trajectory leading to it, so that
206 the convex objective can be cast into a linear reward. To do this, we define the extended state
207 space $\mathcal{S}_\ell$ to be the set of all the possible histories up to length H, so that $s_\ell \in \mathcal{S}_\ell$ now represents
208 a history. Then, we can keep $\mathcal{A}_\ell, P_\ell, \mu_\ell$ equivalent to $\mathcal{A}, P, \mu$ of the original $\mathcal{CM}$, where for the
209 extended transition model $P_\ell(s'_\ell | s_\ell, a)$ we solely consider the last state in the history s_ℓ to define the
210 conditional probability to the next history s'_ℓ. Finally, we just need to define a scalar reward function
211 $r_\ell : \mathcal{S}_\ell \to \mathbb{R}$ such that $r_\ell(s_\ell) = \mathcal{F}(d_{s_\ell})$ for all the histories s_ℓ of length H and $r_\ell(s_\ell) = 0$ otherwise,
212 where we denoted with d_{s_ℓ} the empirical state distribution induced by s_ℓ.

213 Notably, the problem of finding an optimal policy for the extended MDP $\mathcal{M}_\ell$, i.e., $\pi^* \in$
214 $\arg\max_{\pi \in \Pi} r_\ell \cdot d^\pi$, is equivalent to solve the problem (5). Whereas $\mathcal{M}_\ell$ can be solved with
215 classical MDP methods [24], the size of the policy $\pi : \mathcal{S}_\ell \to \Delta(\mathcal{A}_\ell)$ to be learned does scale with
216 the size of $\mathcal{M}_\ell$, which grows exponentially in the episode horizon as we have $|\mathcal{S}_\ell| > S^H$. Thus, the
217 extended MDP formulation and the resulting insight cast some doubts on the notion that the convex
218 RL is not significantly harder than standard RL [31, 30].

219 **Challenged assumption 2.** *Convex RL is only slightly harder than the standard RL formulation.*

5.2 Partially Observable MDP Formulation of the Single Trial Convex RL Setting

221 Instead of temporally extending the convex MDP $\mathcal{CM}$ as in the previous section, which causes
222 the policy space to grow exponentially with the episode horizon H, we can alternatively formulate
223 $\mathcal{CM}$ as a Partially Observable MDP (POMDP) [3, 18] $\mathcal{PM} = (\mathcal{S}_\ell, \mathcal{A}_\ell, P_\ell, \mu_\ell, r_\ell, \Omega, O)$, in which
224 Ω denotes an observation space, and $O : \mathcal{S}_\ell \to \Delta(\Omega)$ is an observation function. The process to
225 build $\mathcal{PM}$ is rather similar to the one we employed for the extended MDP $\mathcal{M}_\ell$, and the components
226 $\mathcal{S}_\ell, \mathcal{A}_\ell, P_\ell, \mu_\ell, r_\ell$ remain indeed unchanged. However, in a POMDP the agent does not directly
227 access a state $s_\ell \in \mathcal{S}_\ell$, but just a partial observation $o \in \Omega$ that is given by the observation function
228 O. Here $O(s_\ell) = o$ is a deterministic function such that the given observation o is the last state
229 in the history s_ℓ. Since the agent only observes o, a stationary policy can be defined as a function

$\pi : \Omega \to \Delta(\mathcal{A})$, for which the size depends on the number of states S of the convex MDP $\mathcal{CM}$, being $\Omega = \mathcal{S}$. However, it is well known [18] that history-dependent policies should be considered for the problem of optimizing a POMDP. This is in sharp contrast with the current convex MDP literature, which only considers stationary policies due to the infinite trials formulation [31].

Challenged assumption 3. *The set of stationary randomized policies is sufficient for convex RL.*

5.3 Online Learning in Single Trial Convex RL

Let us assume to have access to a planning oracle that returns an optimal policy π^* for a given $\mathcal{CM}$, so that we can sidestep the concerns on the computational feasibility reported in previous sections. It is worth investigating the complexity of learning π^* from *online interactions* with an unknown $\mathcal{CM}$. A typical measure of this complexity is the online learning regret $\mathcal{R}(N)$, which is defined as

$$\mathcal{R}(N) := \sum_{t=1}^{N} V^* - V^{(t)},$$

where N is the number of learning episodes, $V^* = V_1^{\pi^*}(s_1)$ is the value of the optimal policy, $V^{(t)} = V^{\pi_t}$ is the value of the policy π_t deployed at the episode t. We now aim to study the regret $\mathcal{R}(N)$ induced by a principled algorithm. To this purpose, we can cast our learning problem in the Once-Per-Episode (OPE) RL formulation [5]. To translate our $\zeta_1(\pi) = \mathbb{E}_{d \sim p^\pi}[\mathcal{F}(d)]$ into an OPE problem, we have to encode $\mathcal{F}$ into a linear representation, which we can get through

$$\mathcal{F}(d) \approx B_{\mathcal{F}, d_{\mathbf{w}}}(d),$$

in which $\mathbf{w}$ is a $d_{\mathbf{w}}$-dimensional vector of linear parameters and $B_{\mathcal{F}, d_{\mathbf{w}}}$ is a multivariate Bernstein polynomial [8, Ch. 9] of degree $d_{\mathbf{w}}$. Then, with some other minor changes that are detailed in the Appendix, we can invoke the analysis of OPE-UCBVI in [5] to provide an upper bound to the regret $\mathcal{R}(N)$ in our setting. Before stating the regret result, we recall that $\mathcal{F}$ is $L_{\mathcal{F}}$-Lipschitz (Assumption 4.1) and we report an additional smoothness assumption on the value function.

Assumption 5.1. *Let $Lip(\Delta(\mathcal{S}))$ the space of the $L_{\mathcal{F}}$-Lipschitz functions on $\Delta(\mathcal{S})$, and let $\mathcal{F}', \mathcal{F}'' \in Lip(\Delta(\mathcal{S}))$. The value function $V : Lip(\Delta(\mathcal{S})) \to \mathbb{R}$ is L_V-Lipschitz continuous, i.e.,*

$$|V(\mathcal{F}') - V(\mathcal{F}'')| \leq L_V \|\mathcal{F}' - \mathcal{F}''\|_\infty, \quad \forall \mathcal{F}', \mathcal{F}''.$$

> **Theorem 5.1** (Regret). *For any $\delta \in (0, 1]$, and unknown convex MDP $\mathcal{CM}$, the regret of the OPE-UCBVI algorithm is upper bounded as*
>
> $$\mathcal{R}(N) \leq \underbrace{N L_V L_{\mathcal{F}} \big(S/d_{\mathbf{w}} \big)^{\frac{1}{2}}}_{\text{approximation term}} + \underbrace{\mathcal{R}_\delta(N)}_{\text{pure learning regret}}$$
>
> *with probability $1 - \delta$, where $\mathcal{R}_\delta(N)$ is sub-linear in N.*

Compared to the analysis of [5], our regret bound admits an additional approximation term that scales linearly with N. This is the cost we have for approximating the unknown $\mathcal{F}$ with a linear model. Even if we can overcome the linearity in N with a sufficiently large representation $d_{\mathbf{w}}$, this would negatively impact the pure learning term, which scales with $O(d_{\mathbf{w}}^3 \sqrt{N})$ [5, Thr. 3.2]. Notably, for the online learning setting with known function $\mathcal{F}$, $d_{\mathbf{w}} = 1$, the approximation term vanishes, leading to a cumulatively sub-linear regret $O(\sqrt{N})$. This observation motivates the development of $\mathcal{F}$-specific algorithms to address the online learning problem in the single trial convex RL setting.

6 Illustrative Examples and Experimental Approximation Error

In this section, we evaluate the performance achieved by a policy $\pi^\dagger \in \arg\max_{\pi \in \Pi} \zeta_n(\pi)$, obtained by maximizing the finite trials objective (4), against a policy $\pi^\star \in \arg\max_{\pi \in \Pi} \zeta_\infty(\pi)$, obtained by maximizing the infinite trials objective (3), over a *finite amount of trajectories*. We show that optimizing the infinite trials objective can lead to sub-optimal policies across a wide range of applications. In particular, we cover examples from imitation learning, risk-averse RL, and pure exploration. We carefully selected MDPs that are as simple as possible in order to stress the generality of our results. For the sake of clarity, we restrict the discussion to the single trial setting ($n = 1$).

(a) Pure exploration   (b) Risk-averse RL   (c) Imitation learning

Figure 3: Visualization of the illustrative MDPs. In **(b)**, state 0 is a low-reward (r) low-risk state, state 2 is a high-reward (R) high-risk state, and state 1 is a penalty state with zero reward.

Pure Exploration We consider the maximum state entropy exploration objective as stated in [16], i.e., $\mathcal{F}(d^\pi) = H(d^\pi) = -\mathbb{E}_{s \sim d^\pi}\left[\log d^\pi(s)\right]$, and the MDP in Figure 3a. In this example, the agent aims to maximize the state entropy over finite trajectories of H steps. Notice that this happens when a policy induces an empirical state distribution that is close to uniform. In Figure 4a, we compare the average entropy induced by the optimal finite trials policy $\pi^\dagger$ and the optimal infinite trials policy $\pi^\star$. An agent following the policy $\pi^\dagger$ always achieves a uniform empirical state distribution leading to the maximum entropy. Moreover, $\pi^\dagger$ is a non-Markovian deterministic policy. In contrast, the policy π^* is randomized in all the three states. As a result, this policy induces sub-optimal empirical state distributions with *strictly positive* probability, as shown in Figure 4d.

Risk-Averse RL For the risk-averse example, we study the Conditional Value-at-Risk (CVaR) $\mathcal{F}(d^\pi) = \mathrm{CVaR}_\alpha(\lambda \cdot d^\pi)$, where d^π is an admissible state distribution and r is a reward vector [25]. Consider an instance of the MDP in Figure 3b in which the agent aims to maximize the CVaR over finite trajectories of H steps. First, notice that a financial semantics can be attributed to the given MDP: an agent, starting in state 2, can decide whether to invest in risky assets, e.g., crypto-currencies, or in safe ones, e.g., treasury bills. Because of the stochastic transitions, a policy would need to be reactive to the realizations of the transition model in order to maximize the single trial objective (5). This kind of behavior is achieved by an optimal finite trials policy $\pi^\dagger$. As a matter of fact, $\pi^\dagger$ is a non-Markovian policy, which can take decisions as a function of the history, and thus takes into account the realizations of the stochastic transition model. On the other hand, an optimal infinite trials policy π^* is a Markovian policy, and it cannot take into account the current history. As a result, the policy π^* induces sub-optimal trajectories with *strictly positive* probability (see Figure 4e). In Figure 4b, we compare the average CVaR on a single trajectory induced by the optimal finite trials policy $\pi^\dagger$ and the optimal infinite trials policy $\pi^\star$. Overall, $\pi^\dagger$ performs significantly better than $\pi^\star$.

Imitation Learning We consider the distribution matching formulation of the imitation learning problem [19], i.e., $\mathcal{F}(d_\pi) = KL\left(d_\pi \,\|\, d_E\right)$, and the MDP in Figure 3c. The agent aims to learn a policy π inducing an empirical state distribution d_π close to the empirical state distribution d_E demonstrated by an expert. In Figure 4c, we compare the average KL-divergence induced by the optimal finite trials policy $\pi^\dagger$ and the optimal infinite trials policy $\pi^\star$. An agent following the policy $\pi^\dagger$ induces a state visitation distribution that perfectly matches the expert. In contrast, an agent following π^* induces sub-optimal trajectories with *strictly positive* probability, as shown in Figure 4f.

7 Related Work

To the best of our knowledge, [31] were the first to introduce the convex RL problem, under the name of RL with general utilities, with the goal of unifying a set of practically relevant non-scalar objectives for RL under a unique general framework. Especially, they investigated a hidden convexity of the convex RL objective[4] that allows for statistically efficient policy optimization in the infinite trials setting. More recently, [30, 12] have considered reinterpretations of the infinite trials convex RL formulation from game-theoretic perspectives. The former [30] notes that the convex RL problem can be seen as a min-max game between the policy player and a cost player. The latter [12] shows that the convex RL problem is a subclass of mean-field games.

Another relevant branch of literature is the one investigating the expressivity of scalar (Markovian) rewards [1, 26]. Especially, [1] shows that not all the notions of task, such as inducing a set of

---

[4]The convex RL objective, even when it is convex in the state distribution, it can be non-convex in the policy.

Figure 4: With $\pi^\star$ we denote an optimal finite trial policy, with $\pi^\dagger$ an optimal infinite trial policy. In **(a, d)** we report the average and the empirical distribution of the entropy achieved in the pure exploration MDP ($H = 6$) of Figure 3a. In **(b, e)** we report the average and the empirical distribution of $\mathrm{CVaR}_\alpha(\pi)$ achieved in the risk-averse MDP ($H = 5$) of Figure 3b. In **(c, f)** we report the average and the empirical distribution of $\mathrm{KL}(d_\pi||d_E)$ (with $d_E = (1/3, 2/3)$) achieved in the imitation learning MDP ($H = 12$) of Figure 3c. We provide 95 % c.i. over 1000 runs.

admissible policies, a (partial) policy ordering, a trajectory ordering, can be naturally encoded with a scalar reward function. Whereas the convex RL formulation extends the expressivity of scalar RL w.r.t. all these three notions of task, it is still not sufficient to cover any instance. Convex RL is powerful in terms of the policy ordering it can induce, but it is inherently limited on the trajectory ordering as it only accounts for the infinite trials state distribution. Instead, the finite trials convex RL setting that we presented in this paper is naturally expressive in terms of trajectory orderings, at the expense of a diminished expressivity on the policy orderings w.r.t. infinite trials convex RL.

Previous works concerning RL in the presence of trajectory feedback are also related to this work. Most of this literature assumes an underlying scalar reward model [e.g., 9] which only delays the feedback at the end of the episode. One notable exception is the once-per-episode formulation in [5], which we have already commented on in Section 5.

Finally, the work in [6, 7] considers MDP with vectorial rewards as a mean to encode convex objectives in RL with a multi-objective flavor. They show that stationary policies are in general sub-optimal for the introduced online learning setting, where non-stationarity becomes essential. In this setting, they provide principled procedures to learn an optimal policy with sub-linear regret.

8   Conclusion and Future Directions

While in classic RL the optimization of an infinite trials objective leads to the optimal policy for the finite trials counterpart, we have shown that true convex RL does not have this property. First, we have formalized the concept of finite trials convex RL, which captures a problem that until now has been cast into an unfounded optimization problem. Then, we have given an upper bound on the approximation error obtained by erroneously optimizing the infinite trials objective, as it is currently done in practice. Finally, we have presented intuitive, yet general, experimental examples to show that the approximation error can be significant in relevant applications. Since the finite trials setting is the standard in both simulated and real-world RL, we believe that shedding light on the above mentioned performance gap will lead to better approaches for convex RL and related areas. Future work could target approximate solutions to the finite trials objective rather than the infinite trials one, which can cause sub-optimality even when solved exactly. Methods in POMDPs [15, 21] or optimistic planning algorithms [4] could provide useful inspiration.

References

[1] David Abel, Will Dabney, Anna Harutyunyan, Mark K Ho, Michael Littman, Doina Precup, and Satinder Singh. On the expressivity of markov reward. *Advances in Neural Information Processing Systems*, 2021.

[2] Eitan Altman. *Constrained Markov decision processes*, volume 7. CRC Press, 1999.

[3] Karl Johan Åström. Optimal control of markov processes with incomplete state information i. *Journal of Mathematical Analysis and Applications*, 10:174–205, 1965.

[4] Sébastien Bubeck and Rémi Munos. Open loop optimistic planning. In *Conference on Learning Theory*, 2010.

[5] Niladri S Chatterji, Aldo Pacchiano, Peter L Bartlett, and Michael I Jordan. On the theory of reinforcement learning with once-per-episode feedback. *arXiv preprint arXiv:2105.14363*, 2021.

[6] Wang Chi Cheung. Exploration-exploitation trade-off in reinforcement learning on online markov decision processes with global concave rewards. *arXiv preprint arXiv:1905.06466*, 2019.

[7] Wang Chi Cheung. Regret minimization for reinforcement learning with vectorial feedback and complex objectives. *Advances in Neural Information Processing Systems*, 32:726–736, 2019.

[8] Zeev Ditzian and Vilmos Totik. Moduli of smoothness. 1987.

[9] Yonathan Efroni, Nadav Merlis, and Shie Mannor. Reinforcement learning with trajectory feedback. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

[10] Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2018.

[11] Javier Garcıa and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16(1):1437–1480, 2015.

[12] Matthieu Geist, Julien Pérolat, Mathieu Laurière, Romuald Elie, Sarah Perrin, Olivier Bachem, Rémi Munos, and Olivier Pietquin. Concave utility reinforcement learning: the mean-field game viewpoint. *arXiv preprint arXiv:2106.03787*, 2021.

[13] Seyed Kamyar Seyed Ghasemipour, Richard Zemel, and Shixiang Gu. A divergence minimization perspective on imitation learning methods. In *Conference on Robot Learning*, pages 1259–1277. PMLR, 2020.

[14] Karol Gregor, Danilo Rezende, and Daan Wierstra. Variational intrinsic control. *International Conference on Learning Representations, Workshop Track*, 2017.

[15] Milos Hauskrecht. Value-function approximations for partially observable markov decision processes. *Journal of artificial intelligence research*, 13:33–94, 2000.

[16] Elad Hazan, Sham Kakade, Karan Singh, and Abby Van Soest. Provably efficient maximum entropy exploration. In *Proceedings of the International Conference on Machine Learning*, 2019.

[17] Ahmed Hussein, Mohamed Medhat Gaber, Eyad Elyan, and Chrisina Jayne. Imitation learning: A survey of learning methods. *ACM Computing Surveys (CSUR)*, 50(2):1–35, 2017.

[18] Leslie Pack Kaelbling, Michael L Littman, and Anthony R Cassandra. Planning and acting in partially observable stochastic domains. *Artificial intelligence*, 1998.

[19] Ilya Kostrikov, Ofir Nachum, and Jonathan Tompson. Imitation learning via off-policy distribution matching. In *International Conference on Learning Representations*, 2019.

[20] Lisa Lee, Benjamin Eysenbach, Emilio Parisotto, Eric Xing, Sergey Levine, and Ruslan Salakhutdinov. Reinforcement learning with convex constraints. *arXiv preprint arXiv:1906.05274*, 2019.

[21] Michael L Littman, Anthony R Cassandra, and Leslie Pack Kaelbling. Learning policies for partially observable environments: Scaling up. In *Machine Learning Proceedings 1995*, pages 362–370. Elsevier, 1995.

[22] Sobhan Miryoosefi, Kianté Brantley, Hal Daumé III, Miroslav Dudík, and Robert E. Schapire. Reinforcement learning with convex constraints. *arXiv preprint arXiv:1906.09323*, 2019.

[23] LA Prashanth and Mohammad Ghavamzadeh. Actor-critic algorithms for risk-sensitive mdps. In *Proceedings of the 26th International Conference on Neural Information Processing Systems-Volume 1*, pages 252–260, 2013.

[24] Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

[25] R Tyrrell Rockafellar and Stanislav Uryasev. Optimization of conditional value-at-risk. *Journal of risk*, 2000.

[26] David Silver, Satinder Singh, Doina Precup, and Richard S Sutton. Reward is enough. *Artificial Intelligence*, 2021.

[27] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[28] Aviv Tamar and Shie Mannor. Variance adjusted actor critic algorithms, 2013.

[29] Tsachy Weissman, Erik Ordentlich, Gadiel Seroussi, Sergio Verdu, and Marcelo J Weinberger. Inequalities for the l1 deviation of the empirical distribution. *Hewlett-Packard Labs, Tech. Rep*, 2003.

[30] Tom Zahavy, Brendan O'Donoghue, Guillaume Desjardins, and Satinder Singh. Reward is enough for convex mdps. *arXiv preprint arXiv:2106.00661*, 2021.

[31] Junyu Zhang, Alec Koppel, Amrit Singh Bedi, Csaba Szepesvari, and Mengdi Wang. Variational policy gradient method for reinforcement learning with general utilities. *Advances in Neural Information Processing Systems*, 2020.